

X2C

*Project Documentation
DemoApplication*

December 23, 2016
© Linz Center of Mechatronics GmbH

Contents

I X2C Model	3
1 Version Information	3
1.1 X2C	3
1.2 Operating System	3
1.3 Scilab	3
2 Model Structure	4
2.1 Xcos Model	4
2.2 Subsystems	5
3 Model Parameter	6
3.1 Sample Time	6
3.2 Scilab Parameter	6
4 Mask Parameter	7
II User Specific Documentation	9
III Hardware Documentation	10
IV Frame Program Documentation	11
5 File Index	11
5.1 File List	11
6 File Documentation	11
6.1 inc/bl.h File Reference	11
6.1.1 Detailed Description	11
6.2 inc/bl_platform.h File Reference	12
6.2.1 Detailed Description	12
6.3 inc/Hardware.h File Reference	12
6.3.1 Detailed Description	13
6.3.2 Function Documentation	13
6.4 inc/lwipopts.h File Reference	14
6.4.1 Detailed Description	14
6.4.2 Macro Definition Documentation	14
6.5 inc/Main.h File Reference	14
6.5.1 Detailed Description	14
6.5.2 Function Documentation	14
6.6 inc/MMUConfig.h File Reference	15
6.6.1 Detailed Description	15
6.7 src/bl_platform.c File Reference	15
6.7.1 Detailed Description	16
6.7.2 Function Documentation	16
V Used X2C-Blocks	19

7 Project Specific Blocks	19
8 Internal Library Blocks	19
AutoSwitch	19
Constant	23
Delay	26
I	29
Negation	33
Sin3Gen	36
SinGen	41

Part I

X2C Model

1 Version Information

1.1 X2C

- X2Cfull: Version 1068

1.2 Operating System

- OS: Windows 7 6.1

1.3 Scilab

- Scilab: Version 5.5.1.1412169962
- Java: Version 1.6.0_41

2 Model Structure

2.1 Xcos Model




Figure 1: DemoApplication

2.2 Subsystems




Figure 2: DemoApplication_Oscillator

3 Model Parameter

3.1 Sample Time

Sample Time	
T_S	$100\mu s$

3.2 Scilab Parameter

```
1 // File with model parameters such as sample time, scaling factors, etc...
2 //
3 // Copyright (c) 2017, Linz Center of Mechatronics GmbH (LCM) http://www.lcm.at/
4 // All rights reserved.
5 //
6 // This file is licensed according to the BSD 3-clause license as follows:
7 //
8 // Redistribution and use in source and binary forms, with or without
9 // modification, are permitted provided that the following conditions are met:
10 //      * Redistributions of source code must retain the above copyright
11 //        notice, this list of conditions and the following disclaimer.
12 //      * Redistributions in binary form must reproduce the above copyright
13 //        notice, this list of conditions and the following disclaimer in the
14 //        documentation and/or other materials provided with the distribution.
15 //      * Neither the name of the "Linz Center of Mechatronics GmbH" and "LCM" nor
16 //        the names of its contributors may be used to endorse or promote products
17 //        derived from this software without specific prior written permission.
18 //
19 // THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
20 // ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
21 // WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
22 // IN NO EVENT SHALL "Linz Center of Mechatronics GmbH" BE LIABLE FOR ANY
23 // DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
24 // (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
25 // LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
26 // ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
27 // (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
28 // SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
29 //
30 // $LastChangedRevision: 844 $
31 // $LastChangedDate::: 2016-09-01 15:18:35 +0200#$$
32 //
33 // This file is part of X2C. http://www.mechatronic-simulation.org/
34 //
35 // Sampling time
36 X2C_sampleTime = 100e-6;      // 10kHz sampling frequency
37 //
38 // Scaling factors
39 //
40 // Controller parameters
```

Listing 1: ModelParameter.sce

4 Mask Parameter

Constant: Amplitude	
Value	0.7
Used Implementation	FiP16

AutoSwitch: AutoSwitch	
Thresh_up	0.6
Thresh_down	0.4
Used Implementation	FiP16

AutoSwitch: AutoSwitch1	
Thresh_up	0.0
Thresh_down	0.0
Used Implementation	FiP16

Constant: Frequency	
Value	0.0080
Used Implementation	FiP16

Constant: LED off	
Value	0.0
Used Implementation	FiP16

Constant: LED on	
Value	1.0
Used Implementation	FiP16

Constant: LED_on_off	
Value	0.0
Used Implementation	FiP16

AutoSwitch: Oscillator__AutoSwitch	
Thresh_up	0.5
Thresh_down	-0.5
Used Implementation	FiP16

Constant: Oscillator__Constant	
Value	1.0
Used Implementation	FiP16

Delay: Oscillator_Delay	
ts_fact	1.0
Used Implementation	FiP16

Constant: Oscillator_Enable	
Value	1.0
Used Implementation	FiP8

Constant: Oscillator_Init	
Value	0.0
Used Implementation	FiP16

I: Oscillator_Integrator	
Ki	25.0
ts_fact	1.0
Used Implementation	FiP16

Negation: Oscillator_Negation	
Used Implementation	FiP16

Sin3Gen: Sin3Gen	
fmax	1000.0
Offset	0.0
ts_fact	1.0
Used Implementation	FiP16

SinGen: SinGen	
fmax	1000.0
Offset	0.0
Phase	0.0
ts_fact	1.0
Used Implementation	FiP16

Part II

User Specific Documentation

Feel free to add your documentation here!

Part III

Hardware Documentation

Part IV

Frame Program Documentation

5 File Index

5.1 File List

Here is a list of all documented files with brief descriptions:


inc/bl.h	This file defines boot macros and objects	11
inc/bl_platform.h	This file exports the APIs used for configuring devices required during boot	12
inc/Hardware.h	Hardware initialization	12
inc/lwipopts.h		14
inc/Main.h	Main function	14
inc/MMUConfig.h	MMU configuration	15
src/bl_platform.c	Initializes AM335x Device Peripherals	15

6 File Documentation

6.1 inc/bl.h File Reference

This file defines boot macros and objects.

This graph shows which files directly or indirectly include this file:



6.1.1 Detailed Description


This file defines boot macros and objects.

6.2 inc/bl_platform.h File Reference


This file exports the APIs used for configuring devices required during boot.

```
#include "soc_AM335x.h"
```

Include dependency graph for bl_platform.h:



This graph shows which files directly or indirectly include this file:



6.2.1 Detailed Description


This file exports the APIs used for configuring devices required during boot.

6.3 inc/Hardware.h File Reference

Hardware initialization.

```
#include "gpio_v2.h"
#include "bl_platform.h"
```

Include dependency graph for Hardware.h:



Functions

- void `initHardware (void)`
Initialization of hardware.

6.3.1 Detailed Description

Hardware initialization.

6.3.2 Function Documentation


6.3.2.1 void initHardware (void)

Initialization of hardware.

- Configuration of IO ports
- Configuration of timer 2
 - 24MHz timer clock
 - Generation of cyclic interrupt with selected sample time
 - Interrupt calls X2C main task

6.4 inc/lwipopts.h File Reference

```
#include "consoleUtils.h"  
Include dependency graph for lwipopts.h:
```



Macros

- `#define LWIP_NETIF_HOSTNAME 1`

6.4.1 Detailed Description

- Configuration options for lwIP

Copyright (c) 2010 Texas Instruments Incorporated

6.4.2 Macro Definition Documentation

6.4.2.1 #define LWIP_NETIF_HOSTNAME 1

User specific macros.

6.5 inc/Main.h File Reference

Main function.

Functions

- `void mainTask (void)`

Main control task.

6.5.1 Detailed Description

Main function.

X2C maintenance table, protocol & hardware initialization.
Uses Atmel Software Framework (ASF).

6.5.2 Function Documentation

6.5.2.1 void mainTask (void)

Main control task.

TODO: This task has to be called periodically. Calling rate = 100us

- assign imports (not available in this demo)
- update X2C
- update outports

6.6 inc/MMUConfig.h File Reference

MMU configuration.

6.6.1 Detailed Description


MMU configuration.

6.7 src/bl_platform.c File Reference

Initializes AM335x Device Peripherals.

```
#include "hw_types.h"
#include "hw_cm_cefuse.h"
#include "hw_cm_device.h"
#include "hw_cm_dpll.h"
#include "hw_cm_gfx.h"
#include "hw_cm_mpu.h"
#include "hw_cm_per.h"
#include "hw_cm_rtc.h"
#include "hw_cm_wkup.h"
#include "hw_control_AM335x.h"
#include "hw_emif4d.h"
#include "bl.h"
#include "gpmc.h"
#include "bl_platform.h"
#include "uartStdio.h"
#include "watchdog.h"
#include "hsi2c.h"
#include "gpio_v2.h"
#include "board.h"
#include "device.h"
#include "string.h"
```

Include dependency graph for bl_platform.c:



Functions

- void [ConfigureVdd2](#) (unsigned int opVolMultiplier, unsigned maxLoadCurrent, unsigned int timeStep, unsigned int supplyState)
 - Configure vdd2 for various parameters such as Multiplier, Maximum Load Current etc
- void [SelectVdd2Source](#) (unsigned int vddSource)
 - Select the VDD2 value. VDD2_OP_REG or VDD2_SR_REG.
- void [SetVdd2OpVoltage](#) (unsigned int opVolSelector)

- void **SetVdd2SrVoltage** (unsigned int opVolSelector)

set *VDD2_OP* voltage value.
- void **SelectI2CInstance** (unsigned int i2cInstance)

Select I2C interface whether SR I2C or Control I2C.
- void **ConfigureVdd1** (unsigned int opVolMultiplier, unsigned maxLoadCurrent, unsigned int timeStep, unsigned int supplyState)
 - *Configure vdd1 for various parameters such as Multiplier, Maximum Load Current etc*
- void **SelectVdd1Source** (unsigned int vddSource)

Select the VDD1 value. VDD1_OP_REG or VDD1_SR_REG.
- void **SetVdd1OpVoltage** (unsigned int opVolSelector)

set *VDD1_OP* voltage value.

6.7.1 Detailed Description

Initializes AM335x Device Peripherals.

6.7.2 Function Documentation

6.7.2.1 void **ConfigureVdd1** (*unsigned int opVolMultiplier, unsigned maxLoadCurrent, unsigned int timeStep, unsigned int supplyState*)

- Configure vdd1 for various parameters such as Multiplier, Maximum Load Current etc

Parameters

<i>opVolMultipler</i>	- Multiplier.
<i>maxLoadCurrent</i>	- Maximum Load Current.
<i>timeStep</i>	- Time step - voltage change per us(micro sec).
<i>supplyState</i>	- Supply state (on (high/low power mode), off)

Returns

: None.

6.7.2.2 void **ConfigureVdd2** (*unsigned int opVolMultiplier, unsigned maxLoadCurrent, unsigned int timeStep, unsigned int supplyState*)

- Configure vdd2 for various parameters such as Multiplier, Maximum Load Current etc

Parameters

<i>opVolMultiplier</i>	- Multiplier.
<i>maxLoadCurrent</i>	- Maximum Load Current.
<i>timeStep</i>	- Time step - voltage change per us(micro sec).
<i>supplyState</i>	- Supply state (on (high/low power mode), off)

Returns

: None.

6.7.2.3 void SelectI2CInstance (unsigned int *i2cInstance*)

Select I2C interface whether SR I2C or Control I2C.

Parameters

<i>i2cInstance</i>	- I2c instance to select.
--------------------	---------------------------

Returns

None.

6.7.2.4 void SelectVdd1Source (unsigned int *vddSource*)

Select the VDD1 value. VDD1_OP_REG or VDD1_SR_REG.

Parameters

<i>vddSource</i>	- VDD2 value.
------------------	---------------

Returns

None.

6.7.2.5 void SelectVdd2Source (unsigned int *vddSource*)

Select the VDD2 value. VDD2_OP_REG or VDD2_SR_REG.

Parameters

<i>vddSource</i>	- VDD2 value.
------------------	---------------

Returns

None.

6.7.2.6 void SetVdd1OpVoltage (unsigned int *opVolSelector*)

set VDD1_OP voltage value.

Parameters

<i>opVolSelc-tor</i>	- VDD2_OP voltage value.
----------------------	--------------------------

Returns

None.

6.7.2.7 void SetVdd2OpVoltage (unsigned int *opVolSelector*)

set VDD2_OP voltage value.

Parameters

<i>opVolSelc-tor</i>	- VDD2_OP voltage value.
----------------------	--------------------------

Returns

None.

6.7.2.8 void SetVdd2SrVoltage (unsigned int *opVolSelector*)

set VDD2_SR voltage value

Parameters

<i>opVolSelc-tor</i>	- VDD2_SR voltage value.
----------------------	--------------------------

Returns

None.


Part V

Used X2C-Blocks

7 Project Specific Blocks

8 Internal Library Blocks

Block: AutoSwitch



Imports	
In1	Input #1
Switch	Input #2: Threshold signal
In3	Input #3

Outports	
Out	Either value of input #1 or input #3 dependent on value of input #2

Mask Parameters	
Thresh_up	Threshold level for rising switch signal
Thresh_down	Threshold level for falling switch signal

Description:

Switch between In1 and In3 dependent on Switch signal:

Switch signal rising: Switch \geq Threshold up \rightarrow Out = In1

Switch signal falling: Switch $<$ Threshold down \rightarrow Out = In3

Implementations:

- FiP8** 8 Bit Fixed Point Implementation
- FiP16** 16 Bit Fixed Point Implementation
- FiP32** 32 Bit Fixed Point Implementation
- Float32** 32 Bit Floating Point Implementation
- Float64** 64 Bit Floating Point Implementation

Implementation: FiP8

Name	FiP8
ID	128
Revision	0.1
C filename	AutoSwitch_FiP8.c
H filename	AutoSwitch_FiP8.h

8 Bit Fixed Point Implementation

Controller Parameters	
Thresh_up	Threshold level for rising switch signal
Thresh_down	Threshold level for falling switch signal
Status	Current hysteresis state

Data Structure:

```
typedef struct {
    uint16          ID ;
    int8            *In1 ;
    int8            *Switch ;
    int8            *In3 ;
    int8            Out ;
    int8            Thresh_up ;
    int8            Thresh_down ;
    int8            Status ;
} AUTOSWITCH_FIP8 ;
```

Implementation: FiP16

Name	FiP16
ID	129
Revision	0.1
C filename	AutoSwitch_FiP16.c
H filename	AutoSwitch_FiP16.h

16 Bit Fixed Point Implementation

Controller Parameters	
Thresh_up	Threshold level for rising switch signal
Thresh_down	Threshold level for falling switch signal
Status	Current hysteresis state

Data Structure:

```
typedef struct {
    uint16          ID ;
    int16            *In1 ;
    int16            *Switch ;
    int16            *In3 ;
```

```

    int16          Out;
    int16          Thresh_up;
    int16          Thresh_down;
    int8           Status;
} AUTOSWITCH_FIP16;

```

Implementation: FiP32

Name	FiP32
ID	130
Revision	0.1
C filename	AutoSwitch_FiP32.c
H filename	AutoSwitch_FiP32.h

32 Bit Fixed Point Implementation

Controller Parameters	
Thresh_up	Threshold level for rising switch signal
Thresh_down	Threshold level for falling switch signal
Status	Current hysteresis state

Data Structure:

```

typedef struct {
    uint16          ID ;
    int32          *In1 ;
    int32          *Switch ;
    int32          *In3 ;
    int32          Out;
    int32          Thresh_up;
    int32          Thresh_down;
    int8           Status;
} AUTOSWITCH_FIP32;

```

Implementation: Float32

Name	Float32
ID	131
Revision	0.1
C filename	AutoSwitch_Float32.c
H filename	AutoSwitch_Float32.h

32 Bit Floating Point Implementation

Controller Parameters	
Thresh_up	Threshold level for rising switch signal
Thresh_down	Threshold level for falling switch signal
Status	Current hysteresis state

Data Structure:

```
typedef struct {
    uint16      ID ;
    float32    *In1 ;
    float32    *Switch ;
    float32    *In3 ;
    float32      Out ;
    float32    Thresh_up ;
    float32    Thresh_down ;
    int8       Status ;
} AUTOSWITCH_FLOAT32;
```

Implementation: Float64

Name	Float64
ID	132
Revision	0.1
C filename	AutoSwitch_Float64.c
H filename	AutoSwitch_Float64.h

64 Bit Floating Point Implementation

Controller Parameters	
Thresh_up	Threshold level for rising switch signal
Thresh_down	Threshold level for falling switch signal
Status	Current hysteresis state

Data Structure:

```
typedef struct {
    uint16      ID ;
    float64    *In1 ;
    float64    *Switch ;
    float64    *In3 ;
    float64      Out ;
    float64    Thresh_up ;
    float64    Thresh_down ;
    int8       Status ;
} AUTOSWITCH_FLOAT64;
```

Block: Constant



Outports	
Out	Constant output

Mask Parameters	
Value	Constant factor

Description:

Constant value.

Implementations:

- FiP8** 8 Bit Fixed Point Implementation
- FiP16** 16 Bit Fixed Point Implementation
- FiP32** 32 Bit Fixed Point Implementation
- Float32** 32 Bit Floating Point Implementation
- Float64** 64 Bit Floating Point Implementation

Implementation: FiP8

Name	FiP8
ID	48
Revision	0.3
C filename	Constant_FiP8.c
H filename	Constant_FiP8.h

8 Bit Fixed Point Implementation

Controller Parameters	
K	Constant factor

Data Structure:

```
typedef struct {
    uint16          ID ;
    int8           Out ;
    int8           K;
} CONSTANT_FIP8;
```

Implementation: FiP16

Name FiP16
ID 49
Revision 0.3
C filename Constant_FiP16.c
H filename Constant_FiP16.h

16 Bit Fixed Point Implementation

Controller Parameters	
K	Constant factor

Data Structure:

```
typedef struct {
    uint16          ID;
    int16           Out;
    int16           K;
} CONSTANT_FIP16;
```

Implementation: FiP32

Name FiP32
ID 50
Revision 0.3
C filename Constant_FiP32.c
H filename Constant_FiP32.h

32 Bit Fixed Point Implementation

Controller Parameters	
K	Constant factor

Data Structure:

```
typedef struct {
    uint16          ID;
    int32           Out;
    int32           K;
} CONSTANT_FIP32;
```

Implementation: Float32

Name Float32
ID 51
Revision 0.1
C filename Constant_Float32.c
H filename Constant_Float32.h

32 Bit Floating Point Implementation

Controller Parameters	
K	Constant factor

Data Structure:

```

typedef struct {
    uint16          ID ;
    float32         Out ;
    float32         K;
} CONSTANT_FLOAT32;
  
```

Implementation: Float64

Name Float64
ID 52
Revision 0.1
C filename Constant_Float64.c
H filename Constant_Float64.h

64 Bit Floating Point Implementation

Controller Parameters	
K	Constant factor

Data Structure:

```

typedef struct {
    uint16          ID ;
    float64         Out ;
    float64         K;
} CONSTANT_FLOAT64;
  
```

Block: Delay



Imports	
In	Input In(k)

Outports	
Out	Output Out(k)=In(k-1)

Mask Parameters	
ts_fact	Multiplication factor of base sampling time (in integer format)

Description:

Output delay by one sample time interval.

This block can be used to enable feedback loops in the model.

Implementations:

- FiP16** 16 Bit Fixed Point Implementation
- FiP32** 32 Bit Fixed Point Implementation
- Float32** 32 Bit Floating Point Implementation
- Float64** 64 Bit Floating Point Implementation

Implementation: FiP16

Name	FiP16
ID	3425
Revision	0.1
C filename	Delay_FiP16.c
H filename	Delay_FiP16.h

16 Bit Fixed Point Implementation

Controller Parameters	
In_old	Input value from previous cycle

Data Structure:

```
typedef struct {
    uint16          ID;
```

```

        int16      *In ;
        int16      Out;
        int16      In_old;
} DELAY_FIP16;

```

Implementation: FiP32

Name	FiP32
ID	3426
Revision	0.1
C filename	Delay_FiP32.c
H filename	Delay_FiP32.h

32 Bit Fixed Point Implementation

Controller Parameters	
In_old	Input value from previous cycle

Data Structure:

```

typedef struct {
    uint16      ID ;
    int32      *In ;
    int32      Out;
    int32      In_old;
} DELAY_FIP32;

```

Implementation: Float32

Name	Float32
ID	3427
Revision	0.1
C filename	Delay_Float32.c
H filename	Delay_Float32.h

32 Bit Floating Point Implementation

Controller Parameters	
In_old	Input value from previous cycle

Data Structure:

```

typedef struct {
    uint16      ID ;
    float32     *In ;
    float32     Out;
    float32     In_old ;
} DELAY_FLOAT32;

```

Implementation: Float64

Name Float64
ID 3428
Revision 0.1
C filename Delay_Float64.c
H filename Delay_Float64.h


64 Bit Floating Point Implementation

Controller Parameters	
In_old	Input value from previous cycle

Data Structure:

```
typedef struct {
    uint16          ID ;
    float64         *In ;
    float64         Out ;
    float64         In_old ;
} DELAY_FLOAT64;
```

Block: I



Imports	
In	Control error input
Init	Value which is loaded at initialization function call
Enable	Enable == 0: Deactivation of block; Out set to 0 Enable 0->1: Preload of integral part Enable == 1: Activation of block

Outports	
Out	Control value

Mask Parameters	
Ki	Integral Factor
ts_fact	Multiplication factor of base sampling time (in integer format)

Description:

I controller:

$$G(s) = Ki/s = 1/(Ti^*s)$$

Each fixed point implementation uses the next higher integer datatype for the integrational value storage variable.

A rising flank at the *Enable* import will preload the integrational part with the value present on the *Init* import.

Transfer function (zero-order hold discretization method):

$$G(z) = K_I T_s \frac{1}{z - 1}$$

Implementations:

- FiP8** 8 Bit Fixed Point Implementation
- FiP16** 16 Bit Fixed Point Implementation
- FiP32** 32 Bit Fixed Point Implementation
- Float32** 32 Bit Floating Point Implementation
- Float64** 64 Bit Floating Point Implementation

Implementation: FiP8

Name	FiP8
ID	3200
Revision	1.0
C filename	I_FiP8.c
H filename	I_FiP8.h

8 Bit Fixed Point Implementation

Controller Parameters	
b0	Integral coefficient
sfr	Shift factor for I coefficient b0
i_old	Integrator value from previous cycle
enable_old	Enable value of previous cycle

Data Structure:

```
typedef struct {
    uint16          ID ;
    int8            *In ;
    int8            *Init ;
    int8            *Enable ;
    int8            Out ;
    int8            b0 ;
    int8            sfr ;
    int16           i_old ;
    int8            enable_old ;
} I_FIP8 ;
```

Implementation: FiP16

Name	FiP16
ID	3201
Revision	1.0
C filename	I_FiP16.c
H filename	I_FiP16.h

16 Bit Fixed Point Implementation

Controller Parameters	
b0	Integral coefficient
sfr	Shift factor for I coefficient b0
i_old	Integrator value from previous cycle
enable_old	Enable value of previous cycle

Data Structure:

```
typedef struct {
```

```

    uint16      ID ;
    int16       *In ;
    int16       *Init ;
    int8        *Enable ;
    int16       Out;
    int16       b0;
    int8        sfr;
    int32       i_old ;
    int8        enable_old ;
} I_FIP16 ;

```

Implementation: FiP32

Name	FiP32
ID	3202
Revision	1.0
C filename	I_FiP32.c
H filename	I_FiP32.h

32 Bit Fixed Point Implementation

Controller Parameters	
b0	Integral coefficient
sfr	Shift factor for I coefficient b0
i_old	Integrator value from previous cycle
enable_old	Enable value of previous cycle

Data Structure:

```

typedef struct {
    uint16      ID ;
    int32       *In ;
    int32       *Init ;
    int8        *Enable ;
    int32       Out;
    int32       b0;
    int8        sfr;
    int64       i_old ;
    int8        enable_old ;
} I_FIP32 ;

```

Implementation: Float32

Name	Float32
ID	3203
Revision	0.1
C filename	I_Float32.c
H filename	I_Float32.h

32 Bit Floating Point Implementation

Controller Parameters	
b0	Integral coefficient
i_old	Integrator value from previous cycle
enable_old	Enable value of previous cycle

Data Structure:

```
typedef struct {
    uint16      ID ;
    float32     *In ;
    float32     *Init ;
    int8        *Enable ;
    float32     Out ;
    float32     b0 ;
    float32     i_old ;
    int8        enable_old ;
} I_FLOAT32;
```

Implementation: Float64

Name	Float64
ID	3204
Revision	0.1
C filename	I_Float64.c
H filename	I_Float64.h

64 Bit Floating Point Implementation

Controller Parameters	
b0	Integral coefficient
i_old	Integrator value from previous cycle
enable_old	Enable value of previous cycle

Data Structure:

```
typedef struct {
    uint16      ID ;
    float64     *In ;
    float64     *Init ;
    int8        *Enable ;
    float64     Out ;
    float64     b0 ;
    float64     i_old ;
    int8        enable_old ;
} I_FLOAT64;
```

Block: Negation



Imports	
In	Input

Outports	
Out	Negated input value

Description:

Negation of input signal.

Calculation:

$$Out = -In$$

Implementations:

- FiP8** 8 Bit Fixed Point Implementation
- FiP16** 16 Bit Fixed Point Implementation
- FiP32** 32 Bit Fixed Point Implementation
- Float32** 32 Bit Floating Point Implementation
- Float64** 64 Bit Floating Point Implementation

Implementation: FiP8

Name	FiP8
ID	5040
Revision	0.1
C filename	Negation_FiP8.c
H filename	Negation_FiP8.h

8 Bit Fixed Point Implementation

Data Structure:

```
typedef struct {
    uint16          ID ;
    int8            *In ;
    int8            Out ;
} NEGATION_FIP8;
```

Implementation: FiP16

Name FiP16
ID 5041
Revision 0.1
C filename Negation_FiP16.c
H filename Negation_FiP16.h

16 Bit Fixed Point Implementation

Data Structure:

```
typedef struct {
    uint16      ID ;
    int16       *In ;
    int16       Out ;
} NEGATION_FIP16;
```

Implementation: FiP32

Name FiP32
ID 5042
Revision 0.1
C filename Negation_FiP32.c
H filename Negation_FiP32.h

32 Bit Fixed Point Implementation

Data Structure:

```
typedef struct {
    uint16      ID ;
    int32       *In ;
    int32       Out ;
} NEGATION_FIP32;
```

Implementation: Float32

Name Float32
ID 5043
Revision 0.1
C filename Negation_Float32.c
H filename Negation_Float32.h

32 Bit Floating Point Implementation

Data Structure:

```
typedef struct {
    uint16      ID ;
    float32    *In ;
    float32    Out ;
}
```

```
} NEGATION_FLOAT32;
```

Implementation: Float64


Name Float64
ID 5044
Revision 0.1
C filename Negation_Float64.c
H filename Negation_Float64.h

64 Bit Floating Point Implementation

Data Structure:

```
typedef struct {
    uint16          ID ;
    float64        *In ;
    float64        Out ;
} NEGATION_FLOAT64;
```

Block: Sin3Gen



Imports	
A	Amplitude
f	Frequency

Outports	
u	Sine wave output phase u
v	Sine wave output phase v
w	Sine wave output phase w

Mask Parameters	
fmax	Maximum Frequency in Hz
Offset	Offset
ts_fact	Multiplication factor of base sampling time (in integer format)

Description:

Generation of a 3 sine waves with amplitude (A) and frequency (f).

Calculation fixed point implementation:

$$\begin{aligned} u_k &= A_k \cdot \sin(2f_k \cdot f_{max} \cdot kT_S) + A_{Offset} \\ v_k &= A_k \cdot \sin(2f_k \cdot f_{max} \cdot kT_S - \frac{2\pi}{3}) + A_{Offset} \\ w_k &= A_k \cdot \sin(2f_k \cdot f_{max} \cdot kT_S + \frac{2\pi}{3}) + A_{Offset} \end{aligned}$$

For sine calculation a lookup table with 256 entries is used. This results in a short computation time but with the downside of reduced accuracy for the FiP32 implementation.

Calculation floating point implementation (parameter *f_max* is ignored):

$$\begin{aligned} u_k &= A_k \cdot \sin(2\pi f_k \cdot kT_S) + A_{Offset} \\ v_k &= A_k \cdot \sin(2\pi f_k \cdot kT_S - \frac{2\pi}{3}) + A_{Offset} \\ w_k &= A_k \cdot \sin(2\pi f_k \cdot kT_S + \frac{2\pi}{3}) + A_{Offset} \end{aligned}$$

Implementations:

FiP8	8 Bit Fixed Point Implementation
FiP16	16 Bit Fixed Point Implementation
FiP32	32 Bit Fixed Point Implementation
Float32	32 Bit Floating Point Implementation
Float64	64 Bit Floating Point Implementation

Implementation: FiP8

Name	FiP8
ID	432
Revision	1.0
C filename	Sin3Gen_FiP8.c
H filename	Sin3Gen_FiP8.h

8 Bit Fixed Point Implementation

Controller Parameters	
delta_phi	Angle increment
offset	Amplitude offset
phi	Current angle

Data Structure:

```
typedef struct {
    uint16          ID ;
    int8            *A;
    int8            *f ;
    int8            u;
    int8            v;
    int8            w;
    int8            delta_phi;
    int8            offset;
    int8            phi;
} SIN3GEN_FIP8;
```

Implementation: FiP16

Name	FiP16
ID	433
Revision	1.0
C filename	Sin3Gen_FiP16.c
H filename	Sin3Gen_FiP16.h

16 Bit Fixed Point Implementation

Controller Parameters	
delta_phi	Angle increment
offset	Amplitude offset
phi	Current angle

Data Structure:

```
typedef struct {
    uint16      ID ;
    int16       *A;
    int16       *f ;
    int16       u;
    int16       v;
    int16       w;
    int16      delta_phi;
    int16      offset;
    int16      phi;
} SIN3GEN_FIP16;
```

Implementation: FiP32

Name	FiP32
ID	434
Revision	1.0
C filename	Sin3Gen_FiP32.c
H filename	Sin3Gen_FiP32.h

32 Bit Fixed Point Implementation

Controller Parameters	
delta_phi	Angle increment
offset	Amplitude offset
phi	Current angle

Data Structure:

```
typedef struct {
    uint16      ID ;
    int32       *A;
    int32       *f ;
    int32       u;
    int32       v;
    int32       w;
    int32      delta_phi;
    int32      offset;
    int32      phi;
} SIN3GEN_FIP32;
```

Implementation: Float32

Name	Float32
ID	435
Revision	0.1
C filename	Sin3Gen_Float32.c
H filename	Sin3Gen_Float32.h

32 Bit Floating Point Implementation

Controller Parameters	
delta_phi	Angle increment
offset	Amplitude offset
phi	Current angle

Data Structure:

```
typedef struct {
    uint16          ID ;
    float32         *A ;
    float32         *f ;
    float32         u ;
    float32         v ;
    float32         w ;
    float32         delta_phi ;
    float32         offset ;
    float32         phi ;
} SIN3GEN_FLOAT32;
```

Implementation: Float64

Name	Float64
ID	436
Revision	0.1
C filename	Sin3Gen_Float64.c
H filename	Sin3Gen_Float64.h

64 Bit Floating Point Implementation


Controller Parameters	
delta_phi	Angle increment
offset	Amplitude offset
phi	Current angle

Data Structure:

```
typedef struct {
    uint16          ID ;
    float64         *A ;
    float64         *f ;
```

```
    float64      u;
    float64      v;
    float64      w;
    float64      delta_phi;
    float64      offset;
    float64      phi;
} SIN3GEN_FLOAT64;
```

Block: SinGen



Inputs	
A	Amplitude
f	Frequency

Outputs	
u	Sine wave output

Mask Parameters	
fmax	Maximum Frequency in Hz
Offset	Offset
Phase	Phase [-Pi..Pi]
ts_fact	Multiplication factor of base sampling time (in integer format)

Description:

Generation of a sine wave with amplitude (A) and frequency (f).

Calculation fixed point implementation:

$$u_k = A_k \cdot \sin(2f_k \cdot f_{max} \cdot kT_S + \phi_{Phase}) + A_{Offset}$$

For sine calculation a lookup table with 256 entries is used. This results in a short computation time but with the downside of reduced accuracy for the FiP32 implementation.

Calculation floating point implementation (parameter *f_max* is ignored):

$$u_k = A_k \cdot \sin(2\pi f_k \cdot kT_S + \phi_{Phase}) + A_{Offset}$$

Implementations:

- FiP8** 8 Bit Fixed Point Implementation
- FiP16** 16 Bit Fixed Point Implementation
- FiP32** 32 Bit Fixed Point Implementation
- Float32** 32 Bit Floating Point Implementation
- Float64** 64 Bit Floating Point Implementation

Implementation: FiP8

Name	FiP8
ID	416
Revision	1.0
C filename	SinGen_FiP8.c
H filename	SinGen_FiP8.h

8 Bit Fixed Point Implementation

Controller Parameters	
delta_phi	Angle increment
phase	Angle offset
offset	Amplitude offset
phi	Current angle

Data Structure:

```
typedef struct {
    uint16      ID ;
    int8        *A;
    int8        *f ;
    int8        u;
    int8        delta_phi;
    int8        phase;
    int8        offset;
    int8        phi;
} SINGEN_FIP8;
```

Implementation: FiP16

Name	FiP16
ID	417
Revision	1.0
C filename	SinGen_FiP16.c
H filename	SinGen_FiP16.h

16 Bit Fixed Point Implementation

Controller Parameters	
delta_phi	Angle increment
phase	Angle offset
offset	Amplitude offset
phi	Current angle

Data Structure:

```
typedef struct {
    uint16      ID ;
    int16        *A;
    int16        *f ;
```

```

    int16      u;
    int16      delta_phi;
    int16      phase;
    int16      offset;
    int16      phi;
} SINGEN_FIP16;

```

Implementation: FiP32

Name	FiP32
ID	418
Revision	1.0
C filename	SinGen_FiP32.c
H filename	SinGen_FiP32.h

32 Bit Fixed Point Implementation

Controller Parameters	
delta_phi	Angle increment
phase	Angle offset
offset	Amplitude offset
phi	Current angle

Data Structure:

```

typedef struct {
    uint16      ID ;
    int32      *A;
    int32      *f ;
    int32      u;
    int32      delta_phi;
    int32      phase;
    int32      offset;
    int32      phi;
} SINGEN_FIP32;

```

Implementation: Float32

Name	Float32
ID	419
Revision	0.1
C filename	SinGen_Float32.c
H filename	SinGen_Float32.h

32 Bit Floating Point Implementation

Controller Parameters	
delta_phi	Angle increment
phase	Angle offset
offset	Amplitude offset
phi	Current angle

Data Structure:

```
typedef struct {
    uint16          ID ;
    float32         *A ;
    float32         *f ;
    float32         u ;
    float32         delta_phi ;
    float32         phase ;
    float32         offset ;
    float32         phi ;
} SINGEN_FLOAT32;
```

Implementation: Float64

Name	Float64
ID	420
Revision	0.1
C filename	SinGen_Float64.c
H filename	SinGen_Float64.h

64 Bit Floating Point Implementation

Controller Parameters	
delta_phi	Angle increment
phase	Angle offset
offset	Amplitude offset
phi	Current angle

Data Structure:

```
typedef struct {
    uint16          ID ;
    float64         *A ;
    float64         *f ;
    float64         u ;
    float64         delta_phi ;
    float64         phase ;
    float64         offset ;
    float64         phi ;
} SINGEN_FLOAT64;
```