



# ***Project Documentation DemoApplication***

January 18, 2023

© Linz Center of Mechatronics GmbH

# Contents

<b>I</b>	<b>X2C Model</b>	<b>2</b>
<b>1</b>	<b>Version Information</b>	<b>2</b>
1.1	X2C	2
1.2	Operating System	2
1.3	Scilab	2
<b>2</b>	<b>Model Structure</b>	<b>3</b>
2.1	Xcos Model	3
2.2	Subsystems	4
<b>3</b>	<b>Model Parameter</b>	<b>5</b>
3.1	Sample Time	5
<b>4</b>	<b>Mask Parameter</b>	<b>6</b>
4.1	Inports	6
4.1.1	Inports with auto generated ID	6
4.2	Outports	6
4.2.1	Outports with auto generated ID	6
4.3	Blocks	6
4.3.1	Blocks with auto generated ID	6
<b>II</b>	<b>Frame Program Documentation</b>	<b>9</b>
<b>5</b>	<b>File Index</b>	<b>9</b>
5.1	File List	9
<b>6</b>	<b>File Documentation</b>	<b>9</b>
6.1	inc/Hardware.h File Reference	9
6.1.1	Detailed Description	9
6.1.2	Function Documentation	9
<b>III</b>	<b>Used X2C-Blocks</b>	<b>11</b>
<b>7</b>	<b>Project Specific Blocks</b>	<b>11</b>
<b>8</b>	<b>Internal Library Blocks</b>	<b>11</b>
	AutoSwitch	11
	Constant	14
	Delay	17
	Gain	19
	I	21
	Inport	24
	Negation	25
	Outport	27
	Sin3Gen	28
	SinGen	31

## **Part I**

# **X2C Model**

## **1 Version Information**

### **1.1 X2C**

- X2C Development: Version 6.4.2727

### **1.2 Operating System**

- OS: Windows 10 10.0

### **1.3 Scilab**

- Scilab: Version 6.1.1.1626343451
- Java: Version 1.8.0\_292

## 2 Model Structure

### 2.1 Xcos Model




Figure 1: DemoApplication

## 2.2 Subsystems




Figure 2: Oscillator

### 3 Model Parameter

#### 3.1 Sample Time

Sample Time	
$T_S$	$100\mu s$

## 4 Mask Parameter

### 4.1 Inports

#### 4.1.1 Inports with auto generated ID

B1_User	
Block Type	Inport - int16
ts_fact	1.0
Simulation Gain	1.0
Simulation Offset	0.0

CPU_Temp	
Block Type	Inport - float32
ts_fact	1.0
Simulation Gain	1.0
Simulation Offset	0.0

### 4.2 Outports

#### 4.2.1 Outports with auto generated ID

LD2	
Block Type	Outport - int16
ts_fact	1.0
Simulation Gain	1.0
Simulation Offset	0.0

Osc_out	
Block Type	Outport - int16
ts_fact	1.0
Simulation Gain	1.0
Simulation Offset	0.0

### 4.3 Blocks

#### 4.3.1 Blocks with auto generated ID

Amplitude	
Block Type	Constant - FiP16
Value	0.5

AutoSwitch	
Block Type	AutoSwitch - FiP16
Thresh_up	0.0
Thresh_down	0.0

AutoSwitch1	
Block Type	AutoSwitch - FiP16
Thresh_up	0.5
Thresh_down	0.5

Frequency	
Block Type	Constant - FiP16
Value	0.005

Gain	
Block Type	Gain - FiP16
Gain	2.0

LED off	
Block Type	Constant - FiP16
Value	0.0

LED on	
Block Type	Constant - FiP16
Value	1.0

Oscillator/AutoSwitch	
Block Type	AutoSwitch - FiP16
Thresh_up	0.5
Thresh_down	-0.5

Oscillator/Constant	
Block Type	Constant - FiP16
Value	1.0

Oscillator/Delay	
Block Type	Delay - FiP16
ts_fact	1.0



Oscillator/Enable	
Block Type	Constant - Bool
Value	1.0

Oscillator/Init	
Block Type	Constant - FiP16
Value	0.0

Oscillator/Integrator	
Block Type	I - FiP16
Ki	50.0
ts_fact	1.0

Oscillator/Negation	
Block Type	Negation - FiP16

Sin3Gen	
Block Type	Sin3Gen - FiP16
fmax	1000.0
Offset	0.0
ts_fact	1.0

SinGen	
Block Type	SinGen - FiP16
fmax	1000.0
Offset	0.0
Phase	0.0
ts_fact	1.0

## Part II

# Frame Program Documentation

## 5 File Index

### 5.1 File List

Here is a list of all documented files with brief descriptions:

[inc/Hardware.h](#)  
Hardware configuration

9


## 6 File Documentation

### 6.1 inc/Hardware.h File Reference

Hardware configuration.

```
#include "SerialGeneric.h"
```

Include dependency graph for Hardware.h:



### Functions

- void [initSerial](#) (tSerial \*serialSTM32)  
*Initialization of serial interface.*
- float32 [calculateCpuTemperature](#) (int16 adcValue)  
*Routine to calculate temperature from internal temperature sensor.*

#### 6.1.1 Detailed Description

Hardware configuration.

#### 6.1.2 Function Documentation

##### 6.1.2.1 float32 calculateCpuTemperature ( int16 *adcValue* )

Routine to calculate temperature from internal temperature sensor.

NOTE: Internal temperature sensor measurement is not very accurate. Factory calibration has +/-10mV voltage reference tolerance and +/-5°C temperature reference tolerance. Additionally, linearity over temperature is specified with +/-2°C.

Parameters

<i>adcValue</i>	ADC result from internal temperature sensor channel
-----------------	---

Returns

CPU temperature in degree Celsius

#### **6.1.2.2 void initSerial ( tSerial \* *serialSTM32* )**

Initialization of serial interface.

- hook serial functions

## Part III

# Used X2C-Blocks

## 7 Project Specific Blocks

## 8 Internal Library Blocks

### Block: AutoSwitch

---



Inports	
In1	Input #1
Switch	Input #2: Threshold signal
In3	Input #3

Outputs	
Out	Either value of input #1 or input #3 dependent on value of input #2

Mask Parameters		
Name	ID	Description
Thresh_up	1	Threshold level for rising switch signal
Thresh_down	2	Threshold level for falling switch signal

#### Description:

Switch between In1 and In3 dependent on Switch signal:  
Switch signal rising: Switch  $\geq$  Threshold up  $\rightarrow$  Out = In1  
Switch signal falling: Switch  $<$  Threshold down  $\rightarrow$  Out = In3

#### Implementations:

<b>FiP16</b>	16 Bit Fixed Point Implementation
<b>FiP32</b>	32 Bit Fixed Point Implementation
<b>Float32</b>	32 Bit Floating Point Implementation
<b>Float64</b>	64 Bit Floating Point Implementation

#### Implementation: FiP16

---

16 Bit Fixed Point Implementation

Inports Data Type	
In1	int16
Switch	int16
In3	int16

Outports Data Type	
Out	int16

### Implementation: FiP32

32 Bit Fixed Point Implementation

Inports Data Type	
In1	int32
Switch	int32
In3	int32

Outports Data Type	
Out	int32

### Implementation: Float32

32 Bit Floating Point Implementation

Inports Data Type	
In1	float32
Switch	float32
In3	float32

Outports Data Type	
Out	float32

### Implementation: Float64

64 Bit Floating Point Implementation

Inports Data Type	
In1	float64
Switch	float64
In3	float64

Outports Data Type	
Out	float64

## Block: Constant

---



Outputs	
Out	Constant output

Mask Parameters		
Name	ID	Description
Value	1	Constant factor

### Description:

Constant value.

### Implementations:

<b>Bool</b>	Boolean Implementation
<b>Int8</b>	8 Bit Integer Implementation
<b>Int16</b>	16 Bit Integer Implementation
<b>Int32</b>	32 Bit Integer Implementation
<b>FiP8</b>	8 Bit Fixed Point Implementation
<b>FiP16</b>	16 Bit Fixed Point Implementation
<b>FiP32</b>	32 Bit Fixed Point Implementation
<b>Float32</b>	32 Bit Floating Point Implementation
<b>Float64</b>	64 Bit Floating Point Implementation

### Implementation: Bool

---

Boolean Implementation

Outputs Data Type	
Out	bool

### Implementation: Int8

---

8 Bit Integer Implementation

Outputs Data Type	
Out	int8

### Implementation: Int16

---

16 Bit Integer Implementation

Outports Data Type	
Out	int16

### Implementation: Int32

---

32 Bit Integer Implementation

Outports Data Type	
Out	int32

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

Outports Data Type	
Out	int8

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

Outports Data Type	
Out	int16

### Implementation: FiP32

---

32 Bit Fixed Point Implementation

Outports Data Type	
Out	int32

### Implementation: Float32

---

32 Bit Floating Point Implementation

Outports Data Type	
Out	float32



## Implementation: Float64

---

64 Bit Floating Point Implementation

Outports Data Type	
Out	float64

## Block: Delay

---



Inports	
In	Input In(k)

Outputs	
Out	Output Out(k)=In(k-1)

Mask Parameters		
Name	ID	Description
ts_fact	1	Multiplication factor of base sampling time (in integer format)

### Description:

Output delay by one sample time interval.

This block can be used to enable feedback loops in the model.

### Implementations:

<b>Bool</b>	Boolean Integration
<b>FiP16</b>	16 Bit Fixed Point Implementation
<b>FiP32</b>	32 Bit Fixed Point Implementation
<b>Float32</b>	32 Bit Floating Point Implementation
<b>Float64</b>	64 Bit Floating Point Implementation

### Implementation: Bool

---

Boolean Integration

Inports Data Type	
In	bool

Outputs Data Type	
Out	bool

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

Inports Data Type	
In	int16

Outports Data Type	
Out	int16

### Implementation: FiP32

32 Bit Fixed Point Implementation

Inports Data Type	
In	int32

Outports Data Type	
Out	int32

### Implementation: Float32

32 Bit Floating Point Implementation

Inports Data Type	
In	float32

Outports Data Type	
Out	float32

### Implementation: Float64

64 Bit Floating Point Implementation

Inports Data Type	
In	float64

Outports Data Type	
Out	float64

## Block: Gain

---



Inports	
In	Input

Outports	
Out	Amplified input

Mask Parameters		
Name	ID	Description
Gain	1	Gain factor in floating point format

### Description:

Amplification of input by gain factor.

### Implementations:

<b>FiP8</b>	8 Bit Fixed Point Implementation
<b>FiP16</b>	16 Bit Fixed Point Implementation
<b>FiP32</b>	32 Bit Fixed Point Implementation
<b>Float32</b>	32 Bit Floating Point Implementation
<b>Float64</b>	64 Bit Floating Point Implementation

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

Inports Data Type	
In	int8

Outports Data Type	
Out	int8

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

Inports Data Type	
In	int16

Outports Data Type	
Out	int16

### Implementation: FiP32

32 Bit Fixed Point Implementation

Inports Data Type	
In	int32

Outports Data Type	
Out	int32

### Implementation: Float32

32 Bit Floating Point Implementation

Inports Data Type	
In	float32

Outports Data Type	
Out	float32


### Implementation: Float64

64 Bit Floating Point Implementation

Inports Data Type	
In	float64

Outports Data Type	
Out	float64

## Block: I



Inports	
In	Control error input
Init	Value which is loaded at initialization function call
Enable	Enable == 0: Deactivation of block; Out set to 0 Enable 0->1: Preload of integral part Enable == 1: Activation of block

Outports	
Out	Control value

Mask Parameters		
Name	ID	Description
Ki	1	Integral Factor
ts_fact	2	Multiplication factor of base sampling time (in integer format)

### Description:

I controller:

$$G(s) = K_i/s = 1/(T_i*s)$$

Each fixed point implementation uses the next higher integer datatype for the integrational value storage variable.

A rising flank at the *Enable* input will preload the integrational part with the value present on the *Init* input.

Transfer function (zero-order hold discretization method):

$$G(z) = K_i T_s \frac{1}{z - 1}$$

### Implementations:

<b>FiP8</b>	8 Bit Fixed Point Implementation
<b>FiP16</b>	16 Bit Fixed Point Implementation
<b>FiP32</b>	32 Bit Fixed Point Implementation
<b>Float32</b>	32 Bit Floating Point Implementation
<b>Float64</b>	64 Bit Floating Point Implementation

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

Inports Data Type	
In	int8
Init	int8
Enable	bool

Outports Data Type	
Out	int8

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

Inports Data Type	
In	int16
Init	int16
Enable	bool

Outports Data Type	
Out	int16

### Implementation: FiP32

---

32 Bit Fixed Point Implementation

Inports Data Type	
In	int32
Init	int32
Enable	bool

Outports Data Type	
Out	int32

### Implementation: Float32

---

32 Bit Floating Point Implementation

Inports Data Type	
In	float32
Init	float32
Enable	bool

Outports Data Type	
Out	float32

### Implementation: Float64

64 Bit Floating Point Implementation

Inports Data Type	
In	float64
Init	float64
Enable	bool

Outports Data Type	
Out	float64



## Block: Inport




Inports	
IN	Signal from frame program

Mask Parameters	
ts_fact	Multiplication factor of base sampling time (in integer format)
Gain	Gain value used in simulation
Offset	Offset value used in simulation

### Description:

Serves as interface to the frame program. The input of this block is intended for simulation purposes and can be left unconnected if not used. Also the parameters *Gain* and *Offset* are only used during simulation. The schematic for simulation can be seen in the figure below.

**Note:** Currently, *Gain* and *Offset* parameters are only available in Matlab/Simulink.



### Data Types:

<b>int8</b>	8 Bit Fixed Point
<b>int16</b>	16 Bit Fixed Point
<b>int32</b>	32 Bit Fixed Point
<b>float32</b>	32 Bit Floating Point
<b>float64</b>	64 Bit Floating Point

## Block: Negation

---



Inports	
In	Input

Outputs	
Out	Negated input value

### Description:

Negation of input signal.

Calculation:

$$\text{Out} = -\text{In}$$

### Implementations:

<b>FiP8</b>	8 Bit Fixed Point Implementation
<b>FiP16</b>	16 Bit Fixed Point Implementation
<b>FiP32</b>	32 Bit Fixed Point Implementation
<b>Float32</b>	32 Bit Floating Point Implementation
<b>Float64</b>	64 Bit Floating Point Implementation

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

Inports Data Type	
In	int8

Outports Data Type	
Out	int8

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

Inports Data Type	
In	int16

Outports Data Type	
Out	int16

### Implementation: FiP32

32 Bit Fixed Point Implementation

Inports Data Type	
In	int32

Outports Data Type	
Out	int32

### Implementation: Float32

32 Bit Floating Point Implementation

Inports Data Type	
In	float32

Outports Data Type	
Out	float32


### Implementation: Float64

64 Bit Floating Point Implementation

Inports Data Type	
In	float64

Outports Data Type	
Out	float64

## Block: Output




Outputs	
OUT	Signal to frame program

Mask Parameters	
ts_fact	Multiplication factor of base sampling time (in integer format)
Gain	Gain value used in simulation
Offset	Offset value used in simulation

### Description:

Serves as interface to the frame program. The output of this block is intended for simulation purposes and can be left unconnected if not used. Also the parameters *Gain*, and *Offset* are only used during simulation. The schematic for simulation can be seen in the figure below. The Unit Delay block is only used during simulation and should reflect the time delay caused by a discrete controller.


**Note:** Currently, *Gain* and *Offset* parameters are only available in Matlab/Simulink.



### Data Types:

<b>int8</b>	8 Bit Fixed Point
<b>int16</b>	16 Bit Fixed Point
<b>int32</b>	32 Bit Fixed Point
<b>float32</b>	32 Bit Floating Point
<b>float64</b>	64 Bit Floating Point

## Block: Sin3Gen



Inports	
A	Amplitude
f	Frequency

Outputs	
u	Sine wave output phase u
v	Sine wave output phase v
w	Sine wave output phase w

Mask Parameters		
Name	ID	Description
fmax	1	Maximum Frequency in Hz
Offset	2	Offset
ts_fact	3	Multiplication factor of base sampling time (in integer format)

### Description:

Generation of a 3 sine waves with amplitude (A) and frequency (f).

Calculation fixed point implementation:

$$\begin{aligned}
 u_k &= A_k \sin(2f_k f_{\max} kT_s) + A_{\text{offset}} \\
 v_k &= A_k \sin\left(2f_k f_{\max} kT_s - \frac{2\pi}{3}\right) + A_{\text{offset}} \\
 w_k &= A_k \sin\left(2f_k f_{\max} kT_s + \frac{2\pi}{3}\right) + A_{\text{offset}}
 \end{aligned}$$

For sine calculation a lookup table with 256 entries is used. This results in a short computation time but with the downside of reduced accuracy for the FiP32 implementation.

Calculation floating point implementation (parameter  $f_{\max}$  is ignored):

$$\begin{aligned}
 u_k &= A_k \sin(2\pi f_k kT_s) + A_{\text{offset}} \\
 v_k &= A_k \sin\left(2\pi f_k kT_s - \frac{2\pi}{3}\right) + A_{\text{offset}} \\
 w_k &= A_k \sin\left(2\pi f_k kT_s + \frac{2\pi}{3}\right) + A_{\text{offset}}
 \end{aligned}$$

**Implementations:**

<b>FiP16</b>	16 Bit Fixed Point Implementation
<b>FiP32</b>	32 Bit Fixed Point Implementation
<b>Float32</b>	32 Bit Floating Point Implementation
<b>Float64</b>	64 Bit Floating Point Implementation

**Implementation: FiP16**

---

16 Bit Fixed Point Implementation

Inports Data Type	
A	int16
f	int16

Outports Data Type	
u	int16
v	int16
w	int16

**Implementation: FiP32**

---

32 Bit Fixed Point Implementation

Inports Data Type	
A	int32
f	int32

Outports Data Type	
u	int32
v	int32
w	int32

**Implementation: Float32**

---

32 Bit Floating Point Implementation

Inports Data Type	
A	float32
f	float32

Outports Data Type	
u	float32
v	float32
w	float32

### Implementation: Float64

---


64 Bit Floating Point Implementation

Inports Data Type	
A	float64
f	float64

Outports Data Type	
u	float64
v	float64
w	float64

## Block: SinGen

---



Inports	
A	Amplitude
f	Frequency

Outputs	
u	Sine wave output

Mask Parameters		
Name	ID	Description
fmax	1	Maximum Frequency in Hz
Offset	2	Offset
Phase	3	Phase [-Pi..Pi]
ts_fact	4	Multiplication factor of base sampling time (in integer format)

### Description:

Generation of a sine wave with amplitude (A) and frequency (f).

Calculation fixed point implementation:

$$u_k = A_k \sin(2f_k f_{\max} k T_s + \phi_{\text{phase}}) + A_{\text{offset}}$$

For sine calculation a lookup table with 256 entries is used. This results in a short computation time but with the downside of reduced accuracy for the FiP32 implementation.

Calculation floating point implementation (parameter  $f_{\max}$  is ignored):

$$u_k = A_k \sin(2\pi f_k k T_s + \phi_{\text{phase}}) + A_{\text{offset}}$$

### Implementations:

<b>FiP16</b>	16 Bit Fixed Point Implementation
<b>FiP32</b>	32 Bit Fixed Point Implementation
<b>Float32</b>	32 Bit Floating Point Implementation
<b>Float64</b>	64 Bit Floating Point Implementation

### Implementation: FiP16

---

16 Bit Fixed Point Implementation



Inports Data Type	
A	int16
f	int16

Outports Data Type	
u	int16

### Implementation: FiP32

32 Bit Fixed Point Implementation

Inports Data Type	
A	int32
f	int32

Outports Data Type	
u	int32

### Implementation: Float32

32 Bit Floating Point Implementation

Inports Data Type	
A	float32
f	float32

Outports Data Type	
u	float32

### Implementation: Float64

64 Bit Floating Point Implementation

Inports Data Type	
A	float64
f	float64

Outports Data Type	
u	float64