



# ***Documentation***

***X2C v6.6.4510***

**August 30, 2026**

©Linz Center of Mechatronics GmbH

# Contents

|          |                                 |             |
|----------|---------------------------------|-------------|
| <b>1</b> | <b>Test Settings</b>            | <b>4</b>    |
| 1.1      | Test Settings for C28xx         | 4           |
| 1.2      | Test Settings for dsPIC33E      | 4           |
| 1.3      | Test Settings for PIC32         | 4           |
| 1.4      | Test Settings for STM32         | 4           |
| 1.5      | Test Settings for TM4C          | 4           |
| 1.6      | Test Settings for XMC4000       | 5           |
| <b>2</b> | <b>Basic</b>                    | <b>6</b>    |
|          | CommunicatorStart (Xcos only)   | 7           |
|          | CreateDocumentation             | 8           |
|          | Interact (Xcos only)            | 9           |
|          | ModelTransformation (Xcos only) | 10          |
| <b>3</b> | <b>Control</b>                  | <b>11</b>   |
|          | AdaptivePT1                     | 12          |
|          | D                               | 31          |
|          | Delay                           | 106         |
|          | DLimit                          | 132         |
|          | DT1                             | 207         |
|          | I                               | 226         |
|          | ILimit                          | 277         |
|          | P                               | 328         |
|          | PI                              | 378         |
|          | PID                             | 453         |
|          | PIDLimit                        | 560         |
|          | PLimit                          | 668         |
|          | PLimit                          | 744         |
|          | PT1                             | 795         |
|          | TDSysO1                         | 814         |
|          | TDSysO2                         | 889         |
|          | TF1                             | 956         |
|          | TF2                             | 959         |
|          | ul                              | 961         |
| <b>4</b> | <b>Filter</b>                   | <b>1012</b> |
|          | ACDC                            | 1013        |
|          | AdaptiveNotch                   | 1039        |
|          | BandpassBiQ                     | 1042        |
|          | BandstopBiQ                     | 1046        |
|          | Bilin                           | 1050        |
|          | Biquad                          | 1124        |
|          | FundFreq                        | 1230        |
|          | HighpassBiQ                     | 1256        |
|          | IIR                             | 1261        |
|          | LowpassBiQ                      | 1263        |
|          | MinMaxPeriodic                  | 1268        |
|          | NotchBiQ                        | 1295        |

|          |                |             |
|----------|----------------|-------------|
| <b>5</b> | <b>General</b> | <b>1402</b> |
|          | And            | 1403        |
|          | AutoSwitch     | 1412        |
|          | Constant       | 1510        |
|          | Gain           | 1561        |
|          | Inport         | 1635        |
|          | Int2Real       | 1636        |
|          | Limitation     | 1711        |
|          | LookupTable    | 1737        |
|          | LookupTable1D  | 1739        |
|          | LookupTable2D  | 1792        |
|          | LookupTable3D  | 1867        |
|          | LoopBreaker    | 1966        |
|          | ManualSwitch   | 1992        |
|          | Maximum        | 2091        |
|          | Minimum        | 2117        |
|          | Not            | 2143        |
|          | Or             | 2152        |
|          | Outport        | 2161        |
|          | RateLimiter    | 2162        |
|          | Real2Int       | 2237        |
|          | Saturation     | 2304        |
|          | SaveSignal     | 2330        |
|          | Selector       | 2332        |
|          | Sequencer      | 2384        |
|          | Sin2Limiter    | 2411        |
|          | Sin3Gen        | 2414        |
|          | SinGen         | 2449        |
|          | TypeConv       | 2467        |
|          | uConstant      | 2551        |
|          | uGain          | 2602        |
|          | uRateLimiter   | 2676        |
|          | uSaveSignal    | 2727        |
|          | Xor            | 2729        |
| <b>6</b> | <b>Math</b>    | <b>2738</b> |
|          | Abs            | 2739        |
|          | Acos           | 2765        |
|          | Add            | 2791        |
|          | Asin           | 2817        |
|          | Atan2          | 2843        |
|          | Average        | 2870        |
|          | Cos            | 2968        |
|          | Div            | 2995        |
|          | Exp            | 3022        |
|          | L2Norm         | 3049        |
|          | Mult           | 3075        |
|          | Negation       | 3101        |
|          | Sign           | 3127        |
|          | Sin            | 3153        |
|          | Sqrt           | 3180        |
|          | Sub            | 3207        |
|          | Sum            | 3233        |

|      |       |      |
|------|-------|------|
| uAdd | ..... | 3333 |
| uSub | ..... | 3359 |



# 1 Test Settings

## 1.1 Test Settings for C28xx

- Environment: Texas Instruments CCS 12.8.1
- Compiler F28335: v16.9.5.LTS
- Compiler F28379D: v22.6.1 LTS
- Optimization: -O2
- Floating point support: fpu32 (when applicable)
- Conversion on target: float32
- All functions are loaded from RAM

## 1.2 Test Settings for dsPIC33E

- Environment: Microchip MPLABX v6.20
- Compiler: XC16 v1.70
- Optimization: -O2
- Conversion on target: float32

## 1.3 Test Settings for PIC32

- Environment: Microchip MPLABX v6.20
- Compiler: XC32 v5.10
- Optimization: -O2
- Conversion on target: float32

## 1.4 Test Settings for STM32

- Environment: STMicroelectronics STM32CubeIDE v1.19.0
- Compiler STM32F0: GNU Tools for STM32 (10.3-2021.10)
- Compiler STM32G4: GNU Tools for STM32 (13.3.rel1)
- Optimization: -O2
- Conversion on target: float32

## 1.5 Test Settings for TM4C


- Environment: Texas Instruments CCS 12.8.1
- Compiler: v16.9.4.LTS
- Optimization: -O2
- Floating point support: FPv4SPD166
- Conversion on target: float32

## **1.6 Test Settings for XMC4000**

- Environment: Infineon DAVE v4.5.0
- Compiler: ARM-GCC-49
- Optimization: -O2
- Floating point support: fpv4-sp-d16
- Conversion on target: float32

## 2 Basic

Virtual blocks to configure basic code generation, simulation and help generation settings.



## Block: CommunicatorStart (Xcos only)

---



### Description:

With a double-click on this block, the X2C Communicator will start. The Communicator will connect to Scilab via Java Remote Method Invocation (Java RMI) to enable data exchange between Scilab and X2C.

## Block: CreateDocumentation

---



### Description:

With a double-click on this block, a documentation with all relevant information about the current X2C project can be created. The document will be created in `<ProjectDir>\Doc` and will be called `ProjectDocumentation_<NameOfModel>.pdf`.

### Parameters

**User documentation:** It is possible to add user specific documentation to the project documentation. When creating the project documentation, the `X2CCode` directory is scanned for the specified tex file (`UserDoc.tex` by default). If the file is present, it will be included in the documentation.

**Test reports:** If the checkbox `Add test reports` is selected, test reports of the C-Unit tests of the used X2C blocks are added to the project documentation.

### Requirements

In order to generate a documentation in PDF-format a TeX-compiler (e.g. `MiKTeX`) has to be installed. The software tools `Doxygen` and `Graphviz` are recommended to get documentation of the C-code.

## Block: Interact (Xcos only)

---



### Description:

When double-clicked, the block executes the Scilab script *doInteraction.sci*, if available. By customizing the script, the user can execute simple tasks, e.g. setting block parameters, read parameter values, display status information, etc., repeatedly and effortlessly.

## Block: ModelTransformation (Xcos only)

---




### Description:

With a double-click on this block, the Xcos model will be analyzed. All relevant information for code generation are gathered, transfered to the Communicator and written to the model XML file.


### 3 Control

This library contains blocks for building control algorithms.





## Block: AdaptivePT1



First order low pass with adaptive cut off frequency:

$$G(s) = V/(s/(2\pi fc) + 1)$$

| Inports |                  |
|---------|------------------|
| In      | Input In(k)      |
| fc      | Cutoff frequency |

| Outports |               |
|----------|---------------|
| Out      | Output Out(k) |

| Mask Parameters |    |                                                                        |
|-----------------|----|------------------------------------------------------------------------|
| Name            | ID | Description                                                            |
| V               | 1  | Gain                                                                   |
| fmax            | 2  | Maximum frequency [Hz]<br>(not used in floating point implementations) |
| ts_fact         | 3  | Multiplication factor of base sampling time (in integer format)        |
| method          | 4  | Discretization method                                                  |

### Description:

Transfer function (zero-order hold discretization method):

$$G(z) = V \frac{1 - e^{-2\pi fc T_s}}{z - e^{-2\pi fc T_s}}$$

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP8

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | int8 |
| fc                | int8 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |
| fc                | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |
| fc                | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |
| fc                | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

## Implementation: Float64

---

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |
| fc                | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: AdaptivePT1 FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block AdaptivePT1.

| Test results   |      |      |      |      |     |        |
|----------------|------|------|------|------|-----|--------|
| Time step      | 1    | 2    | 3    | 4    | ... | 105    |
| CPU cycles     | 129  | 129  | 129  | 129  | ... | 129    |
| Inputs         |      |      |      |      |     |        |
| In (DSP)       | 0    | 0    | 0    | 0    | ... | -9830  |
| fc (DSP)       | 7537 | 7537 | 7537 | 7537 | ... | 7537   |
| In             | 0    | 0    | 0    | 0    | ... | -0.3   |
| fc             | 0.23 | 0.23 | 0.23 | 0.23 | ... | 0.23   |
| Parameters     |      |      |      |      |     |        |
| V              | 1.1  |      |      |      |     |        |
| fmax           | 1000 |      |      |      |     |        |
| ts_fact        | 1    |      |      |      |     |        |
| method         | zoh  |      |      |      |     |        |
| Outputs        |      |      |      |      |     |        |
| Out            | 0    | 0    | 0    | 0    | ... | -0.329 |
| Exp. Out       | 0    | 0    | 0    | 0    | ... | -0.329 |
| Out (DSP)      | 0    | 0    | 0    | 0    | ... | -10778 |
| Exp. Out (DSP) | 0    | 0    | 0    | 0    | ... | -10780 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 6,1035e-04$ ( $\pm 20$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 129 |
| Max CPU cycles  | 129 |
| Avg CPU cycles  | 129 |

**Verification: AdaptivePT1 FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block AdaptivePT1.

| Test results   |      |      |      |      |     |        |
|----------------|------|------|------|------|-----|--------|
| Time step      | 1    | 2    | 3    | 4    | ... | 105    |
| CPU cycles     | 85   | 85   | 85   | 85   | ... | 85     |
| Inputs         |      |      |      |      |     |        |
| In (DSP)       | 0    | 0    | 0    | 0    | ... | -9830  |
| fc (DSP)       | 7537 | 7537 | 7537 | 7537 | ... | 7537   |
| In             | 0    | 0    | 0    | 0    | ... | -0.3   |
| fc             | 0.23 | 0.23 | 0.23 | 0.23 | ... | 0.23   |
| Parameters     |      |      |      |      |     |        |
| V              | 1.1  |      |      |      |     |        |
| fmax           | 1000 |      |      |      |     |        |
| ts_fact        | 1    |      |      |      |     |        |
| method         | zoh  |      |      |      |     |        |
| Outputs        |      |      |      |      |     |        |
| Out            | 0    | 0    | 0    | 0    | ... | -0.329 |
| Exp. Out       | 0    | 0    | 0    | 0    | ... | -0.329 |
| Out (DSP)      | 0    | 0    | 0    | 0    | ... | -10778 |
| Exp. Out (DSP) | 0    | 0    | 0    | 0    | ... | -10780 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 6,1035e-04$ ( $\pm 20$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 85 |
| Max CPU cycles  | 85 |
| Avg CPU cycles  | 85 |

**Verification: AdaptivePT1 FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block AdaptivePT1.

| Test results   |      |      |      |      |     |        |
|----------------|------|------|------|------|-----|--------|
| Time step      | 1    | 2    | 3    | 4    | ... | 105    |
| CPU cycles     | 132  | 132  | 132  | 132  | ... | 132    |
| Inputs         |      |      |      |      |     |        |
| In (DSP)       | 0    | 0    | 0    | 0    | ... | -9830  |
| fc (DSP)       | 7537 | 7537 | 7537 | 7537 | ... | 7537   |
| In             | 0    | 0    | 0    | 0    | ... | -0.3   |
| fc             | 0.23 | 0.23 | 0.23 | 0.23 | ... | 0.23   |
| Parameters     |      |      |      |      |     |        |
| V              | 1.1  |      |      |      |     |        |
| fmax           | 1000 |      |      |      |     |        |
| ts_fact        | 1    |      |      |      |     |        |
| method         | zoh  |      |      |      |     |        |
| Outputs        |      |      |      |      |     |        |
| Out            | 0    | 0    | 0    | 0    | ... | -0.329 |
| Exp. Out       | 0    | 0    | 0    | 0    | ... | -0.329 |
| Out (DSP)      | 0    | 0    | 0    | 0    | ... | -10778 |
| Exp. Out (DSP) | 0    | 0    | 0    | 0    | ... | -10780 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 6,1035e-04$ ( $\pm 20$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 132 |
| Max CPU cycles  | 132 |
| Avg CPU cycles  | 132 |

**Verification: AdaptivePT1 FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block AdaptivePT1.

| Test results   |      |      |      |      |     |        |
|----------------|------|------|------|------|-----|--------|
| Time step      | 1    | 2    | 3    | 4    | ... | 105    |
| CPU cycles     | 120  | 120  | 120  | 120  | ... | 120    |
| Inputs         |      |      |      |      |     |        |
| In (DSP)       | 0    | 0    | 0    | 0    | ... | -9830  |
| fc (DSP)       | 7537 | 7537 | 7537 | 7537 | ... | 7537   |
| In             | 0    | 0    | 0    | 0    | ... | -0.3   |
| fc             | 0.23 | 0.23 | 0.23 | 0.23 | ... | 0.23   |
| Parameters     |      |      |      |      |     |        |
| V              | 1.1  |      |      |      |     |        |
| fmax           | 1000 |      |      |      |     |        |
| ts_fact        | 1    |      |      |      |     |        |
| method         | zoh  |      |      |      |     |        |
| Outputs        |      |      |      |      |     |        |
| Out            | 0    | 0    | 0    | 0    | ... | -0.329 |
| Exp. Out       | 0    | 0    | 0    | 0    | ... | -0.329 |
| Out (DSP)      | 0    | 0    | 0    | 0    | ... | -10778 |
| Exp. Out (DSP) | 0    | 0    | 0    | 0    | ... | -10780 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 6,1035e-04$ ( $\pm 20$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 120 |
| Max CPU cycles  | 120 |
| Avg CPU cycles  | 120 |

**Verification: AdaptivePT1 FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block AdaptivePT1.

| Test results   |      |      |      |      |     |        |
|----------------|------|------|------|------|-----|--------|
| Time step      | 1    | 2    | 3    | 4    | ... | 105    |
| CPU cycles     | 81   | 81   | 81   | 81   | ... | 81     |
| Inputs         |      |      |      |      |     |        |
| In (DSP)       | 0    | 0    | 0    | 0    | ... | -9830  |
| fc (DSP)       | 7537 | 7537 | 7537 | 7537 | ... | 7537   |
| In             | 0    | 0    | 0    | 0    | ... | -0.3   |
| fc             | 0.23 | 0.23 | 0.23 | 0.23 | ... | 0.23   |
| Parameters     |      |      |      |      |     |        |
| V              | 1.1  |      |      |      |     |        |
| fmax           | 1000 |      |      |      |     |        |
| ts_fact        | 1    |      |      |      |     |        |
| method         | zoh  |      |      |      |     |        |
| Outputs        |      |      |      |      |     |        |
| Out            | 0    | 0    | 0    | 0    | ... | -0.329 |
| Exp. Out       | 0    | 0    | 0    | 0    | ... | -0.329 |
| Out (DSP)      | 0    | 0    | 0    | 0    | ... | -10778 |
| Exp. Out (DSP) | 0    | 0    | 0    | 0    | ... | -10780 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 6,1035e-04$ ( $\pm 20$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 81 |
| Max CPU cycles  | 81 |
| Avg CPU cycles  | 81 |



**Verification: AdaptivePT1 FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block AdaptivePT1.

| Test results   |      |      |      |      |     |        |
|----------------|------|------|------|------|-----|--------|
| Time step      | 1    | 2    | 3    | 4    | ... | 105    |
| CPU cycles     | 154  | 127  | 127  | 127  | ... | 127    |
| Inputs         |      |      |      |      |     |        |
| In (DSP)       | 0    | 0    | 0    | 0    | ... | -9830  |
| fc (DSP)       | 7537 | 7537 | 7537 | 7537 | ... | 7537   |
| In             | 0    | 0    | 0    | 0    | ... | -0.3   |
| fc             | 0.23 | 0.23 | 0.23 | 0.23 | ... | 0.23   |
| Parameters     |      |      |      |      |     |        |
| V              | 1.1  |      |      |      |     |        |
| fmax           | 1000 |      |      |      |     |        |
| ts_fact        | 1    |      |      |      |     |        |
| method         | zoh  |      |      |      |     |        |
| Outputs        |      |      |      |      |     |        |
| Out            | 0    | 0    | 0    | 0    | ... | -0.329 |
| Exp. Out       | 0    | 0    | 0    | 0    | ... | -0.329 |
| Out (DSP)      | 0    | 0    | 0    | 0    | ... | -10778 |
| Exp. Out (DSP) | 0    | 0    | 0    | 0    | ... | -10780 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 6,1035e-04$ ( $\pm 20$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 127 |
| Max CPU cycles  | 154 |
| Avg CPU cycles  | 127 |

**Verification: AdaptivePT1 FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block AdaptivePT1.

| Test results   |      |      |      |      |     |        |
|----------------|------|------|------|------|-----|--------|
| Time step      | 1    | 2    | 3    | 4    | ... | 105    |
| CPU cycles     | 118  | 118  | 118  | 118  | ... | 118    |
| Inputs         |      |      |      |      |     |        |
| In (DSP)       | 0    | 0    | 0    | 0    | ... | -9830  |
| fc (DSP)       | 7537 | 7537 | 7537 | 7537 | ... | 7537   |
| In             | 0    | 0    | 0    | 0    | ... | -0.3   |
| fc             | 0.23 | 0.23 | 0.23 | 0.23 | ... | 0.23   |
| Parameters     |      |      |      |      |     |        |
| V              | 1.1  |      |      |      |     |        |
| fmax           | 1000 |      |      |      |     |        |
| ts_fact        | 1    |      |      |      |     |        |
| method         | zoh  |      |      |      |     |        |
| Outputs        |      |      |      |      |     |        |
| Out            | 0    | 0    | 0    | 0    | ... | -0.329 |
| Exp. Out       | 0    | 0    | 0    | 0    | ... | -0.329 |
| Out (DSP)      | 0    | 0    | 0    | 0    | ... | -10778 |
| Exp. Out (DSP) | 0    | 0    | 0    | 0    | ... | -10780 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 6,1035e-04$ ( $\pm 20$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 118 |
| Max CPU cycles  | 118 |
| Avg CPU cycles  | 118 |

**Verification: AdaptivePT1 FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block AdaptivePT1.

| Test results   |      |      |      |      |     |        |
|----------------|------|------|------|------|-----|--------|
| Time step      | 1    | 2    | 3    | 4    | ... | 105    |
| CPU cycles     | 131  | 131  | 131  | 131  | ... | 131    |
| Inputs         |      |      |      |      |     |        |
| In (DSP)       | 0    | 0    | 0    | 0    | ... | -9830  |
| fc (DSP)       | 7537 | 7537 | 7537 | 7537 | ... | 7537   |
| In             | 0    | 0    | 0    | 0    | ... | -0.3   |
| fc             | 0.23 | 0.23 | 0.23 | 0.23 | ... | 0.23   |
| Parameters     |      |      |      |      |     |        |
| V              | 1.1  |      |      |      |     |        |
| fmax           | 1000 |      |      |      |     |        |
| ts_fact        | 1    |      |      |      |     |        |
| method         | zoh  |      |      |      |     |        |
| Outputs        |      |      |      |      |     |        |
| Out            | 0    | 0    | 0    | 0    | ... | -0.329 |
| Exp. Out       | 0    | 0    | 0    | 0    | ... | -0.329 |
| Out (DSP)      | 0    | 0    | 0    | 0    | ... | -10778 |
| Exp. Out (DSP) | 0    | 0    | 0    | 0    | ... | -10780 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 6,1035e-04$ ( $\pm 20$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 131 |
| Max CPU cycles  | 131 |
| Avg CPU cycles  | 131 |

**Verification: AdaptivePT1 FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block AdaptivePT1.

| Test results   |           |           |     |            |
|----------------|-----------|-----------|-----|------------|
| Time step      | 1         | 2         | ... | 105        |
| CPU cycles     | 276       | 276       | ... | 276        |
| Inputs         |           |           |     |            |
| In (DSP)       | 0         | 0         | ... | -644245094 |
| fc (DSP)       | 493921239 | 493921239 | ... | 493921239  |
| In             | 0         | 0         | ... | -0.3       |
| fc             | 0.23      | 0.23      | ... | 0.23       |
| Parameters     |           |           |     |            |
| V              | 1.1       |           |     |            |
| fmax           | 1000      |           |     |            |
| ts_fact        | 1         |           |     |            |
| method         | zoh       |           |     |            |
| Outputs        |           |           |     |            |
| Out            | 0         | 0         | ... | -0.329     |
| Exp. Out       | 0         | 0         | ... | -0.329     |
| Out (DSP)      | 0         | 0         | ... | -706485147 |
| Exp. Out (DSP) | 0         | 0         | ... | -706485964 |

| Test settings |                                            |
|---------------|--------------------------------------------|
| Tolerance Out | $\pm 2,3749\text{e-}05$ ( $\pm 51000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 276 |
| Max CPU cycles  | 276 |
| Avg CPU cycles  | 276 |

**Verification: AdaptivePT1 FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block AdaptivePT1.

| Test results   |           |           |     |            |
|----------------|-----------|-----------|-----|------------|
| Time step      | 1         | 2         | ... | 105        |
| CPU cycles     | 171       | 171       | ... | 171        |
| Inputs         |           |           |     |            |
| In (DSP)       | 0         | 0         | ... | -644245094 |
| fc (DSP)       | 493921239 | 493921239 | ... | 493921239  |
| In             | 0         | 0         | ... | -0.3       |
| fc             | 0.23      | 0.23      | ... | 0.23       |
| Parameters     |           |           |     |            |
| V              | 1.1       |           |     |            |
| fmax           | 1000      |           |     |            |
| ts_fact        | 1         |           |     |            |
| method         | zoh       |           |     |            |
| Outputs        |           |           |     |            |
| Out            | 0         | 0         | ... | -0.329     |
| Exp. Out       | 0         | 0         | ... | -0.329     |
| Out (DSP)      | 0         | 0         | ... | -706485147 |
| Exp. Out (DSP) | 0         | 0         | ... | -706485964 |

| Test settings |                                            |
|---------------|--------------------------------------------|
| Tolerance Out | $\pm 2,3749\text{e-}05$ ( $\pm 51000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 171 |
| Max CPU cycles  | 171 |
| Avg CPU cycles  | 171 |

**Verification: AdaptivePT1 FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block AdaptivePT1.

| Test results   |           |           |     |            |
|----------------|-----------|-----------|-----|------------|
| Time step      | 1         | 2         | ... | 105        |
| CPU cycles     | 192       | 192       | ... | 192        |
| Inputs         |           |           |     |            |
| In (DSP)       | 0         | 0         | ... | -644245094 |
| fc (DSP)       | 493921239 | 493921239 | ... | 493921239  |
| In             | 0         | 0         | ... | -0.3       |
| fc             | 0.23      | 0.23      | ... | 0.23       |
| Parameters     |           |           |     |            |
| V              | 1.1       |           |     |            |
| fmax           | 1000      |           |     |            |
| ts_fact        | 1         |           |     |            |
| method         | zoh       |           |     |            |
| Outputs        |           |           |     |            |
| Out            | 0         | 0         | ... | -0.329     |
| Exp. Out       | 0         | 0         | ... | -0.329     |
| Out (DSP)      | 0         | 0         | ... | -706485147 |
| Exp. Out (DSP) | 0         | 0         | ... | -706485964 |

| Test settings |                                            |
|---------------|--------------------------------------------|
| Tolerance Out | $\pm 2,3749\text{e-}05$ ( $\pm 51000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 192 |
| Max CPU cycles  | 192 |
| Avg CPU cycles  | 192 |

**Verification: AdaptivePT1 FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block AdaptivePT1.

| Test results   |           |           |     |            |
|----------------|-----------|-----------|-----|------------|
| Time step      | 1         | 2         | ... | 105        |
| CPU cycles     | 503       | 503       | ... | 500        |
| Inputs         |           |           |     |            |
| In (DSP)       | 0         | 0         | ... | -644245094 |
| fc (DSP)       | 493921239 | 493921239 | ... | 493921239  |
| In             | 0         | 0         | ... | -0.3       |
| fc             | 0.23      | 0.23      | ... | 0.23       |
| Parameters     |           |           |     |            |
| V              | 1.1       |           |     |            |
| fmax           | 1000      |           |     |            |
| ts_fact        | 1         |           |     |            |
| method         | zoh       |           |     |            |
| Outputs        |           |           |     |            |
| Out            | 0         | 0         | ... | -0.329     |
| Exp. Out       | 0         | 0         | ... | -0.329     |
| Out (DSP)      | 0         | 0         | ... | -706485147 |
| Exp. Out (DSP) | 0         | 0         | ... | -706485964 |

| Test settings |                                            |
|---------------|--------------------------------------------|
| Tolerance Out | $\pm 2,3749\text{e-}05$ ( $\pm 51000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 500 |
| Max CPU cycles  | 563 |
| Avg CPU cycles  | 503 |

**Verification: AdaptivePT1 FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block AdaptivePT1.

| Test results   |           |           |     |            |
|----------------|-----------|-----------|-----|------------|
| Time step      | 1         | 2         | ... | 105        |
| CPU cycles     | 137       | 137       | ... | 139        |
| Inputs         |           |           |     |            |
| In (DSP)       | 0         | 0         | ... | -644245094 |
| fc (DSP)       | 493921239 | 493921239 | ... | 493921239  |
| In             | 0         | 0         | ... | -0.3       |
| fc             | 0.23      | 0.23      | ... | 0.23       |
| Parameters     |           |           |     |            |
| V              | 1.1       |           |     |            |
| fmax           | 1000      |           |     |            |
| ts_fact        | 1         |           |     |            |
| method         | zoh       |           |     |            |
| Outputs        |           |           |     |            |
| Out            | 0         | 0         | ... | -0.329     |
| Exp. Out       | 0         | 0         | ... | -0.329     |
| Out (DSP)      | 0         | 0         | ... | -706485147 |
| Exp. Out (DSP) | 0         | 0         | ... | -706485964 |

| Test settings |                                            |
|---------------|--------------------------------------------|
| Tolerance Out | $\pm 2,3749\text{e-}05$ ( $\pm 51000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 137 |
| Max CPU cycles  | 139 |
| Avg CPU cycles  | 138 |



**Verification: AdaptivePT1 FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block AdaptivePT1.

| Test results   |           |           |     |            |
|----------------|-----------|-----------|-----|------------|
| Time step      | 1         | 2         | ... | 105        |
| CPU cycles     | 208       | 167       | ... | 167        |
| Inputs         |           |           |     |            |
| In (DSP)       | 0         | 0         | ... | -644245094 |
| fc (DSP)       | 493921239 | 493921239 | ... | 493921239  |
| In             | 0         | 0         | ... | -0.3       |
| fc             | 0.23      | 0.23      | ... | 0.23       |
| Parameters     |           |           |     |            |
| V              | 1.1       |           |     |            |
| fmax           | 1000      |           |     |            |
| ts_fact        | 1         |           |     |            |
| method         | zoh       |           |     |            |
| Outputs        |           |           |     |            |
| Out            | 0         | 0         | ... | -0.329     |
| Exp. Out       | 0         | 0         | ... | -0.329     |
| Out (DSP)      | 0         | 0         | ... | -706485147 |
| Exp. Out (DSP) | 0         | 0         | ... | -706485964 |

| Test settings |                                            |
|---------------|--------------------------------------------|
| Tolerance Out | $\pm 2,3749\text{e-}05$ ( $\pm 51000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 167 |
| Max CPU cycles  | 208 |
| Avg CPU cycles  | 167 |

**Verification: AdaptivePT1 FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block AdaptivePT1.

| Test results   |           |           |     |            |
|----------------|-----------|-----------|-----|------------|
| Time step      | 1         | 2         | ... | 105        |
| CPU cycles     | 239       | 239       | ... | 239        |
| Inputs         |           |           |     |            |
| In (DSP)       | 0         | 0         | ... | -644245094 |
| fc (DSP)       | 493921239 | 493921239 | ... | 493921239  |
| In             | 0         | 0         | ... | -0.3       |
| fc             | 0.23      | 0.23      | ... | 0.23       |
| Parameters     |           |           |     |            |
| V              | 1.1       |           |     |            |
| fmax           | 1000      |           |     |            |
| ts_fact        | 1         |           |     |            |
| method         | zoh       |           |     |            |
| Outputs        |           |           |     |            |
| Out            | 0         | 0         | ... | -0.329     |
| Exp. Out       | 0         | 0         | ... | -0.329     |
| Out (DSP)      | 0         | 0         | ... | -706485147 |
| Exp. Out (DSP) | 0         | 0         | ... | -706485964 |

| Test settings |                                            |
|---------------|--------------------------------------------|
| Tolerance Out | $\pm 2,3749\text{e-}05$ ( $\pm 51000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 239 |
| Max CPU cycles  | 239 |
| Avg CPU cycles  | 239 |

**Verification: AdaptivePT1 FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**


Inport test for Control block AdaptivePT1.

| Test results   |           |           |     |            |
|----------------|-----------|-----------|-----|------------|
| Time step      | 1         | 2         | ... | 105        |
| CPU cycles     | 990       | 990       | ... | 1004       |
| Inputs         |           |           |     |            |
| In (DSP)       | 0         | 0         | ... | -644245094 |
| fc (DSP)       | 493921239 | 493921239 | ... | 493921239  |
| In             | 0         | 0         | ... | -0.3       |
| fc             | 0.23      | 0.23      | ... | 0.23       |
| Parameters     |           |           |     |            |
| V              | 1.1       |           |     |            |
| fmax           | 1000      |           |     |            |
| ts_fact        | 1         |           |     |            |
| method         | zoh       |           |     |            |
| Outputs        |           |           |     |            |
| Out            | 0         | 0         | ... | -0.329     |
| Exp. Out       | 0         | 0         | ... | -0.329     |
| Out (DSP)      | 0         | 0         | ... | -706485147 |
| Exp. Out (DSP) | 0         | 0         | ... | -706485964 |

| Test settings |                                            |
|---------------|--------------------------------------------|
| Tolerance Out | $\pm 2,3749\text{e-}05$ ( $\pm 51000$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 990  |
| Max CPU cycles  | 1004 |
| Avg CPU cycles  | 995  |

## Block: D



D Controller:

$$G(s) = K_d s / (s / (2\pi f_c) + 1)$$

| Inports |                                                                                                                                   |
|---------|-----------------------------------------------------------------------------------------------------------------------------------|
| In      | Control error input                                                                                                               |
| D0      | Derivational value which is loaded during initialization. (Usually this input is connect to the In input.)                        |
| Enable  | Enable == 0: Deactivation of block; Out set to 0<br>Enable 0->1: Preload of derivational part<br>Enable == 1: Activation of block |

| Outports |               |
|----------|---------------|
| Out      | Control value |

| Mask Parameters |    |                                                                 |
|-----------------|----|-----------------------------------------------------------------|
| Name            | ID | Description                                                     |
| Kd              | 1  | Derivative Factor                                               |
| fc              | 2  | Cutoff frequency of realization low pass                        |
| ts_fact         | 3  | Multiplication factor of base sampling time (in integer format) |

### Description:

A rising flank at the *Enable* input will preload the derivational part with the value present on the *Init* input.

Transfer function (zero-order hold discretization method):

$$G(z) = K_d 2\pi f_c \frac{z - 1}{z - e^{-2\pi f_c T_s}}$$

**Developer note:** The source code of block *DLimit* is used.

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP16

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |
| D0                | int16 |
| Enable            | bool  |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |
| D0                | int32 |
| Enable            | bool  |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |
| D0                | float32 |
| Enable            | bool    |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |
| D0                | float64 |
| Enable            | bool    |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: D FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block D.

| Test results   |       |      |      |        |     |       |
|----------------|-------|------|------|--------|-----|-------|
| Time step      | 1     | 2    | 3    | 4      | ... | 201   |
| CPU cycles     | 77    | 77   | 77   | 125    | ... | 120   |
| Inputs         |       |      |      |        |     |       |
| In (DSP)       | 0     | 0    | 0    | 0      | ... | 0     |
| D0 (DSP)       | 655   | 655  | 655  | 655    | ... | 655   |
| Enable (DSP)   | 0     | 0    | 0    | 1      | ... | 1     |
| In             | 0     | 0    | 0    | 0      | ... | 0     |
| D0             | 0.02  | 0.02 | 0.02 | 0.02   | ... | 0.02  |
| Enable         | 0     | 0    | 0    | 1      | ... | 1     |
| Parameters     |       |      |      |        |     |       |
| Kd             | 0.003 |      |      |        |     |       |
| fc             | 200   |      |      |        |     |       |
| ts_fact        | 1     |      |      |        |     |       |
| Outputs        |       |      |      |        |     |       |
| Out            | 0     | 0    | 0    | -0.075 | ... | 0.002 |
| Exp. Out       | 0     | 0    | 0    | -0.075 | ... | 0.002 |
| Out (DSP)      | 0     | 0    | 0    | -2470  | ... | 61    |
| Exp. Out (DSP) | 0     | 0    | 0    | -2471  | ... | 58    |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 77  |
| Max CPU cycles  | 125 |
| Avg CPU cycles  | 119 |

**Test case: Conversion test****OK**

Conversion test for Control block D.

| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>b0d</b>                   | 0      | 26374  | 24822  | 17453  | ... | -31416 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block D.



| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26373 | -24822 | -17453 | ... | 31415  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23933 |
| <b>b0d</b>                   | 0      | 26373  | 24822  | 17453  | ... | -31415 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 1,0000e+00$ |
| Tolerance a0d  | $\pm 1,0000e+00$ |
| Tolerance b0d  | $\pm 1,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 2821  |
| Max CPU cycles  | 10490 |
| Avg CPU cycles  | 9335  |

**Verification: D FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block D.

| Test results   |       |      |      |        |     |       |
|----------------|-------|------|------|--------|-----|-------|
| Time step      | 1     | 2    | 3    | 4      | ... | 201   |
| CPU cycles     | 51    | 51   | 51   | 79     | ... | 77    |
| Inputs         |       |      |      |        |     |       |
| In (DSP)       | 0     | 0    | 0    | 0      | ... | 0     |
| D0 (DSP)       | 655   | 655  | 655  | 655    | ... | 655   |
| Enable (DSP)   | 0     | 0    | 0    | 1      | ... | 1     |
| In             | 0     | 0    | 0    | 0      | ... | 0     |
| D0             | 0.02  | 0.02 | 0.02 | 0.02   | ... | 0.02  |
| Enable         | 0     | 0    | 0    | 1      | ... | 1     |
| Parameters     |       |      |      |        |     |       |
| Kd             | 0.003 |      |      |        |     |       |
| fc             | 200   |      |      |        |     |       |
| ts_fact        | 1     |      |      |        |     |       |
| Outputs        |       |      |      |        |     |       |
| Out            | 0     | 0    | 0    | -0.075 | ... | 0.002 |
| Exp. Out       | 0     | 0    | 0    | -0.075 | ... | 0.002 |
| Out (DSP)      | 0     | 0    | 0    | -2470  | ... | 61    |
| Exp. Out (DSP) | 0     | 0    | 0    | -2471  | ... | 58    |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 51 |
| Max CPU cycles  | 79 |
| Avg CPU cycles  | 76 |

**Test case: Conversion test****OK**

Conversion test for Control block D.

| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>b0d</b>                   | 0      | 26374  | 24822  | 17453  | ... | -31416 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block D.

| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26373 | -24822 | -17453 | ... | 31415  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23933 |
| <b>b0d</b>                   | 0      | 26373  | 24822  | 17453  | ... | -31415 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 1,0000e+00$ |
| Tolerance a0d  | $\pm 1,0000e+00$ |
| Tolerance b0d  | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1363 |
| Max CPU cycles  | 6395 |
| Avg CPU cycles  | 5342 |

**Verification: D FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block D.

| Test results   |       |      |      |        |     |       |
|----------------|-------|------|------|--------|-----|-------|
| Time step      | 1     | 2    | 3    | 4      | ... | 201   |
| CPU cycles     | 73    | 73   | 73   | 131    | ... | 111   |
| Inputs         |       |      |      |        |     |       |
| In (DSP)       | 0     | 0    | 0    | 0      | ... | 0     |
| D0 (DSP)       | 655   | 655  | 655  | 655    | ... | 655   |
| Enable (DSP)   | 0     | 0    | 0    | 1      | ... | 1     |
| In             | 0     | 0    | 0    | 0      | ... | 0     |
| D0             | 0.02  | 0.02 | 0.02 | 0.02   | ... | 0.02  |
| Enable         | 0     | 0    | 0    | 1      | ... | 1     |
| Parameters     |       |      |      |        |     |       |
| Kd             | 0.003 |      |      |        |     |       |
| fc             | 200   |      |      |        |     |       |
| ts_fact        | 1     |      |      |        |     |       |
| Outputs        |       |      |      |        |     |       |
| Out            | 0     | 0    | 0    | -0.075 | ... | 0.002 |
| Exp. Out       | 0     | 0    | 0    | -0.075 | ... | 0.002 |
| Out (DSP)      | 0     | 0    | 0    | -2470  | ... | 61    |
| Exp. Out (DSP) | 0     | 0    | 0    | -2471  | ... | 58    |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 73  |
| Max CPU cycles  | 131 |
| Avg CPU cycles  | 110 |

**Test case: Conversion test****OK**

Conversion test for Control block D.

| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>b0d</b>                   | 0      | 26374  | 24822  | 17453  | ... | -31416 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block D.

| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26373 | -24822 | -17453 | ... | 31415  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23933 |
| <b>b0d</b>                   | 0      | 26373  | 24822  | 17453  | ... | -31415 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 1,0000e+00$ |
| Tolerance a0d  | $\pm 1,0000e+00$ |
| Tolerance b0d  | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1668 |
| Max CPU cycles  | 3699 |
| Avg CPU cycles  | 3272 |

**Verification: D FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block D.

| Test results   |       |      |      |        |     |       |
|----------------|-------|------|------|--------|-----|-------|
| Time step      | 1     | 2    | 3    | 4      | ... | 201   |
| CPU cycles     | 70    | 70   | 70   | 126    | ... | 114   |
| Inputs         |       |      |      |        |     |       |
| In (DSP)       | 0     | 0    | 0    | 0      | ... | 0     |
| D0 (DSP)       | 655   | 655  | 655  | 655    | ... | 655   |
| Enable (DSP)   | 0     | 0    | 0    | 1      | ... | 1     |
| In             | 0     | 0    | 0    | 0      | ... | 0     |
| D0             | 0.02  | 0.02 | 0.02 | 0.02   | ... | 0.02  |
| Enable         | 0     | 0    | 0    | 1      | ... | 1     |
| Parameters     |       |      |      |        |     |       |
| Kd             | 0.003 |      |      |        |     |       |
| fc             | 200   |      |      |        |     |       |
| ts_fact        | 1     |      |      |        |     |       |
| Outputs        |       |      |      |        |     |       |
| Out            | 0     | 0    | 0    | -0.075 | ... | 0.002 |
| Exp. Out       | 0     | 0    | 0    | -0.075 | ... | 0.002 |
| Out (DSP)      | 0     | 0    | 0    | -2470  | ... | 61    |
| Exp. Out (DSP) | 0     | 0    | 0    | -2471  | ... | 58    |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 70  |
| Max CPU cycles  | 126 |
| Avg CPU cycles  | 113 |

**Test case: Conversion test****OK**

Conversion test for Control block D.



| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>b0d</b>                   | 0      | 26374  | 24822  | 17453  | ... | -31416 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block D.

| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26373 | -24822 | -17453 | ... | 31415  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23933 |
| <b>b0d</b>                   | 0      | 26373  | 24822  | 17453  | ... | -31415 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 1,0000e+00$ |
| Tolerance a0d  | $\pm 1,0000e+00$ |
| Tolerance b0d  | $\pm 1,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 4309  |
| Max CPU cycles  | 17120 |
| Avg CPU cycles  | 15168 |

**Verification: D FiP16 CPU PIC32MX170F256**

Date of Test 2026-06-19  
Target controller PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block D.

| Test results   |       |      |      |        |     |       |
|----------------|-------|------|------|--------|-----|-------|
| Time step      | 1     | 2    | 3    | 4      | ... | 201   |
| CPU cycles     | 37    | 37   | 37   | 78     | ... | 73    |
| Inputs         |       |      |      |        |     |       |
| In (DSP)       | 0     | 0    | 0    | 0      | ... | 0     |
| D0 (DSP)       | 655   | 655  | 655  | 655    | ... | 655   |
| Enable (DSP)   | 0     | 0    | 0    | 1      | ... | 1     |
| In             | 0     | 0    | 0    | 0      | ... | 0     |
| D0             | 0.02  | 0.02 | 0.02 | 0.02   | ... | 0.02  |
| Enable         | 0     | 0    | 0    | 1      | ... | 1     |
| Parameters     |       |      |      |        |     |       |
| Kd             | 0.003 |      |      |        |     |       |
| fc             | 200   |      |      |        |     |       |
| ts_fact        | 1     |      |      |        |     |       |
| Outputs        |       |      |      |        |     |       |
| Out            | 0     | 0    | 0    | -0.075 | ... | 0.002 |
| Exp. Out       | 0     | 0    | 0    | -0.075 | ... | 0.002 |
| Out (DSP)      | 0     | 0    | 0    | -2470  | ... | 61    |
| Exp. Out (DSP) | 0     | 0    | 0    | -2471  | ... | 58    |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 37 |
| Max CPU cycles  | 78 |
| Avg CPU cycles  | 72 |

**Test case: Conversion test****OK**

Conversion test for Control block D.

| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>b0d</b>                   | 0      | 26374  | 24822  | 17453  | ... | -31416 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block D.

| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26373 | -24822 | -17453 | ... | 31415  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23933 |
| <b>b0d</b>                   | 0      | 26373  | 24822  | 17453  | ... | -31415 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 1,0000e+00$ |
| Tolerance a0d  | $\pm 1,0000e+00$ |
| Tolerance b0d  | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1688 |
| Max CPU cycles  | 5799 |
| Avg CPU cycles  | 5201 |

**Verification: D FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block D.

| Test results   |       |      |      |        |     |       |
|----------------|-------|------|------|--------|-----|-------|
| Time step      | 1     | 2    | 3    | 4      | ... | 201   |
| CPU cycles     | 97    | 79   | 79   | 124    | ... | 109   |
| Inputs         |       |      |      |        |     |       |
| In (DSP)       | 0     | 0    | 0    | 0      | ... | 0     |
| D0 (DSP)       | 655   | 655  | 655  | 655    | ... | 655   |
| Enable (DSP)   | 0     | 0    | 0    | 1      | ... | 1     |
| In             | 0     | 0    | 0    | 0      | ... | 0     |
| D0             | 0.02  | 0.02 | 0.02 | 0.02   | ... | 0.02  |
| Enable         | 0     | 0    | 0    | 1      | ... | 1     |
| Parameters     |       |      |      |        |     |       |
| Kd             | 0.003 |      |      |        |     |       |
| fc             | 200   |      |      |        |     |       |
| ts_fact        | 1     |      |      |        |     |       |
| Outputs        |       |      |      |        |     |       |
| Out            | 0     | 0    | 0    | -0.075 | ... | 0.002 |
| Exp. Out       | 0     | 0    | 0    | -0.075 | ... | 0.002 |
| Out (DSP)      | 0     | 0    | 0    | -2470  | ... | 61    |
| Exp. Out (DSP) | 0     | 0    | 0    | -2471  | ... | 58    |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 79  |
| Max CPU cycles  | 124 |
| Avg CPU cycles  | 108 |

**Test case: Conversion test****OK**

Conversion test for Control block D.

| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>b0d</b>                   | 0      | 26374  | 24822  | 17453  | ... | -31416 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block D.

| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26373 | -24822 | -17453 | ... | 31415  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23933 |
| <b>b0d</b>                   | 0      | 26373  | 24822  | 17453  | ... | -31415 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 1,0000e+00$ |
| Tolerance a0d  | $\pm 1,0000e+00$ |
| Tolerance b0d  | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1430 |
| Max CPU cycles  | 3258 |
| Avg CPU cycles  | 2900 |



**Verification: D FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block D.

| Test results   |       |      |      |        |     |       |
|----------------|-------|------|------|--------|-----|-------|
| Time step      | 1     | 2    | 3    | 4      | ... | 201   |
| CPU cycles     | 70    | 70   | 70   | 127    | ... | 122   |
| Inputs         |       |      |      |        |     |       |
| In (DSP)       | 0     | 0    | 0    | 0      | ... | 0     |
| D0 (DSP)       | 655   | 655  | 655  | 655    | ... | 655   |
| Enable (DSP)   | 0     | 0    | 0    | 1      | ... | 1     |
| In             | 0     | 0    | 0    | 0      | ... | 0     |
| D0             | 0.02  | 0.02 | 0.02 | 0.02   | ... | 0.02  |
| Enable         | 0     | 0    | 0    | 1      | ... | 1     |
| Parameters     |       |      |      |        |     |       |
| Kd             | 0.003 |      |      |        |     |       |
| fc             | 200   |      |      |        |     |       |
| ts_fact        | 1     |      |      |        |     |       |
| Outputs        |       |      |      |        |     |       |
| Out            | 0     | 0    | 0    | -0.075 | ... | 0.002 |
| Exp. Out       | 0     | 0    | 0    | -0.075 | ... | 0.002 |
| Out (DSP)      | 0     | 0    | 0    | -2470  | ... | 61    |
| Exp. Out (DSP) | 0     | 0    | 0    | -2471  | ... | 58    |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 70  |
| Max CPU cycles  | 127 |
| Avg CPU cycles  | 121 |

**Test case: Conversion test****OK**

Conversion test for Control block D.

| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>b0d</b>                   | 0      | 26374  | 24822  | 17453  | ... | -31416 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block D.

| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26373 | -24822 | -17453 | ... | 31415  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23933 |
| <b>b0d</b>                   | 0      | 26373  | 24822  | 17453  | ... | -31415 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 1,0000e+00$ |
| Tolerance a0d  | $\pm 1,0000e+00$ |
| Tolerance b0d  | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2028 |
| Max CPU cycles  | 8070 |
| Avg CPU cycles  | 7162 |

**Verification: D FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block D.

| Test results   |       |      |      |        |     |       |
|----------------|-------|------|------|--------|-----|-------|
| Time step      | 1     | 2    | 3    | 4      | ... | 201   |
| CPU cycles     | 52    | 52   | 52   | 95     | ... | 99    |
| Inputs         |       |      |      |        |     |       |
| In (DSP)       | 0     | 0    | 0    | 0      | ... | 0     |
| D0 (DSP)       | 655   | 655  | 655  | 655    | ... | 655   |
| Enable (DSP)   | 0     | 0    | 0    | 1      | ... | 1     |
| In             | 0     | 0    | 0    | 0      | ... | 0     |
| D0             | 0.02  | 0.02 | 0.02 | 0.02   | ... | 0.02  |
| Enable         | 0     | 0    | 0    | 1      | ... | 1     |
| Parameters     |       |      |      |        |     |       |
| Kd             | 0.003 |      |      |        |     |       |
| fc             | 200   |      |      |        |     |       |
| ts_fact        | 1     |      |      |        |     |       |
| Outputs        |       |      |      |        |     |       |
| Out            | 0     | 0    | 0    | -0.075 | ... | 0.002 |
| Exp. Out       | 0     | 0    | 0    | -0.075 | ... | 0.002 |
| Out (DSP)      | 0     | 0    | 0    | -2470  | ... | 61    |
| Exp. Out (DSP) | 0     | 0    | 0    | -2471  | ... | 58    |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 52 |
| Max CPU cycles  | 99 |
| Avg CPU cycles  | 98 |

**Test case: Conversion test****OK**

Conversion test for Control block D.

| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>b0d</b>                   | 0      | 26374  | 24822  | 17453  | ... | -31416 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block D.

| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26373 | -24822 | -17453 | ... | 31415  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23933 |
| <b>b0d</b>                   | 0      | 26373  | 24822  | 17453  | ... | -31415 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 1,0000e+00$ |
| Tolerance a0d  | $\pm 1,0000e+00$ |
| Tolerance b0d  | $\pm 1,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 6401  |
| Max CPU cycles  | 35059 |
| Avg CPU cycles  | 31162 |

**Verification: D FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block D.

| Test results   |          |          |     |          |
|----------------|----------|----------|-----|----------|
| Time step      | 1        | 2        | ... | 201      |
| CPU cycles     | 87       | 87       | ... | 252      |
| Inputs         |          |          |     |          |
| In (DSP)       | 0        | 0        | ... | 0        |
| D0 (DSP)       | 42949673 | 42949673 | ... | 42949673 |
| Enable (DSP)   | 0        | 0        | ... | 1        |
| In             | 0        | 0        | ... | 0        |
| D0             | 0.02     | 0.02     | ... | 0.02     |
| Enable         | 0        | 0        | ... | 1        |
| Parameters     |          |          |     |          |
| Kd             | 0.003    |          |     |          |
| fc             | 200      |          |     |          |
| ts_fact        | 1        |          |     |          |
| Outputs        |          |          |     |          |
| Out            | 0        | 0        | ... | 0.002    |
| Exp. Out       | 0        | 0        | ... | 0.002    |
| Out (DSP)      | 0        | 0        | ... | 3772137  |
| Exp. Out (DSP) | 0        | 0        | ... | 3772137  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 87  |
| Max CPU cycles  | 258 |
| Avg CPU cycles  | 249 |

**Test case: Conversion test****OK**

Conversion test for Control block D.

| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437568 | ... | 2058874161  |
| <b>a0d</b>                   | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>b0d</b>                   | 0           | 1728437568  | ... | -2058874161 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block D.



| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437632 | ... | 2058874240  |
| <b>a0d</b>                   | -2147483647 | -2128824832 | ... | -1568527872 |
| <b>b0d</b>                   | 0           | 1728437632  | ... | -2058874240 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 2,0000e+02$ |
| Tolerance a0d  | $\pm 2,0000e+02$ |
| Tolerance b0d  | $\pm 2,0000e+02$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 3469  |
| Max CPU cycles  | 11682 |
| Avg CPU cycles  | 10135 |

**Verification: D FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block D.

| Test results   |          |          |     |          |
|----------------|----------|----------|-----|----------|
| Time step      | 1        | 2        | ... | 201      |
| CPU cycles     | 53       | 53       | ... | 115      |
| Inputs         |          |          |     |          |
| In (DSP)       | 0        | 0        | ... | 0        |
| D0 (DSP)       | 42949673 | 42949673 | ... | 42949673 |
| Enable (DSP)   | 0        | 0        | ... | 1        |
| In             | 0        | 0        | ... | 0        |
| D0             | 0.02     | 0.02     | ... | 0.02     |
| Enable         | 0        | 0        | ... | 1        |
| Parameters     |          |          |     |          |
| Kd             | 0.003    |          |     |          |
| fc             | 200      |          |     |          |
| ts_fact        | 1        |          |     |          |
| Outputs        |          |          |     |          |
| Out            | 0        | 0        | ... | 0.002    |
| Exp. Out       | 0        | 0        | ... | 0.002    |
| Out (DSP)      | 0        | 0        | ... | 3772137  |
| Exp. Out (DSP) | 0        | 0        | ... | 3772137  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 53  |
| Max CPU cycles  | 119 |
| Avg CPU cycles  | 114 |

**Test case: Conversion test****OK**

Conversion test for Control block D.

| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437568 | ... | 2058874161  |
| <b>a0d</b>                   | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>b0d</b>                   | 0           | 1728437568  | ... | -2058874161 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block D.

| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437632 | ... | 2058874240  |
| <b>a0d</b>                   | -2147483647 | -2128824832 | ... | -1568527872 |
| <b>b0d</b>                   | 0           | 1728437632  | ... | -2058874240 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 2,0000e+02$ |
| Tolerance a0d  | $\pm 2,0000e+02$ |
| Tolerance b0d  | $\pm 2,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1431 |
| Max CPU cycles  | 5085 |
| Avg CPU cycles  | 4311 |

**Verification: D FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block D.

| Test results   |          |          |     |          |
|----------------|----------|----------|-----|----------|
| Time step      | 1        | 2        | ... | 201      |
| CPU cycles     | 86       | 86       | ... | 151      |
| Inputs         |          |          |     |          |
| In (DSP)       | 0        | 0        | ... | 0        |
| D0 (DSP)       | 42949673 | 42949673 | ... | 42949673 |
| Enable (DSP)   | 0        | 0        | ... | 1        |
| In             | 0        | 0        | ... | 0        |
| D0             | 0.02     | 0.02     | ... | 0.02     |
| Enable         | 0        | 0        | ... | 1        |
| Parameters     |          |          |     |          |
| Kd             | 0.003    |          |     |          |
| fc             | 200      |          |     |          |
| ts_fact        | 1        |          |     |          |
| Outputs        |          |          |     |          |
| Out            | 0        | 0        | ... | 0.002    |
| Exp. Out       | 0        | 0        | ... | 0.002    |
| Out (DSP)      | 0        | 0        | ... | 3772137  |
| Exp. Out (DSP) | 0        | 0        | ... | 3772137  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 86  |
| Max CPU cycles  | 176 |
| Avg CPU cycles  | 150 |

**Test case: Conversion test****OK**

Conversion test for Control block D.

| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437568 | ... | 2058874161  |
| <b>a0d</b>                   | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>b0d</b>                   | 0           | 1728437568  | ... | -2058874161 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block D.

| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437632 | ... | 2058874240  |
| <b>a0d</b>                   | -2147483647 | -2128824832 | ... | -1568527872 |
| <b>b0d</b>                   | 0           | 1728437632  | ... | -2058874240 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 2,0000e+02$ |
| Tolerance a0d  | $\pm 2,0000e+02$ |
| Tolerance b0d  | $\pm 2,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2520 |
| Max CPU cycles  | 4518 |
| Avg CPU cycles  | 4141 |

**Verification: D FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block D.

| Test results   |          |          |     |          |
|----------------|----------|----------|-----|----------|
| Time step      | 1        | 2        | ... | 201      |
| CPU cycles     | 84       | 84       | ... | 371      |
| Inputs         |          |          |     |          |
| In (DSP)       | 0        | 0        | ... | 0        |
| D0 (DSP)       | 42949673 | 42949673 | ... | 42949673 |
| Enable (DSP)   | 0        | 0        | ... | 1        |
| In             | 0        | 0        | ... | 0        |
| D0             | 0.02     | 0.02     | ... | 0.02     |
| Enable         | 0        | 0        | ... | 1        |
| Parameters     |          |          |     |          |
| Kd             | 0.003    |          |     |          |
| fc             | 200      |          |     |          |
| ts_fact        | 1        |          |     |          |
| Outputs        |          |          |     |          |
| Out            | 0        | 0        | ... | 0.002    |
| Exp. Out       | 0        | 0        | ... | 0.002    |
| Out (DSP)      | 0        | 0        | ... | 3772137  |
| Exp. Out (DSP) | 0        | 0        | ... | 3772137  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 84  |
| Max CPU cycles  | 430 |
| Avg CPU cycles  | 369 |

**Test case: Conversion test****OK**

Conversion test for Control block D.



| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437568 | ... | 2058874161  |
| <b>a0d</b>                   | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>b0d</b>                   | 0           | 1728437568  | ... | -2058874161 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block D.

| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437632 | ... | 2058874240  |
| <b>a0d</b>                   | -2147483647 | -2128824832 | ... | -1568527872 |
| <b>b0d</b>                   | 0           | 1728437632  | ... | -2058874240 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 2,0000e+02$ |
| Tolerance a0d  | $\pm 2,0000e+02$ |
| Tolerance b0d  | $\pm 2,0000e+02$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 7826  |
| Max CPU cycles  | 21007 |
| Avg CPU cycles  | 18923 |

**Verification: D FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block D.

| Test results   |          |          |     |          |
|----------------|----------|----------|-----|----------|
| Time step      | 1        | 2        | ... | 201      |
| CPU cycles     | 37       | 37       | ... | 96       |
| Inputs         |          |          |     |          |
| In (DSP)       | 0        | 0        | ... | 0        |
| D0 (DSP)       | 42949673 | 42949673 | ... | 42949673 |
| Enable (DSP)   | 0        | 0        | ... | 1        |
| In             | 0        | 0        | ... | 0        |
| D0             | 0.02     | 0.02     | ... | 0.02     |
| Enable         | 0        | 0        | ... | 1        |
| Parameters     |          |          |     |          |
| Kd             | 0.003    |          |     |          |
| fc             | 200      |          |     |          |
| ts_fact        | 1        |          |     |          |
| Outputs        |          |          |     |          |
| Out            | 0        | 0        | ... | 0.002    |
| Exp. Out       | 0        | 0        | ... | 0.002    |
| Out (DSP)      | 0        | 0        | ... | 3772137  |
| Exp. Out (DSP) | 0        | 0        | ... | 3772137  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 37  |
| Max CPU cycles  | 101 |
| Avg CPU cycles  | 95  |

**Test case: Conversion test****OK**

Conversion test for Control block D.

| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437568 | ... | 2058874161  |
| <b>a0d</b>                   | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>b0d</b>                   | 0           | 1728437568  | ... | -2058874161 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block D.

| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437632 | ... | 2058874240  |
| <b>a0d</b>                   | -2147483647 | -2128824832 | ... | -1568527872 |
| <b>b0d</b>                   | 0           | 1728437632  | ... | -2058874240 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 2,0000e+02$ |
| Tolerance a0d  | $\pm 2,0000e+02$ |
| Tolerance b0d  | $\pm 2,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2913 |
| Max CPU cycles  | 7307 |
| Avg CPU cycles  | 6491 |

**Verification: D FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block D.

| Test results   |          |          |     |          |
|----------------|----------|----------|-----|----------|
| Time step      | 1        | 2        | ... | 201      |
| CPU cycles     | 103      | 93       | ... | 151      |
| Inputs         |          |          |     |          |
| In (DSP)       | 0        | 0        | ... | 0        |
| D0 (DSP)       | 42949673 | 42949673 | ... | 42949673 |
| Enable (DSP)   | 0        | 0        | ... | 1        |
| In             | 0        | 0        | ... | 0        |
| D0             | 0.02     | 0.02     | ... | 0.02     |
| Enable         | 0        | 0        | ... | 1        |
| Parameters     |          |          |     |          |
| Kd             | 0.003    |          |     |          |
| fc             | 200      |          |     |          |
| ts_fact        | 1        |          |     |          |
| Outputs        |          |          |     |          |
| Out            | 0        | 0        | ... | 0.002    |
| Exp. Out       | 0        | 0        | ... | 0.002    |
| Out (DSP)      | 0        | 0        | ... | 3772137  |
| Exp. Out (DSP) | 0        | 0        | ... | 3772137  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 93  |
| Max CPU cycles  | 191 |
| Avg CPU cycles  | 150 |

**Test case: Conversion test****OK**

Conversion test for Control block D.

| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437568 | ... | 2058874161  |
| <b>a0d</b>                   | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>b0d</b>                   | 0           | 1728437568  | ... | -2058874161 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block D.

| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437632 | ... | 2058874240  |
| <b>a0d</b>                   | -2147483647 | -2128824832 | ... | -1568527872 |
| <b>b0d</b>                   | 0           | 1728437632  | ... | -2058874240 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 2,0000e+02$ |
| Tolerance a0d  | $\pm 2,0000e+02$ |
| Tolerance b0d  | $\pm 2,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2080 |
| Max CPU cycles  | 3936 |
| Avg CPU cycles  | 3577 |



**Verification: D FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block D.

| Test results   |          |          |     |          |
|----------------|----------|----------|-----|----------|
| Time step      | 1        | 2        | ... | 201      |
| CPU cycles     | 71       | 71       | ... | 227      |
| Inputs         |          |          |     |          |
| In (DSP)       | 0        | 0        | ... | 0        |
| D0 (DSP)       | 42949673 | 42949673 | ... | 42949673 |
| Enable (DSP)   | 0        | 0        | ... | 1        |
| In             | 0        | 0        | ... | 0        |
| D0             | 0.02     | 0.02     | ... | 0.02     |
| Enable         | 0        | 0        | ... | 1        |
| Parameters     |          |          |     |          |
| Kd             | 0.003    |          |     |          |
| fc             | 200      |          |     |          |
| ts_fact        | 1        |          |     |          |
| Outputs        |          |          |     |          |
| Out            | 0        | 0        | ... | 0.002    |
| Exp. Out       | 0        | 0        | ... | 0.002    |
| Out (DSP)      | 0        | 0        | ... | 3772137  |
| Exp. Out (DSP) | 0        | 0        | ... | 3772137  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 71  |
| Max CPU cycles  | 231 |
| Avg CPU cycles  | 224 |

**Test case: Conversion test****OK**

Conversion test for Control block D.

| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437568 | ... | 2058874161  |
| <b>a0d</b>                   | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>b0d</b>                   | 0           | 1728437568  | ... | -2058874161 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block D.

| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437632 | ... | 2058874240  |
| <b>a0d</b>                   | -2147483647 | -2128824832 | ... | -1568527872 |
| <b>b0d</b>                   | 0           | 1728437632  | ... | -2058874240 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 2,0000e+02$ |
| Tolerance a0d  | $\pm 2,0000e+02$ |
| Tolerance b0d  | $\pm 2,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2457 |
| Max CPU cycles  | 8937 |
| Avg CPU cycles  | 7718 |

**Verification: D FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block D.

| Test results   |          |          |     |          |
|----------------|----------|----------|-----|----------|
| Time step      | 1        | 2        | ... | 201      |
| CPU cycles     | 70       | 70       | ... | 741      |
| Inputs         |          |          |     |          |
| In (DSP)       | 0        | 0        | ... | 0        |
| D0 (DSP)       | 42949673 | 42949673 | ... | 42949673 |
| Enable (DSP)   | 0        | 0        | ... | 1        |
| In             | 0        | 0        | ... | 0        |
| D0             | 0.02     | 0.02     | ... | 0.02     |
| Enable         | 0        | 0        | ... | 1        |
| Parameters     |          |          |     |          |
| Kd             | 0.003    |          |     |          |
| fc             | 200      |          |     |          |
| ts_fact        | 1        |          |     |          |
| Outputs        |          |          |     |          |
| Out            | 0        | 0        | ... | 0.002    |
| Exp. Out       | 0        | 0        | ... | 0.002    |
| Out (DSP)      | 0        | 0        | ... | 3772137  |
| Exp. Out (DSP) | 0        | 0        | ... | 3772137  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 70  |
| Max CPU cycles  | 750 |
| Avg CPU cycles  | 733 |

**Test case: Conversion test****OK**

Conversion test for Control block D.

| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437568 | ... | 2058874161  |
| <b>a0d</b>                   | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>b0d</b>                   | 0           | 1728437568  | ... | -2058874161 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block D.

| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437632 | ... | 2058874240  |
| <b>a0d</b>                   | -2147483647 | -2128824832 | ... | -1568527872 |
| <b>b0d</b>                   | 0           | 1728437632  | ... | -2058874240 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 2,0000e+02$ |
| Tolerance a0d  | $\pm 2,0000e+02$ |
| Tolerance b0d  | $\pm 2,0000e+02$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 7460  |
| Max CPU cycles  | 36680 |
| Avg CPU cycles  | 31565 |

**Verification: D Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block D.

| Test results   |       |      |     |       |
|----------------|-------|------|-----|-------|
| Time step      | 1     | 2    | ... | 201   |
| CPU cycles     | 81    | 81   | ... | 118   |
| Inputs         |       |      |     |       |
| In (DSP)       | 0     | 0    | ... | 0     |
| D0 (DSP)       | 0.02  | 0.02 | ... | 0.02  |
| Enable (DSP)   | 0     | 0    | ... | 1     |
| In             | 0     | 0    | ... | 0     |
| D0             | 0.02  | 0.02 | ... | 0.02  |
| Enable         | 0     | 0    | ... | 1     |
| Parameters     |       |      |     |       |
| Kd             | 0.003 |      |     |       |
| fc             | 200   |      |     |       |
| ts_fact        | 1     |      |     |       |
| Outputs        |       |      |     |       |
| Out            | 0     | 0    | ... | 0.002 |
| Exp. Out       | 0     | 0    | ... | 0.002 |
| Out (DSP)      | 0     | 0    | ... | 0.002 |
| Exp. Out (DSP) | 0     | 0    | ... | 0.002 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 9,3132e-06$ ( $\pm 20000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 81  |
| Max CPU cycles  | 123 |
| Avg CPU cycles  | 117 |

**Test case: Conversion test****OK**

Conversion test for Control block D.

| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.927  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.927 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 0,0000e+00$ |
| Tolerance a0d | $\pm 1,0000e-15$ |
| Tolerance b0d | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block D.

| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.928  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.928 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |



| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 3,0000e-03$ |
| Tolerance a0d | $\pm 1,0000e-07$ |
| Tolerance b0d | $\pm 3,0000e-03$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2140 |
| Max CPU cycles  | 2483 |
| Avg CPU cycles  | 2463 |

**Verification: D Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block D.

| Test results   |       |      |     |       |
|----------------|-------|------|-----|-------|
| Time step      | 1     | 2    | ... | 201   |
| CPU cycles     | 45    | 45   | ... | 87    |
| Inputs         |       |      |     |       |
| In (DSP)       | 0     | 0    | ... | 0     |
| D0 (DSP)       | 0.02  | 0.02 | ... | 0.02  |
| Enable (DSP)   | 0     | 0    | ... | 1     |
| In             | 0     | 0    | ... | 0     |
| D0             | 0.02  | 0.02 | ... | 0.02  |
| Enable         | 0     | 0    | ... | 1     |
| Parameters     |       |      |     |       |
| Kd             | 0.003 |      |     |       |
| fc             | 200   |      |     |       |
| ts_fact        | 1     |      |     |       |
| Outputs        |       |      |     |       |
| Out            | 0     | 0    | ... | 0.002 |
| Exp. Out       | 0     | 0    | ... | 0.002 |
| Out (DSP)      | 0     | 0    | ... | 0.002 |
| Exp. Out (DSP) | 0     | 0    | ... | 0.002 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 9,3132e-06$ ( $\pm 20000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 45 |
| Max CPU cycles  | 91 |
| Avg CPU cycles  | 86 |

**Test case: Conversion test****OK**

Conversion test for Control block D.

| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.927  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.927 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 0,0000e+00$ |
| Tolerance a0d | $\pm 1,0000e-15$ |
| Tolerance b0d | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block D.

| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.928  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.928 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 3,0000e-03$ |
| Tolerance a0d | $\pm 1,0000e-07$ |
| Tolerance b0d | $\pm 3,0000e-03$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1009 |
| Max CPU cycles  | 1053 |
| Avg CPU cycles  | 1051 |

**Verification: D Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block D.

| Test results   |       |      |     |       |
|----------------|-------|------|-----|-------|
| Time step      | 1     | 2    | ... | 201   |
| CPU cycles     | 73    | 73   | ... | 118   |
| Inputs         |       |      |     |       |
| In (DSP)       | 0     | 0    | ... | 0     |
| D0 (DSP)       | 0.02  | 0.02 | ... | 0.02  |
| Enable (DSP)   | 0     | 0    | ... | 1     |
| In             | 0     | 0    | ... | 0     |
| D0             | 0.02  | 0.02 | ... | 0.02  |
| Enable         | 0     | 0    | ... | 1     |
| Parameters     |       |      |     |       |
| Kd             | 0.003 |      |     |       |
| fc             | 200   |      |     |       |
| ts_fact        | 1     |      |     |       |
| Outputs        |       |      |     |       |
| Out            | 0     | 0    | ... | 0.002 |
| Exp. Out       | 0     | 0    | ... | 0.002 |
| Out (DSP)      | 0     | 0    | ... | 0.002 |
| Exp. Out (DSP) | 0     | 0    | ... | 0.002 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 9,3132e-06$ ( $\pm 20000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 73  |
| Max CPU cycles  | 135 |
| Avg CPU cycles  | 117 |

**Test case: Conversion test****OK**

Conversion test for Control block D.

| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.927  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.927 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 0,0000e+00$ |
| Tolerance a0d | $\pm 1,0000e-15$ |
| Tolerance b0d | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block D.

| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.928  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.928 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 3,0000e-03$ |
| Tolerance a0d | $\pm 1,0000e-07$ |
| Tolerance b0d | $\pm 3,0000e-03$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1172 |
| Max CPU cycles  | 1250 |
| Avg CPU cycles  | 1243 |

**Verification: D Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block D.

| Test results   |       |      |     |       |
|----------------|-------|------|-----|-------|
| Time step      | 1     | 2    | ... | 201   |
| CPU cycles     | 77    | 77   | ... | 870   |
| Inputs         |       |      |     |       |
| In (DSP)       | 0     | 0    | ... | 0     |
| D0 (DSP)       | 0.02  | 0.02 | ... | 0.02  |
| Enable (DSP)   | 0     | 0    | ... | 1     |
| In             | 0     | 0    | ... | 0     |
| D0             | 0.02  | 0.02 | ... | 0.02  |
| Enable         | 0     | 0    | ... | 1     |
| Parameters     |       |      |     |       |
| Kd             | 0.003 |      |     |       |
| fc             | 200   |      |     |       |
| ts_fact        | 1     |      |     |       |
| Outputs        |       |      |     |       |
| Out            | 0     | 0    | ... | 0.002 |
| Exp. Out       | 0     | 0    | ... | 0.002 |
| Out (DSP)      | 0     | 0    | ... | 0.002 |
| Exp. Out (DSP) | 0     | 0    | ... | 0.002 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 9,3132e-06$ ( $\pm 20000$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 77   |
| Max CPU cycles  | 1034 |
| Avg CPU cycles  | 927  |

**Test case: Conversion test****OK**

Conversion test for Control block D.



| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.927  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.927 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 0,0000e+00$ |
| Tolerance a0d | $\pm 1,0000e-15$ |
| Tolerance b0d | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block D.

| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.928  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.928 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 3,0000e-03$ |
| Tolerance a0d | $\pm 1,0000e-07$ |
| Tolerance b0d | $\pm 3,0000e-03$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2958 |
| Max CPU cycles  | 5975 |
| Avg CPU cycles  | 5801 |

**Verification: D Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block D.

| Test results   |       |      |     |       |
|----------------|-------|------|-----|-------|
| Time step      | 1     | 2    | ... | 201   |
| CPU cycles     | 63    | 63   | ... | 343   |
| Inputs         |       |      |     |       |
| In (DSP)       | 0     | 0    | ... | 0     |
| D0 (DSP)       | 0.02  | 0.02 | ... | 0.02  |
| Enable (DSP)   | 0     | 0    | ... | 1     |
| In             | 0     | 0    | ... | 0     |
| D0             | 0.02  | 0.02 | ... | 0.02  |
| Enable         | 0     | 0    | ... | 1     |
| Parameters     |       |      |     |       |
| Kd             | 0.003 |      |     |       |
| fc             | 200   |      |     |       |
| ts_fact        | 1     |      |     |       |
| Outputs        |       |      |     |       |
| Out            | 0     | 0    | ... | 0.002 |
| Exp. Out       | 0     | 0    | ... | 0.002 |
| Out (DSP)      | 0     | 0    | ... | 0.002 |
| Exp. Out (DSP) | 0     | 0    | ... | 0.002 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 9,3132e-06$ ( $\pm 20000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 63  |
| Max CPU cycles  | 433 |
| Avg CPU cycles  | 369 |

**Test case: Conversion test****OK**

Conversion test for Control block D.

| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.927  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.927 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 0,0000e+00$ |
| Tolerance a0d | $\pm 1,0000e-15$ |
| Tolerance b0d | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block D.

| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.928  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.928 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 3,0000e-03$ |
| Tolerance a0d | $\pm 1,0000e-07$ |
| Tolerance b0d | $\pm 3,0000e-03$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 964  |
| Max CPU cycles  | 1208 |
| Avg CPU cycles  | 1195 |

**Verification: D Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block D.

| Test results   |       |      |     |       |
|----------------|-------|------|-----|-------|
| Time step      | 1     | 2    | ... | 201   |
| CPU cycles     | 81    | 64   | ... | 106   |
| Inputs         |       |      |     |       |
| In (DSP)       | 0     | 0    | ... | 0     |
| D0 (DSP)       | 0.02  | 0.02 | ... | 0.02  |
| Enable (DSP)   | 0     | 0    | ... | 1     |
| In             | 0     | 0    | ... | 0     |
| D0             | 0.02  | 0.02 | ... | 0.02  |
| Enable         | 0     | 0    | ... | 1     |
| Parameters     |       |      |     |       |
| Kd             | 0.003 |      |     |       |
| fc             | 200   |      |     |       |
| ts_fact        | 1     |      |     |       |
| Outputs        |       |      |     |       |
| Out            | 0     | 0    | ... | 0.002 |
| Exp. Out       | 0     | 0    | ... | 0.002 |
| Out (DSP)      | 0     | 0    | ... | 0.002 |
| Exp. Out (DSP) | 0     | 0    | ... | 0.002 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 9,3132e-06$ ( $\pm 20000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 64  |
| Max CPU cycles  | 128 |
| Avg CPU cycles  | 105 |

**Test case: Conversion test****OK**

Conversion test for Control block D.

| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.927  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.927 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 0,0000e+00$ |
| Tolerance a0d | $\pm 1,0000e-15$ |
| Tolerance b0d | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block D.

| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.928  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.928 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 3,0000e-03$ |
| Tolerance a0d | $\pm 1,0000e-07$ |
| Tolerance b0d | $\pm 3,0000e-03$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1051 |
| Max CPU cycles  | 1151 |
| Avg CPU cycles  | 1055 |



**Verification: D Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block D.

| Test results   |       |      |     |       |
|----------------|-------|------|-----|-------|
| Time step      | 1     | 2    | ... | 201   |
| CPU cycles     | 74    | 74   | ... | 123   |
| Inputs         |       |      |     |       |
| In (DSP)       | 0     | 0    | ... | 0     |
| D0 (DSP)       | 0.02  | 0.02 | ... | 0.02  |
| Enable (DSP)   | 0     | 0    | ... | 1     |
| In             | 0     | 0    | ... | 0     |
| D0             | 0.02  | 0.02 | ... | 0.02  |
| Enable         | 0     | 0    | ... | 1     |
| Parameters     |       |      |     |       |
| Kd             | 0.003 |      |     |       |
| fc             | 200   |      |     |       |
| ts_fact        | 1     |      |     |       |
| Outputs        |       |      |     |       |
| Out            | 0     | 0    | ... | 0.002 |
| Exp. Out       | 0     | 0    | ... | 0.002 |
| Out (DSP)      | 0     | 0    | ... | 0.002 |
| Exp. Out (DSP) | 0     | 0    | ... | 0.002 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 9,3132e-06$ ( $\pm 20000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 74  |
| Max CPU cycles  | 124 |
| Avg CPU cycles  | 122 |

**Test case: Conversion test****OK**

Conversion test for Control block D.

| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.927  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.927 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 0,0000e+00$ |
| Tolerance a0d | $\pm 1,0000e-15$ |
| Tolerance b0d | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block D.

| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.928  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.928 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 3,0000e-03$ |
| Tolerance a0d | $\pm 1,0000e-07$ |
| Tolerance b0d | $\pm 3,0000e-03$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1571 |
| Max CPU cycles  | 1848 |
| Avg CPU cycles  | 1830 |

**Verification: D Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block D.

| Test results   |       |      |     |       |
|----------------|-------|------|-----|-------|
| Time step      | 1     | 2    | ... | 201   |
| CPU cycles     | 63    | 63   | ... | 937   |
| Inputs         |       |      |     |       |
| In (DSP)       | 0     | 0    | ... | 0     |
| D0 (DSP)       | 0.02  | 0.02 | ... | 0.02  |
| Enable (DSP)   | 0     | 0    | ... | 1     |
| In             | 0     | 0    | ... | 0     |
| D0             | 0.02  | 0.02 | ... | 0.02  |
| Enable         | 0     | 0    | ... | 1     |
| Parameters     |       |      |     |       |
| Kd             | 0.003 |      |     |       |
| fc             | 200   |      |     |       |
| ts_fact        | 1     |      |     |       |
| Outputs        |       |      |     |       |
| Out            | 0     | 0    | ... | 0.002 |
| Exp. Out       | 0     | 0    | ... | 0.002 |
| Out (DSP)      | 0     | 0    | ... | 0.002 |
| Exp. Out (DSP) | 0     | 0    | ... | 0.002 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 9,3132e-06$ ( $\pm 20000$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 63   |
| Max CPU cycles  | 1274 |
| Avg CPU cycles  | 1005 |

**Test case: Conversion test****OK**

Conversion test for Control block D.

| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.927  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.927 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 0,0000e+00$ |
| Tolerance a0d | $\pm 1,0000e-15$ |
| Tolerance b0d | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block D.

| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.928  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.928 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 3,0000e-03$ |
| Tolerance a0d | $\pm 1,0000e-07$ |
| Tolerance b0d | $\pm 3,0000e-03$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3639 |
| Max CPU cycles  | 7392 |
| Avg CPU cycles  | 7022 |

## Block: Delay



Output delay by one sample time interval.

| Inports |             |
|---------|-------------|
| In      | Input In(k) |

| Outports |                       |
|----------|-----------------------|
| Out      | Output Out(k)=In(k-1) |

| Mask Parameters |    |                                                                 |
|-----------------|----|-----------------------------------------------------------------|
| Name            | ID | Description                                                     |
| ts_fact         | 1  | Multiplication factor of base sampling time (in integer format) |

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>Bool</b>    | Boolean Integration                  |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: Bool

Boolean Integration

| Inports Data Type |      |
|-------------------|------|
| In                | bool |

| Outports Data Type |      |
|--------------------|------|
| Out                | bool |

### Implementation: FiP16

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |



**Verification: Delay FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block Delay.

| Test results   |    |       |       |       |     |    |
|----------------|----|-------|-------|-------|-----|----|
| Time step      | 1  | 2     | 3     | 4     | ... | 18 |
| CPU cycles     | 56 | 56    | 56    | 56    | ... | 56 |
| Inputs         |    |       |       |       |     |    |
| In (DSP)       | 0  | 32767 | 32767 | 32767 | ... | 0  |
| In             | 0  | 1     | 1     | 1.1   | ... | 0  |
| Parameters     |    |       |       |       |     |    |
| ts_fact        | 1  |       |       |       |     |    |
| Outputs        |    |       |       |       |     |    |
| Out            | 0  | 0     | 1     | 1     | ... | 0  |
| Exp. Out       | 0  | 0     | 1     | 1     | ... | 0  |
| Out (DSP)      | 0  | 0     | 32767 | 32767 | ... | 0  |
| Exp. Out (DSP) | 0  | 0     | 32767 | 32767 | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 56 |
| Avg CPU cycles  | 56 |

## Verification: Delay FiP16 CPU TM4C123GH6

Date of Test 2026-06-19  
Target controller TM4C123GH6

### Test case: Inport test

OK

Inport test for Control block Delay.

| Test results   |    |       |       |       |     |    |
|----------------|----|-------|-------|-------|-----|----|
| Time step      | 1  | 2     | 3     | 4     | ... | 18 |
| CPU cycles     | 25 | 25    | 25    | 25    | ... | 25 |
| Inputs         |    |       |       |       |     |    |
| In (DSP)       | 0  | 32767 | 32767 | 32767 | ... | 0  |
| In             | 0  | 1     | 1     | 1.1   | ... | 0  |
| Parameters     |    |       |       |       |     |    |
| ts_fact        | 1  |       |       |       |     |    |
| Outputs        |    |       |       |       |     |    |
| Out            | 0  | 0     | 1     | 1     | ... | 0  |
| Exp. Out       | 0  | 0     | 1     | 1     | ... | 0  |
| Out (DSP)      | 0  | 0     | 32767 | 32767 | ... | 0  |
| Exp. Out (DSP) | 0  | 0     | 32767 | 32767 | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 25 |
| Max CPU cycles  | 25 |
| Avg CPU cycles  | 25 |

**Verification: Delay FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block Delay.

| Test results   |    |       |       |       |     |    |
|----------------|----|-------|-------|-------|-----|----|
| Time step      | 1  | 2     | 3     | 4     | ... | 18 |
| CPU cycles     | 61 | 61    | 61    | 61    | ... | 61 |
| Inputs         |    |       |       |       |     |    |
| In (DSP)       | 0  | 32767 | 32767 | 32767 | ... | 0  |
| In             | 0  | 1     | 1     | 1.1   | ... | 0  |
| Parameters     |    |       |       |       |     |    |
| ts_fact        | 1  |       |       |       |     |    |
| Outputs        |    |       |       |       |     |    |
| Out            | 0  | 0     | 1     | 1     | ... | 0  |
| Exp. Out       | 0  | 0     | 1     | 1     | ... | 0  |
| Out (DSP)      | 0  | 0     | 32767 | 32767 | ... | 0  |
| Exp. Out (DSP) | 0  | 0     | 32767 | 32767 | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 61 |
| Max CPU cycles  | 61 |
| Avg CPU cycles  | 61 |

**Verification: Delay FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block Delay.

| Test results   |    |       |       |       |     |    |
|----------------|----|-------|-------|-------|-----|----|
| Time step      | 1  | 2     | 3     | 4     | ... | 18 |
| CPU cycles     | 51 | 51    | 51    | 51    | ... | 51 |
| Inputs         |    |       |       |       |     |    |
| In (DSP)       | 0  | 32767 | 32767 | 32767 | ... | 0  |
| In             | 0  | 1     | 1     | 1.1   | ... | 0  |
| Parameters     |    |       |       |       |     |    |
| ts_fact        | 1  |       |       |       |     |    |
| Outputs        |    |       |       |       |     |    |
| Out            | 0  | 0     | 1     | 1     | ... | 0  |
| Exp. Out       | 0  | 0     | 1     | 1     | ... | 0  |
| Out (DSP)      | 0  | 0     | 32767 | 32767 | ... | 0  |
| Exp. Out (DSP) | 0  | 0     | 32767 | 32767 | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 51 |
| Max CPU cycles  | 51 |
| Avg CPU cycles  | 51 |

**Verification: Delay FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block Delay.

| Test results   |    |       |       |       |     |    |
|----------------|----|-------|-------|-------|-----|----|
| Time step      | 1  | 2     | 3     | 4     | ... | 18 |
| CPU cycles     | 30 | 30    | 30    | 30    | ... | 30 |
| Inputs         |    |       |       |       |     |    |
| In (DSP)       | 0  | 32767 | 32767 | 32767 | ... | 0  |
| In             | 0  | 1     | 1     | 1.1   | ... | 0  |
| Parameters     |    |       |       |       |     |    |
| ts_fact        | 1  |       |       |       |     |    |
| Outputs        |    |       |       |       |     |    |
| Out            | 0  | 0     | 1     | 1     | ... | 0  |
| Exp. Out       | 0  | 0     | 1     | 1     | ... | 0  |
| Out (DSP)      | 0  | 0     | 32767 | 32767 | ... | 0  |
| Exp. Out (DSP) | 0  | 0     | 32767 | 32767 | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 30 |
| Max CPU cycles  | 30 |
| Avg CPU cycles  | 30 |

**Verification: Delay FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block Delay.

| Test results   |    |       |       |       |     |    |
|----------------|----|-------|-------|-------|-----|----|
| Time step      | 1  | 2     | 3     | 4     | ... | 18 |
| CPU cycles     | 65 | 54    | 54    | 54    | ... | 54 |
| Inputs         |    |       |       |       |     |    |
| In (DSP)       | 0  | 32767 | 32767 | 32767 | ... | 0  |
| In             | 0  | 1     | 1     | 1.1   | ... | 0  |
| Parameters     |    |       |       |       |     |    |
| ts_fact        | 1  |       |       |       |     |    |
| Outputs        |    |       |       |       |     |    |
| Out            | 0  | 0     | 1     | 1     | ... | 0  |
| Exp. Out       | 0  | 0     | 1     | 1     | ... | 0  |
| Out (DSP)      | 0  | 0     | 32767 | 32767 | ... | 0  |
| Exp. Out (DSP) | 0  | 0     | 32767 | 32767 | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 54 |
| Max CPU cycles  | 65 |
| Avg CPU cycles  | 54 |

**Verification: Delay FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block Delay.

| Test results   |    |       |       |       |     |    |
|----------------|----|-------|-------|-------|-----|----|
| Time step      | 1  | 2     | 3     | 4     | ... | 18 |
| CPU cycles     | 43 | 43    | 43    | 43    | ... | 43 |
| Inputs         |    |       |       |       |     |    |
| In (DSP)       | 0  | 32767 | 32767 | 32767 | ... | 0  |
| In             | 0  | 1     | 1     | 1.1   | ... | 0  |
| Parameters     |    |       |       |       |     |    |
| ts_fact        | 1  |       |       |       |     |    |
| Outputs        |    |       |       |       |     |    |
| Out            | 0  | 0     | 1     | 1     | ... | 0  |
| Exp. Out       | 0  | 0     | 1     | 1     | ... | 0  |
| Out (DSP)      | 0  | 0     | 32767 | 32767 | ... | 0  |
| Exp. Out (DSP) | 0  | 0     | 32767 | 32767 | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 43 |
| Max CPU cycles  | 43 |
| Avg CPU cycles  | 43 |

**Verification: Delay FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block Delay.

| Test results   |    |       |       |       |     |    |
|----------------|----|-------|-------|-------|-----|----|
| Time step      | 1  | 2     | 3     | 4     | ... | 18 |
| CPU cycles     | 39 | 39    | 39    | 39    | ... | 39 |
| Inputs         |    |       |       |       |     |    |
| In (DSP)       | 0  | 32767 | 32767 | 32767 | ... | 0  |
| In             | 0  | 1     | 1     | 1.1   | ... | 0  |
| Parameters     |    |       |       |       |     |    |
| ts_fact        | 1  |       |       |       |     |    |
| Outputs        |    |       |       |       |     |    |
| Out            | 0  | 0     | 1     | 1     | ... | 0  |
| Exp. Out       | 0  | 0     | 1     | 1     | ... | 0  |
| Out (DSP)      | 0  | 0     | 32767 | 32767 | ... | 0  |
| Exp. Out (DSP) | 0  | 0     | 32767 | 32767 | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 39 |
| Max CPU cycles  | 39 |
| Avg CPU cycles  | 39 |



**Verification: Delay FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block Delay.

| Test results   |    |            |     |    |
|----------------|----|------------|-----|----|
| Time step      | 1  | 2          | ... | 18 |
| CPU cycles     | 56 | 56         | ... | 56 |
| Inputs         |    |            |     |    |
| In (DSP)       | 0  | 2147483647 | ... | 0  |
| In             | 0  | 1          | ... | 0  |
| Parameters     |    |            |     |    |
| ts_fact        | 1  |            |     |    |
| Outputs        |    |            |     |    |
| Out            | 0  | 0          | ... | 0  |
| Exp. Out       | 0  | 0          | ... | 0  |
| Out (DSP)      | 0  | 0          | ... | 0  |
| Exp. Out (DSP) | 0  | 0          | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 56 |
| Avg CPU cycles  | 56 |

**Verification: Delay FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block Delay.

| Test results   |    |            |     |    |
|----------------|----|------------|-----|----|
| Time step      | 1  | 2          | ... | 18 |
| CPU cycles     | 25 | 25         | ... | 25 |
| Inputs         |    |            |     |    |
| In (DSP)       | 0  | 2147483647 | ... | 0  |
| In             | 0  | 1          | ... | 0  |
| Parameters     |    |            |     |    |
| ts_fact        | 1  |            |     |    |
| Outputs        |    |            |     |    |
| Out            | 0  | 0          | ... | 0  |
| Exp. Out       | 0  | 0          | ... | 0  |
| Out (DSP)      | 0  | 0          | ... | 0  |
| Exp. Out (DSP) | 0  | 0          | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 25 |
| Max CPU cycles  | 25 |
| Avg CPU cycles  | 25 |

**Verification: Delay FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block Delay.

| Test results   |    |            |     |    |
|----------------|----|------------|-----|----|
| Time step      | 1  | 2          | ... | 18 |
| CPU cycles     | 58 | 58         | ... | 58 |
| Inputs         |    |            |     |    |
| In (DSP)       | 0  | 2147483647 | ... | 0  |
| In             | 0  | 1          | ... | 0  |
| Parameters     |    |            |     |    |
| ts_fact        | 1  |            |     |    |
| Outputs        |    |            |     |    |
| Out            | 0  | 0          | ... | 0  |
| Exp. Out       | 0  | 0          | ... | 0  |
| Out (DSP)      | 0  | 0          | ... | 0  |
| Exp. Out (DSP) | 0  | 0          | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 58 |
| Max CPU cycles  | 58 |
| Avg CPU cycles  | 58 |

**Verification: Delay FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block Delay.

| Test results   |    |            |     |    |
|----------------|----|------------|-----|----|
| Time step      | 1  | 2          | ... | 18 |
| CPU cycles     | 50 | 50         | ... | 50 |
| Inputs         |    |            |     |    |
| In (DSP)       | 0  | 2147483647 | ... | 0  |
| In             | 0  | 1          | ... | 0  |
| Parameters     |    |            |     |    |
| ts_fact        | 1  |            |     |    |
| Outputs        |    |            |     |    |
| Out            | 0  | 0          | ... | 0  |
| Exp. Out       | 0  | 0          | ... | 0  |
| Out (DSP)      | 0  | 0          | ... | 0  |
| Exp. Out (DSP) | 0  | 0          | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 50 |
| Max CPU cycles  | 50 |
| Avg CPU cycles  | 50 |

**Verification: Delay FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block Delay.

| Test results   |    |            |     |    |
|----------------|----|------------|-----|----|
| Time step      | 1  | 2          | ... | 18 |
| CPU cycles     | 30 | 30         | ... | 30 |
| Inputs         |    |            |     |    |
| In (DSP)       | 0  | 2147483647 | ... | 0  |
| In             | 0  | 1          | ... | 0  |
| Parameters     |    |            |     |    |
| ts_fact        | 1  |            |     |    |
| Outputs        |    |            |     |    |
| Out            | 0  | 0          | ... | 0  |
| Exp. Out       | 0  | 0          | ... | 0  |
| Out (DSP)      | 0  | 0          | ... | 0  |
| Exp. Out (DSP) | 0  | 0          | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 30 |
| Max CPU cycles  | 30 |
| Avg CPU cycles  | 30 |

**Verification: Delay FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block Delay.

| Test results   |    |            |     |    |
|----------------|----|------------|-----|----|
| Time step      | 1  | 2          | ... | 18 |
| CPU cycles     | 54 | 54         | ... | 54 |
| Inputs         |    |            |     |    |
| In (DSP)       | 0  | 2147483647 | ... | 0  |
| In             | 0  | 1          | ... | 0  |
| Parameters     |    |            |     |    |
| ts_fact        | 1  |            |     |    |
| Outputs        |    |            |     |    |
| Out            | 0  | 0          | ... | 0  |
| Exp. Out       | 0  | 0          | ... | 0  |
| Out (DSP)      | 0  | 0          | ... | 0  |
| Exp. Out (DSP) | 0  | 0          | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 54 |
| Max CPU cycles  | 54 |
| Avg CPU cycles  | 54 |

**Verification: Delay FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block Delay.

| Test results   |    |            |     |    |
|----------------|----|------------|-----|----|
| Time step      | 1  | 2          | ... | 18 |
| CPU cycles     | 45 | 45         | ... | 45 |
| Inputs         |    |            |     |    |
| In (DSP)       | 0  | 2147483647 | ... | 0  |
| In             | 0  | 1          | ... | 0  |
| Parameters     |    |            |     |    |
| ts_fact        | 1  |            |     |    |
| Outputs        |    |            |     |    |
| Out            | 0  | 0          | ... | 0  |
| Exp. Out       | 0  | 0          | ... | 0  |
| Out (DSP)      | 0  | 0          | ... | 0  |
| Exp. Out (DSP) | 0  | 0          | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 45 |
| Max CPU cycles  | 45 |
| Avg CPU cycles  | 45 |

**Verification: Delay FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block Delay.

| Test results   |    |            |     |    |
|----------------|----|------------|-----|----|
| Time step      | 1  | 2          | ... | 18 |
| CPU cycles     | 43 | 43         | ... | 43 |
| Inputs         |    |            |     |    |
| In (DSP)       | 0  | 2147483647 | ... | 0  |
| In             | 0  | 1          | ... | 0  |
| Parameters     |    |            |     |    |
| ts_fact        | 1  |            |     |    |
| Outputs        |    |            |     |    |
| Out            | 0  | 0          | ... | 0  |
| Exp. Out       | 0  | 0          | ... | 0  |
| Out (DSP)      | 0  | 0          | ... | 0  |
| Exp. Out (DSP) | 0  | 0          | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 43 |
| Max CPU cycles  | 43 |
| Avg CPU cycles  | 43 |



**Verification: Delay Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block Delay.

| Test results   |    |    |     |    |
|----------------|----|----|-----|----|
| Time step      | 1  | 2  | ... | 18 |
| CPU cycles     | 56 | 56 | ... | 56 |
| Inputs         |    |    |     |    |
| In (DSP)       | 0  | 1  | ... | 0  |
| In             | 0  | 1  | ... | 0  |
| Parameters     |    |    |     |    |
| ts_fact        | 1  |    |     |    |
| Outputs        |    |    |     |    |
| Out            | 0  | 0  | ... | 0  |
| Exp. Out       | 0  | 0  | ... | 0  |
| Out (DSP)      | 0  | 0  | ... | 0  |
| Exp. Out (DSP) | 0  | 0  | ... | 0  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 56 |
| Avg CPU cycles  | 56 |

**Verification: Delay Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block Delay.

| Test results   |    |    |     |    |
|----------------|----|----|-----|----|
| Time step      | 1  | 2  | ... | 18 |
| CPU cycles     | 25 | 25 | ... | 25 |
| Inputs         |    |    |     |    |
| In (DSP)       | 0  | 1  | ... | 0  |
| In             | 0  | 1  | ... | 0  |
| Parameters     |    |    |     |    |
| ts_fact        | 1  |    |     |    |
| Outputs        |    |    |     |    |
| Out            | 0  | 0  | ... | 0  |
| Exp. Out       | 0  | 0  | ... | 0  |
| Out (DSP)      | 0  | 0  | ... | 0  |
| Exp. Out (DSP) | 0  | 0  | ... | 0  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 25 |
| Max CPU cycles  | 25 |
| Avg CPU cycles  | 25 |

**Verification: Delay Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block Delay.

| Test results   |    |    |     |    |
|----------------|----|----|-----|----|
| Time step      | 1  | 2  | ... | 18 |
| CPU cycles     | 58 | 58 | ... | 58 |
| Inputs         |    |    |     |    |
| In (DSP)       | 0  | 1  | ... | 0  |
| In             | 0  | 1  | ... | 0  |
| Parameters     |    |    |     |    |
| ts_fact        | 1  |    |     |    |
| Outputs        |    |    |     |    |
| Out            | 0  | 0  | ... | 0  |
| Exp. Out       | 0  | 0  | ... | 0  |
| Out (DSP)      | 0  | 0  | ... | 0  |
| Exp. Out (DSP) | 0  | 0  | ... | 0  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 58 |
| Max CPU cycles  | 58 |
| Avg CPU cycles  | 58 |

**Verification: Delay Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block Delay.

| Test results   |    |    |     |    |
|----------------|----|----|-----|----|
| Time step      | 1  | 2  | ... | 18 |
| CPU cycles     | 50 | 50 | ... | 50 |
| Inputs         |    |    |     |    |
| In (DSP)       | 0  | 1  | ... | 0  |
| In             | 0  | 1  | ... | 0  |
| Parameters     |    |    |     |    |
| ts_fact        | 1  |    |     |    |
| Outputs        |    |    |     |    |
| Out            | 0  | 0  | ... | 0  |
| Exp. Out       | 0  | 0  | ... | 0  |
| Out (DSP)      | 0  | 0  | ... | 0  |
| Exp. Out (DSP) | 0  | 0  | ... | 0  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 50 |
| Max CPU cycles  | 50 |
| Avg CPU cycles  | 50 |

**Verification: Delay Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block Delay.

| Test results   |    |    |     |    |
|----------------|----|----|-----|----|
| Time step      | 1  | 2  | ... | 18 |
| CPU cycles     | 30 | 30 | ... | 30 |
| Inputs         |    |    |     |    |
| In (DSP)       | 0  | 1  | ... | 0  |
| In             | 0  | 1  | ... | 0  |
| Parameters     |    |    |     |    |
| ts_fact        | 1  |    |     |    |
| Outputs        |    |    |     |    |
| Out            | 0  | 0  | ... | 0  |
| Exp. Out       | 0  | 0  | ... | 0  |
| Out (DSP)      | 0  | 0  | ... | 0  |
| Exp. Out (DSP) | 0  | 0  | ... | 0  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 30 |
| Max CPU cycles  | 30 |
| Avg CPU cycles  | 30 |

**Verification: Delay Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block Delay.

| Test results   |    |    |     |    |
|----------------|----|----|-----|----|
| Time step      | 1  | 2  | ... | 18 |
| CPU cycles     | 65 | 54 | ... | 54 |
| Inputs         |    |    |     |    |
| In (DSP)       | 0  | 1  | ... | 0  |
| In             | 0  | 1  | ... | 0  |
| Parameters     |    |    |     |    |
| ts_fact        | 1  |    |     |    |
| Outputs        |    |    |     |    |
| Out            | 0  | 0  | ... | 0  |
| Exp. Out       | 0  | 0  | ... | 0  |
| Out (DSP)      | 0  | 0  | ... | 0  |
| Exp. Out (DSP) | 0  | 0  | ... | 0  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 54 |
| Max CPU cycles  | 65 |
| Avg CPU cycles  | 54 |

**Verification: Delay Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block Delay.

| Test results   |    |    |     |    |
|----------------|----|----|-----|----|
| Time step      | 1  | 2  | ... | 18 |
| CPU cycles     | 45 | 45 | ... | 45 |
| Inputs         |    |    |     |    |
| In (DSP)       | 0  | 1  | ... | 0  |
| In             | 0  | 1  | ... | 0  |
| Parameters     |    |    |     |    |
| ts_fact        | 1  |    |     |    |
| Outputs        |    |    |     |    |
| Out            | 0  | 0  | ... | 0  |
| Exp. Out       | 0  | 0  | ... | 0  |
| Out (DSP)      | 0  | 0  | ... | 0  |
| Exp. Out (DSP) | 0  | 0  | ... | 0  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 45 |
| Max CPU cycles  | 45 |
| Avg CPU cycles  | 45 |

**Verification: Delay Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block Delay.


| Test results   |    |    |     |    |
|----------------|----|----|-----|----|
| Time step      | 1  | 2  | ... | 18 |
| CPU cycles     | 43 | 43 | ... | 43 |
| Inputs         |    |    |     |    |
| In (DSP)       | 0  | 1  | ... | 0  |
| In             | 0  | 1  | ... | 0  |
| Parameters     |    |    |     |    |
| ts_fact        | 1  |    |     |    |
| Outputs        |    |    |     |    |
| Out            | 0  | 0  | ... | 0  |
| Exp. Out       | 0  | 0  | ... | 0  |
| Out (DSP)      | 0  | 0  | ... | 0  |
| Exp. Out (DSP) | 0  | 0  | ... | 0  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 43 |
| Max CPU cycles  | 43 |
| Avg CPU cycles  | 43 |



## Block: DLimit



D Controller with Output Limitation:

$$G(s) = K_d s / (s / (2\pi f_c) + 1)$$

| Inports |                                                                                                              |
|---------|--------------------------------------------------------------------------------------------------------------|
| In      | Control error input                                                                                          |
| D0      | Derivational value which is loaded during initialization. (Usually this inport is connect to the In inport.) |
| max     | Maximum output value                                                                                         |
| min     | Minimum output value                                                                                         |
| Enable  | Enable == 0: Deactivation of block; Out set to 0<br>Enable == 1: Activation of block                         |

| Outports |               |
|----------|---------------|
| Out      | Control value |

| Mask Parameters |    |                                                                 |
|-----------------|----|-----------------------------------------------------------------|
| Name            | ID | Description                                                     |
| Kd              | 1  | Derivative Factor                                               |
| fc              | 2  | Cutoff frequency of realization low pass                        |
| ts_fact         | 3  | Multiplication factor of base sampling time (in integer format) |

### Description:

A rising flank at the *Enable* inport will preload the derivational part with the value present on the *Init* inport.

Transfer function (zero-order hold discretization method):

$$G(z) = K_d 2\pi f_c \frac{z - 1}{z - e^{-2\pi f_c T_s}}$$

**Developer note:** The source code of this block is used for block *D*.

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP16

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |
| D0                | int16 |
| max               | int16 |
| min               | int16 |
| Enable            | bool  |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |
| D0                | int32 |
| max               | int32 |
| min               | int32 |
| Enable            | bool  |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |
| D0                | float32 |
| max               | float32 |
| min               | float32 |
| Enable            | bool    |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

## Implementation: Float64

---

### 64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |
| D0                | float64 |
| max               | float64 |
| min               | float64 |
| Enable            | bool    |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: DLimit FiP16 CPU TMS320F28335**

Date of Test 2026-06-19

Target controller TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block DLimit.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 79    | 79    | 79    | 151   | ... | 146   |
| Inputs         |       |       |       |       |     |       |
| In (DSP)       | 0     | 0     | 0     | 0     | ... | 0     |
| D0 (DSP)       | 655   | 655   | 655   | 655   | ... | 655   |
| max (DSP)      | 26214 | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915  | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0     | 0     | 0     | 1     | ... | 1     |
| In             | 0     | 0     | 0     | 0     | ... | 0     |
| D0             | 0.02  | 0.02  | 0.02  | 0.02  | ... | 0.02  |
| max            | 0.8   | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15  | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0     | 0     | 0     | 1     | ... | 1     |
| Parameters     |       |       |       |       |     |       |
| Kd             | 0.003 |       |       |       |     |       |
| fc             | 200   |       |       |       |     |       |
| ts_fact        | 1     |       |       |       |     |       |
| Outputs        |       |       |       |       |     |       |
| Out            | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Exp. Out       | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Out (DSP)      | 0     | 0     | 0     | 4915  | ... | 4915  |
| Exp. Out (DSP) | 0     | 0     | 0     | 4915  | ... | 4915  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 79  |
| Max CPU cycles  | 151 |
| Avg CPU cycles  | 144 |

**Test case: Conversion test****OK**

Conversion test for Control block DLimit.

| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>b0d</b>                   | 0      | 26374  | 24822  | 17453  | ... | -31416 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for Control block DLimit.

| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26373 | -24822 | -17453 | ... | 31415  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23933 |
| <b>b0d</b>                   | 0      | 26373  | 24822  | 17453  | ... | -31415 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 1,0000e+00$ |
| Tolerance a0d  | $\pm 1,0000e+00$ |
| Tolerance b0d  | $\pm 1,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 2816  |
| Max CPU cycles  | 10485 |
| Avg CPU cycles  | 9330  |

**Verification: DLimit FiP16 CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block DLimit.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 51    | 51    | 51    | 101   | ... | 99    |
| Inputs         |       |       |       |       |     |       |
| In (DSP)       | 0     | 0     | 0     | 0     | ... | 0     |
| D0 (DSP)       | 655   | 655   | 655   | 655   | ... | 655   |
| max (DSP)      | 26214 | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915  | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0     | 0     | 0     | 1     | ... | 1     |
| In             | 0     | 0     | 0     | 0     | ... | 0     |
| D0             | 0.02  | 0.02  | 0.02  | 0.02  | ... | 0.02  |
| max            | 0.8   | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15  | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0     | 0     | 0     | 1     | ... | 1     |
| Parameters     |       |       |       |       |     |       |
| Kd             | 0.003 |       |       |       |     |       |
| fc             | 200   |       |       |       |     |       |
| ts_fact        | 1     |       |       |       |     |       |
| Outputs        |       |       |       |       |     |       |
| Out            | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Exp. Out       | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Out (DSP)      | 0     | 0     | 0     | 4915  | ... | 4915  |
| Exp. Out (DSP) | 0     | 0     | 0     | 4915  | ... | 4915  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 51  |
| Max CPU cycles  | 101 |
| Avg CPU cycles  | 98  |

**Test case: Conversion test****OK**

Conversion test for Control block DLimit.

| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>b0d</b>                   | 0      | 26374  | 24822  | 17453  | ... | -31416 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for Control block DLimit.



| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26373 | -24822 | -17453 | ... | 31415  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23933 |
| <b>b0d</b>                   | 0      | 26373  | 24822  | 17453  | ... | -31415 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 1,0000e+00$ |
| Tolerance a0d  | $\pm 1,0000e+00$ |
| Tolerance b0d  | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1363 |
| Max CPU cycles  | 6395 |
| Avg CPU cycles  | 5342 |

**Verification: DLimit FiP16 CPU STM32G474RE**

Date of Test 2026-06-19  
Target controller STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block DLimit.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 78    | 78    | 78    | 148   | ... | 133   |
| Inputs         |       |       |       |       |     |       |
| In (DSP)       | 0     | 0     | 0     | 0     | ... | 0     |
| D0 (DSP)       | 655   | 655   | 655   | 655   | ... | 655   |
| max (DSP)      | 26214 | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915  | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0     | 0     | 0     | 1     | ... | 1     |
| In             | 0     | 0     | 0     | 0     | ... | 0     |
| D0             | 0.02  | 0.02  | 0.02  | 0.02  | ... | 0.02  |
| max            | 0.8   | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15  | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0     | 0     | 0     | 1     | ... | 1     |
| Parameters     |       |       |       |       |     |       |
| Kd             | 0.003 |       |       |       |     |       |
| fc             | 200   |       |       |       |     |       |
| ts_fact        | 1     |       |       |       |     |       |
| Outputs        |       |       |       |       |     |       |
| Out            | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Exp. Out       | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Out (DSP)      | 0     | 0     | 0     | 4915  | ... | 4915  |
| Exp. Out (DSP) | 0     | 0     | 0     | 4915  | ... | 4915  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 78  |
| Max CPU cycles  | 191 |
| Avg CPU cycles  | 132 |

**Test case: Conversion test****OK**

Conversion test for Control block DLimit.

| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>b0d</b>                   | 0      | 26374  | 24822  | 17453  | ... | -31416 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for Control block DLimit.

| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26373 | -24822 | -17453 | ... | 31415  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23933 |
| <b>b0d</b>                   | 0      | 26373  | 24822  | 17453  | ... | -31415 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 1,0000e+00$ |
| Tolerance a0d  | $\pm 1,0000e+00$ |
| Tolerance b0d  | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1668 |
| Max CPU cycles  | 3646 |
| Avg CPU cycles  | 3276 |

**Verification: DLimit FiP16 CPU STM32F072RB**

Date of Test 2026-06-19  
Target controller STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block DLimit.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 72    | 72    | 72    | 145   | ... | 132   |
| Inputs         |       |       |       |       |     |       |
| In (DSP)       | 0     | 0     | 0     | 0     | ... | 0     |
| D0 (DSP)       | 655   | 655   | 655   | 655   | ... | 655   |
| max (DSP)      | 26214 | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915  | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0     | 0     | 0     | 1     | ... | 1     |
| In             | 0     | 0     | 0     | 0     | ... | 0     |
| D0             | 0.02  | 0.02  | 0.02  | 0.02  | ... | 0.02  |
| max            | 0.8   | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15  | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0     | 0     | 0     | 1     | ... | 1     |
| Parameters     |       |       |       |       |     |       |
| Kd             | 0.003 |       |       |       |     |       |
| fc             | 200   |       |       |       |     |       |
| ts_fact        | 1     |       |       |       |     |       |
| Outputs        |       |       |       |       |     |       |
| Out            | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Exp. Out       | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Out (DSP)      | 0     | 0     | 0     | 4915  | ... | 4915  |
| Exp. Out (DSP) | 0     | 0     | 0     | 4915  | ... | 4915  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 72  |
| Max CPU cycles  | 194 |
| Avg CPU cycles  | 132 |

**Test case: Conversion test****OK**

Conversion test for Control block DLimit.

| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>b0d</b>                   | 0      | 26374  | 24822  | 17453  | ... | -31416 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for Control block DLimit.

| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26373 | -24822 | -17453 | ... | 31415  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23933 |
| <b>b0d</b>                   | 0      | 26373  | 24822  | 17453  | ... | -31415 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 1,0000e+00$ |
| Tolerance a0d  | $\pm 1,0000e+00$ |
| Tolerance b0d  | $\pm 1,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 4310  |
| Max CPU cycles  | 17162 |
| Avg CPU cycles  | 15165 |

**Verification: DLimit FiP16 CPU PIC32MX170F256**

Date of Test 2026-06-19  
Target controller PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block DLimit.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 37    | 37    | 37    | 93    | ... | 88    |
| Inputs         |       |       |       |       |     |       |
| In (DSP)       | 0     | 0     | 0     | 0     | ... | 0     |
| D0 (DSP)       | 655   | 655   | 655   | 655   | ... | 655   |
| max (DSP)      | 26214 | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915  | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0     | 0     | 0     | 1     | ... | 1     |
| In             | 0     | 0     | 0     | 0     | ... | 0     |
| D0             | 0.02  | 0.02  | 0.02  | 0.02  | ... | 0.02  |
| max            | 0.8   | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15  | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0     | 0     | 0     | 1     | ... | 1     |
| Parameters     |       |       |       |       |     |       |
| Kd             | 0.003 |       |       |       |     |       |
| fc             | 200   |       |       |       |     |       |
| ts_fact        | 1     |       |       |       |     |       |
| Outputs        |       |       |       |       |     |       |
| Out            | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Exp. Out       | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Out (DSP)      | 0     | 0     | 0     | 4915  | ... | 4915  |
| Exp. Out (DSP) | 0     | 0     | 0     | 4915  | ... | 4915  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 37 |
| Max CPU cycles  | 93 |
| Avg CPU cycles  | 87 |



**Test case: Conversion test****OK**

Conversion test for Control block DLimit.

| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>b0d</b>                   | 0      | 26374  | 24822  | 17453  | ... | -31416 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for Control block DLimit.

| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26373 | -24822 | -17453 | ... | 31415  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23933 |
| <b>b0d</b>                   | 0      | 26373  | 24822  | 17453  | ... | -31415 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 1,0000e+00$ |
| Tolerance a0d  | $\pm 1,0000e+00$ |
| Tolerance b0d  | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1688 |
| Max CPU cycles  | 5799 |
| Avg CPU cycles  | 5201 |

**Verification: DLimit FiP16 CPU XMC4800-F144K2048**

Date of Test 2026-06-19  
Target controller XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block DLimit.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 95    | 77    | 77    | 147   | ... | 126   |
| Inputs         |       |       |       |       |     |       |
| In (DSP)       | 0     | 0     | 0     | 0     | ... | 0     |
| D0 (DSP)       | 655   | 655   | 655   | 655   | ... | 655   |
| max (DSP)      | 26214 | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915  | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0     | 0     | 0     | 1     | ... | 1     |
| In             | 0     | 0     | 0     | 0     | ... | 0     |
| D0             | 0.02  | 0.02  | 0.02  | 0.02  | ... | 0.02  |
| max            | 0.8   | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15  | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0     | 0     | 0     | 1     | ... | 1     |
| Parameters     |       |       |       |       |     |       |
| Kd             | 0.003 |       |       |       |     |       |
| fc             | 200   |       |       |       |     |       |
| ts_fact        | 1     |       |       |       |     |       |
| Outputs        |       |       |       |       |     |       |
| Out            | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Exp. Out       | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Out (DSP)      | 0     | 0     | 0     | 4915  | ... | 4915  |
| Exp. Out (DSP) | 0     | 0     | 0     | 4915  | ... | 4915  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 77  |
| Max CPU cycles  | 147 |
| Avg CPU cycles  | 125 |

**Test case: Conversion test****OK**

Conversion test for Control block DLimit.

| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>b0d</b>                   | 0      | 26374  | 24822  | 17453  | ... | -31416 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for Control block DLimit.

| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26373 | -24822 | -17453 | ... | 31415  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23933 |
| <b>b0d</b>                   | 0      | 26373  | 24822  | 17453  | ... | -31415 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 1,0000e+00$ |
| Tolerance a0d  | $\pm 1,0000e+00$ |
| Tolerance b0d  | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1257 |
| Max CPU cycles  | 3084 |
| Avg CPU cycles  | 2729 |

**Verification: DLimit FiP16 CPU TMS320F28379D**

Date of Test 2026-06-22  
Target controller TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block DLimit.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 70    | 70    | 70    | 153   | ... | 148   |
| Inputs         |       |       |       |       |     |       |
| In (DSP)       | 0     | 0     | 0     | 0     | ... | 0     |
| D0 (DSP)       | 655   | 655   | 655   | 655   | ... | 655   |
| max (DSP)      | 26214 | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915  | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0     | 0     | 0     | 1     | ... | 1     |
| In             | 0     | 0     | 0     | 0     | ... | 0     |
| D0             | 0.02  | 0.02  | 0.02  | 0.02  | ... | 0.02  |
| max            | 0.8   | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15  | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0     | 0     | 0     | 1     | ... | 1     |
| Parameters     |       |       |       |       |     |       |
| Kd             | 0.003 |       |       |       |     |       |
| fc             | 200   |       |       |       |     |       |
| ts_fact        | 1     |       |       |       |     |       |
| Outputs        |       |       |       |       |     |       |
| Out            | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Exp. Out       | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Out (DSP)      | 0     | 0     | 0     | 4915  | ... | 4915  |
| Exp. Out (DSP) | 0     | 0     | 0     | 4915  | ... | 4915  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 70  |
| Max CPU cycles  | 153 |
| Avg CPU cycles  | 146 |

**Test case: Conversion test****OK**

Conversion test for Control block DLimit.

| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>b0d</b>                   | 0      | 26374  | 24822  | 17453  | ... | -31416 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for Control block DLimit.

| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26373 | -24822 | -17453 | ... | 31415  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23933 |
| <b>b0d</b>                   | 0      | 26373  | 24822  | 17453  | ... | -31415 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 1,0000e+00$ |
| Tolerance a0d  | $\pm 1,0000e+00$ |
| Tolerance b0d  | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2019 |
| Max CPU cycles  | 8061 |
| Avg CPU cycles  | 7153 |



**Verification: DLimit FiP16 CPU dsPIC33EP256MC502**

Date of Test 2026-06-23  
Target controller dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block DLimit.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 52    | 52    | 52    | 120   | ... | 124   |
| Inputs         |       |       |       |       |     |       |
| In (DSP)       | 0     | 0     | 0     | 0     | ... | 0     |
| D0 (DSP)       | 655   | 655   | 655   | 655   | ... | 655   |
| max (DSP)      | 26214 | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915  | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0     | 0     | 0     | 1     | ... | 1     |
| In             | 0     | 0     | 0     | 0     | ... | 0     |
| D0             | 0.02  | 0.02  | 0.02  | 0.02  | ... | 0.02  |
| max            | 0.8   | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15  | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0     | 0     | 0     | 1     | ... | 1     |
| Parameters     |       |       |       |       |     |       |
| Kd             | 0.003 |       |       |       |     |       |
| fc             | 200   |       |       |       |     |       |
| ts_fact        | 1     |       |       |       |     |       |
| Outputs        |       |       |       |       |     |       |
| Out            | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Exp. Out       | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Out (DSP)      | 0     | 0     | 0     | 4915  | ... | 4915  |
| Exp. Out (DSP) | 0     | 0     | 0     | 4915  | ... | 4915  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 52  |
| Max CPU cycles  | 124 |
| Avg CPU cycles  | 121 |

**Test case: Conversion test****OK**

Conversion test for Control block DLimit.

| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>b0d</b>                   | 0      | 26374  | 24822  | 17453  | ... | -31416 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for Control block DLimit.

| Test results                 |        |        |        |        |     |        |
|------------------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37     |
| <i>Mask parameters</i>       |        |        |        |        |     |        |
| <b>Kd</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10     |
| <b>fc</b>                    | 0      | 13.889 | 27.778 | 41.667 | ... | 500    |
| <b>ts_fact</b>               | 1      | 1      | 1      | 1      | ... | 1      |
| <i>Controller parameters</i> |        |        |        |        |     |        |
| <b>sfrd</b>                  | 15     | 5      | 4      | 3      | ... | 0      |
| <b>b1d</b>                   | 0      | -26373 | -24822 | -17453 | ... | 31415  |
| <b>a0d</b>                   | -32767 | -32483 | -32201 | -31921 | ... | -23933 |
| <b>b0d</b>                   | 0      | 26373  | 24822  | 17453  | ... | -31415 |
| <b>Exp. sfrd</b>             | 15     | 5      | 4      | 3      | ... | 0      |
| <b>Exp. b1d</b>              | 0      | -26374 | -24822 | -17453 | ... | 31416  |
| <b>Exp. a0d</b>              | -32767 | -32483 | -32201 | -31921 | ... | -23934 |
| <b>Exp. b0d</b>              | 0      | 26374  | 24822  | 17453  | ... | -31416 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 1,0000e+00$ |
| Tolerance a0d  | $\pm 1,0000e+00$ |
| Tolerance b0d  | $\pm 1,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 6401  |
| Max CPU cycles  | 35059 |
| Avg CPU cycles  | 31162 |

**Verification: DLimit FiP32 CPU TMS320F28335**

Date of Test 2026-06-19  
Target controller TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block DLimit.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 201        |
| CPU cycles     | 88         | 88         | ... | 360        |
| Inputs         |            |            |     |            |
| In (DSP)       | 0          | 0          | ... | 0          |
| D0 (DSP)       | 42949673   | 42949673   | ... | 42949673   |
| max (DSP)      | 1717986918 | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547  | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0          | 0          | ... | 1          |
| In             | 0          | 0          | ... | 0          |
| D0             | 0.02       | 0.02       | ... | 0.02       |
| max            | 0.8        | 0.8        | ... | 0.8        |
| min            | 0.15       | 0.15       | ... | 0.15       |
| Enable         | 0          | 0          | ... | 1          |
| Parameters     |            |            |     |            |
| Kd             | 0.003      |            |     |            |
| fc             | 200        |            |     |            |
| ts_fact        | 1          |            |     |            |
| Outputs        |            |            |     |            |
| Out            | 0          | 0          | ... | 0.15       |
| Exp. Out       | 0          | 0          | ... | 0.15       |
| Out (DSP)      | 0          | 0          | ... | 322122547  |
| Exp. Out (DSP) | 0          | 0          | ... | 322122547  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 88  |
| Max CPU cycles  | 401 |
| Avg CPU cycles  | 355 |

**Test case: Conversion test**

OK

Conversion test for Control block DLimit.

| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437568 | ... | 2058874161  |
| <b>a0d</b>                   | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>b0d</b>                   | 0           | 1728437568  | ... | -2058874161 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block DLimit.

| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437632 | ... | 2058874240  |
| <b>a0d</b>                   | -2147483647 | -2128824832 | ... | -1568527872 |
| <b>b0d</b>                   | 0           | 1728437632  | ... | -2058874240 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 2,0000e+02$ |
| Tolerance a0d  | $\pm 2,0000e+02$ |
| Tolerance b0d  | $\pm 2,0000e+02$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 3452  |
| Max CPU cycles  | 11665 |
| Avg CPU cycles  | 10118 |

**Verification: DLimit FiP32 CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block DLimit.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 201        |
| CPU cycles     | 53         | 53         | ... | 135        |
| Inputs         |            |            |     |            |
| In (DSP)       | 0          | 0          | ... | 0          |
| D0 (DSP)       | 42949673   | 42949673   | ... | 42949673   |
| max (DSP)      | 1717986918 | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547  | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0          | 0          | ... | 1          |
| In             | 0          | 0          | ... | 0          |
| D0             | 0.02       | 0.02       | ... | 0.02       |
| max            | 0.8        | 0.8        | ... | 0.8        |
| min            | 0.15       | 0.15       | ... | 0.15       |
| Enable         | 0          | 0          | ... | 1          |
| Parameters     |            |            |     |            |
| Kd             | 0.003      |            |     |            |
| fc             | 200        |            |     |            |
| ts_fact        | 1          |            |     |            |
| Outputs        |            |            |     |            |
| Out            | 0          | 0          | ... | 0.15       |
| Exp. Out       | 0          | 0          | ... | 0.15       |
| Out (DSP)      | 0          | 0          | ... | 322122547  |
| Exp. Out (DSP) | 0          | 0          | ... | 322122547  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 53  |
| Max CPU cycles  | 137 |
| Avg CPU cycles  | 133 |

**Test case: Conversion test****OK**

Conversion test for Control block DLimit.

| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437568 | ... | 2058874161  |
| <b>a0d</b>                   | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>b0d</b>                   | 0           | 1728437568  | ... | -2058874161 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for Control block DLimit.



| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437632 | ... | 2058874240  |
| <b>a0d</b>                   | -2147483647 | -2128824832 | ... | -1568527872 |
| <b>b0d</b>                   | 0           | 1728437632  | ... | -2058874240 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 2,0000e+02$ |
| Tolerance a0d  | $\pm 2,0000e+02$ |
| Tolerance b0d  | $\pm 2,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1431 |
| Max CPU cycles  | 5085 |
| Avg CPU cycles  | 4311 |

**Verification: DLimit FiP32 CPU STM32G474RE**

Date of Test 2026-06-19  
Target controller STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block DLimit.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 201        |
| CPU cycles     | 86         | 86         | ... | 172        |
| Inputs         |            |            |     |            |
| In (DSP)       | 0          | 0          | ... | 0          |
| D0 (DSP)       | 42949673   | 42949673   | ... | 42949673   |
| max (DSP)      | 1717986918 | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547  | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0          | 0          | ... | 1          |
| In             | 0          | 0          | ... | 0          |
| D0             | 0.02       | 0.02       | ... | 0.02       |
| max            | 0.8        | 0.8        | ... | 0.8        |
| min            | 0.15       | 0.15       | ... | 0.15       |
| Enable         | 0          | 0          | ... | 1          |
| Parameters     |            |            |     |            |
| Kd             | 0.003      |            |     |            |
| fc             | 200        |            |     |            |
| ts_fact        | 1          |            |     |            |
| Outputs        |            |            |     |            |
| Out            | 0          | 0          | ... | 0.15       |
| Exp. Out       | 0          | 0          | ... | 0.15       |
| Out (DSP)      | 0          | 0          | ... | 322122547  |
| Exp. Out (DSP) | 0          | 0          | ... | 322122547  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 86  |
| Max CPU cycles  | 194 |
| Avg CPU cycles  | 170 |

**Test case: Conversion test****OK**

Conversion test for Control block DLimit.

| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437568 | ... | 2058874161  |
| <b>a0d</b>                   | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>b0d</b>                   | 0           | 1728437568  | ... | -2058874161 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for Control block DLimit.

| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437632 | ... | 2058874240  |
| <b>a0d</b>                   | -2147483647 | -2128824832 | ... | -1568527872 |
| <b>b0d</b>                   | 0           | 1728437632  | ... | -2058874240 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 2,0000e+02$ |
| Tolerance a0d  | $\pm 2,0000e+02$ |
| Tolerance b0d  | $\pm 2,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2520 |
| Max CPU cycles  | 4575 |
| Avg CPU cycles  | 4143 |

**Verification: DLimit FiP32 CPU STM32F072RB**

Date of Test 2026-06-19  
Target controller STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block DLimit.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 201        |
| CPU cycles     | 87         | 87         | ... | 404        |
| Inputs         |            |            |     |            |
| In (DSP)       | 0          | 0          | ... | 0          |
| D0 (DSP)       | 42949673   | 42949673   | ... | 42949673   |
| max (DSP)      | 1717986918 | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547  | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0          | 0          | ... | 1          |
| In             | 0          | 0          | ... | 0          |
| D0             | 0.02       | 0.02       | ... | 0.02       |
| max            | 0.8        | 0.8        | ... | 0.8        |
| min            | 0.15       | 0.15       | ... | 0.15       |
| Enable         | 0          | 0          | ... | 1          |
| Parameters     |            |            |     |            |
| Kd             | 0.003      |            |     |            |
| fc             | 200        |            |     |            |
| ts_fact        | 1          |            |     |            |
| Outputs        |            |            |     |            |
| Out            | 0          | 0          | ... | 0.15       |
| Exp. Out       | 0          | 0          | ... | 0.15       |
| Out (DSP)      | 0          | 0          | ... | 322122547  |
| Exp. Out (DSP) | 0          | 0          | ... | 322122547  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 87  |
| Max CPU cycles  | 410 |
| Avg CPU cycles  | 399 |

**Test case: Conversion test**

OK

Conversion test for Control block DLimit.

| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437568 | ... | 2058874161  |
| <b>a0d</b>                   | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>b0d</b>                   | 0           | 1728437568  | ... | -2058874161 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block DLimit.

| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437632 | ... | 2058874240  |
| <b>a0d</b>                   | -2147483647 | -2128824832 | ... | -1568527872 |
| <b>b0d</b>                   | 0           | 1728437632  | ... | -2058874240 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 2,0000e+02$ |
| Tolerance a0d  | $\pm 2,0000e+02$ |
| Tolerance b0d  | $\pm 2,0000e+02$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 7766  |
| Max CPU cycles  | 20968 |
| Avg CPU cycles  | 18920 |

**Verification: DLimit FiP32 CPU PIC32MX170F256**

Date of Test 2026-06-19  
Target controller PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block DLimit.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 201        |
| CPU cycles     | 37         | 37         | ... | 119        |
| Inputs         |            |            |     |            |
| In (DSP)       | 0          | 0          | ... | 0          |
| D0 (DSP)       | 42949673   | 42949673   | ... | 42949673   |
| max (DSP)      | 1717986918 | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547  | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0          | 0          | ... | 1          |
| In             | 0          | 0          | ... | 0          |
| D0             | 0.02       | 0.02       | ... | 0.02       |
| max            | 0.8        | 0.8        | ... | 0.8        |
| min            | 0.15       | 0.15       | ... | 0.15       |
| Enable         | 0          | 0          | ... | 1          |
| Parameters     |            |            |     |            |
| Kd             | 0.003      |            |     |            |
| fc             | 200        |            |     |            |
| ts_fact        | 1          |            |     |            |
| Outputs        |            |            |     |            |
| Out            | 0          | 0          | ... | 0.15       |
| Exp. Out       | 0          | 0          | ... | 0.15       |
| Out (DSP)      | 0          | 0          | ... | 322122547  |
| Exp. Out (DSP) | 0          | 0          | ... | 322122547  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 37  |
| Max CPU cycles  | 123 |
| Avg CPU cycles  | 118 |



**Test case: Conversion test**

OK

Conversion test for Control block DLimit.

| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437568 | ... | 2058874161  |
| <b>a0d</b>                   | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>b0d</b>                   | 0           | 1728437568  | ... | -2058874161 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block DLimit.

| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437632 | ... | 2058874240  |
| <b>a0d</b>                   | -2147483647 | -2128824832 | ... | -1568527872 |
| <b>b0d</b>                   | 0           | 1728437632  | ... | -2058874240 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 2,0000e+02$ |
| Tolerance a0d  | $\pm 2,0000e+02$ |
| Tolerance b0d  | $\pm 2,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2913 |
| Max CPU cycles  | 7307 |
| Avg CPU cycles  | 6491 |

**Verification: DLimit FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block DLimit.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 201        |
| CPU cycles     | 103        | 83         | ... | 157        |
| Inputs         |            |            |     |            |
| In (DSP)       | 0          | 0          | ... | 0          |
| D0 (DSP)       | 42949673   | 42949673   | ... | 42949673   |
| max (DSP)      | 1717986918 | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547  | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0          | 0          | ... | 1          |
| In             | 0          | 0          | ... | 0          |
| D0             | 0.02       | 0.02       | ... | 0.02       |
| max            | 0.8        | 0.8        | ... | 0.8        |
| min            | 0.15       | 0.15       | ... | 0.15       |
| Enable         | 0          | 0          | ... | 1          |
| Parameters     |            |            |     |            |
| Kd             | 0.003      |            |     |            |
| fc             | 200        |            |     |            |
| ts_fact        | 1          |            |     |            |
| Outputs        |            |            |     |            |
| Out            | 0          | 0          | ... | 0.15       |
| Exp. Out       | 0          | 0          | ... | 0.15       |
| Out (DSP)      | 0          | 0          | ... | 322122547  |
| Exp. Out (DSP) | 0          | 0          | ... | 322122547  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 83  |
| Max CPU cycles  | 189 |
| Avg CPU cycles  | 156 |

**Test case: Conversion test**

OK

Conversion test for Control block DLimit.

| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437568 | ... | 2058874161  |
| <b>a0d</b>                   | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>b0d</b>                   | 0           | 1728437568  | ... | -2058874161 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block DLimit.

| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437632 | ... | 2058874240  |
| <b>a0d</b>                   | -2147483647 | -2128824832 | ... | -1568527872 |
| <b>b0d</b>                   | 0           | 1728437632  | ... | -2058874240 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 2,0000e+02$ |
| Tolerance a0d  | $\pm 2,0000e+02$ |
| Tolerance b0d  | $\pm 2,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2097 |
| Max CPU cycles  | 3961 |
| Avg CPU cycles  | 3599 |

**Verification: DLimit FiP32 CPU TMS320F28379D**

Date of Test 2026-06-22  
Target controller TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block DLimit.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 201        |
| CPU cycles     | 73         | 73         | ... | 317        |
| Inputs         |            |            |     |            |
| In (DSP)       | 0          | 0          | ... | 0          |
| D0 (DSP)       | 42949673   | 42949673   | ... | 42949673   |
| max (DSP)      | 1717986918 | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547  | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0          | 0          | ... | 1          |
| In             | 0          | 0          | ... | 0          |
| D0             | 0.02       | 0.02       | ... | 0.02       |
| max            | 0.8        | 0.8        | ... | 0.8        |
| min            | 0.15       | 0.15       | ... | 0.15       |
| Enable         | 0          | 0          | ... | 1          |
| Parameters     |            |            |     |            |
| Kd             | 0.003      |            |     |            |
| fc             | 200        |            |     |            |
| ts_fact        | 1          |            |     |            |
| Outputs        |            |            |     |            |
| Out            | 0          | 0          | ... | 0.15       |
| Exp. Out       | 0          | 0          | ... | 0.15       |
| Out (DSP)      | 0          | 0          | ... | 322122547  |
| Exp. Out (DSP) | 0          | 0          | ... | 322122547  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 73  |
| Max CPU cycles  | 343 |
| Avg CPU cycles  | 313 |

**Test case: Conversion test****OK**

Conversion test for Control block DLimit.

| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437568 | ... | 2058874161  |
| <b>a0d</b>                   | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>b0d</b>                   | 0           | 1728437568  | ... | -2058874161 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for Control block DLimit.

| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437632 | ... | 2058874240  |
| <b>a0d</b>                   | -2147483647 | -2128824832 | ... | -1568527872 |
| <b>b0d</b>                   | 0           | 1728437632  | ... | -2058874240 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 2,0000e+02$ |
| Tolerance a0d  | $\pm 2,0000e+02$ |
| Tolerance b0d  | $\pm 2,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2458 |
| Max CPU cycles  | 8938 |
| Avg CPU cycles  | 7719 |



**Verification: DLimit FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block DLimit.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 201        |
| CPU cycles     | 70         | 70         | ... | 778        |
| Inputs         |            |            |     |            |
| In (DSP)       | 0          | 0          | ... | 0          |
| D0 (DSP)       | 42949673   | 42949673   | ... | 42949673   |
| max (DSP)      | 1717986918 | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547  | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0          | 0          | ... | 1          |
| In             | 0          | 0          | ... | 0          |
| D0             | 0.02       | 0.02       | ... | 0.02       |
| max            | 0.8        | 0.8        | ... | 0.8        |
| min            | 0.15       | 0.15       | ... | 0.15       |
| Enable         | 0          | 0          | ... | 1          |
| Parameters     |            |            |     |            |
| Kd             | 0.003      |            |     |            |
| fc             | 200        |            |     |            |
| ts_fact        | 1          |            |     |            |
| Outputs        |            |            |     |            |
| Out            | 0          | 0          | ... | 0.15       |
| Exp. Out       | 0          | 0          | ... | 0.15       |
| Out (DSP)      | 0          | 0          | ... | 322122547  |
| Exp. Out (DSP) | 0          | 0          | ... | 322122547  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 70  |
| Max CPU cycles  | 786 |
| Avg CPU cycles  | 768 |

**Test case: Conversion test**

OK

Conversion test for Control block DLimit.

| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437568 | ... | 2058874161  |
| <b>a0d</b>                   | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>b0d</b>                   | 0           | 1728437568  | ... | -2058874161 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 0,0000e+00$ |
| Tolerance a0d  | $\pm 0,0000e+00$ |
| Tolerance b0d  | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block DLimit.

| Test results                 |             |             |     |             |
|------------------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>             | 1           | 2           | ... | 37          |
| <i>Mask parameters</i>       |             |             |     |             |
| <b>Kd</b>                    | -10         | -9.444      | ... | 10          |
| <b>fc</b>                    | 0           | 13.889      | ... | 500         |
| <b>ts_fact</b>               | 1           | 1           | ... | 1           |
| <i>Controller parameters</i> |             |             |     |             |
| <b>sfrd</b>                  | 31          | 21          | ... | 16          |
| <b>b1d</b>                   | 0           | -1728437632 | ... | 2058874240  |
| <b>a0d</b>                   | -2147483647 | -2128824832 | ... | -1568527872 |
| <b>b0d</b>                   | 0           | 1728437632  | ... | -2058874240 |
| <b>Exp. sfrd</b>             | 31          | 21          | ... | 16          |
| <b>Exp. b1d</b>              | 0           | -1728437568 | ... | 2058874161  |
| <b>Exp. a0d</b>              | -2147483647 | -2128824851 | ... | -1568527835 |
| <b>Exp. b0d</b>              | 0           | 1728437568  | ... | -2058874161 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrd | $\pm 0,0000e+00$ |
| Tolerance b1d  | $\pm 2,0000e+02$ |
| Tolerance a0d  | $\pm 2,0000e+02$ |
| Tolerance b0d  | $\pm 2,0000e+02$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 7460  |
| Max CPU cycles  | 36680 |
| Avg CPU cycles  | 31565 |

**Verification: DLimit Float32 CPU TMS320F28335**

Date of Test 2026-06-19  
Target controller TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block DLimit.

| Test results   |       |      |     |      |
|----------------|-------|------|-----|------|
| Time step      | 1     | 2    | ... | 201  |
| CPU cycles     | 82    | 82   | ... | 125  |
| Inputs         |       |      |     |      |
| In (DSP)       | 0     | 0    | ... | 0    |
| D0 (DSP)       | 0.02  | 0.02 | ... | 0.02 |
| max (DSP)      | 0.8   | 0.8  | ... | 0.8  |
| min (DSP)      | 0.15  | 0.15 | ... | 0.15 |
| Enable (DSP)   | 0     | 0    | ... | 1    |
| In             | 0     | 0    | ... | 0    |
| D0             | 0.02  | 0.02 | ... | 0.02 |
| max            | 0.8   | 0.8  | ... | 0.8  |
| min            | 0.15  | 0.15 | ... | 0.15 |
| Enable         | 0     | 0    | ... | 1    |
| Parameters     |       |      |     |      |
| Kd             | 0.003 |      |     |      |
| fc             | 200   |      |     |      |
| ts_fact        | 1     |      |     |      |
| Outputs        |       |      |     |      |
| Out            | 0     | 0    | ... | 0.15 |
| Exp. Out       | 0     | 0    | ... | 0.15 |
| Out (DSP)      | 0     | 0    | ... | 0.15 |
| Exp. Out (DSP) | 0     | 0    | ... | 0.15 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 9,3132e-06$ ( $\pm 20000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 82  |
| Max CPU cycles  | 130 |
| Avg CPU cycles  | 124 |

**Test case: Conversion test**

OK

Conversion test for Control block DLimit.

| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.927  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.927 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 0,0000e+00$ |
| Tolerance a0d | $\pm 1,0000e-15$ |
| Tolerance b0d | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block DLimit.

| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.928  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.928 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 3,0000e-03$ |
| Tolerance a0d | $\pm 1,0000e-07$ |
| Tolerance b0d | $\pm 3,0000e-03$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2153 |
| Max CPU cycles  | 2496 |
| Avg CPU cycles  | 2476 |

**Verification: DLimit Float32 CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block DLimit.

| Test results   |       |      |     |      |
|----------------|-------|------|-----|------|
| Time step      | 1     | 2    | ... | 201  |
| CPU cycles     | 45    | 45   | ... | 87   |
| Inputs         |       |      |     |      |
| In (DSP)       | 0     | 0    | ... | 0    |
| D0 (DSP)       | 0.02  | 0.02 | ... | 0.02 |
| max (DSP)      | 0.8   | 0.8  | ... | 0.8  |
| min (DSP)      | 0.15  | 0.15 | ... | 0.15 |
| Enable (DSP)   | 0     | 0    | ... | 1    |
| In             | 0     | 0    | ... | 0    |
| D0             | 0.02  | 0.02 | ... | 0.02 |
| max            | 0.8   | 0.8  | ... | 0.8  |
| min            | 0.15  | 0.15 | ... | 0.15 |
| Enable         | 0     | 0    | ... | 1    |
| Parameters     |       |      |     |      |
| Kd             | 0.003 |      |     |      |
| fc             | 200   |      |     |      |
| ts_fact        | 1     |      |     |      |
| Outputs        |       |      |     |      |
| Out            | 0     | 0    | ... | 0.15 |
| Exp. Out       | 0     | 0    | ... | 0.15 |
| Out (DSP)      | 0     | 0    | ... | 0.15 |
| Exp. Out (DSP) | 0     | 0    | ... | 0.15 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 9,3132e-06$ ( $\pm 20000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 45 |
| Max CPU cycles  | 91 |
| Avg CPU cycles  | 86 |

**Test case: Conversion test**

OK

Conversion test for Control block DLimit.

| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.927  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.927 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 0,0000e+00$ |
| Tolerance a0d | $\pm 1,0000e-15$ |
| Tolerance b0d | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block DLimit.

| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.928  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.928 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |



| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 3,0000e-03$ |
| Tolerance a0d | $\pm 1,0000e-07$ |
| Tolerance b0d | $\pm 3,0000e-03$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1009 |
| Max CPU cycles  | 1053 |
| Avg CPU cycles  | 1051 |

**Verification: DLimit Float32 CPU STM32G474RE**

Date of Test 2026-06-19  
Target controller STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block DLimit.

| Test results   |       |      |     |      |
|----------------|-------|------|-----|------|
| Time step      | 1     | 2    | ... | 201  |
| CPU cycles     | 78    | 78   | ... | 113  |
| Inputs         |       |      |     |      |
| In (DSP)       | 0     | 0    | ... | 0    |
| D0 (DSP)       | 0.02  | 0.02 | ... | 0.02 |
| max (DSP)      | 0.8   | 0.8  | ... | 0.8  |
| min (DSP)      | 0.15  | 0.15 | ... | 0.15 |
| Enable (DSP)   | 0     | 0    | ... | 1    |
| In             | 0     | 0    | ... | 0    |
| D0             | 0.02  | 0.02 | ... | 0.02 |
| max            | 0.8   | 0.8  | ... | 0.8  |
| min            | 0.15  | 0.15 | ... | 0.15 |
| Enable         | 0     | 0    | ... | 1    |
| Parameters     |       |      |     |      |
| Kd             | 0.003 |      |     |      |
| fc             | 200   |      |     |      |
| ts_fact        | 1     |      |     |      |
| Outputs        |       |      |     |      |
| Out            | 0     | 0    | ... | 0.15 |
| Exp. Out       | 0     | 0    | ... | 0.15 |
| Out (DSP)      | 0     | 0    | ... | 0.15 |
| Exp. Out (DSP) | 0     | 0    | ... | 0.15 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 9,3132e-06$ ( $\pm 20000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 78  |
| Max CPU cycles  | 130 |
| Avg CPU cycles  | 112 |

**Test case: Conversion test**

OK

Conversion test for Control block DLimit.

| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.927  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.927 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 0,0000e+00$ |
| Tolerance a0d | $\pm 1,0000e-15$ |
| Tolerance b0d | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block DLimit.

| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.928  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.928 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 3,0000e-03$ |
| Tolerance a0d | $\pm 1,0000e-07$ |
| Tolerance b0d | $\pm 3,0000e-03$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1170 |
| Max CPU cycles  | 1245 |
| Avg CPU cycles  | 1238 |

**Verification: DLimit Float32 CPU STM32F072RB**

Date of Test 2026-06-19  
Target controller STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block DLimit.

| Test results   |       |      |     |      |
|----------------|-------|------|-----|------|
| Time step      | 1     | 2    | ... | 201  |
| CPU cycles     | 80    | 80   | ... | 891  |
| Inputs         |       |      |     |      |
| In (DSP)       | 0     | 0    | ... | 0    |
| D0 (DSP)       | 0.02  | 0.02 | ... | 0.02 |
| max (DSP)      | 0.8   | 0.8  | ... | 0.8  |
| min (DSP)      | 0.15  | 0.15 | ... | 0.15 |
| Enable (DSP)   | 0     | 0    | ... | 1    |
| In             | 0     | 0    | ... | 0    |
| D0             | 0.02  | 0.02 | ... | 0.02 |
| max            | 0.8   | 0.8  | ... | 0.8  |
| min            | 0.15  | 0.15 | ... | 0.15 |
| Enable         | 0     | 0    | ... | 1    |
| Parameters     |       |      |     |      |
| Kd             | 0.003 |      |     |      |
| fc             | 200   |      |     |      |
| ts_fact        | 1     |      |     |      |
| Outputs        |       |      |     |      |
| Out            | 0     | 0    | ... | 0.15 |
| Exp. Out       | 0     | 0    | ... | 0.15 |
| Out (DSP)      | 0     | 0    | ... | 0.15 |
| Exp. Out (DSP) | 0     | 0    | ... | 0.15 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 9,3132e-06$ ( $\pm 20000$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 80   |
| Max CPU cycles  | 1070 |
| Avg CPU cycles  | 954  |

**Test case: Conversion test**

OK

Conversion test for Control block DLimit.

| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.927  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.927 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 0,0000e+00$ |
| Tolerance a0d | $\pm 1,0000e-15$ |
| Tolerance b0d | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block DLimit.

| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.928  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.928 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 3,0000e-03$ |
| Tolerance a0d | $\pm 1,0000e-07$ |
| Tolerance b0d | $\pm 3,0000e-03$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2958 |
| Max CPU cycles  | 5933 |
| Avg CPU cycles  | 5798 |

**Verification: DLimit Float32 CPU PIC32MX170F256**

Date of Test 2026-06-19  
Target controller PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block DLimit.

| Test results   |       |      |     |      |
|----------------|-------|------|-----|------|
| Time step      | 1     | 2    | ... | 201  |
| CPU cycles     | 63    | 63   | ... | 347  |
| Inputs         |       |      |     |      |
| In (DSP)       | 0     | 0    | ... | 0    |
| D0 (DSP)       | 0.02  | 0.02 | ... | 0.02 |
| max (DSP)      | 0.8   | 0.8  | ... | 0.8  |
| min (DSP)      | 0.15  | 0.15 | ... | 0.15 |
| Enable (DSP)   | 0     | 0    | ... | 1    |
| In             | 0     | 0    | ... | 0    |
| D0             | 0.02  | 0.02 | ... | 0.02 |
| max            | 0.8   | 0.8  | ... | 0.8  |
| min            | 0.15  | 0.15 | ... | 0.15 |
| Enable         | 0     | 0    | ... | 1    |
| Parameters     |       |      |     |      |
| Kd             | 0.003 |      |     |      |
| fc             | 200   |      |     |      |
| ts_fact        | 1     |      |     |      |
| Outputs        |       |      |     |      |
| Out            | 0     | 0    | ... | 0.15 |
| Exp. Out       | 0     | 0    | ... | 0.15 |
| Out (DSP)      | 0     | 0    | ... | 0.15 |
| Exp. Out (DSP) | 0     | 0    | ... | 0.15 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 9,3132e-06$ ( $\pm 20000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 63  |
| Max CPU cycles  | 436 |
| Avg CPU cycles  | 373 |



**Test case: Conversion test**

OK

Conversion test for Control block DLimit.

| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.927  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.927 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 0,0000e+00$ |
| Tolerance a0d | $\pm 1,0000e-15$ |
| Tolerance b0d | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block DLimit.

| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.928  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.928 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 3,0000e-03$ |
| Tolerance a0d | $\pm 1,0000e-07$ |
| Tolerance b0d | $\pm 3,0000e-03$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 964  |
| Max CPU cycles  | 1208 |
| Avg CPU cycles  | 1195 |

**Verification: DLimit Float32 CPU XMC4800-F144K2048**

Date of Test 2026-06-19  
Target controller XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block DLimit.

| Test results   |       |      |     |      |
|----------------|-------|------|-----|------|
| Time step      | 1     | 2    | ... | 201  |
| CPU cycles     | 76    | 64   | ... | 108  |
| Inputs         |       |      |     |      |
| In (DSP)       | 0     | 0    | ... | 0    |
| D0 (DSP)       | 0.02  | 0.02 | ... | 0.02 |
| max (DSP)      | 0.8   | 0.8  | ... | 0.8  |
| min (DSP)      | 0.15  | 0.15 | ... | 0.15 |
| Enable (DSP)   | 0     | 0    | ... | 1    |
| In             | 0     | 0    | ... | 0    |
| D0             | 0.02  | 0.02 | ... | 0.02 |
| max            | 0.8   | 0.8  | ... | 0.8  |
| min            | 0.15  | 0.15 | ... | 0.15 |
| Enable         | 0     | 0    | ... | 1    |
| Parameters     |       |      |     |      |
| Kd             | 0.003 |      |     |      |
| fc             | 200   |      |     |      |
| ts_fact        | 1     |      |     |      |
| Outputs        |       |      |     |      |
| Out            | 0     | 0    | ... | 0.15 |
| Exp. Out       | 0     | 0    | ... | 0.15 |
| Out (DSP)      | 0     | 0    | ... | 0.15 |
| Exp. Out (DSP) | 0     | 0    | ... | 0.15 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 9,3132e-06$ ( $\pm 20000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 64  |
| Max CPU cycles  | 121 |
| Avg CPU cycles  | 107 |

**Test case: Conversion test**

OK

Conversion test for Control block DLimit.

| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.927  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.927 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 0,0000e+00$ |
| Tolerance a0d | $\pm 1,0000e-15$ |
| Tolerance b0d | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block DLimit.

| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.928  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.928 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 3,0000e-03$ |
| Tolerance a0d | $\pm 1,0000e-07$ |
| Tolerance b0d | $\pm 3,0000e-03$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1122 |
| Max CPU cycles  | 1129 |
| Avg CPU cycles  | 1128 |

**Verification: DLimit Float32 CPU TMS320F28379D**

Date of Test 2026-06-22  
Target controller TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block DLimit.

| Test results   |       |      |     |      |
|----------------|-------|------|-----|------|
| Time step      | 1     | 2    | ... | 201  |
| CPU cycles     | 74    | 74   | ... | 129  |
| Inputs         |       |      |     |      |
| In (DSP)       | 0     | 0    | ... | 0    |
| D0 (DSP)       | 0.02  | 0.02 | ... | 0.02 |
| max (DSP)      | 0.8   | 0.8  | ... | 0.8  |
| min (DSP)      | 0.15  | 0.15 | ... | 0.15 |
| Enable (DSP)   | 0     | 0    | ... | 1    |
| In             | 0     | 0    | ... | 0    |
| D0             | 0.02  | 0.02 | ... | 0.02 |
| max            | 0.8   | 0.8  | ... | 0.8  |
| min            | 0.15  | 0.15 | ... | 0.15 |
| Enable         | 0     | 0    | ... | 1    |
| Parameters     |       |      |     |      |
| Kd             | 0.003 |      |     |      |
| fc             | 200   |      |     |      |
| ts_fact        | 1     |      |     |      |
| Outputs        |       |      |     |      |
| Out            | 0     | 0    | ... | 0.15 |
| Exp. Out       | 0     | 0    | ... | 0.15 |
| Out (DSP)      | 0     | 0    | ... | 0.15 |
| Exp. Out (DSP) | 0     | 0    | ... | 0.15 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 9,3132e-06$ ( $\pm 20000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 74  |
| Max CPU cycles  | 134 |
| Avg CPU cycles  | 128 |

**Test case: Conversion test**

OK

Conversion test for Control block DLimit.

| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.927  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.927 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 0,0000e+00$ |
| Tolerance a0d | $\pm 1,0000e-15$ |
| Tolerance b0d | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block DLimit.

| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.928  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.928 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 3,0000e-03$ |
| Tolerance a0d | $\pm 1,0000e-07$ |
| Tolerance b0d | $\pm 3,0000e-03$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1568 |
| Max CPU cycles  | 1845 |
| Avg CPU cycles  | 1827 |



**Verification: DLimit Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block DLimit.

| Test results   |       |      |     |      |
|----------------|-------|------|-----|------|
| Time step      | 1     | 2    | ... | 201  |
| CPU cycles     | 67    | 67   | ... | 952  |
| Inputs         |       |      |     |      |
| In (DSP)       | 0     | 0    | ... | 0    |
| D0 (DSP)       | 0.02  | 0.02 | ... | 0.02 |
| max (DSP)      | 0.8   | 0.8  | ... | 0.8  |
| min (DSP)      | 0.15  | 0.15 | ... | 0.15 |
| Enable (DSP)   | 0     | 0    | ... | 1    |
| In             | 0     | 0    | ... | 0    |
| D0             | 0.02  | 0.02 | ... | 0.02 |
| max            | 0.8   | 0.8  | ... | 0.8  |
| min            | 0.15  | 0.15 | ... | 0.15 |
| Enable         | 0     | 0    | ... | 1    |
| Parameters     |       |      |     |      |
| Kd             | 0.003 |      |     |      |
| fc             | 200   |      |     |      |
| ts_fact        | 1     |      |     |      |
| Outputs        |       |      |     |      |
| Out            | 0     | 0    | ... | 0.15 |
| Exp. Out       | 0     | 0    | ... | 0.15 |
| Out (DSP)      | 0     | 0    | ... | 0.15 |
| Exp. Out (DSP) | 0     | 0    | ... | 0.15 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 9,3132e-06$ ( $\pm 20000$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 67   |
| Max CPU cycles  | 1118 |
| Avg CPU cycles  | 1017 |

**Test case: Conversion test**

OK

Conversion test for Control block DLimit.

| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.927  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.927 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 0,0000e+00$ |
| Tolerance a0d | $\pm 1,0000e-15$ |
| Tolerance b0d | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block DLimit.


| Test results                 |     |          |     |            |
|------------------------------|-----|----------|-----|------------|
| <b>Time step</b>             | 1   | 2        | ... | 37         |
| <i>Mask parameters</i>       |     |          |     |            |
| <b>Kd</b>                    | -10 | -9.444   | ... | 10         |
| <b>fc</b>                    | 0   | 13.889   | ... | 500        |
| <b>ts_fact</b>               | 1   | 1        | ... | 1          |
| <i>Controller parameters</i> |     |          |     |            |
| <b>b1d</b>                   | 0   | -824.183 | ... | 31415.928  |
| <b>a0d</b>                   | -1  | -0.991   | ... | -0.73      |
| <b>b0d</b>                   | 0   | 824.183  | ... | -31415.928 |
| <b>Exp. b1d</b>              | 0   | -824.183 | ... | 31415.927  |
| <b>Exp. a0d</b>              | -1  | -0.991   | ... | -0.73      |
| <b>Exp. b0d</b>              | 0   | 824.183  | ... | -31415.927 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1d | $\pm 3,0000e-03$ |
| Tolerance a0d | $\pm 1,0000e-07$ |
| Tolerance b0d | $\pm 3,0000e-03$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3639 |
| Max CPU cycles  | 7392 |
| Avg CPU cycles  | 7022 |

## Block: DT1

---



First order high pass:

$$G(s) = V \cdot s / (s/w + 1)$$

| Inports |             |
|---------|-------------|
| In      | Input In(k) |

| Outports |               |
|----------|---------------|
| Out      | Output Out(k) |

| Mask Parameters |    |                                                                 |
|-----------------|----|-----------------------------------------------------------------|
| Name            | ID | Description                                                     |
| V               | 1  | Gain                                                            |
| fc              | 2  | Cut off frequency of low pass filter                            |
| ts_fact         | 3  | Multiplication factor of base sampling time (in integer format) |
| method          | 4  | Discretization method                                           |

### Description:

Due to limited value range in the 8 bit fixed point implementation rather high deviations from expected output values may occur.

**Developer note:** The source code of block *TF1* is used.

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | int8 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: DT1 FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block DT1.

| Test results   |      |    |    |    |     |        |
|----------------|------|----|----|----|-----|--------|
| Time step      | 1    | 2  | 3  | 4  | ... | 105    |
| CPU cycles     | 88   | 88 | 88 | 88 | ... | 88     |
| Inputs         |      |    |    |    |     |        |
| In (DSP)       | 0    | 0  | 0  | 0  | ... | -4915  |
| In             | 0    | 0  | 0  | 0  | ... | -0.15  |
| Parameters     |      |    |    |    |     |        |
| V              | 0.01 |    |    |    |     |        |
| fc             | 47   |    |    |    |     |        |
| ts_fact        | 1    |    |    |    |     |        |
| method         | zoh  |    |    |    |     |        |
| Outputs        |      |    |    |    |     |        |
| Out            | 0    | 0  | 0  | 0  | ... | -0.157 |
| Exp. Out       | 0    | 0  | 0  | 0  | ... | -0.158 |
| Out (DSP)      | 0    | 0  | 0  | 0  | ... | -5153  |
| Exp. Out (DSP) | 0    | 0  | 0  | 0  | ... | -5172  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 6,1035e-04$ ( $\pm 20$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 88 |
| Max CPU cycles  | 88 |
| Avg CPU cycles  | 88 |

**Verification: DT1 FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block DT1.

| Test results   |      |    |    |    |     |        |
|----------------|------|----|----|----|-----|--------|
| Time step      | 1    | 2  | 3  | 4  | ... | 105    |
| CPU cycles     | 69   | 69 | 69 | 69 | ... | 69     |
| Inputs         |      |    |    |    |     |        |
| In (DSP)       | 0    | 0  | 0  | 0  | ... | -4915  |
| In             | 0    | 0  | 0  | 0  | ... | -0.15  |
| Parameters     |      |    |    |    |     |        |
| V              | 0.01 |    |    |    |     |        |
| fc             | 47   |    |    |    |     |        |
| ts_fact        | 1    |    |    |    |     |        |
| method         | zoh  |    |    |    |     |        |
| Outputs        |      |    |    |    |     |        |
| Out            | 0    | 0  | 0  | 0  | ... | -0.157 |
| Exp. Out       | 0    | 0  | 0  | 0  | ... | -0.158 |
| Out (DSP)      | 0    | 0  | 0  | 0  | ... | -5153  |
| Exp. Out (DSP) | 0    | 0  | 0  | 0  | ... | -5172  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 6,1035e-04$ ( $\pm 20$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 69 |
| Max CPU cycles  | 69 |
| Avg CPU cycles  | 69 |



**Verification: DT1 FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block DT1.

| Test results   |      |     |     |     |     |        |
|----------------|------|-----|-----|-----|-----|--------|
| Time step      | 1    | 2   | 3   | 4   | ... | 105    |
| CPU cycles     | 104  | 104 | 104 | 104 | ... | 104    |
| Inputs         |      |     |     |     |     |        |
| In (DSP)       | 0    | 0   | 0   | 0   | ... | -4915  |
| In             | 0    | 0   | 0   | 0   | ... | -0.15  |
| Parameters     |      |     |     |     |     |        |
| V              | 0.01 |     |     |     |     |        |
| fc             | 47   |     |     |     |     |        |
| ts_fact        | 1    |     |     |     |     |        |
| method         | zoh  |     |     |     |     |        |
| Outputs        |      |     |     |     |     |        |
| Out            | 0    | 0   | 0   | 0   | ... | -0.157 |
| Exp. Out       | 0    | 0   | 0   | 0   | ... | -0.158 |
| Out (DSP)      | 0    | 0   | 0   | 0   | ... | -5153  |
| Exp. Out (DSP) | 0    | 0   | 0   | 0   | ... | -5172  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 6,1035e-04$ ( $\pm 20$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 104 |
| Max CPU cycles  | 104 |
| Avg CPU cycles  | 104 |

**Verification: DT1 FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block DT1.

| Test results   |      |    |    |    |     |        |
|----------------|------|----|----|----|-----|--------|
| Time step      | 1    | 2  | 3  | 4  | ... | 105    |
| CPU cycles     | 96   | 96 | 96 | 96 | ... | 96     |
| Inputs         |      |    |    |    |     |        |
| In (DSP)       | 0    | 0  | 0  | 0  | ... | -4915  |
| In             | 0    | 0  | 0  | 0  | ... | -0.15  |
| Parameters     |      |    |    |    |     |        |
| V              | 0.01 |    |    |    |     |        |
| fc             | 47   |    |    |    |     |        |
| ts_fact        | 1    |    |    |    |     |        |
| method         | zoh  |    |    |    |     |        |
| Outputs        |      |    |    |    |     |        |
| Out            | 0    | 0  | 0  | 0  | ... | -0.157 |
| Exp. Out       | 0    | 0  | 0  | 0  | ... | -0.158 |
| Out (DSP)      | 0    | 0  | 0  | 0  | ... | -5153  |
| Exp. Out (DSP) | 0    | 0  | 0  | 0  | ... | -5172  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 6,1035e-04$ ( $\pm 20$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 96  |
| Max CPU cycles  | 155 |
| Avg CPU cycles  | 96  |

**Verification: DT1 FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block DT1.

| Test results   |      |    |    |    |     |        |
|----------------|------|----|----|----|-----|--------|
| Time step      | 1    | 2  | 3  | 4  | ... | 105    |
| CPU cycles     | 59   | 59 | 59 | 59 | ... | 59     |
| Inputs         |      |    |    |    |     |        |
| In (DSP)       | 0    | 0  | 0  | 0  | ... | -4915  |
| In             | 0    | 0  | 0  | 0  | ... | -0.15  |
| Parameters     |      |    |    |    |     |        |
| V              | 0.01 |    |    |    |     |        |
| fc             | 47   |    |    |    |     |        |
| ts_fact        | 1    |    |    |    |     |        |
| method         | zoh  |    |    |    |     |        |
| Outputs        |      |    |    |    |     |        |
| Out            | 0    | 0  | 0  | 0  | ... | -0.157 |
| Exp. Out       | 0    | 0  | 0  | 0  | ... | -0.158 |
| Out (DSP)      | 0    | 0  | 0  | 0  | ... | -5153  |
| Exp. Out (DSP) | 0    | 0  | 0  | 0  | ... | -5172  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 6,1035e-04$ ( $\pm 20$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 59 |
| Avg CPU cycles  | 59 |

**Verification: DT1 FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block DT1.

| Test results   |      |    |    |    |     |        |
|----------------|------|----|----|----|-----|--------|
| Time step      | 1    | 2  | 3  | 4  | ... | 105    |
| CPU cycles     | 122  | 96 | 96 | 96 | ... | 96     |
| Inputs         |      |    |    |    |     |        |
| In (DSP)       | 0    | 0  | 0  | 0  | ... | -4915  |
| In             | 0    | 0  | 0  | 0  | ... | -0.15  |
| Parameters     |      |    |    |    |     |        |
| V              | 0.01 |    |    |    |     |        |
| fc             | 47   |    |    |    |     |        |
| ts_fact        | 1    |    |    |    |     |        |
| method         | zoh  |    |    |    |     |        |
| Outputs        |      |    |    |    |     |        |
| Out            | 0    | 0  | 0  | 0  | ... | -0.157 |
| Exp. Out       | 0    | 0  | 0  | 0  | ... | -0.158 |
| Out (DSP)      | 0    | 0  | 0  | 0  | ... | -5153  |
| Exp. Out (DSP) | 0    | 0  | 0  | 0  | ... | -5172  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 6,1035e-04$ ( $\pm 20$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 96  |
| Max CPU cycles  | 122 |
| Avg CPU cycles  | 96  |

**Verification: DT1 FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block DT1.

| Test results   |      |    |    |    |     |        |
|----------------|------|----|----|----|-----|--------|
| Time step      | 1    | 2  | 3  | 4  | ... | 105    |
| CPU cycles     | 86   | 86 | 86 | 86 | ... | 86     |
| Inputs         |      |    |    |    |     |        |
| In (DSP)       | 0    | 0  | 0  | 0  | ... | -4915  |
| In             | 0    | 0  | 0  | 0  | ... | -0.15  |
| Parameters     |      |    |    |    |     |        |
| V              | 0.01 |    |    |    |     |        |
| fc             | 47   |    |    |    |     |        |
| ts_fact        | 1    |    |    |    |     |        |
| method         | zoh  |    |    |    |     |        |
| Outputs        |      |    |    |    |     |        |
| Out            | 0    | 0  | 0  | 0  | ... | -0.157 |
| Exp. Out       | 0    | 0  | 0  | 0  | ... | -0.158 |
| Out (DSP)      | 0    | 0  | 0  | 0  | ... | -5153  |
| Exp. Out (DSP) | 0    | 0  | 0  | 0  | ... | -5172  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 6,1035e-04$ ( $\pm 20$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 86 |
| Max CPU cycles  | 86 |
| Avg CPU cycles  | 86 |

**Verification: DT1 FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block DT1.

| Test results   |      |    |    |    |     |        |
|----------------|------|----|----|----|-----|--------|
| Time step      | 1    | 2  | 3  | 4  | ... | 105    |
| CPU cycles     | 91   | 91 | 91 | 91 | ... | 91     |
| Inputs         |      |    |    |    |     |        |
| In (DSP)       | 0    | 0  | 0  | 0  | ... | -4915  |
| In             | 0    | 0  | 0  | 0  | ... | -0.15  |
| Parameters     |      |    |    |    |     |        |
| V              | 0.01 |    |    |    |     |        |
| fc             | 47   |    |    |    |     |        |
| ts_fact        | 1    |    |    |    |     |        |
| method         | zoh  |    |    |    |     |        |
| Outputs        |      |    |    |    |     |        |
| Out            | 0    | 0  | 0  | 0  | ... | -0.157 |
| Exp. Out       | 0    | 0  | 0  | 0  | ... | -0.158 |
| Out (DSP)      | 0    | 0  | 0  | 0  | ... | -5153  |
| Exp. Out (DSP) | 0    | 0  | 0  | 0  | ... | -5172  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 6,1035e-04$ ( $\pm 20$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 91 |
| Max CPU cycles  | 91 |
| Avg CPU cycles  | 91 |

**Verification: DT1 FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block DT1.

| Test results   |      |     |     |            |
|----------------|------|-----|-----|------------|
| Time step      | 1    | 2   | ... | 105        |
| CPU cycles     | 221  | 221 | ... | 221        |
| Inputs         |      |     |     |            |
| In (DSP)       | 0    | 0   | ... | -322122547 |
| In             | 0    | 0   | ... | -0.15      |
| Parameters     |      |     |     |            |
| V              | 0.01 |     |     |            |
| fc             | 47   |     |     |            |
| ts_fact        | 1    |     |     |            |
| method         | zoh  |     |     |            |
| Outputs        |      |     |     |            |
| Out            | 0    | 0   | ... | -0.158     |
| Exp. Out       | 0    | 0   | ... | -0.158     |
| Out (DSP)      | 0    | 0   | ... | -338924496 |
| Exp. Out (DSP) | 0    | 0   | ... | -338924509 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 9,3132e-09$ ( $\pm 20$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 221 |
| Max CPU cycles  | 221 |
| Avg CPU cycles  | 221 |

**Verification: DT1 FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block DT1.

| Test results   |      |     |     |            |
|----------------|------|-----|-----|------------|
| Time step      | 1    | 2   | ... | 105        |
| CPU cycles     | 121  | 121 | ... | 121        |
| Inputs         |      |     |     |            |
| In (DSP)       | 0    | 0   | ... | -322122547 |
| In             | 0    | 0   | ... | -0.15      |
| Parameters     |      |     |     |            |
| V              | 0.01 |     |     |            |
| fc             | 47   |     |     |            |
| ts_fact        | 1    |     |     |            |
| method         | zoh  |     |     |            |
| Outputs        |      |     |     |            |
| Out            | 0    | 0   | ... | -0.158     |
| Exp. Out       | 0    | 0   | ... | -0.158     |
| Out (DSP)      | 0    | 0   | ... | -338924496 |
| Exp. Out (DSP) | 0    | 0   | ... | -338924509 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 9,3132e-09$ ( $\pm 20$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 121 |
| Max CPU cycles  | 121 |
| Avg CPU cycles  | 121 |



**Verification: DT1 FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block DT1.

| Test results   |      |     |     |            |
|----------------|------|-----|-----|------------|
| Time step      | 1    | 2   | ... | 105        |
| CPU cycles     | 142  | 142 | ... | 142        |
| Inputs         |      |     |     |            |
| In (DSP)       | 0    | 0   | ... | -322122547 |
| In             | 0    | 0   | ... | -0.15      |
| Parameters     |      |     |     |            |
| V              | 0.01 |     |     |            |
| fc             | 47   |     |     |            |
| ts_fact        | 1    |     |     |            |
| method         | zoh  |     |     |            |
| Outputs        |      |     |     |            |
| Out            | 0    | 0   | ... | -0.158     |
| Exp. Out       | 0    | 0   | ... | -0.158     |
| Out (DSP)      | 0    | 0   | ... | -338924496 |
| Exp. Out (DSP) | 0    | 0   | ... | -338924509 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 9,3132e-09$ ( $\pm 20$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 142 |
| Max CPU cycles  | 142 |
| Avg CPU cycles  | 142 |

**Verification: DT1 FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block DT1.

| Test results   |      |     |     |            |
|----------------|------|-----|-----|------------|
| Time step      | 1    | 2   | ... | 105        |
| CPU cycles     | 373  | 373 | ... | 381        |
| Inputs         |      |     |     |            |
| In (DSP)       | 0    | 0   | ... | -322122547 |
| In             | 0    | 0   | ... | -0.15      |
| Parameters     |      |     |     |            |
| V              | 0.01 |     |     |            |
| fc             | 47   |     |     |            |
| ts_fact        | 1    |     |     |            |
| method         | zoh  |     |     |            |
| Outputs        |      |     |     |            |
| Out            | 0    | 0   | ... | -0.158     |
| Exp. Out       | 0    | 0   | ... | -0.158     |
| Out (DSP)      | 0    | 0   | ... | -338924496 |
| Exp. Out (DSP) | 0    | 0   | ... | -338924509 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 9,3132e-09$ ( $\pm 20$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 373 |
| Max CPU cycles  | 442 |
| Avg CPU cycles  | 377 |

**Verification: DT1 FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block DT1.

| Test results   |      |    |     |            |
|----------------|------|----|-----|------------|
| Time step      | 1    | 2  | ... | 105        |
| CPU cycles     | 87   | 87 | ... | 89         |
| Inputs         |      |    |     |            |
| In (DSP)       | 0    | 0  | ... | -322122547 |
| In             | 0    | 0  | ... | -0.15      |
| Parameters     |      |    |     |            |
| V              | 0.01 |    |     |            |
| fc             | 47   |    |     |            |
| ts_fact        | 1    |    |     |            |
| method         | zoh  |    |     |            |
| Outputs        |      |    |     |            |
| Out            | 0    | 0  | ... | -0.158     |
| Exp. Out       | 0    | 0  | ... | -0.158     |
| Out (DSP)      | 0    | 0  | ... | -338924496 |
| Exp. Out (DSP) | 0    | 0  | ... | -338924509 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 9,3132e-09$ ( $\pm 20$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 87 |
| Max CPU cycles  | 89 |
| Avg CPU cycles  | 88 |

**Verification: DT1 FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block DT1.

| Test results   |      |     |     |            |
|----------------|------|-----|-----|------------|
| Time step      | 1    | 2   | ... | 105        |
| CPU cycles     | 150  | 133 | ... | 133        |
| Inputs         |      |     |     |            |
| In (DSP)       | 0    | 0   | ... | -322122547 |
| In             | 0    | 0   | ... | -0.15      |
| Parameters     |      |     |     |            |
| V              | 0.01 |     |     |            |
| fc             | 47   |     |     |            |
| ts_fact        | 1    |     |     |            |
| method         | zoh  |     |     |            |
| Outputs        |      |     |     |            |
| Out            | 0    | 0   | ... | -0.158     |
| Exp. Out       | 0    | 0   | ... | -0.158     |
| Out (DSP)      | 0    | 0   | ... | -338924496 |
| Exp. Out (DSP) | 0    | 0   | ... | -338924509 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 9,3132e-09$ ( $\pm 20$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 133 |
| Max CPU cycles  | 150 |
| Avg CPU cycles  | 133 |

**Verification: DT1 FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block DT1.

| Test results   |      |     |     |            |
|----------------|------|-----|-----|------------|
| Time step      | 1    | 2   | ... | 105        |
| CPU cycles     | 191  | 191 | ... | 191        |
| Inputs         |      |     |     |            |
| In (DSP)       | 0    | 0   | ... | -322122547 |
| In             | 0    | 0   | ... | -0.15      |
| Parameters     |      |     |     |            |
| V              | 0.01 |     |     |            |
| fc             | 47   |     |     |            |
| ts_fact        | 1    |     |     |            |
| method         | zoh  |     |     |            |
| Outputs        |      |     |     |            |
| Out            | 0    | 0   | ... | -0.158     |
| Exp. Out       | 0    | 0   | ... | -0.158     |
| Out (DSP)      | 0    | 0   | ... | -338924496 |
| Exp. Out (DSP) | 0    | 0   | ... | -338924509 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 9,3132e-09$ ( $\pm 20$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 191 |
| Max CPU cycles  | 191 |
| Avg CPU cycles  | 191 |

**Verification: DT1 FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block DT1.

| Test results   |      |      |     |            |
|----------------|------|------|-----|------------|
| Time step      | 1    | 2    | ... | 105        |
| CPU cycles     | 1025 | 1025 | ... | 1034       |
| Inputs         |      |      |     |            |
| In (DSP)       | 0    | 0    | ... | -322122547 |
| In             | 0    | 0    | ... | -0.15      |
| Parameters     |      |      |     |            |
| V              | 0.01 |      |     |            |
| fc             | 47   |      |     |            |
| ts_fact        | 1    |      |     |            |
| method         | zoh  |      |     |            |
| Outputs        |      |      |     |            |
| Out            | 0    | 0    | ... | -0.158     |
| Exp. Out       | 0    | 0    | ... | -0.158     |
| Out (DSP)      | 0    | 0    | ... | -338924496 |
| Exp. Out (DSP) | 0    | 0    | ... | -338924509 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 9,3132e-09$ ( $\pm 20$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1025 |
| Max CPU cycles  | 1034 |
| Avg CPU cycles  | 1029 |

## Block: I



I controller:

$$G(s) = K_i/s = 1/(T_i*s)$$

| Inports |                                                                                                                               |
|---------|-------------------------------------------------------------------------------------------------------------------------------|
| In      | Control error input                                                                                                           |
| I0      | Integral value which is loaded at initialization function call                                                                |
| Enable  | Enable == 0: Deactivation of block; Out set to 0<br>Enable 0->1: Preload of integral part<br>Enable == 1: Activation of block |

| Outputs |               |
|---------|---------------|
| Out     | Control value |

| Mask Parameters |    |                                                                 |
|-----------------|----|-----------------------------------------------------------------|
| Name            | ID | Description                                                     |
| Ki              | 1  | Integral Factor                                                 |
| ts_fact         | 2  | Multiplication factor of base sampling time (in integer format) |

### Description:

Each fixed point implementation uses the next higher integer datatype for the integrational value storage variable.

A rising flank at the *Enable* inport will preload the integrational part with the value present on the *Init* inport.

Transfer function (zero-order hold discretization method):

$$G(z) = K_i T_s \frac{1}{z - 1}$$

**Developer note:** The source code of block *ILimit* is used.

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP16

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |
| I0                | int16 |
| Enable            | bool  |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |
| I0                | int32 |
| Enable            | bool  |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |
| I0                | float32 |
| Enable            | bool    |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation



| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |
| I0                | float64 |
| Enable            | bool    |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: I FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block I.

| Test results   |      |      |      |      |     |        |
|----------------|------|------|------|------|-----|--------|
| Time step      | 1    | 2    | 3    | 4    | ... | 201    |
| CPU cycles     | 68   | 68   | 68   | 120  | ... | 115    |
| Inputs         |      |      |      |      |     |        |
| In (DSP)       | 0    | 0    | 0    | 0    | ... | 0      |
| I0 (DSP)       | 3604 | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0    | 0    | 0    | 1    | ... | 1      |
| In             | 0    | 0    | 0    | 0    | ... | 0      |
| I0             | 0.11 | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0    | 0    | 0    | 1    | ... | 1      |
| Parameters     |      |      |      |      |     |        |
| Ki             | 2500 |      |      |      |     |        |
| ts_fact        | 1    |      |      |      |     |        |
| Outputs        |      |      |      |      |     |        |
| Out            | 0    | 0    | 0    | 0.11 | ... | -1     |
| Exp. Out       | 0    | 0    | 0    | 0.11 | ... | -1     |
| Out (DSP)      | 0    | 0    | 0    | 3604 | ... | -32767 |
| Exp. Out (DSP) | 0    | 0    | 0    | 3604 | ... | -32768 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 68  |
| Max CPU cycles  | 124 |
| Avg CPU cycles  | 114 |

**Test case: Conversion test****OK**

Conversion test for Control block I.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block I.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1333 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2082 |
| Max CPU cycles  | 2176 |
| Avg CPU cycles  | 2166 |

**Verification: I FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block I.

| Test results   |      |      |      |      |     |        |
|----------------|------|------|------|------|-----|--------|
| Time step      | 1    | 2    | 3    | 4    | ... | 201    |
| CPU cycles     | 45   | 45   | 45   | 73   | ... | 69     |
| Inputs         |      |      |      |      |     |        |
| In (DSP)       | 0    | 0    | 0    | 0    | ... | 0      |
| I0 (DSP)       | 3604 | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0    | 0    | 0    | 1    | ... | 1      |
| In             | 0    | 0    | 0    | 0    | ... | 0      |
| I0             | 0.11 | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0    | 0    | 0    | 1    | ... | 1      |
| Parameters     |      |      |      |      |     |        |
| Ki             | 2500 |      |      |      |     |        |
| ts_fact        | 1    |      |      |      |     |        |
| Outputs        |      |      |      |      |     |        |
| Out            | 0    | 0    | 0    | 0.11 | ... | -1     |
| Exp. Out       | 0    | 0    | 0    | 0.11 | ... | -1     |
| Out (DSP)      | 0    | 0    | 0    | 3604 | ... | -32767 |
| Exp. Out (DSP) | 0    | 0    | 0    | 3604 | ... | -32768 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 45 |
| Max CPU cycles  | 81 |
| Avg CPU cycles  | 69 |

**Test case: Conversion test****OK**

Conversion test for Control block I.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block I.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1333 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1071 |
| Max CPU cycles  | 1141 |
| Avg CPU cycles  | 1139 |

**Verification: I FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block I.

| Test results   |      |      |      |      |     |        |
|----------------|------|------|------|------|-----|--------|
| Time step      | 1    | 2    | 3    | 4    | ... | 201    |
| CPU cycles     | 68   | 68   | 68   | 112  | ... | 137    |
| Inputs         |      |      |      |      |     |        |
| In (DSP)       | 0    | 0    | 0    | 0    | ... | 0      |
| I0 (DSP)       | 3604 | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0    | 0    | 0    | 1    | ... | 1      |
| In             | 0    | 0    | 0    | 0    | ... | 0      |
| I0             | 0.11 | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0    | 0    | 0    | 1    | ... | 1      |
| Parameters     |      |      |      |      |     |        |
| Ki             | 2500 |      |      |      |     |        |
| ts_fact        | 1    |      |      |      |     |        |
| Outputs        |      |      |      |      |     |        |
| Out            | 0    | 0    | 0    | 0.11 | ... | -1     |
| Exp. Out       | 0    | 0    | 0    | 0.11 | ... | -1     |
| Out (DSP)      | 0    | 0    | 0    | 3604 | ... | -32767 |
| Exp. Out (DSP) | 0    | 0    | 0    | 3604 | ... | -32768 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 68  |
| Max CPU cycles  | 141 |
| Avg CPU cycles  | 134 |

**Test case: Conversion test****OK**

Conversion test for Control block I.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block I.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1333 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1186 |
| Max CPU cycles  | 1299 |
| Avg CPU cycles  | 1225 |

**Verification: I FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block I.

| Test results   |      |      |      |      |     |        |
|----------------|------|------|------|------|-----|--------|
| Time step      | 1    | 2    | 3    | 4    | ... | 201    |
| CPU cycles     | 65   | 65   | 65   | 102  | ... | 111    |
| Inputs         |      |      |      |      |     |        |
| In (DSP)       | 0    | 0    | 0    | 0    | ... | 0      |
| I0 (DSP)       | 3604 | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0    | 0    | 0    | 1    | ... | 1      |
| In             | 0    | 0    | 0    | 0    | ... | 0      |
| I0             | 0.11 | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0    | 0    | 0    | 1    | ... | 1      |
| Parameters     |      |      |      |      |     |        |
| Ki             | 2500 |      |      |      |     |        |
| ts_fact        | 1    |      |      |      |     |        |
| Outputs        |      |      |      |      |     |        |
| Out            | 0    | 0    | 0    | 0.11 | ... | -1     |
| Exp. Out       | 0    | 0    | 0    | 0.11 | ... | -1     |
| Out (DSP)      | 0    | 0    | 0    | 3604 | ... | -32767 |
| Exp. Out (DSP) | 0    | 0    | 0    | 3604 | ... | -32768 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 65  |
| Max CPU cycles  | 111 |
| Avg CPU cycles  | 109 |

**Test case: Conversion test****OK**

Conversion test for Control block I.



| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block I.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1333 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2537 |
| Max CPU cycles  | 3021 |
| Avg CPU cycles  | 2947 |

**Verification: I FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block I.

| Test results   |      |      |      |      |     |        |
|----------------|------|------|------|------|-----|--------|
| Time step      | 1    | 2    | 3    | 4    | ... | 201    |
| CPU cycles     | 31   | 31   | 31   | 60   | ... | 61     |
| Inputs         |      |      |      |      |     |        |
| In (DSP)       | 0    | 0    | 0    | 0    | ... | 0      |
| I0 (DSP)       | 3604 | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0    | 0    | 0    | 1    | ... | 1      |
| In             | 0    | 0    | 0    | 0    | ... | 0      |
| I0             | 0.11 | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0    | 0    | 0    | 1    | ... | 1      |
| Parameters     |      |      |      |      |     |        |
| Ki             | 2500 |      |      |      |     |        |
| ts_fact        | 1    |      |      |      |     |        |
| Outputs        |      |      |      |      |     |        |
| Out            | 0    | 0    | 0    | 0.11 | ... | -1     |
| Exp. Out       | 0    | 0    | 0    | 0.11 | ... | -1     |
| Out (DSP)      | 0    | 0    | 0    | 3604 | ... | -32767 |
| Exp. Out (DSP) | 0    | 0    | 0    | 3604 | ... | -32768 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 69 |
| Avg CPU cycles  | 61 |

**Test case: Conversion test****OK**

Conversion test for Control block I.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block I.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1333 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1072 |
| Max CPU cycles  | 1188 |
| Avg CPU cycles  | 1179 |

**Verification: I FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block I.

| Test results   |      |      |      |      |     |        |
|----------------|------|------|------|------|-----|--------|
| Time step      | 1    | 2    | 3    | 4    | ... | 201    |
| CPU cycles     | 73   | 59   | 59   | 115  | ... | 90     |
| Inputs         |      |      |      |      |     |        |
| In (DSP)       | 0    | 0    | 0    | 0    | ... | 0      |
| I0 (DSP)       | 3604 | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0    | 0    | 0    | 1    | ... | 1      |
| In             | 0    | 0    | 0    | 0    | ... | 0      |
| I0             | 0.11 | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0    | 0    | 0    | 1    | ... | 1      |
| Parameters     |      |      |      |      |     |        |
| Ki             | 2500 |      |      |      |     |        |
| ts_fact        | 1    |      |      |      |     |        |
| Outputs        |      |      |      |      |     |        |
| Out            | 0    | 0    | 0    | 0.11 | ... | -1     |
| Exp. Out       | 0    | 0    | 0    | 0.11 | ... | -1     |
| Out (DSP)      | 0    | 0    | 0    | 3604 | ... | -32767 |
| Exp. Out (DSP) | 0    | 0    | 0    | 3604 | ... | -32768 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 59  |
| Max CPU cycles  | 115 |
| Avg CPU cycles  | 90  |

**Test case: Conversion test****OK**

Conversion test for Control block I.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block I.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1333 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 843 |
| Max CPU cycles  | 966 |
| Avg CPU cycles  | 864 |

**Verification: I FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block I.

| Test results   |      |      |      |      |     |        |
|----------------|------|------|------|------|-----|--------|
| Time step      | 1    | 2    | 3    | 4    | ... | 201    |
| CPU cycles     | 61   | 61   | 61   | 128  | ... | 120    |
| Inputs         |      |      |      |      |     |        |
| In (DSP)       | 0    | 0    | 0    | 0    | ... | 0      |
| I0 (DSP)       | 3604 | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0    | 0    | 0    | 1    | ... | 1      |
| In             | 0    | 0    | 0    | 0    | ... | 0      |
| I0             | 0.11 | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0    | 0    | 0    | 1    | ... | 1      |
| Parameters     |      |      |      |      |     |        |
| Ki             | 2500 |      |      |      |     |        |
| ts_fact        | 1    |      |      |      |     |        |
| Outputs        |      |      |      |      |     |        |
| Out            | 0    | 0    | 0    | 0.11 | ... | -1     |
| Exp. Out       | 0    | 0    | 0    | 0.11 | ... | -1     |
| Out (DSP)      | 0    | 0    | 0    | 3604 | ... | -32767 |
| Exp. Out (DSP) | 0    | 0    | 0    | 3604 | ... | -32768 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 61  |
| Max CPU cycles  | 128 |
| Avg CPU cycles  | 119 |

**Test case: Conversion test****OK**

Conversion test for Control block I.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block I.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1333 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1582 |
| Max CPU cycles  | 1652 |
| Avg CPU cycles  | 1647 |

**Verification: I FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block I.

| Test results   |      |      |      |      |     |        |
|----------------|------|------|------|------|-----|--------|
| Time step      | 1    | 2    | 3    | 4    | ... | 201    |
| CPU cycles     | 52   | 52   | 52   | 100  | ... | 92     |
| Inputs         |      |      |      |      |     |        |
| In (DSP)       | 0    | 0    | 0    | 0    | ... | 0      |
| I0 (DSP)       | 3604 | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0    | 0    | 0    | 1    | ... | 1      |
| In             | 0    | 0    | 0    | 0    | ... | 0      |
| I0             | 0.11 | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0    | 0    | 0    | 1    | ... | 1      |
| Parameters     |      |      |      |      |     |        |
| Ki             | 2500 |      |      |      |     |        |
| ts_fact        | 1    |      |      |      |     |        |
| Outputs        |      |      |      |      |     |        |
| Out            | 0    | 0    | 0    | 0.11 | ... | -1     |
| Exp. Out       | 0    | 0    | 0    | 0.11 | ... | -1     |
| Out (DSP)      | 0    | 0    | 0    | 3604 | ... | -32767 |
| Exp. Out (DSP) | 0    | 0    | 0    | 3604 | ... | -32768 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 52  |
| Max CPU cycles  | 101 |
| Avg CPU cycles  | 92  |

**Test case: Conversion test****OK**

Conversion test for Control block I.



| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block I.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1333 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 4133 |
| Max CPU cycles  | 5289 |
| Avg CPU cycles  | 5242 |

**Verification: I FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block I.

| Test results   |           |           |     |             |
|----------------|-----------|-----------|-----|-------------|
| Time step      | 1         | 2         | ... | 201         |
| CPU cycles     | 84        | 84        | ... | 250         |
| Inputs         |           |           |     |             |
| In (DSP)       | 0         | 0         | ... | 0           |
| I0 (DSP)       | 236223201 | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0         | 0         | ... | 1           |
| In             | 0         | 0         | ... | 0           |
| I0             | 0.11      | 0.11      | ... | 0.11        |
| Enable         | 0         | 0         | ... | 1           |
| Parameters     |           |           |     |             |
| Ki             | 2500      |           |     |             |
| ts_fact        | 1         |           |     |             |
| Outputs        |           |           |     |             |
| Out            | 0         | 0         | ... | -1          |
| Exp. Out       | 0         | 0         | ... | -1          |
| Out (DSP)      | 0         | 0         | ... | -2147483647 |
| Exp. Out (DSP) | 0         | 0         | ... | -2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 84  |
| Max CPU cycles  | 328 |
| Avg CPU cycles  | 251 |

**Test case: Conversion test****OK**

Conversion test for Control block I.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block I.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2275 |
| Max CPU cycles  | 2417 |
| Avg CPU cycles  | 2402 |

**Verification: I FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block I.

| Test results   |           |           |     |             |
|----------------|-----------|-----------|-----|-------------|
| Time step      | 1         | 2         | ... | 201         |
| CPU cycles     | 55        | 55        | ... | 127         |
| Inputs         |           |           |     |             |
| In (DSP)       | 0         | 0         | ... | 0           |
| I0 (DSP)       | 236223201 | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0         | 0         | ... | 1           |
| In             | 0         | 0         | ... | 0           |
| I0             | 0.11      | 0.11      | ... | 0.11        |
| Enable         | 0         | 0         | ... | 1           |
| Parameters     |           |           |     |             |
| Ki             | 2500      |           |     |             |
| ts_fact        | 1         |           |     |             |
| Outputs        |           |           |     |             |
| Out            | 0         | 0         | ... | -1          |
| Exp. Out       | 0         | 0         | ... | -1          |
| Out (DSP)      | 0         | 0         | ... | -2147483647 |
| Exp. Out (DSP) | 0         | 0         | ... | -2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 55  |
| Max CPU cycles  | 139 |
| Avg CPU cycles  | 126 |

**Test case: Conversion test****OK**

Conversion test for Control block I.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block I.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1027 |
| Max CPU cycles  | 1125 |
| Avg CPU cycles  | 1121 |

**Verification: I FIP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block I.

| Test results   |           |           |     |             |
|----------------|-----------|-----------|-----|-------------|
| Time step      | 1         | 2         | ... | 201         |
| CPU cycles     | 81        | 81        | ... | 169         |
| Inputs         |           |           |     |             |
| In (DSP)       | 0         | 0         | ... | 0           |
| I0 (DSP)       | 236223201 | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0         | 0         | ... | 1           |
| In             | 0         | 0         | ... | 0           |
| I0             | 0.11      | 0.11      | ... | 0.11        |
| Enable         | 0         | 0         | ... | 1           |
| Parameters     |           |           |     |             |
| Ki             | 2500      |           |     |             |
| ts_fact        | 1         |           |     |             |
| Outputs        |           |           |     |             |
| Out            | 0         | 0         | ... | -1          |
| Exp. Out       | 0         | 0         | ... | -1          |
| Out (DSP)      | 0         | 0         | ... | -2147483647 |
| Exp. Out (DSP) | 0         | 0         | ... | -2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 81  |
| Max CPU cycles  | 176 |
| Avg CPU cycles  | 167 |

**Test case: Conversion test****OK**

Conversion test for Control block I.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block I.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1563 |
| Max CPU cycles  | 1667 |
| Avg CPU cycles  | 1596 |

**Verification: I FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block I.

| Test results   |           |           |     |             |
|----------------|-----------|-----------|-----|-------------|
| Time step      | 1         | 2         | ... | 201         |
| CPU cycles     | 91        | 91        | ... | 248         |
| Inputs         |           |           |     |             |
| In (DSP)       | 0         | 0         | ... | 0           |
| I0 (DSP)       | 236223201 | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0         | 0         | ... | 1           |
| In             | 0         | 0         | ... | 0           |
| I0             | 0.11      | 0.11      | ... | 0.11        |
| Enable         | 0         | 0         | ... | 1           |
| Parameters     |           |           |     |             |
| Ki             | 2500      |           |     |             |
| ts_fact        | 1         |           |     |             |
| Outputs        |           |           |     |             |
| Out            | 0         | 0         | ... | -1          |
| Exp. Out       | 0         | 0         | ... | -1          |
| Out (DSP)      | 0         | 0         | ... | -2147483647 |
| Exp. Out (DSP) | 0         | 0         | ... | -2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 91  |
| Max CPU cycles  | 296 |
| Avg CPU cycles  | 241 |

**Test case: Conversion test****OK**

Conversion test for Control block I.



| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block I.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3570 |
| Max CPU cycles  | 4293 |
| Avg CPU cycles  | 4224 |

**Verification: I FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block I.

| Test results   |           |           |     |             |
|----------------|-----------|-----------|-----|-------------|
| Time step      | 1         | 2         | ... | 201         |
| CPU cycles     | 31        | 31        | ... | 84          |
| Inputs         |           |           |     |             |
| In (DSP)       | 0         | 0         | ... | 0           |
| I0 (DSP)       | 236223201 | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0         | 0         | ... | 1           |
| In             | 0         | 0         | ... | 0           |
| I0             | 0.11      | 0.11      | ... | 0.11        |
| Enable         | 0         | 0         | ... | 1           |
| Parameters     |           |           |     |             |
| Ki             | 2500      |           |     |             |
| ts_fact        | 1         |           |     |             |
| Outputs        |           |           |     |             |
| Out            | 0         | 0         | ... | -1          |
| Exp. Out       | 0         | 0         | ... | -1          |
| Out (DSP)      | 0         | 0         | ... | -2147483647 |
| Exp. Out (DSP) | 0         | 0         | ... | -2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 97 |
| Avg CPU cycles  | 84 |

**Test case: Conversion test****OK**

Conversion test for Control block I.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block I.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1528 |
| Max CPU cycles  | 1722 |
| Avg CPU cycles  | 1707 |

**Verification: I FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block I.

| Test results   |           |           |     |             |
|----------------|-----------|-----------|-----|-------------|
| Time step      | 1         | 2         | ... | 201         |
| CPU cycles     | 77        | 59        | ... | 130         |
| Inputs         |           |           |     |             |
| In (DSP)       | 0         | 0         | ... | 0           |
| I0 (DSP)       | 236223201 | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0         | 0         | ... | 1           |
| In             | 0         | 0         | ... | 0           |
| I0             | 0.11      | 0.11      | ... | 0.11        |
| Enable         | 0         | 0         | ... | 1           |
| Parameters     |           |           |     |             |
| Ki             | 2500      |           |     |             |
| ts_fact        | 1         |           |     |             |
| Outputs        |           |           |     |             |
| Out            | 0         | 0         | ... | -1          |
| Exp. Out       | 0         | 0         | ... | -1          |
| Out (DSP)      | 0         | 0         | ... | -2147483647 |
| Exp. Out (DSP) | 0         | 0         | ... | -2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 59  |
| Max CPU cycles  | 161 |
| Avg CPU cycles  | 129 |

**Test case: Conversion test****OK**

Conversion test for Control block I.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block I.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1165 |
| Max CPU cycles  | 1308 |
| Avg CPU cycles  | 1193 |

**Verification: I FIP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block I.

| Test results   |           |           |     |             |
|----------------|-----------|-----------|-----|-------------|
| Time step      | 1         | 2         | ... | 201         |
| CPU cycles     | 73        | 73        | ... | 227         |
| Inputs         |           |           |     |             |
| In (DSP)       | 0         | 0         | ... | 0           |
| I0 (DSP)       | 236223201 | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0         | 0         | ... | 1           |
| In             | 0         | 0         | ... | 0           |
| I0             | 0.11      | 0.11      | ... | 0.11        |
| Enable         | 0         | 0         | ... | 1           |
| Parameters     |           |           |     |             |
| Ki             | 2500      |           |     |             |
| ts_fact        | 1         |           |     |             |
| Outputs        |           |           |     |             |
| Out            | 0         | 0         | ... | -1          |
| Exp. Out       | 0         | 0         | ... | -1          |
| Out (DSP)      | 0         | 0         | ... | -2147483647 |
| Exp. Out (DSP) | 0         | 0         | ... | -2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 73  |
| Max CPU cycles  | 289 |
| Avg CPU cycles  | 228 |

**Test case: Conversion test****OK**

Conversion test for Control block I.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block I.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1692 |
| Max CPU cycles  | 1805 |
| Avg CPU cycles  | 1795 |

**Verification: I FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block I.

| Test results   |           |           |     |             |
|----------------|-----------|-----------|-----|-------------|
| Time step      | 1         | 2         | ... | 201         |
| CPU cycles     | 53        | 53        | ... | 238         |
| Inputs         |           |           |     |             |
| In (DSP)       | 0         | 0         | ... | 0           |
| I0 (DSP)       | 236223201 | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0         | 0         | ... | 1           |
| In             | 0         | 0         | ... | 0           |
| I0             | 0.11      | 0.11      | ... | 0.11        |
| Enable         | 0         | 0         | ... | 1           |
| Parameters     |           |           |     |             |
| Ki             | 2500      |           |     |             |
| ts_fact        | 1         |           |     |             |
| Outputs        |           |           |     |             |
| Out            | 0         | 0         | ... | -1          |
| Exp. Out       | 0         | 0         | ... | -1          |
| Out (DSP)      | 0         | 0         | ... | -2147483647 |
| Exp. Out (DSP) | 0         | 0         | ... | -2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 53  |
| Max CPU cycles  | 261 |
| Avg CPU cycles  | 237 |

**Test case: Conversion test****OK**

Conversion test for Control block I.



| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block I.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 4539 |
| Max CPU cycles  | 5609 |
| Avg CPU cycles  | 5551 |

**Verification: I Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block I.

| Test results   |      |      |     |       |
|----------------|------|------|-----|-------|
| Time step      | 1    | 2    | ... | 201   |
| CPU cycles     | 69   | 69   | ... | 104   |
| Inputs         |      |      |     |       |
| In (DSP)       | 0    | 0    | ... | 0     |
| I0 (DSP)       | 0.11 | 0.11 | ... | 0.11  |
| Enable (DSP)   | 0    | 0    | ... | 1     |
| In             | 0    | 0    | ... | 0     |
| I0             | 0.11 | 0.11 | ... | 0.11  |
| Enable         | 0    | 0    | ... | 1     |
| Parameters     |      |      |     |       |
| Ki             | 2500 |      |     |       |
| ts_fact        | 1    |      |     |       |
| Outputs        |      |      |     |       |
| Out            | 0    | 0    | ... | -1.84 |
| Exp. Out       | 0    | 0    | ... | -1.84 |
| Out (DSP)      | 0    | 0    | ... | -1.84 |
| Exp. Out (DSP) | 0    | 0    | ... | -1.84 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 69  |
| Max CPU cycles  | 109 |
| Avg CPU cycles  | 103 |

**Test case: Conversion test****OK**

Conversion test for Control block I.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block I.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e-08$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1495 |
| Max CPU cycles  | 1518 |
| Avg CPU cycles  | 1500 |

**Verification: I Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block I.

| Test results   |      |      |     |       |
|----------------|------|------|-----|-------|
| Time step      | 1    | 2    | ... | 201   |
| CPU cycles     | 41   | 41   | ... | 77    |
| Inputs         |      |      |     |       |
| In (DSP)       | 0    | 0    | ... | 0     |
| I0 (DSP)       | 0.11 | 0.11 | ... | 0.11  |
| Enable (DSP)   | 0    | 0    | ... | 1     |
| In             | 0    | 0    | ... | 0     |
| I0             | 0.11 | 0.11 | ... | 0.11  |
| Enable         | 0    | 0    | ... | 1     |
| Parameters     |      |      |     |       |
| Ki             | 2500 |      |     |       |
| ts_fact        | 1    |      |     |       |
| Outputs        |      |      |     |       |
| Out            | 0    | 0    | ... | -1.84 |
| Exp. Out       | 0    | 0    | ... | -1.84 |
| Out (DSP)      | 0    | 0    | ... | -1.84 |
| Exp. Out (DSP) | 0    | 0    | ... | -1.84 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 41 |
| Max CPU cycles  | 77 |
| Avg CPU cycles  | 76 |

**Test case: Conversion test****OK**

Conversion test for Control block I.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block I.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 741 |
| Max CPU cycles  | 741 |
| Avg CPU cycles  | 741 |

**Verification: I Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block I.

| Test results   |      |      |     |       |
|----------------|------|------|-----|-------|
| Time step      | 1    | 2    | ... | 201   |
| CPU cycles     | 78   | 78   | ... | 123   |
| Inputs         |      |      |     |       |
| In (DSP)       | 0    | 0    | ... | 0     |
| I0 (DSP)       | 0.11 | 0.11 | ... | 0.11  |
| Enable (DSP)   | 0    | 0    | ... | 1     |
| In             | 0    | 0    | ... | 0     |
| I0             | 0.11 | 0.11 | ... | 0.11  |
| Enable         | 0    | 0    | ... | 1     |
| Parameters     |      |      |     |       |
| Ki             | 2500 |      |     |       |
| ts_fact        | 1    |      |     |       |
| Outputs        |      |      |     |       |
| Out            | 0    | 0    | ... | -1.84 |
| Exp. Out       | 0    | 0    | ... | -1.84 |
| Out (DSP)      | 0    | 0    | ... | -1.84 |
| Exp. Out (DSP) | 0    | 0    | ... | -1.84 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 78  |
| Max CPU cycles  | 130 |
| Avg CPU cycles  | 122 |

**Test case: Conversion test****OK**

Conversion test for Control block I.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block I.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 771 |
| Max CPU cycles  | 868 |
| Avg CPU cycles  | 806 |

**Verification: I Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block I.

| Test results   |      |      |     |       |
|----------------|------|------|-----|-------|
| Time step      | 1    | 2    | ... | 201   |
| CPU cycles     | 73   | 73   | ... | 467   |
| Inputs         |      |      |     |       |
| In (DSP)       | 0    | 0    | ... | 0     |
| I0 (DSP)       | 0.11 | 0.11 | ... | 0.11  |
| Enable (DSP)   | 0    | 0    | ... | 1     |
| In             | 0    | 0    | ... | 0     |
| I0             | 0.11 | 0.11 | ... | 0.11  |
| Enable         | 0    | 0    | ... | 1     |
| Parameters     |      |      |     |       |
| Ki             | 2500 |      |     |       |
| ts_fact        | 1    |      |     |       |
| Outputs        |      |      |     |       |
| Out            | 0    | 0    | ... | -1.84 |
| Exp. Out       | 0    | 0    | ... | -1.84 |
| Out (DSP)      | 0    | 0    | ... | -1.84 |
| Exp. Out (DSP) | 0    | 0    | ... | -1.84 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 73  |
| Max CPU cycles  | 643 |
| Avg CPU cycles  | 542 |

**Test case: Conversion test****OK**

Conversion test for Control block I.



| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block I.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e-08$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1589 |
| Max CPU cycles  | 1735 |
| Avg CPU cycles  | 1670 |

**Verification: I Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block I.

| Test results   |      |      |     |       |
|----------------|------|------|-----|-------|
| Time step      | 1    | 2    | ... | 201   |
| CPU cycles     | 57   | 57   | ... | 214   |
| Inputs         |      |      |     |       |
| In (DSP)       | 0    | 0    | ... | 0     |
| I0 (DSP)       | 0.11 | 0.11 | ... | 0.11  |
| Enable (DSP)   | 0    | 0    | ... | 1     |
| In             | 0    | 0    | ... | 0     |
| I0             | 0.11 | 0.11 | ... | 0.11  |
| Enable         | 0    | 0    | ... | 1     |
| Parameters     |      |      |     |       |
| Ki             | 2500 |      |     |       |
| ts_fact        | 1    |      |     |       |
| Outputs        |      |      |     |       |
| Out            | 0    | 0    | ... | -1.84 |
| Exp. Out       | 0    | 0    | ... | -1.84 |
| Out (DSP)      | 0    | 0    | ... | -1.84 |
| Exp. Out (DSP) | 0    | 0    | ... | -1.84 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 57  |
| Max CPU cycles  | 264 |
| Avg CPU cycles  | 241 |

**Test case: Conversion test****OK**

Conversion test for Control block I.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block I.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 583 |
| Max CPU cycles  | 602 |
| Avg CPU cycles  | 597 |

**Verification: I Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block I.

| Test results   |      |      |     |       |
|----------------|------|------|-----|-------|
| Time step      | 1    | 2    | ... | 201   |
| CPU cycles     | 79   | 60   | ... | 93    |
| Inputs         |      |      |     |       |
| In (DSP)       | 0    | 0    | ... | 0     |
| I0 (DSP)       | 0.11 | 0.11 | ... | 0.11  |
| Enable (DSP)   | 0    | 0    | ... | 1     |
| In             | 0    | 0    | ... | 0     |
| I0             | 0.11 | 0.11 | ... | 0.11  |
| Enable         | 0    | 0    | ... | 1     |
| Parameters     |      |      |     |       |
| Ki             | 2500 |      |     |       |
| ts_fact        | 1    |      |     |       |
| Outputs        |      |      |     |       |
| Out            | 0    | 0    | ... | -1.84 |
| Exp. Out       | 0    | 0    | ... | -1.84 |
| Out (DSP)      | 0    | 0    | ... | -1.84 |
| Exp. Out (DSP) | 0    | 0    | ... | -1.84 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 60  |
| Max CPU cycles  | 110 |
| Avg CPU cycles  | 92  |

**Test case: Conversion test****OK**

Conversion test for Control block I.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block I.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 595 |
| Max CPU cycles  | 683 |
| Avg CPU cycles  | 614 |

**Verification: I Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block I.

| Test results   |      |      |     |       |
|----------------|------|------|-----|-------|
| Time step      | 1    | 2    | ... | 201   |
| CPU cycles     | 65   | 65   | ... | 105   |
| Inputs         |      |      |     |       |
| In (DSP)       | 0    | 0    | ... | 0     |
| I0 (DSP)       | 0.11 | 0.11 | ... | 0.11  |
| Enable (DSP)   | 0    | 0    | ... | 1     |
| In             | 0    | 0    | ... | 0     |
| I0             | 0.11 | 0.11 | ... | 0.11  |
| Enable         | 0    | 0    | ... | 1     |
| Parameters     |      |      |     |       |
| Ki             | 2500 |      |     |       |
| ts_fact        | 1    |      |     |       |
| Outputs        |      |      |     |       |
| Out            | 0    | 0    | ... | -1.84 |
| Exp. Out       | 0    | 0    | ... | -1.84 |
| Out (DSP)      | 0    | 0    | ... | -1.84 |
| Exp. Out (DSP) | 0    | 0    | ... | -1.84 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 65  |
| Max CPU cycles  | 108 |
| Avg CPU cycles  | 104 |

**Test case: Conversion test****OK**

Conversion test for Control block I.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block I.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e-08$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1163 |
| Max CPU cycles  | 1179 |
| Avg CPU cycles  | 1165 |

**Verification: I Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block I.

| Test results   |      |      |     |       |
|----------------|------|------|-----|-------|
| Time step      | 1    | 2    | ... | 201   |
| CPU cycles     | 59   | 59   | ... | 500   |
| Inputs         |      |      |     |       |
| In (DSP)       | 0    | 0    | ... | 0     |
| I0 (DSP)       | 0.11 | 0.11 | ... | 0.11  |
| Enable (DSP)   | 0    | 0    | ... | 1     |
| In             | 0    | 0    | ... | 0     |
| I0             | 0.11 | 0.11 | ... | 0.11  |
| Enable         | 0    | 0    | ... | 1     |
| Parameters     |      |      |     |       |
| Ki             | 2500 |      |     |       |
| ts_fact        | 1    |      |     |       |
| Outputs        |      |      |     |       |
| Out            | 0    | 0    | ... | -1.84 |
| Exp. Out       | 0    | 0    | ... | -1.84 |
| Out (DSP)      | 0    | 0    | ... | -1.84 |
| Exp. Out (DSP) | 0    | 0    | ... | -1.84 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 59  |
| Max CPU cycles  | 659 |
| Avg CPU cycles  | 589 |

**Test case: Conversion test****OK**

Conversion test for Control block I.



| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK


Conversion-on-Target test for Control block I.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e-08$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2155 |
| Max CPU cycles  | 2551 |
| Avg CPU cycles  | 2531 |

## Block: ILimit



I controller with output limitation:

$$G(s) = K_i/s = 1/(T_i \cdot s)$$

| Inports |                                                                                                                               |
|---------|-------------------------------------------------------------------------------------------------------------------------------|
| In      | Control error input                                                                                                           |
| I0      | Integral value which is loaded at initialization function call                                                                |
| max     | Maximum output value                                                                                                          |
| min     | Minimum output value                                                                                                          |
| Enable  | Enable == 0: Deactivation of block; Out set to 0<br>Enable 0->1: Preload of integral part<br>Enable == 1: Activation of block |

| Outputs |               |
|---------|---------------|
| Out     | Control value |

| Mask Parameters |    |                                                                 |
|-----------------|----|-----------------------------------------------------------------|
| Name            | ID | Description                                                     |
| Ki              | 1  | Integral Factor                                                 |
| ts_fact         | 2  | Multiplication factor of base sampling time (in integer format) |

### Description:

Each fixed point implementation uses the next higher integer datatype for the integrational value storage variable.

A rising flank at the *Enable* input will preload the integrational part with the value present on the *Init* input.

Transfer function (zero-order hold discretization method):

$$G(z) = K_i T_s \frac{1}{z - 1}$$

**Developer note:** The source code of this block is used for block *I*.

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP16

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |
| I0                | int16 |
| max               | int16 |
| min               | int16 |
| Enable            | bool  |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |
| I0                | int32 |
| max               | int32 |
| min               | int32 |
| Enable            | bool  |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |
| I0                | float32 |
| max               | float32 |
| min               | float32 |
| Enable            | bool    |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

## Implementation: Float64

---

### 64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |
| I0                | float64 |
| max               | float64 |
| min               | float64 |
| Enable            | bool    |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: ILimit FiP16 CPU TMS320F28335**

Date of Test 2026-06-19  
Target controller TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block ILimit.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 69    | 69    | 69    | 134   | ... | 120   |
| Inputs         |       |       |       |       |     |       |
| In (DSP)       | 0     | 0     | 0     | 0     | ... | 0     |
| I0 (DSP)       | 3604  | 3604  | 3604  | 3604  | ... | 3604  |
| max (DSP)      | 26214 | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915  | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0     | 0     | 0     | 1     | ... | 1     |
| In             | 0     | 0     | 0     | 0     | ... | 0     |
| I0             | 0.11  | 0.11  | 0.11  | 0.11  | ... | 0.11  |
| max            | 0.8   | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15  | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0     | 0     | 0     | 1     | ... | 1     |
| Parameters     |       |       |       |       |     |       |
| Ki             | 2500  |       |       |       |     |       |
| ts_fact        | 1     |       |       |       |     |       |
| Outputs        |       |       |       |       |     |       |
| Out            | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Exp. Out       | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Out (DSP)      | 0     | 0     | 0     | 4915  | ... | 4915  |
| Exp. Out (DSP) | 0     | 0     | 0     | 4915  | ... | 4915  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 69  |
| Max CPU cycles  | 134 |
| Avg CPU cycles  | 119 |

**Test case: Conversion test****OK**

Conversion test for Control block ILimit.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ILimit.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1333 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2076 |
| Max CPU cycles  | 2170 |
| Avg CPU cycles  | 2160 |

**Verification: ILimit FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block ILimit.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 47    | 47    | 47    | 93    | ... | 77    |
| Inputs         |       |       |       |       |     |       |
| In (DSP)       | 0     | 0     | 0     | 0     | ... | 0     |
| I0 (DSP)       | 3604  | 3604  | 3604  | 3604  | ... | 3604  |
| max (DSP)      | 26214 | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915  | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0     | 0     | 0     | 1     | ... | 1     |
| In             | 0     | 0     | 0     | 0     | ... | 0     |
| I0             | 0.11  | 0.11  | 0.11  | 0.11  | ... | 0.11  |
| max            | 0.8   | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15  | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0     | 0     | 0     | 1     | ... | 1     |
| Parameters     |       |       |       |       |     |       |
| Ki             | 2500  |       |       |       |     |       |
| ts_fact        | 1     |       |       |       |     |       |
| Outputs        |       |       |       |       |     |       |
| Out            | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Exp. Out       | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Out (DSP)      | 0     | 0     | 0     | 4915  | ... | 4915  |
| Exp. Out (DSP) | 0     | 0     | 0     | 4915  | ... | 4915  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 47 |
| Max CPU cycles  | 93 |
| Avg CPU cycles  | 77 |

**Test case: Conversion test****OK**

Conversion test for Control block ILimit.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ILimit.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1333 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1071 |
| Max CPU cycles  | 1141 |
| Avg CPU cycles  | 1139 |



**Verification: ILimit FiP16 CPU STM32G474RE**

Date of Test 2026-06-19  
Target controller STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block ILimit.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 71    | 71    | 71    | 137   | ... | 121   |
| Inputs         |       |       |       |       |     |       |
| In (DSP)       | 0     | 0     | 0     | 0     | ... | 0     |
| I0 (DSP)       | 3604  | 3604  | 3604  | 3604  | ... | 3604  |
| max (DSP)      | 26214 | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915  | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0     | 0     | 0     | 1     | ... | 1     |
| In             | 0     | 0     | 0     | 0     | ... | 0     |
| I0             | 0.11  | 0.11  | 0.11  | 0.11  | ... | 0.11  |
| max            | 0.8   | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15  | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0     | 0     | 0     | 1     | ... | 1     |
| Parameters     |       |       |       |       |     |       |
| Ki             | 2500  |       |       |       |     |       |
| ts_fact        | 1     |       |       |       |     |       |
| Outputs        |       |       |       |       |     |       |
| Out            | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Exp. Out       | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Out (DSP)      | 0     | 0     | 0     | 4915  | ... | 4915  |
| Exp. Out (DSP) | 0     | 0     | 0     | 4915  | ... | 4915  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 71  |
| Max CPU cycles  | 137 |
| Avg CPU cycles  | 119 |

**Test case: Conversion test****OK**

Conversion test for Control block ILimit.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ILimit.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1333 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1180 |
| Max CPU cycles  | 1235 |
| Avg CPU cycles  | 1217 |

**Verification: ILimit FiP16 CPU STM32F072RB**

Date of Test 2026-06-19  
Target controller STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block ILimit.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 66    | 66    | 66    | 125   | ... | 113   |
| Inputs         |       |       |       |       |     |       |
| In (DSP)       | 0     | 0     | 0     | 0     | ... | 0     |
| I0 (DSP)       | 3604  | 3604  | 3604  | 3604  | ... | 3604  |
| max (DSP)      | 26214 | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915  | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0     | 0     | 0     | 1     | ... | 1     |
| In             | 0     | 0     | 0     | 0     | ... | 0     |
| I0             | 0.11  | 0.11  | 0.11  | 0.11  | ... | 0.11  |
| max            | 0.8   | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15  | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0     | 0     | 0     | 1     | ... | 1     |
| Parameters     |       |       |       |       |     |       |
| Ki             | 2500  |       |       |       |     |       |
| ts_fact        | 1     |       |       |       |     |       |
| Outputs        |       |       |       |       |     |       |
| Out            | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Exp. Out       | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Out (DSP)      | 0     | 0     | 0     | 4915  | ... | 4915  |
| Exp. Out (DSP) | 0     | 0     | 0     | 4915  | ... | 4915  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 66  |
| Max CPU cycles  | 125 |
| Avg CPU cycles  | 110 |

**Test case: Conversion test****OK**

Conversion test for Control block ILimit.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ILimit.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1333 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2537 |
| Max CPU cycles  | 3016 |
| Avg CPU cycles  | 2946 |

**Verification: ILimit FiP16 CPU PIC32MX170F256**

Date of Test 2026-06-19  
Target controller PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block ILimit.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 31    | 31    | 31    | 81    | ... | 70    |
| Inputs         |       |       |       |       |     |       |
| In (DSP)       | 0     | 0     | 0     | 0     | ... | 0     |
| I0 (DSP)       | 3604  | 3604  | 3604  | 3604  | ... | 3604  |
| max (DSP)      | 26214 | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915  | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0     | 0     | 0     | 1     | ... | 1     |
| In             | 0     | 0     | 0     | 0     | ... | 0     |
| I0             | 0.11  | 0.11  | 0.11  | 0.11  | ... | 0.11  |
| max            | 0.8   | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15  | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0     | 0     | 0     | 1     | ... | 1     |
| Parameters     |       |       |       |       |     |       |
| Ki             | 2500  |       |       |       |     |       |
| ts_fact        | 1     |       |       |       |     |       |
| Outputs        |       |       |       |       |     |       |
| Out            | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Exp. Out       | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Out (DSP)      | 0     | 0     | 0     | 4915  | ... | 4915  |
| Exp. Out (DSP) | 0     | 0     | 0     | 4915  | ... | 4915  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 81 |
| Avg CPU cycles  | 69 |

**Test case: Conversion test****OK**

Conversion test for Control block ILimit.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ILimit.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1333 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1072 |
| Max CPU cycles  | 1188 |
| Avg CPU cycles  | 1179 |

**Verification: ILimit FiP16 CPU XMC4800-F144K2048**

Date of Test 2026-06-19  
Target controller XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block ILimit.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 74    | 59    | 59    | 119   | ... | 102   |
| Inputs         |       |       |       |       |     |       |
| In (DSP)       | 0     | 0     | 0     | 0     | ... | 0     |
| I0 (DSP)       | 3604  | 3604  | 3604  | 3604  | ... | 3604  |
| max (DSP)      | 26214 | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915  | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0     | 0     | 0     | 1     | ... | 1     |
| In             | 0     | 0     | 0     | 0     | ... | 0     |
| I0             | 0.11  | 0.11  | 0.11  | 0.11  | ... | 0.11  |
| max            | 0.8   | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15  | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0     | 0     | 0     | 1     | ... | 1     |
| Parameters     |       |       |       |       |     |       |
| Ki             | 2500  |       |       |       |     |       |
| ts_fact        | 1     |       |       |       |     |       |
| Outputs        |       |       |       |       |     |       |
| Out            | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Exp. Out       | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Out (DSP)      | 0     | 0     | 0     | 4915  | ... | 4915  |
| Exp. Out (DSP) | 0     | 0     | 0     | 4915  | ... | 4915  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 59  |
| Max CPU cycles  | 119 |
| Avg CPU cycles  | 100 |

**Test case: Conversion test****OK**

Conversion test for Control block ILimit.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ILimit.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1333 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 833 |
| Max CPU cycles  | 941 |
| Avg CPU cycles  | 854 |



**Verification: ILimit FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block ILimit.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 65    | 65    | 65    | 137   | ... | 125   |
| Inputs         |       |       |       |       |     |       |
| In (DSP)       | 0     | 0     | 0     | 0     | ... | 0     |
| I0 (DSP)       | 3604  | 3604  | 3604  | 3604  | ... | 3604  |
| max (DSP)      | 26214 | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915  | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0     | 0     | 0     | 1     | ... | 1     |
| In             | 0     | 0     | 0     | 0     | ... | 0     |
| I0             | 0.11  | 0.11  | 0.11  | 0.11  | ... | 0.11  |
| max            | 0.8   | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15  | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0     | 0     | 0     | 1     | ... | 1     |
| Parameters     |       |       |       |       |     |       |
| Ki             | 2500  |       |       |       |     |       |
| ts_fact        | 1     |       |       |       |     |       |
| Outputs        |       |       |       |       |     |       |
| Out            | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Exp. Out       | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Out (DSP)      | 0     | 0     | 0     | 4915  | ... | 4915  |
| Exp. Out (DSP) | 0     | 0     | 0     | 4915  | ... | 4915  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 65  |
| Max CPU cycles  | 137 |
| Avg CPU cycles  | 124 |

**Test case: Conversion test****OK**

Conversion test for Control block ILimit.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ILimit.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1333 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1579 |
| Max CPU cycles  | 1649 |
| Avg CPU cycles  | 1644 |

**Verification: ILimit FiP16 CPU dsPIC33EP256MC502**

Date of Test 2026-06-23  
Target controller dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block ILimit.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 52    | 52    | 52    | 115   | ... | 103   |
| Inputs         |       |       |       |       |     |       |
| In (DSP)       | 0     | 0     | 0     | 0     | ... | 0     |
| I0 (DSP)       | 3604  | 3604  | 3604  | 3604  | ... | 3604  |
| max (DSP)      | 26214 | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915  | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0     | 0     | 0     | 1     | ... | 1     |
| In             | 0     | 0     | 0     | 0     | ... | 0     |
| I0             | 0.11  | 0.11  | 0.11  | 0.11  | ... | 0.11  |
| max            | 0.8   | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15  | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0     | 0     | 0     | 1     | ... | 1     |
| Parameters     |       |       |       |       |     |       |
| Ki             | 2500  |       |       |       |     |       |
| ts_fact        | 1     |       |       |       |     |       |
| Outputs        |       |       |       |       |     |       |
| Out            | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Exp. Out       | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Out (DSP)      | 0     | 0     | 0     | 4915  | ... | 4915  |
| Exp. Out (DSP) | 0     | 0     | 0     | 4915  | ... | 4915  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 52  |
| Max CPU cycles  | 115 |
| Avg CPU cycles  | 102 |

**Test case: Conversion test****OK**

Conversion test for Control block ILimit.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ILimit.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1333 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 4133 |
| Max CPU cycles  | 5289 |
| Avg CPU cycles  | 5242 |

**Verification: ILimit FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block ILimit.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 201        |
| CPU cycles     | 85         | 85         | ... | 245        |
| Inputs         |            |            |     |            |
| In (DSP)       | 0          | 0          | ... | 0          |
| I0 (DSP)       | 236223201  | 236223201  | ... | 236223201  |
| max (DSP)      | 1717986918 | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547  | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0          | 0          | ... | 1          |
| In             | 0          | 0          | ... | 0          |
| I0             | 0.11       | 0.11       | ... | 0.11       |
| max            | 0.8        | 0.8        | ... | 0.8        |
| min            | 0.15       | 0.15       | ... | 0.15       |
| Enable         | 0          | 0          | ... | 1          |
| Parameters     |            |            |     |            |
| Ki             | 2500       |            |     |            |
| ts_fact        | 1          |            |     |            |
| Outputs        |            |            |     |            |
| Out            | 0          | 0          | ... | 0.15       |
| Exp. Out       | 0          | 0          | ... | 0.15       |
| Out (DSP)      | 0          | 0          | ... | 322122547  |
| Exp. Out (DSP) | 0          | 0          | ... | 322122547  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 85  |
| Max CPU cycles  | 333 |
| Avg CPU cycles  | 254 |

**Test case: Conversion test****OK**

Conversion test for Control block ILimit.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ILimit.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2274 |
| Max CPU cycles  | 2416 |
| Avg CPU cycles  | 2401 |

**Verification: ILimit FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block ILimit.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 201        |
| CPU cycles     | 55         | 55         | ... | 129        |
| Inputs         |            |            |     |            |
| In (DSP)       | 0          | 0          | ... | 0          |
| I0 (DSP)       | 236223201  | 236223201  | ... | 236223201  |
| max (DSP)      | 1717986918 | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547  | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0          | 0          | ... | 1          |
| In             | 0          | 0          | ... | 0          |
| I0             | 0.11       | 0.11       | ... | 0.11       |
| max            | 0.8        | 0.8        | ... | 0.8        |
| min            | 0.15       | 0.15       | ... | 0.15       |
| Enable         | 0          | 0          | ... | 1          |
| Parameters     |            |            |     |            |
| Ki             | 2500       |            |     |            |
| ts_fact        | 1          |            |     |            |
| Outputs        |            |            |     |            |
| Out            | 0          | 0          | ... | 0.15       |
| Exp. Out       | 0          | 0          | ... | 0.15       |
| Out (DSP)      | 0          | 0          | ... | 322122547  |
| Exp. Out (DSP) | 0          | 0          | ... | 322122547  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 55  |
| Max CPU cycles  | 153 |
| Avg CPU cycles  | 130 |

**Test case: Conversion test****OK**

Conversion test for Control block ILimit.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ILimit.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1027 |
| Max CPU cycles  | 1125 |
| Avg CPU cycles  | 1121 |



**Verification: ILimit FiP32 CPU STM32G474RE**

Date of Test 2026-06-19  
Target controller STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block ILimit.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 201        |
| CPU cycles     | 82         | 82         | ... | 154        |
| Inputs         |            |            |     |            |
| In (DSP)       | 0          | 0          | ... | 0          |
| I0 (DSP)       | 236223201  | 236223201  | ... | 236223201  |
| max (DSP)      | 1717986918 | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547  | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0          | 0          | ... | 1          |
| In             | 0          | 0          | ... | 0          |
| I0             | 0.11       | 0.11       | ... | 0.11       |
| max            | 0.8        | 0.8        | ... | 0.8        |
| min            | 0.15       | 0.15       | ... | 0.15       |
| Enable         | 0          | 0          | ... | 1          |
| Parameters     |            |            |     |            |
| Ki             | 2500       |            |     |            |
| ts_fact        | 1          |            |     |            |
| Outputs        |            |            |     |            |
| Out            | 0          | 0          | ... | 0.15       |
| Exp. Out       | 0          | 0          | ... | 0.15       |
| Out (DSP)      | 0          | 0          | ... | 322122547  |
| Exp. Out (DSP) | 0          | 0          | ... | 322122547  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 82  |
| Max CPU cycles  | 182 |
| Avg CPU cycles  | 152 |

**Test case: Conversion test****OK**

Conversion test for Control block ILimit.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ILimit.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1555 |
| Max CPU cycles  | 1614 |
| Avg CPU cycles  | 1599 |

**Verification: ILimit FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block ILimit.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 201        |
| CPU cycles     | 88         | 88         | ... | 253        |
| Inputs         |            |            |     |            |
| In (DSP)       | 0          | 0          | ... | 0          |
| I0 (DSP)       | 236223201  | 236223201  | ... | 236223201  |
| max (DSP)      | 1717986918 | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547  | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0          | 0          | ... | 1          |
| In             | 0          | 0          | ... | 0          |
| I0             | 0.11       | 0.11       | ... | 0.11       |
| max            | 0.8        | 0.8        | ... | 0.8        |
| min            | 0.15       | 0.15       | ... | 0.15       |
| Enable         | 0          | 0          | ... | 1          |
| Parameters     |            |            |     |            |
| Ki             | 2500       |            |     |            |
| ts_fact        | 1          |            |     |            |
| Outputs        |            |            |     |            |
| Out            | 0          | 0          | ... | 0.15       |
| Exp. Out       | 0          | 0          | ... | 0.15       |
| Out (DSP)      | 0          | 0          | ... | 322122547  |
| Exp. Out (DSP) | 0          | 0          | ... | 322122547  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 88  |
| Max CPU cycles  | 313 |
| Avg CPU cycles  | 251 |

**Test case: Conversion test****OK**

Conversion test for Control block ILimit.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ILimit.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3571 |
| Max CPU cycles  | 4311 |
| Avg CPU cycles  | 4227 |

**Verification: ILimit FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block ILimit.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 201        |
| CPU cycles     | 31         | 31         | ... | 104        |
| Inputs         |            |            |     |            |
| In (DSP)       | 0          | 0          | ... | 0          |
| I0 (DSP)       | 236223201  | 236223201  | ... | 236223201  |
| max (DSP)      | 1717986918 | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547  | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0          | 0          | ... | 1          |
| In             | 0          | 0          | ... | 0          |
| I0             | 0.11       | 0.11       | ... | 0.11       |
| max            | 0.8        | 0.8        | ... | 0.8        |
| min            | 0.15       | 0.15       | ... | 0.15       |
| Enable         | 0          | 0          | ... | 1          |
| Parameters     |            |            |     |            |
| Ki             | 2500       |            |     |            |
| ts_fact        | 1          |            |     |            |
| Outputs        |            |            |     |            |
| Out            | 0          | 0          | ... | 0.15       |
| Exp. Out       | 0          | 0          | ... | 0.15       |
| Out (DSP)      | 0          | 0          | ... | 322122547  |
| Exp. Out (DSP) | 0          | 0          | ... | 322122547  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 31  |
| Max CPU cycles  | 114 |
| Avg CPU cycles  | 102 |

**Test case: Conversion test****OK**

Conversion test for Control block ILimit.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ILimit.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1528 |
| Max CPU cycles  | 1722 |
| Avg CPU cycles  | 1707 |

**Verification: ILimit FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block ILimit.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 201        |
| CPU cycles     | 99         | 79         | ... | 137        |
| Inputs         |            |            |     |            |
| In (DSP)       | 0          | 0          | ... | 0          |
| I0 (DSP)       | 236223201  | 236223201  | ... | 236223201  |
| max (DSP)      | 1717986918 | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547  | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0          | 0          | ... | 1          |
| In             | 0          | 0          | ... | 0          |
| I0             | 0.11       | 0.11       | ... | 0.11       |
| max            | 0.8        | 0.8        | ... | 0.8        |
| min            | 0.15       | 0.15       | ... | 0.15       |
| Enable         | 0          | 0          | ... | 1          |
| Parameters     |            |            |     |            |
| Ki             | 2500       |            |     |            |
| ts_fact        | 1          |            |     |            |
| Outputs        |            |            |     |            |
| Out            | 0          | 0          | ... | 0.15       |
| Exp. Out       | 0          | 0          | ... | 0.15       |
| Out (DSP)      | 0          | 0          | ... | 322122547  |
| Exp. Out (DSP) | 0          | 0          | ... | 322122547  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 79  |
| Max CPU cycles  | 172 |
| Avg CPU cycles  | 136 |

**Test case: Conversion test****OK**

Conversion test for Control block ILimit.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ILimit.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1092 |
| Max CPU cycles  | 1271 |
| Avg CPU cycles  | 1121 |



**Verification: ILimit FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block ILimit.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 201        |
| CPU cycles     | 70         | 70         | ... | 226        |
| Inputs         |            |            |     |            |
| In (DSP)       | 0          | 0          | ... | 0          |
| I0 (DSP)       | 236223201  | 236223201  | ... | 236223201  |
| max (DSP)      | 1717986918 | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547  | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0          | 0          | ... | 1          |
| In             | 0          | 0          | ... | 0          |
| I0             | 0.11       | 0.11       | ... | 0.11       |
| max            | 0.8        | 0.8        | ... | 0.8        |
| min            | 0.15       | 0.15       | ... | 0.15       |
| Enable         | 0          | 0          | ... | 1          |
| Parameters     |            |            |     |            |
| Ki             | 2500       |            |     |            |
| ts_fact        | 1          |            |     |            |
| Outputs        |            |            |     |            |
| Out            | 0          | 0          | ... | 0.15       |
| Exp. Out       | 0          | 0          | ... | 0.15       |
| Out (DSP)      | 0          | 0          | ... | 322122547  |
| Exp. Out (DSP) | 0          | 0          | ... | 322122547  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 70  |
| Max CPU cycles  | 295 |
| Avg CPU cycles  | 232 |

**Test case: Conversion test****OK**

Conversion test for Control block ILimit.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ILimit.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1688 |
| Max CPU cycles  | 1801 |
| Avg CPU cycles  | 1791 |

**Verification: ILimit FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block ILimit.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 201        |
| CPU cycles     | 55         | 55         | ... | 267        |
| Inputs         |            |            |     |            |
| In (DSP)       | 0          | 0          | ... | 0          |
| I0 (DSP)       | 236223201  | 236223201  | ... | 236223201  |
| max (DSP)      | 1717986918 | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547  | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0          | 0          | ... | 1          |
| In             | 0          | 0          | ... | 0          |
| I0             | 0.11       | 0.11       | ... | 0.11       |
| max            | 0.8        | 0.8        | ... | 0.8        |
| min            | 0.15       | 0.15       | ... | 0.15       |
| Enable         | 0          | 0          | ... | 1          |
| Parameters     |            |            |     |            |
| Ki             | 2500       |            |     |            |
| ts_fact        | 1          |            |     |            |
| Outputs        |            |            |     |            |
| Out            | 0          | 0          | ... | 0.15       |
| Exp. Out       | 0          | 0          | ... | 0.15       |
| Out (DSP)      | 0          | 0          | ... | 322122547  |
| Exp. Out (DSP) | 0          | 0          | ... | 322122547  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 55  |
| Max CPU cycles  | 293 |
| Avg CPU cycles  | 266 |

**Test case: Conversion test****OK**

Conversion test for Control block ILimit.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ILimit.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 4539 |
| Max CPU cycles  | 5609 |
| Avg CPU cycles  | 5551 |

**Verification: ILimit Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block ILimit.

| Test results   |      |      |     |      |
|----------------|------|------|-----|------|
| Time step      | 1    | 2    | ... | 201  |
| CPU cycles     | 73   | 73   | ... | 113  |
| Inputs         |      |      |     |      |
| In (DSP)       | 0    | 0    | ... | 0    |
| I0 (DSP)       | 0.11 | 0.11 | ... | 0.11 |
| max (DSP)      | 0.8  | 0.8  | ... | 0.8  |
| min (DSP)      | 0.15 | 0.15 | ... | 0.15 |
| Enable (DSP)   | 0    | 0    | ... | 1    |
| In             | 0    | 0    | ... | 0    |
| I0             | 0.11 | 0.11 | ... | 0.11 |
| max            | 0.8  | 0.8  | ... | 0.8  |
| min            | 0.15 | 0.15 | ... | 0.15 |
| Enable         | 0    | 0    | ... | 1    |
| Parameters     |      |      |     |      |
| Ki             | 2500 |      |     |      |
| ts_fact        | 1    |      |     |      |
| Outputs        |      |      |     |      |
| Out            | 0    | 0    | ... | 0.15 |
| Exp. Out       | 0    | 0    | ... | 0.15 |
| Out (DSP)      | 0    | 0    | ... | 0.15 |
| Exp. Out (DSP) | 0    | 0    | ... | 0.15 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 73  |
| Max CPU cycles  | 127 |
| Avg CPU cycles  | 113 |

**Test case: Conversion test****OK**

Conversion test for Control block ILimit.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ILimit.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e-08$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1495 |
| Max CPU cycles  | 1518 |
| Avg CPU cycles  | 1500 |

**Verification: ILimit Float32 CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block ILimit.

| Test results   |      |      |     |      |
|----------------|------|------|-----|------|
| Time step      | 1    | 2    | ... | 201  |
| CPU cycles     | 41   | 41   | ... | 79   |
| Inputs         |      |      |     |      |
| In (DSP)       | 0    | 0    | ... | 0    |
| I0 (DSP)       | 0.11 | 0.11 | ... | 0.11 |
| max (DSP)      | 0.8  | 0.8  | ... | 0.8  |
| min (DSP)      | 0.15 | 0.15 | ... | 0.15 |
| Enable (DSP)   | 0    | 0    | ... | 1    |
| In             | 0    | 0    | ... | 0    |
| I0             | 0.11 | 0.11 | ... | 0.11 |
| max            | 0.8  | 0.8  | ... | 0.8  |
| min            | 0.15 | 0.15 | ... | 0.15 |
| Enable         | 0    | 0    | ... | 1    |
| Parameters     |      |      |     |      |
| Ki             | 2500 |      |     |      |
| ts_fact        | 1    |      |     |      |
| Outputs        |      |      |     |      |
| Out            | 0    | 0    | ... | 0.15 |
| Exp. Out       | 0    | 0    | ... | 0.15 |
| Out (DSP)      | 0    | 0    | ... | 0.15 |
| Exp. Out (DSP) | 0    | 0    | ... | 0.15 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 41 |
| Max CPU cycles  | 95 |
| Avg CPU cycles  | 79 |

**Test case: Conversion test****OK**

Conversion test for Control block ILimit.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ILimit.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 741 |
| Max CPU cycles  | 741 |
| Avg CPU cycles  | 741 |



**Verification: ILimit Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block ILimit.

| Test results   |      |      |     |      |
|----------------|------|------|-----|------|
| Time step      | 1    | 2    | ... | 201  |
| CPU cycles     | 78   | 78   | ... | 123  |
| Inputs         |      |      |     |      |
| In (DSP)       | 0    | 0    | ... | 0    |
| I0 (DSP)       | 0.11 | 0.11 | ... | 0.11 |
| max (DSP)      | 0.8  | 0.8  | ... | 0.8  |
| min (DSP)      | 0.15 | 0.15 | ... | 0.15 |
| Enable (DSP)   | 0    | 0    | ... | 1    |
| In             | 0    | 0    | ... | 0    |
| I0             | 0.11 | 0.11 | ... | 0.11 |
| max            | 0.8  | 0.8  | ... | 0.8  |
| min            | 0.15 | 0.15 | ... | 0.15 |
| Enable         | 0    | 0    | ... | 1    |
| Parameters     |      |      |     |      |
| Ki             | 2500 |      |     |      |
| ts_fact        | 1    |      |     |      |
| Outputs        |      |      |     |      |
| Out            | 0    | 0    | ... | 0.15 |
| Exp. Out       | 0    | 0    | ... | 0.15 |
| Out (DSP)      | 0    | 0    | ... | 0.15 |
| Exp. Out (DSP) | 0    | 0    | ... | 0.15 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 78  |
| Max CPU cycles  | 139 |
| Avg CPU cycles  | 120 |

**Test case: Conversion test****OK**

Conversion test for Control block ILimit.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ILimit.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 789 |
| Max CPU cycles  | 890 |
| Avg CPU cycles  | 824 |

**Verification: ILimit Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block ILimit.

| Test results   |      |      |     |      |
|----------------|------|------|-----|------|
| Time step      | 1    | 2    | ... | 201  |
| CPU cycles     | 74   | 74   | ... | 486  |
| Inputs         |      |      |     |      |
| In (DSP)       | 0    | 0    | ... | 0    |
| I0 (DSP)       | 0.11 | 0.11 | ... | 0.11 |
| max (DSP)      | 0.8  | 0.8  | ... | 0.8  |
| min (DSP)      | 0.15 | 0.15 | ... | 0.15 |
| Enable (DSP)   | 0    | 0    | ... | 1    |
| In             | 0    | 0    | ... | 0    |
| I0             | 0.11 | 0.11 | ... | 0.11 |
| max            | 0.8  | 0.8  | ... | 0.8  |
| min            | 0.15 | 0.15 | ... | 0.15 |
| Enable         | 0    | 0    | ... | 1    |
| Parameters     |      |      |     |      |
| Ki             | 2500 |      |     |      |
| ts_fact        | 1    |      |     |      |
| Outputs        |      |      |     |      |
| Out            | 0    | 0    | ... | 0.15 |
| Exp. Out       | 0    | 0    | ... | 0.15 |
| Out (DSP)      | 0    | 0    | ... | 0.15 |
| Exp. Out (DSP) | 0    | 0    | ... | 0.15 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 74  |
| Max CPU cycles  | 703 |
| Avg CPU cycles  | 575 |

**Test case: Conversion test****OK**

Conversion test for Control block ILimit.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ILimit.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e-08$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1589 |
| Max CPU cycles  | 1733 |
| Avg CPU cycles  | 1670 |

**Verification: ILimit Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block ILimit.

| Test results   |      |      |     |      |
|----------------|------|------|-----|------|
| Time step      | 1    | 2    | ... | 201  |
| CPU cycles     | 57   | 57   | ... | 217  |
| Inputs         |      |      |     |      |
| In (DSP)       | 0    | 0    | ... | 0    |
| I0 (DSP)       | 0.11 | 0.11 | ... | 0.11 |
| max (DSP)      | 0.8  | 0.8  | ... | 0.8  |
| min (DSP)      | 0.15 | 0.15 | ... | 0.15 |
| Enable (DSP)   | 0    | 0    | ... | 1    |
| In             | 0    | 0    | ... | 0    |
| I0             | 0.11 | 0.11 | ... | 0.11 |
| max            | 0.8  | 0.8  | ... | 0.8  |
| min            | 0.15 | 0.15 | ... | 0.15 |
| Enable         | 0    | 0    | ... | 1    |
| Parameters     |      |      |     |      |
| Ki             | 2500 |      |     |      |
| ts_fact        | 1    |      |     |      |
| Outputs        |      |      |     |      |
| Out            | 0    | 0    | ... | 0.15 |
| Exp. Out       | 0    | 0    | ... | 0.15 |
| Out (DSP)      | 0    | 0    | ... | 0.15 |
| Exp. Out (DSP) | 0    | 0    | ... | 0.15 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 57  |
| Max CPU cycles  | 305 |
| Avg CPU cycles  | 249 |

**Test case: Conversion test****OK**

Conversion test for Control block ILimit.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ILimit.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 583 |
| Max CPU cycles  | 602 |
| Avg CPU cycles  | 597 |

**Verification: ILimit Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block ILimit.

| Test results   |      |      |     |      |
|----------------|------|------|-----|------|
| Time step      | 1    | 2    | ... | 201  |
| CPU cycles     | 82   | 60   | ... | 98   |
| Inputs         |      |      |     |      |
| In (DSP)       | 0    | 0    | ... | 0    |
| I0 (DSP)       | 0.11 | 0.11 | ... | 0.11 |
| max (DSP)      | 0.8  | 0.8  | ... | 0.8  |
| min (DSP)      | 0.15 | 0.15 | ... | 0.15 |
| Enable (DSP)   | 0    | 0    | ... | 1    |
| In             | 0    | 0    | ... | 0    |
| I0             | 0.11 | 0.11 | ... | 0.11 |
| max            | 0.8  | 0.8  | ... | 0.8  |
| min            | 0.15 | 0.15 | ... | 0.15 |
| Enable         | 0    | 0    | ... | 1    |
| Parameters     |      |      |     |      |
| Ki             | 2500 |      |     |      |
| ts_fact        | 1    |      |     |      |
| Outputs        |      |      |     |      |
| Out            | 0    | 0    | ... | 0.15 |
| Exp. Out       | 0    | 0    | ... | 0.15 |
| Out (DSP)      | 0    | 0    | ... | 0.15 |
| Exp. Out (DSP) | 0    | 0    | ... | 0.15 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 60  |
| Max CPU cycles  | 118 |
| Avg CPU cycles  | 97  |

**Test case: Conversion test****OK**

Conversion test for Control block ILimit.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ILimit.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 634 |
| Max CPU cycles  | 694 |
| Avg CPU cycles  | 652 |



**Verification: ILimit Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block ILimit.

| Test results   |      |      |     |      |
|----------------|------|------|-----|------|
| Time step      | 1    | 2    | ... | 201  |
| CPU cycles     | 68   | 68   | ... | 117  |
| Inputs         |      |      |     |      |
| In (DSP)       | 0    | 0    | ... | 0    |
| I0 (DSP)       | 0.11 | 0.11 | ... | 0.11 |
| max (DSP)      | 0.8  | 0.8  | ... | 0.8  |
| min (DSP)      | 0.15 | 0.15 | ... | 0.15 |
| Enable (DSP)   | 0    | 0    | ... | 1    |
| In             | 0    | 0    | ... | 0    |
| I0             | 0.11 | 0.11 | ... | 0.11 |
| max            | 0.8  | 0.8  | ... | 0.8  |
| min            | 0.15 | 0.15 | ... | 0.15 |
| Enable         | 0    | 0    | ... | 1    |
| Parameters     |      |      |     |      |
| Ki             | 2500 |      |     |      |
| ts_fact        | 1    |      |     |      |
| Outputs        |      |      |     |      |
| Out            | 0    | 0    | ... | 0.15 |
| Exp. Out       | 0    | 0    | ... | 0.15 |
| Out (DSP)      | 0    | 0    | ... | 0.15 |
| Exp. Out (DSP) | 0    | 0    | ... | 0.15 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 68  |
| Max CPU cycles  | 132 |
| Avg CPU cycles  | 118 |

**Test case: Conversion test****OK**

Conversion test for Control block ILimit.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ILimit.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e-08$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1150 |
| Max CPU cycles  | 1166 |
| Avg CPU cycles  | 1152 |

**Verification: ILimit Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block ILimit.

| Test results   |      |      |     |      |
|----------------|------|------|-----|------|
| Time step      | 1    | 2    | ... | 201  |
| CPU cycles     | 64   | 64   | ... | 522  |
| Inputs         |      |      |     |      |
| In (DSP)       | 0    | 0    | ... | 0    |
| I0 (DSP)       | 0.11 | 0.11 | ... | 0.11 |
| max (DSP)      | 0.8  | 0.8  | ... | 0.8  |
| min (DSP)      | 0.15 | 0.15 | ... | 0.15 |
| Enable (DSP)   | 0    | 0    | ... | 1    |
| In             | 0    | 0    | ... | 0    |
| I0             | 0.11 | 0.11 | ... | 0.11 |
| max            | 0.8  | 0.8  | ... | 0.8  |
| min            | 0.15 | 0.15 | ... | 0.15 |
| Enable         | 0    | 0    | ... | 1    |
| Parameters     |      |      |     |      |
| Ki             | 2500 |      |     |      |
| ts_fact        | 1    |      |     |      |
| Outputs        |      |      |     |      |
| Out            | 0    | 0    | ... | 0.15 |
| Exp. Out       | 0    | 0    | ... | 0.15 |
| Out (DSP)      | 0    | 0    | ... | 0.15 |
| Exp. Out (DSP) | 0    | 0    | ... | 0.15 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 64  |
| Max CPU cycles  | 733 |
| Avg CPU cycles  | 621 |

**Test case: Conversion test****OK**

Conversion test for Control block ILimit.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ILimit.


| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e-08$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2155 |
| Max CPU cycles  | 2551 |
| Avg CPU cycles  | 2531 |

## Block: P

---



P controller:

$$G(s) = K_p$$

| Inports |                                                                                      |
|---------|--------------------------------------------------------------------------------------|
| In      | Control error input                                                                  |
| Enable  | Enable == 0: Deactivation of block; Out set to 0<br>Enable == 1: Activation of block |

| Outports |               |
|----------|---------------|
| Out      | Control value |

| Mask Parameters |    |                     |
|-----------------|----|---------------------|
| Name            | ID | Description         |
| Kp              | 1  | Proportional Factor |

### Description:

Transfer function (zero-order hold discretization method):

$$G(z) = K_p$$

**Developer note:** The source code of block *PLimit* is used.

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |
| Enable            | bool  |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |
| Enable            | bool  |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |
| Enable            | bool    |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |
| Enable            | bool    |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: P FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block P.

| Test results   |    |    |    |    |     |     |
|----------------|----|----|----|----|-----|-----|
| Time step      | 1  | 2  | 3  | 4  | ... | 201 |
| CPU cycles     | 63 | 63 | 63 | 84 | ... | 84  |
| Inputs         |    |    |    |    |     |     |
| In (DSP)       | 0  | 0  | 0  | 0  | ... | 0   |
| Enable (DSP)   | 0  | 0  | 0  | 1  | ... | 1   |
| In             | 0  | 0  | 0  | 0  | ... | 0   |
| Enable         | 0  | 0  | 0  | 1  | ... | 1   |
| Parameters     |    |    |    |    |     |     |
| Kp             | 2  |    |    |    |     |     |
| Outputs        |    |    |    |    |     |     |
| Out            | 0  | 0  | 0  | 0  | ... | 0   |
| Exp. Out       | 0  | 0  | 0  | 0  | ... | 0   |
| Out (DSP)      | 0  | 0  | 0  | 0  | ... | 0   |
| Exp. Out (DSP) | 0  | 0  | 0  | 0  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 63 |
| Max CPU cycles  | 84 |
| Avg CPU cycles  | 83 |

**Test case: Conversion test****OK**

Conversion test for Control block P.

| Test results                 |        |        |        |        |     |       |
|------------------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |        |        |        |     |       |
| <b>Kp</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| <i>Controller parameters</i> |        |        |        |        |     |       |
| <b>sfrb1</b>                 | 11     | 11     | 11     | 11     | ... | 11    |
| <b>b1</b>                    | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>Exp. sfrb1</b>            | 11     | 11     | 11     | 11     | ... | 11    |
| <b>Exp. b1</b>               | -20480 | -19342 | -18204 | -17067 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block P.

| Test results                 |        |        |        |        |     |       |
|------------------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |        |        |        |     |       |
| <b>Kp</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| <i>Controller parameters</i> |        |        |        |        |     |       |
| <b>sfrb1</b>                 | 11     | 11     | 11     | 11     | ... | 11    |
| <b>b1</b>                    | -20480 | -19342 | -18204 | -17066 | ... | 20480 |
| <b>Exp. sfrb1</b>            | 11     | 11     | 11     | 11     | ... | 11    |
| <b>Exp. b1</b>               | -20480 | -19342 | -18204 | -17067 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1389 |
| Max CPU cycles  | 3539 |
| Avg CPU cycles  | 2786 |



**Verification: P FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block P.

| Test results   |    |    |    |    |     |     |
|----------------|----|----|----|----|-----|-----|
| Time step      | 1  | 2  | 3  | 4  | ... | 201 |
| CPU cycles     | 31 | 31 | 31 | 45 | ... | 45  |
| Inputs         |    |    |    |    |     |     |
| In (DSP)       | 0  | 0  | 0  | 0  | ... | 0   |
| Enable (DSP)   | 0  | 0  | 0  | 1  | ... | 1   |
| In             | 0  | 0  | 0  | 0  | ... | 0   |
| Enable         | 0  | 0  | 0  | 1  | ... | 1   |
| Parameters     |    |    |    |    |     |     |
| Kp             | 2  |    |    |    |     |     |
| Outputs        |    |    |    |    |     |     |
| Out            | 0  | 0  | 0  | 0  | ... | 0   |
| Exp. Out       | 0  | 0  | 0  | 0  | ... | 0   |
| Out (DSP)      | 0  | 0  | 0  | 0  | ... | 0   |
| Exp. Out (DSP) | 0  | 0  | 0  | 0  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 45 |
| Avg CPU cycles  | 44 |

**Test case: Conversion test****OK**

Conversion test for Control block P.

| Test results                 |        |        |        |        |     |       |
|------------------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |        |        |        |     |       |
| <b>Kp</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| <i>Controller parameters</i> |        |        |        |        |     |       |
| <b>sfrb1</b>                 | 11     | 11     | 11     | 11     | ... | 11    |
| <b>b1</b>                    | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>Exp. sfrb1</b>            | 11     | 11     | 11     | 11     | ... | 11    |
| <b>Exp. b1</b>               | -20480 | -19342 | -18204 | -17067 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block P.

| Test results                 |        |        |        |        |     |       |
|------------------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |        |        |        |     |       |
| <b>Kp</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| <i>Controller parameters</i> |        |        |        |        |     |       |
| <b>sfrb1</b>                 | 11     | 11     | 11     | 11     | ... | 11    |
| <b>b1</b>                    | -20480 | -19342 | -18204 | -17066 | ... | 20480 |
| <b>Exp. sfrb1</b>            | 11     | 11     | 11     | 11     | ... | 11    |
| <b>Exp. b1</b>               | -20480 | -19342 | -18204 | -17067 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 727  |
| Max CPU cycles  | 1979 |
| Avg CPU cycles  | 1536 |

**Verification: P FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block P.

| Test results   |    |    |    |    |     |     |
|----------------|----|----|----|----|-----|-----|
| Time step      | 1  | 2  | 3  | 4  | ... | 201 |
| CPU cycles     | 71 | 71 | 71 | 86 | ... | 86  |
| Inputs         |    |    |    |    |     |     |
| In (DSP)       | 0  | 0  | 0  | 0  | ... | 0   |
| Enable (DSP)   | 0  | 0  | 0  | 1  | ... | 1   |
| In             | 0  | 0  | 0  | 0  | ... | 0   |
| Enable         | 0  | 0  | 0  | 1  | ... | 1   |
| Parameters     |    |    |    |    |     |     |
| Kp             | 2  |    |    |    |     |     |
| Outputs        |    |    |    |    |     |     |
| Out            | 0  | 0  | 0  | 0  | ... | 0   |
| Exp. Out       | 0  | 0  | 0  | 0  | ... | 0   |
| Out (DSP)      | 0  | 0  | 0  | 0  | ... | 0   |
| Exp. Out (DSP) | 0  | 0  | 0  | 0  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 71 |
| Max CPU cycles  | 86 |
| Avg CPU cycles  | 85 |

**Test case: Conversion test****OK**

Conversion test for Control block P.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| Time step             | 1      | 2      | 3      | 4      | ... | 37    |
| Mask parameters       |        |        |        |        |     |       |
| Kp                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| Controller parameters |        |        |        |        |     |       |
| sfrb1                 | 11     | 11     | 11     | 11     | ... | 11    |
| b1                    | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| Exp. sfrb1            | 11     | 11     | 11     | 11     | ... | 11    |
| Exp. b1               | -20480 | -19342 | -18204 | -17067 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block P.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| Time step             | 1      | 2      | 3      | 4      | ... | 37    |
| Mask parameters       |        |        |        |        |     |       |
| Kp                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| Controller parameters |        |        |        |        |     |       |
| sfrb1                 | 11     | 11     | 11     | 11     | ... | 11    |
| b1                    | -20480 | -19342 | -18204 | -17066 | ... | 20480 |
| Exp. sfrb1            | 11     | 11     | 11     | 11     | ... | 11    |
| Exp. b1               | -20480 | -19342 | -18204 | -17067 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 924  |
| Max CPU cycles  | 1516 |
| Avg CPU cycles  | 1264 |

**Verification: P FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block P.

| Test results   |    |    |    |    |     |     |
|----------------|----|----|----|----|-----|-----|
| Time step      | 1  | 2  | 3  | 4  | ... | 201 |
| CPU cycles     | 53 | 53 | 53 | 71 | ... | 71  |
| Inputs         |    |    |    |    |     |     |
| In (DSP)       | 0  | 0  | 0  | 0  | ... | 0   |
| Enable (DSP)   | 0  | 0  | 0  | 1  | ... | 1   |
| In             | 0  | 0  | 0  | 0  | ... | 0   |
| Enable         | 0  | 0  | 0  | 1  | ... | 1   |
| Parameters     |    |    |    |    |     |     |
| Kp             | 2  |    |    |    |     |     |
| Outputs        |    |    |    |    |     |     |
| Out            | 0  | 0  | 0  | 0  | ... | 0   |
| Exp. Out       | 0  | 0  | 0  | 0  | ... | 0   |
| Out (DSP)      | 0  | 0  | 0  | 0  | ... | 0   |
| Exp. Out (DSP) | 0  | 0  | 0  | 0  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 53  |
| Max CPU cycles  | 131 |
| Avg CPU cycles  | 71  |

**Test case: Conversion test****OK**

Conversion test for Control block P.

| Test results                 |        |        |        |        |     |       |
|------------------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |        |        |        |     |       |
| <b>Kp</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| <i>Controller parameters</i> |        |        |        |        |     |       |
| <b>sfrb1</b>                 | 11     | 11     | 11     | 11     | ... | 11    |
| <b>b1</b>                    | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>Exp. sfrb1</b>            | 11     | 11     | 11     | 11     | ... | 11    |
| <b>Exp. b1</b>               | -20480 | -19342 | -18204 | -17067 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block P.

| Test results                 |        |        |        |        |     |       |
|------------------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |        |        |        |     |       |
| <b>Kp</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| <i>Controller parameters</i> |        |        |        |        |     |       |
| <b>sfrb1</b>                 | 11     | 11     | 11     | 11     | ... | 11    |
| <b>b1</b>                    | -20480 | -19342 | -18204 | -17066 | ... | 20480 |
| <b>Exp. sfrb1</b>            | 11     | 11     | 11     | 11     | ... | 11    |
| <b>Exp. b1</b>               | -20480 | -19342 | -18204 | -17067 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1698 |
| Max CPU cycles  | 4552 |
| Avg CPU cycles  | 3615 |

**Verification: P FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block P.

| Test results   |    |    |    |    |     |     |
|----------------|----|----|----|----|-----|-----|
| Time step      | 1  | 2  | 3  | 4  | ... | 201 |
| CPU cycles     | 30 | 30 | 30 | 50 | ... | 50  |
| Inputs         |    |    |    |    |     |     |
| In (DSP)       | 0  | 0  | 0  | 0  | ... | 0   |
| Enable (DSP)   | 0  | 0  | 0  | 1  | ... | 1   |
| In             | 0  | 0  | 0  | 0  | ... | 0   |
| Enable         | 0  | 0  | 0  | 1  | ... | 1   |
| Parameters     |    |    |    |    |     |     |
| Kp             | 2  |    |    |    |     |     |
| Outputs        |    |    |    |    |     |     |
| Out            | 0  | 0  | 0  | 0  | ... | 0   |
| Exp. Out       | 0  | 0  | 0  | 0  | ... | 0   |
| Out (DSP)      | 0  | 0  | 0  | 0  | ... | 0   |
| Exp. Out (DSP) | 0  | 0  | 0  | 0  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 30 |
| Max CPU cycles  | 50 |
| Avg CPU cycles  | 49 |

**Test case: Conversion test****OK**

Conversion test for Control block P.

| Test results                 |        |        |        |        |     |       |
|------------------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |        |        |        |     |       |
| <b>Kp</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| <i>Controller parameters</i> |        |        |        |        |     |       |
| <b>sfrb1</b>                 | 11     | 11     | 11     | 11     | ... | 11    |
| <b>b1</b>                    | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>Exp. sfrb1</b>            | 11     | 11     | 11     | 11     | ... | 11    |
| <b>Exp. b1</b>               | -20480 | -19342 | -18204 | -17067 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block P.

| Test results                 |        |        |        |        |     |       |
|------------------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |        |        |        |     |       |
| <b>Kp</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| <i>Controller parameters</i> |        |        |        |        |     |       |
| <b>sfrb1</b>                 | 11     | 11     | 11     | 11     | ... | 11    |
| <b>b1</b>                    | -20480 | -19342 | -18204 | -17066 | ... | 20480 |
| <b>Exp. sfrb1</b>            | 11     | 11     | 11     | 11     | ... | 11    |
| <b>Exp. b1</b>               | -20480 | -19342 | -18204 | -17067 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 774  |
| Max CPU cycles  | 1943 |
| Avg CPU cycles  | 1547 |



**Verification: P FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block P.

| Test results   |    |    |    |    |     |     |
|----------------|----|----|----|----|-----|-----|
| Time step      | 1  | 2  | 3  | 4  | ... | 201 |
| CPU cycles     | 71 | 58 | 58 | 84 | ... | 84  |
| Inputs         |    |    |    |    |     |     |
| In (DSP)       | 0  | 0  | 0  | 0  | ... | 0   |
| Enable (DSP)   | 0  | 0  | 0  | 1  | ... | 1   |
| In             | 0  | 0  | 0  | 0  | ... | 0   |
| Enable         | 0  | 0  | 0  | 1  | ... | 1   |
| Parameters     |    |    |    |    |     |     |
| Kp             | 2  |    |    |    |     |     |
| Outputs        |    |    |    |    |     |     |
| Out            | 0  | 0  | 0  | 0  | ... | 0   |
| Exp. Out       | 0  | 0  | 0  | 0  | ... | 0   |
| Out (DSP)      | 0  | 0  | 0  | 0  | ... | 0   |
| Exp. Out (DSP) | 0  | 0  | 0  | 0  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 58 |
| Max CPU cycles  | 84 |
| Avg CPU cycles  | 83 |

**Test case: Conversion test****OK**

Conversion test for Control block P.

| Test results                 |        |        |        |        |     |       |
|------------------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |        |        |        |     |       |
| <b>Kp</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| <i>Controller parameters</i> |        |        |        |        |     |       |
| <b>sfrb1</b>                 | 11     | 11     | 11     | 11     | ... | 11    |
| <b>b1</b>                    | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>Exp. sfrb1</b>            | 11     | 11     | 11     | 11     | ... | 11    |
| <b>Exp. b1</b>               | -20480 | -19342 | -18204 | -17067 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block P.

| Test results                 |        |        |        |        |     |       |
|------------------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |        |        |        |     |       |
| <b>Kp</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| <i>Controller parameters</i> |        |        |        |        |     |       |
| <b>sfrb1</b>                 | 11     | 11     | 11     | 11     | ... | 11    |
| <b>b1</b>                    | -20480 | -19342 | -18204 | -17066 | ... | 20480 |
| <b>Exp. sfrb1</b>            | 11     | 11     | 11     | 11     | ... | 11    |
| <b>Exp. b1</b>               | -20480 | -19342 | -18204 | -17067 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 640  |
| Max CPU cycles  | 1191 |
| Avg CPU cycles  | 952  |

**Verification: P FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block P.

| Test results   |    |    |    |    |     |     |
|----------------|----|----|----|----|-----|-----|
| Time step      | 1  | 2  | 3  | 4  | ... | 201 |
| CPU cycles     | 53 | 53 | 53 | 74 | ... | 74  |
| Inputs         |    |    |    |    |     |     |
| In (DSP)       | 0  | 0  | 0  | 0  | ... | 0   |
| Enable (DSP)   | 0  | 0  | 0  | 1  | ... | 1   |
| In             | 0  | 0  | 0  | 0  | ... | 0   |
| Enable         | 0  | 0  | 0  | 1  | ... | 1   |
| Parameters     |    |    |    |    |     |     |
| Kp             | 2  |    |    |    |     |     |
| Outputs        |    |    |    |    |     |     |
| Out            | 0  | 0  | 0  | 0  | ... | 0   |
| Exp. Out       | 0  | 0  | 0  | 0  | ... | 0   |
| Out (DSP)      | 0  | 0  | 0  | 0  | ... | 0   |
| Exp. Out (DSP) | 0  | 0  | 0  | 0  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 53 |
| Max CPU cycles  | 74 |
| Avg CPU cycles  | 73 |

**Test case: Conversion test****OK**

Conversion test for Control block P.

| Test results                 |        |        |        |        |     |       |
|------------------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |        |        |        |     |       |
| <b>Kp</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| <i>Controller parameters</i> |        |        |        |        |     |       |
| <b>sfrb1</b>                 | 11     | 11     | 11     | 11     | ... | 11    |
| <b>b1</b>                    | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>Exp. sfrb1</b>            | 11     | 11     | 11     | 11     | ... | 11    |
| <b>Exp. b1</b>               | -20480 | -19342 | -18204 | -17067 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block P.

| Test results                 |        |        |        |        |     |       |
|------------------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |        |        |        |     |       |
| <b>Kp</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| <i>Controller parameters</i> |        |        |        |        |     |       |
| <b>sfrb1</b>                 | 11     | 11     | 11     | 11     | ... | 11    |
| <b>b1</b>                    | -20480 | -19342 | -18204 | -17066 | ... | 20480 |
| <b>Exp. sfrb1</b>            | 11     | 11     | 11     | 11     | ... | 11    |
| <b>Exp. b1</b>               | -20480 | -19342 | -18204 | -17067 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1074 |
| Max CPU cycles  | 2764 |
| Avg CPU cycles  | 2171 |

**Verification: P FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block P.

| Test results   |    |    |    |    |     |     |
|----------------|----|----|----|----|-----|-----|
| Time step      | 1  | 2  | 3  | 4  | ... | 201 |
| CPU cycles     | 39 | 39 | 39 | 65 | ... | 65  |
| Inputs         |    |    |    |    |     |     |
| In (DSP)       | 0  | 0  | 0  | 0  | ... | 0   |
| Enable (DSP)   | 0  | 0  | 0  | 1  | ... | 1   |
| In             | 0  | 0  | 0  | 0  | ... | 0   |
| Enable         | 0  | 0  | 0  | 1  | ... | 1   |
| Parameters     |    |    |    |    |     |     |
| Kp             | 2  |    |    |    |     |     |
| Outputs        |    |    |    |    |     |     |
| Out            | 0  | 0  | 0  | 0  | ... | 0   |
| Exp. Out       | 0  | 0  | 0  | 0  | ... | 0   |
| Out (DSP)      | 0  | 0  | 0  | 0  | ... | 0   |
| Exp. Out (DSP) | 0  | 0  | 0  | 0  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 39 |
| Max CPU cycles  | 65 |
| Avg CPU cycles  | 64 |

**Test case: Conversion test****OK**

Conversion test for Control block P.

| Test results                 |        |        |        |        |     |       |
|------------------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |        |        |        |     |       |
| <b>Kp</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| <i>Controller parameters</i> |        |        |        |        |     |       |
| <b>sfrb1</b>                 | 11     | 11     | 11     | 11     | ... | 11    |
| <b>b1</b>                    | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>Exp. sfrb1</b>            | 11     | 11     | 11     | 11     | ... | 11    |
| <b>Exp. b1</b>               | -20480 | -19342 | -18204 | -17067 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block P.

| Test results                 |        |        |        |        |     |       |
|------------------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |        |        |        |     |       |
| <b>Kp</b>                    | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| <i>Controller parameters</i> |        |        |        |        |     |       |
| <b>sfrb1</b>                 | 11     | 11     | 11     | 11     | ... | 11    |
| <b>b1</b>                    | -20480 | -19342 | -18204 | -17066 | ... | 20480 |
| <b>Exp. sfrb1</b>            | 11     | 11     | 11     | 11     | ... | 11    |
| <b>Exp. b1</b>               | -20480 | -19342 | -18204 | -17067 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 2497  |
| Max CPU cycles  | 10438 |
| Avg CPU cycles  | 7887  |

**Verification: P FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block P.

| Test results   |    |    |     |     |
|----------------|----|----|-----|-----|
| Time step      | 1  | 2  | ... | 201 |
| CPU cycles     | 65 | 65 | ... | 190 |
| Inputs         |    |    |     |     |
| In (DSP)       | 0  | 0  | ... | 0   |
| Enable (DSP)   | 0  | 0  | ... | 1   |
| In             | 0  | 0  | ... | 0   |
| Enable         | 0  | 0  | ... | 1   |
| Parameters     |    |    |     |     |
| Kp             | 2  |    |     |     |
| Outputs        |    |    |     |     |
| Out            | 0  | 0  | ... | 0   |
| Exp. Out       | 0  | 0  | ... | 0   |
| Out (DSP)      | 0  | 0  | ... | 0   |
| Exp. Out (DSP) | 0  | 0  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 65  |
| Max CPU cycles  | 190 |
| Avg CPU cycles  | 188 |

**Test case: Conversion test****OK**

Conversion test for Control block P.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1342177280 | -1267611876 | ... | 1342177280 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1342177280 | -1267611876 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block P.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1342177280 | -1267611904 | ... | 1342177280 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1342177280 | -1267611876 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1597 |
| Max CPU cycles  | 3795 |
| Avg CPU cycles  | 3037 |



**Verification: P FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block P.

| Test results   |    |    |     |     |
|----------------|----|----|-----|-----|
| Time step      | 1  | 2  | ... | 201 |
| CPU cycles     | 43 | 43 | ... | 85  |
| Inputs         |    |    |     |     |
| In (DSP)       | 0  | 0  | ... | 0   |
| Enable (DSP)   | 0  | 0  | ... | 1   |
| In             | 0  | 0  | ... | 0   |
| Enable         | 0  | 0  | ... | 1   |
| Parameters     |    |    |     |     |
| Kp             | 2  |    |     |     |
| Outputs        |    |    |     |     |
| Out            | 0  | 0  | ... | 0   |
| Exp. Out       | 0  | 0  | ... | 0   |
| Out (DSP)      | 0  | 0  | ... | 0   |
| Exp. Out (DSP) | 0  | 0  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 43 |
| Max CPU cycles  | 85 |
| Avg CPU cycles  | 84 |

**Test case: Conversion test****OK**

Conversion test for Control block P.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1342177280 | -1267611876 | ... | 1342177280 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1342177280 | -1267611876 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block P.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1342177280 | -1267611904 | ... | 1342177280 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1342177280 | -1267611876 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 689  |
| Max CPU cycles  | 1585 |
| Avg CPU cycles  | 1281 |

**Verification: P FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block P.

| Test results   |    |    |     |     |
|----------------|----|----|-----|-----|
| Time step      | 1  | 2  | ... | 201 |
| CPU cycles     | 68 | 68 | ... | 114 |
| Inputs         |    |    |     |     |
| In (DSP)       | 0  | 0  | ... | 0   |
| Enable (DSP)   | 0  | 0  | ... | 1   |
| In             | 0  | 0  | ... | 0   |
| Enable         | 0  | 0  | ... | 1   |
| Parameters     |    |    |     |     |
| Kp             | 2  |    |     |     |
| Outputs        |    |    |     |     |
| Out            | 0  | 0  | ... | 0   |
| Exp. Out       | 0  | 0  | ... | 0   |
| Out (DSP)      | 0  | 0  | ... | 0   |
| Exp. Out (DSP) | 0  | 0  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 68  |
| Max CPU cycles  | 114 |
| Avg CPU cycles  | 113 |

**Test case: Conversion test****OK**

Conversion test for Control block P.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1342177280 | -1267611876 | ... | 1342177280 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1342177280 | -1267611876 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block P.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1342177280 | -1267611904 | ... | 1342177280 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1342177280 | -1267611876 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1262 |
| Max CPU cycles  | 1828 |
| Avg CPU cycles  | 1637 |

**Verification: P FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block P.

| Test results   |    |    |     |     |
|----------------|----|----|-----|-----|
| Time step      | 1  | 2  | ... | 201 |
| CPU cycles     | 63 | 63 | ... | 173 |
| Inputs         |    |    |     |     |
| In (DSP)       | 0  | 0  | ... | 0   |
| Enable (DSP)   | 0  | 0  | ... | 1   |
| In             | 0  | 0  | ... | 0   |
| Enable         | 0  | 0  | ... | 1   |
| Parameters     |    |    |     |     |
| Kp             | 2  |    |     |     |
| Outputs        |    |    |     |     |
| Out            | 0  | 0  | ... | 0   |
| Exp. Out       | 0  | 0  | ... | 0   |
| Out (DSP)      | 0  | 0  | ... | 0   |
| Exp. Out (DSP) | 0  | 0  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 63  |
| Max CPU cycles  | 233 |
| Avg CPU cycles  | 170 |

**Test case: Conversion test****OK**

Conversion test for Control block P.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1342177280 | -1267611876 | ... | 1342177280 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1342177280 | -1267611876 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block P.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1342177280 | -1267611904 | ... | 1342177280 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1342177280 | -1267611876 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2673 |
| Max CPU cycles  | 5824 |
| Avg CPU cycles  | 4879 |

**Verification: P FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block P.

| Test results   |    |    |     |     |
|----------------|----|----|-----|-----|
| Time step      | 1  | 2  | ... | 201 |
| CPU cycles     | 30 | 30 | ... | 65  |
| Inputs         |    |    |     |     |
| In (DSP)       | 0  | 0  | ... | 0   |
| Enable (DSP)   | 0  | 0  | ... | 1   |
| In             | 0  | 0  | ... | 0   |
| Enable         | 0  | 0  | ... | 1   |
| Parameters     |    |    |     |     |
| Kp             | 2  |    |     |     |
| Outputs        |    |    |     |     |
| Out            | 0  | 0  | ... | 0   |
| Exp. Out       | 0  | 0  | ... | 0   |
| Out (DSP)      | 0  | 0  | ... | 0   |
| Exp. Out (DSP) | 0  | 0  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 30 |
| Max CPU cycles  | 66 |
| Avg CPU cycles  | 64 |

**Test case: Conversion test****OK**

Conversion test for Control block P.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1342177280 | -1267611876 | ... | 1342177280 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1342177280 | -1267611876 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block P.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1342177280 | -1267611904 | ... | 1342177280 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1342177280 | -1267611876 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1230 |
| Max CPU cycles  | 2413 |
| Avg CPU cycles  | 2016 |



**Verification: P FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block P.

| Test results   |    |    |     |     |
|----------------|----|----|-----|-----|
| Time step      | 1  | 2  | ... | 201 |
| CPU cycles     | 80 | 58 | ... | 106 |
| Inputs         |    |    |     |     |
| In (DSP)       | 0  | 0  | ... | 0   |
| Enable (DSP)   | 0  | 0  | ... | 1   |
| In             | 0  | 0  | ... | 0   |
| Enable         | 0  | 0  | ... | 1   |
| Parameters     |    |    |     |     |
| Kp             | 2  |    |     |     |
| Outputs        |    |    |     |     |
| Out            | 0  | 0  | ... | 0   |
| Exp. Out       | 0  | 0  | ... | 0   |
| Out (DSP)      | 0  | 0  | ... | 0   |
| Exp. Out (DSP) | 0  | 0  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 58  |
| Max CPU cycles  | 108 |
| Avg CPU cycles  | 105 |

**Test case: Conversion test****OK**

Conversion test for Control block P.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1342177280 | -1267611876 | ... | 1342177280 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1342177280 | -1267611876 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block P.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1342177280 | -1267611904 | ... | 1342177280 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1342177280 | -1267611876 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 958  |
| Max CPU cycles  | 1527 |
| Avg CPU cycles  | 1278 |

**Verification: P FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block P.

| Test results   |    |    |     |     |
|----------------|----|----|-----|-----|
| Time step      | 1  | 2  | ... | 201 |
| CPU cycles     | 57 | 57 | ... | 161 |
| Inputs         |    |    |     |     |
| In (DSP)       | 0  | 0  | ... | 0   |
| Enable (DSP)   | 0  | 0  | ... | 1   |
| In             | 0  | 0  | ... | 0   |
| Enable         | 0  | 0  | ... | 1   |
| Parameters     |    |    |     |     |
| Kp             | 2  |    |     |     |
| Outputs        |    |    |     |     |
| Out            | 0  | 0  | ... | 0   |
| Exp. Out       | 0  | 0  | ... | 0   |
| Out (DSP)      | 0  | 0  | ... | 0   |
| Exp. Out (DSP) | 0  | 0  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 57  |
| Max CPU cycles  | 161 |
| Avg CPU cycles  | 159 |

**Test case: Conversion test****OK**

Conversion test for Control block P.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1342177280 | -1267611876 | ... | 1342177280 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1342177280 | -1267611876 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block P.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1342177280 | -1267611904 | ... | 1342177280 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1342177280 | -1267611876 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1198 |
| Max CPU cycles  | 2931 |
| Avg CPU cycles  | 2333 |

**Verification: P FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block P.

| Test results   |    |    |     |     |
|----------------|----|----|-----|-----|
| Time step      | 1  | 2  | ... | 201 |
| CPU cycles     | 47 | 47 | ... | 460 |
| Inputs         |    |    |     |     |
| In (DSP)       | 0  | 0  | ... | 0   |
| Enable (DSP)   | 0  | 0  | ... | 1   |
| In             | 0  | 0  | ... | 0   |
| Enable         | 0  | 0  | ... | 1   |
| Parameters     |    |    |     |     |
| Kp             | 2  |    |     |     |
| Outputs        |    |    |     |     |
| Out            | 0  | 0  | ... | 0   |
| Exp. Out       | 0  | 0  | ... | 0   |
| Out (DSP)      | 0  | 0  | ... | 0   |
| Exp. Out (DSP) | 0  | 0  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 47  |
| Max CPU cycles  | 467 |
| Avg CPU cycles  | 455 |

**Test case: Conversion test****OK**

Conversion test for Control block P.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1342177280 | -1267611876 | ... | 1342177280 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1342177280 | -1267611876 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block P.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1342177280 | -1267611904 | ... | 1342177280 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1342177280 | -1267611876 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+02$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 2903  |
| Max CPU cycles  | 10578 |
| Avg CPU cycles  | 8126  |

**Verification: P Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block P.

| Test results   |    |    |     |     |
|----------------|----|----|-----|-----|
| Time step      | 1  | 2  | ... | 201 |
| CPU cycles     | 66 | 66 | ... | 83  |
| Inputs         |    |    |     |     |
| In (DSP)       | 0  | 0  | ... | 0   |
| Enable (DSP)   | 0  | 0  | ... | 1   |
| In             | 0  | 0  | ... | 0   |
| Enable         | 0  | 0  | ... | 1   |
| Parameters     |    |    |     |     |
| Kp             | 2  |    |     |     |
| Outputs        |    |    |     |     |
| Out            | 0  | 0  | ... | 0   |
| Exp. Out       | 0  | 0  | ... | 0   |
| Out (DSP)      | 0  | 0  | ... | 0   |
| Exp. Out (DSP) | 0  | 0  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 66 |
| Max CPU cycles  | 83 |
| Avg CPU cycles  | 82 |

**Test case: Conversion test****OK**

Conversion test for Control block P.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Kp</b>                    | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>b1</b>                    | -10 | -9.444 | ... | 10 |
| <b>Exp. b1</b>               | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block P.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Kp</b>                    | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>b1</b>                    | -10 | -9.444 | ... | 10 |
| <b>Exp. b1</b>               | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 818 |
| Max CPU cycles  | 829 |
| Avg CPU cycles  | 818 |



**Verification: P Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block P.

| Test results   |    |    |     |     |
|----------------|----|----|-----|-----|
| Time step      | 1  | 2  | ... | 201 |
| CPU cycles     | 29 | 29 | ... | 53  |
| Inputs         |    |    |     |     |
| In (DSP)       | 0  | 0  | ... | 0   |
| Enable (DSP)   | 0  | 0  | ... | 1   |
| In             | 0  | 0  | ... | 0   |
| Enable         | 0  | 0  | ... | 1   |
| Parameters     |    |    |     |     |
| Kp             | 2  |    |     |     |
| Outputs        |    |    |     |     |
| Out            | 0  | 0  | ... | 0   |
| Exp. Out       | 0  | 0  | ... | 0   |
| Out (DSP)      | 0  | 0  | ... | 0   |
| Exp. Out (DSP) | 0  | 0  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 53 |
| Avg CPU cycles  | 52 |

**Test case: Conversion test****OK**

Conversion test for Control block P.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Kp</b>                    | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>b1</b>                    | -10 | -9.444 | ... | 10 |
| <b>Exp. b1</b>               | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block P.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Kp</b>                    | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>b1</b>                    | -10 | -9.444 | ... | 10 |
| <b>Exp. b1</b>               | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 397 |
| Max CPU cycles  | 397 |
| Avg CPU cycles  | 397 |

**Verification: P Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block P.

| Test results   |    |    |     |     |
|----------------|----|----|-----|-----|
| Time step      | 1  | 2  | ... | 201 |
| CPU cycles     | 76 | 76 | ... | 106 |
| Inputs         |    |    |     |     |
| In (DSP)       | 0  | 0  | ... | 0   |
| Enable (DSP)   | 0  | 0  | ... | 1   |
| In             | 0  | 0  | ... | 0   |
| Enable         | 0  | 0  | ... | 1   |
| Parameters     |    |    |     |     |
| Kp             | 2  |    |     |     |
| Outputs        |    |    |     |     |
| Out            | 0  | 0  | ... | 0   |
| Exp. Out       | 0  | 0  | ... | 0   |
| Out (DSP)      | 0  | 0  | ... | 0   |
| Exp. Out (DSP) | 0  | 0  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 76  |
| Max CPU cycles  | 106 |
| Avg CPU cycles  | 105 |

**Test case: Conversion test****OK**

Conversion test for Control block P.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Kp</b>                    | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>b1</b>                    | -10 | -9.444 | ... | 10 |
| <b>Exp. b1</b>               | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block P.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Kp</b>                    | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>b1</b>                    | -10 | -9.444 | ... | 10 |
| <b>Exp. b1</b>               | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 475 |
| Max CPU cycles  | 541 |
| Avg CPU cycles  | 476 |

**Verification: P Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block P.

| Test results   |    |    |     |     |
|----------------|----|----|-----|-----|
| Time step      | 1  | 2  | ... | 201 |
| CPU cycles     | 64 | 64 | ... | 340 |
| Inputs         |    |    |     |     |
| In (DSP)       | 0  | 0  | ... | 0   |
| Enable (DSP)   | 0  | 0  | ... | 1   |
| In             | 0  | 0  | ... | 0   |
| Enable         | 0  | 0  | ... | 1   |
| Parameters     |    |    |     |     |
| Kp             | 2  |    |     |     |
| Outputs        |    |    |     |     |
| Out            | 0  | 0  | ... | 0   |
| Exp. Out       | 0  | 0  | ... | 0   |
| Out (DSP)      | 0  | 0  | ... | 0   |
| Exp. Out (DSP) | 0  | 0  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 64  |
| Max CPU cycles  | 416 |
| Avg CPU cycles  | 388 |

**Test case: Conversion test****OK**

Conversion test for Control block P.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Kp</b>                    | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>b1</b>                    | -10 | -9.444 | ... | 10 |
| <b>Exp. b1</b>               | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block P.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Kp</b>                    | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>b1</b>                    | -10 | -9.444 | ... | 10 |
| <b>Exp. b1</b>               | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 667 |
| Max CPU cycles  | 696 |
| Avg CPU cycles  | 694 |

**Verification: P Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block P.

| Test results   |    |    |     |     |
|----------------|----|----|-----|-----|
| Time step      | 1  | 2  | ... | 201 |
| CPU cycles     | 30 | 30 | ... | 163 |
| Inputs         |    |    |     |     |
| In (DSP)       | 0  | 0  | ... | 0   |
| Enable (DSP)   | 0  | 0  | ... | 1   |
| In             | 0  | 0  | ... | 0   |
| Enable         | 0  | 0  | ... | 1   |
| Parameters     |    |    |     |     |
| Kp             | 2  |    |     |     |
| Outputs        |    |    |     |     |
| Out            | 0  | 0  | ... | 0   |
| Exp. Out       | 0  | 0  | ... | 0   |
| Out (DSP)      | 0  | 0  | ... | 0   |
| Exp. Out (DSP) | 0  | 0  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 30  |
| Max CPU cycles  | 183 |
| Avg CPU cycles  | 174 |

**Test case: Conversion test****OK**

Conversion test for Control block P.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Kp</b>                    | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>b1</b>                    | -10 | -9.444 | ... | 10 |
| <b>Exp. b1</b>               | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block P.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Kp</b>                    | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>b1</b>                    | -10 | -9.444 | ... | 10 |
| <b>Exp. b1</b>               | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 277 |
| Max CPU cycles  | 278 |
| Avg CPU cycles  | 277 |



**Verification: P Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block P.

| Test results   |    |    |     |     |
|----------------|----|----|-----|-----|
| Time step      | 1  | 2  | ... | 201 |
| CPU cycles     | 77 | 59 | ... | 80  |
| Inputs         |    |    |     |     |
| In (DSP)       | 0  | 0  | ... | 0   |
| Enable (DSP)   | 0  | 0  | ... | 1   |
| In             | 0  | 0  | ... | 0   |
| Enable         | 0  | 0  | ... | 1   |
| Parameters     |    |    |     |     |
| Kp             | 2  |    |     |     |
| Outputs        |    |    |     |     |
| Out            | 0  | 0  | ... | 0   |
| Exp. Out       | 0  | 0  | ... | 0   |
| Out (DSP)      | 0  | 0  | ... | 0   |
| Exp. Out (DSP) | 0  | 0  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 80 |
| Avg CPU cycles  | 79 |

**Test case: Conversion test****OK**

Conversion test for Control block P.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Kp</b>                    | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>b1</b>                    | -10 | -9.444 | ... | 10 |
| <b>Exp. b1</b>               | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block P.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Kp</b>                    | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>b1</b>                    | -10 | -9.444 | ... | 10 |
| <b>Exp. b1</b>               | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 389 |
| Max CPU cycles  | 433 |
| Avg CPU cycles  | 391 |

**Verification: P Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block P.

| Test results   |    |    |     |     |
|----------------|----|----|-----|-----|
| Time step      | 1  | 2  | ... | 201 |
| CPU cycles     | 59 | 59 | ... | 83  |
| Inputs         |    |    |     |     |
| In (DSP)       | 0  | 0  | ... | 0   |
| Enable (DSP)   | 0  | 0  | ... | 1   |
| In             | 0  | 0  | ... | 0   |
| Enable         | 0  | 0  | ... | 1   |
| Parameters     |    |    |     |     |
| Kp             | 2  |    |     |     |
| Outputs        |    |    |     |     |
| Out            | 0  | 0  | ... | 0   |
| Exp. Out       | 0  | 0  | ... | 0   |
| Out (DSP)      | 0  | 0  | ... | 0   |
| Exp. Out (DSP) | 0  | 0  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 83 |
| Avg CPU cycles  | 82 |

**Test case: Conversion test****OK**

Conversion test for Control block P.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Kp</b>                    | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>b1</b>                    | -10 | -9.444 | ... | 10 |
| <b>Exp. b1</b>               | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block P.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Kp</b>                    | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>b1</b>                    | -10 | -9.444 | ... | 10 |
| <b>Exp. b1</b>               | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 649 |
| Max CPU cycles  | 660 |
| Avg CPU cycles  | 649 |

**Verification: P Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block P.

| Test results   |    |    |     |     |
|----------------|----|----|-----|-----|
| Time step      | 1  | 2  | ... | 201 |
| CPU cycles     | 51 | 51 | ... | 365 |
| Inputs         |    |    |     |     |
| In (DSP)       | 0  | 0  | ... | 0   |
| Enable (DSP)   | 0  | 0  | ... | 1   |
| In             | 0  | 0  | ... | 0   |
| Enable         | 0  | 0  | ... | 1   |
| Parameters     |    |    |     |     |
| Kp             | 2  |    |     |     |
| Outputs        |    |    |     |     |
| Out            | 0  | 0  | ... | 0   |
| Exp. Out       | 0  | 0  | ... | 0   |
| Out (DSP)      | 0  | 0  | ... | 0   |
| Exp. Out (DSP) | 0  | 0  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 51  |
| Max CPU cycles  | 407 |
| Avg CPU cycles  | 390 |

**Test case: Conversion test****OK**

Conversion test for Control block P.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Kp</b>                    | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>b1</b>                    | -10 | -9.444 | ... | 10 |
| <b>Exp. b1</b>               | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK


Conversion-on-Target test for Control block P.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Kp</b>                    | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>b1</b>                    | -10 | -9.444 | ... | 10 |
| <b>Exp. b1</b>               | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 515 |
| Max CPU cycles  | 860 |
| Avg CPU cycles  | 848 |

## Block: PI



PI controller:

$$G(s) = K_p + K_i/s$$

| Inports |                                                                                                                               |
|---------|-------------------------------------------------------------------------------------------------------------------------------|
| In      | Control error input                                                                                                           |
| Init    | Initial value of output Out when enabled                                                                                      |
| Enable  | Enable == 0: Deactivation of block; Out set to 0<br>Enable 0->1: Preload of integral part<br>Enable == 1: Activation of block |

| Outputs |               |
|---------|---------------|
| Out     | Control value |

| Mask Parameters |    |                                                                 |
|-----------------|----|-----------------------------------------------------------------|
| Name            | ID | Description                                                     |
| Kp              | 1  | Proportional Factor                                             |
| Ki              | 2  | Integral Factor                                                 |
| initHandling    | 3  | Determines what the signal provided on Init input is used for   |
| ts_fact         | 4  | Multiplication factor of base sampling time (in integer format) |

### Description:

#### Preloading Integral

A rising edge at the *Enable* inport enables the controller and preloads the integral.

One may choose from two options how to preload the integral value:

- Preload the integral from the *Init* inport.
- Preload the integral such that the first output of the controller matches the current value at the *Init* inport.  
This option allows controller switching without disturbing the control.

**Note:** Each fixed point implementation uses the next higher integer data type for the integral value storage variable.

**Transfer function** (zero-order hold discretization method):

When the block is enabled, the PI controller realizes the following transfer function:

$$G(z) = K_p + K_i T_s \frac{1}{z - 1}$$

**Developer note:** The source code of block *PILimit* is used.

## Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | int8 |
| Init              | int8 |
| Enable            | bool |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |
| Init              | int16 |
| Enable            | bool  |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

---

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |
| Init              | int32 |
| Enable            | bool  |



| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |
| Init              | float32 |
| Enable            | bool    |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |
| Init              | float64 |
| Enable            | bool    |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: PI FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block PI.

| Test results   |                     |      |      |      |     |        |
|----------------|---------------------|------|------|------|-----|--------|
| Time step      | 1                   | 2    | 3    | 4    | ... | 201    |
| CPU cycles     | 67                  | 67   | 67   | 131  | ... | 122    |
| Inputs         |                     |      |      |      |     |        |
| In (DSP)       | 0                   | 0    | 0    | 0    | ... | 0      |
| Init (DSP)     | 3604                | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0                   | 0    | 0    | 1    | ... | 1      |
| In             | 0                   | 0    | 0    | 0    | ... | 0      |
| Init           | 0.11                | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0                   | 0    | 0    | 1    | ... | 1      |
| Parameters     |                     |      |      |      |     |        |
| Kp             | 2                   |      |      |      |     |        |
| Ki             | 2500                |      |      |      |     |        |
| initHandling   | initialize integral |      |      |      |     |        |
| ts_fact        | 1                   |      |      |      |     |        |
| Outputs        |                     |      |      |      |     |        |
| Out            | 0                   | 0    | 0    | 0.11 | ... | -0.528 |
| Exp. Out       | 0                   | 0    | 0    | 0.11 | ... | -0.528 |
| Out (DSP)      | 0                   | 0    | 0    | 3604 | ... | -17292 |
| Exp. Out (DSP) | 0                   | 0    | 0    | 3604 | ... | -17285 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 67  |
| Max CPU cycles  | 131 |
| Avg CPU cycles  | 119 |

**Test case: Conversion test****OK**

Conversion test for Control block PI.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 20480      |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 20480      |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PI.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 204        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 204        |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e+00$ |
| Tolerance b1           | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3083 |
| Max CPU cycles  | 5333 |
| Avg CPU cycles  | 4571 |

**Verification: PI FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block PI.

| Test results   |                     |      |      |      |     |        |
|----------------|---------------------|------|------|------|-----|--------|
| Time step      | 1                   | 2    | 3    | 4    | ... | 201    |
| CPU cycles     | 43                  | 43   | 43   | 91   | ... | 85     |
| Inputs         |                     |      |      |      |     |        |
| In (DSP)       | 0                   | 0    | 0    | 0    | ... | 0      |
| Init (DSP)     | 3604                | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0                   | 0    | 0    | 1    | ... | 1      |
| In             | 0                   | 0    | 0    | 0    | ... | 0      |
| Init           | 0.11                | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0                   | 0    | 0    | 1    | ... | 1      |
| Parameters     |                     |      |      |      |     |        |
| Kp             | 2                   |      |      |      |     |        |
| Ki             | 2500                |      |      |      |     |        |
| initHandling   | initialize integral |      |      |      |     |        |
| ts_fact        | 1                   |      |      |      |     |        |
| Outputs        |                     |      |      |      |     |        |
| Out            | 0                   | 0    | 0    | 0.11 | ... | -0.528 |
| Exp. Out       | 0                   | 0    | 0    | 0.11 | ... | -0.528 |
| Out (DSP)      | 0                   | 0    | 0    | 3604 | ... | -17292 |
| Exp. Out (DSP) | 0                   | 0    | 0    | 3604 | ... | -17285 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 43 |
| Max CPU cycles  | 91 |
| Avg CPU cycles  | 83 |

**Test case: Conversion test****OK**

Conversion test for Control block PI.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 20480      |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 20480      |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PI.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 204        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 204        |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e+00$ |
| Tolerance b1           | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1561 |
| Max CPU cycles  | 2887 |
| Avg CPU cycles  | 2439 |

**Verification: PI FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block PI.

| Test results   |                     |      |      |      |     |        |
|----------------|---------------------|------|------|------|-----|--------|
| Time step      | 1                   | 2    | 3    | 4    | ... | 201    |
| CPU cycles     | 68                  | 68   | 68   | 154  | ... | 142    |
| Inputs         |                     |      |      |      |     |        |
| In (DSP)       | 0                   | 0    | 0    | 0    | ... | 0      |
| Init (DSP)     | 3604                | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0                   | 0    | 0    | 1    | ... | 1      |
| In             | 0                   | 0    | 0    | 0    | ... | 0      |
| Init           | 0.11                | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0                   | 0    | 0    | 1    | ... | 1      |
| Parameters     |                     |      |      |      |     |        |
| Kp             | 2                   |      |      |      |     |        |
| Ki             | 2500                |      |      |      |     |        |
| initHandling   | initialize integral |      |      |      |     |        |
| ts_fact        | 1                   |      |      |      |     |        |
| Outputs        |                     |      |      |      |     |        |
| Out            | 0                   | 0    | 0    | 0.11 | ... | -0.528 |
| Exp. Out       | 0                   | 0    | 0    | 0.11 | ... | -0.528 |
| Out (DSP)      | 0                   | 0    | 0    | 3604 | ... | -17292 |
| Exp. Out (DSP) | 0                   | 0    | 0    | 3604 | ... | -17285 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 68  |
| Max CPU cycles  | 154 |
| Avg CPU cycles  | 129 |

**Test case: Conversion test****OK**

Conversion test for Control block PI.



| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 20480      |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 20480      |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PI.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 20480      |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 20480      |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e+00$ |
| Tolerance b1           | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1580 |
| Max CPU cycles  | 2085 |
| Avg CPU cycles  | 1901 |

**Verification: PI FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block PI.

| Test results   |                     |      |      |      |     |        |
|----------------|---------------------|------|------|------|-----|--------|
| Time step      | 1                   | 2    | 3    | 4    | ... | 201    |
| CPU cycles     | 67                  | 67   | 67   | 135  | ... | 123    |
| Inputs         |                     |      |      |      |     |        |
| In (DSP)       | 0                   | 0    | 0    | 0    | ... | 0      |
| Init (DSP)     | 3604                | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0                   | 0    | 0    | 1    | ... | 1      |
| In             | 0                   | 0    | 0    | 0    | ... | 0      |
| Init           | 0.11                | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0                   | 0    | 0    | 1    | ... | 1      |
| Parameters     |                     |      |      |      |     |        |
| Kp             | 2                   |      |      |      |     |        |
| Ki             | 2500                |      |      |      |     |        |
| initHandling   | initialize integral |      |      |      |     |        |
| ts_fact        | 1                   |      |      |      |     |        |
| Outputs        |                     |      |      |      |     |        |
| Out            | 0                   | 0    | 0    | 0.11 | ... | -0.528 |
| Exp. Out       | 0                   | 0    | 0    | 0.11 | ... | -0.528 |
| Out (DSP)      | 0                   | 0    | 0    | 3604 | ... | -17292 |
| Exp. Out (DSP) | 0                   | 0    | 0    | 3604 | ... | -17285 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 67  |
| Max CPU cycles  | 183 |
| Avg CPU cycles  | 115 |

**Test case: Conversion test****OK**

Conversion test for Control block PI.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 20480      |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 20480      |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PI.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 204        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 204        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 4005 |
| Max CPU cycles  | 7385 |
| Avg CPU cycles  | 6391 |

**Verification: PI FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block PI.

| Test results   |                     |      |      |      |     |        |
|----------------|---------------------|------|------|------|-----|--------|
| Time step      | 1                   | 2    | 3    | 4    | ... | 201    |
| CPU cycles     | 31                  | 31   | 31   | 83   | ... | 74     |
| Inputs         |                     |      |      |      |     |        |
| In (DSP)       | 0                   | 0    | 0    | 0    | ... | 0      |
| Init (DSP)     | 3604                | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0                   | 0    | 0    | 1    | ... | 1      |
| In             | 0                   | 0    | 0    | 0    | ... | 0      |
| Init           | 0.11                | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0                   | 0    | 0    | 1    | ... | 1      |
| Parameters     |                     |      |      |      |     |        |
| Kp             | 2                   |      |      |      |     |        |
| Ki             | 2500                |      |      |      |     |        |
| initHandling   | initialize integral |      |      |      |     |        |
| ts_fact        | 1                   |      |      |      |     |        |
| Outputs        |                     |      |      |      |     |        |
| Out            | 0                   | 0    | 0    | 0.11 | ... | -0.528 |
| Exp. Out       | 0                   | 0    | 0    | 0.11 | ... | -0.528 |
| Out (DSP)      | 0                   | 0    | 0    | 3604 | ... | -17292 |
| Exp. Out (DSP) | 0                   | 0    | 0    | 3604 | ... | -17285 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 83 |
| Avg CPU cycles  | 69 |

**Test case: Conversion test****OK**

Conversion test for Control block PI.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 20480      |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 20480      |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PI.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 20480      |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 20480      |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e+00$ |
| Tolerance b1           | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1749 |
| Max CPU cycles  | 3034 |
| Avg CPU cycles  | 2632 |



**Verification: PI FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block PI.

| Test results   |                     |      |      |      |     |        |
|----------------|---------------------|------|------|------|-----|--------|
| Time step      | 1                   | 2    | 3    | 4    | ... | 201    |
| CPU cycles     | 78                  | 59   | 59   | 122  | ... | 98     |
| Inputs         |                     |      |      |      |     |        |
| In (DSP)       | 0                   | 0    | 0    | 0    | ... | 0      |
| Init (DSP)     | 3604                | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0                   | 0    | 0    | 1    | ... | 1      |
| In             | 0                   | 0    | 0    | 0    | ... | 0      |
| Init           | 0.11                | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0                   | 0    | 0    | 1    | ... | 1      |
| Parameters     |                     |      |      |      |     |        |
| Kp             | 2                   |      |      |      |     |        |
| Ki             | 2500                |      |      |      |     |        |
| initHandling   | initialize integral |      |      |      |     |        |
| ts_fact        | 1                   |      |      |      |     |        |
| Outputs        |                     |      |      |      |     |        |
| Out            | 0                   | 0    | 0    | 0.11 | ... | -0.528 |
| Exp. Out       | 0                   | 0    | 0    | 0.11 | ... | -0.528 |
| Out (DSP)      | 0                   | 0    | 0    | 3604 | ... | -17292 |
| Exp. Out (DSP) | 0                   | 0    | 0    | 3604 | ... | -17285 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 59  |
| Max CPU cycles  | 122 |
| Avg CPU cycles  | 95  |

**Test case: Conversion test****OK**

Conversion test for Control block PI.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 20480      |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 20480      |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PI.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 20480      |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 20480      |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e+00$ |
| Tolerance b1           | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1375 |
| Max CPU cycles  | 2015 |
| Avg CPU cycles  | 1690 |

**Verification: PI FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block PI.

| Test results   |                     |      |      |      |     |        |
|----------------|---------------------|------|------|------|-----|--------|
| Time step      | 1                   | 2    | 3    | 4    | ... | 201    |
| CPU cycles     | 61                  | 61   | 61   | 134  | ... | 122    |
| Inputs         |                     |      |      |      |     |        |
| In (DSP)       | 0                   | 0    | 0    | 0    | ... | 0      |
| Init (DSP)     | 3604                | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0                   | 0    | 0    | 1    | ... | 1      |
| In             | 0                   | 0    | 0    | 0    | ... | 0      |
| Init           | 0.11                | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0                   | 0    | 0    | 1    | ... | 1      |
| Parameters     |                     |      |      |      |     |        |
| Kp             | 2                   |      |      |      |     |        |
| Ki             | 2500                |      |      |      |     |        |
| initHandling   | initialize integral |      |      |      |     |        |
| ts_fact        | 1                   |      |      |      |     |        |
| Outputs        |                     |      |      |      |     |        |
| Out            | 0                   | 0    | 0    | 0.11 | ... | -0.528 |
| Exp. Out       | 0                   | 0    | 0    | 0.11 | ... | -0.528 |
| Out (DSP)      | 0                   | 0    | 0    | 3604 | ... | -17292 |
| Exp. Out (DSP) | 0                   | 0    | 0    | 3604 | ... | -17285 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 61  |
| Max CPU cycles  | 134 |
| Avg CPU cycles  | 119 |

**Test case: Conversion test****OK**

Conversion test for Control block PI.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 20480      |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 20480      |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PI.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 204        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 204        |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e+00$ |
| Tolerance b1           | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2308 |
| Max CPU cycles  | 4073 |
| Avg CPU cycles  | 3473 |

**Verification: PI FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block PI.

| Test results   |                     |      |      |      |     |        |
|----------------|---------------------|------|------|------|-----|--------|
| Time step      | 1                   | 2    | 3    | 4    | ... | 201    |
| CPU cycles     | 47                  | 47   | 47   | 126  | ... | 126    |
| Inputs         |                     |      |      |      |     |        |
| In (DSP)       | 0                   | 0    | 0    | 0    | ... | 0      |
| Init (DSP)     | 3604                | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0                   | 0    | 0    | 1    | ... | 1      |
| In             | 0                   | 0    | 0    | 0    | ... | 0      |
| Init           | 0.11                | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0                   | 0    | 0    | 1    | ... | 1      |
| Parameters     |                     |      |      |      |     |        |
| Kp             | 2                   |      |      |      |     |        |
| Ki             | 2500                |      |      |      |     |        |
| initHandling   | initialize integral |      |      |      |     |        |
| ts_fact        | 1                   |      |      |      |     |        |
| Outputs        |                     |      |      |      |     |        |
| Out            | 0                   | 0    | 0    | 0.11 | ... | -0.528 |
| Exp. Out       | 0                   | 0    | 0    | 0.11 | ... | -0.528 |
| Out (DSP)      | 0                   | 0    | 0    | 3604 | ... | -17292 |
| Exp. Out (DSP) | 0                   | 0    | 0    | 3604 | ... | -17285 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 47  |
| Max CPU cycles  | 126 |
| Avg CPU cycles  | 116 |

**Test case: Conversion test****OK**

Conversion test for Control block PI.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 20480      |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 20480      |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PI.



| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 20480      |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 20480      |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e+00$ |
| Tolerance b1           | $\pm 1,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 6441  |
| Max CPU cycles  | 15553 |
| Avg CPU cycles  | 12970 |

**Verification: PI FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block PI.

| Test results   |                     |           |     |             |
|----------------|---------------------|-----------|-----|-------------|
| Time step      | 1                   | 2         | ... | 201         |
| CPU cycles     | 86                  | 86        | ... | 254         |
| Inputs         |                     |           |     |             |
| In (DSP)       | 0                   | 0         | ... | 0           |
| Init (DSP)     | 236223201           | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0                   | 0         | ... | 1           |
| In             | 0                   | 0         | ... | 0           |
| Init           | 0.11                | 0.11      | ... | 0.11        |
| Enable         | 0                   | 0         | ... | 1           |
| Parameters     |                     |           |     |             |
| Kp             | 2                   |           |     |             |
| Ki             | 2500                |           |     |             |
| initHandling   | initialize integral |           |     |             |
| ts_fact        | 1                   |           |     |             |
| Outputs        |                     |           |     |             |
| Out            | 0                   | 0         | ... | -0.528      |
| Exp. Out       | 0                   | 0         | ... | -0.528      |
| Out (DSP)      | 0                   | 0         | ... | -1132797631 |
| Exp. Out (DSP) | 0                   | 0         | ... | -1132797631 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 86  |
| Max CPU cycles  | 269 |
| Avg CPU cycles  | 238 |

**Test case: Conversion test****OK**

Conversion test for Control block PI.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611876         | ... | 1342177280        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PI.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e+02$ |
| Tolerance b1           | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3436 |
| Max CPU cycles  | 5782 |
| Avg CPU cycles  | 5011 |

**Verification: PI FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block PI.

| Test results   |                     |           |     |             |
|----------------|---------------------|-----------|-----|-------------|
| Time step      | 1                   | 2         | ... | 201         |
| CPU cycles     | 59                  | 59        | ... | 167         |
| Inputs         |                     |           |     |             |
| In (DSP)       | 0                   | 0         | ... | 0           |
| Init (DSP)     | 236223201           | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0                   | 0         | ... | 1           |
| In             | 0                   | 0         | ... | 0           |
| Init           | 0.11                | 0.11      | ... | 0.11        |
| Enable         | 0                   | 0         | ... | 1           |
| Parameters     |                     |           |     |             |
| Kp             | 2                   |           |     |             |
| Ki             | 2500                |           |     |             |
| initHandling   | initialize integral |           |     |             |
| ts_fact        | 1                   |           |     |             |
| Outputs        |                     |           |     |             |
| Out            | 0                   | 0         | ... | -0.528      |
| Exp. Out       | 0                   | 0         | ... | -0.528      |
| Out (DSP)      | 0                   | 0         | ... | -1132797631 |
| Exp. Out (DSP) | 0                   | 0         | ... | -1132797631 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 59  |
| Max CPU cycles  | 179 |
| Avg CPU cycles  | 155 |

**Test case: Conversion test****OK**

Conversion test for Control block PI.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611876         | ... | 1342177280        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PI.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e+02$ |
| Tolerance b1           | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1461 |
| Max CPU cycles  | 2455 |
| Avg CPU cycles  | 2147 |

**Verification: PI FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block PI.

| Test results   |                     |           |     |             |
|----------------|---------------------|-----------|-----|-------------|
| Time step      | 1                   | 2         | ... | 201         |
| CPU cycles     | 83                  | 83        | ... | 199         |
| Inputs         |                     |           |     |             |
| In (DSP)       | 0                   | 0         | ... | 0           |
| Init (DSP)     | 236223201           | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0                   | 0         | ... | 1           |
| In             | 0                   | 0         | ... | 0           |
| Init           | 0.11                | 0.11      | ... | 0.11        |
| Enable         | 0                   | 0         | ... | 1           |
| Parameters     |                     |           |     |             |
| Kp             | 2                   |           |     |             |
| Ki             | 2500                |           |     |             |
| initHandling   | initialize integral |           |     |             |
| ts_fact        | 1                   |           |     |             |
| Outputs        |                     |           |     |             |
| Out            | 0                   | 0         | ... | -0.528      |
| Exp. Out       | 0                   | 0         | ... | -0.528      |
| Out (DSP)      | 0                   | 0         | ... | -1132797631 |
| Exp. Out (DSP) | 0                   | 0         | ... | -1132797631 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 83  |
| Max CPU cycles  | 212 |
| Avg CPU cycles  | 179 |

**Test case: Conversion test****OK**

Conversion test for Control block PI.



| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611876         | ... | 1342177280        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |             |
|---------------------------|-------------|
| Tolerance<br>initHandling | ±0,0000e+00 |
| Tolerance sfrb0           | ±0,0000e+00 |
| Tolerance sfrb1           | ±0,0000e+00 |
| Tolerance b0              | ±0,0000e+00 |
| Tolerance b1              | ±0,0000e+00 |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PI.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+02$ |
| Tolerance b1              | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2164 |
| Max CPU cycles  | 2783 |
| Avg CPU cycles  | 2521 |

**Verification: PI FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block PI.

| Test results   |                     |           |     |             |
|----------------|---------------------|-----------|-----|-------------|
| Time step      | 1                   | 2         | ... | 201         |
| CPU cycles     | 86                  | 86        | ... | 337         |
| Inputs         |                     |           |     |             |
| In (DSP)       | 0                   | 0         | ... | 0           |
| Init (DSP)     | 236223201           | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0                   | 0         | ... | 1           |
| In             | 0                   | 0         | ... | 0           |
| Init           | 0.11                | 0.11      | ... | 0.11        |
| Enable         | 0                   | 0         | ... | 1           |
| Parameters     |                     |           |     |             |
| Kp             | 2                   |           |     |             |
| Ki             | 2500                |           |     |             |
| initHandling   | initialize integral |           |     |             |
| ts_fact        | 1                   |           |     |             |
| Outputs        |                     |           |     |             |
| Out            | 0                   | 0         | ... | -0.528      |
| Exp. Out       | 0                   | 0         | ... | -0.528      |
| Out (DSP)      | 0                   | 0         | ... | -1132797631 |
| Exp. Out (DSP) | 0                   | 0         | ... | -1132797631 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 86  |
| Max CPU cycles  | 349 |
| Avg CPU cycles  | 302 |

**Test case: Conversion test****OK**

Conversion test for Control block PI.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611876         | ... | 1342177280        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PI.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+02$ |
| Tolerance b1              | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 6085 |
| Max CPU cycles  | 9969 |
| Avg CPU cycles  | 8937 |

**Verification: PI FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block PI.

| Test results   |                     |           |     |             |
|----------------|---------------------|-----------|-----|-------------|
| Time step      | 1                   | 2         | ... | 201         |
| CPU cycles     | 31                  | 31        | ... | 118         |
| Inputs         |                     |           |     |             |
| In (DSP)       | 0                   | 0         | ... | 0           |
| Init (DSP)     | 236223201           | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0                   | 0         | ... | 1           |
| In             | 0                   | 0         | ... | 0           |
| Init           | 0.11                | 0.11      | ... | 0.11        |
| Enable         | 0                   | 0         | ... | 1           |
| Parameters     |                     |           |     |             |
| Kp             | 2                   |           |     |             |
| Ki             | 2500                |           |     |             |
| initHandling   | initialize integral |           |     |             |
| ts_fact        | 1                   |           |     |             |
| Outputs        |                     |           |     |             |
| Out            | 0                   | 0         | ... | -0.528      |
| Exp. Out       | 0                   | 0         | ... | -0.528      |
| Out (DSP)      | 0                   | 0         | ... | -1132797631 |
| Exp. Out (DSP) | 0                   | 0         | ... | -1132797631 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 31  |
| Max CPU cycles  | 125 |
| Avg CPU cycles  | 106 |

**Test case: Conversion test****OK**

Conversion test for Control block PI.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611876         | ... | 1342177280        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PI.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+02$ |
| Tolerance b1              | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2658 |
| Max CPU cycles  | 4035 |
| Avg CPU cycles  | 3626 |



**Verification: PI FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block PI.

| Test results   |                     |           |     |             |
|----------------|---------------------|-----------|-----|-------------|
| Time step      | 1                   | 2         | ... | 201         |
| CPU cycles     | 82                  | 59        | ... | 151         |
| Inputs         |                     |           |     |             |
| In (DSP)       | 0                   | 0         | ... | 0           |
| Init (DSP)     | 236223201           | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0                   | 0         | ... | 1           |
| In             | 0                   | 0         | ... | 0           |
| Init           | 0.11                | 0.11      | ... | 0.11        |
| Enable         | 0                   | 0         | ... | 1           |
| Parameters     |                     |           |     |             |
| Kp             | 2                   |           |     |             |
| Ki             | 2500                |           |     |             |
| initHandling   | initialize integral |           |     |             |
| ts_fact        | 1                   |           |     |             |
| Outputs        |                     |           |     |             |
| Out            | 0                   | 0         | ... | -0.528      |
| Exp. Out       | 0                   | 0         | ... | -0.528      |
| Out (DSP)      | 0                   | 0         | ... | -1132797631 |
| Exp. Out (DSP) | 0                   | 0         | ... | -1132797631 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 59  |
| Max CPU cycles  | 191 |
| Avg CPU cycles  | 142 |

**Test case: Conversion test****OK**

Conversion test for Control block PI.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611876         | ... | 1342177280        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PI.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+02$ |
| Tolerance b1              | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1823 |
| Max CPU cycles  | 2619 |
| Avg CPU cycles  | 2176 |

**Verification: PI FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block PI.

| Test results   |                     |           |     |             |
|----------------|---------------------|-----------|-----|-------------|
| Time step      | 1                   | 2         | ... | 201         |
| CPU cycles     | 67                  | 67        | ... | 216         |
| Inputs         |                     |           |     |             |
| In (DSP)       | 0                   | 0         | ... | 0           |
| Init (DSP)     | 236223201           | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0                   | 0         | ... | 1           |
| In             | 0                   | 0         | ... | 0           |
| Init           | 0.11                | 0.11      | ... | 0.11        |
| Enable         | 0                   | 0         | ... | 1           |
| Parameters     |                     |           |     |             |
| Kp             | 2                   |           |     |             |
| Ki             | 2500                |           |     |             |
| initHandling   | initialize integral |           |     |             |
| ts_fact        | 1                   |           |     |             |
| Outputs        |                     |           |     |             |
| Out            | 0                   | 0         | ... | -0.528      |
| Exp. Out       | 0                   | 0         | ... | -0.528      |
| Out (DSP)      | 0                   | 0         | ... | -1132797631 |
| Exp. Out (DSP) | 0                   | 0         | ... | -1132797631 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 67  |
| Max CPU cycles  | 231 |
| Avg CPU cycles  | 206 |

**Test case: Conversion test****OK**

Conversion test for Control block PI.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611876         | ... | 1342177280        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PI.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+02$ |
| Tolerance b1              | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2499 |
| Max CPU cycles  | 4355 |
| Avg CPU cycles  | 3741 |

**Verification: PI FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block PI.

| Test results   |                     |           |     |             |
|----------------|---------------------|-----------|-----|-------------|
| Time step      | 1                   | 2         | ... | 201         |
| CPU cycles     | 64                  | 64        | ... | 647         |
| Inputs         |                     |           |     |             |
| In (DSP)       | 0                   | 0         | ... | 0           |
| Init (DSP)     | 236223201           | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0                   | 0         | ... | 1           |
| In             | 0                   | 0         | ... | 0           |
| Init           | 0.11                | 0.11      | ... | 0.11        |
| Enable         | 0                   | 0         | ... | 1           |
| Parameters     |                     |           |     |             |
| Kp             | 2                   |           |     |             |
| Ki             | 2500                |           |     |             |
| initHandling   | initialize integral |           |     |             |
| ts_fact        | 1                   |           |     |             |
| Outputs        |                     |           |     |             |
| Out            | 0                   | 0         | ... | -0.528      |
| Exp. Out       | 0                   | 0         | ... | -0.528      |
| Out (DSP)      | 0                   | 0         | ... | -1132797631 |
| Exp. Out (DSP) | 0                   | 0         | ... | -1132797631 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 64  |
| Max CPU cycles  | 666 |
| Avg CPU cycles  | 604 |

**Test case: Conversion test****OK**

Conversion test for Control block PI.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611876         | ... | 1342177280        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PI.



| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e+02$ |
| Tolerance b1           | $\pm 1,0000e+02$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 7253  |
| Max CPU cycles  | 15987 |
| Avg CPU cycles  | 13506 |

**Verification: PI Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block PI.

| Test results   |                     |      |     |       |
|----------------|---------------------|------|-----|-------|
| Time step      | 1                   | 2    | ... | 201   |
| CPU cycles     | 71                  | 71   | ... | 117   |
| Inputs         |                     |      |     |       |
| In (DSP)       | 0                   | 0    | ... | 0     |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11  |
| Enable (DSP)   | 0                   | 0    | ... | 1     |
| In             | 0                   | 0    | ... | 0     |
| Init           | 0.11                | 0.11 | ... | 0.11  |
| Enable         | 0                   | 0    | ... | 1     |
| Parameters     |                     |      |     |       |
| Kp             | 2                   |      |     |       |
| Ki             | 2500                |      |     |       |
| initHandling   | initialize integral |      |     |       |
| ts_fact        | 1                   |      |     |       |
| Outputs        |                     |      |     |       |
| Out            | 0                   | 0    | ... | -1.84 |
| Exp. Out       | 0                   | 0    | ... | -1.84 |
| Out (DSP)      | 0                   | 0    | ... | -1.84 |
| Exp. Out (DSP) | 0                   | 0    | ... | -1.84 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 71  |
| Max CPU cycles  | 132 |
| Avg CPU cycles  | 116 |

**Test case: Conversion test****OK**

Conversion test for Control block PI.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PI.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e-10$ |
| Tolerance b1              | $\pm 1,0000e-06$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1914 |
| Max CPU cycles  | 1936 |
| Avg CPU cycles  | 1914 |

**Verification: PI Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block PI.

| Test results   |                     |      |     |       |
|----------------|---------------------|------|-----|-------|
| Time step      | 1                   | 2    | ... | 201   |
| CPU cycles     | 41                  | 41   | ... | 87    |
| Inputs         |                     |      |     |       |
| In (DSP)       | 0                   | 0    | ... | 0     |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11  |
| Enable (DSP)   | 0                   | 0    | ... | 1     |
| In             | 0                   | 0    | ... | 0     |
| Init           | 0.11                | 0.11 | ... | 0.11  |
| Enable         | 0                   | 0    | ... | 1     |
| Parameters     |                     |      |     |       |
| Kp             | 2                   |      |     |       |
| Ki             | 2500                |      |     |       |
| initHandling   | initialize integral |      |     |       |
| ts_fact        | 1                   |      |     |       |
| Outputs        |                     |      |     |       |
| Out            | 0                   | 0    | ... | -1.84 |
| Exp. Out       | 0                   | 0    | ... | -1.84 |
| Out (DSP)      | 0                   | 0    | ... | -1.84 |
| Exp. Out (DSP) | 0                   | 0    | ... | -1.84 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 41  |
| Max CPU cycles  | 101 |
| Avg CPU cycles  | 86  |

**Test case: Conversion test****OK**

Conversion test for Control block PI.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PI.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e-10$ |
| Tolerance b1              | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 903 |
| Max CPU cycles  | 903 |
| Avg CPU cycles  | 903 |

**Verification: PI Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block PI.

| Test results   |                     |      |     |       |
|----------------|---------------------|------|-----|-------|
| Time step      | 1                   | 2    | ... | 201   |
| CPU cycles     | 81                  | 81   | ... | 133   |
| Inputs         |                     |      |     |       |
| In (DSP)       | 0                   | 0    | ... | 0     |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11  |
| Enable (DSP)   | 0                   | 0    | ... | 1     |
| In             | 0                   | 0    | ... | 0     |
| Init           | 0.11                | 0.11 | ... | 0.11  |
| Enable         | 0                   | 0    | ... | 1     |
| Parameters     |                     |      |     |       |
| Kp             | 2                   |      |     |       |
| Ki             | 2500                |      |     |       |
| initHandling   | initialize integral |      |     |       |
| ts_fact        | 1                   |      |     |       |
| Outputs        |                     |      |     |       |
| Out            | 0                   | 0    | ... | -1.84 |
| Exp. Out       | 0                   | 0    | ... | -1.84 |
| Out (DSP)      | 0                   | 0    | ... | -1.84 |
| Exp. Out (DSP) | 0                   | 0    | ... | -1.84 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 81  |
| Max CPU cycles  | 148 |
| Avg CPU cycles  | 132 |

**Test case: Conversion test****OK**

Conversion test for Control block PI.



| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PI.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e-10$ |
| Tolerance b1              | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 916 |
| Max CPU cycles  | 921 |
| Avg CPU cycles  | 916 |

**Verification: PI Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block PI.

| Test results   |                     |      |     |       |
|----------------|---------------------|------|-----|-------|
| Time step      | 1                   | 2    | ... | 201   |
| CPU cycles     | 81                  | 81   | ... | 676   |
| Inputs         |                     |      |     |       |
| In (DSP)       | 0                   | 0    | ... | 0     |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11  |
| Enable (DSP)   | 0                   | 0    | ... | 1     |
| In             | 0                   | 0    | ... | 0     |
| Init           | 0.11                | 0.11 | ... | 0.11  |
| Enable         | 0                   | 0    | ... | 1     |
| Parameters     |                     |      |     |       |
| Kp             | 2                   |      |     |       |
| Ki             | 2500                |      |     |       |
| initHandling   | initialize integral |      |     |       |
| ts_fact        | 1                   |      |     |       |
| Outputs        |                     |      |     |       |
| Out            | 0                   | 0    | ... | -1.84 |
| Exp. Out       | 0                   | 0    | ... | -1.84 |
| Out (DSP)      | 0                   | 0    | ... | -1.84 |
| Exp. Out (DSP) | 0                   | 0    | ... | -1.84 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 81  |
| Max CPU cycles  | 958 |
| Avg CPU cycles  | 818 |

**Test case: Conversion test****OK**

Conversion test for Control block PI.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PI.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e-10$ |
| Tolerance b1              | $\pm 1,0000e-06$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2059 |
| Max CPU cycles  | 2234 |
| Avg CPU cycles  | 2170 |

**Verification: PI Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block PI.

| Test results   |                     |      |     |       |
|----------------|---------------------|------|-----|-------|
| Time step      | 1                   | 2    | ... | 201   |
| CPU cycles     | 65                  | 65   | ... | 288   |
| Inputs         |                     |      |     |       |
| In (DSP)       | 0                   | 0    | ... | 0     |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11  |
| Enable (DSP)   | 0                   | 0    | ... | 1     |
| In             | 0                   | 0    | ... | 0     |
| Init           | 0.11                | 0.11 | ... | 0.11  |
| Enable         | 0                   | 0    | ... | 1     |
| Parameters     |                     |      |     |       |
| Kp             | 2                   |      |     |       |
| Ki             | 2500                |      |     |       |
| initHandling   | initialize integral |      |     |       |
| ts_fact        | 1                   |      |     |       |
| Outputs        |                     |      |     |       |
| Out            | 0                   | 0    | ... | -1.84 |
| Exp. Out       | 0                   | 0    | ... | -1.84 |
| Out (DSP)      | 0                   | 0    | ... | -1.84 |
| Exp. Out (DSP) | 0                   | 0    | ... | -1.84 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 65  |
| Max CPU cycles  | 386 |
| Avg CPU cycles  | 346 |

**Test case: Conversion test****OK**

Conversion test for Control block PI.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PI.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e-10$ |
| Tolerance b1              | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 742 |
| Max CPU cycles  | 761 |
| Avg CPU cycles  | 758 |



**Verification: PI Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block PI.

| Test results   |                     |      |     |       |
|----------------|---------------------|------|-----|-------|
| Time step      | 1                   | 2    | ... | 201   |
| CPU cycles     | 81                  | 60   | ... | 104   |
| Inputs         |                     |      |     |       |
| In (DSP)       | 0                   | 0    | ... | 0     |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11  |
| Enable (DSP)   | 0                   | 0    | ... | 1     |
| In             | 0                   | 0    | ... | 0     |
| Init           | 0.11                | 0.11 | ... | 0.11  |
| Enable         | 0                   | 0    | ... | 1     |
| Parameters     |                     |      |     |       |
| Kp             | 2                   |      |     |       |
| Ki             | 2500                |      |     |       |
| initHandling   | initialize integral |      |     |       |
| ts_fact        | 1                   |      |     |       |
| Outputs        |                     |      |     |       |
| Out            | 0                   | 0    | ... | -1.84 |
| Exp. Out       | 0                   | 0    | ... | -1.84 |
| Out (DSP)      | 0                   | 0    | ... | -1.84 |
| Exp. Out (DSP) | 0                   | 0    | ... | -1.84 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 60  |
| Max CPU cycles  | 151 |
| Avg CPU cycles  | 103 |

**Test case: Conversion test****OK**

Conversion test for Control block PI.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| <b>Time step</b>             | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PI.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| <b>Time step</b>             | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e-10$ |
| Tolerance b1              | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 843 |
| Max CPU cycles  | 989 |
| Avg CPU cycles  | 848 |

**Verification: PI Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block PI.

| Test results   |                     |      |     |       |
|----------------|---------------------|------|-----|-------|
| Time step      | 1                   | 2    | ... | 201   |
| CPU cycles     | 63                  | 63   | ... | 118   |
| Inputs         |                     |      |     |       |
| In (DSP)       | 0                   | 0    | ... | 0     |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11  |
| Enable (DSP)   | 0                   | 0    | ... | 1     |
| In             | 0                   | 0    | ... | 0     |
| Init           | 0.11                | 0.11 | ... | 0.11  |
| Enable         | 0                   | 0    | ... | 1     |
| Parameters     |                     |      |     |       |
| Kp             | 2                   |      |     |       |
| Ki             | 2500                |      |     |       |
| initHandling   | initialize integral |      |     |       |
| ts_fact        | 1                   |      |     |       |
| Outputs        |                     |      |     |       |
| Out            | 0                   | 0    | ... | -1.84 |
| Exp. Out       | 0                   | 0    | ... | -1.84 |
| Out (DSP)      | 0                   | 0    | ... | -1.84 |
| Exp. Out (DSP) | 0                   | 0    | ... | -1.84 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 63  |
| Max CPU cycles  | 137 |
| Avg CPU cycles  | 117 |

**Test case: Conversion test****OK**

Conversion test for Control block PI.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PI.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e-10$ |
| Tolerance b1              | $\pm 1,0000e-06$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1429 |
| Max CPU cycles  | 1451 |
| Avg CPU cycles  | 1429 |

**Verification: PI Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block PI.

| Test results   |                     |      |     |       |
|----------------|---------------------|------|-----|-------|
| Time step      | 1                   | 2    | ... | 201   |
| CPU cycles     | 64                  | 64   | ... | 750   |
| Inputs         |                     |      |     |       |
| In (DSP)       | 0                   | 0    | ... | 0     |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11  |
| Enable (DSP)   | 0                   | 0    | ... | 1     |
| In             | 0                   | 0    | ... | 0     |
| Init           | 0.11                | 0.11 | ... | 0.11  |
| Enable         | 0                   | 0    | ... | 1     |
| Parameters     |                     |      |     |       |
| Kp             | 2                   |      |     |       |
| Ki             | 2500                |      |     |       |
| initHandling   | initialize integral |      |     |       |
| ts_fact        | 1                   |      |     |       |
| Outputs        |                     |      |     |       |
| Out            | 0                   | 0    | ... | -1.84 |
| Exp. Out       | 0                   | 0    | ... | -1.84 |
| Out (DSP)      | 0                   | 0    | ... | -1.84 |
| Exp. Out (DSP) | 0                   | 0    | ... | -1.84 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 64   |
| Max CPU cycles  | 1039 |
| Avg CPU cycles  | 915  |

**Test case: Conversion test****OK**

Conversion test for Control block PI.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PI.


| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |



| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e-10$ |
| Tolerance b1              | $\pm 1,0000e-06$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2488 |
| Max CPU cycles  | 3225 |
| Avg CPU cycles  | 3201 |

## Block: PID



PID controller:

$$G(s) = K_p + K_i/s + K_d*s/(s/(2*\pi*f_c) + 1)$$

| Inports |                                                                                                                               |
|---------|-------------------------------------------------------------------------------------------------------------------------------|
| In      | Control error input                                                                                                           |
| Init    | Initial value of output Out when enabled                                                                                      |
| Enable  | Enable == 0: Deactivation of block; Out set to 0<br>Enable 0->1: Preload of integral part<br>Enable == 1: Activation of block |

| Outputs |               |
|---------|---------------|
| Out     | Control value |

| Mask Parameters |    |                                                                 |
|-----------------|----|-----------------------------------------------------------------|
| Name            | ID | Description                                                     |
| Kp              | 1  | Proportional Factor                                             |
| Ki              | 2  | Integral Factor                                                 |
| Kd              | 3  | Derivative Factor                                               |
| fc              | 4  | Cutoff frequency of realization low pass                        |
| initHandling    | 5  | Determines what the signal provided on Init input is used for   |
| ts_fact         | 6  | Multiplication factor of base sampling time (in integer format) |

### Description:

#### Preloading Integral

A rising edge at the *Enable* inport enables the controller and preloads the integral.

One may choose from two options how to preload the integral value:

- Preload the integral from the *Init* inport.
- Preload the integral such that the first output of the controller matches the current value at the *Init* inport.  
This option allows controller switching without disturbing the control.

**Note:** Each fixed point implementation uses the next higher integer data type for the integral value storage variable.

**Transfer function** (zero-order hold discretization method):

When the block is enabled, the PID controller realizes the following transfer function:

$$G(z) = K_p + K_i T_s \frac{1}{z-1} + K_d 2\pi f_c \frac{z-1}{z - e^{-2\pi f_c T_s}}$$

**FiP8 bug:** When using the TI compiler the step response of the derivative part does not return to zero, but generates an overflow at zero crossing if the derivative parameter value is too high.

**Developer note:** For the fixed point implementations the source code of block *PIDLimit* is used.

#### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

#### Implementation: FiP8

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | int8 |
| Init              | int8 |
| Enable            | bool |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

#### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |
| Init              | int16 |
| Enable            | bool  |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

#### Implementation: FiP32

---

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |
| Init              | int32 |
| Enable            | bool  |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |
| Init              | float32 |
| Enable            | bool    |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |
| Init              | float64 |
| Enable            | bool    |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: PID FiP16 CPU TMS320F28335**

Date of Test 2026-06-19  
Target controller TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block PID.

| Test results   |                     |      |      |      |     |        |
|----------------|---------------------|------|------|------|-----|--------|
| Time step      | 1                   | 2    | 3    | 4    | ... | 201    |
| CPU cycles     | 80                  | 80   | 80   | 165  | ... | 175    |
| Inputs         |                     |      |      |      |     |        |
| In (DSP)       | 0                   | 0    | 0    | 0    | ... | 0      |
| Init (DSP)     | 3604                | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0                   | 0    | 0    | 1    | ... | 1      |
| In             | 0                   | 0    | 0    | 0    | ... | 0      |
| Init           | 0.11                | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0                   | 0    | 0    | 1    | ... | 1      |
| Parameters     |                     |      |      |      |     |        |
| Kp             | 2                   |      |      |      |     |        |
| Ki             | 2500                |      |      |      |     |        |
| Kd             | 0.003               |      |      |      |     |        |
| fc             | 200                 |      |      |      |     |        |
| initHandling   | initialize integral |      |      |      |     |        |
| ts_fact        | 1                   |      |      |      |     |        |
| Outputs        |                     |      |      |      |     |        |
| Out            | 0                   | 0    | 0    | 0.11 | ... | -0.526 |
| Exp. Out       | 0                   | 0    | 0    | 0.11 | ... | -0.526 |
| Out (DSP)      | 0                   | 0    | 0    | 3604 | ... | -17231 |
| Exp. Out (DSP) | 0                   | 0    | 0    | 3604 | ... | -17228 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 80  |
| Max CPU cycles  | 175 |
| Avg CPU cycles  | 171 |

**Test case: Conversion test****OK**

Conversion test for Control block PID.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 2048       |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 2048       |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PID.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26373              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26373               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 204        |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 204        |



| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 1,0000e+00$ |
| Tolerance a0d             | $\pm 1,0000e+00$ |
| Tolerance b0d             | $\pm 1,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 5087  |
| Max CPU cycles  | 14657 |
| Avg CPU cycles  | 12746 |

**Verification: PID FiP16 CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block PID.

| Test results   |                     |      |      |      |     |        |
|----------------|---------------------|------|------|------|-----|--------|
| Time step      | 1                   | 2    | 3    | 4    | ... | 201    |
| CPU cycles     | 57                  | 57   | 57   | 117  | ... | 125    |
| Inputs         |                     |      |      |      |     |        |
| In (DSP)       | 0                   | 0    | 0    | 0    | ... | 0      |
| Init (DSP)     | 3604                | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0                   | 0    | 0    | 1    | ... | 1      |
| In             | 0                   | 0    | 0    | 0    | ... | 0      |
| Init           | 0.11                | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0                   | 0    | 0    | 1    | ... | 1      |
| Parameters     |                     |      |      |      |     |        |
| Kp             | 2                   |      |      |      |     |        |
| Ki             | 2500                |      |      |      |     |        |
| Kd             | 0.003               |      |      |      |     |        |
| fc             | 200                 |      |      |      |     |        |
| initHandling   | initialize integral |      |      |      |     |        |
| ts_fact        | 1                   |      |      |      |     |        |
| Outputs        |                     |      |      |      |     |        |
| Out            | 0                   | 0    | 0    | 0.11 | ... | -0.526 |
| Exp. Out       | 0                   | 0    | 0    | 0.11 | ... | -0.526 |
| Out (DSP)      | 0                   | 0    | 0    | 3604 | ... | -17231 |
| Exp. Out (DSP) | 0                   | 0    | 0    | 3604 | ... | -17228 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 57  |
| Max CPU cycles  | 125 |
| Avg CPU cycles  | 121 |

**Test case: Conversion test****OK**

Conversion test for Control block PID.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 2048       |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 2048       |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PID.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26373              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26373               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 2048       |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 2048       |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 1,0000e+00$ |
| Tolerance a0d             | $\pm 1,0000e+00$ |
| Tolerance b0d             | $\pm 1,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2373 |
| Max CPU cycles  | 8689 |
| Avg CPU cycles  | 7188 |

**Verification: PID FiP16 CPU STM32G474RE**

Date of Test 2026-06-19  
Target controller STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block PID.

| Test results   |                     |      |      |      |     |        |
|----------------|---------------------|------|------|------|-----|--------|
| Time step      | 1                   | 2    | 3    | 4    | ... | 201    |
| CPU cycles     | 82                  | 82   | 82   | 188  | ... | 188    |
| Inputs         |                     |      |      |      |     |        |
| In (DSP)       | 0                   | 0    | 0    | 0    | ... | 0      |
| Init (DSP)     | 3604                | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0                   | 0    | 0    | 1    | ... | 1      |
| In             | 0                   | 0    | 0    | 0    | ... | 0      |
| Init           | 0.11                | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0                   | 0    | 0    | 1    | ... | 1      |
| Parameters     |                     |      |      |      |     |        |
| Kp             | 2                   |      |      |      |     |        |
| Ki             | 2500                |      |      |      |     |        |
| Kd             | 0.003               |      |      |      |     |        |
| fc             | 200                 |      |      |      |     |        |
| initHandling   | initialize integral |      |      |      |     |        |
| ts_fact        | 1                   |      |      |      |     |        |
| Outputs        |                     |      |      |      |     |        |
| Out            | 0                   | 0    | 0    | 0.11 | ... | -0.526 |
| Exp. Out       | 0                   | 0    | 0    | 0.11 | ... | -0.526 |
| Out (DSP)      | 0                   | 0    | 0    | 3604 | ... | -17231 |
| Exp. Out (DSP) | 0                   | 0    | 0    | 3604 | ... | -17228 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 82  |
| Max CPU cycles  | 188 |
| Avg CPU cycles  | 174 |

**Test case: Conversion test****OK**

Conversion test for Control block PID.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 2048       |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 2048       |



| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PID.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26373              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26373               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 2048       |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 2048       |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 1,0000e+00$ |
| Tolerance a0d             | $\pm 1,0000e+00$ |
| Tolerance b0d             | $\pm 1,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2606 |
| Max CPU cycles  | 4949 |
| Avg CPU cycles  | 4396 |

**Verification: PID FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block PID.

| Test results   |                     |      |      |      |     |        |
|----------------|---------------------|------|------|------|-----|--------|
| Time step      | 1                   | 2    | 3    | 4    | ... | 201    |
| CPU cycles     | 77                  | 77   | 77   | 176  | ... | 189    |
| Inputs         |                     |      |      |      |     |        |
| In (DSP)       | 0                   | 0    | 0    | 0    | ... | 0      |
| Init (DSP)     | 3604                | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0                   | 0    | 0    | 1    | ... | 1      |
| In             | 0                   | 0    | 0    | 0    | ... | 0      |
| Init           | 0.11                | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0                   | 0    | 0    | 1    | ... | 1      |
| Parameters     |                     |      |      |      |     |        |
| Kp             | 2                   |      |      |      |     |        |
| Ki             | 2500                |      |      |      |     |        |
| Kd             | 0.003               |      |      |      |     |        |
| fc             | 200                 |      |      |      |     |        |
| initHandling   | initialize integral |      |      |      |     |        |
| ts_fact        | 1                   |      |      |      |     |        |
| Outputs        |                     |      |      |      |     |        |
| Out            | 0                   | 0    | 0    | 0.11 | ... | -0.526 |
| Exp. Out       | 0                   | 0    | 0    | 0.11 | ... | -0.526 |
| Out (DSP)      | 0                   | 0    | 0    | 3604 | ... | -17231 |
| Exp. Out (DSP) | 0                   | 0    | 0    | 3604 | ... | -17228 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 77  |
| Max CPU cycles  | 249 |
| Avg CPU cycles  | 179 |

**Test case: Conversion test****OK**

Conversion test for Control block PID.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 2048       |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 2048       |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PID.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26373              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26373               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 2048       |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 2048       |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 1,0000e+00$ |
| Tolerance a0d             | $\pm 1,0000e+00$ |
| Tolerance b0d             | $\pm 1,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 10053 |
| Max CPU cycles  | 23335 |
| Avg CPU cycles  | 20428 |



**Verification: PID FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block PID.

| Test results   |                     |      |      |      |     |        |
|----------------|---------------------|------|------|------|-----|--------|
| Time step      | 1                   | 2    | 3    | 4    | ... | 201    |
| CPU cycles     | 31                  | 31   | 31   | 100  | ... | 111    |
| Inputs         |                     |      |      |      |     |        |
| In (DSP)       | 0                   | 0    | 0    | 0    | ... | 0      |
| Init (DSP)     | 3604                | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0                   | 0    | 0    | 1    | ... | 1      |
| In             | 0                   | 0    | 0    | 0    | ... | 0      |
| Init           | 0.11                | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0                   | 0    | 0    | 1    | ... | 1      |
| Parameters     |                     |      |      |      |     |        |
| Kp             | 2                   |      |      |      |     |        |
| Ki             | 2500                |      |      |      |     |        |
| Kd             | 0.003               |      |      |      |     |        |
| fc             | 200                 |      |      |      |     |        |
| initHandling   | initialize integral |      |      |      |     |        |
| ts_fact        | 1                   |      |      |      |     |        |
| Outputs        |                     |      |      |      |     |        |
| Out            | 0                   | 0    | 0    | 0.11 | ... | -0.526 |
| Exp. Out       | 0                   | 0    | 0    | 0.11 | ... | -0.526 |
| Out (DSP)      | 0                   | 0    | 0    | 3604 | ... | -17231 |
| Exp. Out (DSP) | 0                   | 0    | 0    | 3604 | ... | -17228 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 31  |
| Max CPU cycles  | 111 |
| Avg CPU cycles  | 105 |

**Test case: Conversion test****OK**

Conversion test for Control block PID.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 204        |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 204        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PID.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26373              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26373               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 204        |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 204        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 1,0000e+00$ |
| Tolerance a0d             | $\pm 1,0000e+00$ |
| Tolerance b0d             | $\pm 1,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3200 |
| Max CPU cycles  | 8384 |
| Avg CPU cycles  | 7391 |

**Verification: PID FiP16 CPU XMC4800-F144K2048**

Date of Test 2026-06-19  
Target controller XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block PID.

| Test results   |                     |      |      |      |     |        |
|----------------|---------------------|------|------|------|-----|--------|
| Time step      | 1                   | 2    | 3    | 4    | ... | 201    |
| CPU cycles     | 81                  | 59   | 59   | 155  | ... | 142    |
| Inputs         |                     |      |      |      |     |        |
| In (DSP)       | 0                   | 0    | 0    | 0    | ... | 0      |
| Init (DSP)     | 3604                | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0                   | 0    | 0    | 1    | ... | 1      |
| In             | 0                   | 0    | 0    | 0    | ... | 0      |
| Init           | 0.11                | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0                   | 0    | 0    | 1    | ... | 1      |
| Parameters     |                     |      |      |      |     |        |
| Kp             | 2                   |      |      |      |     |        |
| Ki             | 2500                |      |      |      |     |        |
| Kd             | 0.003               |      |      |      |     |        |
| fc             | 200                 |      |      |      |     |        |
| initHandling   | initialize integral |      |      |      |     |        |
| ts_fact        | 1                   |      |      |      |     |        |
| Outputs        |                     |      |      |      |     |        |
| Out            | 0                   | 0    | 0    | 0.11 | ... | -0.526 |
| Exp. Out       | 0                   | 0    | 0    | 0.11 | ... | -0.526 |
| Out (DSP)      | 0                   | 0    | 0    | 3604 | ... | -17231 |
| Exp. Out (DSP) | 0                   | 0    | 0    | 3604 | ... | -17228 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 59  |
| Max CPU cycles  | 162 |
| Avg CPU cycles  | 138 |

**Test case: Conversion test****OK**

Conversion test for Control block PID.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 2048       |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 2048       |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PID.



| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26373              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26373               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 2048       |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 2048       |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 1,0000e+00$ |
| Tolerance a0d             | $\pm 1,0000e+00$ |
| Tolerance b0d             | $\pm 1,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2119 |
| Max CPU cycles  | 4443 |
| Avg CPU cycles  | 3912 |

**Verification: PID FiP16 CPU TMS320F28379D**

Date of Test 2026-06-22  
Target controller TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block PID.

| Test results   |                     |      |      |      |     |        |
|----------------|---------------------|------|------|------|-----|--------|
| Time step      | 1                   | 2    | 3    | 4    | ... | 201    |
| CPU cycles     | 70                  | 70   | 70   | 167  | ... | 177    |
| Inputs         |                     |      |      |      |     |        |
| In (DSP)       | 0                   | 0    | 0    | 0    | ... | 0      |
| Init (DSP)     | 3604                | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0                   | 0    | 0    | 1    | ... | 1      |
| In             | 0                   | 0    | 0    | 0    | ... | 0      |
| Init           | 0.11                | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0                   | 0    | 0    | 1    | ... | 1      |
| Parameters     |                     |      |      |      |     |        |
| Kp             | 2                   |      |      |      |     |        |
| Ki             | 2500                |      |      |      |     |        |
| Kd             | 0.003               |      |      |      |     |        |
| fc             | 200                 |      |      |      |     |        |
| initHandling   | initialize integral |      |      |      |     |        |
| ts_fact        | 1                   |      |      |      |     |        |
| Outputs        |                     |      |      |      |     |        |
| Out            | 0                   | 0    | 0    | 0.11 | ... | -0.526 |
| Exp. Out       | 0                   | 0    | 0    | 0.11 | ... | -0.526 |
| Out (DSP)      | 0                   | 0    | 0    | 3604 | ... | -17231 |
| Exp. Out (DSP) | 0                   | 0    | 0    | 3604 | ... | -17228 |

| Test settings |                                         |
|---------------|-----------------------------------------|
| Tolerance Out | $\pm 3,0518\text{e-}04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 70  |
| Max CPU cycles  | 180 |
| Avg CPU cycles  | 174 |

**Test case: Conversion test****OK**

Conversion test for Control block PID.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 2048       |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 2048       |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PID.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26373              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26373               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 2048       |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 2048       |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 1,0000e+00$ |
| Tolerance a0d             | $\pm 1,0000e+00$ |
| Tolerance b0d             | $\pm 1,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 3687  |
| Max CPU cycles  | 11219 |
| Avg CPU cycles  | 9710  |

**Verification: PID FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block PID.

| Test results   |                     |      |      |      |     |        |
|----------------|---------------------|------|------|------|-----|--------|
| Time step      | 1                   | 2    | 3    | 4    | ... | 201    |
| CPU cycles     | 53                  | 53   | 53   | 154  | ... | 180    |
| Inputs         |                     |      |      |      |     |        |
| In (DSP)       | 0                   | 0    | 0    | 0    | ... | 0      |
| Init (DSP)     | 3604                | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0                   | 0    | 0    | 1    | ... | 1      |
| In             | 0                   | 0    | 0    | 0    | ... | 0      |
| Init           | 0.11                | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0                   | 0    | 0    | 1    | ... | 1      |
| Parameters     |                     |      |      |      |     |        |
| Kp             | 2                   |      |      |      |     |        |
| Ki             | 2500                |      |      |      |     |        |
| Kd             | 0.003               |      |      |      |     |        |
| fc             | 200                 |      |      |      |     |        |
| initHandling   | initialize integral |      |      |      |     |        |
| ts_fact        | 1                   |      |      |      |     |        |
| Outputs        |                     |      |      |      |     |        |
| Out            | 0                   | 0    | 0    | 0.11 | ... | -0.526 |
| Exp. Out       | 0                   | 0    | 0    | 0.11 | ... | -0.526 |
| Out (DSP)      | 0                   | 0    | 0    | 3604 | ... | -17231 |
| Exp. Out (DSP) | 0                   | 0    | 0    | 3604 | ... | -17228 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 53  |
| Max CPU cycles  | 180 |
| Avg CPU cycles  | 169 |

**Test case: Conversion test****OK**

Conversion test for Control block PID.



| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 2048       |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 2048       |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PID.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26373              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26373               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 2048       |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 2048       |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 1,0000e+00$ |
| Tolerance a0d             | $\pm 1,0000e+00$ |
| Tolerance b0d             | $\pm 1,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 14127 |
| Max CPU cycles  | 48820 |
| Avg CPU cycles  | 42388 |

**Verification: PID FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block PID.

| Test results   |                     |           |     |             |
|----------------|---------------------|-----------|-----|-------------|
| Time step      | 1                   | 2         | ... | 201         |
| CPU cycles     | 84                  | 84        | ... | 425         |
| Inputs         |                     |           |     |             |
| In (DSP)       | 0                   | 0         | ... | 0           |
| Init (DSP)     | 236223201           | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0                   | 0         | ... | 1           |
| In             | 0                   | 0         | ... | 0           |
| Init           | 0.11                | 0.11      | ... | 0.11        |
| Enable         | 0                   | 0         | ... | 1           |
| Parameters     |                     |           |     |             |
| Kp             | 2                   |           |     |             |
| Ki             | 2500                |           |     |             |
| Kd             | 0.003               |           |     |             |
| fc             | 200                 |           |     |             |
| initHandling   | initialize integral |           |     |             |
| ts_fact        | 1                   |           |     |             |
| Outputs        |                     |           |     |             |
| Out            | 0                   | 0         | ... | -0.526      |
| Exp. Out       | 0                   | 0         | ... | -0.526      |
| Out (DSP)      | 0                   | 0         | ... | -1129025494 |
| Exp. Out (DSP) | 0                   | 0         | ... | -1129025494 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 84  |
| Max CPU cycles  | 431 |
| Avg CPU cycles  | 406 |

**Test case: Conversion test****OK**

Conversion test for Control block PID.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437568         | ... | 2058874161        |
| <b>a0d</b>                   | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>b0d</b>                   | 0                   | 1728437568          | ... | -2058874161       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611876         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PID.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437632         | ... | 2058874240        |
| <b>a0d</b>                   | -2147483647         | -2128824832         | ... | -1568527872       |
| <b>b0d</b>                   | 0                   | 1728437632          | ... | -2058874240       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |



| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 2,0000e+02$ |
| Tolerance a0d             | $\pm 2,0000e+02$ |
| Tolerance b0d             | $\pm 2,0000e+02$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+02$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 6090  |
| Max CPU cycles  | 16311 |
| Avg CPU cycles  | 13994 |

**Verification: PID FiP32 CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block PID.

| Test results   |                     |           |     |             |
|----------------|---------------------|-----------|-----|-------------|
| Time step      | 1                   | 2         | ... | 201         |
| CPU cycles     | 63                  | 63        | ... | 253         |
| Inputs         |                     |           |     |             |
| In (DSP)       | 0                   | 0         | ... | 0           |
| Init (DSP)     | 236223201           | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0                   | 0         | ... | 1           |
| In             | 0                   | 0         | ... | 0           |
| Init           | 0.11                | 0.11      | ... | 0.11        |
| Enable         | 0                   | 0         | ... | 1           |
| Parameters     |                     |           |     |             |
| Kp             | 2                   |           |     |             |
| Ki             | 2500                |           |     |             |
| Kd             | 0.003               |           |     |             |
| fc             | 200                 |           |     |             |
| initHandling   | initialize integral |           |     |             |
| ts_fact        | 1                   |           |     |             |
| Outputs        |                     |           |     |             |
| Out            | 0                   | 0         | ... | -0.526      |
| Exp. Out       | 0                   | 0         | ... | -0.526      |
| Out (DSP)      | 0                   | 0         | ... | -1129025494 |
| Exp. Out (DSP) | 0                   | 0         | ... | -1129025494 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 63  |
| Max CPU cycles  | 253 |
| Avg CPU cycles  | 237 |

**Test case: Conversion test****OK**

Conversion test for Control block PID.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437568         | ... | 2058874161        |
| <b>a0d</b>                   | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>b0d</b>                   | 0                   | 1728437568          | ... | -2058874161       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611876         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PID.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437632         | ... | 2058874240        |
| <b>a0d</b>                   | -2147483647         | -2128824832         | ... | -1568527872       |
| <b>b0d</b>                   | 0                   | 1728437632          | ... | -2058874240       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 2,0000e+02$ |
| Tolerance a0d             | $\pm 2,0000e+02$ |
| Tolerance b0d             | $\pm 2,0000e+02$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2341 |
| Max CPU cycles  | 6943 |
| Avg CPU cycles  | 5862 |

**Verification: PID FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block PID.

| Test results   |                     |           |     |             |
|----------------|---------------------|-----------|-----|-------------|
| Time step      | 1                   | 2         | ... | 201         |
| CPU cycles     | 89                  | 89        | ... | 296         |
| Inputs         |                     |           |     |             |
| In (DSP)       | 0                   | 0         | ... | 0           |
| Init (DSP)     | 236223201           | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0                   | 0         | ... | 1           |
| In             | 0                   | 0         | ... | 0           |
| Init           | 0.11                | 0.11      | ... | 0.11        |
| Enable         | 0                   | 0         | ... | 1           |
| Parameters     |                     |           |     |             |
| Kp             | 2                   |           |     |             |
| Ki             | 2500                |           |     |             |
| Kd             | 0.003               |           |     |             |
| fc             | 200                 |           |     |             |
| initHandling   | initialize integral |           |     |             |
| ts_fact        | 1                   |           |     |             |
| Outputs        |                     |           |     |             |
| Out            | 0                   | 0         | ... | -0.526      |
| Exp. Out       | 0                   | 0         | ... | -0.526      |
| Out (DSP)      | 0                   | 0         | ... | -1129025494 |
| Exp. Out (DSP) | 0                   | 0         | ... | -1129025494 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 89  |
| Max CPU cycles  | 296 |
| Avg CPU cycles  | 270 |

**Test case: Conversion test****OK**

Conversion test for Control block PID.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437568         | ... | 2058874161        |
| <b>a0d</b>                   | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>b0d</b>                   | 0                   | 1728437568          | ... | -2058874161       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611876         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |



| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PID.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437632         | ... | 2058874240        |
| <b>a0d</b>                   | -2147483647         | -2128824832         | ... | -1568527872       |
| <b>b0d</b>                   | 0                   | 1728437632          | ... | -2058874240       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 2,0000e+02$ |
| Tolerance a0d             | $\pm 2,0000e+02$ |
| Tolerance b0d             | $\pm 2,0000e+02$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3836 |
| Max CPU cycles  | 6293 |
| Avg CPU cycles  | 5747 |

**Verification: PID FiP32 CPU STM32F072RB**

Date of Test 2026-06-19  
Target controller STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block PID.

| Test results   |                     |           |     |             |
|----------------|---------------------|-----------|-----|-------------|
| Time step      | 1                   | 2         | ... | 201         |
| CPU cycles     | 88                  | 88        | ... | 686         |
| Inputs         |                     |           |     |             |
| In (DSP)       | 0                   | 0         | ... | 0           |
| Init (DSP)     | 236223201           | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0                   | 0         | ... | 1           |
| In             | 0                   | 0         | ... | 0           |
| Init           | 0.11                | 0.11      | ... | 0.11        |
| Enable         | 0                   | 0         | ... | 1           |
| Parameters     |                     |           |     |             |
| Kp             | 2                   |           |     |             |
| Ki             | 2500                |           |     |             |
| Kd             | 0.003               |           |     |             |
| fc             | 200                 |           |     |             |
| initHandling   | initialize integral |           |     |             |
| ts_fact        | 1                   |           |     |             |
| Outputs        |                     |           |     |             |
| Out            | 0                   | 0         | ... | -0.526      |
| Exp. Out       | 0                   | 0         | ... | -0.526      |
| Out (DSP)      | 0                   | 0         | ... | -1129025494 |
| Exp. Out (DSP) | 0                   | 0         | ... | -1129025494 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 88  |
| Max CPU cycles  | 753 |
| Avg CPU cycles  | 643 |

**Test case: Conversion test****OK**

Conversion test for Control block PID.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437568         | ... | 2058874161        |
| <b>a0d</b>                   | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>b0d</b>                   | 0                   | 1728437568          | ... | -2058874161       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611876         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PID.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437632         | ... | 2058874240        |
| <b>a0d</b>                   | -2147483647         | -2128824832         | ... | -1568527872       |
| <b>b0d</b>                   | 0                   | 1728437632          | ... | -2058874240       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 2,0000e+02$ |
| Tolerance a0d             | $\pm 2,0000e+02$ |
| Tolerance b0d             | $\pm 2,0000e+02$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+02$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 15408 |
| Max CPU cycles  | 29718 |
| Avg CPU cycles  | 26735 |



**Verification: PID FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block PID.

| Test results   |                     |           |     |             |
|----------------|---------------------|-----------|-----|-------------|
| Time step      | 1                   | 2         | ... | 201         |
| CPU cycles     | 31                  | 31        | ... | 196         |
| Inputs         |                     |           |     |             |
| In (DSP)       | 0                   | 0         | ... | 0           |
| Init (DSP)     | 236223201           | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0                   | 0         | ... | 1           |
| In             | 0                   | 0         | ... | 0           |
| Init           | 0.11                | 0.11      | ... | 0.11        |
| Enable         | 0                   | 0         | ... | 1           |
| Parameters     |                     |           |     |             |
| Kp             | 2                   |           |     |             |
| Ki             | 2500                |           |     |             |
| Kd             | 0.003               |           |     |             |
| fc             | 200                 |           |     |             |
| initHandling   | initialize integral |           |     |             |
| ts_fact        | 1                   |           |     |             |
| Outputs        |                     |           |     |             |
| Out            | 0                   | 0         | ... | -0.526      |
| Exp. Out       | 0                   | 0         | ... | -0.526      |
| Out (DSP)      | 0                   | 0         | ... | -1129025494 |
| Exp. Out (DSP) | 0                   | 0         | ... | -1129025494 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 31  |
| Max CPU cycles  | 200 |
| Avg CPU cycles  | 182 |

**Test case: Conversion test****OK**

Conversion test for Control block PID.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437568         | ... | 2058874161        |
| <b>a0d</b>                   | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>b0d</b>                   | 0                   | 1728437568          | ... | -2058874161       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611876         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PID.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437632         | ... | 2058874240        |
| <b>a0d</b>                   | -2147483647         | -2128824832         | ... | -1568527872       |
| <b>b0d</b>                   | 0                   | 1728437632          | ... | -2058874240       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 2,0000e+02$ |
| Tolerance a0d             | $\pm 2,0000e+02$ |
| Tolerance b0d             | $\pm 2,0000e+02$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+02$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 5332  |
| Max CPU cycles  | 10879 |
| Avg CPU cycles  | 9677  |

**Verification: PID FiP32 CPU XMC4800-F144K2048**

Date of Test 2026-06-19  
Target controller XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block PID.

| Test results   |                     |           |     |             |
|----------------|---------------------|-----------|-----|-------------|
| Time step      | 1                   | 2         | ... | 201         |
| CPU cycles     | 77                  | 59        | ... | 255         |
| Inputs         |                     |           |     |             |
| In (DSP)       | 0                   | 0         | ... | 0           |
| Init (DSP)     | 236223201           | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0                   | 0         | ... | 1           |
| In             | 0                   | 0         | ... | 0           |
| Init           | 0.11                | 0.11      | ... | 0.11        |
| Enable         | 0                   | 0         | ... | 1           |
| Parameters     |                     |           |     |             |
| Kp             | 2                   |           |     |             |
| Ki             | 2500                |           |     |             |
| Kd             | 0.003               |           |     |             |
| fc             | 200                 |           |     |             |
| initHandling   | initialize integral |           |     |             |
| ts_fact        | 1                   |           |     |             |
| Outputs        |                     |           |     |             |
| Out            | 0                   | 0         | ... | -0.526      |
| Exp. Out       | 0                   | 0         | ... | -0.526      |
| Out (DSP)      | 0                   | 0         | ... | -1129025494 |
| Exp. Out (DSP) | 0                   | 0         | ... | -1129025494 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 59  |
| Max CPU cycles  | 289 |
| Avg CPU cycles  | 242 |

**Test case: Conversion test****OK**

Conversion test for Control block PID.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437568         | ... | 2058874161        |
| <b>a0d</b>                   | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>b0d</b>                   | 0                   | 1728437568          | ... | -2058874161       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611876         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PID.



| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437632         | ... | 2058874240        |
| <b>a0d</b>                   | -2147483647         | -2128824832         | ... | -1568527872       |
| <b>b0d</b>                   | 0                   | 1728437632          | ... | -2058874240       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 2,0000e+02$ |
| Tolerance a0d             | $\pm 2,0000e+02$ |
| Tolerance b0d             | $\pm 2,0000e+02$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3528 |
| Max CPU cycles  | 5903 |
| Avg CPU cycles  | 5376 |

**Verification: PID FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block PID.

| Test results   |                     |           |     |             |
|----------------|---------------------|-----------|-----|-------------|
| Time step      | 1                   | 2         | ... | 201         |
| CPU cycles     | 72                  | 72        | ... | 366         |
| Inputs         |                     |           |     |             |
| In (DSP)       | 0                   | 0         | ... | 0           |
| Init (DSP)     | 236223201           | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0                   | 0         | ... | 1           |
| In             | 0                   | 0         | ... | 0           |
| Init           | 0.11                | 0.11      | ... | 0.11        |
| Enable         | 0                   | 0         | ... | 1           |
| Parameters     |                     |           |     |             |
| Kp             | 2                   |           |     |             |
| Ki             | 2500                |           |     |             |
| Kd             | 0.003               |           |     |             |
| fc             | 200                 |           |     |             |
| initHandling   | initialize integral |           |     |             |
| ts_fact        | 1                   |           |     |             |
| Outputs        |                     |           |     |             |
| Out            | 0                   | 0         | ... | -0.526      |
| Exp. Out       | 0                   | 0         | ... | -0.526      |
| Out (DSP)      | 0                   | 0         | ... | -1129025494 |
| Exp. Out (DSP) | 0                   | 0         | ... | -1129025494 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 72  |
| Max CPU cycles  | 376 |
| Avg CPU cycles  | 352 |

**Test case: Conversion test****OK**

Conversion test for Control block PID.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437568         | ... | 2058874161        |
| <b>a0d</b>                   | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>b0d</b>                   | 0                   | 1728437568          | ... | -2058874161       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611876         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PID.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437632         | ... | 2058874240        |
| <b>a0d</b>                   | -2147483647         | -2128824832         | ... | -1568527872       |
| <b>b0d</b>                   | 0                   | 1728437632          | ... | -2058874240       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 2,0000e+02$ |
| Tolerance a0d             | $\pm 2,0000e+02$ |
| Tolerance b0d             | $\pm 2,0000e+02$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+02$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 4340  |
| Max CPU cycles  | 12405 |
| Avg CPU cycles  | 10574 |

**Verification: PID FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block PID.

| Test results   |                     |           |     |             |
|----------------|---------------------|-----------|-----|-------------|
| Time step      | 1                   | 2         | ... | 201         |
| CPU cycles     | 64                  | 64        | ... | 1348        |
| Inputs         |                     |           |     |             |
| In (DSP)       | 0                   | 0         | ... | 0           |
| Init (DSP)     | 236223201           | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0                   | 0         | ... | 1           |
| In             | 0                   | 0         | ... | 0           |
| Init           | 0.11                | 0.11      | ... | 0.11        |
| Enable         | 0                   | 0         | ... | 1           |
| Parameters     |                     |           |     |             |
| Kp             | 2                   |           |     |             |
| Ki             | 2500                |           |     |             |
| Kd             | 0.003               |           |     |             |
| fc             | 200                 |           |     |             |
| initHandling   | initialize integral |           |     |             |
| ts_fact        | 1                   |           |     |             |
| Outputs        |                     |           |     |             |
| Out            | 0                   | 0         | ... | -0.526      |
| Exp. Out       | 0                   | 0         | ... | -0.526      |
| Out (DSP)      | 0                   | 0         | ... | -1129025494 |
| Exp. Out (DSP) | 0                   | 0         | ... | -1129025494 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 64   |
| Max CPU cycles  | 1379 |
| Avg CPU cycles  | 1296 |

**Test case: Conversion test****OK**

Conversion test for Control block PID.



| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437568         | ... | 2058874161        |
| <b>a0d</b>                   | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>b0d</b>                   | 0                   | 1728437568          | ... | -2058874161       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611876         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PID.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437632         | ... | 2058874240        |
| <b>a0d</b>                   | -2147483647         | -2128824832         | ... | -1568527872       |
| <b>b0d</b>                   | 0                   | 1728437632          | ... | -2058874240       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 2,0000e+02$ |
| Tolerance a0d             | $\pm 2,0000e+02$ |
| Tolerance b0d             | $\pm 2,0000e+02$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+02$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 15980 |
| Max CPU cycles  | 50882 |
| Avg CPU cycles  | 43326 |

**Verification: PID Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block PID.

| Test results   |                     |      |     |        |
|----------------|---------------------|------|-----|--------|
| Time step      | 1                   | 2    | ... | 201    |
| CPU cycles     | 86                  | 86   | ... | 159    |
| Inputs         |                     |      |     |        |
| In (DSP)       | 0                   | 0    | ... | 0      |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11   |
| Enable (DSP)   | 0                   | 0    | ... | 1      |
| In             | 0                   | 0    | ... | 0      |
| Init           | 0.11                | 0.11 | ... | 0.11   |
| Enable         | 0                   | 0    | ... | 1      |
| Parameters     |                     |      |     |        |
| Kp             | 2                   |      |     |        |
| Ki             | 2500                |      |     |        |
| Kd             | 0.003               |      |     |        |
| fc             | 200                 |      |     |        |
| initHandling   | initialize integral |      |     |        |
| ts_fact        | 1                   |      |     |        |
| Outputs        |                     |      |     |        |
| Out            | 0                   | 0    | ... | -1.838 |
| Exp. Out       | 0                   | 0    | ... | -1.838 |
| Out (DSP)      | 0                   | 0    | ... | -1.838 |
| Exp. Out (DSP) | 0                   | 0    | ... | -1.838 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 2,3283e-06$ ( $\pm 5000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 86  |
| Max CPU cycles  | 170 |
| Avg CPU cycles  | 157 |

**Test case: Conversion test****OK**

Conversion test for Control block PID.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.927         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.927        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 0,0000e+00$ |
| Tolerance a0d          | $\pm 1,0000e-15$ |
| Tolerance b0d          | $\pm 0,0000e+00$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PID.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.928         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.928        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 3,0000e-03$ |
| Tolerance a0d          | $\pm 1,0000e-07$ |
| Tolerance b0d          | $\pm 3,0000e-03$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e-10$ |
| Tolerance b1           | $\pm 1,0000e-06$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2955 |
| Max CPU cycles  | 3320 |
| Avg CPU cycles  | 3279 |

**Verification: PID Float32 CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block PID.

| Test results   |                     |      |     |        |
|----------------|---------------------|------|-----|--------|
| Time step      | 1                   | 2    | ... | 201    |
| CPU cycles     | 41                  | 41   | ... | 119    |
| Inputs         |                     |      |     |        |
| In (DSP)       | 0                   | 0    | ... | 0      |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11   |
| Enable (DSP)   | 0                   | 0    | ... | 1      |
| In             | 0                   | 0    | ... | 0      |
| Init           | 0.11                | 0.11 | ... | 0.11   |
| Enable         | 0                   | 0    | ... | 1      |
| Parameters     |                     |      |     |        |
| Kp             | 2                   |      |     |        |
| Ki             | 2500                |      |     |        |
| Kd             | 0.003               |      |     |        |
| fc             | 200                 |      |     |        |
| initHandling   | initialize integral |      |     |        |
| ts_fact        | 1                   |      |     |        |
| Outputs        |                     |      |     |        |
| Out            | 0                   | 0    | ... | -1.838 |
| Exp. Out       | 0                   | 0    | ... | -1.838 |
| Out (DSP)      | 0                   | 0    | ... | -1.838 |
| Exp. Out (DSP) | 0                   | 0    | ... | -1.838 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 2,3283e-06$ ( $\pm 5000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 41  |
| Max CPU cycles  | 119 |
| Avg CPU cycles  | 117 |

**Test case: Conversion test****OK**

Conversion test for Control block PID.



| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.927         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.927        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 0,0000e+00$ |
| Tolerance a0d          | $\pm 1,0000e-15$ |
| Tolerance b0d          | $\pm 0,0000e+00$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PID.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.928         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.928        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 3,0000e-03$ |
| Tolerance a0d          | $\pm 1,0000e-07$ |
| Tolerance b0d          | $\pm 3,0000e-03$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e-10$ |
| Tolerance b1           | $\pm 1,0000e-06$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1309 |
| Max CPU cycles  | 1355 |
| Avg CPU cycles  | 1351 |

**Verification: PID Float32 CPU STM32G474RE**

Date of Test 2026-06-19  
Target controller STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block PID.

| Test results   |                     |      |     |        |
|----------------|---------------------|------|-----|--------|
| Time step      | 1                   | 2    | ... | 201    |
| CPU cycles     | 73                  | 73   | ... | 173    |
| Inputs         |                     |      |     |        |
| In (DSP)       | 0                   | 0    | ... | 0      |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11   |
| Enable (DSP)   | 0                   | 0    | ... | 1      |
| In             | 0                   | 0    | ... | 0      |
| Init           | 0.11                | 0.11 | ... | 0.11   |
| Enable         | 0                   | 0    | ... | 1      |
| Parameters     |                     |      |     |        |
| Kp             | 2                   |      |     |        |
| Ki             | 2500                |      |     |        |
| Kd             | 0.003               |      |     |        |
| fc             | 200                 |      |     |        |
| initHandling   | initialize integral |      |     |        |
| ts_fact        | 1                   |      |     |        |
| Outputs        |                     |      |     |        |
| Out            | 0                   | 0    | ... | -1.838 |
| Exp. Out       | 0                   | 0    | ... | -1.838 |
| Out (DSP)      | 0                   | 0    | ... | -1.838 |
| Exp. Out (DSP) | 0                   | 0    | ... | -1.838 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 2,3283e-06$ ( $\pm 5000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 73  |
| Max CPU cycles  | 179 |
| Avg CPU cycles  | 171 |

**Test case: Conversion test****OK**

Conversion test for Control block PID.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.927         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.927        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 0,0000e+00$ |
| Tolerance a0d          | $\pm 1,0000e-15$ |
| Tolerance b0d          | $\pm 0,0000e+00$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PID.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.928         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.928        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 3,0000e-03$ |
| Tolerance a0d          | $\pm 1,0000e-07$ |
| Tolerance b0d          | $\pm 3,0000e-03$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e-10$ |
| Tolerance b1           | $\pm 1,0000e-06$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1488 |
| Max CPU cycles  | 1562 |
| Avg CPU cycles  | 1556 |

**Verification: PID Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block PID.

| Test results   |                     |      |     |        |
|----------------|---------------------|------|-----|--------|
| Time step      | 1                   | 2    | ... | 201    |
| CPU cycles     | 82                  | 82   | ... | 1440   |
| Inputs         |                     |      |     |        |
| In (DSP)       | 0                   | 0    | ... | 0      |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11   |
| Enable (DSP)   | 0                   | 0    | ... | 1      |
| In             | 0                   | 0    | ... | 0      |
| Init           | 0.11                | 0.11 | ... | 0.11   |
| Enable         | 0                   | 0    | ... | 1      |
| Parameters     |                     |      |     |        |
| Kp             | 2                   |      |     |        |
| Ki             | 2500                |      |     |        |
| Kd             | 0.003               |      |     |        |
| fc             | 200                 |      |     |        |
| initHandling   | initialize integral |      |     |        |
| ts_fact        | 1                   |      |     |        |
| Outputs        |                     |      |     |        |
| Out            | 0                   | 0    | ... | -1.838 |
| Exp. Out       | 0                   | 0    | ... | -1.838 |
| Out (DSP)      | 0                   | 0    | ... | -1.838 |
| Exp. Out (DSP) | 0                   | 0    | ... | -1.838 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 2,3283e-06$ ( $\pm 5000$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 82   |
| Max CPU cycles  | 1806 |
| Avg CPU cycles  | 1621 |

**Test case: Conversion test****OK**

Conversion test for Control block PID.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.927         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.927        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 0,0000e+00$ |
| Tolerance a0d          | $\pm 1,0000e-15$ |
| Tolerance b0d          | $\pm 0,0000e+00$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PID.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.928         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.928        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 3,0000e-03$ |
| Tolerance a0d          | $\pm 1,0000e-07$ |
| Tolerance b0d          | $\pm 3,0000e-03$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e-10$ |
| Tolerance b1           | $\pm 1,0000e-06$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 4055 |
| Max CPU cycles  | 7090 |
| Avg CPU cycles  | 6914 |



**Verification: PID Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block PID.

| Test results   |                     |      |     |        |
|----------------|---------------------|------|-----|--------|
| Time step      | 1                   | 2    | ... | 201    |
| CPU cycles     | 69                  | 69   | ... | 559    |
| Inputs         |                     |      |     |        |
| In (DSP)       | 0                   | 0    | ... | 0      |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11   |
| Enable (DSP)   | 0                   | 0    | ... | 1      |
| In             | 0                   | 0    | ... | 0      |
| Init           | 0.11                | 0.11 | ... | 0.11   |
| Enable         | 0                   | 0    | ... | 1      |
| Parameters     |                     |      |     |        |
| Kp             | 2                   |      |     |        |
| Ki             | 2500                |      |     |        |
| Kd             | 0.003               |      |     |        |
| fc             | 200                 |      |     |        |
| initHandling   | initialize integral |      |     |        |
| ts_fact        | 1                   |      |     |        |
| Outputs        |                     |      |     |        |
| Out            | 0                   | 0    | ... | -1.838 |
| Exp. Out       | 0                   | 0    | ... | -1.838 |
| Out (DSP)      | 0                   | 0    | ... | -1.838 |
| Exp. Out (DSP) | 0                   | 0    | ... | -1.838 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 2,3283e-06$ ( $\pm 5000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 69  |
| Max CPU cycles  | 731 |
| Avg CPU cycles  | 635 |

**Test case: Conversion test****OK**

Conversion test for Control block PID.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.927         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.927        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 0,0000e+00$ |
| Tolerance a0d          | $\pm 1,0000e-15$ |
| Tolerance b0d          | $\pm 0,0000e+00$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PID.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.928         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.928        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 3,0000e-03$ |
| Tolerance a0d          | $\pm 1,0000e-07$ |
| Tolerance b0d          | $\pm 3,0000e-03$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e-10$ |
| Tolerance b1           | $\pm 1,0000e-06$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1304 |
| Max CPU cycles  | 1551 |
| Avg CPU cycles  | 1538 |

**Verification: PID Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block PID.

| Test results   |                     |      |     |        |
|----------------|---------------------|------|-----|--------|
| Time step      | 1                   | 2    | ... | 201    |
| CPU cycles     | 78                  | 60   | ... | 136    |
| Inputs         |                     |      |     |        |
| In (DSP)       | 0                   | 0    | ... | 0      |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11   |
| Enable (DSP)   | 0                   | 0    | ... | 1      |
| In             | 0                   | 0    | ... | 0      |
| Init           | 0.11                | 0.11 | ... | 0.11   |
| Enable         | 0                   | 0    | ... | 1      |
| Parameters     |                     |      |     |        |
| Kp             | 2                   |      |     |        |
| Ki             | 2500                |      |     |        |
| Kd             | 0.003               |      |     |        |
| fc             | 200                 |      |     |        |
| initHandling   | initialize integral |      |     |        |
| ts_fact        | 1                   |      |     |        |
| Outputs        |                     |      |     |        |
| Out            | 0                   | 0    | ... | -1.838 |
| Exp. Out       | 0                   | 0    | ... | -1.838 |
| Out (DSP)      | 0                   | 0    | ... | -1.838 |
| Exp. Out (DSP) | 0                   | 0    | ... | -1.838 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 2,3283e-06$ ( $\pm 5000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 60  |
| Max CPU cycles  | 178 |
| Avg CPU cycles  | 135 |

**Test case: Conversion test****OK**

Conversion test for Control block PID.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.927         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.927        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 0,0000e+00$ |
| Tolerance a0d          | $\pm 1,0000e-15$ |
| Tolerance b0d          | $\pm 0,0000e+00$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PID.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.928         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.928        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 3,0000e-03$ |
| Tolerance a0d          | $\pm 1,0000e-07$ |
| Tolerance b0d          | $\pm 3,0000e-03$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e-10$ |
| Tolerance b1           | $\pm 1,0000e-06$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1391 |
| Max CPU cycles  | 1535 |
| Avg CPU cycles  | 1398 |

**Verification: PID Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block PID.

| Test results   |                     |      |     |        |
|----------------|---------------------|------|-----|--------|
| Time step      | 1                   | 2    | ... | 201    |
| CPU cycles     | 72                  | 72   | ... | 150    |
| Inputs         |                     |      |     |        |
| In (DSP)       | 0                   | 0    | ... | 0      |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11   |
| Enable (DSP)   | 0                   | 0    | ... | 1      |
| In             | 0                   | 0    | ... | 0      |
| Init           | 0.11                | 0.11 | ... | 0.11   |
| Enable         | 0                   | 0    | ... | 1      |
| Parameters     |                     |      |     |        |
| Kp             | 2                   |      |     |        |
| Ki             | 2500                |      |     |        |
| Kd             | 0.003               |      |     |        |
| fc             | 200                 |      |     |        |
| initHandling   | initialize integral |      |     |        |
| ts_fact        | 1                   |      |     |        |
| Outputs        |                     |      |     |        |
| Out            | 0                   | 0    | ... | -1.838 |
| Exp. Out       | 0                   | 0    | ... | -1.838 |
| Out (DSP)      | 0                   | 0    | ... | -1.838 |
| Exp. Out (DSP) | 0                   | 0    | ... | -1.838 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 2,3283e-06$ ( $\pm 5000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 72  |
| Max CPU cycles  | 175 |
| Avg CPU cycles  | 148 |

**Test case: Conversion test****OK**

Conversion test for Control block PID.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.927         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.927        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 0,0000e+00$ |
| Tolerance a0d          | $\pm 1,0000e-15$ |
| Tolerance b0d          | $\pm 0,0000e+00$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PID.



| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.928         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.928        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 3,0000e-03$ |
| Tolerance a0d          | $\pm 1,0000e-07$ |
| Tolerance b0d          | $\pm 3,0000e-03$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e-10$ |
| Tolerance b1           | $\pm 1,0000e-06$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2097 |
| Max CPU cycles  | 2396 |
| Avg CPU cycles  | 2356 |

**Verification: PID Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block PID.

| Test results   |                     |      |     |        |
|----------------|---------------------|------|-----|--------|
| Time step      | 1                   | 2    | ... | 201    |
| CPU cycles     | 64                  | 64   | ... | 1692   |
| Inputs         |                     |      |     |        |
| In (DSP)       | 0                   | 0    | ... | 0      |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11   |
| Enable (DSP)   | 0                   | 0    | ... | 1      |
| In             | 0                   | 0    | ... | 0      |
| Init           | 0.11                | 0.11 | ... | 0.11   |
| Enable         | 0                   | 0    | ... | 1      |
| Parameters     |                     |      |     |        |
| Kp             | 2                   |      |     |        |
| Ki             | 2500                |      |     |        |
| Kd             | 0.003               |      |     |        |
| fc             | 200                 |      |     |        |
| initHandling   | initialize integral |      |     |        |
| ts_fact        | 1                   |      |     |        |
| Outputs        |                     |      |     |        |
| Out            | 0                   | 0    | ... | -1.838 |
| Exp. Out       | 0                   | 0    | ... | -1.838 |
| Out (DSP)      | 0                   | 0    | ... | -1.838 |
| Exp. Out (DSP) | 0                   | 0    | ... | -1.838 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 2,3283e-06$ ( $\pm 5000$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 64   |
| Max CPU cycles  | 2170 |
| Avg CPU cycles  | 1876 |

**Test case: Conversion test****OK**

Conversion test for Control block PID.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.927         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.927        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 0,0000e+00$ |
| Tolerance a0d          | $\pm 1,0000e-15$ |
| Tolerance b0d          | $\pm 0,0000e+00$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK


Conversion-on-Target test for Control block PID.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.928         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.928        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 3,0000e-03$ |
| Tolerance a0d          | $\pm 1,0000e-07$ |
| Tolerance b0d          | $\pm 3,0000e-03$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e-10$ |
| Tolerance b1           | $\pm 1,0000e-06$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 5102 |
| Max CPU cycles  | 8863 |
| Avg CPU cycles  | 8469 |

## Block: PIDLimit



PID Controller with Output Limitation and anti wind-up method clamping:

$$G(s) = K_p + K_i/s + K_d*s/(s/(2*\pi*fc) + 1)$$

| Inports |                                                                                                                               |
|---------|-------------------------------------------------------------------------------------------------------------------------------|
| In      | Control error input                                                                                                           |
| Init    | Initial value of output Out when enabled                                                                                      |
| max     | Maximum output value                                                                                                          |
| min     | Minimum output value                                                                                                          |
| Enable  | Enable == 0: Deactivation of block; Out set to 0<br>Enable 0->1: Preload of integral part<br>Enable == 1: Activation of block |

| Outputs |               |
|---------|---------------|
| Out     | Control value |

| Mask Parameters |    |                                                                 |
|-----------------|----|-----------------------------------------------------------------|
| Name            | ID | Description                                                     |
| Kp              | 1  | Proportional Factor                                             |
| Ki              | 2  | Integral Factor                                                 |
| Kd              | 3  | Derivative Factor                                               |
| fc              | 4  | Cutoff frequency of realization low pass                        |
| initHandling    | 5  | Determines what the signal provided on Init input is used for   |
| ts_fact         | 6  | Multiplication factor of base sampling time (in integer format) |

### Description:

#### Preloading Integral

A rising edge at the *Enable* input enables the controller and preloads the integral.

One may choose from two options how to preload the integral value:

- Preload the integral from the *Init* input.
- Preload the integral such that the first output of the controller matches the current value at the *Init* input.  
This option allows controller switching without disturbing the control.

**Note:** Each fixed point implementation uses the next higher integer data type for the integral value storage variable.

**Transfer function** (zero-order hold discretization method):

When the block is enabled, the PID controller realizes the following transfer function:

$$G(z) = K_p + K_i T_s \frac{1}{z - 1} + K_d 2\pi f_c \frac{z - 1}{z - e^{-2\pi f_c T_s}}$$

### Anti Wind-Up

The implemented anti wind-up method is clamping. If the output signal out exceeds the upper or lower limit value, which is given by the inport max and the inport min, the integrator is clamped if the controller input would increase the saturation even further.

**FiP8 bug:** When using the TI compiler the step response of the derivative part doesn't return to zero, but generates an overflow at zero crossing if the derivative parameter value is too high.

**Developer note:** The fixed point implementation source code of this block is used for block *PID*.

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP8

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | int8 |
| Init              | int8 |
| max               | int8 |
| min               | int8 |
| Enable            | bool |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |
| Init              | int16 |
| max               | int16 |
| min               | int16 |
| Enable            | bool  |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |
| Init              | int32 |
| max               | int32 |
| min               | int32 |
| Enable            | bool  |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |
| Init              | float32 |
| max               | float32 |
| min               | float32 |
| Enable            | bool    |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

## Implementation: Float64

---

### 64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |
| Init              | float64 |
| max               | float64 |
| min               | float64 |
| Enable            | bool    |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |



**Verification: PIDLimit FiP16 CPU TMS320F28335**

Date of Test 2026-06-19

Target controller TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block PIDLimit.

| Test results   |                     |       |       |       |     |       |
|----------------|---------------------|-------|-------|-------|-----|-------|
| Time step      | 1                   | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 81                  | 81    | 81    | 182   | ... | 182   |
| Inputs         |                     |       |       |       |     |       |
| In (DSP)       | 0                   | 0     | 0     | 0     | ... | 0     |
| Init (DSP)     | 3604                | 3604  | 3604  | 3604  | ... | 3604  |
| max (DSP)      | 26214               | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915                | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0                   | 0     | 0     | 1     | ... | 1     |
| In             | 0                   | 0     | 0     | 0     | ... | 0     |
| Init           | 0.11                | 0.11  | 0.11  | 0.11  | ... | 0.11  |
| max            | 0.8                 | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15                | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0                   | 0     | 0     | 1     | ... | 1     |
| Parameters     |                     |       |       |       |     |       |
| Kp             | 2                   |       |       |       |     |       |
| Ki             | 2500                |       |       |       |     |       |
| Kd             | 0.003               |       |       |       |     |       |
| fc             | 200                 |       |       |       |     |       |
| initHandling   | initialize integral |       |       |       |     |       |
| ts_fact        | 1                   |       |       |       |     |       |
| Outputs        |                     |       |       |       |     |       |
| Out            | 0                   | 0     | 0     | 0.15  | ... | 0.649 |
| Exp. Out       | 0                   | 0     | 0     | 0.15  | ... | 0.649 |
| Out (DSP)      | 0                   | 0     | 0     | 4915  | ... | 21273 |
| Exp. Out (DSP) | 0                   | 0     | 0     | 4915  | ... | 21275 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 81  |
| Max CPU cycles  | 188 |
| Avg CPU cycles  | 176 |

### Test case: Conversion test

OK

Conversion test for Control block PIDLimit.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 204        |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 204        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PIDLimit.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26373              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26373               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 2048       |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 2048       |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 1,0000e+00$ |
| Tolerance a0d             | $\pm 1,0000e+00$ |
| Tolerance b0d             | $\pm 1,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 5082  |
| Max CPU cycles  | 14652 |
| Avg CPU cycles  | 12741 |

**Verification: PIDLimit FiP16 CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block PIDLimit.

| Test results   |                     |       |       |       |     |       |
|----------------|---------------------|-------|-------|-------|-----|-------|
| Time step      | 1                   | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 57                  | 57    | 57    | 131   | ... | 127   |
| Inputs         |                     |       |       |       |     |       |
| In (DSP)       | 0                   | 0     | 0     | 0     | ... | 0     |
| Init (DSP)     | 3604                | 3604  | 3604  | 3604  | ... | 3604  |
| max (DSP)      | 26214               | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915                | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0                   | 0     | 0     | 1     | ... | 1     |
| In             | 0                   | 0     | 0     | 0     | ... | 0     |
| Init           | 0.11                | 0.11  | 0.11  | 0.11  | ... | 0.11  |
| max            | 0.8                 | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15                | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0                   | 0     | 0     | 1     | ... | 1     |
| Parameters     |                     |       |       |       |     |       |
| Kp             | 2                   |       |       |       |     |       |
| Ki             | 2500                |       |       |       |     |       |
| Kd             | 0.003               |       |       |       |     |       |
| fc             | 200                 |       |       |       |     |       |
| initHandling   | initialize integral |       |       |       |     |       |
| ts_fact        | 1                   |       |       |       |     |       |
| Outputs        |                     |       |       |       |     |       |
| Out            | 0                   | 0     | 0     | 0.15  | ... | 0.649 |
| Exp. Out       | 0                   | 0     | 0     | 0.15  | ... | 0.649 |
| Out (DSP)      | 0                   | 0     | 0     | 4915  | ... | 21273 |
| Exp. Out (DSP) | 0                   | 0     | 0     | 4915  | ... | 21275 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 57  |
| Max CPU cycles  | 133 |
| Avg CPU cycles  | 124 |

### Test case: Conversion test

OK

Conversion test for Control block PIDLimit.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 204        |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 204        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PIDLimit.



| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26373              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26373               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 2048       |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 2048       |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 1,0000e+00$ |
| Tolerance a0d             | $\pm 1,0000e+00$ |
| Tolerance b0d             | $\pm 1,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2373 |
| Max CPU cycles  | 8689 |
| Avg CPU cycles  | 7188 |

**Verification: PIDLimit FiP16 CPU STM32G474RE**

Date of Test 2026-06-19  
Target controller STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block PIDLimit.

| Test results   |                     |       |       |       |     |       |
|----------------|---------------------|-------|-------|-------|-----|-------|
| Time step      | 1                   | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 82                  | 82    | 82    | 198   | ... | 183   |
| Inputs         |                     |       |       |       |     |       |
| In (DSP)       | 0                   | 0     | 0     | 0     | ... | 0     |
| Init (DSP)     | 3604                | 3604  | 3604  | 3604  | ... | 3604  |
| max (DSP)      | 26214               | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915                | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0                   | 0     | 0     | 1     | ... | 1     |
| In             | 0                   | 0     | 0     | 0     | ... | 0     |
| Init           | 0.11                | 0.11  | 0.11  | 0.11  | ... | 0.11  |
| max            | 0.8                 | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15                | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0                   | 0     | 0     | 1     | ... | 1     |
| Parameters     |                     |       |       |       |     |       |
| Kp             | 2                   |       |       |       |     |       |
| Ki             | 2500                |       |       |       |     |       |
| Kd             | 0.003               |       |       |       |     |       |
| fc             | 200                 |       |       |       |     |       |
| initHandling   | initialize integral |       |       |       |     |       |
| ts_fact        | 1                   |       |       |       |     |       |
| Outputs        |                     |       |       |       |     |       |
| Out            | 0                   | 0     | 0     | 0.15  | ... | 0.649 |
| Exp. Out       | 0                   | 0     | 0     | 0.15  | ... | 0.649 |
| Out (DSP)      | 0                   | 0     | 0     | 4915  | ... | 21273 |
| Exp. Out (DSP) | 0                   | 0     | 0     | 4915  | ... | 21275 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 82  |
| Max CPU cycles  | 198 |
| Avg CPU cycles  | 169 |

### Test case: Conversion test

OK

Conversion test for Control block PIDLimit.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 204        |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 204        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PIDLimit.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26373              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26373               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 2048       |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 2048       |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 1,0000e+00$ |
| Tolerance a0d             | $\pm 1,0000e+00$ |
| Tolerance b0d             | $\pm 1,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2558 |
| Max CPU cycles  | 4965 |
| Avg CPU cycles  | 4412 |

**Verification: PIDLimit FiP16 CPU STM32F072RB**

Date of Test 2026-06-19  
Target controller STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block PIDLimit.

| Test results   |                     |       |       |       |     |       |
|----------------|---------------------|-------|-------|-------|-----|-------|
| Time step      | 1                   | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 76                  | 76    | 76    | 187   | ... | 185   |
| Inputs         |                     |       |       |       |     |       |
| In (DSP)       | 0                   | 0     | 0     | 0     | ... | 0     |
| Init (DSP)     | 3604                | 3604  | 3604  | 3604  | ... | 3604  |
| max (DSP)      | 26214               | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915                | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0                   | 0     | 0     | 1     | ... | 1     |
| In             | 0                   | 0     | 0     | 0     | ... | 0     |
| Init           | 0.11                | 0.11  | 0.11  | 0.11  | ... | 0.11  |
| max            | 0.8                 | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15                | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0                   | 0     | 0     | 1     | ... | 1     |
| Parameters     |                     |       |       |       |     |       |
| Kp             | 2                   |       |       |       |     |       |
| Ki             | 2500                |       |       |       |     |       |
| Kd             | 0.003               |       |       |       |     |       |
| fc             | 200                 |       |       |       |     |       |
| initHandling   | initialize integral |       |       |       |     |       |
| ts_fact        | 1                   |       |       |       |     |       |
| Outputs        |                     |       |       |       |     |       |
| Out            | 0                   | 0     | 0     | 0.15  | ... | 0.649 |
| Exp. Out       | 0                   | 0     | 0     | 0.15  | ... | 0.649 |
| Out (DSP)      | 0                   | 0     | 0     | 4915  | ... | 21273 |
| Exp. Out (DSP) | 0                   | 0     | 0     | 4915  | ... | 21275 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |



| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 76  |
| Max CPU cycles  | 193 |
| Avg CPU cycles  | 175 |

### Test case: Conversion test

OK

Conversion test for Control block PIDLimit.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 204        |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 204        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PIDLimit.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26373              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26373               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 204        |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 204        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 1,0000e+00$ |
| Tolerance a0d             | $\pm 1,0000e+00$ |
| Tolerance b0d             | $\pm 1,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 9997  |
| Max CPU cycles  | 23339 |
| Avg CPU cycles  | 20433 |

**Verification: PIDLimit FiP16 CPU PIC32MX170F256**

Date of Test 2026-06-19  
Target controller PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block PIDLimit.

| Test results   |                     |       |       |       |     |       |
|----------------|---------------------|-------|-------|-------|-----|-------|
| Time step      | 1                   | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 31                  | 31    | 31    | 108   | ... | 115   |
| Inputs         |                     |       |       |       |     |       |
| In (DSP)       | 0                   | 0     | 0     | 0     | ... | 0     |
| Init (DSP)     | 3604                | 3604  | 3604  | 3604  | ... | 3604  |
| max (DSP)      | 26214               | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915                | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0                   | 0     | 0     | 1     | ... | 1     |
| In             | 0                   | 0     | 0     | 0     | ... | 0     |
| Init           | 0.11                | 0.11  | 0.11  | 0.11  | ... | 0.11  |
| max            | 0.8                 | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15                | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0                   | 0     | 0     | 1     | ... | 1     |
| Parameters     |                     |       |       |       |     |       |
| Kp             | 2                   |       |       |       |     |       |
| Ki             | 2500                |       |       |       |     |       |
| Kd             | 0.003               |       |       |       |     |       |
| fc             | 200                 |       |       |       |     |       |
| initHandling   | initialize integral |       |       |       |     |       |
| ts_fact        | 1                   |       |       |       |     |       |
| Outputs        |                     |       |       |       |     |       |
| Out            | 0                   | 0     | 0     | 0.15  | ... | 0.649 |
| Exp. Out       | 0                   | 0     | 0     | 0.15  | ... | 0.649 |
| Out (DSP)      | 0                   | 0     | 0     | 4915  | ... | 21273 |
| Exp. Out (DSP) | 0                   | 0     | 0     | 4915  | ... | 21275 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 31  |
| Max CPU cycles  | 118 |
| Avg CPU cycles  | 106 |

### Test case: Conversion test

OK

Conversion test for Control block PIDLimit.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 204        |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 204        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PIDLimit.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26373              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26373               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 2048       |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 2048       |



| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 1,0000e+00$ |
| Tolerance a0d             | $\pm 1,0000e+00$ |
| Tolerance b0d             | $\pm 1,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3200 |
| Max CPU cycles  | 8384 |
| Avg CPU cycles  | 7391 |

**Verification: PIDLimit FiP16 CPU XMC4800-F144K2048**

Date of Test 2026-06-19  
Target controller XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block PIDLimit.

| Test results   |                     |       |       |       |     |       |
|----------------|---------------------|-------|-------|-------|-----|-------|
| Time step      | 1                   | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 82                  | 59    | 59    | 197   | ... | 156   |
| Inputs         |                     |       |       |       |     |       |
| In (DSP)       | 0                   | 0     | 0     | 0     | ... | 0     |
| Init (DSP)     | 3604                | 3604  | 3604  | 3604  | ... | 3604  |
| max (DSP)      | 26214               | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915                | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0                   | 0     | 0     | 1     | ... | 1     |
| In             | 0                   | 0     | 0     | 0     | ... | 0     |
| Init           | 0.11                | 0.11  | 0.11  | 0.11  | ... | 0.11  |
| max            | 0.8                 | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15                | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0                   | 0     | 0     | 1     | ... | 1     |
| Parameters     |                     |       |       |       |     |       |
| Kp             | 2                   |       |       |       |     |       |
| Ki             | 2500                |       |       |       |     |       |
| Kd             | 0.003               |       |       |       |     |       |
| fc             | 200                 |       |       |       |     |       |
| initHandling   | initialize integral |       |       |       |     |       |
| ts_fact        | 1                   |       |       |       |     |       |
| Outputs        |                     |       |       |       |     |       |
| Out            | 0                   | 0     | 0     | 0.15  | ... | 0.649 |
| Exp. Out       | 0                   | 0     | 0     | 0.15  | ... | 0.649 |
| Out (DSP)      | 0                   | 0     | 0     | 4915  | ... | 21273 |
| Exp. Out (DSP) | 0                   | 0     | 0     | 4915  | ... | 21275 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 59  |
| Max CPU cycles  | 197 |
| Avg CPU cycles  | 150 |

### Test case: Conversion test

OK

Conversion test for Control block PIDLimit.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 204        |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 204        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PIDLimit.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26373              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26373               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 2048       |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 2048       |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 1,0000e+00$ |
| Tolerance a0d             | $\pm 1,0000e+00$ |
| Tolerance b0d             | $\pm 1,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2203 |
| Max CPU cycles  | 4527 |
| Avg CPU cycles  | 3994 |

**Verification: PIDLimit FiP16 CPU TMS320F28379D**

Date of Test 2026-06-22  
Target controller TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block PIDLimit.

| Test results   |                     |       |       |       |     |       |
|----------------|---------------------|-------|-------|-------|-----|-------|
| Time step      | 1                   | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 75                  | 75    | 75    | 185   | ... | 184   |
| Inputs         |                     |       |       |       |     |       |
| In (DSP)       | 0                   | 0     | 0     | 0     | ... | 0     |
| Init (DSP)     | 3604                | 3604  | 3604  | 3604  | ... | 3604  |
| max (DSP)      | 26214               | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915                | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0                   | 0     | 0     | 1     | ... | 1     |
| In             | 0                   | 0     | 0     | 0     | ... | 0     |
| Init           | 0.11                | 0.11  | 0.11  | 0.11  | ... | 0.11  |
| max            | 0.8                 | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15                | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0                   | 0     | 0     | 1     | ... | 1     |
| Parameters     |                     |       |       |       |     |       |
| Kp             | 2                   |       |       |       |     |       |
| Ki             | 2500                |       |       |       |     |       |
| Kd             | 0.003               |       |       |       |     |       |
| fc             | 200                 |       |       |       |     |       |
| initHandling   | initialize integral |       |       |       |     |       |
| ts_fact        | 1                   |       |       |       |     |       |
| Outputs        |                     |       |       |       |     |       |
| Out            | 0                   | 0     | 0     | 0.15  | ... | 0.649 |
| Exp. Out       | 0                   | 0     | 0     | 0.15  | ... | 0.649 |
| Out (DSP)      | 0                   | 0     | 0     | 4915  | ... | 21273 |
| Exp. Out (DSP) | 0                   | 0     | 0     | 4915  | ... | 21275 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 75  |
| Max CPU cycles  | 190 |
| Avg CPU cycles  | 180 |

### Test case: Conversion test

OK

Conversion test for Control block PIDLimit.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 204        |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 204        |



| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PIDLimit.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26373              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26373               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 204        |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 204        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 1,0000e+00$ |
| Tolerance a0d             | $\pm 1,0000e+00$ |
| Tolerance b0d             | $\pm 1,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 3685  |
| Max CPU cycles  | 11217 |
| Avg CPU cycles  | 9708  |

**Verification: PIDLimit FiP16 CPU dsPIC33EP256MC502**

Date of Test 2026-06-23  
Target controller dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block PIDLimit.

| Test results   |                     |       |       |       |     |       |
|----------------|---------------------|-------|-------|-------|-----|-------|
| Time step      | 1                   | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 55                  | 55    | 55    | 162   | ... | 188   |
| Inputs         |                     |       |       |       |     |       |
| In (DSP)       | 0                   | 0     | 0     | 0     | ... | 0     |
| Init (DSP)     | 3604                | 3604  | 3604  | 3604  | ... | 3604  |
| max (DSP)      | 26214               | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915                | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0                   | 0     | 0     | 1     | ... | 1     |
| In             | 0                   | 0     | 0     | 0     | ... | 0     |
| Init           | 0.11                | 0.11  | 0.11  | 0.11  | ... | 0.11  |
| max            | 0.8                 | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15                | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0                   | 0     | 0     | 1     | ... | 1     |
| Parameters     |                     |       |       |       |     |       |
| Kp             | 2                   |       |       |       |     |       |
| Ki             | 2500                |       |       |       |     |       |
| Kd             | 0.003               |       |       |       |     |       |
| fc             | 200                 |       |       |       |     |       |
| initHandling   | initialize integral |       |       |       |     |       |
| ts_fact        | 1                   |       |       |       |     |       |
| Outputs        |                     |       |       |       |     |       |
| Out            | 0                   | 0     | 0     | 0.15  | ... | 0.649 |
| Exp. Out       | 0                   | 0     | 0     | 0.15  | ... | 0.649 |
| Out (DSP)      | 0                   | 0     | 0     | 4915  | ... | 21273 |
| Exp. Out (DSP) | 0                   | 0     | 0     | 4915  | ... | 21275 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 55  |
| Max CPU cycles  | 190 |
| Avg CPU cycles  | 170 |

### Test case: Conversion test

OK

Conversion test for Control block PIDLimit.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 204        |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 204        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PIDLimit.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>Kd</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>fc</b>                    | 0                   | 13.889              | 27.778              | 41.667              | ... | 50         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>sfrd</b>                  | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>b1d</b>                   | 0                   | -26373              | -24822              | -17453              | ... | 314        |
| <b>a0d</b>                   | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>b0d</b>                   | 0                   | 26373               | 24822               | 17453               | ... | -314       |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 204        |
| <b>Exp. sfrd</b>             | 15                  | 5                   | 4                   | 3                   | ... | 0          |
| <b>Exp. b1d</b>              | 0                   | -26374              | -24822              | -17453              | ... | 314        |
| <b>Exp. a0d</b>              | -32767              | -32483              | -32201              | -31921              | ... | -239       |
| <b>Exp. b0d</b>              | 0                   | 26374               | 24822               | 17453               | ... | -314       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 204        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 1,0000e+00$ |
| Tolerance a0d             | $\pm 1,0000e+00$ |
| Tolerance b0d             | $\pm 1,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 14127 |
| Max CPU cycles  | 48820 |
| Avg CPU cycles  | 42388 |



**Verification: PIDLimit FiP32 CPU TMS320F28335**

Date of Test 2026-06-19  
Target controller TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block PIDLimit.

| Test results   |                     |            |     |            |
|----------------|---------------------|------------|-----|------------|
| Time step      | 1                   | 2          | ... | 201        |
| CPU cycles     | 85                  | 85         | ... | 426        |
| Inputs         |                     |            |     |            |
| In (DSP)       | 0                   | 0          | ... | 0          |
| Init (DSP)     | 236223201           | 236223201  | ... | 236223201  |
| max (DSP)      | 1717986918          | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547           | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0                   | 0          | ... | 1          |
| In             | 0                   | 0          | ... | 0          |
| Init           | 0.11                | 0.11       | ... | 0.11       |
| max            | 0.8                 | 0.8        | ... | 0.8        |
| min            | 0.15                | 0.15       | ... | 0.15       |
| Enable         | 0                   | 0          | ... | 1          |
| Parameters     |                     |            |     |            |
| Kp             | 2                   |            |     |            |
| Ki             | 2500                |            |     |            |
| Kd             | 0.003               |            |     |            |
| fc             | 200                 |            |     |            |
| initHandling   | initialize integral |            |     |            |
| ts_fact        | 1                   |            |     |            |
| Outputs        |                     |            |     |            |
| Out            | 0                   | 0          | ... | 0.649      |
| Exp. Out       | 0                   | 0          | ... | 0.649      |
| Out (DSP)      | 0                   | 0          | ... | 1394267794 |
| Exp. Out (DSP) | 0                   | 0          | ... | 1394267794 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 65536$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 85  |
| Max CPU cycles  | 458 |
| Avg CPU cycles  | 403 |

### Test case: Conversion test

OK

Conversion test for Control block PIDLimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437568         | ... | 2058874161        |
| <b>a0d</b>                   | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>b0d</b>                   | 0                   | 1728437568          | ... | -2058874161       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611876         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PIDLimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437632         | ... | 2058874240        |
| <b>a0d</b>                   | -2147483647         | -2128824832         | ... | -1568527872       |
| <b>b0d</b>                   | 0                   | 1728437632          | ... | -2058874240       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 2,0000e+02$ |
| Tolerance a0d             | $\pm 2,0000e+02$ |
| Tolerance b0d             | $\pm 2,0000e+02$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+02$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 6090  |
| Max CPU cycles  | 16311 |
| Avg CPU cycles  | 13994 |

**Verification: PIDLimit FiP32 CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block PIDLimit.

| Test results   |                     |            |     |            |
|----------------|---------------------|------------|-----|------------|
| Time step      | 1                   | 2          | ... | 201        |
| CPU cycles     | 63                  | 63         | ... | 251        |
| Inputs         |                     |            |     |            |
| In (DSP)       | 0                   | 0          | ... | 0          |
| Init (DSP)     | 236223201           | 236223201  | ... | 236223201  |
| max (DSP)      | 1717986918          | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547           | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0                   | 0          | ... | 1          |
| In             | 0                   | 0          | ... | 0          |
| Init           | 0.11                | 0.11       | ... | 0.11       |
| max            | 0.8                 | 0.8        | ... | 0.8        |
| min            | 0.15                | 0.15       | ... | 0.15       |
| Enable         | 0                   | 0          | ... | 1          |
| Parameters     |                     |            |     |            |
| Kp             | 2                   |            |     |            |
| Ki             | 2500                |            |     |            |
| Kd             | 0.003               |            |     |            |
| fc             | 200                 |            |     |            |
| initHandling   | initialize integral |            |     |            |
| ts_fact        | 1                   |            |     |            |
| Outputs        |                     |            |     |            |
| Out            | 0                   | 0          | ... | 0.649      |
| Exp. Out       | 0                   | 0          | ... | 0.649      |
| Out (DSP)      | 0                   | 0          | ... | 1394267794 |
| Exp. Out (DSP) | 0                   | 0          | ... | 1394267794 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 65536$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 63  |
| Max CPU cycles  | 251 |
| Avg CPU cycles  | 228 |

### Test case: Conversion test

OK

Conversion test for Control block PIDLimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437568         | ... | 2058874161        |
| <b>a0d</b>                   | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>b0d</b>                   | 0                   | 1728437568          | ... | -2058874161       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611876         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PIDLimit.



| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437632         | ... | 2058874240        |
| <b>a0d</b>                   | -2147483647         | -2128824832         | ... | -1568527872       |
| <b>b0d</b>                   | 0                   | 1728437632          | ... | -2058874240       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 2,0000e+02$ |
| Tolerance a0d             | $\pm 2,0000e+02$ |
| Tolerance b0d             | $\pm 2,0000e+02$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2341 |
| Max CPU cycles  | 6943 |
| Avg CPU cycles  | 5862 |

**Verification: PIDLimit FiP32 CPU STM32G474RE**

Date of Test 2026-06-19  
Target controller STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block PIDLimit.

| Test results   |                     |            |     |            |
|----------------|---------------------|------------|-----|------------|
| Time step      | 1                   | 2          | ... | 201        |
| CPU cycles     | 90                  | 90         | ... | 281        |
| Inputs         |                     |            |     |            |
| In (DSP)       | 0                   | 0          | ... | 0          |
| Init (DSP)     | 236223201           | 236223201  | ... | 236223201  |
| max (DSP)      | 1717986918          | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547           | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0                   | 0          | ... | 1          |
| In             | 0                   | 0          | ... | 0          |
| Init           | 0.11                | 0.11       | ... | 0.11       |
| max            | 0.8                 | 0.8        | ... | 0.8        |
| min            | 0.15                | 0.15       | ... | 0.15       |
| Enable         | 0                   | 0          | ... | 1          |
| Parameters     |                     |            |     |            |
| Kp             | 2                   |            |     |            |
| Ki             | 2500                |            |     |            |
| Kd             | 0.003               |            |     |            |
| fc             | 200                 |            |     |            |
| initHandling   | initialize integral |            |     |            |
| ts_fact        | 1                   |            |     |            |
| Outputs        |                     |            |     |            |
| Out            | 0                   | 0          | ... | 0.649      |
| Exp. Out       | 0                   | 0          | ... | 0.649      |
| Out (DSP)      | 0                   | 0          | ... | 1394267794 |
| Exp. Out (DSP) | 0                   | 0          | ... | 1394267794 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 65536$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 90  |
| Max CPU cycles  | 334 |
| Avg CPU cycles  | 253 |

### Test case: Conversion test

OK

Conversion test for Control block PIDLimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437568         | ... | 2058874161        |
| <b>a0d</b>                   | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>b0d</b>                   | 0                   | 1728437568          | ... | -2058874161       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611876         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PIDLimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437632         | ... | 2058874240        |
| <b>a0d</b>                   | -2147483647         | -2128824832         | ... | -1568527872       |
| <b>b0d</b>                   | 0                   | 1728437632          | ... | -2058874240       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 2,0000e+02$ |
| Tolerance a0d             | $\pm 2,0000e+02$ |
| Tolerance b0d             | $\pm 2,0000e+02$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3841 |
| Max CPU cycles  | 6358 |
| Avg CPU cycles  | 5749 |

**Verification: PIDLimit FiP32 CPU STM32F072RB**

Date of Test 2026-06-19  
Target controller STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block PIDLimit.

| Test results   |                     |            |     |            |
|----------------|---------------------|------------|-----|------------|
| Time step      | 1                   | 2          | ... | 201        |
| CPU cycles     | 90                  | 90         | ... | 676        |
| Inputs         |                     |            |     |            |
| In (DSP)       | 0                   | 0          | ... | 0          |
| Init (DSP)     | 236223201           | 236223201  | ... | 236223201  |
| max (DSP)      | 1717986918          | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547           | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0                   | 0          | ... | 1          |
| In             | 0                   | 0          | ... | 0          |
| Init           | 0.11                | 0.11       | ... | 0.11       |
| max            | 0.8                 | 0.8        | ... | 0.8        |
| min            | 0.15                | 0.15       | ... | 0.15       |
| Enable         | 0                   | 0          | ... | 1          |
| Parameters     |                     |            |     |            |
| Kp             | 2                   |            |     |            |
| Ki             | 2500                |            |     |            |
| Kd             | 0.003               |            |     |            |
| fc             | 200                 |            |     |            |
| initHandling   | initialize integral |            |     |            |
| ts_fact        | 1                   |            |     |            |
| Outputs        |                     |            |     |            |
| Out            | 0                   | 0          | ... | 0.649      |
| Exp. Out       | 0                   | 0          | ... | 0.649      |
| Out (DSP)      | 0                   | 0          | ... | 1394267794 |
| Exp. Out (DSP) | 0                   | 0          | ... | 1394267794 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 65536$ LSB) |



| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 90  |
| Max CPU cycles  | 735 |
| Avg CPU cycles  | 609 |

### Test case: Conversion test

OK

Conversion test for Control block PIDLimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437568         | ... | 2058874161        |
| <b>a0d</b>                   | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>b0d</b>                   | 0                   | 1728437568          | ... | -2058874161       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611876         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PIDLimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437632         | ... | 2058874240        |
| <b>a0d</b>                   | -2147483647         | -2128824832         | ... | -1568527872       |
| <b>b0d</b>                   | 0                   | 1728437632          | ... | -2058874240       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 2,0000e+02$ |
| Tolerance a0d             | $\pm 2,0000e+02$ |
| Tolerance b0d             | $\pm 2,0000e+02$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+02$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 15408 |
| Max CPU cycles  | 29717 |
| Avg CPU cycles  | 26731 |

**Verification: PIDLimit FiP32 CPU PIC32MX170F256**

Date of Test 2026-06-19  
Target controller PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block PIDLimit.

| Test results   |                     |            |     |            |
|----------------|---------------------|------------|-----|------------|
| Time step      | 1                   | 2          | ... | 201        |
| CPU cycles     | 31                  | 31         | ... | 204        |
| Inputs         |                     |            |     |            |
| In (DSP)       | 0                   | 0          | ... | 0          |
| Init (DSP)     | 236223201           | 236223201  | ... | 236223201  |
| max (DSP)      | 1717986918          | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547           | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0                   | 0          | ... | 1          |
| In             | 0                   | 0          | ... | 0          |
| Init           | 0.11                | 0.11       | ... | 0.11       |
| max            | 0.8                 | 0.8        | ... | 0.8        |
| min            | 0.15                | 0.15       | ... | 0.15       |
| Enable         | 0                   | 0          | ... | 1          |
| Parameters     |                     |            |     |            |
| Kp             | 2                   |            |     |            |
| Ki             | 2500                |            |     |            |
| Kd             | 0.003               |            |     |            |
| fc             | 200                 |            |     |            |
| initHandling   | initialize integral |            |     |            |
| ts_fact        | 1                   |            |     |            |
| Outputs        |                     |            |     |            |
| Out            | 0                   | 0          | ... | 0.649      |
| Exp. Out       | 0                   | 0          | ... | 0.649      |
| Out (DSP)      | 0                   | 0          | ... | 1394267794 |
| Exp. Out (DSP) | 0                   | 0          | ... | 1394267794 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 65536$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 31  |
| Max CPU cycles  | 204 |
| Avg CPU cycles  | 182 |

### Test case: Conversion test

OK

Conversion test for Control block PIDLimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437568         | ... | 2058874161        |
| <b>a0d</b>                   | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>b0d</b>                   | 0                   | 1728437568          | ... | -2058874161       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611876         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PIDLimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437632         | ... | 2058874240        |
| <b>a0d</b>                   | -2147483647         | -2128824832         | ... | -1568527872       |
| <b>b0d</b>                   | 0                   | 1728437632          | ... | -2058874240       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |



| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 2,0000e+02$ |
| Tolerance a0d             | $\pm 2,0000e+02$ |
| Tolerance b0d             | $\pm 2,0000e+02$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+02$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 5332  |
| Max CPU cycles  | 10879 |
| Avg CPU cycles  | 9677  |

**Verification: PIDLimit FiP32 CPU XMC4800-F144K2048**

Date of Test 2026-06-19  
Target controller XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block PIDLimit.

| Test results   |                     |            |     |            |
|----------------|---------------------|------------|-----|------------|
| Time step      | 1                   | 2          | ... | 201        |
| CPU cycles     | 81                  | 59         | ... | 258        |
| Inputs         |                     |            |     |            |
| In (DSP)       | 0                   | 0          | ... | 0          |
| Init (DSP)     | 236223201           | 236223201  | ... | 236223201  |
| max (DSP)      | 1717986918          | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547           | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0                   | 0          | ... | 1          |
| In             | 0                   | 0          | ... | 0          |
| Init           | 0.11                | 0.11       | ... | 0.11       |
| max            | 0.8                 | 0.8        | ... | 0.8        |
| min            | 0.15                | 0.15       | ... | 0.15       |
| Enable         | 0                   | 0          | ... | 1          |
| Parameters     |                     |            |     |            |
| Kp             | 2                   |            |     |            |
| Ki             | 2500                |            |     |            |
| Kd             | 0.003               |            |     |            |
| fc             | 200                 |            |     |            |
| initHandling   | initialize integral |            |     |            |
| ts_fact        | 1                   |            |     |            |
| Outputs        |                     |            |     |            |
| Out            | 0                   | 0          | ... | 0.649      |
| Exp. Out       | 0                   | 0          | ... | 0.649      |
| Out (DSP)      | 0                   | 0          | ... | 1394267794 |
| Exp. Out (DSP) | 0                   | 0          | ... | 1394267794 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 65536$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 59  |
| Max CPU cycles  | 291 |
| Avg CPU cycles  | 242 |

### Test case: Conversion test

OK

Conversion test for Control block PIDLimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437568         | ... | 2058874161        |
| <b>a0d</b>                   | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>b0d</b>                   | 0                   | 1728437568          | ... | -2058874161       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611876         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PIDLimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437632         | ... | 2058874240        |
| <b>a0d</b>                   | -2147483647         | -2128824832         | ... | -1568527872       |
| <b>b0d</b>                   | 0                   | 1728437632          | ... | -2058874240       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 2,0000e+02$ |
| Tolerance a0d             | $\pm 2,0000e+02$ |
| Tolerance b0d             | $\pm 2,0000e+02$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3423 |
| Max CPU cycles  | 5798 |
| Avg CPU cycles  | 5275 |

**Verification: PIDLimit FiP32 CPU TMS320F28379D**

Date of Test 2026-06-22  
Target controller TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block PIDLimit.

| Test results   |                     |            |     |            |
|----------------|---------------------|------------|-----|------------|
| Time step      | 1                   | 2          | ... | 201        |
| CPU cycles     | 73                  | 73         | ... | 370        |
| Inputs         |                     |            |     |            |
| In (DSP)       | 0                   | 0          | ... | 0          |
| Init (DSP)     | 236223201           | 236223201  | ... | 236223201  |
| max (DSP)      | 1717986918          | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547           | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0                   | 0          | ... | 1          |
| In             | 0                   | 0          | ... | 0          |
| Init           | 0.11                | 0.11       | ... | 0.11       |
| max            | 0.8                 | 0.8        | ... | 0.8        |
| min            | 0.15                | 0.15       | ... | 0.15       |
| Enable         | 0                   | 0          | ... | 1          |
| Parameters     |                     |            |     |            |
| Kp             | 2                   |            |     |            |
| Ki             | 2500                |            |     |            |
| Kd             | 0.003               |            |     |            |
| fc             | 200                 |            |     |            |
| initHandling   | initialize integral |            |     |            |
| ts_fact        | 1                   |            |     |            |
| Outputs        |                     |            |     |            |
| Out            | 0                   | 0          | ... | 0.649      |
| Exp. Out       | 0                   | 0          | ... | 0.649      |
| Out (DSP)      | 0                   | 0          | ... | 1394267794 |
| Exp. Out (DSP) | 0                   | 0          | ... | 1394267794 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 65536$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 73  |
| Max CPU cycles  | 390 |
| Avg CPU cycles  | 352 |

### Test case: Conversion test

OK

Conversion test for Control block PIDLimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437568         | ... | 2058874161        |
| <b>a0d</b>                   | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>b0d</b>                   | 0                   | 1728437568          | ... | -2058874161       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611876         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |



| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PIDLimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437632         | ... | 2058874240        |
| <b>a0d</b>                   | -2147483647         | -2128824832         | ... | -1568527872       |
| <b>b0d</b>                   | 0                   | 1728437632          | ... | -2058874240       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 2,0000e+02$ |
| Tolerance a0d             | $\pm 2,0000e+02$ |
| Tolerance b0d             | $\pm 2,0000e+02$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+02$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 4343  |
| Max CPU cycles  | 12410 |
| Avg CPU cycles  | 10577 |

**Verification: PIDLimit FiP32 CPU dsPIC33EP256MC502**

Date of Test 2026-06-23  
Target controller dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block PIDLimit.

| Test results   |                     |            |     |            |
|----------------|---------------------|------------|-----|------------|
| Time step      | 1                   | 2          | ... | 201        |
| CPU cycles     | 64                  | 64         | ... | 1377       |
| Inputs         |                     |            |     |            |
| In (DSP)       | 0                   | 0          | ... | 0          |
| Init (DSP)     | 236223201           | 236223201  | ... | 236223201  |
| max (DSP)      | 1717986918          | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547           | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0                   | 0          | ... | 1          |
| In             | 0                   | 0          | ... | 0          |
| Init           | 0.11                | 0.11       | ... | 0.11       |
| max            | 0.8                 | 0.8        | ... | 0.8        |
| min            | 0.15                | 0.15       | ... | 0.15       |
| Enable         | 0                   | 0          | ... | 1          |
| Parameters     |                     |            |     |            |
| Kp             | 2                   |            |     |            |
| Ki             | 2500                |            |     |            |
| Kd             | 0.003               |            |     |            |
| fc             | 200                 |            |     |            |
| initHandling   | initialize integral |            |     |            |
| ts_fact        | 1                   |            |     |            |
| Outputs        |                     |            |     |            |
| Out            | 0                   | 0          | ... | 0.649      |
| Exp. Out       | 0                   | 0          | ... | 0.649      |
| Out (DSP)      | 0                   | 0          | ... | 1394267794 |
| Exp. Out (DSP) | 0                   | 0          | ... | 1394267794 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 65536$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 64   |
| Max CPU cycles  | 1400 |
| Avg CPU cycles  | 1303 |

### Test case: Conversion test

OK

Conversion test for Control block PIDLimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437568         | ... | 2058874161        |
| <b>a0d</b>                   | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>b0d</b>                   | 0                   | 1728437568          | ... | -2058874161       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611876         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 0,0000e+00$ |
| Tolerance a0d             | $\pm 0,0000e+00$ |
| Tolerance b0d             | $\pm 0,0000e+00$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PIDLimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>sfrd</b>                  | 31                  | 21                  | ... | 16                |
| <b>b1d</b>                   | 0                   | -1728437632         | ... | 2058874240        |
| <b>a0d</b>                   | -2147483647         | -2128824832         | ... | -1568527872       |
| <b>b0d</b>                   | 0                   | 1728437632          | ... | -2058874240       |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. sfrd</b>             | 31                  | 21                  | ... | 16                |
| <b>Exp. b1d</b>              | 0                   | -1728437568         | ... | 2058874161        |
| <b>Exp. a0d</b>              | -2147483647         | -2128824851         | ... | -1568527835       |
| <b>Exp. b0d</b>              | 0                   | 1728437568          | ... | -2058874161       |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance sfrd            | $\pm 0,0000e+00$ |
| Tolerance b1d             | $\pm 2,0000e+02$ |
| Tolerance a0d             | $\pm 2,0000e+02$ |
| Tolerance b0d             | $\pm 2,0000e+02$ |
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+02$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 15980 |
| Max CPU cycles  | 50882 |
| Avg CPU cycles  | 43326 |



**Verification: PIDLimit Float32 CPU TMS320F28335**

Date of Test 2026-06-19  
Target controller TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block PIDLimit.

| Test results   |                     |      |     |       |
|----------------|---------------------|------|-----|-------|
| Time step      | 1                   | 2    | ... | 201   |
| CPU cycles     | 87                  | 87   | ... | 168   |
| Inputs         |                     |      |     |       |
| In (DSP)       | 0                   | 0    | ... | 0     |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11  |
| max (DSP)      | 0.8                 | 0.8  | ... | 0.8   |
| min (DSP)      | 0.15                | 0.15 | ... | 0.15  |
| Enable (DSP)   | 0                   | 0    | ... | 1     |
| In             | 0                   | 0    | ... | 0     |
| Init           | 0.11                | 0.11 | ... | 0.11  |
| max            | 0.8                 | 0.8  | ... | 0.8   |
| min            | 0.15                | 0.15 | ... | 0.15  |
| Enable         | 0                   | 0    | ... | 1     |
| Parameters     |                     |      |     |       |
| Kp             | 2                   |      |     |       |
| Ki             | 2500                |      |     |       |
| Kd             | 0.003               |      |     |       |
| fc             | 200                 |      |     |       |
| initHandling   | initialize integral |      |     |       |
| ts_fact        | 1                   |      |     |       |
| Outputs        |                     |      |     |       |
| Out            | 0                   | 0    | ... | 0.649 |
| Exp. Out       | 0                   | 0    | ... | 0.649 |
| Out (DSP)      | 0                   | 0    | ... | 0.649 |
| Exp. Out (DSP) | 0                   | 0    | ... | 0.649 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 87  |
| Max CPU cycles  | 181 |
| Avg CPU cycles  | 163 |

### Test case: Conversion test

OK

Conversion test for Control block PIDLimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.927         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.927        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 0,0000e+00$ |
| Tolerance a0d          | $\pm 1,0000e-15$ |
| Tolerance b0d          | $\pm 0,0000e+00$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PIDLimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.928         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.928        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 3,0000e-03$ |
| Tolerance a0d          | $\pm 1,0000e-07$ |
| Tolerance b0d          | $\pm 3,0000e-03$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e-10$ |
| Tolerance b1           | $\pm 1,0000e-06$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2933 |
| Max CPU cycles  | 3298 |
| Avg CPU cycles  | 3257 |

**Verification: PIDLimit Float32 CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block PIDLimit.

| Test results   |                     |      |     |       |
|----------------|---------------------|------|-----|-------|
| Time step      | 1                   | 2    | ... | 201   |
| CPU cycles     | 45                  | 45   | ... | 123   |
| Inputs         |                     |      |     |       |
| In (DSP)       | 0                   | 0    | ... | 0     |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11  |
| max (DSP)      | 0.8                 | 0.8  | ... | 0.8   |
| min (DSP)      | 0.15                | 0.15 | ... | 0.15  |
| Enable (DSP)   | 0                   | 0    | ... | 1     |
| In             | 0                   | 0    | ... | 0     |
| Init           | 0.11                | 0.11 | ... | 0.11  |
| max            | 0.8                 | 0.8  | ... | 0.8   |
| min            | 0.15                | 0.15 | ... | 0.15  |
| Enable         | 0                   | 0    | ... | 1     |
| Parameters     |                     |      |     |       |
| Kp             | 2                   |      |     |       |
| Ki             | 2500                |      |     |       |
| Kd             | 0.003               |      |     |       |
| fc             | 200                 |      |     |       |
| initHandling   | initialize integral |      |     |       |
| ts_fact        | 1                   |      |     |       |
| Outputs        |                     |      |     |       |
| Out            | 0                   | 0    | ... | 0.649 |
| Exp. Out       | 0                   | 0    | ... | 0.649 |
| Out (DSP)      | 0                   | 0    | ... | 0.649 |
| Exp. Out (DSP) | 0                   | 0    | ... | 0.649 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 45  |
| Max CPU cycles  | 131 |
| Avg CPU cycles  | 118 |

### Test case: Conversion test

OK

Conversion test for Control block PIDLimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.927         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.927        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 0,0000e+00$ |
| Tolerance a0d          | $\pm 1,0000e-15$ |
| Tolerance b0d          | $\pm 0,0000e+00$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PIDLimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.928         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.928        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 3,0000e-03$ |
| Tolerance a0d          | $\pm 1,0000e-07$ |
| Tolerance b0d          | $\pm 3,0000e-03$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e-10$ |
| Tolerance b1           | $\pm 1,0000e-06$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1309 |
| Max CPU cycles  | 1355 |
| Avg CPU cycles  | 1351 |

**Verification: PIDLimit Float32 CPU STM32G474RE**

Date of Test 2026-06-19  
Target controller STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block PIDLimit.

| Test results   |                     |      |     |       |
|----------------|---------------------|------|-----|-------|
| Time step      | 1                   | 2    | ... | 201   |
| CPU cycles     | 73                  | 73   | ... | 173   |
| Inputs         |                     |      |     |       |
| In (DSP)       | 0                   | 0    | ... | 0     |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11  |
| max (DSP)      | 0.8                 | 0.8  | ... | 0.8   |
| min (DSP)      | 0.15                | 0.15 | ... | 0.15  |
| Enable (DSP)   | 0                   | 0    | ... | 1     |
| In             | 0                   | 0    | ... | 0     |
| Init           | 0.11                | 0.11 | ... | 0.11  |
| max            | 0.8                 | 0.8  | ... | 0.8   |
| min            | 0.15                | 0.15 | ... | 0.15  |
| Enable         | 0                   | 0    | ... | 1     |
| Parameters     |                     |      |     |       |
| Kp             | 2                   |      |     |       |
| Ki             | 2500                |      |     |       |
| Kd             | 0.003               |      |     |       |
| fc             | 200                 |      |     |       |
| initHandling   | initialize integral |      |     |       |
| ts_fact        | 1                   |      |     |       |
| Outputs        |                     |      |     |       |
| Out            | 0                   | 0    | ... | 0.649 |
| Exp. Out       | 0                   | 0    | ... | 0.649 |
| Out (DSP)      | 0                   | 0    | ... | 0.649 |
| Exp. Out (DSP) | 0                   | 0    | ... | 0.649 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 73  |
| Max CPU cycles  | 174 |
| Avg CPU cycles  | 155 |

### Test case: Conversion test

OK

Conversion test for Control block PIDLimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.927         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.927        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 0,0000e+00$ |
| Tolerance a0d          | $\pm 1,0000e-15$ |
| Tolerance b0d          | $\pm 0,0000e+00$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |



**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PIDLimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.928         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.928        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 3,0000e-03$ |
| Tolerance a0d          | $\pm 1,0000e-07$ |
| Tolerance b0d          | $\pm 3,0000e-03$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e-10$ |
| Tolerance b1           | $\pm 1,0000e-06$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1495 |
| Max CPU cycles  | 1570 |
| Avg CPU cycles  | 1563 |

**Verification: PIDLimit Float32 CPU STM32F072RB**

Date of Test 2026-06-19  
Target controller STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block PIDLimit.

| Test results   |                     |      |     |       |
|----------------|---------------------|------|-----|-------|
| Time step      | 1                   | 2    | ... | 201   |
| CPU cycles     | 88                  | 88   | ... | 1478  |
| Inputs         |                     |      |     |       |
| In (DSP)       | 0                   | 0    | ... | 0     |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11  |
| max (DSP)      | 0.8                 | 0.8  | ... | 0.8   |
| min (DSP)      | 0.15                | 0.15 | ... | 0.15  |
| Enable (DSP)   | 0                   | 0    | ... | 1     |
| In             | 0                   | 0    | ... | 0     |
| Init           | 0.11                | 0.11 | ... | 0.11  |
| max            | 0.8                 | 0.8  | ... | 0.8   |
| min            | 0.15                | 0.15 | ... | 0.15  |
| Enable         | 0                   | 0    | ... | 1     |
| Parameters     |                     |      |     |       |
| Kp             | 2                   |      |     |       |
| Ki             | 2500                |      |     |       |
| Kd             | 0.003               |      |     |       |
| fc             | 200                 |      |     |       |
| initHandling   | initialize integral |      |     |       |
| ts_fact        | 1                   |      |     |       |
| Outputs        |                     |      |     |       |
| Out            | 0                   | 0    | ... | 0.649 |
| Exp. Out       | 0                   | 0    | ... | 0.649 |
| Out (DSP)      | 0                   | 0    | ... | 0.649 |
| Exp. Out (DSP) | 0                   | 0    | ... | 0.649 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 88   |
| Max CPU cycles  | 1819 |
| Avg CPU cycles  | 1527 |

### Test case: Conversion test

OK

Conversion test for Control block PIDLimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.927         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.927        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 0,0000e+00$ |
| Tolerance a0d          | $\pm 1,0000e-15$ |
| Tolerance b0d          | $\pm 0,0000e+00$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PIDLimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.928         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.928        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 3,0000e-03$ |
| Tolerance a0d          | $\pm 1,0000e-07$ |
| Tolerance b0d          | $\pm 3,0000e-03$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e-10$ |
| Tolerance b1           | $\pm 1,0000e-06$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 4055 |
| Max CPU cycles  | 7049 |
| Avg CPU cycles  | 6909 |

**Verification: PIDLimit Float32 CPU PIC32MX170F256**

Date of Test 2026-06-19  
Target controller PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block PIDLimit.

| Test results   |                     |      |     |       |
|----------------|---------------------|------|-----|-------|
| Time step      | 1                   | 2    | ... | 201   |
| CPU cycles     | 73                  | 73   | ... | 555   |
| Inputs         |                     |      |     |       |
| In (DSP)       | 0                   | 0    | ... | 0     |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11  |
| max (DSP)      | 0.8                 | 0.8  | ... | 0.8   |
| min (DSP)      | 0.15                | 0.15 | ... | 0.15  |
| Enable (DSP)   | 0                   | 0    | ... | 1     |
| In             | 0                   | 0    | ... | 0     |
| Init           | 0.11                | 0.11 | ... | 0.11  |
| max            | 0.8                 | 0.8  | ... | 0.8   |
| min            | 0.15                | 0.15 | ... | 0.15  |
| Enable         | 0                   | 0    | ... | 1     |
| Parameters     |                     |      |     |       |
| Kp             | 2                   |      |     |       |
| Ki             | 2500                |      |     |       |
| Kd             | 0.003               |      |     |       |
| fc             | 200                 |      |     |       |
| initHandling   | initialize integral |      |     |       |
| ts_fact        | 1                   |      |     |       |
| Outputs        |                     |      |     |       |
| Out            | 0                   | 0    | ... | 0.649 |
| Exp. Out       | 0                   | 0    | ... | 0.649 |
| Out (DSP)      | 0                   | 0    | ... | 0.649 |
| Exp. Out (DSP) | 0                   | 0    | ... | 0.649 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 73  |
| Max CPU cycles  | 699 |
| Avg CPU cycles  | 595 |

### Test case: Conversion test

OK

Conversion test for Control block PIDLimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.927         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.927        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 0,0000e+00$ |
| Tolerance a0d          | $\pm 1,0000e-15$ |
| Tolerance b0d          | $\pm 0,0000e+00$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PIDLimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.928         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.928        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 3,0000e-03$ |
| Tolerance a0d          | $\pm 1,0000e-07$ |
| Tolerance b0d          | $\pm 3,0000e-03$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e-10$ |
| Tolerance b1           | $\pm 1,0000e-06$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1304 |
| Max CPU cycles  | 1551 |
| Avg CPU cycles  | 1538 |

**Verification: PIDLimit Float32 CPU XMC4800-F144K2048**

Date of Test 2026-06-19  
Target controller XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block PIDLimit.

| Test results   |                     |      |     |       |
|----------------|---------------------|------|-----|-------|
| Time step      | 1                   | 2    | ... | 201   |
| CPU cycles     | 88                  | 60   | ... | 138   |
| Inputs         |                     |      |     |       |
| In (DSP)       | 0                   | 0    | ... | 0     |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11  |
| max (DSP)      | 0.8                 | 0.8  | ... | 0.8   |
| min (DSP)      | 0.15                | 0.15 | ... | 0.15  |
| Enable (DSP)   | 0                   | 0    | ... | 1     |
| In             | 0                   | 0    | ... | 0     |
| Init           | 0.11                | 0.11 | ... | 0.11  |
| max            | 0.8                 | 0.8  | ... | 0.8   |
| min            | 0.15                | 0.15 | ... | 0.15  |
| Enable         | 0                   | 0    | ... | 1     |
| Parameters     |                     |      |     |       |
| Kp             | 2                   |      |     |       |
| Ki             | 2500                |      |     |       |
| Kd             | 0.003               |      |     |       |
| fc             | 200                 |      |     |       |
| initHandling   | initialize integral |      |     |       |
| ts_fact        | 1                   |      |     |       |
| Outputs        |                     |      |     |       |
| Out            | 0                   | 0    | ... | 0.649 |
| Exp. Out       | 0                   | 0    | ... | 0.649 |
| Out (DSP)      | 0                   | 0    | ... | 0.649 |
| Exp. Out (DSP) | 0                   | 0    | ... | 0.649 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |



| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 60  |
| Max CPU cycles  | 193 |
| Avg CPU cycles  | 133 |

### Test case: Conversion test

OK

Conversion test for Control block PIDLimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.927         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.927        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 0,0000e+00$ |
| Tolerance a0d          | $\pm 1,0000e-15$ |
| Tolerance b0d          | $\pm 0,0000e+00$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PIDLimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.928         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.928        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 3,0000e-03$ |
| Tolerance a0d          | $\pm 1,0000e-07$ |
| Tolerance b0d          | $\pm 3,0000e-03$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e-10$ |
| Tolerance b1           | $\pm 1,0000e-06$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1502 |
| Max CPU cycles  | 1564 |
| Avg CPU cycles  | 1508 |

**Verification: PIDLimit Float32 CPU TMS320F28379D**

Date of Test 2026-06-22  
Target controller TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block PIDLimit.

| Test results   |                     |      |     |       |
|----------------|---------------------|------|-----|-------|
| Time step      | 1                   | 2    | ... | 201   |
| CPU cycles     | 71                  | 71   | ... | 157   |
| Inputs         |                     |      |     |       |
| In (DSP)       | 0                   | 0    | ... | 0     |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11  |
| max (DSP)      | 0.8                 | 0.8  | ... | 0.8   |
| min (DSP)      | 0.15                | 0.15 | ... | 0.15  |
| Enable (DSP)   | 0                   | 0    | ... | 1     |
| In             | 0                   | 0    | ... | 0     |
| Init           | 0.11                | 0.11 | ... | 0.11  |
| max            | 0.8                 | 0.8  | ... | 0.8   |
| min            | 0.15                | 0.15 | ... | 0.15  |
| Enable         | 0                   | 0    | ... | 1     |
| Parameters     |                     |      |     |       |
| Kp             | 2                   |      |     |       |
| Ki             | 2500                |      |     |       |
| Kd             | 0.003               |      |     |       |
| fc             | 200                 |      |     |       |
| initHandling   | initialize integral |      |     |       |
| ts_fact        | 1                   |      |     |       |
| Outputs        |                     |      |     |       |
| Out            | 0                   | 0    | ... | 0.649 |
| Exp. Out       | 0                   | 0    | ... | 0.649 |
| Out (DSP)      | 0                   | 0    | ... | 0.649 |
| Exp. Out (DSP) | 0                   | 0    | ... | 0.649 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 71  |
| Max CPU cycles  | 176 |
| Avg CPU cycles  | 154 |

### Test case: Conversion test

OK

Conversion test for Control block PIDLimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.927         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.927        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 0,0000e+00$ |
| Tolerance a0d          | $\pm 1,0000e-15$ |
| Tolerance b0d          | $\pm 0,0000e+00$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PIDLimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.928         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.928        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 3,0000e-03$ |
| Tolerance a0d          | $\pm 1,0000e-07$ |
| Tolerance b0d          | $\pm 3,0000e-03$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e-10$ |
| Tolerance b1           | $\pm 1,0000e-06$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2092 |
| Max CPU cycles  | 2391 |
| Avg CPU cycles  | 2351 |

**Verification: PIDLimit Float32 CPU dsPIC33EP256MC502**

Date of Test 2026-06-23  
Target controller dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block PIDLimit.

| Test results   |                     |      |     |       |
|----------------|---------------------|------|-----|-------|
| Time step      | 1                   | 2    | ... | 201   |
| CPU cycles     | 64                  | 64   | ... | 1684  |
| Inputs         |                     |      |     |       |
| In (DSP)       | 0                   | 0    | ... | 0     |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11  |
| max (DSP)      | 0.8                 | 0.8  | ... | 0.8   |
| min (DSP)      | 0.15                | 0.15 | ... | 0.15  |
| Enable (DSP)   | 0                   | 0    | ... | 1     |
| In             | 0                   | 0    | ... | 0     |
| Init           | 0.11                | 0.11 | ... | 0.11  |
| max            | 0.8                 | 0.8  | ... | 0.8   |
| min            | 0.15                | 0.15 | ... | 0.15  |
| Enable         | 0                   | 0    | ... | 1     |
| Parameters     |                     |      |     |       |
| Kp             | 2                   |      |     |       |
| Ki             | 2500                |      |     |       |
| Kd             | 0.003               |      |     |       |
| fc             | 200                 |      |     |       |
| initHandling   | initialize integral |      |     |       |
| ts_fact        | 1                   |      |     |       |
| Outputs        |                     |      |     |       |
| Out            | 0                   | 0    | ... | 0.649 |
| Exp. Out       | 0                   | 0    | ... | 0.649 |
| Out (DSP)      | 0                   | 0    | ... | 0.649 |
| Exp. Out (DSP) | 0                   | 0    | ... | 0.649 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 64   |
| Max CPU cycles  | 2045 |
| Avg CPU cycles  | 1741 |

### Test case: Conversion test

OK

Conversion test for Control block PIDLimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.927         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.927        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 0,0000e+00$ |
| Tolerance a0d          | $\pm 1,0000e-15$ |
| Tolerance b0d          | $\pm 0,0000e+00$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PIDLimit.


| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>Kd</b>                    | -10                 | -9.444              | ... | 10                |
| <b>fc</b>                    | 0                   | 13.889              | ... | 500               |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>b1d</b>                   | 0                   | -824.183            | ... | 31415.928         |
| <b>a0d</b>                   | -1                  | -0.991              | ... | -0.73             |
| <b>b0d</b>                   | 0                   | 824.183             | ... | -31415.928        |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. b1d</b>              | 0                   | -824.183            | ... | 31415.927         |
| <b>Exp. a0d</b>              | -1                  | -0.991              | ... | -0.73             |
| <b>Exp. b0d</b>              | 0                   | 824.183             | ... | -31415.927        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance b1d          | $\pm 3,0000e-03$ |
| Tolerance a0d          | $\pm 1,0000e-07$ |
| Tolerance b0d          | $\pm 3,0000e-03$ |
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e-10$ |
| Tolerance b1           | $\pm 1,0000e-06$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 5102 |
| Max CPU cycles  | 8863 |
| Avg CPU cycles  | 8469 |



## Block: PILimit



PI controller with output limitation and anti wind-up method clamping:

$$G(s) = K_p + K_i/s$$

| Inports |                                                                                                                               |
|---------|-------------------------------------------------------------------------------------------------------------------------------|
| In      | Control error input                                                                                                           |
| Init    | Initial value of output Out when enabled                                                                                      |
| max     | Maximum output value                                                                                                          |
| min     | Minimum output value                                                                                                          |
| Enable  | Enable == 0: Deactivation of block; Out set to 0<br>Enable 0->1: Preload of integral part<br>Enable == 1: Activation of block |

| Outports |               |
|----------|---------------|
| Out      | Control value |

| Mask Parameters |    |                                                                 |
|-----------------|----|-----------------------------------------------------------------|
| Name            | ID | Description                                                     |
| Kp              | 1  | Proportional Factor                                             |
| Ki              | 2  | Integral Factor                                                 |
| initHandling    | 3  | Determines what the signal provided on Init input is used for   |
| ts_fact         | 4  | Multiplication factor of base sampling time (in integer format) |

### Description:

#### Preloading Integral

A rising edge at the *Enable* inport enables the controller and preloads the integral.

One may choose from two options how to preload the integral value:

- Preload the integral from the *Init* inport.
- Preload the integral such that the first output of the controller matches the current value at the *Init* inport.  
This option allows controller switching without disturbing the control.

**Note:** Each fixed point implementation uses the next higher integer data type for the integral value storage variable.

**Transfer function** (zero-order hold discretization method):

When the block is enabled, the PI controller realizes the following transfer function: Transfer

function (zero-order hold discretization method):

$$G(z) = K_p + K_i T_s \frac{1}{z - 1}$$

### Anti Wind-Up

The implemented anti wind-up method is clamping. If the output signal out exceeds the upper or lower limit value, which is given by the inport max and the inport min, the integrator is clamped if the controller input would increase the saturation even further.

**Developer note:** The source code of this block is used for block *PI*.

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP8

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | int8 |
| Init              | int8 |
| max               | int8 |
| min               | int8 |
| Enable            | bool |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |
| Init              | int16 |
| max               | int16 |
| min               | int16 |
| Enable            | bool  |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |
| Init              | int32 |
| max               | int32 |
| min               | int32 |
| Enable            | bool  |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |
| Init              | float32 |
| max               | float32 |
| min               | float32 |
| Enable            | bool    |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |
| Init              | float64 |
| max               | float64 |
| min               | float64 |
| Enable            | bool    |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: PILimit FiP16 CPU TMS320F28335**

Date of Test 2026-06-19  
Target controller TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block PILimit.

| Test results   |                     |       |       |       |     |       |
|----------------|---------------------|-------|-------|-------|-----|-------|
| Time step      | 1                   | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 67                  | 67    | 67    | 148   | ... | 129   |
| Inputs         |                     |       |       |       |     |       |
| In (DSP)       | 0                   | 0     | 0     | 0     | ... | 0     |
| Init (DSP)     | 3604                | 3604  | 3604  | 3604  | ... | 3604  |
| max (DSP)      | 26214               | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915                | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0                   | 0     | 0     | 1     | ... | 1     |
| In             | 0                   | 0     | 0     | 0     | ... | 0     |
| Init           | 0.11                | 0.11  | 0.11  | 0.11  | ... | 0.11  |
| max            | 0.8                 | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15                | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0                   | 0     | 0     | 1     | ... | 1     |
| Parameters     |                     |       |       |       |     |       |
| Kp             | 2                   |       |       |       |     |       |
| Ki             | 2500                |       |       |       |     |       |
| initHandling   | initialize integral |       |       |       |     |       |
| ts_fact        | 1                   |       |       |       |     |       |
| Outputs        |                     |       |       |       |     |       |
| Out            | 0                   | 0     | 0     | 0.15  | ... | 0.647 |
| Exp. Out       | 0                   | 0     | 0     | 0.15  | ... | 0.647 |
| Out (DSP)      | 0                   | 0     | 0     | 4915  | ... | 21212 |
| Exp. Out (DSP) | 0                   | 0     | 0     | 4915  | ... | 21217 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 67  |
| Max CPU cycles  | 148 |
| Avg CPU cycles  | 123 |

**Test case: Conversion test**

OK

Conversion test for Control block PILimit.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 20480      |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 20480      |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PILimit.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 20480      |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 20480      |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3071 |
| Max CPU cycles  | 5316 |
| Avg CPU cycles  | 4559 |

**Verification: PILimit FiP16 CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block PILimit.

| Test results   |                     |       |       |       |     |       |
|----------------|---------------------|-------|-------|-------|-----|-------|
| Time step      | 1                   | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 43                  | 43    | 43    | 105   | ... | 83    |
| Inputs         |                     |       |       |       |     |       |
| In (DSP)       | 0                   | 0     | 0     | 0     | ... | 0     |
| Init (DSP)     | 3604                | 3604  | 3604  | 3604  | ... | 3604  |
| max (DSP)      | 26214               | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915                | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0                   | 0     | 0     | 1     | ... | 1     |
| In             | 0                   | 0     | 0     | 0     | ... | 0     |
| Init           | 0.11                | 0.11  | 0.11  | 0.11  | ... | 0.11  |
| max            | 0.8                 | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15                | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0                   | 0     | 0     | 1     | ... | 1     |
| Parameters     |                     |       |       |       |     |       |
| Kp             | 2                   |       |       |       |     |       |
| Ki             | 2500                |       |       |       |     |       |
| initHandling   | initialize integral |       |       |       |     |       |
| ts_fact        | 1                   |       |       |       |     |       |
| Outputs        |                     |       |       |       |     |       |
| Out            | 0                   | 0     | 0     | 0.15  | ... | 0.647 |
| Exp. Out       | 0                   | 0     | 0     | 0.15  | ... | 0.647 |
| Out (DSP)      | 0                   | 0     | 0     | 4915  | ... | 21212 |
| Exp. Out (DSP) | 0                   | 0     | 0     | 4915  | ... | 21217 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 43  |
| Max CPU cycles  | 105 |
| Avg CPU cycles  | 81  |



**Test case: Conversion test**

OK

Conversion test for Control block PILimit.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 20480      |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 20480      |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PILimit.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 20480      |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 20480      |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1563 |
| Max CPU cycles  | 2889 |
| Avg CPU cycles  | 2441 |

**Verification: PILimit FiP16 CPU STM32G474RE**

Date of Test 2026-06-19  
Target controller STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block PILimit.

| Test results   |                     |       |       |       |     |       |
|----------------|---------------------|-------|-------|-------|-----|-------|
| Time step      | 1                   | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 73                  | 73    | 73    | 137   | ... | 135   |
| Inputs         |                     |       |       |       |     |       |
| In (DSP)       | 0                   | 0     | 0     | 0     | ... | 0     |
| Init (DSP)     | 3604                | 3604  | 3604  | 3604  | ... | 3604  |
| max (DSP)      | 26214               | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915                | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0                   | 0     | 0     | 1     | ... | 1     |
| In             | 0                   | 0     | 0     | 0     | ... | 0     |
| Init           | 0.11                | 0.11  | 0.11  | 0.11  | ... | 0.11  |
| max            | 0.8                 | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15                | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0                   | 0     | 0     | 1     | ... | 1     |
| Parameters     |                     |       |       |       |     |       |
| Kp             | 2                   |       |       |       |     |       |
| Ki             | 2500                |       |       |       |     |       |
| initHandling   | initialize integral |       |       |       |     |       |
| ts_fact        | 1                   |       |       |       |     |       |
| Outputs        |                     |       |       |       |     |       |
| Out            | 0                   | 0     | 0     | 0.15  | ... | 0.647 |
| Exp. Out       | 0                   | 0     | 0     | 0.15  | ... | 0.647 |
| Out (DSP)      | 0                   | 0     | 0     | 4915  | ... | 21212 |
| Exp. Out (DSP) | 0                   | 0     | 0     | 4915  | ... | 21217 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 73  |
| Max CPU cycles  | 137 |
| Avg CPU cycles  | 120 |

**Test case: Conversion test****OK**

Conversion test for Control block PILimit.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 204        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 204        |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for Control block PILimit.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 20480      |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 20480      |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1585 |
| Max CPU cycles  | 2090 |
| Avg CPU cycles  | 1906 |

**Verification: PILimit FiP16 CPU STM32F072RB**

Date of Test 2026-06-19  
Target controller STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block PILimit.

| Test results   |                     |       |       |       |     |       |
|----------------|---------------------|-------|-------|-------|-----|-------|
| Time step      | 1                   | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 68                  | 68    | 68    | 153   | ... | 123   |
| Inputs         |                     |       |       |       |     |       |
| In (DSP)       | 0                   | 0     | 0     | 0     | ... | 0     |
| Init (DSP)     | 3604                | 3604  | 3604  | 3604  | ... | 3604  |
| max (DSP)      | 26214               | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915                | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0                   | 0     | 0     | 1     | ... | 1     |
| In             | 0                   | 0     | 0     | 0     | ... | 0     |
| Init           | 0.11                | 0.11  | 0.11  | 0.11  | ... | 0.11  |
| max            | 0.8                 | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15                | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0                   | 0     | 0     | 1     | ... | 1     |
| Parameters     |                     |       |       |       |     |       |
| Kp             | 2                   |       |       |       |     |       |
| Ki             | 2500                |       |       |       |     |       |
| initHandling   | initialize integral |       |       |       |     |       |
| ts_fact        | 1                   |       |       |       |     |       |
| Outputs        |                     |       |       |       |     |       |
| Out            | 0                   | 0     | 0     | 0.15  | ... | 0.647 |
| Exp. Out       | 0                   | 0     | 0     | 0.15  | ... | 0.647 |
| Out (DSP)      | 0                   | 0     | 0     | 4915  | ... | 21212 |
| Exp. Out (DSP) | 0                   | 0     | 0     | 4915  | ... | 21217 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 68  |
| Max CPU cycles  | 183 |
| Avg CPU cycles  | 113 |

**Test case: Conversion test****OK**

Conversion test for Control block PILimit.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 20480      |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 20480      |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for Control block PILimit.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 204        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 204        |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 4006 |
| Max CPU cycles  | 7402 |
| Avg CPU cycles  | 6391 |



**Verification: PILimit FiP16 CPU PIC32MX170F256**

Date of Test 2026-06-19  
Target controller PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block PILimit.

| Test results   |                     |       |       |       |     |       |
|----------------|---------------------|-------|-------|-------|-----|-------|
| Time step      | 1                   | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 31                  | 31    | 31    | 92    | ... | 79    |
| Inputs         |                     |       |       |       |     |       |
| In (DSP)       | 0                   | 0     | 0     | 0     | ... | 0     |
| Init (DSP)     | 3604                | 3604  | 3604  | 3604  | ... | 3604  |
| max (DSP)      | 26214               | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915                | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0                   | 0     | 0     | 1     | ... | 1     |
| In             | 0                   | 0     | 0     | 0     | ... | 0     |
| Init           | 0.11                | 0.11  | 0.11  | 0.11  | ... | 0.11  |
| max            | 0.8                 | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15                | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0                   | 0     | 0     | 1     | ... | 1     |
| Parameters     |                     |       |       |       |     |       |
| Kp             | 2                   |       |       |       |     |       |
| Ki             | 2500                |       |       |       |     |       |
| initHandling   | initialize integral |       |       |       |     |       |
| ts_fact        | 1                   |       |       |       |     |       |
| Outputs        |                     |       |       |       |     |       |
| Out            | 0                   | 0     | 0     | 0.15  | ... | 0.647 |
| Exp. Out       | 0                   | 0     | 0     | 0.15  | ... | 0.647 |
| Out (DSP)      | 0                   | 0     | 0     | 4915  | ... | 21212 |
| Exp. Out (DSP) | 0                   | 0     | 0     | 4915  | ... | 21217 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 92 |
| Avg CPU cycles  | 71 |

**Test case: Conversion test****OK**

Conversion test for Control block PILimit.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 204        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 204        |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for Control block PILimit.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 20480      |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 20480      |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1749 |
| Max CPU cycles  | 3034 |
| Avg CPU cycles  | 2632 |

**Verification: PILimit FiP16 CPU XMC4800-F144K2048**

Date of Test 2026-06-19  
Target controller XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block PILimit.

| Test results   |                     |       |       |       |     |       |
|----------------|---------------------|-------|-------|-------|-----|-------|
| Time step      | 1                   | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 74                  | 59    | 59    | 146   | ... | 104   |
| Inputs         |                     |       |       |       |     |       |
| In (DSP)       | 0                   | 0     | 0     | 0     | ... | 0     |
| Init (DSP)     | 3604                | 3604  | 3604  | 3604  | ... | 3604  |
| max (DSP)      | 26214               | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915                | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0                   | 0     | 0     | 1     | ... | 1     |
| In             | 0                   | 0     | 0     | 0     | ... | 0     |
| Init           | 0.11                | 0.11  | 0.11  | 0.11  | ... | 0.11  |
| max            | 0.8                 | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15                | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0                   | 0     | 0     | 1     | ... | 1     |
| Parameters     |                     |       |       |       |     |       |
| Kp             | 2                   |       |       |       |     |       |
| Ki             | 2500                |       |       |       |     |       |
| initHandling   | initialize integral |       |       |       |     |       |
| ts_fact        | 1                   |       |       |       |     |       |
| Outputs        |                     |       |       |       |     |       |
| Out            | 0                   | 0     | 0     | 0.15  | ... | 0.647 |
| Exp. Out       | 0                   | 0     | 0     | 0.15  | ... | 0.647 |
| Out (DSP)      | 0                   | 0     | 0     | 4915  | ... | 21212 |
| Exp. Out (DSP) | 0                   | 0     | 0     | 4915  | ... | 21217 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 59  |
| Max CPU cycles  | 146 |
| Avg CPU cycles  | 100 |

**Test case: Conversion test**

OK

Conversion test for Control block PILimit.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 204        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 204        |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PILimit.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 20480      |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 20480      |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1365 |
| Max CPU cycles  | 2005 |
| Avg CPU cycles  | 1687 |

**Verification: PILimit FiP16 CPU TMS320F28379D**

Date of Test 2026-06-22  
Target controller TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block PILimit.

| Test results   |                     |       |       |       |     |       |
|----------------|---------------------|-------|-------|-------|-----|-------|
| Time step      | 1                   | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 57                  | 57    | 57    | 154   | ... | 129   |
| Inputs         |                     |       |       |       |     |       |
| In (DSP)       | 0                   | 0     | 0     | 0     | ... | 0     |
| Init (DSP)     | 3604                | 3604  | 3604  | 3604  | ... | 3604  |
| max (DSP)      | 26214               | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915                | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0                   | 0     | 0     | 1     | ... | 1     |
| In             | 0                   | 0     | 0     | 0     | ... | 0     |
| Init           | 0.11                | 0.11  | 0.11  | 0.11  | ... | 0.11  |
| max            | 0.8                 | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15                | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0                   | 0     | 0     | 1     | ... | 1     |
| Parameters     |                     |       |       |       |     |       |
| Kp             | 2                   |       |       |       |     |       |
| Ki             | 2500                |       |       |       |     |       |
| initHandling   | initialize integral |       |       |       |     |       |
| ts_fact        | 1                   |       |       |       |     |       |
| Outputs        |                     |       |       |       |     |       |
| Out            | 0                   | 0     | 0     | 0.15  | ... | 0.647 |
| Exp. Out       | 0                   | 0     | 0     | 0.15  | ... | 0.647 |
| Out (DSP)      | 0                   | 0     | 0     | 4915  | ... | 21212 |
| Exp. Out (DSP) | 0                   | 0     | 0     | 4915  | ... | 21217 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 57  |
| Max CPU cycles  | 154 |
| Avg CPU cycles  | 124 |

**Test case: Conversion test****OK**

Conversion test for Control block PILimit.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 20480      |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 20480      |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for Control block PILimit.



| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 204        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 204        |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2294 |
| Max CPU cycles  | 4061 |
| Avg CPU cycles  | 3459 |

**Verification: PILimit FiP16 CPU dsPIC33EP256MC502**

Date of Test 2026-06-23  
Target controller dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block PILimit.

| Test results   |                     |       |       |       |     |       |
|----------------|---------------------|-------|-------|-------|-----|-------|
| Time step      | 1                   | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 49                  | 49    | 49    | 131   | ... | 123   |
| Inputs         |                     |       |       |       |     |       |
| In (DSP)       | 0                   | 0     | 0     | 0     | ... | 0     |
| Init (DSP)     | 3604                | 3604  | 3604  | 3604  | ... | 3604  |
| max (DSP)      | 26214               | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915                | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0                   | 0     | 0     | 1     | ... | 1     |
| In             | 0                   | 0     | 0     | 0     | ... | 0     |
| Init           | 0.11                | 0.11  | 0.11  | 0.11  | ... | 0.11  |
| max            | 0.8                 | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15                | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0                   | 0     | 0     | 1     | ... | 1     |
| Parameters     |                     |       |       |       |     |       |
| Kp             | 2                   |       |       |       |     |       |
| Ki             | 2500                |       |       |       |     |       |
| initHandling   | initialize integral |       |       |       |     |       |
| ts_fact        | 1                   |       |       |       |     |       |
| Outputs        |                     |       |       |       |     |       |
| Out            | 0                   | 0     | 0     | 0.15  | ... | 0.647 |
| Exp. Out       | 0                   | 0     | 0     | 0.15  | ... | 0.647 |
| Out (DSP)      | 0                   | 0     | 0     | 4915  | ... | 21212 |
| Exp. Out (DSP) | 0                   | 0     | 0     | 4915  | ... | 21217 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 49  |
| Max CPU cycles  | 131 |
| Avg CPU cycles  | 109 |

**Test case: Conversion test****OK**

Conversion test for Control block PILimit.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17067              | ... | 204        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 204        |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for Control block PILimit.

| Test results                 |                     |                     |                     |                     |     |            |
|------------------------------|---------------------|---------------------|---------------------|---------------------|-----|------------|
| Time step                    | 1                   | 2                   | 3                   | 4                   | ... | 37         |
| <i>Mask parameters</i>       |                     |                     |                     |                     |     |            |
| <b>Kp</b>                    | -10                 | -9.444              | -8.889              | -8.333              | ... | 10         |
| <b>Ki</b>                    | -11                 | -10.389             | -9.778              | -9.167              | ... | 11         |
| <b>initHandling</b>          | initialize integral | initialize integral | initialize integral | initialize integral | ... | initialize |
| <b>ts_fact</b>               | 1                   | 1                   | 1                   | 1                   | ... | 1          |
| <i>Controller parameters</i> |                     |                     |                     |                     |     |            |
| <b>initHandling</b>          | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>sfrb0</b>                 | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>sfrb1</b>                 | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>b0</b>                    | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>b1</b>                    | -20480              | -19342              | -18204              | -17066              | ... | 20480      |
| <b>Exp. initHandling</b>     | 0                   | 0                   | 0                   | 0                   | ... | 1          |
| <b>Exp. sfrb0</b>            | 15                  | 15                  | 15                  | 15                  | ... | 15         |
| <b>Exp. sfrb1</b>            | 11                  | 11                  | 11                  | 11                  | ... | 11         |
| <b>Exp. b0</b>               | -36                 | -34                 | -32                 | -30                 | ... | 36         |
| <b>Exp. b1</b>               | -20480              | -19342              | -18204              | -17067              | ... | 20480      |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 1,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 6441  |
| Max CPU cycles  | 15553 |
| Avg CPU cycles  | 12970 |

**Verification: PILimit FiP32 CPU TMS320F28335**

Date of Test 2026-06-19  
Target controller TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block PILimit.

| Test results   |                     |            |     |            |
|----------------|---------------------|------------|-----|------------|
| Time step      | 1                   | 2          | ... | 201        |
| CPU cycles     | 85                  | 85         | ... | 240        |
| Inputs         |                     |            |     |            |
| In (DSP)       | 0                   | 0          | ... | 0          |
| Init (DSP)     | 236223201           | 236223201  | ... | 236223201  |
| max (DSP)      | 1717986918          | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547           | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0                   | 0          | ... | 1          |
| In             | 0                   | 0          | ... | 0          |
| Init           | 0.11                | 0.11       | ... | 0.11       |
| max            | 0.8                 | 0.8        | ... | 0.8        |
| min            | 0.15                | 0.15       | ... | 0.15       |
| Enable         | 0                   | 0          | ... | 1          |
| Parameters     |                     |            |     |            |
| Kp             | 2                   |            |     |            |
| Ki             | 2500                |            |     |            |
| initHandling   | initialize integral |            |     |            |
| ts_fact        | 1                   |            |     |            |
| Outputs        |                     |            |     |            |
| Out            | 0                   | 0          | ... | 0.647      |
| Exp. Out       | 0                   | 0          | ... | 0.647      |
| Out (DSP)      | 0                   | 0          | ... | 1390495657 |
| Exp. Out (DSP) | 0                   | 0          | ... | 1390495657 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 85  |
| Max CPU cycles  | 266 |
| Avg CPU cycles  | 223 |

**Test case: Conversion test**

OK

Conversion test for Control block PILimit.

| Test results          |                     |                     |     |                   |
|-----------------------|---------------------|---------------------|-----|-------------------|
| Time step             | 1                   | 2                   | ... | 37                |
| Mask parameters       |                     |                     |     |                   |
| Kp                    | -10                 | -9.444              | ... | 10                |
| Ki                    | -11                 | -10.389             | ... | 11                |
| initHandling          | initialize integral | initialize integral | ... | initialize output |
| ts_fact               | 1                   | 1                   | ... | 1                 |
| Controller parameters |                     |                     |     |                   |
| initHandling          | 0                   | 0                   | ... | 1                 |
| sfrb0                 | 31                  | 31                  | ... | 31                |
| sfrb1                 | 27                  | 27                  | ... | 27                |
| b0                    | -2362232            | -2230997            | ... | 2362232           |
| b1                    | -1342177280         | -1267611876         | ... | 1342177280        |
| Exp. initHandling     | 0                   | 0                   | ... | 1                 |
| Exp. sfrb0            | 31                  | 31                  | ... | 31                |
| Exp. sfrb1            | 27                  | 27                  | ... | 27                |
| Exp. b0               | -2362232            | -2230997            | ... | 2362232           |
| Exp. b1               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PILimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3435 |
| Max CPU cycles  | 5782 |
| Avg CPU cycles  | 5010 |

**Verification: PILimit FiP32 CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block PILimit.

| Test results   |                     |            |     |            |
|----------------|---------------------|------------|-----|------------|
| Time step      | 1                   | 2          | ... | 201        |
| CPU cycles     | 59                  | 59         | ... | 177        |
| Inputs         |                     |            |     |            |
| In (DSP)       | 0                   | 0          | ... | 0          |
| Init (DSP)     | 236223201           | 236223201  | ... | 236223201  |
| max (DSP)      | 1717986918          | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547           | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0                   | 0          | ... | 1          |
| In             | 0                   | 0          | ... | 0          |
| Init           | 0.11                | 0.11       | ... | 0.11       |
| max            | 0.8                 | 0.8        | ... | 0.8        |
| min            | 0.15                | 0.15       | ... | 0.15       |
| Enable         | 0                   | 0          | ... | 1          |
| Parameters     |                     |            |     |            |
| Kp             | 2                   |            |     |            |
| Ki             | 2500                |            |     |            |
| initHandling   | initialize integral |            |     |            |
| ts_fact        | 1                   |            |     |            |
| Outputs        |                     |            |     |            |
| Out            | 0                   | 0          | ... | 0.647      |
| Exp. Out       | 0                   | 0          | ... | 0.647      |
| Out (DSP)      | 0                   | 0          | ... | 1390495657 |
| Exp. Out (DSP) | 0                   | 0          | ... | 1390495657 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 59  |
| Max CPU cycles  | 197 |
| Avg CPU cycles  | 155 |



**Test case: Conversion test****OK**

Conversion test for Control block PILimit.

| Test results          |                     |                     |     |                   |
|-----------------------|---------------------|---------------------|-----|-------------------|
| Time step             | 1                   | 2                   | ... | 37                |
| Mask parameters       |                     |                     |     |                   |
| Kp                    | -10                 | -9.444              | ... | 10                |
| Ki                    | -11                 | -10.389             | ... | 11                |
| initHandling          | initialize integral | initialize integral | ... | initialize output |
| ts_fact               | 1                   | 1                   | ... | 1                 |
| Controller parameters |                     |                     |     |                   |
| initHandling          | 0                   | 0                   | ... | 1                 |
| sfrb0                 | 31                  | 31                  | ... | 31                |
| sfrb1                 | 27                  | 27                  | ... | 27                |
| b0                    | -2362232            | -2230997            | ... | 2362232           |
| b1                    | -1342177280         | -1267611876         | ... | 1342177280        |
| Exp. initHandling     | 0                   | 0                   | ... | 1                 |
| Exp. sfrb0            | 31                  | 31                  | ... | 31                |
| Exp. sfrb1            | 27                  | 27                  | ... | 27                |
| Exp. b0               | -2362232            | -2230997            | ... | 2362232           |
| Exp. b1               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for Control block PILimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e+00$ |
| Tolerance b1           | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1461 |
| Max CPU cycles  | 2455 |
| Avg CPU cycles  | 2147 |

**Verification: PILimit FiP32 CPU STM32G474RE**

Date of Test 2026-06-19  
Target controller STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block PILimit.

| Test results   |                     |            |     |            |
|----------------|---------------------|------------|-----|------------|
| Time step      | 1                   | 2          | ... | 201        |
| CPU cycles     | 84                  | 84         | ... | 191        |
| Inputs         |                     |            |     |            |
| In (DSP)       | 0                   | 0          | ... | 0          |
| Init (DSP)     | 236223201           | 236223201  | ... | 236223201  |
| max (DSP)      | 1717986918          | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547           | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0                   | 0          | ... | 1          |
| In             | 0                   | 0          | ... | 0          |
| Init           | 0.11                | 0.11       | ... | 0.11       |
| max            | 0.8                 | 0.8        | ... | 0.8        |
| min            | 0.15                | 0.15       | ... | 0.15       |
| Enable         | 0                   | 0          | ... | 1          |
| Parameters     |                     |            |     |            |
| Kp             | 2                   |            |     |            |
| Ki             | 2500                |            |     |            |
| initHandling   | initialize integral |            |     |            |
| ts_fact        | 1                   |            |     |            |
| Outputs        |                     |            |     |            |
| Out            | 0                   | 0          | ... | 0.647      |
| Exp. Out       | 0                   | 0          | ... | 0.647      |
| Out (DSP)      | 0                   | 0          | ... | 1390495657 |
| Exp. Out (DSP) | 0                   | 0          | ... | 1390495657 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 84  |
| Max CPU cycles  | 226 |
| Avg CPU cycles  | 165 |

**Test case: Conversion test**

OK

Conversion test for Control block PILimit.

| Test results          |                     |                     |     |                   |
|-----------------------|---------------------|---------------------|-----|-------------------|
| Time step             | 1                   | 2                   | ... | 37                |
| Mask parameters       |                     |                     |     |                   |
| Kp                    | -10                 | -9.444              | ... | 10                |
| Ki                    | -11                 | -10.389             | ... | 11                |
| initHandling          | initialize integral | initialize integral | ... | initialize output |
| ts_fact               | 1                   | 1                   | ... | 1                 |
| Controller parameters |                     |                     |     |                   |
| initHandling          | 0                   | 0                   | ... | 1                 |
| sfrb0                 | 31                  | 31                  | ... | 31                |
| sfrb1                 | 27                  | 27                  | ... | 27                |
| b0                    | -2362232            | -2230997            | ... | 2362232           |
| b1                    | -1342177280         | -1267611876         | ... | 1342177280        |
| Exp. initHandling     | 0                   | 0                   | ... | 1                 |
| Exp. sfrb0            | 31                  | 31                  | ... | 31                |
| Exp. sfrb1            | 27                  | 27                  | ... | 27                |
| Exp. b0               | -2362232            | -2230997            | ... | 2362232           |
| Exp. b1               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PILimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e+00$ |
| Tolerance b1           | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2164 |
| Max CPU cycles  | 2721 |
| Avg CPU cycles  | 2520 |

**Verification: PILimit FiP32 CPU STM32F072RB**

Date of Test 2026-06-19  
Target controller STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block PILimit.

| Test results   |                     |            |     |            |
|----------------|---------------------|------------|-----|------------|
| Time step      | 1                   | 2          | ... | 201        |
| CPU cycles     | 91                  | 91         | ... | 351        |
| Inputs         |                     |            |     |            |
| In (DSP)       | 0                   | 0          | ... | 0          |
| Init (DSP)     | 236223201           | 236223201  | ... | 236223201  |
| max (DSP)      | 1717986918          | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547           | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0                   | 0          | ... | 1          |
| In             | 0                   | 0          | ... | 0          |
| Init           | 0.11                | 0.11       | ... | 0.11       |
| max            | 0.8                 | 0.8        | ... | 0.8        |
| min            | 0.15                | 0.15       | ... | 0.15       |
| Enable         | 0                   | 0          | ... | 1          |
| Parameters     |                     |            |     |            |
| Kp             | 2                   |            |     |            |
| Ki             | 2500                |            |     |            |
| initHandling   | initialize integral |            |     |            |
| ts_fact        | 1                   |            |     |            |
| Outputs        |                     |            |     |            |
| Out            | 0                   | 0          | ... | 0.647      |
| Exp. Out       | 0                   | 0          | ... | 0.647      |
| Out (DSP)      | 0                   | 0          | ... | 1390495657 |
| Exp. Out (DSP) | 0                   | 0          | ... | 1390495657 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 91  |
| Max CPU cycles  | 373 |
| Avg CPU cycles  | 295 |

**Test case: Conversion test****OK**

Conversion test for Control block PILimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611876         | ... | 1342177280        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for Control block PILimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e+00$ |
| Tolerance b1           | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 6087 |
| Max CPU cycles  | 9970 |
| Avg CPU cycles  | 8951 |



**Verification: PILimit FiP32 CPU PIC32MX170F256**

Date of Test 2026-06-19  
Target controller PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block PILimit.

| Test results   |                     |            |     |            |
|----------------|---------------------|------------|-----|------------|
| Time step      | 1                   | 2          | ... | 201        |
| CPU cycles     | 31                  | 31         | ... | 130        |
| Inputs         |                     |            |     |            |
| In (DSP)       | 0                   | 0          | ... | 0          |
| Init (DSP)     | 236223201           | 236223201  | ... | 236223201  |
| max (DSP)      | 1717986918          | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547           | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0                   | 0          | ... | 1          |
| In             | 0                   | 0          | ... | 0          |
| Init           | 0.11                | 0.11       | ... | 0.11       |
| max            | 0.8                 | 0.8        | ... | 0.8        |
| min            | 0.15                | 0.15       | ... | 0.15       |
| Enable         | 0                   | 0          | ... | 1          |
| Parameters     |                     |            |     |            |
| Kp             | 2                   |            |     |            |
| Ki             | 2500                |            |     |            |
| initHandling   | initialize integral |            |     |            |
| ts_fact        | 1                   |            |     |            |
| Outputs        |                     |            |     |            |
| Out            | 0                   | 0          | ... | 0.647      |
| Exp. Out       | 0                   | 0          | ... | 0.647      |
| Out (DSP)      | 0                   | 0          | ... | 1390495657 |
| Exp. Out (DSP) | 0                   | 0          | ... | 1390495657 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 31  |
| Max CPU cycles  | 144 |
| Avg CPU cycles  | 111 |

**Test case: Conversion test****OK**

Conversion test for Control block PILimit.

| Test results          |                     |                     |     |                   |
|-----------------------|---------------------|---------------------|-----|-------------------|
| Time step             | 1                   | 2                   | ... | 37                |
| Mask parameters       |                     |                     |     |                   |
| Kp                    | -10                 | -9.444              | ... | 10                |
| Ki                    | -11                 | -10.389             | ... | 11                |
| initHandling          | initialize integral | initialize integral | ... | initialize output |
| ts_fact               | 1                   | 1                   | ... | 1                 |
| Controller parameters |                     |                     |     |                   |
| initHandling          | 0                   | 0                   | ... | 1                 |
| sfrb0                 | 31                  | 31                  | ... | 31                |
| sfrb1                 | 27                  | 27                  | ... | 27                |
| b0                    | -2362232            | -2230997            | ... | 2362232           |
| b1                    | -1342177280         | -1267611876         | ... | 1342177280        |
| Exp. initHandling     | 0                   | 0                   | ... | 1                 |
| Exp. sfrb0            | 31                  | 31                  | ... | 31                |
| Exp. sfrb1            | 27                  | 27                  | ... | 27                |
| Exp. b0               | -2362232            | -2230997            | ... | 2362232           |
| Exp. b1               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for Control block PILimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e+00$ |
| Tolerance b1           | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2658 |
| Max CPU cycles  | 4035 |
| Avg CPU cycles  | 3626 |

**Verification: PILimit FiP32 CPU XMC4800-F144K2048**

Date of Test 2026-06-19  
Target controller XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block PILimit.

| Test results   |                     |            |     |            |
|----------------|---------------------|------------|-----|------------|
| Time step      | 1                   | 2          | ... | 201        |
| CPU cycles     | 83                  | 59         | ... | 164        |
| Inputs         |                     |            |     |            |
| In (DSP)       | 0                   | 0          | ... | 0          |
| Init (DSP)     | 236223201           | 236223201  | ... | 236223201  |
| max (DSP)      | 1717986918          | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547           | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0                   | 0          | ... | 1          |
| In             | 0                   | 0          | ... | 0          |
| Init           | 0.11                | 0.11       | ... | 0.11       |
| max            | 0.8                 | 0.8        | ... | 0.8        |
| min            | 0.15                | 0.15       | ... | 0.15       |
| Enable         | 0                   | 0          | ... | 1          |
| Parameters     |                     |            |     |            |
| Kp             | 2                   |            |     |            |
| Ki             | 2500                |            |     |            |
| initHandling   | initialize integral |            |     |            |
| ts_fact        | 1                   |            |     |            |
| Outputs        |                     |            |     |            |
| Out            | 0                   | 0          | ... | 0.647      |
| Exp. Out       | 0                   | 0          | ... | 0.647      |
| Out (DSP)      | 0                   | 0          | ... | 1390495657 |
| Exp. Out (DSP) | 0                   | 0          | ... | 1390495657 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 59  |
| Max CPU cycles  | 228 |
| Avg CPU cycles  | 152 |

**Test case: Conversion test****OK**

Conversion test for Control block PILimit.

| Test results          |                     |                     |     |                   |
|-----------------------|---------------------|---------------------|-----|-------------------|
| Time step             | 1                   | 2                   | ... | 37                |
| Mask parameters       |                     |                     |     |                   |
| Kp                    | -10                 | -9.444              | ... | 10                |
| Ki                    | -11                 | -10.389             | ... | 11                |
| initHandling          | initialize integral | initialize integral | ... | initialize output |
| ts_fact               | 1                   | 1                   | ... | 1                 |
| Controller parameters |                     |                     |     |                   |
| initHandling          | 0                   | 0                   | ... | 1                 |
| sfrb0                 | 31                  | 31                  | ... | 31                |
| sfrb1                 | 27                  | 27                  | ... | 27                |
| b0                    | -2362232            | -2230997            | ... | 2362232           |
| b1                    | -1342177280         | -1267611876         | ... | 1342177280        |
| Exp. initHandling     | 0                   | 0                   | ... | 1                 |
| Exp. sfrb0            | 31                  | 31                  | ... | 31                |
| Exp. sfrb1            | 27                  | 27                  | ... | 27                |
| Exp. b0               | -2362232            | -2230997            | ... | 2362232           |
| Exp. b1               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for Control block PILimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e+00$ |
| Tolerance b1           | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1859 |
| Max CPU cycles  | 2570 |
| Avg CPU cycles  | 2210 |

**Verification: PILimit FiP32 CPU TMS320F28379D**

Date of Test 2026-06-22  
Target controller TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block PILimit.

| Test results   |                     |            |     |            |
|----------------|---------------------|------------|-----|------------|
| Time step      | 1                   | 2          | ... | 201        |
| CPU cycles     | 68                  | 68         | ... | 215        |
| Inputs         |                     |            |     |            |
| In (DSP)       | 0                   | 0          | ... | 0          |
| Init (DSP)     | 236223201           | 236223201  | ... | 236223201  |
| max (DSP)      | 1717986918          | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547           | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0                   | 0          | ... | 1          |
| In             | 0                   | 0          | ... | 0          |
| Init           | 0.11                | 0.11       | ... | 0.11       |
| max            | 0.8                 | 0.8        | ... | 0.8        |
| min            | 0.15                | 0.15       | ... | 0.15       |
| Enable         | 0                   | 0          | ... | 1          |
| Parameters     |                     |            |     |            |
| Kp             | 2                   |            |     |            |
| Ki             | 2500                |            |     |            |
| initHandling   | initialize integral |            |     |            |
| ts_fact        | 1                   |            |     |            |
| Outputs        |                     |            |     |            |
| Out            | 0                   | 0          | ... | 0.647      |
| Exp. Out       | 0                   | 0          | ... | 0.647      |
| Out (DSP)      | 0                   | 0          | ... | 1390495657 |
| Exp. Out (DSP) | 0                   | 0          | ... | 1390495657 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 68  |
| Max CPU cycles  | 247 |
| Avg CPU cycles  | 202 |

**Test case: Conversion test****OK**

Conversion test for Control block PILimit.

| Test results          |                     |                     |     |                   |
|-----------------------|---------------------|---------------------|-----|-------------------|
| Time step             | 1                   | 2                   | ... | 37                |
| Mask parameters       |                     |                     |     |                   |
| Kp                    | -10                 | -9.444              | ... | 10                |
| Ki                    | -11                 | -10.389             | ... | 11                |
| initHandling          | initialize integral | initialize integral | ... | initialize output |
| ts_fact               | 1                   | 1                   | ... | 1                 |
| Controller parameters |                     |                     |     |                   |
| initHandling          | 0                   | 0                   | ... | 1                 |
| sfrb0                 | 31                  | 31                  | ... | 31                |
| sfrb1                 | 27                  | 27                  | ... | 27                |
| b0                    | -2362232            | -2230997            | ... | 2362232           |
| b1                    | -1342177280         | -1267611876         | ... | 1342177280        |
| Exp. initHandling     | 0                   | 0                   | ... | 1                 |
| Exp. sfrb0            | 31                  | 31                  | ... | 31                |
| Exp. sfrb1            | 27                  | 27                  | ... | 27                |
| Exp. b0               | -2362232            | -2230997            | ... | 2362232           |
| Exp. b1               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for Control block PILimit.



| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 1,0000e+00$ |
| Tolerance b1           | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2500 |
| Max CPU cycles  | 4353 |
| Avg CPU cycles  | 3742 |

**Verification: PILimit FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block PILimit.

| Test results   |                     |            |     |            |
|----------------|---------------------|------------|-----|------------|
| Time step      | 1                   | 2          | ... | 201        |
| CPU cycles     | 63                  | 63         | ... | 669        |
| Inputs         |                     |            |     |            |
| In (DSP)       | 0                   | 0          | ... | 0          |
| Init (DSP)     | 236223201           | 236223201  | ... | 236223201  |
| max (DSP)      | 1717986918          | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547           | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0                   | 0          | ... | 1          |
| In             | 0                   | 0          | ... | 0          |
| Init           | 0.11                | 0.11       | ... | 0.11       |
| max            | 0.8                 | 0.8        | ... | 0.8        |
| min            | 0.15                | 0.15       | ... | 0.15       |
| Enable         | 0                   | 0          | ... | 1          |
| Parameters     |                     |            |     |            |
| Kp             | 2                   |            |     |            |
| Ki             | 2500                |            |     |            |
| initHandling   | initialize integral |            |     |            |
| ts_fact        | 1                   |            |     |            |
| Outputs        |                     |            |     |            |
| Out            | 0                   | 0          | ... | 0.647      |
| Exp. Out       | 0                   | 0          | ... | 0.647      |
| Out (DSP)      | 0                   | 0          | ... | 1390495657 |
| Exp. Out (DSP) | 0                   | 0          | ... | 1390495657 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 63  |
| Max CPU cycles  | 699 |
| Avg CPU cycles  | 604 |

**Test case: Conversion test**

OK

Conversion test for Control block PILimit.

| Test results          |                     |                     |     |                   |
|-----------------------|---------------------|---------------------|-----|-------------------|
| Time step             | 1                   | 2                   | ... | 37                |
| Mask parameters       |                     |                     |     |                   |
| Kp                    | -10                 | -9.444              | ... | 10                |
| Ki                    | -11                 | -10.389             | ... | 11                |
| initHandling          | initialize integral | initialize integral | ... | initialize output |
| ts_fact               | 1                   | 1                   | ... | 1                 |
| Controller parameters |                     |                     |     |                   |
| initHandling          | 0                   | 0                   | ... | 1                 |
| sfrb0                 | 31                  | 31                  | ... | 31                |
| sfrb1                 | 27                  | 27                  | ... | 27                |
| b0                    | -2362232            | -2230997            | ... | 2362232           |
| b1                    | -1342177280         | -1267611876         | ... | 1342177280        |
| Exp. initHandling     | 0                   | 0                   | ... | 1                 |
| Exp. sfrb0            | 31                  | 31                  | ... | 31                |
| Exp. sfrb1            | 27                  | 27                  | ... | 27                |
| Exp. b0               | -2362232            | -2230997            | ... | 2362232           |
| Exp. b1               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0        | $\pm 0,0000e+00$ |
| Tolerance sfrb1        | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PILimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>sfrb0</b>                 | 31                  | 31                  | ... | 31                |
| <b>sfrb1</b>                 | 27                  | 27                  | ... | 27                |
| <b>b0</b>                    | -2362232            | -2230997            | ... | 2362232           |
| <b>b1</b>                    | -1342177280         | -1267611904         | ... | 1342177280        |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. sfrb0</b>            | 31                  | 31                  | ... | 31                |
| <b>Exp. sfrb1</b>            | 27                  | 27                  | ... | 27                |
| <b>Exp. b0</b>               | -2362232            | -2230997            | ... | 2362232           |
| <b>Exp. b1</b>               | -1342177280         | -1267611876         | ... | 1342177280        |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance sfrb0           | $\pm 0,0000e+00$ |
| Tolerance sfrb1           | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e+00$ |
| Tolerance b1              | $\pm 1,0000e+02$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 7253  |
| Max CPU cycles  | 15987 |
| Avg CPU cycles  | 13506 |

**Verification: PILimit Float32 CPU TMS320F28335**

Date of Test 2026-06-19  
Target controller TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block PILimit.

| Test results   |                     |      |     |       |
|----------------|---------------------|------|-----|-------|
| Time step      | 1                   | 2    | ... | 201   |
| CPU cycles     | 73                  | 73   | ... | 128   |
| Inputs         |                     |      |     |       |
| In (DSP)       | 0                   | 0    | ... | 0     |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11  |
| max (DSP)      | 0.8                 | 0.8  | ... | 0.8   |
| min (DSP)      | 0.15                | 0.15 | ... | 0.15  |
| Enable (DSP)   | 0                   | 0    | ... | 1     |
| In             | 0                   | 0    | ... | 0     |
| Init           | 0.11                | 0.11 | ... | 0.11  |
| max            | 0.8                 | 0.8  | ... | 0.8   |
| min            | 0.15                | 0.15 | ... | 0.15  |
| Enable         | 0                   | 0    | ... | 1     |
| Parameters     |                     |      |     |       |
| Kp             | 2                   |      |     |       |
| Ki             | 2500                |      |     |       |
| initHandling   | initialize integral |      |     |       |
| ts_fact        | 1                   |      |     |       |
| Outputs        |                     |      |     |       |
| Out            | 0                   | 0    | ... | 0.647 |
| Exp. Out       | 0                   | 0    | ... | 0.647 |
| Out (DSP)      | 0                   | 0    | ... | 0.647 |
| Exp. Out (DSP) | 0                   | 0    | ... | 0.647 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 73  |
| Max CPU cycles  | 150 |
| Avg CPU cycles  | 122 |

**Test case: Conversion test**

OK

Conversion test for Control block PILimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| <b>Time step</b>             | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PILimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| <b>Time step</b>             | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e-10$ |
| Tolerance b1              | $\pm 1,0000e-06$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1925 |
| Max CPU cycles  | 1947 |
| Avg CPU cycles  | 1925 |

**Verification: PILimit Float32 CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block PILimit.

| Test results   |                     |      |     |       |
|----------------|---------------------|------|-----|-------|
| Time step      | 1                   | 2    | ... | 201   |
| CPU cycles     | 45                  | 45   | ... | 93    |
| Inputs         |                     |      |     |       |
| In (DSP)       | 0                   | 0    | ... | 0     |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11  |
| max (DSP)      | 0.8                 | 0.8  | ... | 0.8   |
| min (DSP)      | 0.15                | 0.15 | ... | 0.15  |
| Enable (DSP)   | 0                   | 0    | ... | 1     |
| In             | 0                   | 0    | ... | 0     |
| Init           | 0.11                | 0.11 | ... | 0.11  |
| max            | 0.8                 | 0.8  | ... | 0.8   |
| min            | 0.15                | 0.15 | ... | 0.15  |
| Enable         | 0                   | 0    | ... | 1     |
| Parameters     |                     |      |     |       |
| Kp             | 2                   |      |     |       |
| Ki             | 2500                |      |     |       |
| initHandling   | initialize integral |      |     |       |
| ts_fact        | 1                   |      |     |       |
| Outputs        |                     |      |     |       |
| Out            | 0                   | 0    | ... | 0.647 |
| Exp. Out       | 0                   | 0    | ... | 0.647 |
| Out (DSP)      | 0                   | 0    | ... | 0.647 |
| Exp. Out (DSP) | 0                   | 0    | ... | 0.647 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 45  |
| Max CPU cycles  | 115 |
| Avg CPU cycles  | 90  |



**Test case: Conversion test**

OK

Conversion test for Control block PILimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| <b>Time step</b>             | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PILimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| <b>Time step</b>             | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e-10$ |
| Tolerance b1              | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 903 |
| Max CPU cycles  | 903 |
| Avg CPU cycles  | 903 |

**Verification: PILimit Float32 CPU STM32G474RE**

Date of Test 2026-06-19  
Target controller STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block PILimit.

| Test results   |                     |      |     |       |
|----------------|---------------------|------|-----|-------|
| Time step      | 1                   | 2    | ... | 201   |
| CPU cycles     | 78                  | 78   | ... | 121   |
| Inputs         |                     |      |     |       |
| In (DSP)       | 0                   | 0    | ... | 0     |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11  |
| max (DSP)      | 0.8                 | 0.8  | ... | 0.8   |
| min (DSP)      | 0.15                | 0.15 | ... | 0.15  |
| Enable (DSP)   | 0                   | 0    | ... | 1     |
| In             | 0                   | 0    | ... | 0     |
| Init           | 0.11                | 0.11 | ... | 0.11  |
| max            | 0.8                 | 0.8  | ... | 0.8   |
| min            | 0.15                | 0.15 | ... | 0.15  |
| Enable         | 0                   | 0    | ... | 1     |
| Parameters     |                     |      |     |       |
| Kp             | 2                   |      |     |       |
| Ki             | 2500                |      |     |       |
| initHandling   | initialize integral |      |     |       |
| ts_fact        | 1                   |      |     |       |
| Outputs        |                     |      |     |       |
| Out            | 0                   | 0    | ... | 0.647 |
| Exp. Out       | 0                   | 0    | ... | 0.647 |
| Out (DSP)      | 0                   | 0    | ... | 0.647 |
| Exp. Out (DSP) | 0                   | 0    | ... | 0.647 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 78  |
| Max CPU cycles  | 172 |
| Avg CPU cycles  | 117 |

**Test case: Conversion test****OK**

Conversion test for Control block PILimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| <b>Time step</b>             | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for Control block PILimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| <b>Time step</b>             | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e-10$ |
| Tolerance b1              | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 918 |
| Max CPU cycles  | 979 |
| Avg CPU cycles  | 919 |

**Verification: PILimit Float32 CPU STM32F072RB**

Date of Test 2026-06-19  
Target controller STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block PILimit.

| Test results   |                     |      |     |       |
|----------------|---------------------|------|-----|-------|
| Time step      | 1                   | 2    | ... | 201   |
| CPU cycles     | 82                  | 82   | ... | 702   |
| Inputs         |                     |      |     |       |
| In (DSP)       | 0                   | 0    | ... | 0     |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11  |
| max (DSP)      | 0.8                 | 0.8  | ... | 0.8   |
| min (DSP)      | 0.15                | 0.15 | ... | 0.15  |
| Enable (DSP)   | 0                   | 0    | ... | 1     |
| In             | 0                   | 0    | ... | 0     |
| Init           | 0.11                | 0.11 | ... | 0.11  |
| max            | 0.8                 | 0.8  | ... | 0.8   |
| min            | 0.15                | 0.15 | ... | 0.15  |
| Enable         | 0                   | 0    | ... | 1     |
| Parameters     |                     |      |     |       |
| Kp             | 2                   |      |     |       |
| Ki             | 2500                |      |     |       |
| initHandling   | initialize integral |      |     |       |
| ts_fact        | 1                   |      |     |       |
| Outputs        |                     |      |     |       |
| Out            | 0                   | 0    | ... | 0.647 |
| Exp. Out       | 0                   | 0    | ... | 0.647 |
| Out (DSP)      | 0                   | 0    | ... | 0.647 |
| Exp. Out (DSP) | 0                   | 0    | ... | 0.647 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 82  |
| Max CPU cycles  | 976 |
| Avg CPU cycles  | 720 |

**Test case: Conversion test**

OK

Conversion test for Control block PILimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| <b>Time step</b>             | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PILimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| <b>Time step</b>             | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e-10$ |
| Tolerance b1              | $\pm 1,0000e-06$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2118 |
| Max CPU cycles  | 2212 |
| Avg CPU cycles  | 2170 |



**Verification: PILimit Float32 CPU PIC32MX170F256**

Date of Test 2026-06-19  
Target controller PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block PILimit.

| Test results   |                     |      |     |       |
|----------------|---------------------|------|-----|-------|
| Time step      | 1                   | 2    | ... | 201   |
| CPU cycles     | 69                  | 69   | ... | 290   |
| Inputs         |                     |      |     |       |
| In (DSP)       | 0                   | 0    | ... | 0     |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11  |
| max (DSP)      | 0.8                 | 0.8  | ... | 0.8   |
| min (DSP)      | 0.15                | 0.15 | ... | 0.15  |
| Enable (DSP)   | 0                   | 0    | ... | 1     |
| In             | 0                   | 0    | ... | 0     |
| Init           | 0.11                | 0.11 | ... | 0.11  |
| max            | 0.8                 | 0.8  | ... | 0.8   |
| min            | 0.15                | 0.15 | ... | 0.15  |
| Enable         | 0                   | 0    | ... | 1     |
| Parameters     |                     |      |     |       |
| Kp             | 2                   |      |     |       |
| Ki             | 2500                |      |     |       |
| initHandling   | initialize integral |      |     |       |
| ts_fact        | 1                   |      |     |       |
| Outputs        |                     |      |     |       |
| Out            | 0                   | 0    | ... | 0.647 |
| Exp. Out       | 0                   | 0    | ... | 0.647 |
| Out (DSP)      | 0                   | 0    | ... | 0.647 |
| Exp. Out (DSP) | 0                   | 0    | ... | 0.647 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 69  |
| Max CPU cycles  | 390 |
| Avg CPU cycles  | 308 |

**Test case: Conversion test**

OK

Conversion test for Control block PILimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| <b>Time step</b>             | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PILimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| <b>Time step</b>             | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e-10$ |
| Tolerance b1              | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 742 |
| Max CPU cycles  | 761 |
| Avg CPU cycles  | 758 |

**Verification: PILimit Float32 CPU XMC4800-F144K2048**

Date of Test 2026-06-19  
Target controller XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block PILimit.

| Test results   |                     |      |     |       |
|----------------|---------------------|------|-----|-------|
| Time step      | 1                   | 2    | ... | 201   |
| CPU cycles     | 79                  | 60   | ... | 110   |
| Inputs         |                     |      |     |       |
| In (DSP)       | 0                   | 0    | ... | 0     |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11  |
| max (DSP)      | 0.8                 | 0.8  | ... | 0.8   |
| min (DSP)      | 0.15                | 0.15 | ... | 0.15  |
| Enable (DSP)   | 0                   | 0    | ... | 1     |
| In             | 0                   | 0    | ... | 0     |
| Init           | 0.11                | 0.11 | ... | 0.11  |
| max            | 0.8                 | 0.8  | ... | 0.8   |
| min            | 0.15                | 0.15 | ... | 0.15  |
| Enable         | 0                   | 0    | ... | 1     |
| Parameters     |                     |      |     |       |
| Kp             | 2                   |      |     |       |
| Ki             | 2500                |      |     |       |
| initHandling   | initialize integral |      |     |       |
| ts_fact        | 1                   |      |     |       |
| Outputs        |                     |      |     |       |
| Out            | 0                   | 0    | ... | 0.647 |
| Exp. Out       | 0                   | 0    | ... | 0.647 |
| Out (DSP)      | 0                   | 0    | ... | 0.647 |
| Exp. Out (DSP) | 0                   | 0    | ... | 0.647 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 60  |
| Max CPU cycles  | 166 |
| Avg CPU cycles  | 107 |

**Test case: Conversion test**

OK

Conversion test for Control block PILimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| Time step                    | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| Kp                           | -10                 | -9.444              | ... | 10                |
| Ki                           | -11                 | -10.389             | ... | 11                |
| initHandling                 | initialize integral | initialize integral | ... | initialize output |
| ts_fact                      | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| initHandling                 | 0                   | 0                   | ... | 1                 |
| b0                           | -0.001              | -0.001              | ... | 0.001             |
| b1                           | -10                 | -9.444              | ... | 10                |
| Exp. initHandling            | 0                   | 0                   | ... | 1                 |
| Exp. b0                      | -0.001              | -0.001              | ... | 0.001             |
| Exp. b1                      | -10                 | -9.444              | ... | 10                |

| Test settings          |                  |
|------------------------|------------------|
| Tolerance initHandling | $\pm 0,0000e+00$ |
| Tolerance b0           | $\pm 0,0000e+00$ |
| Tolerance b1           | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PILimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| <b>Time step</b>             | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e-10$ |
| Tolerance b1              | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 882 |
| Max CPU cycles  | 996 |
| Avg CPU cycles  | 887 |

**Verification: PILimit Float32 CPU TMS320F28379D**

Date of Test 2026-06-22  
Target controller TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block PILimit.

| Test results   |                     |      |     |       |
|----------------|---------------------|------|-----|-------|
| Time step      | 1                   | 2    | ... | 201   |
| CPU cycles     | 67                  | 67   | ... | 134   |
| Inputs         |                     |      |     |       |
| In (DSP)       | 0                   | 0    | ... | 0     |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11  |
| max (DSP)      | 0.8                 | 0.8  | ... | 0.8   |
| min (DSP)      | 0.15                | 0.15 | ... | 0.15  |
| Enable (DSP)   | 0                   | 0    | ... | 1     |
| In             | 0                   | 0    | ... | 0     |
| Init           | 0.11                | 0.11 | ... | 0.11  |
| max            | 0.8                 | 0.8  | ... | 0.8   |
| min            | 0.15                | 0.15 | ... | 0.15  |
| Enable         | 0                   | 0    | ... | 1     |
| Parameters     |                     |      |     |       |
| Kp             | 2                   |      |     |       |
| Ki             | 2500                |      |     |       |
| initHandling   | initialize integral |      |     |       |
| ts_fact        | 1                   |      |     |       |
| Outputs        |                     |      |     |       |
| Out            | 0                   | 0    | ... | 0.647 |
| Exp. Out       | 0                   | 0    | ... | 0.647 |
| Out (DSP)      | 0                   | 0    | ... | 0.647 |
| Exp. Out (DSP) | 0                   | 0    | ... | 0.647 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 67  |
| Max CPU cycles  | 164 |
| Avg CPU cycles  | 126 |

**Test case: Conversion test**

OK

Conversion test for Control block PILimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| <b>Time step</b>             | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Control block PILimit.



| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| <b>Time step</b>             | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e-10$ |
| Tolerance b1              | $\pm 1,0000e-06$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1427 |
| Max CPU cycles  | 1449 |
| Avg CPU cycles  | 1427 |

**Verification: PILimit Float32 CPU dsPIC33EP256MC502**

Date of Test 2026-06-23  
Target controller dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block PILimit.

| Test results   |                     |      |     |       |
|----------------|---------------------|------|-----|-------|
| Time step      | 1                   | 2    | ... | 201   |
| CPU cycles     | 64                  | 64   | ... | 749   |
| Inputs         |                     |      |     |       |
| In (DSP)       | 0                   | 0    | ... | 0     |
| Init (DSP)     | 0.11                | 0.11 | ... | 0.11  |
| max (DSP)      | 0.8                 | 0.8  | ... | 0.8   |
| min (DSP)      | 0.15                | 0.15 | ... | 0.15  |
| Enable (DSP)   | 0                   | 0    | ... | 1     |
| In             | 0                   | 0    | ... | 0     |
| Init           | 0.11                | 0.11 | ... | 0.11  |
| max            | 0.8                 | 0.8  | ... | 0.8   |
| min            | 0.15                | 0.15 | ... | 0.15  |
| Enable         | 0                   | 0    | ... | 1     |
| Parameters     |                     |      |     |       |
| Kp             | 2                   |      |     |       |
| Ki             | 2500                |      |     |       |
| initHandling   | initialize integral |      |     |       |
| ts_fact        | 1                   |      |     |       |
| Outputs        |                     |      |     |       |
| Out            | 0                   | 0    | ... | 0.647 |
| Exp. Out       | 0                   | 0    | ... | 0.647 |
| Out (DSP)      | 0                   | 0    | ... | 0.647 |
| Exp. Out (DSP) | 0                   | 0    | ... | 0.647 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 64   |
| Max CPU cycles  | 1021 |
| Avg CPU cycles  | 775  |

**Test case: Conversion test****OK**

Conversion test for Control block PILimit.

| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| <b>Time step</b>             | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 0,0000e+00$ |
| Tolerance b1              | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for Control block PILimit.


| Test results                 |                     |                     |     |                   |
|------------------------------|---------------------|---------------------|-----|-------------------|
| <b>Time step</b>             | 1                   | 2                   | ... | 37                |
| <i>Mask parameters</i>       |                     |                     |     |                   |
| <b>Kp</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Ki</b>                    | -11                 | -10.389             | ... | 11                |
| <b>initHandling</b>          | initialize integral | initialize integral | ... | initialize output |
| <b>ts_fact</b>               | 1                   | 1                   | ... | 1                 |
| <i>Controller parameters</i> |                     |                     |     |                   |
| <b>initHandling</b>          | 0                   | 0                   | ... | 1                 |
| <b>b0</b>                    | -0.001              | -0.001              | ... | 0.001             |
| <b>b1</b>                    | -10                 | -9.444              | ... | 10                |
| <b>Exp. initHandling</b>     | 0                   | 0                   | ... | 1                 |
| <b>Exp. b0</b>               | -0.001              | -0.001              | ... | 0.001             |
| <b>Exp. b1</b>               | -10                 | -9.444              | ... | 10                |

| Test settings             |                  |
|---------------------------|------------------|
| Tolerance<br>initHandling | $\pm 0,0000e+00$ |
| Tolerance b0              | $\pm 1,0000e-10$ |
| Tolerance b1              | $\pm 1,0000e-06$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2488 |
| Max CPU cycles  | 3225 |
| Avg CPU cycles  | 3201 |

## Block: PLimit

---



P controller with output limitation:

$$G(s) = K_p$$

| Inports |                                                                                      |
|---------|--------------------------------------------------------------------------------------|
| In      | Control error input                                                                  |
| max     | Maximum output value                                                                 |
| min     | Minimum output value                                                                 |
| Enable  | Enable == 0: Deactivation of block; Out set to 0<br>Enable == 1: Activation of block |

| Outports |               |
|----------|---------------|
| Out      | Control value |

| Mask Parameters |    |                     |
|-----------------|----|---------------------|
| Name            | ID | Description         |
| Kp              | 1  | Proportional Factor |

### Description:

Transfer function (zero-order hold discretization method):

$$G(z) = K_p$$

**Developer note:** The source code of this block is used for block *P*.

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |
| max               | int16 |
| min               | int16 |
| Enable            | bool  |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |
| max               | int32 |
| min               | int32 |
| Enable            | bool  |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |
| max               | float32 |
| min               | float32 |
| Enable            | bool    |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |
| max               | float64 |
| min               | float64 |
| Enable            | bool    |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: PLimit FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block PLimit.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 64    | 64    | 64    | 90    | ... | 90    |
| Inputs         |       |       |       |       |     |       |
| In (DSP)       | 0     | 0     | 0     | 0     | ... | 0     |
| max (DSP)      | 26214 | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915  | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0     | 0     | 0     | 1     | ... | 1     |
| In             | 0     | 0     | 0     | 0     | ... | 0     |
| max            | 0.8   | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15  | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0     | 0     | 0     | 1     | ... | 1     |
| Parameters     |       |       |       |       |     |       |
| Kp             | 2     |       |       |       |     |       |
| Outputs        |       |       |       |       |     |       |
| Out            | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Exp. Out       | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Out (DSP)      | 0     | 0     | 0     | 4915  | ... | 4915  |
| Exp. Out (DSP) | 0     | 0     | 0     | 4915  | ... | 4915  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 64 |
| Max CPU cycles  | 90 |
| Avg CPU cycles  | 89 |

**Test case: Conversion test****OK**

Conversion test for Control block PLimit.



| Test results                 |        |         |        |        |     |       |
|------------------------------|--------|---------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2       | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |         |        |        |     |       |
| <b>Kp</b>                    | -11    | -10.389 | -9.778 | -9.167 | ... | 11    |
| <i>Controller parameters</i> |        |         |        |        |     |       |
| <b>sfrb1</b>                 | 11     | 11      | 11     | 11     | ... | 11    |
| <b>b1</b>                    | -22528 | -21276  | -20025 | -18773 | ... | 22528 |
| <b>Exp. sfrb1</b>            | 11     | 11      | 11     | 11     | ... | 11    |
| <b>Exp. b1</b>               | -22528 | -21276  | -20025 | -18773 | ... | 22528 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PLimit.

| Test results                 |        |         |        |        |     |       |
|------------------------------|--------|---------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2       | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |         |        |        |     |       |
| <b>Kp</b>                    | -11    | -10.389 | -9.778 | -9.167 | ... | 11    |
| <i>Controller parameters</i> |        |         |        |        |     |       |
| <b>sfrb1</b>                 | 11     | 11      | 11     | 11     | ... | 11    |
| <b>b1</b>                    | -22528 | -21276  | -20024 | -18773 | ... | 22528 |
| <b>Exp. sfrb1</b>            | 11     | 11      | 11     | 11     | ... | 11    |
| <b>Exp. b1</b>               | -22528 | -21276  | -20025 | -18773 | ... | 22528 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1406 |
| Max CPU cycles  | 3556 |
| Avg CPU cycles  | 2858 |

**Verification: PLimit FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block PLimit.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 37    | 37    | 37    | 53    | ... | 53    |
| Inputs         |       |       |       |       |     |       |
| In (DSP)       | 0     | 0     | 0     | 0     | ... | 0     |
| max (DSP)      | 26214 | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915  | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0     | 0     | 0     | 1     | ... | 1     |
| In             | 0     | 0     | 0     | 0     | ... | 0     |
| max            | 0.8   | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15  | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0     | 0     | 0     | 1     | ... | 1     |
| Parameters     |       |       |       |       |     |       |
| Kp             | 2     |       |       |       |     |       |
| Outputs        |       |       |       |       |     |       |
| Out            | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Exp. Out       | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Out (DSP)      | 0     | 0     | 0     | 4915  | ... | 4915  |
| Exp. Out (DSP) | 0     | 0     | 0     | 4915  | ... | 4915  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 37 |
| Max CPU cycles  | 53 |
| Avg CPU cycles  | 52 |

**Test case: Conversion test****OK**

Conversion test for Control block PLimit.

| Test results                 |        |         |        |        |     |       |
|------------------------------|--------|---------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2       | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |         |        |        |     |       |
| <b>Kp</b>                    | -11    | -10.389 | -9.778 | -9.167 | ... | 11    |
| <i>Controller parameters</i> |        |         |        |        |     |       |
| <b>sfrb1</b>                 | 11     | 11      | 11     | 11     | ... | 11    |
| <b>b1</b>                    | -22528 | -21276  | -20025 | -18773 | ... | 22528 |
| <b>Exp. sfrb1</b>            | 11     | 11      | 11     | 11     | ... | 11    |
| <b>Exp. b1</b>               | -22528 | -21276  | -20025 | -18773 | ... | 22528 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PLimit.

| Test results                 |        |         |        |        |     |       |
|------------------------------|--------|---------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2       | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |         |        |        |     |       |
| <b>Kp</b>                    | -11    | -10.389 | -9.778 | -9.167 | ... | 11    |
| <i>Controller parameters</i> |        |         |        |        |     |       |
| <b>sfrb1</b>                 | 11     | 11      | 11     | 11     | ... | 11    |
| <b>b1</b>                    | -22528 | -21276  | -20024 | -18773 | ... | 22528 |
| <b>Exp. sfrb1</b>            | 11     | 11      | 11     | 11     | ... | 11    |
| <b>Exp. b1</b>               | -22528 | -21276  | -20025 | -18773 | ... | 22528 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 727  |
| Max CPU cycles  | 1979 |
| Avg CPU cycles  | 1569 |

**Verification: PLimit FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block PLimit.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 68    | 68    | 68    | 83    | ... | 83    |
| Inputs         |       |       |       |       |     |       |
| In (DSP)       | 0     | 0     | 0     | 0     | ... | 0     |
| max (DSP)      | 26214 | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915  | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0     | 0     | 0     | 1     | ... | 1     |
| In             | 0     | 0     | 0     | 0     | ... | 0     |
| max            | 0.8   | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15  | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0     | 0     | 0     | 1     | ... | 1     |
| Parameters     |       |       |       |       |     |       |
| Kp             | 2     |       |       |       |     |       |
| Outputs        |       |       |       |       |     |       |
| Out            | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Exp. Out       | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Out (DSP)      | 0     | 0     | 0     | 4915  | ... | 4915  |
| Exp. Out (DSP) | 0     | 0     | 0     | 4915  | ... | 4915  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 68 |
| Max CPU cycles  | 83 |
| Avg CPU cycles  | 82 |

**Test case: Conversion test****OK**

Conversion test for Control block PLimit.

| Test results                 |        |         |        |        |     |       |
|------------------------------|--------|---------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2       | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |         |        |        |     |       |
| <b>Kp</b>                    | -11    | -10.389 | -9.778 | -9.167 | ... | 11    |
| <i>Controller parameters</i> |        |         |        |        |     |       |
| <b>sfrb1</b>                 | 11     | 11      | 11     | 11     | ... | 11    |
| <b>b1</b>                    | -22528 | -21276  | -20025 | -18773 | ... | 22528 |
| <b>Exp. sfrb1</b>            | 11     | 11      | 11     | 11     | ... | 11    |
| <b>Exp. b1</b>               | -22528 | -21276  | -20025 | -18773 | ... | 22528 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PLimit.

| Test results                 |        |         |        |        |     |       |
|------------------------------|--------|---------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2       | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |         |        |        |     |       |
| <b>Kp</b>                    | -11    | -10.389 | -9.778 | -9.167 | ... | 11    |
| <i>Controller parameters</i> |        |         |        |        |     |       |
| <b>sfrb1</b>                 | 11     | 11      | 11     | 11     | ... | 11    |
| <b>b1</b>                    | -22528 | -21276  | -20024 | -18773 | ... | 22528 |
| <b>Exp. sfrb1</b>            | 11     | 11      | 11     | 11     | ... | 11    |
| <b>Exp. b1</b>               | -22528 | -21276  | -20025 | -18773 | ... | 22528 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 911  |
| Max CPU cycles  | 1434 |
| Avg CPU cycles  | 1263 |

**Verification: PLimit FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block PLimit.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 52    | 52    | 52    | 82    | ... | 82    |
| Inputs         |       |       |       |       |     |       |
| In (DSP)       | 0     | 0     | 0     | 0     | ... | 0     |
| max (DSP)      | 26214 | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915  | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0     | 0     | 0     | 1     | ... | 1     |
| In             | 0     | 0     | 0     | 0     | ... | 0     |
| max            | 0.8   | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15  | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0     | 0     | 0     | 1     | ... | 1     |
| Parameters     |       |       |       |       |     |       |
| Kp             | 2     |       |       |       |     |       |
| Outputs        |       |       |       |       |     |       |
| Out            | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Exp. Out       | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Out (DSP)      | 0     | 0     | 0     | 4915  | ... | 4915  |
| Exp. Out (DSP) | 0     | 0     | 0     | 4915  | ... | 4915  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 52 |
| Max CPU cycles  | 82 |
| Avg CPU cycles  | 81 |

**Test case: Conversion test****OK**

Conversion test for Control block PLimit.

| Test results                 |        |         |        |        |     |       |
|------------------------------|--------|---------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2       | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |         |        |        |     |       |
| <b>Kp</b>                    | -11    | -10.389 | -9.778 | -9.167 | ... | 11    |
| <i>Controller parameters</i> |        |         |        |        |     |       |
| <b>sfrb1</b>                 | 11     | 11      | 11     | 11     | ... | 11    |
| <b>b1</b>                    | -22528 | -21276  | -20025 | -18773 | ... | 22528 |
| <b>Exp. sfrb1</b>            | 11     | 11      | 11     | 11     | ... | 11    |
| <b>Exp. b1</b>               | -22528 | -21276  | -20025 | -18773 | ... | 22528 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PLimit.

| Test results                 |        |         |        |        |     |       |
|------------------------------|--------|---------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2       | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |         |        |        |     |       |
| <b>Kp</b>                    | -11    | -10.389 | -9.778 | -9.167 | ... | 11    |
| <i>Controller parameters</i> |        |         |        |        |     |       |
| <b>sfrb1</b>                 | 11     | 11      | 11     | 11     | ... | 11    |
| <b>b1</b>                    | -22528 | -21276  | -20024 | -18773 | ... | 22528 |
| <b>Exp. sfrb1</b>            | 11     | 11      | 11     | 11     | ... | 11    |
| <b>Exp. b1</b>               | -22528 | -21276  | -20025 | -18773 | ... | 22528 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1640 |
| Max CPU cycles  | 4611 |
| Avg CPU cycles  | 3683 |

**Verification: PLimit FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block PLimit.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 30    | 30    | 30    | 56    | ... | 56    |
| Inputs         |       |       |       |       |     |       |
| In (DSP)       | 0     | 0     | 0     | 0     | ... | 0     |
| max (DSP)      | 26214 | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915  | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0     | 0     | 0     | 1     | ... | 1     |
| In             | 0     | 0     | 0     | 0     | ... | 0     |
| max            | 0.8   | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15  | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0     | 0     | 0     | 1     | ... | 1     |
| Parameters     |       |       |       |       |     |       |
| Kp             | 2     |       |       |       |     |       |
| Outputs        |       |       |       |       |     |       |
| Out            | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Exp. Out       | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Out (DSP)      | 0     | 0     | 0     | 4915  | ... | 4915  |
| Exp. Out (DSP) | 0     | 0     | 0     | 4915  | ... | 4915  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 30 |
| Max CPU cycles  | 56 |
| Avg CPU cycles  | 55 |

**Test case: Conversion test****OK**

Conversion test for Control block PLimit.



| Test results                 |        |         |        |        |     |       |
|------------------------------|--------|---------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2       | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |         |        |        |     |       |
| <b>Kp</b>                    | -11    | -10.389 | -9.778 | -9.167 | ... | 11    |
| <i>Controller parameters</i> |        |         |        |        |     |       |
| <b>sfrb1</b>                 | 11     | 11      | 11     | 11     | ... | 11    |
| <b>b1</b>                    | -22528 | -21276  | -20025 | -18773 | ... | 22528 |
| <b>Exp. sfrb1</b>            | 11     | 11      | 11     | 11     | ... | 11    |
| <b>Exp. b1</b>               | -22528 | -21276  | -20025 | -18773 | ... | 22528 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PLimit.

| Test results                 |        |         |        |        |     |       |
|------------------------------|--------|---------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2       | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |         |        |        |     |       |
| <b>Kp</b>                    | -11    | -10.389 | -9.778 | -9.167 | ... | 11    |
| <i>Controller parameters</i> |        |         |        |        |     |       |
| <b>sfrb1</b>                 | 11     | 11      | 11     | 11     | ... | 11    |
| <b>b1</b>                    | -22528 | -21276  | -20024 | -18773 | ... | 22528 |
| <b>Exp. sfrb1</b>            | 11     | 11      | 11     | 11     | ... | 11    |
| <b>Exp. b1</b>               | -22528 | -21276  | -20025 | -18773 | ... | 22528 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 774  |
| Max CPU cycles  | 1943 |
| Avg CPU cycles  | 1576 |

**Verification: PLimit FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block PLimit.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 72    | 58    | 58    | 83    | ... | 83    |
| Inputs         |       |       |       |       |     |       |
| In (DSP)       | 0     | 0     | 0     | 0     | ... | 0     |
| max (DSP)      | 26214 | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915  | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0     | 0     | 0     | 1     | ... | 1     |
| In             | 0     | 0     | 0     | 0     | ... | 0     |
| max            | 0.8   | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15  | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0     | 0     | 0     | 1     | ... | 1     |
| Parameters     |       |       |       |       |     |       |
| Kp             | 2     |       |       |       |     |       |
| Outputs        |       |       |       |       |     |       |
| Out            | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Exp. Out       | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Out (DSP)      | 0     | 0     | 0     | 4915  | ... | 4915  |
| Exp. Out (DSP) | 0     | 0     | 0     | 4915  | ... | 4915  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 58 |
| Max CPU cycles  | 83 |
| Avg CPU cycles  | 82 |

**Test case: Conversion test****OK**

Conversion test for Control block PLimit.

| Test results                 |        |         |        |        |     |       |
|------------------------------|--------|---------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2       | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |         |        |        |     |       |
| <b>Kp</b>                    | -11    | -10.389 | -9.778 | -9.167 | ... | 11    |
| <i>Controller parameters</i> |        |         |        |        |     |       |
| <b>sfrb1</b>                 | 11     | 11      | 11     | 11     | ... | 11    |
| <b>b1</b>                    | -22528 | -21276  | -20025 | -18773 | ... | 22528 |
| <b>Exp. sfrb1</b>            | 11     | 11      | 11     | 11     | ... | 11    |
| <b>Exp. b1</b>               | -22528 | -21276  | -20025 | -18773 | ... | 22528 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PLimit.

| Test results                 |        |         |        |        |     |       |
|------------------------------|--------|---------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2       | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |         |        |        |     |       |
| <b>Kp</b>                    | -11    | -10.389 | -9.778 | -9.167 | ... | 11    |
| <i>Controller parameters</i> |        |         |        |        |     |       |
| <b>sfrb1</b>                 | 11     | 11      | 11     | 11     | ... | 11    |
| <b>b1</b>                    | -22528 | -21276  | -20024 | -18773 | ... | 22528 |
| <b>Exp. sfrb1</b>            | 11     | 11      | 11     | 11     | ... | 11    |
| <b>Exp. b1</b>               | -22528 | -21276  | -20025 | -18773 | ... | 22528 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 667  |
| Max CPU cycles  | 1218 |
| Avg CPU cycles  | 992  |

**Verification: PLimit FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block PLimit.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 60    | 60    | 60    | 86    | ... | 86    |
| Inputs         |       |       |       |       |     |       |
| In (DSP)       | 0     | 0     | 0     | 0     | ... | 0     |
| max (DSP)      | 26214 | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915  | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0     | 0     | 0     | 1     | ... | 1     |
| In             | 0     | 0     | 0     | 0     | ... | 0     |
| max            | 0.8   | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15  | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0     | 0     | 0     | 1     | ... | 1     |
| Parameters     |       |       |       |       |     |       |
| Kp             | 2     |       |       |       |     |       |
| Outputs        |       |       |       |       |     |       |
| Out            | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Exp. Out       | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Out (DSP)      | 0     | 0     | 0     | 4915  | ... | 4915  |
| Exp. Out (DSP) | 0     | 0     | 0     | 4915  | ... | 4915  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 60 |
| Max CPU cycles  | 86 |
| Avg CPU cycles  | 85 |

**Test case: Conversion test****OK**

Conversion test for Control block PLimit.

| Test results                 |        |         |        |        |     |       |
|------------------------------|--------|---------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2       | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |         |        |        |     |       |
| <b>Kp</b>                    | -11    | -10.389 | -9.778 | -9.167 | ... | 11    |
| <i>Controller parameters</i> |        |         |        |        |     |       |
| <b>sfrb1</b>                 | 11     | 11      | 11     | 11     | ... | 11    |
| <b>b1</b>                    | -22528 | -21276  | -20025 | -18773 | ... | 22528 |
| <b>Exp. sfrb1</b>            | 11     | 11      | 11     | 11     | ... | 11    |
| <b>Exp. b1</b>               | -22528 | -21276  | -20025 | -18773 | ... | 22528 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PLimit.

| Test results                 |        |         |        |        |     |       |
|------------------------------|--------|---------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2       | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |         |        |        |     |       |
| <b>Kp</b>                    | -11    | -10.389 | -9.778 | -9.167 | ... | 11    |
| <i>Controller parameters</i> |        |         |        |        |     |       |
| <b>sfrb1</b>                 | 11     | 11      | 11     | 11     | ... | 11    |
| <b>b1</b>                    | -22528 | -21276  | -20024 | -18773 | ... | 22528 |
| <b>Exp. sfrb1</b>            | 11     | 11      | 11     | 11     | ... | 11    |
| <b>Exp. b1</b>               | -22528 | -21276  | -20025 | -18773 | ... | 22528 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1079 |
| Max CPU cycles  | 2769 |
| Avg CPU cycles  | 2219 |

**Verification: PLimit FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block PLimit.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 201   |
| CPU cycles     | 39    | 39    | 39    | 74    | ... | 74    |
| Inputs         |       |       |       |       |     |       |
| In (DSP)       | 0     | 0     | 0     | 0     | ... | 0     |
| max (DSP)      | 26214 | 26214 | 26214 | 26214 | ... | 26214 |
| min (DSP)      | 4915  | 4915  | 4915  | 4915  | ... | 4915  |
| Enable (DSP)   | 0     | 0     | 0     | 1     | ... | 1     |
| In             | 0     | 0     | 0     | 0     | ... | 0     |
| max            | 0.8   | 0.8   | 0.8   | 0.8   | ... | 0.8   |
| min            | 0.15  | 0.15  | 0.15  | 0.15  | ... | 0.15  |
| Enable         | 0     | 0     | 0     | 1     | ... | 1     |
| Parameters     |       |       |       |       |     |       |
| Kp             | 2     |       |       |       |     |       |
| Outputs        |       |       |       |       |     |       |
| Out            | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Exp. Out       | 0     | 0     | 0     | 0.15  | ... | 0.15  |
| Out (DSP)      | 0     | 0     | 0     | 4915  | ... | 4915  |
| Exp. Out (DSP) | 0     | 0     | 0     | 4915  | ... | 4915  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 39 |
| Max CPU cycles  | 74 |
| Avg CPU cycles  | 73 |

**Test case: Conversion test****OK**

Conversion test for Control block PLimit.

| Test results                 |        |         |        |        |     |       |
|------------------------------|--------|---------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2       | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |         |        |        |     |       |
| <b>Kp</b>                    | -11    | -10.389 | -9.778 | -9.167 | ... | 11    |
| <i>Controller parameters</i> |        |         |        |        |     |       |
| <b>sfrb1</b>                 | 11     | 11      | 11     | 11     | ... | 11    |
| <b>b1</b>                    | -22528 | -21276  | -20025 | -18773 | ... | 22528 |
| <b>Exp. sfrb1</b>            | 11     | 11      | 11     | 11     | ... | 11    |
| <b>Exp. b1</b>               | -22528 | -21276  | -20025 | -18773 | ... | 22528 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PLimit.

| Test results                 |        |         |        |        |     |       |
|------------------------------|--------|---------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2       | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |         |        |        |     |       |
| <b>Kp</b>                    | -11    | -10.389 | -9.778 | -9.167 | ... | 11    |
| <i>Controller parameters</i> |        |         |        |        |     |       |
| <b>sfrb1</b>                 | 11     | 11      | 11     | 11     | ... | 11    |
| <b>b1</b>                    | -22528 | -21276  | -20024 | -18773 | ... | 22528 |
| <b>Exp. sfrb1</b>            | 11     | 11      | 11     | 11     | ... | 11    |
| <b>Exp. b1</b>               | -22528 | -21276  | -20025 | -18773 | ... | 22528 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 2497  |
| Max CPU cycles  | 10438 |
| Avg CPU cycles  | 8074  |

**Verification: PLimit FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block PLimit.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 201        |
| CPU cycles     | 67         | 67         | ... | 184        |
| Inputs         |            |            |     |            |
| In (DSP)       | 0          | 0          | ... | 0          |
| max (DSP)      | 1717986918 | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547  | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0          | 0          | ... | 1          |
| In             | 0          | 0          | ... | 0          |
| max            | 0.8        | 0.8        | ... | 0.8        |
| min            | 0.15       | 0.15       | ... | 0.15       |
| Enable         | 0          | 0          | ... | 1          |
| Parameters     |            |            |     |            |
| Kp             | 2          |            |     |            |
| Outputs        |            |            |     |            |
| Out            | 0          | 0          | ... | 0.15       |
| Exp. Out       | 0          | 0          | ... | 0.15       |
| Out (DSP)      | 0          | 0          | ... | 322122547  |
| Exp. Out (DSP) | 0          | 0          | ... | 322122547  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 67  |
| Max CPU cycles  | 220 |
| Avg CPU cycles  | 191 |

**Test case: Conversion test****OK**

Conversion test for Control block PLimit.



| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -11         | -10.389     | ... | 11         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1476395008 | -1394373063 | ... | 1476395008 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1476395008 | -1394373063 | ... | 1476395008 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PLimit.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -11         | -10.389     | ... | 11         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1476395008 | -1394373120 | ... | 1476395008 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1476395008 | -1394373063 | ... | 1476395008 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1586 |
| Max CPU cycles  | 3784 |
| Avg CPU cycles  | 3082 |

**Verification: PLimit FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block PLimit.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 201        |
| CPU cycles     | 43         | 43         | ... | 87         |
| Inputs         |            |            |     |            |
| In (DSP)       | 0          | 0          | ... | 0          |
| max (DSP)      | 1717986918 | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547  | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0          | 0          | ... | 1          |
| In             | 0          | 0          | ... | 0          |
| max            | 0.8        | 0.8        | ... | 0.8        |
| min            | 0.15       | 0.15       | ... | 0.15       |
| Enable         | 0          | 0          | ... | 1          |
| Parameters     |            |            |     |            |
| Kp             | 2          |            |     |            |
| Outputs        |            |            |     |            |
| Out            | 0          | 0          | ... | 0.15       |
| Exp. Out       | 0          | 0          | ... | 0.15       |
| Out (DSP)      | 0          | 0          | ... | 322122547  |
| Exp. Out (DSP) | 0          | 0          | ... | 322122547  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 43 |
| Max CPU cycles  | 87 |
| Avg CPU cycles  | 86 |

**Test case: Conversion test****OK**

Conversion test for Control block PLimit.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -11         | -10.389     | ... | 11         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1476395008 | -1394373063 | ... | 1476395008 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1476395008 | -1394373063 | ... | 1476395008 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PLimit.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -11         | -10.389     | ... | 11         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1476395008 | -1394373120 | ... | 1476395008 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1476395008 | -1394373063 | ... | 1476395008 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 689  |
| Max CPU cycles  | 1585 |
| Avg CPU cycles  | 1303 |

**Verification: PLimit FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block PLimit.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 201        |
| CPU cycles     | 68         | 68         | ... | 111        |
| Inputs         |            |            |     |            |
| In (DSP)       | 0          | 0          | ... | 0          |
| max (DSP)      | 1717986918 | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547  | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0          | 0          | ... | 1          |
| In             | 0          | 0          | ... | 0          |
| max            | 0.8        | 0.8        | ... | 0.8        |
| min            | 0.15       | 0.15       | ... | 0.15       |
| Enable         | 0          | 0          | ... | 1          |
| Parameters     |            |            |     |            |
| Kp             | 2          |            |     |            |
| Outputs        |            |            |     |            |
| Out            | 0          | 0          | ... | 0.15       |
| Exp. Out       | 0          | 0          | ... | 0.15       |
| Out (DSP)      | 0          | 0          | ... | 322122547  |
| Exp. Out (DSP) | 0          | 0          | ... | 322122547  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 68  |
| Max CPU cycles  | 111 |
| Avg CPU cycles  | 110 |

**Test case: Conversion test****OK**

Conversion test for Control block PLimit.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -11         | -10.389     | ... | 11         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1476395008 | -1394373063 | ... | 1476395008 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1476395008 | -1394373063 | ... | 1476395008 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PLimit.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -11         | -10.389     | ... | 11         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1476395008 | -1394373120 | ... | 1476395008 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1476395008 | -1394373063 | ... | 1476395008 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1275 |
| Max CPU cycles  | 1841 |
| Avg CPU cycles  | 1662 |

**Verification: PLimit FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block PLimit.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 201        |
| CPU cycles     | 64         | 64         | ... | 189        |
| Inputs         |            |            |     |            |
| In (DSP)       | 0          | 0          | ... | 0          |
| max (DSP)      | 1717986918 | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547  | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0          | 0          | ... | 1          |
| In             | 0          | 0          | ... | 0          |
| max            | 0.8        | 0.8        | ... | 0.8        |
| min            | 0.15       | 0.15       | ... | 0.15       |
| Enable         | 0          | 0          | ... | 1          |
| Parameters     |            |            |     |            |
| Kp             | 2          |            |     |            |
| Outputs        |            |            |     |            |
| Out            | 0          | 0          | ... | 0.15       |
| Exp. Out       | 0          | 0          | ... | 0.15       |
| Out (DSP)      | 0          | 0          | ... | 322122547  |
| Exp. Out (DSP) | 0          | 0          | ... | 322122547  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 64  |
| Max CPU cycles  | 189 |
| Avg CPU cycles  | 184 |

**Test case: Conversion test****OK**

Conversion test for Control block PLimit.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -11         | -10.389     | ... | 11         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1476395008 | -1394373063 | ... | 1476395008 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1476395008 | -1394373063 | ... | 1476395008 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PLimit.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -11         | -10.389     | ... | 11         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1476395008 | -1394373120 | ... | 1476395008 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1476395008 | -1394373063 | ... | 1476395008 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2673 |
| Max CPU cycles  | 5824 |
| Avg CPU cycles  | 4950 |

**Verification: PLimit FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block PLimit.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 201        |
| CPU cycles     | 30         | 30         | ... | 80         |
| Inputs         |            |            |     |            |
| In (DSP)       | 0          | 0          | ... | 0          |
| max (DSP)      | 1717986918 | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547  | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0          | 0          | ... | 1          |
| In             | 0          | 0          | ... | 0          |
| max            | 0.8        | 0.8        | ... | 0.8        |
| min            | 0.15       | 0.15       | ... | 0.15       |
| Enable         | 0          | 0          | ... | 1          |
| Parameters     |            |            |     |            |
| Kp             | 2          |            |     |            |
| Outputs        |            |            |     |            |
| Out            | 0          | 0          | ... | 0.15       |
| Exp. Out       | 0          | 0          | ... | 0.15       |
| Out (DSP)      | 0          | 0          | ... | 322122547  |
| Exp. Out (DSP) | 0          | 0          | ... | 322122547  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 30 |
| Max CPU cycles  | 80 |
| Avg CPU cycles  | 78 |

**Test case: Conversion test****OK**

Conversion test for Control block PLimit.



| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -11         | -10.389     | ... | 11         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1476395008 | -1394373063 | ... | 1476395008 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1476395008 | -1394373063 | ... | 1476395008 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PLimit.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -11         | -10.389     | ... | 11         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1476395008 | -1394373120 | ... | 1476395008 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1476395008 | -1394373063 | ... | 1476395008 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1230 |
| Max CPU cycles  | 2413 |
| Avg CPU cycles  | 2045 |

**Verification: PLimit FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block PLimit.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 201        |
| CPU cycles     | 66         | 58         | ... | 110        |
| Inputs         |            |            |     |            |
| In (DSP)       | 0          | 0          | ... | 0          |
| max (DSP)      | 1717986918 | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547  | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0          | 0          | ... | 1          |
| In             | 0          | 0          | ... | 0          |
| max            | 0.8        | 0.8        | ... | 0.8        |
| min            | 0.15       | 0.15       | ... | 0.15       |
| Enable         | 0          | 0          | ... | 1          |
| Parameters     |            |            |     |            |
| Kp             | 2          |            |     |            |
| Outputs        |            |            |     |            |
| Out            | 0          | 0          | ... | 0.15       |
| Exp. Out       | 0          | 0          | ... | 0.15       |
| Out (DSP)      | 0          | 0          | ... | 322122547  |
| Exp. Out (DSP) | 0          | 0          | ... | 322122547  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 58  |
| Max CPU cycles  | 113 |
| Avg CPU cycles  | 109 |

**Test case: Conversion test****OK**

Conversion test for Control block PLimit.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -11         | -10.389     | ... | 11         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1476395008 | -1394373063 | ... | 1476395008 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1476395008 | -1394373063 | ... | 1476395008 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PLimit.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -11         | -10.389     | ... | 11         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1476395008 | -1394373120 | ... | 1476395008 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1476395008 | -1394373063 | ... | 1476395008 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 918  |
| Max CPU cycles  | 1567 |
| Avg CPU cycles  | 1252 |

**Verification: PLimit FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block PLimit.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 201        |
| CPU cycles     | 65         | 65         | ... | 163        |
| Inputs         |            |            |     |            |
| In (DSP)       | 0          | 0          | ... | 0          |
| max (DSP)      | 1717986918 | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547  | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0          | 0          | ... | 1          |
| In             | 0          | 0          | ... | 0          |
| max            | 0.8        | 0.8        | ... | 0.8        |
| min            | 0.15       | 0.15       | ... | 0.15       |
| Enable         | 0          | 0          | ... | 1          |
| Parameters     |            |            |     |            |
| Kp             | 2          |            |     |            |
| Outputs        |            |            |     |            |
| Out            | 0          | 0          | ... | 0.15       |
| Exp. Out       | 0          | 0          | ... | 0.15       |
| Out (DSP)      | 0          | 0          | ... | 322122547  |
| Exp. Out (DSP) | 0          | 0          | ... | 322122547  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 65  |
| Max CPU cycles  | 183 |
| Avg CPU cycles  | 166 |

**Test case: Conversion test****OK**

Conversion test for Control block PLimit.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -11         | -10.389     | ... | 11         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1476395008 | -1394373063 | ... | 1476395008 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1476395008 | -1394373063 | ... | 1476395008 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PLimit.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -11         | -10.389     | ... | 11         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1476395008 | -1394373120 | ... | 1476395008 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1476395008 | -1394373063 | ... | 1476395008 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1196 |
| Max CPU cycles  | 2929 |
| Avg CPU cycles  | 2375 |

**Verification: PLimit FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block PLimit.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 201        |
| CPU cycles     | 53         | 53         | ... | 496        |
| Inputs         |            |            |     |            |
| In (DSP)       | 0          | 0          | ... | 0          |
| max (DSP)      | 1717986918 | 1717986918 | ... | 1717986918 |
| min (DSP)      | 322122547  | 322122547  | ... | 322122547  |
| Enable (DSP)   | 0          | 0          | ... | 1          |
| In             | 0          | 0          | ... | 0          |
| max            | 0.8        | 0.8        | ... | 0.8        |
| min            | 0.15       | 0.15       | ... | 0.15       |
| Enable         | 0          | 0          | ... | 1          |
| Parameters     |            |            |     |            |
| Kp             | 2          |            |     |            |
| Outputs        |            |            |     |            |
| Out            | 0          | 0          | ... | 0.15       |
| Exp. Out       | 0          | 0          | ... | 0.15       |
| Out (DSP)      | 0          | 0          | ... | 322122547  |
| Exp. Out (DSP) | 0          | 0          | ... | 322122547  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 53  |
| Max CPU cycles  | 503 |
| Avg CPU cycles  | 491 |

**Test case: Conversion test****OK**

Conversion test for Control block PLimit.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -11         | -10.389     | ... | 11         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1476395008 | -1394373063 | ... | 1476395008 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1476395008 | -1394373063 | ... | 1476395008 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PLimit.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Kp                    | -11         | -10.389     | ... | 11         |
| Controller parameters |             |             |     |            |
| sfrb1                 | 27          | 27          | ... | 27         |
| b1                    | -1476395008 | -1394373120 | ... | 1476395008 |
| Exp. sfrb1            | 27          | 27          | ... | 27         |
| Exp. b1               | -1476395008 | -1394373063 | ... | 1476395008 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+02$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 2903  |
| Max CPU cycles  | 10578 |
| Avg CPU cycles  | 8305  |

**Verification: PLimit Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block PLimit.

| Test results   |      |      |     |      |
|----------------|------|------|-----|------|
| Time step      | 1    | 2    | ... | 201  |
| CPU cycles     | 67   | 67   | ... | 86   |
| Inputs         |      |      |     |      |
| In (DSP)       | 0    | 0    | ... | 0    |
| max (DSP)      | 0.8  | 0.8  | ... | 0.8  |
| min (DSP)      | 0.15 | 0.15 | ... | 0.15 |
| Enable (DSP)   | 0    | 0    | ... | 1    |
| In             | 0    | 0    | ... | 0    |
| max            | 0.8  | 0.8  | ... | 0.8  |
| min            | 0.15 | 0.15 | ... | 0.15 |
| Enable         | 0    | 0    | ... | 1    |
| Parameters     |      |      |     |      |
| Kp             | 2    |      |     |      |
| Outputs        |      |      |     |      |
| Out            | 0    | 0    | ... | 0.15 |
| Exp. Out       | 0    | 0    | ... | 0.15 |
| Out (DSP)      | 0    | 0    | ... | 0.15 |
| Exp. Out (DSP) | 0    | 0    | ... | 0.15 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 9,3132e-09$ ( $\pm 20$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 67 |
| Max CPU cycles  | 86 |
| Avg CPU cycles  | 85 |

**Test case: Conversion test****OK**

Conversion test for Control block PLimit.



| Test results                 |     |         |     |    |
|------------------------------|-----|---------|-----|----|
| <b>Time step</b>             | 1   | 2       | ... | 37 |
| <i>Mask parameters</i>       |     |         |     |    |
| <b>Kp</b>                    | -11 | -10.389 | ... | 11 |
| <i>Controller parameters</i> |     |         |     |    |
| <b>b1</b>                    | -11 | -10.389 | ... | 11 |
| <b>Exp. b1</b>               | -11 | -10.389 | ... | 11 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PLimit.

| Test results                 |     |         |     |    |
|------------------------------|-----|---------|-----|----|
| <b>Time step</b>             | 1   | 2       | ... | 37 |
| <i>Mask parameters</i>       |     |         |     |    |
| <b>Kp</b>                    | -11 | -10.389 | ... | 11 |
| <i>Controller parameters</i> |     |         |     |    |
| <b>b1</b>                    | -11 | -10.389 | ... | 11 |
| <b>Exp. b1</b>               | -11 | -10.389 | ... | 11 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 807 |
| Max CPU cycles  | 818 |
| Avg CPU cycles  | 807 |

**Verification: PLimit Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block PLimit.

| Test results   |      |      |     |      |
|----------------|------|------|-----|------|
| Time step      | 1    | 2    | ... | 201  |
| CPU cycles     | 31   | 31   | ... | 61   |
| Inputs         |      |      |     |      |
| In (DSP)       | 0    | 0    | ... | 0    |
| max (DSP)      | 0.8  | 0.8  | ... | 0.8  |
| min (DSP)      | 0.15 | 0.15 | ... | 0.15 |
| Enable (DSP)   | 0    | 0    | ... | 1    |
| In             | 0    | 0    | ... | 0    |
| max            | 0.8  | 0.8  | ... | 0.8  |
| min            | 0.15 | 0.15 | ... | 0.15 |
| Enable         | 0    | 0    | ... | 1    |
| Parameters     |      |      |     |      |
| Kp             | 2    |      |     |      |
| Outputs        |      |      |     |      |
| Out            | 0    | 0    | ... | 0.15 |
| Exp. Out       | 0    | 0    | ... | 0.15 |
| Out (DSP)      | 0    | 0    | ... | 0.15 |
| Exp. Out (DSP) | 0    | 0    | ... | 0.15 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 9,3132e-09$ ( $\pm 20$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 61 |
| Avg CPU cycles  | 60 |

**Test case: Conversion test****OK**

Conversion test for Control block PLimit.

| Test results                 |     |         |     |    |
|------------------------------|-----|---------|-----|----|
| <b>Time step</b>             | 1   | 2       | ... | 37 |
| <i>Mask parameters</i>       |     |         |     |    |
| <b>Kp</b>                    | -11 | -10.389 | ... | 11 |
| <i>Controller parameters</i> |     |         |     |    |
| <b>b1</b>                    | -11 | -10.389 | ... | 11 |
| <b>Exp. b1</b>               | -11 | -10.389 | ... | 11 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PLimit.

| Test results                 |     |         |     |    |
|------------------------------|-----|---------|-----|----|
| <b>Time step</b>             | 1   | 2       | ... | 37 |
| <i>Mask parameters</i>       |     |         |     |    |
| <b>Kp</b>                    | -11 | -10.389 | ... | 11 |
| <i>Controller parameters</i> |     |         |     |    |
| <b>b1</b>                    | -11 | -10.389 | ... | 11 |
| <b>Exp. b1</b>               | -11 | -10.389 | ... | 11 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 397 |
| Max CPU cycles  | 397 |
| Avg CPU cycles  | 397 |

**Verification: PLimit Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block PLimit.

| Test results   |      |      |     |      |
|----------------|------|------|-----|------|
| Time step      | 1    | 2    | ... | 201  |
| CPU cycles     | 76   | 76   | ... | 98   |
| Inputs         |      |      |     |      |
| In (DSP)       | 0    | 0    | ... | 0    |
| max (DSP)      | 0.8  | 0.8  | ... | 0.8  |
| min (DSP)      | 0.15 | 0.15 | ... | 0.15 |
| Enable (DSP)   | 0    | 0    | ... | 1    |
| In             | 0    | 0    | ... | 0    |
| max            | 0.8  | 0.8  | ... | 0.8  |
| min            | 0.15 | 0.15 | ... | 0.15 |
| Enable         | 0    | 0    | ... | 1    |
| Parameters     |      |      |     |      |
| Kp             | 2    |      |     |      |
| Outputs        |      |      |     |      |
| Out            | 0    | 0    | ... | 0.15 |
| Exp. Out       | 0    | 0    | ... | 0.15 |
| Out (DSP)      | 0    | 0    | ... | 0.15 |
| Exp. Out (DSP) | 0    | 0    | ... | 0.15 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 9,3132e-09$ ( $\pm 20$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 76 |
| Max CPU cycles  | 98 |
| Avg CPU cycles  | 97 |

**Test case: Conversion test****OK**

Conversion test for Control block PLimit.

| Test results                 |     |         |     |    |
|------------------------------|-----|---------|-----|----|
| <b>Time step</b>             | 1   | 2       | ... | 37 |
| <i>Mask parameters</i>       |     |         |     |    |
| <b>Kp</b>                    | -11 | -10.389 | ... | 11 |
| <i>Controller parameters</i> |     |         |     |    |
| <b>b1</b>                    | -11 | -10.389 | ... | 11 |
| <b>Exp. b1</b>               | -11 | -10.389 | ... | 11 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PLimit.

| Test results                 |     |         |     |    |
|------------------------------|-----|---------|-----|----|
| <b>Time step</b>             | 1   | 2       | ... | 37 |
| <i>Mask parameters</i>       |     |         |     |    |
| <b>Kp</b>                    | -11 | -10.389 | ... | 11 |
| <i>Controller parameters</i> |     |         |     |    |
| <b>b1</b>                    | -11 | -10.389 | ... | 11 |
| <b>Exp. b1</b>               | -11 | -10.389 | ... | 11 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 470 |
| Max CPU cycles  | 470 |
| Avg CPU cycles  | 470 |

**Verification: PLimit Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block PLimit.

| Test results   |      |      |     |      |
|----------------|------|------|-----|------|
| Time step      | 1    | 2    | ... | 201  |
| CPU cycles     | 64   | 64   | ... | 352  |
| Inputs         |      |      |     |      |
| In (DSP)       | 0    | 0    | ... | 0    |
| max (DSP)      | 0.8  | 0.8  | ... | 0.8  |
| min (DSP)      | 0.15 | 0.15 | ... | 0.15 |
| Enable (DSP)   | 0    | 0    | ... | 1    |
| In             | 0    | 0    | ... | 0    |
| max            | 0.8  | 0.8  | ... | 0.8  |
| min            | 0.15 | 0.15 | ... | 0.15 |
| Enable         | 0    | 0    | ... | 1    |
| Parameters     |      |      |     |      |
| Kp             | 2    |      |     |      |
| Outputs        |      |      |     |      |
| Out            | 0    | 0    | ... | 0.15 |
| Exp. Out       | 0    | 0    | ... | 0.15 |
| Out (DSP)      | 0    | 0    | ... | 0.15 |
| Exp. Out (DSP) | 0    | 0    | ... | 0.15 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 9,3132e-09$ ( $\pm 20$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 64  |
| Max CPU cycles  | 491 |
| Avg CPU cycles  | 399 |

**Test case: Conversion test****OK**

Conversion test for Control block PLimit.

| Test results                 |     |         |     |    |
|------------------------------|-----|---------|-----|----|
| <b>Time step</b>             | 1   | 2       | ... | 37 |
| <i>Mask parameters</i>       |     |         |     |    |
| <b>Kp</b>                    | -11 | -10.389 | ... | 11 |
| <i>Controller parameters</i> |     |         |     |    |
| <b>b1</b>                    | -11 | -10.389 | ... | 11 |
| <b>Exp. b1</b>               | -11 | -10.389 | ... | 11 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PLimit.

| Test results                 |     |         |     |    |
|------------------------------|-----|---------|-----|----|
| <b>Time step</b>             | 1   | 2       | ... | 37 |
| <i>Mask parameters</i>       |     |         |     |    |
| <b>Kp</b>                    | -11 | -10.389 | ... | 11 |
| <i>Controller parameters</i> |     |         |     |    |
| <b>b1</b>                    | -11 | -10.389 | ... | 11 |
| <b>Exp. b1</b>               | -11 | -10.389 | ... | 11 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 667 |
| Max CPU cycles  | 757 |
| Avg CPU cycles  | 695 |

**Verification: PLimit Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block PLimit.

| Test results   |      |      |     |      |
|----------------|------|------|-----|------|
| Time step      | 1    | 2    | ... | 201  |
| CPU cycles     | 30   | 30   | ... | 170  |
| Inputs         |      |      |     |      |
| In (DSP)       | 0    | 0    | ... | 0    |
| max (DSP)      | 0.8  | 0.8  | ... | 0.8  |
| min (DSP)      | 0.15 | 0.15 | ... | 0.15 |
| Enable (DSP)   | 0    | 0    | ... | 1    |
| In             | 0    | 0    | ... | 0    |
| max            | 0.8  | 0.8  | ... | 0.8  |
| min            | 0.15 | 0.15 | ... | 0.15 |
| Enable         | 0    | 0    | ... | 1    |
| Parameters     |      |      |     |      |
| Kp             | 2    |      |     |      |
| Outputs        |      |      |     |      |
| Out            | 0    | 0    | ... | 0.15 |
| Exp. Out       | 0    | 0    | ... | 0.15 |
| Out (DSP)      | 0    | 0    | ... | 0.15 |
| Exp. Out (DSP) | 0    | 0    | ... | 0.15 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 9,3132e-09$ ( $\pm 20$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 30  |
| Max CPU cycles  | 190 |
| Avg CPU cycles  | 181 |

**Test case: Conversion test****OK**

Conversion test for Control block PLimit.



| Test results                 |     |         |     |    |
|------------------------------|-----|---------|-----|----|
| <b>Time step</b>             | 1   | 2       | ... | 37 |
| <i>Mask parameters</i>       |     |         |     |    |
| <b>Kp</b>                    | -11 | -10.389 | ... | 11 |
| <i>Controller parameters</i> |     |         |     |    |
| <b>b1</b>                    | -11 | -10.389 | ... | 11 |
| <b>Exp. b1</b>               | -11 | -10.389 | ... | 11 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PLimit.

| Test results                 |     |         |     |    |
|------------------------------|-----|---------|-----|----|
| <b>Time step</b>             | 1   | 2       | ... | 37 |
| <i>Mask parameters</i>       |     |         |     |    |
| <b>Kp</b>                    | -11 | -10.389 | ... | 11 |
| <i>Controller parameters</i> |     |         |     |    |
| <b>b1</b>                    | -11 | -10.389 | ... | 11 |
| <b>Exp. b1</b>               | -11 | -10.389 | ... | 11 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 277 |
| Max CPU cycles  | 278 |
| Avg CPU cycles  | 277 |

**Verification: PLimit Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block PLimit.

| Test results   |      |      |     |      |
|----------------|------|------|-----|------|
| Time step      | 1    | 2    | ... | 201  |
| CPU cycles     | 73   | 59   | ... | 81   |
| Inputs         |      |      |     |      |
| In (DSP)       | 0    | 0    | ... | 0    |
| max (DSP)      | 0.8  | 0.8  | ... | 0.8  |
| min (DSP)      | 0.15 | 0.15 | ... | 0.15 |
| Enable (DSP)   | 0    | 0    | ... | 1    |
| In             | 0    | 0    | ... | 0    |
| max            | 0.8  | 0.8  | ... | 0.8  |
| min            | 0.15 | 0.15 | ... | 0.15 |
| Enable         | 0    | 0    | ... | 1    |
| Parameters     |      |      |     |      |
| Kp             | 2    |      |     |      |
| Outputs        |      |      |     |      |
| Out            | 0    | 0    | ... | 0.15 |
| Exp. Out       | 0    | 0    | ... | 0.15 |
| Out (DSP)      | 0    | 0    | ... | 0.15 |
| Exp. Out (DSP) | 0    | 0    | ... | 0.15 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 9,3132e-09$ ( $\pm 20$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 81 |
| Avg CPU cycles  | 80 |

**Test case: Conversion test****OK**

Conversion test for Control block PLimit.

| Test results                 |     |         |     |    |
|------------------------------|-----|---------|-----|----|
| <b>Time step</b>             | 1   | 2       | ... | 37 |
| <i>Mask parameters</i>       |     |         |     |    |
| <b>Kp</b>                    | -11 | -10.389 | ... | 11 |
| <i>Controller parameters</i> |     |         |     |    |
| <b>b1</b>                    | -11 | -10.389 | ... | 11 |
| <b>Exp. b1</b>               | -11 | -10.389 | ... | 11 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PLimit.

| Test results                 |     |         |     |    |
|------------------------------|-----|---------|-----|----|
| <b>Time step</b>             | 1   | 2       | ... | 37 |
| <i>Mask parameters</i>       |     |         |     |    |
| <b>Kp</b>                    | -11 | -10.389 | ... | 11 |
| <i>Controller parameters</i> |     |         |     |    |
| <b>b1</b>                    | -11 | -10.389 | ... | 11 |
| <b>Exp. b1</b>               | -11 | -10.389 | ... | 11 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 384 |
| Max CPU cycles  | 416 |
| Avg CPU cycles  | 385 |

**Verification: PLimit Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block PLimit.

| Test results   |      |      |     |      |
|----------------|------|------|-----|------|
| Time step      | 1    | 2    | ... | 201  |
| CPU cycles     | 62   | 62   | ... | 78   |
| Inputs         |      |      |     |      |
| In (DSP)       | 0    | 0    | ... | 0    |
| max (DSP)      | 0.8  | 0.8  | ... | 0.8  |
| min (DSP)      | 0.15 | 0.15 | ... | 0.15 |
| Enable (DSP)   | 0    | 0    | ... | 1    |
| In             | 0    | 0    | ... | 0    |
| max            | 0.8  | 0.8  | ... | 0.8  |
| min            | 0.15 | 0.15 | ... | 0.15 |
| Enable         | 0    | 0    | ... | 1    |
| Parameters     |      |      |     |      |
| Kp             | 2    |      |     |      |
| Outputs        |      |      |     |      |
| Out            | 0    | 0    | ... | 0.15 |
| Exp. Out       | 0    | 0    | ... | 0.15 |
| Out (DSP)      | 0    | 0    | ... | 0.15 |
| Exp. Out (DSP) | 0    | 0    | ... | 0.15 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 9,3132e-09$ ( $\pm 20$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 78 |
| Avg CPU cycles  | 77 |

**Test case: Conversion test****OK**

Conversion test for Control block PLimit.

| Test results                 |     |         |     |    |
|------------------------------|-----|---------|-----|----|
| <b>Time step</b>             | 1   | 2       | ... | 37 |
| <i>Mask parameters</i>       |     |         |     |    |
| <b>Kp</b>                    | -11 | -10.389 | ... | 11 |
| <i>Controller parameters</i> |     |         |     |    |
| <b>b1</b>                    | -11 | -10.389 | ... | 11 |
| <b>Exp. b1</b>               | -11 | -10.389 | ... | 11 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PLimit.

| Test results                 |     |         |     |    |
|------------------------------|-----|---------|-----|----|
| <b>Time step</b>             | 1   | 2       | ... | 37 |
| <i>Mask parameters</i>       |     |         |     |    |
| <b>Kp</b>                    | -11 | -10.389 | ... | 11 |
| <i>Controller parameters</i> |     |         |     |    |
| <b>b1</b>                    | -11 | -10.389 | ... | 11 |
| <b>Exp. b1</b>               | -11 | -10.389 | ... | 11 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 653 |
| Max CPU cycles  | 664 |
| Avg CPU cycles  | 653 |

**Verification: PLimit Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block PLimit.

| Test results   |      |      |     |      |
|----------------|------|------|-----|------|
| Time step      | 1    | 2    | ... | 201  |
| CPU cycles     | 55   | 55   | ... | 386  |
| Inputs         |      |      |     |      |
| In (DSP)       | 0    | 0    | ... | 0    |
| max (DSP)      | 0.8  | 0.8  | ... | 0.8  |
| min (DSP)      | 0.15 | 0.15 | ... | 0.15 |
| Enable (DSP)   | 0    | 0    | ... | 1    |
| In             | 0    | 0    | ... | 0    |
| max            | 0.8  | 0.8  | ... | 0.8  |
| min            | 0.15 | 0.15 | ... | 0.15 |
| Enable         | 0    | 0    | ... | 1    |
| Parameters     |      |      |     |      |
| Kp             | 2    |      |     |      |
| Outputs        |      |      |     |      |
| Out            | 0    | 0    | ... | 0.15 |
| Exp. Out       | 0    | 0    | ... | 0.15 |
| Out (DSP)      | 0    | 0    | ... | 0.15 |
| Exp. Out (DSP) | 0    | 0    | ... | 0.15 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 9,3132e-09$ ( $\pm 20$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 55  |
| Max CPU cycles  | 428 |
| Avg CPU cycles  | 409 |

**Test case: Conversion test****OK**

Conversion test for Control block PLimit.

| Test results                 |     |         |     |    |
|------------------------------|-----|---------|-----|----|
| <b>Time step</b>             | 1   | 2       | ... | 37 |
| <i>Mask parameters</i>       |     |         |     |    |
| <b>Kp</b>                    | -11 | -10.389 | ... | 11 |
| <i>Controller parameters</i> |     |         |     |    |
| <b>b1</b>                    | -11 | -10.389 | ... | 11 |
| <b>Exp. b1</b>               | -11 | -10.389 | ... | 11 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block PLimit.


| Test results                 |     |         |     |    |
|------------------------------|-----|---------|-----|----|
| <b>Time step</b>             | 1   | 2       | ... | 37 |
| <i>Mask parameters</i>       |     |         |     |    |
| <b>Kp</b>                    | -11 | -10.389 | ... | 11 |
| <i>Controller parameters</i> |     |         |     |    |
| <b>b1</b>                    | -11 | -10.389 | ... | 11 |
| <b>Exp. b1</b>               | -11 | -10.389 | ... | 11 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b1  | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 515 |
| Max CPU cycles  | 860 |
| Avg CPU cycles  | 848 |

## Block: PT1

---



First order low pass:

$$G(s) = V/(s/w + 1)$$

| Inports |             |
|---------|-------------|
| In      | Input In(k) |

| Outports |               |
|----------|---------------|
| Out      | Output Out(k) |

| Mask Parameters |    |                                                                 |
|-----------------|----|-----------------------------------------------------------------|
| Name            | ID | Description                                                     |
| V               | 1  | Gain                                                            |
| fc              | 2  | Cut off frequency of low pass filter                            |
| ts_fact         | 3  | Multiplication factor of base sampling time (in integer format) |
| method          | 4  | Discretization method                                           |

### Description:

Due to limited value range in the 8 bit fixed point implementation rather high deviations from expected output values may occur.

**Developer note:** The source code of block *TF1* is used.

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | int8 |



| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: PT1 FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block PT1.

| Test results   |     |    |    |    |     |        |
|----------------|-----|----|----|----|-----|--------|
| Time step      | 1   | 2  | 3  | 4  | ... | 105    |
| CPU cycles     | 88  | 88 | 88 | 88 | ... | 88     |
| Inputs         |     |    |    |    |     |        |
| In (DSP)       | 0   | 0  | 0  | 0  | ... | -9830  |
| In             | 0   | 0  | 0  | 0  | ... | -0.3   |
| Parameters     |     |    |    |    |     |        |
| V              | 1.1 |    |    |    |     |        |
| fc             | 230 |    |    |    |     |        |
| ts_fact        | 1   |    |    |    |     |        |
| method         | zoh |    |    |    |     |        |
| Outputs        |     |    |    |    |     |        |
| Out            | 0   | 0  | 0  | 0  | ... | -0.329 |
| Exp. Out       | 0   | 0  | 0  | 0  | ... | -0.329 |
| Out (DSP)      | 0   | 0  | 0  | 0  | ... | -10776 |
| Exp. Out (DSP) | 0   | 0  | 0  | 0  | ... | -10780 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,5259e-04$ ( $\pm 5$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 88 |
| Max CPU cycles  | 88 |
| Avg CPU cycles  | 88 |

**Verification: PT1 FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block PT1.

| Test results   |     |    |    |    |     |        |
|----------------|-----|----|----|----|-----|--------|
| Time step      | 1   | 2  | 3  | 4  | ... | 105    |
| CPU cycles     | 69  | 69 | 69 | 69 | ... | 69     |
| Inputs         |     |    |    |    |     |        |
| In (DSP)       | 0   | 0  | 0  | 0  | ... | -9830  |
| In             | 0   | 0  | 0  | 0  | ... | -0.3   |
| Parameters     |     |    |    |    |     |        |
| V              | 1.1 |    |    |    |     |        |
| fc             | 230 |    |    |    |     |        |
| ts_fact        | 1   |    |    |    |     |        |
| method         | zoh |    |    |    |     |        |
| Outputs        |     |    |    |    |     |        |
| Out            | 0   | 0  | 0  | 0  | ... | -0.329 |
| Exp. Out       | 0   | 0  | 0  | 0  | ... | -0.329 |
| Out (DSP)      | 0   | 0  | 0  | 0  | ... | -10776 |
| Exp. Out (DSP) | 0   | 0  | 0  | 0  | ... | -10780 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}04$ ( $\pm 5$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 69 |
| Max CPU cycles  | 69 |
| Avg CPU cycles  | 69 |

**Verification: PT1 FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block PT1.

| Test results   |     |     |     |     |     |        |
|----------------|-----|-----|-----|-----|-----|--------|
| Time step      | 1   | 2   | 3   | 4   | ... | 105    |
| CPU cycles     | 104 | 104 | 104 | 104 | ... | 104    |
| Inputs         |     |     |     |     |     |        |
| In (DSP)       | 0   | 0   | 0   | 0   | ... | -9830  |
| In             | 0   | 0   | 0   | 0   | ... | -0.3   |
| Parameters     |     |     |     |     |     |        |
| V              | 1.1 |     |     |     |     |        |
| fc             | 230 |     |     |     |     |        |
| ts_fact        | 1   |     |     |     |     |        |
| method         | zoh |     |     |     |     |        |
| Outputs        |     |     |     |     |     |        |
| Out            | 0   | 0   | 0   | 0   | ... | -0.329 |
| Exp. Out       | 0   | 0   | 0   | 0   | ... | -0.329 |
| Out (DSP)      | 0   | 0   | 0   | 0   | ... | -10776 |
| Exp. Out (DSP) | 0   | 0   | 0   | 0   | ... | -10780 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,5259e-04$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 104 |
| Max CPU cycles  | 104 |
| Avg CPU cycles  | 104 |

**Verification: PT1 FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block PT1.

| Test results   |     |    |    |    |     |        |
|----------------|-----|----|----|----|-----|--------|
| Time step      | 1   | 2  | 3  | 4  | ... | 105    |
| CPU cycles     | 96  | 96 | 96 | 96 | ... | 96     |
| Inputs         |     |    |    |    |     |        |
| In (DSP)       | 0   | 0  | 0  | 0  | ... | -9830  |
| In             | 0   | 0  | 0  | 0  | ... | -0.3   |
| Parameters     |     |    |    |    |     |        |
| V              | 1.1 |    |    |    |     |        |
| fc             | 230 |    |    |    |     |        |
| ts_fact        | 1   |    |    |    |     |        |
| method         | zoh |    |    |    |     |        |
| Outputs        |     |    |    |    |     |        |
| Out            | 0   | 0  | 0  | 0  | ... | -0.329 |
| Exp. Out       | 0   | 0  | 0  | 0  | ... | -0.329 |
| Out (DSP)      | 0   | 0  | 0  | 0  | ... | -10776 |
| Exp. Out (DSP) | 0   | 0  | 0  | 0  | ... | -10780 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}04$ ( $\pm 5$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 96 |
| Max CPU cycles  | 96 |
| Avg CPU cycles  | 96 |

**Verification: PT1 FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block PT1.

| Test results   |     |    |    |    |     |        |
|----------------|-----|----|----|----|-----|--------|
| Time step      | 1   | 2  | 3  | 4  | ... | 105    |
| CPU cycles     | 59  | 59 | 59 | 59 | ... | 59     |
| Inputs         |     |    |    |    |     |        |
| In (DSP)       | 0   | 0  | 0  | 0  | ... | -9830  |
| In             | 0   | 0  | 0  | 0  | ... | -0.3   |
| Parameters     |     |    |    |    |     |        |
| V              | 1.1 |    |    |    |     |        |
| fc             | 230 |    |    |    |     |        |
| ts_fact        | 1   |    |    |    |     |        |
| method         | zoh |    |    |    |     |        |
| Outputs        |     |    |    |    |     |        |
| Out            | 0   | 0  | 0  | 0  | ... | -0.329 |
| Exp. Out       | 0   | 0  | 0  | 0  | ... | -0.329 |
| Out (DSP)      | 0   | 0  | 0  | 0  | ... | -10776 |
| Exp. Out (DSP) | 0   | 0  | 0  | 0  | ... | -10780 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}04$ ( $\pm 5$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 59 |
| Avg CPU cycles  | 59 |

**Verification: PT1 FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block PT1.

| Test results   |     |    |    |    |     |        |
|----------------|-----|----|----|----|-----|--------|
| Time step      | 1   | 2  | 3  | 4  | ... | 105    |
| CPU cycles     | 118 | 96 | 96 | 96 | ... | 96     |
| Inputs         |     |    |    |    |     |        |
| In (DSP)       | 0   | 0  | 0  | 0  | ... | -9830  |
| In             | 0   | 0  | 0  | 0  | ... | -0.3   |
| Parameters     |     |    |    |    |     |        |
| V              | 1.1 |    |    |    |     |        |
| fc             | 230 |    |    |    |     |        |
| ts_fact        | 1   |    |    |    |     |        |
| method         | zoh |    |    |    |     |        |
| Outputs        |     |    |    |    |     |        |
| Out            | 0   | 0  | 0  | 0  | ... | -0.329 |
| Exp. Out       | 0   | 0  | 0  | 0  | ... | -0.329 |
| Out (DSP)      | 0   | 0  | 0  | 0  | ... | -10776 |
| Exp. Out (DSP) | 0   | 0  | 0  | 0  | ... | -10780 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,5259e-04$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 96  |
| Max CPU cycles  | 118 |
| Avg CPU cycles  | 96  |



**Verification: PT1 FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block PT1.

| Test results   |     |    |    |    |     |        |
|----------------|-----|----|----|----|-----|--------|
| Time step      | 1   | 2  | 3  | 4  | ... | 105    |
| CPU cycles     | 85  | 85 | 85 | 85 | ... | 85     |
| Inputs         |     |    |    |    |     |        |
| In (DSP)       | 0   | 0  | 0  | 0  | ... | -9830  |
| In             | 0   | 0  | 0  | 0  | ... | -0.3   |
| Parameters     |     |    |    |    |     |        |
| V              | 1.1 |    |    |    |     |        |
| fc             | 230 |    |    |    |     |        |
| ts_fact        | 1   |    |    |    |     |        |
| method         | zoh |    |    |    |     |        |
| Outputs        |     |    |    |    |     |        |
| Out            | 0   | 0  | 0  | 0  | ... | -0.329 |
| Exp. Out       | 0   | 0  | 0  | 0  | ... | -0.329 |
| Out (DSP)      | 0   | 0  | 0  | 0  | ... | -10776 |
| Exp. Out (DSP) | 0   | 0  | 0  | 0  | ... | -10780 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}04$ ( $\pm 5$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 85 |
| Max CPU cycles  | 85 |
| Avg CPU cycles  | 85 |

**Verification: PT1 FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block PT1.

| Test results   |     |    |    |    |     |        |
|----------------|-----|----|----|----|-----|--------|
| Time step      | 1   | 2  | 3  | 4  | ... | 105    |
| CPU cycles     | 91  | 91 | 91 | 91 | ... | 91     |
| Inputs         |     |    |    |    |     |        |
| In (DSP)       | 0   | 0  | 0  | 0  | ... | -9830  |
| In             | 0   | 0  | 0  | 0  | ... | -0.3   |
| Parameters     |     |    |    |    |     |        |
| V              | 1.1 |    |    |    |     |        |
| fc             | 230 |    |    |    |     |        |
| ts_fact        | 1   |    |    |    |     |        |
| method         | zoh |    |    |    |     |        |
| Outputs        |     |    |    |    |     |        |
| Out            | 0   | 0  | 0  | 0  | ... | -0.329 |
| Exp. Out       | 0   | 0  | 0  | 0  | ... | -0.329 |
| Out (DSP)      | 0   | 0  | 0  | 0  | ... | -10776 |
| Exp. Out (DSP) | 0   | 0  | 0  | 0  | ... | -10780 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,5259e-04$ ( $\pm 5$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 91 |
| Max CPU cycles  | 91 |
| Avg CPU cycles  | 91 |

**Verification: PT1 FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block PT1.

| Test results   |     |     |     |            |
|----------------|-----|-----|-----|------------|
| Time step      | 1   | 2   | ... | 105        |
| CPU cycles     | 221 | 221 | ... | 221        |
| Inputs         |     |     |     |            |
| In (DSP)       | 0   | 0   | ... | -644245094 |
| In             | 0   | 0   | ... | -0.3       |
| Parameters     |     |     |     |            |
| V              | 1.1 |     |     |            |
| fc             | 230 |     |     |            |
| ts_fact        | 1   |     |     |            |
| method         | zoh |     |     |            |
| Outputs        |     |     |     |            |
| Out            | 0   | 0   | ... | -0.329     |
| Exp. Out       | 0   | 0   | ... | -0.329     |
| Out (DSP)      | 0   | 0   | ... | -706485960 |
| Exp. Out (DSP) | 0   | 0   | ... | -706485964 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 221 |
| Max CPU cycles  | 221 |
| Avg CPU cycles  | 221 |

**Verification: PT1 FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block PT1.

| Test results   |     |     |     |            |
|----------------|-----|-----|-----|------------|
| Time step      | 1   | 2   | ... | 105        |
| CPU cycles     | 121 | 121 | ... | 121        |
| Inputs         |     |     |     |            |
| In (DSP)       | 0   | 0   | ... | -644245094 |
| In             | 0   | 0   | ... | -0.3       |
| Parameters     |     |     |     |            |
| V              | 1.1 |     |     |            |
| fc             | 230 |     |     |            |
| ts_fact        | 1   |     |     |            |
| method         | zoh |     |     |            |
| Outputs        |     |     |     |            |
| Out            | 0   | 0   | ... | -0.329     |
| Exp. Out       | 0   | 0   | ... | -0.329     |
| Out (DSP)      | 0   | 0   | ... | -706485960 |
| Exp. Out (DSP) | 0   | 0   | ... | -706485964 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 121 |
| Max CPU cycles  | 121 |
| Avg CPU cycles  | 121 |

**Verification: PT1 FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block PT1.

| Test results   |     |     |     |            |
|----------------|-----|-----|-----|------------|
| Time step      | 1   | 2   | ... | 105        |
| CPU cycles     | 142 | 142 | ... | 142        |
| Inputs         |     |     |     |            |
| In (DSP)       | 0   | 0   | ... | -644245094 |
| In             | 0   | 0   | ... | -0.3       |
| Parameters     |     |     |     |            |
| V              | 1.1 |     |     |            |
| fc             | 230 |     |     |            |
| ts_fact        | 1   |     |     |            |
| method         | zoh |     |     |            |
| Outputs        |     |     |     |            |
| Out            | 0   | 0   | ... | -0.329     |
| Exp. Out       | 0   | 0   | ... | -0.329     |
| Out (DSP)      | 0   | 0   | ... | -706485960 |
| Exp. Out (DSP) | 0   | 0   | ... | -706485964 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 142 |
| Max CPU cycles  | 142 |
| Avg CPU cycles  | 142 |

**Verification: PT1 FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block PT1.

| Test results   |     |     |     |            |
|----------------|-----|-----|-----|------------|
| Time step      | 1   | 2   | ... | 105        |
| CPU cycles     | 373 | 373 | ... | 380        |
| Inputs         |     |     |     |            |
| In (DSP)       | 0   | 0   | ... | -644245094 |
| In             | 0   | 0   | ... | -0.3       |
| Parameters     |     |     |     |            |
| V              | 1.1 |     |     |            |
| fc             | 230 |     |     |            |
| ts_fact        | 1   |     |     |            |
| method         | zoh |     |     |            |
| Outputs        |     |     |     |            |
| Out            | 0   | 0   | ... | -0.329     |
| Exp. Out       | 0   | 0   | ... | -0.329     |
| Out (DSP)      | 0   | 0   | ... | -706485960 |
| Exp. Out (DSP) | 0   | 0   | ... | -706485964 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 373 |
| Max CPU cycles  | 380 |
| Avg CPU cycles  | 375 |

**Verification: PT1 FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block PT1.

| Test results   |     |    |     |            |
|----------------|-----|----|-----|------------|
| Time step      | 1   | 2  | ... | 105        |
| CPU cycles     | 87  | 87 | ... | 89         |
| Inputs         |     |    |     |            |
| In (DSP)       | 0   | 0  | ... | -644245094 |
| In             | 0   | 0  | ... | -0.3       |
| Parameters     |     |    |     |            |
| V              | 1.1 |    |     |            |
| fc             | 230 |    |     |            |
| ts_fact        | 1   |    |     |            |
| method         | zoh |    |     |            |
| Outputs        |     |    |     |            |
| Out            | 0   | 0  | ... | -0.329     |
| Exp. Out       | 0   | 0  | ... | -0.329     |
| Out (DSP)      | 0   | 0  | ... | -706485960 |
| Exp. Out (DSP) | 0   | 0  | ... | -706485964 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 87 |
| Max CPU cycles  | 89 |
| Avg CPU cycles  | 88 |

**Verification: PT1 FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block PT1.

| Test results   |     |     |     |            |
|----------------|-----|-----|-----|------------|
| Time step      | 1   | 2   | ... | 105        |
| CPU cycles     | 154 | 133 | ... | 133        |
| Inputs         |     |     |     |            |
| In (DSP)       | 0   | 0   | ... | -644245094 |
| In             | 0   | 0   | ... | -0.3       |
| Parameters     |     |     |     |            |
| V              | 1.1 |     |     |            |
| fc             | 230 |     |     |            |
| ts_fact        | 1   |     |     |            |
| method         | zoh |     |     |            |
| Outputs        |     |     |     |            |
| Out            | 0   | 0   | ... | -0.329     |
| Exp. Out       | 0   | 0   | ... | -0.329     |
| Out (DSP)      | 0   | 0   | ... | -706485960 |
| Exp. Out (DSP) | 0   | 0   | ... | -706485964 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 133 |
| Max CPU cycles  | 154 |
| Avg CPU cycles  | 133 |



**Verification: PT1 FIP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block PT1.

| Test results   |     |     |     |            |
|----------------|-----|-----|-----|------------|
| Time step      | 1   | 2   | ... | 105        |
| CPU cycles     | 188 | 188 | ... | 188        |
| Inputs         |     |     |     |            |
| In (DSP)       | 0   | 0   | ... | -644245094 |
| In             | 0   | 0   | ... | -0.3       |
| Parameters     |     |     |     |            |
| V              | 1.1 |     |     |            |
| fc             | 230 |     |     |            |
| ts_fact        | 1   |     |     |            |
| method         | zoh |     |     |            |
| Outputs        |     |     |     |            |
| Out            | 0   | 0   | ... | -0.329     |
| Exp. Out       | 0   | 0   | ... | -0.329     |
| Out (DSP)      | 0   | 0   | ... | -706485960 |
| Exp. Out (DSP) | 0   | 0   | ... | -706485964 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 188 |
| Max CPU cycles  | 188 |
| Avg CPU cycles  | 188 |

**Verification: PT1 FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block PT1.

| Test results   |      |      |     |            |
|----------------|------|------|-----|------------|
| Time step      | 1    | 2    | ... | 105        |
| CPU cycles     | 1038 | 1038 | ... | 1053       |
| Inputs         |      |      |     |            |
| In (DSP)       | 0    | 0    | ... | -644245094 |
| In             | 0    | 0    | ... | -0.3       |
| Parameters     |      |      |     |            |
| V              | 1.1  |      |     |            |
| fc             | 230  |      |     |            |
| ts_fact        | 1    |      |     |            |
| method         | zoh  |      |     |            |
| Outputs        |      |      |     |            |
| Out            | 0    | 0    | ... | -0.329     |
| Exp. Out       | 0    | 0    | ... | -0.329     |
| Out (DSP)      | 0    | 0    | ... | -706485960 |
| Exp. Out (DSP) | 0    | 0    | ... | -706485964 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1038 |
| Max CPU cycles  | 1053 |
| Avg CPU cycles  | 1044 |

## Block: TDSysystemO1

---

$$\begin{aligned} \mathbf{x}_{k+1} &= \mathbf{A} \mathbf{x}_k + \mathbf{B} u_k \\ y_k &= \mathbf{C} \mathbf{x}_k + \mathbf{D} u_k \end{aligned}$$

1st order time discrete system with one input and one output.

| Inports |          |
|---------|----------|
| In      | Input #1 |

| Outports |           |
|----------|-----------|
| Out      | Output #1 |

| Mask Parameters |    |                      |
|-----------------|----|----------------------|
| Name            | ID | Description          |
| A               | 1  | State matrix A       |
| B               | 2  | Input matrix B       |
| C               | 3  | Output matrix C      |
| D               | 4  | Feedthrough matrix D |

### Description:

Calculation:

$$\begin{aligned} x_{1,k+1} &= a_{1,1}x_{1,k} + b_{1,1}u_{1,k} \\ y_{1,k} &= c_{1,1}x_{1,k} + d_{1,1}u_{1,k} \end{aligned}$$

or short

$$\begin{aligned} \mathbf{x}_{k+1} &= \mathbf{A}\mathbf{x}_k + \mathbf{B}u_k \\ y_k &= \mathbf{C}\mathbf{x}_k + \mathbf{D}u_k \end{aligned}$$

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | int8 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: TDSys<sub>tem</sub>O1 FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**Inport test for Control block TDSys<sub>tem</sub>O1.

| Test results   |      |       |        |        |     |        |
|----------------|------|-------|--------|--------|-----|--------|
| Time step      | 1    | 2     | 3      | 4      | ... | 174    |
| CPU cycles     | 120  | 120   | 120    | 120    | ... | 120    |
| Inputs         |      |       |        |        |     |        |
| In (DSP)       | 0    | -3271 | -6510  | -9684  | ... | -19661 |
| In             | -0   | -0.1  | -0.199 | -0.296 | ... | -0.6   |
| Parameters     |      |       |        |        |     |        |
| A              | 0.7  |       |        |        |     |        |
| B              | 0.38 |       |        |        |     |        |
| C              | 0.33 |       |        |        |     |        |
| D              | 0.1  |       |        |        |     |        |
| Outputs        |      |       |        |        |     |        |
| Out            | 0    | -0.01 | -0.032 | -0.063 | ... | -0.311 |
| Exp. Out       | -0   | -0.01 | -0.032 | -0.063 | ... | -0.311 |
| Out (DSP)      | 0    | -328  | -1063  | -2073  | ... | -10187 |
| Exp. Out (DSP) | 0    | -327  | -1061  | -2072  | ... | -10184 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,2207\text{e-}04$ ( $\pm 4$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 116 |
| Max CPU cycles  | 120 |
| Avg CPU cycles  | 119 |

**Test case: Conversion test****OK**Conversion test for Control block TDSys<sub>tem</sub>O1.

| Test results                 |    |      |       |       |        |       |
|------------------------------|----|------|-------|-------|--------|-------|
| Time step                    | 1  | 2    | 3     | 4     | 5      | 6     |
| <i>Mask parameters</i>       |    |      |       |       |        |       |
| <b>A</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>B</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>C</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>D</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <i>Controller parameters</i> |    |      |       |       |        |       |
| <b>a11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>c11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>b11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>d11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>sfrd11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrb11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrb11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfra11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. a11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. c11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. b11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. d11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrb11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrb11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrb11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |

| Test settings    |             |
|------------------|-------------|
| Tolerance a11    | ±0,0000e+00 |
| Tolerance c11    | ±0,0000e+00 |
| Tolerance b11    | ±0,0000e+00 |
| Tolerance d11    | ±0,0000e+00 |
| Tolerance sfrd11 | ±0,0000e+00 |
| Tolerance sfrb11 | ±0,0000e+00 |
| Tolerance sfrb11 | ±0,0000e+00 |
| Tolerance sfrb11 | ±0,0000e+00 |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block TDSysTemO1.

| Test results                 |    |      |       |       |        |       |
|------------------------------|----|------|-------|-------|--------|-------|
| Time step                    | 1  | 2    | 3     | 4     | 5      | 6     |
| <i>Mask parameters</i>       |    |      |       |       |        |       |
| <b>A</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>B</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>C</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>D</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <i>Controller parameters</i> |    |      |       |       |        |       |
| <b>a11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>c11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>b11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>d11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>sfrd11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrc11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrb11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfra11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. a11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. c11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. b11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. d11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrc11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrb11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 1,0000e+00$ |
| Tolerance c11    | $\pm 1,0000e+00$ |
| Tolerance b11    | $\pm 1,0000e+00$ |
| Tolerance d11    | $\pm 1,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |
| Tolerance sfrc11 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 4250  |
| Max CPU cycles  | 12850 |
| Avg CPU cycles  | 6619  |



**Verification: TDSys<sub>tem</sub>O1 FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**Inport test for Control block TDSys<sub>tem</sub>O1.

| Test results   |      |       |        |        |     |        |
|----------------|------|-------|--------|--------|-----|--------|
| Time step      | 1    | 2     | 3      | 4      | ... | 174    |
| CPU cycles     | 85   | 85    | 85     | 85     | ... | 85     |
| Inputs         |      |       |        |        |     |        |
| In (DSP)       | 0    | -3271 | -6510  | -9684  | ... | -19661 |
| In             | -0   | -0.1  | -0.199 | -0.296 | ... | -0.6   |
| Parameters     |      |       |        |        |     |        |
| A              | 0.7  |       |        |        |     |        |
| B              | 0.38 |       |        |        |     |        |
| C              | 0.33 |       |        |        |     |        |
| D              | 0.1  |       |        |        |     |        |
| Outputs        |      |       |        |        |     |        |
| Out            | 0    | -0.01 | -0.032 | -0.063 | ... | -0.311 |
| Exp. Out       | -0   | -0.01 | -0.032 | -0.063 | ... | -0.311 |
| Out (DSP)      | 0    | -328  | -1063  | -2073  | ... | -10187 |
| Exp. Out (DSP) | 0    | -327  | -1061  | -2072  | ... | -10184 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,2207\text{e-}04$ ( $\pm 4$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 81 |
| Max CPU cycles  | 87 |
| Avg CPU cycles  | 84 |

**Test case: Conversion test****OK**Conversion test for Control block TDSys<sub>tem</sub>O1.

| Test results                 |    |      |       |       |        |       |
|------------------------------|----|------|-------|-------|--------|-------|
| Time step                    | 1  | 2    | 3     | 4     | 5      | 6     |
| <i>Mask parameters</i>       |    |      |       |       |        |       |
| <b>A</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>B</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>C</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>D</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <i>Controller parameters</i> |    |      |       |       |        |       |
| <b>a11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>c11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>b11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>d11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>sfrd11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrc11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrb11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfra11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. a11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. c11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. b11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. d11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrc11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrb11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |

| Test settings    |             |
|------------------|-------------|
| Tolerance a11    | ±0,0000e+00 |
| Tolerance c11    | ±0,0000e+00 |
| Tolerance b11    | ±0,0000e+00 |
| Tolerance d11    | ±0,0000e+00 |
| Tolerance sfrd11 | ±0,0000e+00 |
| Tolerance sfrc11 | ±0,0000e+00 |
| Tolerance sfrb11 | ±0,0000e+00 |
| Tolerance sfrd11 | ±0,0000e+00 |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block TDSysTemO1.

| Test results                 |    |      |       |       |        |       |
|------------------------------|----|------|-------|-------|--------|-------|
| Time step                    | 1  | 2    | 3     | 4     | 5      | 6     |
| <i>Mask parameters</i>       |    |      |       |       |        |       |
| <b>A</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>B</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>C</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>D</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <i>Controller parameters</i> |    |      |       |       |        |       |
| <b>a11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>c11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>b11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>d11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>sfrd11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrc11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrb11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfra11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. a11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. c11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. b11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. d11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrc11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrb11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 1,0000e+00$ |
| Tolerance c11    | $\pm 1,0000e+00$ |
| Tolerance b11    | $\pm 1,0000e+00$ |
| Tolerance d11    | $\pm 1,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |
| Tolerance sfrc11 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2179 |
| Max CPU cycles  | 7187 |
| Avg CPU cycles  | 3581 |

**Verification: TDSysmO1 FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block TDSysmO1.

| Test results   |      |       |        |        |     |        |
|----------------|------|-------|--------|--------|-----|--------|
| Time step      | 1    | 2     | 3      | 4      | ... | 174    |
| CPU cycles     | 120  | 120   | 120    | 120    | ... | 120    |
| Inputs         |      |       |        |        |     |        |
| In (DSP)       | 0    | -3271 | -6510  | -9684  | ... | -19661 |
| In             | -0   | -0.1  | -0.199 | -0.296 | ... | -0.6   |
| Parameters     |      |       |        |        |     |        |
| A              | 0.7  |       |        |        |     |        |
| B              | 0.38 |       |        |        |     |        |
| C              | 0.33 |       |        |        |     |        |
| D              | 0.1  |       |        |        |     |        |
| Outputs        |      |       |        |        |     |        |
| Out            | 0    | -0.01 | -0.032 | -0.063 | ... | -0.311 |
| Exp. Out       | -0   | -0.01 | -0.032 | -0.063 | ... | -0.311 |
| Out (DSP)      | 0    | -328  | -1063  | -2073  | ... | -10187 |
| Exp. Out (DSP) | 0    | -327  | -1061  | -2072  | ... | -10184 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,2207e-04$ ( $\pm 4$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 120 |
| Max CPU cycles  | 120 |
| Avg CPU cycles  | 120 |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysmO1.

| Test results                 |    |      |       |       |        |       |
|------------------------------|----|------|-------|-------|--------|-------|
| Time step                    | 1  | 2    | 3     | 4     | 5      | 6     |
| <i>Mask parameters</i>       |    |      |       |       |        |       |
| <b>A</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>B</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>C</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>D</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <i>Controller parameters</i> |    |      |       |       |        |       |
| <b>a11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>c11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>b11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>d11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>sfrd11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrc11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrb11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfra11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. a11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. c11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. b11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. d11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrc11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrb11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |

| Test settings    |             |
|------------------|-------------|
| Tolerance a11    | ±0,0000e+00 |
| Tolerance c11    | ±0,0000e+00 |
| Tolerance b11    | ±0,0000e+00 |
| Tolerance d11    | ±0,0000e+00 |
| Tolerance sfrd11 | ±0,0000e+00 |
| Tolerance sfrc11 | ±0,0000e+00 |
| Tolerance sfrb11 | ±0,0000e+00 |
| Tolerance sfrd11 | ±0,0000e+00 |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block TDSysTemO1.

| Test results                 |    |      |       |       |        |       |
|------------------------------|----|------|-------|-------|--------|-------|
| Time step                    | 1  | 2    | 3     | 4     | 5      | 6     |
| <i>Mask parameters</i>       |    |      |       |       |        |       |
| <b>A</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>B</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>C</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>D</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <i>Controller parameters</i> |    |      |       |       |        |       |
| <b>a11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>c11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>b11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>d11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>sfrd11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrc11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrb11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfra11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. a11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. c11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. b11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. d11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrc11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrb11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 1,0000e+00$ |
| Tolerance c11    | $\pm 1,0000e+00$ |
| Tolerance b11    | $\pm 1,0000e+00$ |
| Tolerance d11    | $\pm 1,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |
| Tolerance sfrc11 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2027 |
| Max CPU cycles  | 4070 |
| Avg CPU cycles  | 2554 |

**Verification: TDSysmO1 FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block TDSysmO1.

| Test results   |      |       |        |        |     |        |
|----------------|------|-------|--------|--------|-----|--------|
| Time step      | 1    | 2     | 3      | 4      | ... | 174    |
| CPU cycles     | 121  | 121   | 121    | 121    | ... | 121    |
| Inputs         |      |       |        |        |     |        |
| In (DSP)       | 0    | -3271 | -6510  | -9684  | ... | -19661 |
| In             | -0   | -0.1  | -0.199 | -0.296 | ... | -0.6   |
| Parameters     |      |       |        |        |     |        |
| A              | 0.7  |       |        |        |     |        |
| B              | 0.38 |       |        |        |     |        |
| C              | 0.33 |       |        |        |     |        |
| D              | 0.1  |       |        |        |     |        |
| Outputs        |      |       |        |        |     |        |
| Out            | 0    | -0.01 | -0.032 | -0.063 | ... | -0.311 |
| Exp. Out       | -0   | -0.01 | -0.032 | -0.063 | ... | -0.311 |
| Out (DSP)      | 0    | -328  | -1063  | -2073  | ... | -10187 |
| Exp. Out (DSP) | 0    | -327  | -1061  | -2072  | ... | -10184 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,2207e-04$ ( $\pm 4$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 120 |
| Max CPU cycles  | 122 |
| Avg CPU cycles  | 120 |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysmO1.

| Test results                 |    |      |       |       |        |       |
|------------------------------|----|------|-------|-------|--------|-------|
| Time step                    | 1  | 2    | 3     | 4     | 5      | 6     |
| <i>Mask parameters</i>       |    |      |       |       |        |       |
| <b>A</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>B</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>C</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>D</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <i>Controller parameters</i> |    |      |       |       |        |       |
| <b>a11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>c11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>b11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>d11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>sfrd11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrc11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrb11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfra11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. a11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. c11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. b11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. d11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrc11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrb11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 0,0000e+00$ |
| Tolerance c11    | $\pm 0,0000e+00$ |
| Tolerance b11    | $\pm 0,0000e+00$ |
| Tolerance d11    | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |
| Tolerance sfrc11 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block TDSysTemO1.



| Test results                 |    |      |       |       |        |       |
|------------------------------|----|------|-------|-------|--------|-------|
| Time step                    | 1  | 2    | 3     | 4     | 5      | 6     |
| <i>Mask parameters</i>       |    |      |       |       |        |       |
| <b>A</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>B</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>C</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>D</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <i>Controller parameters</i> |    |      |       |       |        |       |
| <b>a11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>c11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>b11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>d11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>sfrd11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrc11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrb11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfra11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. a11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. c11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. b11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. d11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrc11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrb11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 1,0000e+00$ |
| Tolerance c11    | $\pm 1,0000e+00$ |
| Tolerance b11    | $\pm 1,0000e+00$ |
| Tolerance d11    | $\pm 1,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |
| Tolerance sfrc11 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 5581  |
| Max CPU cycles  | 17193 |
| Avg CPU cycles  | 9328  |

**Verification: TDSys<sub>tem</sub>O1 FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**Inport test for Control block TDSys<sub>tem</sub>O1.

| Test results   |      |       |        |        |     |        |
|----------------|------|-------|--------|--------|-----|--------|
| Time step      | 1    | 2     | 3      | 4      | ... | 174    |
| CPU cycles     | 70   | 70    | 70     | 70     | ... | 70     |
| Inputs         |      |       |        |        |     |        |
| In (DSP)       | 0    | -3271 | -6510  | -9684  | ... | -19661 |
| In             | -0   | -0.1  | -0.199 | -0.296 | ... | -0.6   |
| Parameters     |      |       |        |        |     |        |
| A              | 0.7  |       |        |        |     |        |
| B              | 0.38 |       |        |        |     |        |
| C              | 0.33 |       |        |        |     |        |
| D              | 0.1  |       |        |        |     |        |
| Outputs        |      |       |        |        |     |        |
| Out            | 0    | -0.01 | -0.032 | -0.063 | ... | -0.311 |
| Exp. Out       | -0   | -0.01 | -0.032 | -0.063 | ... | -0.311 |
| Out (DSP)      | 0    | -328  | -1063  | -2073  | ... | -10187 |
| Exp. Out (DSP) | 0    | -327  | -1061  | -2072  | ... | -10184 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,2207e-04$ ( $\pm 4$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 70 |
| Max CPU cycles  | 70 |
| Avg CPU cycles  | 70 |

**Test case: Conversion test****OK**Conversion test for Control block TDSys<sub>tem</sub>O1.

| Test results                 |    |      |       |       |        |       |
|------------------------------|----|------|-------|-------|--------|-------|
| Time step                    | 1  | 2    | 3     | 4     | 5      | 6     |
| <i>Mask parameters</i>       |    |      |       |       |        |       |
| <b>A</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>B</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>C</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>D</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <i>Controller parameters</i> |    |      |       |       |        |       |
| <b>a11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>c11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>b11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>d11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>sfrd11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrc11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrb11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfra11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. a11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. c11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. b11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. d11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrc11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrb11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |

| Test settings    |             |
|------------------|-------------|
| Tolerance a11    | ±0,0000e+00 |
| Tolerance c11    | ±0,0000e+00 |
| Tolerance b11    | ±0,0000e+00 |
| Tolerance d11    | ±0,0000e+00 |
| Tolerance sfrd11 | ±0,0000e+00 |
| Tolerance sfrc11 | ±0,0000e+00 |
| Tolerance sfrb11 | ±0,0000e+00 |
| Tolerance sfrd11 | ±0,0000e+00 |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block TDSysTemO1.

| Test results                 |    |      |       |       |        |       |
|------------------------------|----|------|-------|-------|--------|-------|
| Time step                    | 1  | 2    | 3     | 4     | 5      | 6     |
| <i>Mask parameters</i>       |    |      |       |       |        |       |
| <b>A</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>B</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>C</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>D</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <i>Controller parameters</i> |    |      |       |       |        |       |
| <b>a11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>c11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>b11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>d11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>sfrd11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrc11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrb11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfra11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. a11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. c11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. b11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. d11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrc11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrb11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 1,0000e+00$ |
| Tolerance c11    | $\pm 1,0000e+00$ |
| Tolerance b11    | $\pm 1,0000e+00$ |
| Tolerance d11    | $\pm 1,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |
| Tolerance sfrc11 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2632 |
| Max CPU cycles  | 7292 |
| Avg CPU cycles  | 4019 |

**Verification: TDSysmO1 FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block TDSysmO1.

| Test results   |      |       |        |        |     |        |
|----------------|------|-------|--------|--------|-----|--------|
| Time step      | 1    | 2     | 3      | 4      | ... | 174    |
| CPU cycles     | 145  | 138   | 138    | 138    | ... | 138    |
| Inputs         |      |       |        |        |     |        |
| In (DSP)       | 0    | -3271 | -6510  | -9684  | ... | -19661 |
| In             | -0   | -0.1  | -0.199 | -0.296 | ... | -0.6   |
| Parameters     |      |       |        |        |     |        |
| A              | 0.7  |       |        |        |     |        |
| B              | 0.38 |       |        |        |     |        |
| C              | 0.33 |       |        |        |     |        |
| D              | 0.1  |       |        |        |     |        |
| Outputs        |      |       |        |        |     |        |
| Out            | 0    | -0.01 | -0.032 | -0.063 | ... | -0.311 |
| Exp. Out       | -0   | -0.01 | -0.032 | -0.063 | ... | -0.311 |
| Out (DSP)      | 0    | -328  | -1063  | -2073  | ... | -10187 |
| Exp. Out (DSP) | 0    | -327  | -1061  | -2072  | ... | -10184 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,2207e-04$ ( $\pm 4$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 138 |
| Max CPU cycles  | 145 |
| Avg CPU cycles  | 138 |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysmO1.

| Test results                 |    |      |       |       |        |       |
|------------------------------|----|------|-------|-------|--------|-------|
| Time step                    | 1  | 2    | 3     | 4     | 5      | 6     |
| <i>Mask parameters</i>       |    |      |       |       |        |       |
| <b>A</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>B</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>C</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>D</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <i>Controller parameters</i> |    |      |       |       |        |       |
| <b>a11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>c11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>b11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>d11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>sfrd11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrc11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrb11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfra11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. a11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. c11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. b11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. d11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrc11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrb11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |

| Test settings    |             |
|------------------|-------------|
| Tolerance a11    | ±0,0000e+00 |
| Tolerance c11    | ±0,0000e+00 |
| Tolerance b11    | ±0,0000e+00 |
| Tolerance d11    | ±0,0000e+00 |
| Tolerance sfrd11 | ±0,0000e+00 |
| Tolerance sfrc11 | ±0,0000e+00 |
| Tolerance sfrb11 | ±0,0000e+00 |
| Tolerance sfrd11 | ±0,0000e+00 |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block TDSysTemO1.

| Test results                 |    |      |       |       |        |       |
|------------------------------|----|------|-------|-------|--------|-------|
| Time step                    | 1  | 2    | 3     | 4     | 5      | 6     |
| <i>Mask parameters</i>       |    |      |       |       |        |       |
| <b>A</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>B</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>C</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>D</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <i>Controller parameters</i> |    |      |       |       |        |       |
| <b>a11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>c11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>b11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>d11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>sfrd11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrc11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrb11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfra11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. a11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. c11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. b11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. d11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrc11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrb11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 1,0000e+00$ |
| Tolerance c11    | $\pm 1,0000e+00$ |
| Tolerance b11    | $\pm 1,0000e+00$ |
| Tolerance d11    | $\pm 1,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |
| Tolerance sfrc11 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1698 |
| Max CPU cycles  | 3646 |
| Avg CPU cycles  | 2247 |

**Verification: TDSysmO1 FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block TDSysmO1.

| Test results   |      |       |        |        |     |        |
|----------------|------|-------|--------|--------|-----|--------|
| Time step      | 1    | 2     | 3      | 4      | ... | 174    |
| CPU cycles     | 118  | 118   | 118    | 118    | ... | 118    |
| Inputs         |      |       |        |        |     |        |
| In (DSP)       | 0    | -3271 | -6510  | -9684  | ... | -19661 |
| In             | -0   | -0.1  | -0.199 | -0.296 | ... | -0.6   |
| Parameters     |      |       |        |        |     |        |
| A              | 0.7  |       |        |        |     |        |
| B              | 0.38 |       |        |        |     |        |
| C              | 0.33 |       |        |        |     |        |
| D              | 0.1  |       |        |        |     |        |
| Outputs        |      |       |        |        |     |        |
| Out            | 0    | -0.01 | -0.032 | -0.063 | ... | -0.311 |
| Exp. Out       | -0   | -0.01 | -0.032 | -0.063 | ... | -0.311 |
| Out (DSP)      | 0    | -328  | -1063  | -2073  | ... | -10187 |
| Exp. Out (DSP) | 0    | -327  | -1061  | -2072  | ... | -10184 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,2207e-04$ ( $\pm 4$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 117 |
| Max CPU cycles  | 118 |
| Avg CPU cycles  | 117 |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysmO1.



| Test results                 |    |      |       |       |        |       |
|------------------------------|----|------|-------|-------|--------|-------|
| Time step                    | 1  | 2    | 3     | 4     | 5      | 6     |
| <i>Mask parameters</i>       |    |      |       |       |        |       |
| <b>A</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>B</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>C</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>D</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <i>Controller parameters</i> |    |      |       |       |        |       |
| <b>a11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>c11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>b11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>d11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>sfrd11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrc11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrb11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfra11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. a11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. c11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. b11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. d11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrc11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrb11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 0,0000e+00$ |
| Tolerance c11    | $\pm 0,0000e+00$ |
| Tolerance b11    | $\pm 0,0000e+00$ |
| Tolerance d11    | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |
| Tolerance sfrc11 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block TDSysTemO1.

| Test results                 |    |      |       |       |        |       |
|------------------------------|----|------|-------|-------|--------|-------|
| Time step                    | 1  | 2    | 3     | 4     | 5      | 6     |
| <i>Mask parameters</i>       |    |      |       |       |        |       |
| <b>A</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>B</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>C</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>D</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <i>Controller parameters</i> |    |      |       |       |        |       |
| <b>a11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>c11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>b11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>d11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>sfrd11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrc11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrb11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfra11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. a11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. c11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. b11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. d11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrc11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrb11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 1,0000e+00$ |
| Tolerance c11    | $\pm 1,0000e+00$ |
| Tolerance b11    | $\pm 1,0000e+00$ |
| Tolerance d11    | $\pm 1,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |
| Tolerance sfrc11 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3118 |
| Max CPU cycles  | 9878 |
| Avg CPU cycles  | 4971 |

**Verification: TDSysmO1 FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block TDSysmO1.

| Test results   |      |       |        |        |     |        |
|----------------|------|-------|--------|--------|-----|--------|
| Time step      | 1    | 2     | 3      | 4      | ... | 174    |
| CPU cycles     | 129  | 129   | 129    | 129    | ... | 129    |
| Inputs         |      |       |        |        |     |        |
| In (DSP)       | 0    | -3271 | -6510  | -9684  | ... | -19661 |
| In             | -0   | -0.1  | -0.199 | -0.296 | ... | -0.6   |
| Parameters     |      |       |        |        |     |        |
| A              | 0.7  |       |        |        |     |        |
| B              | 0.38 |       |        |        |     |        |
| C              | 0.33 |       |        |        |     |        |
| D              | 0.1  |       |        |        |     |        |
| Outputs        |      |       |        |        |     |        |
| Out            | 0    | -0.01 | -0.032 | -0.063 | ... | -0.311 |
| Exp. Out       | -0   | -0.01 | -0.032 | -0.063 | ... | -0.311 |
| Out (DSP)      | 0    | -328  | -1063  | -2073  | ... | -10187 |
| Exp. Out (DSP) | 0    | -327  | -1061  | -2072  | ... | -10184 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,2207e-04$ ( $\pm 4$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 128 |
| Max CPU cycles  | 129 |
| Avg CPU cycles  | 128 |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysmO1.

| Test results                 |    |      |       |       |        |       |
|------------------------------|----|------|-------|-------|--------|-------|
| Time step                    | 1  | 2    | 3     | 4     | 5      | 6     |
| <i>Mask parameters</i>       |    |      |       |       |        |       |
| <b>A</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>B</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>C</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>D</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <i>Controller parameters</i> |    |      |       |       |        |       |
| <b>a11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>c11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>b11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>d11</b>                   | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>sfrd11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrc11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrb11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfra11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. a11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. c11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. b11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. d11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrc11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrb11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |

| Test settings    |             |
|------------------|-------------|
| Tolerance a11    | ±0,0000e+00 |
| Tolerance c11    | ±0,0000e+00 |
| Tolerance b11    | ±0,0000e+00 |
| Tolerance d11    | ±0,0000e+00 |
| Tolerance sfrd11 | ±0,0000e+00 |
| Tolerance sfrc11 | ±0,0000e+00 |
| Tolerance sfrb11 | ±0,0000e+00 |
| Tolerance sfrd11 | ±0,0000e+00 |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block TDSysTemO1.

| Test results                 |    |      |       |       |        |       |
|------------------------------|----|------|-------|-------|--------|-------|
| Time step                    | 1  | 2    | 3     | 4     | 5      | 6     |
| <i>Mask parameters</i>       |    |      |       |       |        |       |
| <b>A</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>B</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>C</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <b>D</b>                     | 0  | 0.1  | 1     | 10    | -1     | -0.1  |
| <i>Controller parameters</i> |    |      |       |       |        |       |
| <b>a11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>c11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>b11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>d11</b>                   | 0  | 3276 | 16384 | 20480 | -16384 | -3276 |
| <b>sfrd11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrb11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrd11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>sfrb11</b>                | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. a11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. c11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. b11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. d11</b>              | 0  | 3277 | 16384 | 20480 | -16384 | -3277 |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrb11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrd11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |
| <b>Exp. sfrb11</b>           | 15 | 15   | 14    | 11    | 14     | 15    |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 1,0000e+00$ |
| Tolerance c11    | $\pm 1,0000e+00$ |
| Tolerance b11    | $\pm 1,0000e+00$ |
| Tolerance d11    | $\pm 1,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 9373  |
| Max CPU cycles  | 41121 |
| Avg CPU cycles  | 19781 |

**Verification: TDSys<sub>tem</sub>O1 FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**Inport test for Control block TDSys<sub>tem</sub>O1.

| Test results   |      |            |     |             |
|----------------|------|------------|-----|-------------|
| Time step      | 1    | 2          | ... | 174         |
| CPU cycles     | 350  | 350        | ... | 350         |
| Inputs         |      |            |     |             |
| In (DSP)       | 0    | -214390630 | ... | -1288490189 |
| In             | -0   | -0.1       | ... | -0.6        |
| Parameters     |      |            |     |             |
| A              | 0.7  |            |     |             |
| B              | 0.38 |            |     |             |
| C              | 0.33 |            |     |             |
| D              | 0.1  |            |     |             |
| Outputs        |      |            |     |             |
| Out            | 0    | -0.01      | ... | -0.311      |
| Exp. Out       | -0   | -0.01      | ... | -0.311      |
| Out (DSP)      | 0    | -21439064  | ... | -667434826  |
| Exp. Out (DSP) | 0    | -21439063  | ... | -667434823  |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,8626\text{e-}09$ ( $\pm 4$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 290 |
| Max CPU cycles  | 355 |
| Avg CPU cycles  | 346 |

**Test case: Conversion test****OK**Conversion test for Control block TDSys<sub>tem</sub>O1.

| Test results                 |    |           |     |            |
|------------------------------|----|-----------|-----|------------|
| <b>Time step</b>             | 1  | 2         | ... | 6          |
| <i>Mask parameters</i>       |    |           |     |            |
| <b>A</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>B</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>C</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>D</b>                     | 0  | 0.1       | ... | -0.1       |
| <i>Controller parameters</i> |    |           |     |            |
| <b>a11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>c11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>b11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>d11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>sfrd11</b>                | 31 | 31        | ... | 31         |
| <b>sfrc11</b>                | 31 | 31        | ... | 31         |
| <b>sfrb11</b>                | 31 | 31        | ... | 31         |
| <b>sfra11</b>                | 31 | 31        | ... | 31         |
| <b>Exp. a11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. c11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. b11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. d11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrc11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrb11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 0,0000e+00$ |
| Tolerance c11    | $\pm 0,0000e+00$ |
| Tolerance b11    | $\pm 0,0000e+00$ |
| Tolerance d11    | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |
| Tolerance sfrc11 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block TDSysTemO1.

| Test results                 |    |           |     |            |
|------------------------------|----|-----------|-----|------------|
| <b>Time step</b>             | 1  | 2         | ... | 6          |
| <i>Mask parameters</i>       |    |           |     |            |
| <b>A</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>B</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>C</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>D</b>                     | 0  | 0.1       | ... | -0.1       |
| <i>Controller parameters</i> |    |           |     |            |
| <b>a11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>c11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>b11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>d11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>sfrd11</b>                | 31 | 31        | ... | 31         |
| <b>sfrc11</b>                | 31 | 31        | ... | 31         |
| <b>sfrb11</b>                | 31 | 31        | ... | 31         |
| <b>sfra11</b>                | 31 | 31        | ... | 31         |
| <b>Exp. a11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. c11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. b11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. d11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrc11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrb11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 3,0000e+00$ |
| Tolerance c11    | $\pm 3,0000e+00$ |
| Tolerance b11    | $\pm 3,0000e+00$ |
| Tolerance d11    | $\pm 3,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |
| Tolerance sfrc11 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 4952  |
| Max CPU cycles  | 13744 |
| Avg CPU cycles  | 7472  |



**Verification: TDSys<sub>tem</sub>O1 FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**Inport test for Control block TDSys<sub>tem</sub>O1.

| Test results   |      |            |     |             |
|----------------|------|------------|-----|-------------|
| Time step      | 1    | 2          | ... | 174         |
| CPU cycles     | 199  | 199        | ... | 199         |
| Inputs         |      |            |     |             |
| In (DSP)       | 0    | -214390630 | ... | -1288490189 |
| In             | -0   | -0.1       | ... | -0.6        |
| Parameters     |      |            |     |             |
| A              | 0.7  |            |     |             |
| B              | 0.38 |            |     |             |
| C              | 0.33 |            |     |             |
| D              | 0.1  |            |     |             |
| Outputs        |      |            |     |             |
| Out            | 0    | -0.01      | ... | -0.311      |
| Exp. Out       | -0   | -0.01      | ... | -0.311      |
| Out (DSP)      | 0    | -21439064  | ... | -667434826  |
| Exp. Out (DSP) | 0    | -21439063  | ... | -667434823  |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,8626\text{e-}09$ ( $\pm 4$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 193 |
| Max CPU cycles  | 203 |
| Avg CPU cycles  | 198 |

**Test case: Conversion test****OK**Conversion test for Control block TDSys<sub>tem</sub>O1.

| Test results                 |    |           |     |            |
|------------------------------|----|-----------|-----|------------|
| <b>Time step</b>             | 1  | 2         | ... | 6          |
| <i>Mask parameters</i>       |    |           |     |            |
| <b>A</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>B</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>C</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>D</b>                     | 0  | 0.1       | ... | -0.1       |
| <i>Controller parameters</i> |    |           |     |            |
| <b>a11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>c11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>b11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>d11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>sfrd11</b>                | 31 | 31        | ... | 31         |
| <b>sfrc11</b>                | 31 | 31        | ... | 31         |
| <b>sfrb11</b>                | 31 | 31        | ... | 31         |
| <b>sfra11</b>                | 31 | 31        | ... | 31         |
| <b>Exp. a11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. c11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. b11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. d11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrc11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrb11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 0,0000e+00$ |
| Tolerance c11    | $\pm 0,0000e+00$ |
| Tolerance b11    | $\pm 0,0000e+00$ |
| Tolerance d11    | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |
| Tolerance sfrc11 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block TDSysTemO1.

| Test results                 |    |           |     |            |
|------------------------------|----|-----------|-----|------------|
| <b>Time step</b>             | 1  | 2         | ... | 6          |
| <i>Mask parameters</i>       |    |           |     |            |
| <b>A</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>B</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>C</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>D</b>                     | 0  | 0.1       | ... | -0.1       |
| <i>Controller parameters</i> |    |           |     |            |
| <b>a11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>c11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>b11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>d11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>sfrd11</b>                | 31 | 31        | ... | 31         |
| <b>sfrc11</b>                | 31 | 31        | ... | 31         |
| <b>sfrb11</b>                | 31 | 31        | ... | 31         |
| <b>sfra11</b>                | 31 | 31        | ... | 31         |
| <b>Exp. a11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. c11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. b11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. d11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrc11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrb11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 3,0000e+00$ |
| Tolerance c11    | $\pm 3,0000e+00$ |
| Tolerance b11    | $\pm 3,0000e+00$ |
| Tolerance d11    | $\pm 3,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |
| Tolerance sfrc11 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1979 |
| Max CPU cycles  | 5555 |
| Avg CPU cycles  | 3087 |

**Verification: TDSysmO1 FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block TDSysmO1.

| Test results   |      |            |     |             |
|----------------|------|------------|-----|-------------|
| Time step      | 1    | 2          | ... | 174         |
| CPU cycles     | 217  | 217        | ... | 217         |
| Inputs         |      |            |     |             |
| In (DSP)       | 0    | -214390630 | ... | -1288490189 |
| In             | -0   | -0.1       | ... | -0.6        |
| Parameters     |      |            |     |             |
| A              | 0.7  |            |     |             |
| B              | 0.38 |            |     |             |
| C              | 0.33 |            |     |             |
| D              | 0.1  |            |     |             |
| Outputs        |      |            |     |             |
| Out            | 0    | -0.01      | ... | -0.311      |
| Exp. Out       | -0   | -0.01      | ... | -0.311      |
| Out (DSP)      | 0    | -21439064  | ... | -667434826  |
| Exp. Out (DSP) | 0    | -21439063  | ... | -667434823  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,8626e-09$ ( $\pm 4$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 217 |
| Max CPU cycles  | 217 |
| Avg CPU cycles  | 217 |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysmO1.

| Test results                 |    |           |     |            |
|------------------------------|----|-----------|-----|------------|
| <b>Time step</b>             | 1  | 2         | ... | 6          |
| <i>Mask parameters</i>       |    |           |     |            |
| <b>A</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>B</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>C</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>D</b>                     | 0  | 0.1       | ... | -0.1       |
| <i>Controller parameters</i> |    |           |     |            |
| <b>a11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>c11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>b11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>d11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>sfrd11</b>                | 31 | 31        | ... | 31         |
| <b>sfrc11</b>                | 31 | 31        | ... | 31         |
| <b>sfrb11</b>                | 31 | 31        | ... | 31         |
| <b>sfra11</b>                | 31 | 31        | ... | 31         |
| <b>Exp. a11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. c11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. b11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. d11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrc11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrb11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 0,0000e+00$ |
| Tolerance c11    | $\pm 0,0000e+00$ |
| Tolerance b11    | $\pm 0,0000e+00$ |
| Tolerance d11    | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |
| Tolerance sfrc11 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block TDSysTemO1.

| Test results                 |    |           |     |            |
|------------------------------|----|-----------|-----|------------|
| <b>Time step</b>             | 1  | 2         | ... | 6          |
| <i>Mask parameters</i>       |    |           |     |            |
| <b>A</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>B</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>C</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>D</b>                     | 0  | 0.1       | ... | -0.1       |
| <i>Controller parameters</i> |    |           |     |            |
| <b>a11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>c11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>b11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>d11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>sfrd11</b>                | 31 | 31        | ... | 31         |
| <b>sfrc11</b>                | 31 | 31        | ... | 31         |
| <b>sfrb11</b>                | 31 | 31        | ... | 31         |
| <b>sfra11</b>                | 31 | 31        | ... | 31         |
| <b>Exp. a11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. c11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. b11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. d11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrc11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrb11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 3,0000e+00$ |
| Tolerance c11    | $\pm 3,0000e+00$ |
| Tolerance b11    | $\pm 3,0000e+00$ |
| Tolerance d11    | $\pm 3,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |
| Tolerance sfrc11 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3032 |
| Max CPU cycles  | 5129 |
| Avg CPU cycles  | 3626 |

**Verification: TDSys<sub>tem</sub>O1 FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**Inport test for Control block TDSys<sub>tem</sub>O1.

| Test results   |      |            |     |             |
|----------------|------|------------|-----|-------------|
| Time step      | 1    | 2          | ... | 174         |
| CPU cycles     | 523  | 537        | ... | 537         |
| Inputs         |      |            |     |             |
| In (DSP)       | 0    | -214390630 | ... | -1288490189 |
| In             | -0   | -0.1       | ... | -0.6        |
| Parameters     |      |            |     |             |
| A              | 0.7  |            |     |             |
| B              | 0.38 |            |     |             |
| C              | 0.33 |            |     |             |
| D              | 0.1  |            |     |             |
| Outputs        |      |            |     |             |
| Out            | 0    | -0.01      | ... | -0.311      |
| Exp. Out       | -0   | -0.01      | ... | -0.311      |
| Out (DSP)      | 0    | -21439064  | ... | -667434826  |
| Exp. Out (DSP) | 0    | -21439063  | ... | -667434823  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,8626e-09$ ( $\pm 4$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 523 |
| Max CPU cycles  | 537 |
| Avg CPU cycles  | 528 |

**Test case: Conversion test****OK**Conversion test for Control block TDSys<sub>tem</sub>O1.

| Test results                 |    |           |     |            |
|------------------------------|----|-----------|-----|------------|
| <b>Time step</b>             | 1  | 2         | ... | 6          |
| <i>Mask parameters</i>       |    |           |     |            |
| <b>A</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>B</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>C</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>D</b>                     | 0  | 0.1       | ... | -0.1       |
| <i>Controller parameters</i> |    |           |     |            |
| <b>a11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>c11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>b11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>d11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>sfrd11</b>                | 31 | 31        | ... | 31         |
| <b>sfrc11</b>                | 31 | 31        | ... | 31         |
| <b>sfrb11</b>                | 31 | 31        | ... | 31         |
| <b>sfra11</b>                | 31 | 31        | ... | 31         |
| <b>Exp. a11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. c11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. b11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. d11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrc11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrb11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 0,0000e+00$ |
| Tolerance c11    | $\pm 0,0000e+00$ |
| Tolerance b11    | $\pm 0,0000e+00$ |
| Tolerance d11    | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |
| Tolerance sfrc11 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block TDSysTemO1.



| Test results                 |    |           |     |            |
|------------------------------|----|-----------|-----|------------|
| <b>Time step</b>             | 1  | 2         | ... | 6          |
| <i>Mask parameters</i>       |    |           |     |            |
| <b>A</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>B</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>C</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>D</b>                     | 0  | 0.1       | ... | -0.1       |
| <i>Controller parameters</i> |    |           |     |            |
| <b>a11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>c11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>b11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>d11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>sfrd11</b>                | 31 | 31        | ... | 31         |
| <b>sfrc11</b>                | 31 | 31        | ... | 31         |
| <b>sfrb11</b>                | 31 | 31        | ... | 31         |
| <b>sfra11</b>                | 31 | 31        | ... | 31         |
| <b>Exp. a11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. c11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. b11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. d11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrc11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrb11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 3,0000e+00$ |
| Tolerance c11    | $\pm 3,0000e+00$ |
| Tolerance b11    | $\pm 3,0000e+00$ |
| Tolerance d11    | $\pm 3,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |
| Tolerance sfrc11 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 9744  |
| Max CPU cycles  | 22252 |
| Avg CPU cycles  | 14298 |

**Verification: TDSysmO1 FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block TDSysmO1.

| Test results   |      |            |     |             |
|----------------|------|------------|-----|-------------|
| Time step      | 1    | 2          | ... | 174         |
| CPU cycles     | 138  | 139        | ... | 139         |
| Inputs         |      |            |     |             |
| In (DSP)       | 0    | -214390630 | ... | -1288490189 |
| In             | -0   | -0.1       | ... | -0.6        |
| Parameters     |      |            |     |             |
| A              | 0.7  |            |     |             |
| B              | 0.38 |            |     |             |
| C              | 0.33 |            |     |             |
| D              | 0.1  |            |     |             |
| Outputs        |      |            |     |             |
| Out            | 0    | -0.01      | ... | -0.311      |
| Exp. Out       | -0   | -0.01      | ... | -0.311      |
| Out (DSP)      | 0    | -21439064  | ... | -667434826  |
| Exp. Out (DSP) | 0    | -21439063  | ... | -667434823  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,8626e-09$ ( $\pm 4$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 138 |
| Max CPU cycles  | 143 |
| Avg CPU cycles  | 138 |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysmO1.

| Test results                 |    |           |     |            |
|------------------------------|----|-----------|-----|------------|
| <b>Time step</b>             | 1  | 2         | ... | 6          |
| <i>Mask parameters</i>       |    |           |     |            |
| <b>A</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>B</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>C</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>D</b>                     | 0  | 0.1       | ... | -0.1       |
| <i>Controller parameters</i> |    |           |     |            |
| <b>a11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>c11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>b11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>d11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>sfrd11</b>                | 31 | 31        | ... | 31         |
| <b>sfr11</b>                 | 31 | 31        | ... | 31         |
| <b>sfrb11</b>                | 31 | 31        | ... | 31         |
| <b>sfra11</b>                | 31 | 31        | ... | 31         |
| <b>Exp. a11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. c11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. b11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. d11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfr11</b>            | 31 | 31        | ... | 31         |
| <b>Exp. sfrb11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfr11</b>            | 31 | 31        | ... | 31         |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 0,0000e+00$ |
| Tolerance c11    | $\pm 0,0000e+00$ |
| Tolerance b11    | $\pm 0,0000e+00$ |
| Tolerance d11    | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |
| Tolerance sfr11  | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfr11  | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block TDSysTemO1.

| Test results                 |    |           |     |            |
|------------------------------|----|-----------|-----|------------|
| <b>Time step</b>             | 1  | 2         | ... | 6          |
| <i>Mask parameters</i>       |    |           |     |            |
| <b>A</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>B</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>C</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>D</b>                     | 0  | 0.1       | ... | -0.1       |
| <i>Controller parameters</i> |    |           |     |            |
| <b>a11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>c11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>b11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>d11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>sfrd11</b>                | 31 | 31        | ... | 31         |
| <b>sfrc11</b>                | 31 | 31        | ... | 31         |
| <b>sfrb11</b>                | 31 | 31        | ... | 31         |
| <b>sfra11</b>                | 31 | 31        | ... | 31         |
| <b>Exp. a11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. c11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. b11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. d11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrc11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrb11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 3,0000e+00$ |
| Tolerance c11    | $\pm 3,0000e+00$ |
| Tolerance b11    | $\pm 3,0000e+00$ |
| Tolerance d11    | $\pm 3,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |
| Tolerance sfrc11 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 4459 |
| Max CPU cycles  | 9143 |
| Avg CPU cycles  | 5963 |

**Verification: TDSys<sub>tem</sub>O1 FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**Inport test for Control block TDSys<sub>tem</sub>O1.

| Test results   |      |            |     |             |
|----------------|------|------------|-----|-------------|
| Time step      | 1    | 2          | ... | 174         |
| CPU cycles     | 220  | 179        | ... | 179         |
| Inputs         |      |            |     |             |
| In (DSP)       | 0    | -214390630 | ... | -1288490189 |
| In             | -0   | -0.1       | ... | -0.6        |
| Parameters     |      |            |     |             |
| A              | 0.7  |            |     |             |
| B              | 0.38 |            |     |             |
| C              | 0.33 |            |     |             |
| D              | 0.1  |            |     |             |
| Outputs        |      |            |     |             |
| Out            | 0    | -0.01      | ... | -0.311      |
| Exp. Out       | -0   | -0.01      | ... | -0.311      |
| Out (DSP)      | 0    | -21439064  | ... | -667434826  |
| Exp. Out (DSP) | 0    | -21439063  | ... | -667434823  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,8626e-09$ ( $\pm 4$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 179 |
| Max CPU cycles  | 220 |
| Avg CPU cycles  | 179 |

**Test case: Conversion test****OK**Conversion test for Control block TDSys<sub>tem</sub>O1.

| Test results                 |    |           |     |            |
|------------------------------|----|-----------|-----|------------|
| <b>Time step</b>             | 1  | 2         | ... | 6          |
| <i>Mask parameters</i>       |    |           |     |            |
| <b>A</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>B</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>C</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>D</b>                     | 0  | 0.1       | ... | -0.1       |
| <i>Controller parameters</i> |    |           |     |            |
| <b>a11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>c11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>b11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>d11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>sfrd11</b>                | 31 | 31        | ... | 31         |
| <b>sfrc11</b>                | 31 | 31        | ... | 31         |
| <b>sfrb11</b>                | 31 | 31        | ... | 31         |
| <b>sfra11</b>                | 31 | 31        | ... | 31         |
| <b>Exp. a11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. c11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. b11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. d11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrc11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrb11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 0,0000e+00$ |
| Tolerance c11    | $\pm 0,0000e+00$ |
| Tolerance b11    | $\pm 0,0000e+00$ |
| Tolerance d11    | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |
| Tolerance sfrc11 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block TDSysTemO1.

| Test results                 |    |           |     |            |
|------------------------------|----|-----------|-----|------------|
| <b>Time step</b>             | 1  | 2         | ... | 6          |
| <i>Mask parameters</i>       |    |           |     |            |
| <b>A</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>B</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>C</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>D</b>                     | 0  | 0.1       | ... | -0.1       |
| <i>Controller parameters</i> |    |           |     |            |
| <b>a11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>c11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>b11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>d11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>sfrd11</b>                | 31 | 31        | ... | 31         |
| <b>sfrc11</b>                | 31 | 31        | ... | 31         |
| <b>sfrb11</b>                | 31 | 31        | ... | 31         |
| <b>sfra11</b>                | 31 | 31        | ... | 31         |
| <b>Exp. a11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. c11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. b11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. d11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrc11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrb11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 3,0000e+00$ |
| Tolerance c11    | $\pm 3,0000e+00$ |
| Tolerance b11    | $\pm 3,0000e+00$ |
| Tolerance d11    | $\pm 3,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |
| Tolerance sfrc11 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2871 |
| Max CPU cycles  | 4838 |
| Avg CPU cycles  | 3411 |

**Verification: TDSysSystemO1 FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block TDSysSystemO1.

| Test results   |      |            |     |             |
|----------------|------|------------|-----|-------------|
| Time step      | 1    | 2          | ... | 174         |
| CPU cycles     | 298  | 298        | ... | 298         |
| Inputs         |      |            |     |             |
| In (DSP)       | 0    | -214390630 | ... | -1288490189 |
| In             | -0   | -0.1       | ... | -0.6        |
| Parameters     |      |            |     |             |
| A              | 0.7  |            |     |             |
| B              | 0.38 |            |     |             |
| C              | 0.33 |            |     |             |
| D              | 0.1  |            |     |             |
| Outputs        |      |            |     |             |
| Out            | 0    | -0.01      | ... | -0.311      |
| Exp. Out       | -0   | -0.01      | ... | -0.311      |
| Out (DSP)      | 0    | -21439064  | ... | -667434826  |
| Exp. Out (DSP) | 0    | -21439063  | ... | -667434823  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,8626e-09$ ( $\pm 4$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 256 |
| Max CPU cycles  | 307 |
| Avg CPU cycles  | 296 |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysSystemO1.



| Test results                 |    |           |     |            |
|------------------------------|----|-----------|-----|------------|
| <b>Time step</b>             | 1  | 2         | ... | 6          |
| <i>Mask parameters</i>       |    |           |     |            |
| <b>A</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>B</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>C</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>D</b>                     | 0  | 0.1       | ... | -0.1       |
| <i>Controller parameters</i> |    |           |     |            |
| <b>a11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>c11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>b11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>d11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>sfrd11</b>                | 31 | 31        | ... | 31         |
| <b>sfrc11</b>                | 31 | 31        | ... | 31         |
| <b>sfrb11</b>                | 31 | 31        | ... | 31         |
| <b>sfra11</b>                | 31 | 31        | ... | 31         |
| <b>Exp. a11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. c11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. b11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. d11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrc11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrb11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 0,0000e+00$ |
| Tolerance c11    | $\pm 0,0000e+00$ |
| Tolerance b11    | $\pm 0,0000e+00$ |
| Tolerance d11    | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |
| Tolerance sfrc11 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block TDSysTemO1.

| Test results                 |    |           |     |            |
|------------------------------|----|-----------|-----|------------|
| <b>Time step</b>             | 1  | 2         | ... | 6          |
| <i>Mask parameters</i>       |    |           |     |            |
| <b>A</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>B</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>C</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>D</b>                     | 0  | 0.1       | ... | -0.1       |
| <i>Controller parameters</i> |    |           |     |            |
| <b>a11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>c11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>b11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>d11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>sfrd11</b>                | 31 | 31        | ... | 31         |
| <b>sfrc11</b>                | 31 | 31        | ... | 31         |
| <b>sfrb11</b>                | 31 | 31        | ... | 31         |
| <b>sfra11</b>                | 31 | 31        | ... | 31         |
| <b>Exp. a11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. c11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. b11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. d11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrc11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrb11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 3,0000e+00$ |
| Tolerance c11    | $\pm 3,0000e+00$ |
| Tolerance b11    | $\pm 3,0000e+00$ |
| Tolerance d11    | $\pm 3,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |
| Tolerance sfrc11 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 3528  |
| Max CPU cycles  | 10460 |
| Avg CPU cycles  | 5515  |

**Verification: TDSysmO1 FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block TDSysmO1.

| Test results   |      |            |     |             |
|----------------|------|------------|-----|-------------|
| Time step      | 1    | 2          | ... | 174         |
| CPU cycles     | 1799 | 1813       | ... | 1827        |
| Inputs         |      |            |     |             |
| In (DSP)       | 0    | -214390630 | ... | -1288490189 |
| In             | -0   | -0.1       | ... | -0.6        |
| Parameters     |      |            |     |             |
| A              | 0.7  |            |     |             |
| B              | 0.38 |            |     |             |
| C              | 0.33 |            |     |             |
| D              | 0.1  |            |     |             |
| Outputs        |      |            |     |             |
| Out            | 0    | -0.01      | ... | -0.311      |
| Exp. Out       | -0   | -0.01      | ... | -0.311      |
| Out (DSP)      | 0    | -21439064  | ... | -667434826  |
| Exp. Out (DSP) | 0    | -21439063  | ... | -667434823  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,8626e-09$ ( $\pm 4$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1799 |
| Max CPU cycles  | 1828 |
| Avg CPU cycles  | 1809 |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysmO1.

| Test results                 |    |           |     |            |
|------------------------------|----|-----------|-----|------------|
| <b>Time step</b>             | 1  | 2         | ... | 6          |
| <i>Mask parameters</i>       |    |           |     |            |
| <b>A</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>B</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>C</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>D</b>                     | 0  | 0.1       | ... | -0.1       |
| <i>Controller parameters</i> |    |           |     |            |
| <b>a11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>c11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>b11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>d11</b>                   | 0  | 214748365 | ... | -214748365 |
| <b>sfrd11</b>                | 31 | 31        | ... | 31         |
| <b>sfrc11</b>                | 31 | 31        | ... | 31         |
| <b>sfrb11</b>                | 31 | 31        | ... | 31         |
| <b>sfra11</b>                | 31 | 31        | ... | 31         |
| <b>Exp. a11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. c11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. b11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. d11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrc11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrb11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 0,0000e+00$ |
| Tolerance c11    | $\pm 0,0000e+00$ |
| Tolerance b11    | $\pm 0,0000e+00$ |
| Tolerance d11    | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |
| Tolerance sfrc11 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block TDSysTemO1.

| Test results                 |    |           |     |            |
|------------------------------|----|-----------|-----|------------|
| <b>Time step</b>             | 1  | 2         | ... | 6          |
| <i>Mask parameters</i>       |    |           |     |            |
| <b>A</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>B</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>C</b>                     | 0  | 0.1       | ... | -0.1       |
| <b>D</b>                     | 0  | 0.1       | ... | -0.1       |
| <i>Controller parameters</i> |    |           |     |            |
| <b>a11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>c11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>b11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>d11</b>                   | 0  | 214748368 | ... | -214748368 |
| <b>sfrd11</b>                | 31 | 31        | ... | 31         |
| <b>sfrc11</b>                | 31 | 31        | ... | 31         |
| <b>sfrb11</b>                | 31 | 31        | ... | 31         |
| <b>sfra11</b>                | 31 | 31        | ... | 31         |
| <b>Exp. a11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. c11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. b11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. d11</b>              | 0  | 214748365 | ... | -214748365 |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrc11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrb11</b>           | 31 | 31        | ... | 31         |
| <b>Exp. sfrd11</b>           | 31 | 31        | ... | 31         |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 3,0000e+00$ |
| Tolerance c11    | $\pm 3,0000e+00$ |
| Tolerance b11    | $\pm 3,0000e+00$ |
| Tolerance d11    | $\pm 3,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |
| Tolerance sfrc11 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrd11 | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 10998 |
| Max CPU cycles  | 41682 |
| Avg CPU cycles  | 21084 |

**Verification: TDSys<sub>tem</sub>O1 Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**Inport test for Control block TDSys<sub>tem</sub>O1.

| Test results   |      |       |     |        |
|----------------|------|-------|-----|--------|
| Time step      | 1    | 2     | ... | 174    |
| CPU cycles     | 73   | 73    | ... | 73     |
| Inputs         |      |       |     |        |
| In (DSP)       | -0   | -0.1  | ... | -0.6   |
| In             | -0   | -0.1  | ... | -0.6   |
| Parameters     |      |       |     |        |
| A              | 0.7  |       |     |        |
| B              | 0.38 |       |     |        |
| C              | 0.33 |       |     |        |
| D              | 0.1  |       |     |        |
| Outputs        |      |       |     |        |
| Out            | -0   | -0.01 | ... | -0.311 |
| Exp. Out       | -0   | -0.01 | ... | -0.311 |
| Out (DSP)      | -0   | -0.01 | ... | -0.311 |
| Exp. Out (DSP) | -0   | -0.01 | ... | -0.311 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 9,3132e-08$ ( $\pm 200$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 73 |
| Max CPU cycles  | 73 |
| Avg CPU cycles  | 73 |

**Test case: Conversion test****OK**Conversion test for Control block TDSys<sub>tem</sub>O1.

| Test results          |   |     |     |      |
|-----------------------|---|-----|-----|------|
| Time step             | 1 | 2   | ... | 6    |
| Mask parameters       |   |     |     |      |
| <b>A</b>              | 0 | 0.1 | ... | -0.1 |
| <b>B</b>              | 0 | 0.1 | ... | -0.1 |
| <b>C</b>              | 0 | 0.1 | ... | -0.1 |
| <b>D</b>              | 0 | 0.1 | ... | -0.1 |
| Controller parameters |   |     |     |      |
| <b>a11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>c11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>b11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>d11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>Exp. a11</b>       | 0 | 0.1 | ... | -0.1 |
| <b>Exp. c11</b>       | 0 | 0.1 | ... | -0.1 |
| <b>Exp. b11</b>       | 0 | 0.1 | ... | -0.1 |
| <b>Exp. d11</b>       | 0 | 0.1 | ... | -0.1 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a11 | $\pm 0,0000e+00$ |
| Tolerance c11 | $\pm 0,0000e+00$ |
| Tolerance b11 | $\pm 0,0000e+00$ |
| Tolerance d11 | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block TDSysTemO1.

| Test results                 |   |     |     |      |
|------------------------------|---|-----|-----|------|
| <b>Time step</b>             | 1 | 2   | ... | 6    |
| <i>Mask parameters</i>       |   |     |     |      |
| <b>A</b>                     | 0 | 0.1 | ... | -0.1 |
| <b>B</b>                     | 0 | 0.1 | ... | -0.1 |
| <b>C</b>                     | 0 | 0.1 | ... | -0.1 |
| <b>D</b>                     | 0 | 0.1 | ... | -0.1 |
| <i>Controller parameters</i> |   |     |     |      |
| <b>a11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>c11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>b11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>d11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>Exp. a11</b>              | 0 | 0.1 | ... | -0.1 |
| <b>Exp. c11</b>              | 0 | 0.1 | ... | -0.1 |
| <b>Exp. b11</b>              | 0 | 0.1 | ... | -0.1 |
| <b>Exp. d11</b>              | 0 | 0.1 | ... | -0.1 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a11 | $\pm 2,0000e-09$ |
| Tolerance c11 | $\pm 2,0000e-09$ |
| Tolerance b11 | $\pm 2,0000e-09$ |
| Tolerance d11 | $\pm 2,0000e-09$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1862 |
| Max CPU cycles  | 1906 |
| Avg CPU cycles  | 1869 |



**Verification: TDSys<sub>tem</sub>O1 Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**Inport test for Control block TDSys<sub>tem</sub>O1.

| Test results   |      |       |     |        |
|----------------|------|-------|-----|--------|
| Time step      | 1    | 2     | ... | 174    |
| CPU cycles     | 47   | 47    | ... | 47     |
| Inputs         |      |       |     |        |
| In (DSP)       | -0   | -0.1  | ... | -0.6   |
| In             | -0   | -0.1  | ... | -0.6   |
| Parameters     |      |       |     |        |
| A              | 0.7  |       |     |        |
| B              | 0.38 |       |     |        |
| C              | 0.33 |       |     |        |
| D              | 0.1  |       |     |        |
| Outputs        |      |       |     |        |
| Out            | -0   | -0.01 | ... | -0.311 |
| Exp. Out       | -0   | -0.01 | ... | -0.311 |
| Out (DSP)      | -0   | -0.01 | ... | -0.311 |
| Exp. Out (DSP) | -0   | -0.01 | ... | -0.311 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 9,3132e-08$ ( $\pm 200$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 47 |
| Max CPU cycles  | 47 |
| Avg CPU cycles  | 47 |

**Test case: Conversion test****OK**Conversion test for Control block TDSys<sub>tem</sub>O1.

| Test results          |   |     |     |      |
|-----------------------|---|-----|-----|------|
| Time step             | 1 | 2   | ... | 6    |
| Mask parameters       |   |     |     |      |
| <b>A</b>              | 0 | 0.1 | ... | -0.1 |
| <b>B</b>              | 0 | 0.1 | ... | -0.1 |
| <b>C</b>              | 0 | 0.1 | ... | -0.1 |
| <b>D</b>              | 0 | 0.1 | ... | -0.1 |
| Controller parameters |   |     |     |      |
| <b>a11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>c11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>b11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>d11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>Exp. a11</b>       | 0 | 0.1 | ... | -0.1 |
| <b>Exp. c11</b>       | 0 | 0.1 | ... | -0.1 |
| <b>Exp. b11</b>       | 0 | 0.1 | ... | -0.1 |
| <b>Exp. d11</b>       | 0 | 0.1 | ... | -0.1 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a11 | $\pm 0,0000e+00$ |
| Tolerance c11 | $\pm 0,0000e+00$ |
| Tolerance b11 | $\pm 0,0000e+00$ |
| Tolerance d11 | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block TDSysTemO1.

| Test results                 |   |     |     |      |
|------------------------------|---|-----|-----|------|
| <b>Time step</b>             | 1 | 2   | ... | 6    |
| <i>Mask parameters</i>       |   |     |     |      |
| <b>A</b>                     | 0 | 0.1 | ... | -0.1 |
| <b>B</b>                     | 0 | 0.1 | ... | -0.1 |
| <b>C</b>                     | 0 | 0.1 | ... | -0.1 |
| <b>D</b>                     | 0 | 0.1 | ... | -0.1 |
| <i>Controller parameters</i> |   |     |     |      |
| <b>a11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>c11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>b11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>d11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>Exp. a11</b>              | 0 | 0.1 | ... | -0.1 |
| <b>Exp. c11</b>              | 0 | 0.1 | ... | -0.1 |
| <b>Exp. b11</b>              | 0 | 0.1 | ... | -0.1 |
| <b>Exp. d11</b>              | 0 | 0.1 | ... | -0.1 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a11 | $\pm 2,0000e-09$ |
| Tolerance c11 | $\pm 2,0000e-09$ |
| Tolerance b11 | $\pm 2,0000e-09$ |
| Tolerance d11 | $\pm 2,0000e-09$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 851 |
| Max CPU cycles  | 851 |
| Avg CPU cycles  | 851 |

**Verification: TDSys<sub>tem</sub>O1 Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**Inport test for Control block TDSys<sub>tem</sub>O1.

| Test results   |      |       |     |        |
|----------------|------|-------|-----|--------|
| Time step      | 1    | 2     | ... | 174    |
| CPU cycles     | 86   | 86    | ... | 86     |
| Inputs         |      |       |     |        |
| In (DSP)       | -0   | -0.1  | ... | -0.6   |
| In             | -0   | -0.1  | ... | -0.6   |
| Parameters     |      |       |     |        |
| A              | 0.7  |       |     |        |
| B              | 0.38 |       |     |        |
| C              | 0.33 |       |     |        |
| D              | 0.1  |       |     |        |
| Outputs        |      |       |     |        |
| Out            | -0   | -0.01 | ... | -0.311 |
| Exp. Out       | -0   | -0.01 | ... | -0.311 |
| Out (DSP)      | -0   | -0.01 | ... | -0.311 |
| Exp. Out (DSP) | -0   | -0.01 | ... | -0.311 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 9,3132e-08$ ( $\pm 200$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 86 |
| Max CPU cycles  | 86 |
| Avg CPU cycles  | 86 |

**Test case: Conversion test****OK**Conversion test for Control block TDSys<sub>tem</sub>O1.

| Test results          |   |     |     |      |
|-----------------------|---|-----|-----|------|
| Time step             | 1 | 2   | ... | 6    |
| Mask parameters       |   |     |     |      |
| <b>A</b>              | 0 | 0.1 | ... | -0.1 |
| <b>B</b>              | 0 | 0.1 | ... | -0.1 |
| <b>C</b>              | 0 | 0.1 | ... | -0.1 |
| <b>D</b>              | 0 | 0.1 | ... | -0.1 |
| Controller parameters |   |     |     |      |
| <b>a11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>c11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>b11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>d11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>Exp. a11</b>       | 0 | 0.1 | ... | -0.1 |
| <b>Exp. c11</b>       | 0 | 0.1 | ... | -0.1 |
| <b>Exp. b11</b>       | 0 | 0.1 | ... | -0.1 |
| <b>Exp. d11</b>       | 0 | 0.1 | ... | -0.1 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a11 | $\pm 0,0000e+00$ |
| Tolerance c11 | $\pm 0,0000e+00$ |
| Tolerance b11 | $\pm 0,0000e+00$ |
| Tolerance d11 | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block TDSysSystemO1.

| Test results                 |   |     |     |      |
|------------------------------|---|-----|-----|------|
| <b>Time step</b>             | 1 | 2   | ... | 6    |
| <i>Mask parameters</i>       |   |     |     |      |
| <b>A</b>                     | 0 | 0.1 | ... | -0.1 |
| <b>B</b>                     | 0 | 0.1 | ... | -0.1 |
| <b>C</b>                     | 0 | 0.1 | ... | -0.1 |
| <b>D</b>                     | 0 | 0.1 | ... | -0.1 |
| <i>Controller parameters</i> |   |     |     |      |
| <b>a11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>c11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>b11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>d11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>Exp. a11</b>              | 0 | 0.1 | ... | -0.1 |
| <b>Exp. c11</b>              | 0 | 0.1 | ... | -0.1 |
| <b>Exp. b11</b>              | 0 | 0.1 | ... | -0.1 |
| <b>Exp. d11</b>              | 0 | 0.1 | ... | -0.1 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a11 | $\pm 2,0000e-09$ |
| Tolerance c11 | $\pm 2,0000e-09$ |
| Tolerance b11 | $\pm 2,0000e-09$ |
| Tolerance d11 | $\pm 2,0000e-09$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 810 |
| Max CPU cycles  | 810 |
| Avg CPU cycles  | 810 |

**Verification: TDSys<sub>tem</sub>O1 Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**Inport test for Control block TDSys<sub>tem</sub>O1.

| Test results   |      |       |     |        |
|----------------|------|-------|-----|--------|
| Time step      | 1    | 2     | ... | 174    |
| CPU cycles     | 817  | 967   | ... | 1037   |
| Inputs         |      |       |     |        |
| In (DSP)       | -0   | -0.1  | ... | -0.6   |
| In             | -0   | -0.1  | ... | -0.6   |
| Parameters     |      |       |     |        |
| A              | 0.7  |       |     |        |
| B              | 0.38 |       |     |        |
| C              | 0.33 |       |     |        |
| D              | 0.1  |       |     |        |
| Outputs        |      |       |     |        |
| Out            | -0   | -0.01 | ... | -0.311 |
| Exp. Out       | -0   | -0.01 | ... | -0.311 |
| Out (DSP)      | -0   | -0.01 | ... | -0.311 |
| Exp. Out (DSP) | -0   | -0.01 | ... | -0.311 |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 9,3132\text{e-}08$ ( $\pm 200$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 817  |
| Max CPU cycles  | 1114 |
| Avg CPU cycles  | 999  |

**Test case: Conversion test****OK**Conversion test for Control block TDSys<sub>tem</sub>O1.

| Test results          |   |     |     |      |
|-----------------------|---|-----|-----|------|
| Time step             | 1 | 2   | ... | 6    |
| Mask parameters       |   |     |     |      |
| <b>A</b>              | 0 | 0.1 | ... | -0.1 |
| <b>B</b>              | 0 | 0.1 | ... | -0.1 |
| <b>C</b>              | 0 | 0.1 | ... | -0.1 |
| <b>D</b>              | 0 | 0.1 | ... | -0.1 |
| Controller parameters |   |     |     |      |
| <b>a11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>c11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>b11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>d11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>Exp. a11</b>       | 0 | 0.1 | ... | -0.1 |
| <b>Exp. c11</b>       | 0 | 0.1 | ... | -0.1 |
| <b>Exp. b11</b>       | 0 | 0.1 | ... | -0.1 |
| <b>Exp. d11</b>       | 0 | 0.1 | ... | -0.1 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a11 | $\pm 0,0000e+00$ |
| Tolerance c11 | $\pm 0,0000e+00$ |
| Tolerance b11 | $\pm 0,0000e+00$ |
| Tolerance d11 | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block TDSysTemO1.



| Test results                 |   |     |     |      |
|------------------------------|---|-----|-----|------|
| <b>Time step</b>             | 1 | 2   | ... | 6    |
| <i>Mask parameters</i>       |   |     |     |      |
| <b>A</b>                     | 0 | 0.1 | ... | -0.1 |
| <b>B</b>                     | 0 | 0.1 | ... | -0.1 |
| <b>C</b>                     | 0 | 0.1 | ... | -0.1 |
| <b>D</b>                     | 0 | 0.1 | ... | -0.1 |
| <i>Controller parameters</i> |   |     |     |      |
| <b>a11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>c11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>b11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>d11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>Exp. a11</b>              | 0 | 0.1 | ... | -0.1 |
| <b>Exp. c11</b>              | 0 | 0.1 | ... | -0.1 |
| <b>Exp. b11</b>              | 0 | 0.1 | ... | -0.1 |
| <b>Exp. d11</b>              | 0 | 0.1 | ... | -0.1 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a11 | $\pm 2,0000e-09$ |
| Tolerance c11 | $\pm 2,0000e-09$ |
| Tolerance b11 | $\pm 2,0000e-09$ |
| Tolerance d11 | $\pm 2,0000e-09$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1729 |
| Max CPU cycles  | 1845 |
| Avg CPU cycles  | 1807 |

**Verification: TDSys<sub>tem</sub>O1 Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**Inport test for Control block TDSys<sub>tem</sub>O1.

| Test results   |      |       |     |        |
|----------------|------|-------|-----|--------|
| Time step      | 1    | 2     | ... | 174    |
| CPU cycles     | 289  | 363   | ... | 375    |
| Inputs         |      |       |     |        |
| In (DSP)       | -0   | -0.1  | ... | -0.6   |
| In             | -0   | -0.1  | ... | -0.6   |
| Parameters     |      |       |     |        |
| A              | 0.7  |       |     |        |
| B              | 0.38 |       |     |        |
| C              | 0.33 |       |     |        |
| D              | 0.1  |       |     |        |
| Outputs        |      |       |     |        |
| Out            | -0   | -0.01 | ... | -0.311 |
| Exp. Out       | -0   | -0.01 | ... | -0.311 |
| Out (DSP)      | -0   | -0.01 | ... | -0.311 |
| Exp. Out (DSP) | -0   | -0.01 | ... | -0.311 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 9,3132e-08$ ( $\pm 200$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 287 |
| Max CPU cycles  | 395 |
| Avg CPU cycles  | 359 |

**Test case: Conversion test****OK**Conversion test for Control block TDSys<sub>tem</sub>O1.

| Test results          |   |     |     |      |
|-----------------------|---|-----|-----|------|
| Time step             | 1 | 2   | ... | 6    |
| Mask parameters       |   |     |     |      |
| <b>A</b>              | 0 | 0.1 | ... | -0.1 |
| <b>B</b>              | 0 | 0.1 | ... | -0.1 |
| <b>C</b>              | 0 | 0.1 | ... | -0.1 |
| <b>D</b>              | 0 | 0.1 | ... | -0.1 |
| Controller parameters |   |     |     |      |
| <b>a11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>c11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>b11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>d11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>Exp. a11</b>       | 0 | 0.1 | ... | -0.1 |
| <b>Exp. c11</b>       | 0 | 0.1 | ... | -0.1 |
| <b>Exp. b11</b>       | 0 | 0.1 | ... | -0.1 |
| <b>Exp. d11</b>       | 0 | 0.1 | ... | -0.1 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a11 | $\pm 0,0000e+00$ |
| Tolerance c11 | $\pm 0,0000e+00$ |
| Tolerance b11 | $\pm 0,0000e+00$ |
| Tolerance d11 | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block TDSysTemO1.

| Test results                 |   |     |     |      |
|------------------------------|---|-----|-----|------|
| <b>Time step</b>             | 1 | 2   | ... | 6    |
| <i>Mask parameters</i>       |   |     |     |      |
| <b>A</b>                     | 0 | 0.1 | ... | -0.1 |
| <b>B</b>                     | 0 | 0.1 | ... | -0.1 |
| <b>C</b>                     | 0 | 0.1 | ... | -0.1 |
| <b>D</b>                     | 0 | 0.1 | ... | -0.1 |
| <i>Controller parameters</i> |   |     |     |      |
| <b>a11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>c11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>b11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>d11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>Exp. a11</b>              | 0 | 0.1 | ... | -0.1 |
| <b>Exp. c11</b>              | 0 | 0.1 | ... | -0.1 |
| <b>Exp. b11</b>              | 0 | 0.1 | ... | -0.1 |
| <b>Exp. d11</b>              | 0 | 0.1 | ... | -0.1 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a11 | $\pm 2,0000e-09$ |
| Tolerance c11 | $\pm 2,0000e-09$ |
| Tolerance b11 | $\pm 2,0000e-09$ |
| Tolerance d11 | $\pm 2,0000e-09$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 647 |
| Max CPU cycles  | 651 |
| Avg CPU cycles  | 649 |

**Verification: TDSys<sub>tem</sub>O1 Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**Inport test for Control block TDSys<sub>tem</sub>O1.

| Test results   |      |       |     |        |
|----------------|------|-------|-----|--------|
| Time step      | 1    | 2     | ... | 174    |
| CPU cycles     | 92   | 80    | ... | 80     |
| Inputs         |      |       |     |        |
| In (DSP)       | -0   | -0.1  | ... | -0.6   |
| In             | -0   | -0.1  | ... | -0.6   |
| Parameters     |      |       |     |        |
| A              | 0.7  |       |     |        |
| B              | 0.38 |       |     |        |
| C              | 0.33 |       |     |        |
| D              | 0.1  |       |     |        |
| Outputs        |      |       |     |        |
| Out            | -0   | -0.01 | ... | -0.311 |
| Exp. Out       | -0   | -0.01 | ... | -0.311 |
| Out (DSP)      | -0   | -0.01 | ... | -0.311 |
| Exp. Out (DSP) | -0   | -0.01 | ... | -0.311 |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 9,3132\text{e-}08$ ( $\pm 200$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 80 |
| Max CPU cycles  | 92 |
| Avg CPU cycles  | 80 |

**Test case: Conversion test****OK**Conversion test for Control block TDSys<sub>tem</sub>O1.

| Test results          |   |     |     |      |
|-----------------------|---|-----|-----|------|
| Time step             | 1 | 2   | ... | 6    |
| Mask parameters       |   |     |     |      |
| <b>A</b>              | 0 | 0.1 | ... | -0.1 |
| <b>B</b>              | 0 | 0.1 | ... | -0.1 |
| <b>C</b>              | 0 | 0.1 | ... | -0.1 |
| <b>D</b>              | 0 | 0.1 | ... | -0.1 |
| Controller parameters |   |     |     |      |
| <b>a11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>c11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>b11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>d11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>Exp. a11</b>       | 0 | 0.1 | ... | -0.1 |
| <b>Exp. c11</b>       | 0 | 0.1 | ... | -0.1 |
| <b>Exp. b11</b>       | 0 | 0.1 | ... | -0.1 |
| <b>Exp. d11</b>       | 0 | 0.1 | ... | -0.1 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a11 | $\pm 0,0000e+00$ |
| Tolerance c11 | $\pm 0,0000e+00$ |
| Tolerance b11 | $\pm 0,0000e+00$ |
| Tolerance d11 | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block TDSysTemO1.

| Test results                 |   |     |     |      |
|------------------------------|---|-----|-----|------|
| <b>Time step</b>             | 1 | 2   | ... | 6    |
| <i>Mask parameters</i>       |   |     |     |      |
| <b>A</b>                     | 0 | 0.1 | ... | -0.1 |
| <b>B</b>                     | 0 | 0.1 | ... | -0.1 |
| <b>C</b>                     | 0 | 0.1 | ... | -0.1 |
| <b>D</b>                     | 0 | 0.1 | ... | -0.1 |
| <i>Controller parameters</i> |   |     |     |      |
| <b>a11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>c11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>b11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>d11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>Exp. a11</b>              | 0 | 0.1 | ... | -0.1 |
| <b>Exp. c11</b>              | 0 | 0.1 | ... | -0.1 |
| <b>Exp. b11</b>              | 0 | 0.1 | ... | -0.1 |
| <b>Exp. d11</b>              | 0 | 0.1 | ... | -0.1 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a11 | $\pm 2,0000e-09$ |
| Tolerance c11 | $\pm 2,0000e-09$ |
| Tolerance b11 | $\pm 2,0000e-09$ |
| Tolerance d11 | $\pm 2,0000e-09$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 787 |
| Max CPU cycles  | 907 |
| Avg CPU cycles  | 807 |

**Verification: TDSys<sub>tem</sub>O1 Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**Inport test for Control block TDSys<sub>tem</sub>O1.

| Test results   |      |       |     |        |
|----------------|------|-------|-----|--------|
| Time step      | 1    | 2     | ... | 174    |
| CPU cycles     | 63   | 63    | ... | 63     |
| Inputs         |      |       |     |        |
| In (DSP)       | -0   | -0.1  | ... | -0.6   |
| In             | -0   | -0.1  | ... | -0.6   |
| Parameters     |      |       |     |        |
| A              | 0.7  |       |     |        |
| B              | 0.38 |       |     |        |
| C              | 0.33 |       |     |        |
| D              | 0.1  |       |     |        |
| Outputs        |      |       |     |        |
| Out            | -0   | -0.01 | ... | -0.311 |
| Exp. Out       | -0   | -0.01 | ... | -0.311 |
| Out (DSP)      | -0   | -0.01 | ... | -0.311 |
| Exp. Out (DSP) | -0   | -0.01 | ... | -0.311 |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 9,3132\text{e-}08$ ( $\pm 200$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 63 |
| Max CPU cycles  | 63 |
| Avg CPU cycles  | 63 |

**Test case: Conversion test****OK**Conversion test for Control block TDSys<sub>tem</sub>O1.



| Test results          |   |     |     |      |
|-----------------------|---|-----|-----|------|
| Time step             | 1 | 2   | ... | 6    |
| Mask parameters       |   |     |     |      |
| <b>A</b>              | 0 | 0.1 | ... | -0.1 |
| <b>B</b>              | 0 | 0.1 | ... | -0.1 |
| <b>C</b>              | 0 | 0.1 | ... | -0.1 |
| <b>D</b>              | 0 | 0.1 | ... | -0.1 |
| Controller parameters |   |     |     |      |
| <b>a11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>c11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>b11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>d11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>Exp. a11</b>       | 0 | 0.1 | ... | -0.1 |
| <b>Exp. c11</b>       | 0 | 0.1 | ... | -0.1 |
| <b>Exp. b11</b>       | 0 | 0.1 | ... | -0.1 |
| <b>Exp. d11</b>       | 0 | 0.1 | ... | -0.1 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a11 | $\pm 0,0000e+00$ |
| Tolerance c11 | $\pm 0,0000e+00$ |
| Tolerance b11 | $\pm 0,0000e+00$ |
| Tolerance d11 | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block TDSysTemO1.

| Test results                 |   |     |     |      |
|------------------------------|---|-----|-----|------|
| <b>Time step</b>             | 1 | 2   | ... | 6    |
| <i>Mask parameters</i>       |   |     |     |      |
| <b>A</b>                     | 0 | 0.1 | ... | -0.1 |
| <b>B</b>                     | 0 | 0.1 | ... | -0.1 |
| <b>C</b>                     | 0 | 0.1 | ... | -0.1 |
| <b>D</b>                     | 0 | 0.1 | ... | -0.1 |
| <i>Controller parameters</i> |   |     |     |      |
| <b>a11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>c11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>b11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>d11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>Exp. a11</b>              | 0 | 0.1 | ... | -0.1 |
| <b>Exp. c11</b>              | 0 | 0.1 | ... | -0.1 |
| <b>Exp. b11</b>              | 0 | 0.1 | ... | -0.1 |
| <b>Exp. d11</b>              | 0 | 0.1 | ... | -0.1 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a11 | $\pm 2,0000e-09$ |
| Tolerance c11 | $\pm 2,0000e-09$ |
| Tolerance b11 | $\pm 2,0000e-09$ |
| Tolerance d11 | $\pm 2,0000e-09$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1362 |
| Max CPU cycles  | 1406 |
| Avg CPU cycles  | 1369 |

**Verification: TDSysTemO1 Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block TDSysTemO1.

| Test results   |      |       |     |        |
|----------------|------|-------|-----|--------|
| Time step      | 1    | 2     | ... | 174    |
| CPU cycles     | 809  | 887   | ... | 1027   |
| Inputs         |      |       |     |        |
| In (DSP)       | -0   | -0.1  | ... | -0.6   |
| In             | -0   | -0.1  | ... | -0.6   |
| Parameters     |      |       |     |        |
| A              | 0.7  |       |     |        |
| B              | 0.38 |       |     |        |
| C              | 0.33 |       |     |        |
| D              | 0.1  |       |     |        |
| Outputs        |      |       |     |        |
| Out            | -0   | -0.01 | ... | -0.311 |
| Exp. Out       | -0   | -0.01 | ... | -0.311 |
| Out (DSP)      | -0   | -0.01 | ... | -0.311 |
| Exp. Out (DSP) | -0   | -0.01 | ... | -0.311 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 9,3132e-08$ ( $\pm 200$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 803  |
| Max CPU cycles  | 1370 |
| Avg CPU cycles  | 976  |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysTemO1.

| Test results          |   |     |     |      |
|-----------------------|---|-----|-----|------|
| Time step             | 1 | 2   | ... | 6    |
| Mask parameters       |   |     |     |      |
| <b>A</b>              | 0 | 0.1 | ... | -0.1 |
| <b>B</b>              | 0 | 0.1 | ... | -0.1 |
| <b>C</b>              | 0 | 0.1 | ... | -0.1 |
| <b>D</b>              | 0 | 0.1 | ... | -0.1 |
| Controller parameters |   |     |     |      |
| <b>a11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>c11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>b11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>d11</b>            | 0 | 0.1 | ... | -0.1 |
| <b>Exp. a11</b>       | 0 | 0.1 | ... | -0.1 |
| <b>Exp. c11</b>       | 0 | 0.1 | ... | -0.1 |
| <b>Exp. b11</b>       | 0 | 0.1 | ... | -0.1 |
| <b>Exp. d11</b>       | 0 | 0.1 | ... | -0.1 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a11 | $\pm 0,0000e+00$ |
| Tolerance c11 | $\pm 0,0000e+00$ |
| Tolerance b11 | $\pm 0,0000e+00$ |
| Tolerance d11 | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block TDSysSystemO1.

| Test results                 |   |     |     |      |
|------------------------------|---|-----|-----|------|
| <b>Time step</b>             | 1 | 2   | ... | 6    |
| <i>Mask parameters</i>       |   |     |     |      |
| <b>A</b>                     | 0 | 0.1 | ... | -0.1 |
| <b>B</b>                     | 0 | 0.1 | ... | -0.1 |
| <b>C</b>                     | 0 | 0.1 | ... | -0.1 |
| <b>D</b>                     | 0 | 0.1 | ... | -0.1 |
| <i>Controller parameters</i> |   |     |     |      |
| <b>a11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>c11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>b11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>d11</b>                   | 0 | 0.1 | ... | -0.1 |
| <b>Exp. a11</b>              | 0 | 0.1 | ... | -0.1 |
| <b>Exp. c11</b>              | 0 | 0.1 | ... | -0.1 |
| <b>Exp. b11</b>              | 0 | 0.1 | ... | -0.1 |
| <b>Exp. d11</b>              | 0 | 0.1 | ... | -0.1 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a11 | $\pm 2,0000e-09$ |
| Tolerance c11 | $\pm 2,0000e-09$ |
| Tolerance b11 | $\pm 2,0000e-09$ |
| Tolerance d11 | $\pm 2,0000e-09$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1418 |
| Max CPU cycles  | 2798 |
| Avg CPU cycles  | 2560 |

## Block: TDSysystemO2

$$\begin{aligned} \mathbf{x}_{k+1} &= \mathbf{A} \mathbf{x}_k + \mathbf{B} \mathbf{u}_k \\ \mathbf{y}_k &= \mathbf{x}_k \end{aligned}$$

2nd order time discrete system with two inputs and two outputs.

| Inports |          |
|---------|----------|
| In1     | Input #1 |
| In2     | Input #2 |

| Outports |           |
|----------|-----------|
| Out1     | Output #1 |
| Out2     | Output #2 |

| Mask Parameters |    |                |
|-----------------|----|----------------|
| Name            | ID | Description    |
| A               | 1  | State matrix A |
| B               | 2  | Input matrix B |

### Description:

Calculation:

$$\begin{aligned} \begin{bmatrix} x_{1,k+1} \\ x_{2,k+1} \end{bmatrix} &= \begin{bmatrix} a_{1,1} & a_{1,2} \\ a_{2,1} & a_{2,2} \end{bmatrix} \begin{bmatrix} x_{1,k} \\ x_{2,k} \end{bmatrix} + \begin{bmatrix} b_{1,1} & b_{1,2} \\ b_{2,1} & b_{2,2} \end{bmatrix} \begin{bmatrix} u_{1,k} \\ u_{2,k} \end{bmatrix} \\ \begin{bmatrix} y_{1,k} \\ y_{2,k} \end{bmatrix} &= \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix} \begin{bmatrix} x_{1,k} \\ x_{2,k} \end{bmatrix} + \begin{bmatrix} 0 & 0 \\ 0 & 0 \end{bmatrix} \begin{bmatrix} u_{1,k} \\ u_{2,k} \end{bmatrix} \end{aligned}$$

or short

$$\begin{aligned} \mathbf{x}_{k+1} &= \mathbf{A} \mathbf{x}_k + \mathbf{B} \mathbf{u}_k \\ \mathbf{y}_k &= \mathbf{x}_k \end{aligned}$$

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In1               | int8 |
| In2               | int8 |

| Outports Data Type |      |
|--------------------|------|
| Out1               | int8 |
| Out2               | int8 |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In1               | int16 |
| In2               | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out1               | int16 |
| Out2               | int16 |

### Implementation: FiP32

---

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In1               | int32 |
| In2               | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out1               | int32 |
| Out2               | int32 |

### Implementation: Float32

---

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In1               | float32 |
| In2               | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out1               | float32 |
| Out2               | float32 |

### Implementation: Float64

---

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In1               | float64 |
| In2               | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out1               | float64 |
| Out2               | float64 |



**Verification: TDSysO2 FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block TDSysO2.

| Test results    |        |        |        |        |     |        |
|-----------------|--------|--------|--------|--------|-----|--------|
| Time step       | 1      | 2      | 3      | 4      | ... | 174    |
| CPU cycles      | 171    | 171    | 171    | 171    | ... | 171    |
| Inputs          |        |        |        |        |     |        |
| In1 (DSP)       | 0      | -3271  | -6510  | -9684  | ... | -19661 |
| In2 (DSP)       | -32768 | -32604 | -32115 | -31304 | ... | -19661 |
| In1             | -0     | -0.1   | -0.199 | -0.296 | ... | -0.6   |
| In2             | -1     | -0.995 | -0.98  | -0.955 | ... | -0.6   |
| Parameters      |        |        |        |        |     |        |
| A               | [1x4]  |        |        |        |     |        |
| B               | [1x4]  |        |        |        |     |        |
| Outputs         |        |        |        |        |     |        |
| Out1            | 0      | -0.28  | -0.44  | -0.592 | ... | -0.898 |
| Out2            | 0      | -0.08  | -0.206 | -0.252 | ... | -0.432 |
| Exp. Out1       | 0      | -0.28  | -0.44  | -0.592 | ... | -0.898 |
| Exp. Out2       | 0      | -0.08  | -0.206 | -0.252 | ... | -0.432 |
| Out1 (DSP)      | 0      | -9175  | -14424 | -19405 | ... | -29414 |
| Out2 (DSP)      | 0      | -2621  | -6737  | -8259  | ... | -14158 |
| Exp. Out1 (DSP) | 0      | -9175  | -14422 | -19402 | ... | -29410 |
| Exp. Out2 (DSP) | 0      | -2621  | -6736  | -8258  | ... | -14155 |

| Test settings  |                                 |
|----------------|---------------------------------|
| Tolerance Out1 | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |
| Tolerance Out2 | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 168 |
| Max CPU cycles  | 171 |
| Avg CPU cycles  | 170 |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysO2.

| Test results                 |       |       |       |
|------------------------------|-------|-------|-------|
| Time step                    | 1     | 2     | 3     |
| <i>Mask parameters</i>       |       |       |       |
| <b>A</b>                     | [1x4] | [1x4] | [1x4] |
| <b>B</b>                     | [1x4] | [1x4] | [1x4] |
| <i>Controller parameters</i> |       |       |       |
| <b>a11</b>                   | 0     | 0     | 0     |
| <b>a22</b>                   | 30720 | 24576 | 9830  |
| <b>b21</b>                   | 20480 | 16384 | 6554  |
| <b>a21</b>                   | 20480 | 16384 | 6554  |
| <b>b12</b>                   | 20480 | 16384 | 3277  |
| <b>a12</b>                   | 20480 | 16384 | 3277  |
| <b>b11</b>                   | 0     | 0     | 0     |
| <b>b22</b>                   | 30720 | 24576 | 9830  |
| <b>sfrb12</b>                | 11    | 14    | 15    |
| <b>sfra12</b>                | 11    | 14    | 15    |
| <b>sfrb11</b>                | 15    | 15    | 15    |
| <b>sfrb22</b>                | 10    | 13    | 15    |
| <b>sfra11</b>                | 15    | 15    | 15    |
| <b>sfra22</b>                | 10    | 13    | 15    |
| <b>sfrb21</b>                | 10    | 13    | 15    |
| <b>sfra21</b>                | 10    | 13    | 15    |
| <b>Exp. a11</b>              | 0     | 0     | 0     |
| <b>Exp. a22</b>              | 30720 | 24576 | 9830  |
| <b>Exp. b21</b>              | 20480 | 16384 | 6554  |
| <b>Exp. a21</b>              | 20480 | 16384 | 6554  |
| <b>Exp. b12</b>              | 20480 | 16384 | 3277  |
| <b>Exp. a12</b>              | 20480 | 16384 | 3277  |
| <b>Exp. b11</b>              | 0     | 0     | 0     |
| <b>Exp. b22</b>              | 30720 | 24576 | 9830  |
| <b>Exp. sfrb12</b>           | 11    | 14    | 15    |
| <b>Exp. sfra12</b>           | 11    | 14    | 15    |
| <b>Exp. sfrb11</b>           | 15    | 15    | 15    |
| <b>Exp. sfrb22</b>           | 10    | 13    | 15    |
| <b>Exp. sfra11</b>           | 15    | 15    | 15    |
| <b>Exp. sfra22</b>           | 10    | 13    | 15    |
| <b>Exp. sfrb21</b>           | 10    | 13    | 15    |
| <b>Exp. sfra21</b>           | 10    | 13    | 15    |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 0,0000e+00$ |
| Tolerance a22    | $\pm 0,0000e+00$ |
| Tolerance b21    | $\pm 0,0000e+00$ |
| Tolerance a21    | $\pm 0,0000e+00$ |
| Tolerance b12    | $\pm 0,0000e+00$ |
| Tolerance a12    | $\pm 0,0000e+00$ |
| Tolerance b11    | $\pm 0,0000e+00$ |
| Tolerance b22    | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |

**Verification: TDSys<sub>tem</sub>O2 FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**Inport test for Control block TDSys<sub>tem</sub>O2.

| Test results    |        |        |        |        |     |        |
|-----------------|--------|--------|--------|--------|-----|--------|
| Time step       | 1      | 2      | 3      | 4      | ... | 174    |
| CPU cycles      | 129    | 129    | 129    | 129    | ... | 129    |
| Inputs          |        |        |        |        |     |        |
| In1 (DSP)       | 0      | -3271  | -6510  | -9684  | ... | -19661 |
| In2 (DSP)       | -32768 | -32604 | -32115 | -31304 | ... | -19661 |
| In1             | -0     | -0.1   | -0.199 | -0.296 | ... | -0.6   |
| In2             | -1     | -0.995 | -0.98  | -0.955 | ... | -0.6   |
| Parameters      |        |        |        |        |     |        |
| A               | [1x4]  |        |        |        |     |        |
| B               | [1x4]  |        |        |        |     |        |
| Outputs         |        |        |        |        |     |        |
| Out1            | 0      | -0.28  | -0.44  | -0.592 | ... | -0.898 |
| Out2            | 0      | -0.08  | -0.206 | -0.252 | ... | -0.432 |
| Exp. Out1       | 0      | -0.28  | -0.44  | -0.592 | ... | -0.898 |
| Exp. Out2       | 0      | -0.08  | -0.206 | -0.252 | ... | -0.432 |
| Out1 (DSP)      | 0      | -9175  | -14424 | -19405 | ... | -29414 |
| Out2 (DSP)      | 0      | -2621  | -6737  | -8259  | ... | -14158 |
| Exp. Out1 (DSP) | 0      | -9175  | -14422 | -19402 | ... | -29410 |
| Exp. Out2 (DSP) | 0      | -2621  | -6736  | -8258  | ... | -14155 |

| Test settings  |                                 |
|----------------|---------------------------------|
| Tolerance Out1 | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |
| Tolerance Out2 | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 125 |
| Max CPU cycles  | 129 |
| Avg CPU cycles  | 128 |

**Test case: Conversion test****OK**Conversion test for Control block TDSys<sub>tem</sub>O2.

| Test results                 |       |       |       |
|------------------------------|-------|-------|-------|
| Time step                    | 1     | 2     | 3     |
| <i>Mask parameters</i>       |       |       |       |
| <b>A</b>                     | [1x4] | [1x4] | [1x4] |
| <b>B</b>                     | [1x4] | [1x4] | [1x4] |
| <i>Controller parameters</i> |       |       |       |
| <b>a11</b>                   | 0     | 0     | 0     |
| <b>a22</b>                   | 30720 | 24576 | 9830  |
| <b>b21</b>                   | 20480 | 16384 | 6554  |
| <b>a21</b>                   | 20480 | 16384 | 6554  |
| <b>b12</b>                   | 20480 | 16384 | 3277  |
| <b>a12</b>                   | 20480 | 16384 | 3277  |
| <b>b11</b>                   | 0     | 0     | 0     |
| <b>b22</b>                   | 30720 | 24576 | 9830  |
| <b>sfrb12</b>                | 11    | 14    | 15    |
| <b>sfra12</b>                | 11    | 14    | 15    |
| <b>sfrb11</b>                | 15    | 15    | 15    |
| <b>sfrb22</b>                | 10    | 13    | 15    |
| <b>sfra11</b>                | 15    | 15    | 15    |
| <b>sfra22</b>                | 10    | 13    | 15    |
| <b>sfrb21</b>                | 10    | 13    | 15    |
| <b>sfra21</b>                | 10    | 13    | 15    |
| <b>Exp. a11</b>              | 0     | 0     | 0     |
| <b>Exp. a22</b>              | 30720 | 24576 | 9830  |
| <b>Exp. b21</b>              | 20480 | 16384 | 6554  |
| <b>Exp. a21</b>              | 20480 | 16384 | 6554  |
| <b>Exp. b12</b>              | 20480 | 16384 | 3277  |
| <b>Exp. a12</b>              | 20480 | 16384 | 3277  |
| <b>Exp. b11</b>              | 0     | 0     | 0     |
| <b>Exp. b22</b>              | 30720 | 24576 | 9830  |
| <b>Exp. sfrb12</b>           | 11    | 14    | 15    |
| <b>Exp. sfra12</b>           | 11    | 14    | 15    |
| <b>Exp. sfrb11</b>           | 15    | 15    | 15    |
| <b>Exp. sfrb22</b>           | 10    | 13    | 15    |
| <b>Exp. sfra11</b>           | 15    | 15    | 15    |
| <b>Exp. sfra22</b>           | 10    | 13    | 15    |
| <b>Exp. sfrb21</b>           | 10    | 13    | 15    |
| <b>Exp. sfra21</b>           | 10    | 13    | 15    |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 0,0000e+00$ |
| Tolerance a22    | $\pm 0,0000e+00$ |
| Tolerance b21    | $\pm 0,0000e+00$ |
| Tolerance a21    | $\pm 0,0000e+00$ |
| Tolerance b12    | $\pm 0,0000e+00$ |
| Tolerance a12    | $\pm 0,0000e+00$ |
| Tolerance b11    | $\pm 0,0000e+00$ |
| Tolerance b22    | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |

**Verification: TDSysO2 FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block TDSysO2.

| Test results    |        |        |        |        |     |        |
|-----------------|--------|--------|--------|--------|-----|--------|
| Time step       | 1      | 2      | 3      | 4      | ... | 174    |
| CPU cycles      | 173    | 173    | 173    | 173    | ... | 173    |
| Inputs          |        |        |        |        |     |        |
| In1 (DSP)       | 0      | -3271  | -6510  | -9684  | ... | -19661 |
| In2 (DSP)       | -32768 | -32604 | -32115 | -31304 | ... | -19661 |
| In1             | -0     | -0.1   | -0.199 | -0.296 | ... | -0.6   |
| In2             | -1     | -0.995 | -0.98  | -0.955 | ... | -0.6   |
| Parameters      |        |        |        |        |     |        |
| A               | [1x4]  |        |        |        |     |        |
| B               | [1x4]  |        |        |        |     |        |
| Outputs         |        |        |        |        |     |        |
| Out1            | 0      | -0.28  | -0.44  | -0.592 | ... | -0.898 |
| Out2            | 0      | -0.08  | -0.206 | -0.252 | ... | -0.432 |
| Exp. Out1       | 0      | -0.28  | -0.44  | -0.592 | ... | -0.898 |
| Exp. Out2       | 0      | -0.08  | -0.206 | -0.252 | ... | -0.432 |
| Out1 (DSP)      | 0      | -9175  | -14424 | -19405 | ... | -29414 |
| Out2 (DSP)      | 0      | -2621  | -6737  | -8259  | ... | -14158 |
| Exp. Out1 (DSP) | 0      | -9175  | -14422 | -19402 | ... | -29410 |
| Exp. Out2 (DSP) | 0      | -2621  | -6736  | -8258  | ... | -14155 |

| Test settings  |                                 |
|----------------|---------------------------------|
| Tolerance Out1 | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |
| Tolerance Out2 | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 173 |
| Max CPU cycles  | 173 |
| Avg CPU cycles  | 173 |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysO2.

| Test results                 |       |       |       |
|------------------------------|-------|-------|-------|
| Time step                    | 1     | 2     | 3     |
| <i>Mask parameters</i>       |       |       |       |
| <b>A</b>                     | [1x4] | [1x4] | [1x4] |
| <b>B</b>                     | [1x4] | [1x4] | [1x4] |
| <i>Controller parameters</i> |       |       |       |
| <b>a11</b>                   | 0     | 0     | 0     |
| <b>a22</b>                   | 30720 | 24576 | 9830  |
| <b>b21</b>                   | 20480 | 16384 | 6554  |
| <b>a21</b>                   | 20480 | 16384 | 6554  |
| <b>b12</b>                   | 20480 | 16384 | 3277  |
| <b>a12</b>                   | 20480 | 16384 | 3277  |
| <b>b11</b>                   | 0     | 0     | 0     |
| <b>b22</b>                   | 30720 | 24576 | 9830  |
| <b>sfrb12</b>                | 11    | 14    | 15    |
| <b>sfra12</b>                | 11    | 14    | 15    |
| <b>sfrb11</b>                | 15    | 15    | 15    |
| <b>sfrb22</b>                | 10    | 13    | 15    |
| <b>sfra11</b>                | 15    | 15    | 15    |
| <b>sfra22</b>                | 10    | 13    | 15    |
| <b>sfrb21</b>                | 10    | 13    | 15    |
| <b>sfra21</b>                | 10    | 13    | 15    |
| <b>Exp. a11</b>              | 0     | 0     | 0     |
| <b>Exp. a22</b>              | 30720 | 24576 | 9830  |
| <b>Exp. b21</b>              | 20480 | 16384 | 6554  |
| <b>Exp. a21</b>              | 20480 | 16384 | 6554  |
| <b>Exp. b12</b>              | 20480 | 16384 | 3277  |
| <b>Exp. a12</b>              | 20480 | 16384 | 3277  |
| <b>Exp. b11</b>              | 0     | 0     | 0     |
| <b>Exp. b22</b>              | 30720 | 24576 | 9830  |
| <b>Exp. sfrb12</b>           | 11    | 14    | 15    |
| <b>Exp. sfra12</b>           | 11    | 14    | 15    |
| <b>Exp. sfrb11</b>           | 15    | 15    | 15    |
| <b>Exp. sfrb22</b>           | 10    | 13    | 15    |
| <b>Exp. sfra11</b>           | 15    | 15    | 15    |
| <b>Exp. sfra22</b>           | 10    | 13    | 15    |
| <b>Exp. sfrb21</b>           | 10    | 13    | 15    |
| <b>Exp. sfra21</b>           | 10    | 13    | 15    |



| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 0,0000e+00$ |
| Tolerance a22    | $\pm 0,0000e+00$ |
| Tolerance b21    | $\pm 0,0000e+00$ |
| Tolerance a21    | $\pm 0,0000e+00$ |
| Tolerance b12    | $\pm 0,0000e+00$ |
| Tolerance a12    | $\pm 0,0000e+00$ |
| Tolerance b11    | $\pm 0,0000e+00$ |
| Tolerance b22    | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |

**Verification: TDSysO2 FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block TDSysO2.

| Test results    |        |        |        |        |     |        |
|-----------------|--------|--------|--------|--------|-----|--------|
| Time step       | 1      | 2      | 3      | 4      | ... | 174    |
| CPU cycles      | 172    | 172    | 172    | 172    | ... | 172    |
| Inputs          |        |        |        |        |     |        |
| In1 (DSP)       | 0      | -3271  | -6510  | -9684  | ... | -19661 |
| In2 (DSP)       | -32768 | -32604 | -32115 | -31304 | ... | -19661 |
| In1             | -0     | -0.1   | -0.199 | -0.296 | ... | -0.6   |
| In2             | -1     | -0.995 | -0.98  | -0.955 | ... | -0.6   |
| Parameters      |        |        |        |        |     |        |
| A               | [1x4]  |        |        |        |     |        |
| B               | [1x4]  |        |        |        |     |        |
| Outputs         |        |        |        |        |     |        |
| Out1            | 0      | -0.28  | -0.44  | -0.592 | ... | -0.898 |
| Out2            | 0      | -0.08  | -0.206 | -0.252 | ... | -0.432 |
| Exp. Out1       | 0      | -0.28  | -0.44  | -0.592 | ... | -0.898 |
| Exp. Out2       | 0      | -0.08  | -0.206 | -0.252 | ... | -0.432 |
| Out1 (DSP)      | 0      | -9175  | -14424 | -19405 | ... | -29414 |
| Out2 (DSP)      | 0      | -2621  | -6737  | -8259  | ... | -14158 |
| Exp. Out1 (DSP) | 0      | -9175  | -14422 | -19402 | ... | -29410 |
| Exp. Out2 (DSP) | 0      | -2621  | -6736  | -8258  | ... | -14155 |

| Test settings  |                                 |
|----------------|---------------------------------|
| Tolerance Out1 | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |
| Tolerance Out2 | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 171 |
| Max CPU cycles  | 232 |
| Avg CPU cycles  | 172 |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysO2.

| Test results                 |       |       |       |
|------------------------------|-------|-------|-------|
| Time step                    | 1     | 2     | 3     |
| <i>Mask parameters</i>       |       |       |       |
| <b>A</b>                     | [1x4] | [1x4] | [1x4] |
| <b>B</b>                     | [1x4] | [1x4] | [1x4] |
| <i>Controller parameters</i> |       |       |       |
| <b>a11</b>                   | 0     | 0     | 0     |
| <b>a22</b>                   | 30720 | 24576 | 9830  |
| <b>b21</b>                   | 20480 | 16384 | 6554  |
| <b>a21</b>                   | 20480 | 16384 | 6554  |
| <b>b12</b>                   | 20480 | 16384 | 3277  |
| <b>a12</b>                   | 20480 | 16384 | 3277  |
| <b>b11</b>                   | 0     | 0     | 0     |
| <b>b22</b>                   | 30720 | 24576 | 9830  |
| <b>sfrb12</b>                | 11    | 14    | 15    |
| <b>sfra12</b>                | 11    | 14    | 15    |
| <b>sfrb11</b>                | 15    | 15    | 15    |
| <b>sfrb22</b>                | 10    | 13    | 15    |
| <b>sfra11</b>                | 15    | 15    | 15    |
| <b>sfra22</b>                | 10    | 13    | 15    |
| <b>sfrb21</b>                | 10    | 13    | 15    |
| <b>sfra21</b>                | 10    | 13    | 15    |
| <b>Exp. a11</b>              | 0     | 0     | 0     |
| <b>Exp. a22</b>              | 30720 | 24576 | 9830  |
| <b>Exp. b21</b>              | 20480 | 16384 | 6554  |
| <b>Exp. a21</b>              | 20480 | 16384 | 6554  |
| <b>Exp. b12</b>              | 20480 | 16384 | 3277  |
| <b>Exp. a12</b>              | 20480 | 16384 | 3277  |
| <b>Exp. b11</b>              | 0     | 0     | 0     |
| <b>Exp. b22</b>              | 30720 | 24576 | 9830  |
| <b>Exp. sfrb12</b>           | 11    | 14    | 15    |
| <b>Exp. sfra12</b>           | 11    | 14    | 15    |
| <b>Exp. sfrb11</b>           | 15    | 15    | 15    |
| <b>Exp. sfrb22</b>           | 10    | 13    | 15    |
| <b>Exp. sfra11</b>           | 15    | 15    | 15    |
| <b>Exp. sfra22</b>           | 10    | 13    | 15    |
| <b>Exp. sfrb21</b>           | 10    | 13    | 15    |
| <b>Exp. sfra21</b>           | 10    | 13    | 15    |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 0,0000e+00$ |
| Tolerance a22    | $\pm 0,0000e+00$ |
| Tolerance b21    | $\pm 0,0000e+00$ |
| Tolerance a21    | $\pm 0,0000e+00$ |
| Tolerance b12    | $\pm 0,0000e+00$ |
| Tolerance a12    | $\pm 0,0000e+00$ |
| Tolerance b11    | $\pm 0,0000e+00$ |
| Tolerance b22    | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |

**Verification: TDSysO2 FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block TDSysO2.

| Test results    |        |        |        |        |     |        |
|-----------------|--------|--------|--------|--------|-----|--------|
| Time step       | 1      | 2      | 3      | 4      | ... | 174    |
| CPU cycles      | 143    | 143    | 143    | 143    | ... | 143    |
| Inputs          |        |        |        |        |     |        |
| In1 (DSP)       | 0      | -3271  | -6510  | -9684  | ... | -19661 |
| In2 (DSP)       | -32768 | -32604 | -32115 | -31304 | ... | -19661 |
| In1             | -0     | -0.1   | -0.199 | -0.296 | ... | -0.6   |
| In2             | -1     | -0.995 | -0.98  | -0.955 | ... | -0.6   |
| Parameters      |        |        |        |        |     |        |
| A               | [1x4]  |        |        |        |     |        |
| B               | [1x4]  |        |        |        |     |        |
| Outputs         |        |        |        |        |     |        |
| Out1            | 0      | -0.28  | -0.44  | -0.592 | ... | -0.898 |
| Out2            | 0      | -0.08  | -0.206 | -0.252 | ... | -0.432 |
| Exp. Out1       | 0      | -0.28  | -0.44  | -0.592 | ... | -0.898 |
| Exp. Out2       | 0      | -0.08  | -0.206 | -0.252 | ... | -0.432 |
| Out1 (DSP)      | 0      | -9175  | -14424 | -19405 | ... | -29414 |
| Out2 (DSP)      | 0      | -2621  | -6737  | -8259  | ... | -14158 |
| Exp. Out1 (DSP) | 0      | -9175  | -14422 | -19402 | ... | -29410 |
| Exp. Out2 (DSP) | 0      | -2621  | -6736  | -8258  | ... | -14155 |

| Test settings  |                                 |
|----------------|---------------------------------|
| Tolerance Out1 | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |
| Tolerance Out2 | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 143 |
| Max CPU cycles  | 143 |
| Avg CPU cycles  | 143 |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysO2.

| Test results                 |       |       |       |
|------------------------------|-------|-------|-------|
| Time step                    | 1     | 2     | 3     |
| <i>Mask parameters</i>       |       |       |       |
| <b>A</b>                     | [1x4] | [1x4] | [1x4] |
| <b>B</b>                     | [1x4] | [1x4] | [1x4] |
| <i>Controller parameters</i> |       |       |       |
| <b>a11</b>                   | 0     | 0     | 0     |
| <b>a22</b>                   | 30720 | 24576 | 9830  |
| <b>b21</b>                   | 20480 | 16384 | 6554  |
| <b>a21</b>                   | 20480 | 16384 | 6554  |
| <b>b12</b>                   | 20480 | 16384 | 3277  |
| <b>a12</b>                   | 20480 | 16384 | 3277  |
| <b>b11</b>                   | 0     | 0     | 0     |
| <b>b22</b>                   | 30720 | 24576 | 9830  |
| <b>sfrb12</b>                | 11    | 14    | 15    |
| <b>sfra12</b>                | 11    | 14    | 15    |
| <b>sfrb11</b>                | 15    | 15    | 15    |
| <b>sfrb22</b>                | 10    | 13    | 15    |
| <b>sfra11</b>                | 15    | 15    | 15    |
| <b>sfra22</b>                | 10    | 13    | 15    |
| <b>sfrb21</b>                | 10    | 13    | 15    |
| <b>sfra21</b>                | 10    | 13    | 15    |
| <b>Exp. a11</b>              | 0     | 0     | 0     |
| <b>Exp. a22</b>              | 30720 | 24576 | 9830  |
| <b>Exp. b21</b>              | 20480 | 16384 | 6554  |
| <b>Exp. a21</b>              | 20480 | 16384 | 6554  |
| <b>Exp. b12</b>              | 20480 | 16384 | 3277  |
| <b>Exp. a12</b>              | 20480 | 16384 | 3277  |
| <b>Exp. b11</b>              | 0     | 0     | 0     |
| <b>Exp. b22</b>              | 30720 | 24576 | 9830  |
| <b>Exp. sfrb12</b>           | 11    | 14    | 15    |
| <b>Exp. sfra12</b>           | 11    | 14    | 15    |
| <b>Exp. sfrb11</b>           | 15    | 15    | 15    |
| <b>Exp. sfrb22</b>           | 10    | 13    | 15    |
| <b>Exp. sfra11</b>           | 15    | 15    | 15    |
| <b>Exp. sfra22</b>           | 10    | 13    | 15    |
| <b>Exp. sfrb21</b>           | 10    | 13    | 15    |
| <b>Exp. sfra21</b>           | 10    | 13    | 15    |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 0,0000e+00$ |
| Tolerance a22    | $\pm 0,0000e+00$ |
| Tolerance b21    | $\pm 0,0000e+00$ |
| Tolerance a21    | $\pm 0,0000e+00$ |
| Tolerance b12    | $\pm 0,0000e+00$ |
| Tolerance a12    | $\pm 0,0000e+00$ |
| Tolerance b11    | $\pm 0,0000e+00$ |
| Tolerance b22    | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |

**Verification: TDSys<sub>tem</sub>O2 FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**Inport test for Control block TDSys<sub>tem</sub>O2.

| Test results    |        |        |        |        |     |        |
|-----------------|--------|--------|--------|--------|-----|--------|
| Time step       | 1      | 2      | 3      | 4      | ... | 174    |
| CPU cycles      | 195    | 161    | 161    | 161    | ... | 161    |
| Inputs          |        |        |        |        |     |        |
| In1 (DSP)       | 0      | -3271  | -6510  | -9684  | ... | -19661 |
| In2 (DSP)       | -32768 | -32604 | -32115 | -31304 | ... | -19661 |
| In1             | -0     | -0.1   | -0.199 | -0.296 | ... | -0.6   |
| In2             | -1     | -0.995 | -0.98  | -0.955 | ... | -0.6   |
| Parameters      |        |        |        |        |     |        |
| A               | [1x4]  |        |        |        |     |        |
| B               | [1x4]  |        |        |        |     |        |
| Outputs         |        |        |        |        |     |        |
| Out1            | 0      | -0.28  | -0.44  | -0.592 | ... | -0.898 |
| Out2            | 0      | -0.08  | -0.206 | -0.252 | ... | -0.432 |
| Exp. Out1       | 0      | -0.28  | -0.44  | -0.592 | ... | -0.898 |
| Exp. Out2       | 0      | -0.08  | -0.206 | -0.252 | ... | -0.432 |
| Out1 (DSP)      | 0      | -9175  | -14424 | -19405 | ... | -29414 |
| Out2 (DSP)      | 0      | -2621  | -6737  | -8259  | ... | -14158 |
| Exp. Out1 (DSP) | 0      | -9175  | -14422 | -19402 | ... | -29410 |
| Exp. Out2 (DSP) | 0      | -2621  | -6736  | -8258  | ... | -14155 |

| Test settings  |                                 |
|----------------|---------------------------------|
| Tolerance Out1 | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |
| Tolerance Out2 | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 161 |
| Max CPU cycles  | 195 |
| Avg CPU cycles  | 161 |

**Test case: Conversion test****OK**Conversion test for Control block TDSys<sub>tem</sub>O2.



| Test results                 |       |       |       |
|------------------------------|-------|-------|-------|
| Time step                    | 1     | 2     | 3     |
| <i>Mask parameters</i>       |       |       |       |
| <b>A</b>                     | [1x4] | [1x4] | [1x4] |
| <b>B</b>                     | [1x4] | [1x4] | [1x4] |
| <i>Controller parameters</i> |       |       |       |
| <b>a11</b>                   | 0     | 0     | 0     |
| <b>a22</b>                   | 30720 | 24576 | 9830  |
| <b>b21</b>                   | 20480 | 16384 | 6554  |
| <b>a21</b>                   | 20480 | 16384 | 6554  |
| <b>b12</b>                   | 20480 | 16384 | 3277  |
| <b>a12</b>                   | 20480 | 16384 | 3277  |
| <b>b11</b>                   | 0     | 0     | 0     |
| <b>b22</b>                   | 30720 | 24576 | 9830  |
| <b>sfrb12</b>                | 11    | 14    | 15    |
| <b>sfra12</b>                | 11    | 14    | 15    |
| <b>sfrb11</b>                | 15    | 15    | 15    |
| <b>sfrb22</b>                | 10    | 13    | 15    |
| <b>sfra11</b>                | 15    | 15    | 15    |
| <b>sfra22</b>                | 10    | 13    | 15    |
| <b>sfrb21</b>                | 10    | 13    | 15    |
| <b>sfra21</b>                | 10    | 13    | 15    |
| <b>Exp. a11</b>              | 0     | 0     | 0     |
| <b>Exp. a22</b>              | 30720 | 24576 | 9830  |
| <b>Exp. b21</b>              | 20480 | 16384 | 6554  |
| <b>Exp. a21</b>              | 20480 | 16384 | 6554  |
| <b>Exp. b12</b>              | 20480 | 16384 | 3277  |
| <b>Exp. a12</b>              | 20480 | 16384 | 3277  |
| <b>Exp. b11</b>              | 0     | 0     | 0     |
| <b>Exp. b22</b>              | 30720 | 24576 | 9830  |
| <b>Exp. sfrb12</b>           | 11    | 14    | 15    |
| <b>Exp. sfra12</b>           | 11    | 14    | 15    |
| <b>Exp. sfrb11</b>           | 15    | 15    | 15    |
| <b>Exp. sfrb22</b>           | 10    | 13    | 15    |
| <b>Exp. sfra11</b>           | 15    | 15    | 15    |
| <b>Exp. sfra22</b>           | 10    | 13    | 15    |
| <b>Exp. sfrb21</b>           | 10    | 13    | 15    |
| <b>Exp. sfra21</b>           | 10    | 13    | 15    |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 0,0000e+00$ |
| Tolerance a22    | $\pm 0,0000e+00$ |
| Tolerance b21    | $\pm 0,0000e+00$ |
| Tolerance a21    | $\pm 0,0000e+00$ |
| Tolerance b12    | $\pm 0,0000e+00$ |
| Tolerance a12    | $\pm 0,0000e+00$ |
| Tolerance b11    | $\pm 0,0000e+00$ |
| Tolerance b22    | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |

**Verification: TDSysO2 FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block TDSysO2.

| Test results    |        |        |        |        |     |        |
|-----------------|--------|--------|--------|--------|-----|--------|
| Time step       | 1      | 2      | 3      | 4      | ... | 174    |
| CPU cycles      | 165    | 165    | 165    | 165    | ... | 165    |
| Inputs          |        |        |        |        |     |        |
| In1 (DSP)       | 0      | -3271  | -6510  | -9684  | ... | -19661 |
| In2 (DSP)       | -32768 | -32604 | -32115 | -31304 | ... | -19661 |
| In1             | -0     | -0.1   | -0.199 | -0.296 | ... | -0.6   |
| In2             | -1     | -0.995 | -0.98  | -0.955 | ... | -0.6   |
| Parameters      |        |        |        |        |     |        |
| A               | [1x4]  |        |        |        |     |        |
| B               | [1x4]  |        |        |        |     |        |
| Outputs         |        |        |        |        |     |        |
| Out1            | 0      | -0.28  | -0.44  | -0.592 | ... | -0.898 |
| Out2            | 0      | -0.08  | -0.206 | -0.252 | ... | -0.432 |
| Exp. Out1       | 0      | -0.28  | -0.44  | -0.592 | ... | -0.898 |
| Exp. Out2       | 0      | -0.08  | -0.206 | -0.252 | ... | -0.432 |
| Out1 (DSP)      | 0      | -9175  | -14424 | -19405 | ... | -29414 |
| Out2 (DSP)      | 0      | -2621  | -6737  | -8259  | ... | -14158 |
| Exp. Out1 (DSP) | 0      | -9175  | -14422 | -19402 | ... | -29410 |
| Exp. Out2 (DSP) | 0      | -2621  | -6736  | -8258  | ... | -14155 |

| Test settings  |                                 |
|----------------|---------------------------------|
| Tolerance Out1 | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |
| Tolerance Out2 | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 165 |
| Max CPU cycles  | 166 |
| Avg CPU cycles  | 165 |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysO2.

| Test results                 |       |       |       |
|------------------------------|-------|-------|-------|
| Time step                    | 1     | 2     | 3     |
| <i>Mask parameters</i>       |       |       |       |
| <b>A</b>                     | [1x4] | [1x4] | [1x4] |
| <b>B</b>                     | [1x4] | [1x4] | [1x4] |
| <i>Controller parameters</i> |       |       |       |
| <b>a11</b>                   | 0     | 0     | 0     |
| <b>a22</b>                   | 30720 | 24576 | 9830  |
| <b>b21</b>                   | 20480 | 16384 | 6554  |
| <b>a21</b>                   | 20480 | 16384 | 6554  |
| <b>b12</b>                   | 20480 | 16384 | 3277  |
| <b>a12</b>                   | 20480 | 16384 | 3277  |
| <b>b11</b>                   | 0     | 0     | 0     |
| <b>b22</b>                   | 30720 | 24576 | 9830  |
| <b>sfrb12</b>                | 11    | 14    | 15    |
| <b>sfra12</b>                | 11    | 14    | 15    |
| <b>sfrb11</b>                | 15    | 15    | 15    |
| <b>sfrb22</b>                | 10    | 13    | 15    |
| <b>sfra11</b>                | 15    | 15    | 15    |
| <b>sfra22</b>                | 10    | 13    | 15    |
| <b>sfrb21</b>                | 10    | 13    | 15    |
| <b>sfra21</b>                | 10    | 13    | 15    |
| <b>Exp. a11</b>              | 0     | 0     | 0     |
| <b>Exp. a22</b>              | 30720 | 24576 | 9830  |
| <b>Exp. b21</b>              | 20480 | 16384 | 6554  |
| <b>Exp. a21</b>              | 20480 | 16384 | 6554  |
| <b>Exp. b12</b>              | 20480 | 16384 | 3277  |
| <b>Exp. a12</b>              | 20480 | 16384 | 3277  |
| <b>Exp. b11</b>              | 0     | 0     | 0     |
| <b>Exp. b22</b>              | 30720 | 24576 | 9830  |
| <b>Exp. sfrb12</b>           | 11    | 14    | 15    |
| <b>Exp. sfra12</b>           | 11    | 14    | 15    |
| <b>Exp. sfrb11</b>           | 15    | 15    | 15    |
| <b>Exp. sfrb22</b>           | 10    | 13    | 15    |
| <b>Exp. sfra11</b>           | 15    | 15    | 15    |
| <b>Exp. sfra22</b>           | 10    | 13    | 15    |
| <b>Exp. sfrb21</b>           | 10    | 13    | 15    |
| <b>Exp. sfra21</b>           | 10    | 13    | 15    |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 0,0000e+00$ |
| Tolerance a22    | $\pm 0,0000e+00$ |
| Tolerance b21    | $\pm 0,0000e+00$ |
| Tolerance a21    | $\pm 0,0000e+00$ |
| Tolerance b12    | $\pm 0,0000e+00$ |
| Tolerance a12    | $\pm 0,0000e+00$ |
| Tolerance b11    | $\pm 0,0000e+00$ |
| Tolerance b22    | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |

**Verification: TDSys<sub>tem</sub>O2 FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**Inport test for Control block TDSys<sub>tem</sub>O2.

| Test results    |        |        |        |        |     |        |
|-----------------|--------|--------|--------|--------|-----|--------|
| Time step       | 1      | 2      | 3      | 4      | ... | 174    |
| CPU cycles      | 203    | 203    | 203    | 203    | ... | 203    |
| Inputs          |        |        |        |        |     |        |
| In1 (DSP)       | 0      | -3271  | -6510  | -9684  | ... | -19661 |
| In2 (DSP)       | -32768 | -32604 | -32115 | -31304 | ... | -19661 |
| In1             | -0     | -0.1   | -0.199 | -0.296 | ... | -0.6   |
| In2             | -1     | -0.995 | -0.98  | -0.955 | ... | -0.6   |
| Parameters      |        |        |        |        |     |        |
| A               | [1x4]  |        |        |        |     |        |
| B               | [1x4]  |        |        |        |     |        |
| Outputs         |        |        |        |        |     |        |
| Out1            | 0      | -0.28  | -0.44  | -0.592 | ... | -0.898 |
| Out2            | 0      | -0.08  | -0.206 | -0.252 | ... | -0.432 |
| Exp. Out1       | 0      | -0.28  | -0.44  | -0.592 | ... | -0.898 |
| Exp. Out2       | 0      | -0.08  | -0.206 | -0.252 | ... | -0.432 |
| Out1 (DSP)      | 0      | -9175  | -14424 | -19405 | ... | -29414 |
| Out2 (DSP)      | 0      | -2621  | -6737  | -8259  | ... | -14158 |
| Exp. Out1 (DSP) | 0      | -9175  | -14422 | -19402 | ... | -29410 |
| Exp. Out2 (DSP) | 0      | -2621  | -6736  | -8258  | ... | -14155 |

| Test settings  |                                 |
|----------------|---------------------------------|
| Tolerance Out1 | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |
| Tolerance Out2 | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 202 |
| Max CPU cycles  | 203 |
| Avg CPU cycles  | 202 |

**Test case: Conversion test****OK**Conversion test for Control block TDSys<sub>tem</sub>O2.

| Test results                 |       |       |       |
|------------------------------|-------|-------|-------|
| Time step                    | 1     | 2     | 3     |
| <i>Mask parameters</i>       |       |       |       |
| <b>A</b>                     | [1x4] | [1x4] | [1x4] |
| <b>B</b>                     | [1x4] | [1x4] | [1x4] |
| <i>Controller parameters</i> |       |       |       |
| <b>a11</b>                   | 0     | 0     | 0     |
| <b>a22</b>                   | 30720 | 24576 | 9830  |
| <b>b21</b>                   | 20480 | 16384 | 6554  |
| <b>a21</b>                   | 20480 | 16384 | 6554  |
| <b>b12</b>                   | 20480 | 16384 | 3277  |
| <b>a12</b>                   | 20480 | 16384 | 3277  |
| <b>b11</b>                   | 0     | 0     | 0     |
| <b>b22</b>                   | 30720 | 24576 | 9830  |
| <b>sfrb12</b>                | 11    | 14    | 15    |
| <b>sfra12</b>                | 11    | 14    | 15    |
| <b>sfrb11</b>                | 15    | 15    | 15    |
| <b>sfrb22</b>                | 10    | 13    | 15    |
| <b>sfra11</b>                | 15    | 15    | 15    |
| <b>sfra22</b>                | 10    | 13    | 15    |
| <b>sfrb21</b>                | 10    | 13    | 15    |
| <b>sfra21</b>                | 10    | 13    | 15    |
| <b>Exp. a11</b>              | 0     | 0     | 0     |
| <b>Exp. a22</b>              | 30720 | 24576 | 9830  |
| <b>Exp. b21</b>              | 20480 | 16384 | 6554  |
| <b>Exp. a21</b>              | 20480 | 16384 | 6554  |
| <b>Exp. b12</b>              | 20480 | 16384 | 3277  |
| <b>Exp. a12</b>              | 20480 | 16384 | 3277  |
| <b>Exp. b11</b>              | 0     | 0     | 0     |
| <b>Exp. b22</b>              | 30720 | 24576 | 9830  |
| <b>Exp. sfrb12</b>           | 11    | 14    | 15    |
| <b>Exp. sfra12</b>           | 11    | 14    | 15    |
| <b>Exp. sfrb11</b>           | 15    | 15    | 15    |
| <b>Exp. sfrb22</b>           | 10    | 13    | 15    |
| <b>Exp. sfra11</b>           | 15    | 15    | 15    |
| <b>Exp. sfra22</b>           | 10    | 13    | 15    |
| <b>Exp. sfrb21</b>           | 10    | 13    | 15    |
| <b>Exp. sfra21</b>           | 10    | 13    | 15    |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 0,0000e+00$ |
| Tolerance a22    | $\pm 0,0000e+00$ |
| Tolerance b21    | $\pm 0,0000e+00$ |
| Tolerance a21    | $\pm 0,0000e+00$ |
| Tolerance b12    | $\pm 0,0000e+00$ |
| Tolerance a12    | $\pm 0,0000e+00$ |
| Tolerance b11    | $\pm 0,0000e+00$ |
| Tolerance b22    | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |



**Verification: TDSysmO2 FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block TDSysmO2.

| Test results    |             |             |     |             |
|-----------------|-------------|-------------|-----|-------------|
| Time step       | 1           | 2           | ... | 174         |
| CPU cycles      | 473         | 473         | ... | 473         |
| Inputs          |             |             |     |             |
| In1 (DSP)       | 0           | -214390630  | ... | -1288490189 |
| In2 (DSP)       | -2147483648 | -2136755175 | ... | -1288490189 |
| In1             | -0          | -0.1        | ... | -0.6        |
| In2             | -1          | -0.995      | ... | -0.6        |
| Parameters      |             |             |     |             |
| A               | [1x4]       |             |     |             |
| B               | [1x4]       |             |     |             |
| Outputs         |             |             |     |             |
| Out1            | 0           | -0.28       | ... | -0.898      |
| Out2            | 0           | -0.08       | ... | -0.432      |
| Exp. Out1       | 0           | -0.28       | ... | -0.898      |
| Exp. Out2       | 0           | -0.08       | ... | -0.432      |
| Out1 (DSP)      | 0           | -601295421  | ... | -1927381242 |
| Out2 (DSP)      | 0           | -171798692  | ... | -927641873  |
| Exp. Out1 (DSP) | 0           | -601295421  | ... | -1927381237 |
| Exp. Out2 (DSP) | 0           | -171798692  | ... | -927641869  |

| Test settings  |                                 |
|----------------|---------------------------------|
| Tolerance Out1 | $\pm 3,7253e-09$ ( $\pm 8$ LSB) |
| Tolerance Out2 | $\pm 3,7253e-09$ ( $\pm 8$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 411 |
| Max CPU cycles  | 477 |
| Avg CPU cycles  | 460 |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysmO2.



| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 0,0000e+00$ |
| Tolerance a22    | $\pm 0,0000e+00$ |
| Tolerance b21    | $\pm 0,0000e+00$ |
| Tolerance a21    | $\pm 0,0000e+00$ |
| Tolerance b12    | $\pm 0,0000e+00$ |
| Tolerance a12    | $\pm 0,0000e+00$ |
| Tolerance b11    | $\pm 0,0000e+00$ |
| Tolerance b22    | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |

**Verification: TDSysmO2 FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block TDSysmO2.

| Test results    |             |             |     |             |
|-----------------|-------------|-------------|-----|-------------|
| Time step       | 1           | 2           | ... | 174         |
| CPU cycles      | 351         | 351         | ... | 351         |
| Inputs          |             |             |     |             |
| In1 (DSP)       | 0           | -214390630  | ... | -1288490189 |
| In2 (DSP)       | -2147483648 | -2136755175 | ... | -1288490189 |
| In1             | -0          | -0.1        | ... | -0.6        |
| In2             | -1          | -0.995      | ... | -0.6        |
| Parameters      |             |             |     |             |
| A               | [1x4]       |             |     |             |
| B               | [1x4]       |             |     |             |
| Outputs         |             |             |     |             |
| Out1            | 0           | -0.28       | ... | -0.898      |
| Out2            | 0           | -0.08       | ... | -0.432      |
| Exp. Out1       | 0           | -0.28       | ... | -0.898      |
| Exp. Out2       | 0           | -0.08       | ... | -0.432      |
| Out1 (DSP)      | 0           | -601295421  | ... | -1927381242 |
| Out2 (DSP)      | 0           | -171798692  | ... | -927641873  |
| Exp. Out1 (DSP) | 0           | -601295421  | ... | -1927381237 |
| Exp. Out2 (DSP) | 0           | -171798692  | ... | -927641869  |

| Test settings  |                                 |
|----------------|---------------------------------|
| Tolerance Out1 | $\pm 3,7253e-09$ ( $\pm 8$ LSB) |
| Tolerance Out2 | $\pm 3,7253e-09$ ( $\pm 8$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 345 |
| Max CPU cycles  | 355 |
| Avg CPU cycles  | 349 |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysmO2.

| Test results                 |            |            |           |
|------------------------------|------------|------------|-----------|
| Time step                    | 1          | 2          | 3         |
| <i>Mask parameters</i>       |            |            |           |
| <b>A</b>                     | [1x4]      | [1x4]      | [1x4]     |
| <b>B</b>                     | [1x4]      | [1x4]      | [1x4]     |
| <i>Controller parameters</i> |            |            |           |
| <b>a11</b>                   | 0          | 0          | 0         |
| <b>a22</b>                   | 2013265920 | 1610612736 | 644245094 |
| <b>b21</b>                   | 1342177280 | 1073741824 | 429496730 |
| <b>a21</b>                   | 1342177280 | 1073741824 | 429496730 |
| <b>b12</b>                   | 1342177280 | 1073741824 | 214748365 |
| <b>a12</b>                   | 1342177280 | 1073741824 | 214748365 |
| <b>b11</b>                   | 0          | 0          | 0         |
| <b>b22</b>                   | 2013265920 | 1610612736 | 644245094 |
| <b>sfrb12</b>                | 27         | 30         | 31        |
| <b>sfra12</b>                | 27         | 30         | 31        |
| <b>sfrb11</b>                | 31         | 31         | 31        |
| <b>sfrb22</b>                | 26         | 29         | 31        |
| <b>sfra11</b>                | 31         | 31         | 31        |
| <b>sfra22</b>                | 26         | 29         | 31        |
| <b>sfrb21</b>                | 26         | 29         | 31        |
| <b>sfra21</b>                | 26         | 29         | 31        |
| <b>Exp. a11</b>              | 0          | 0          | 0         |
| <b>Exp. a22</b>              | 2013265920 | 1610612736 | 644245094 |
| <b>Exp. b21</b>              | 1342177280 | 1073741824 | 429496730 |
| <b>Exp. a21</b>              | 1342177280 | 1073741824 | 429496730 |
| <b>Exp. b12</b>              | 1342177280 | 1073741824 | 214748365 |
| <b>Exp. a12</b>              | 1342177280 | 1073741824 | 214748365 |
| <b>Exp. b11</b>              | 0          | 0          | 0         |
| <b>Exp. b22</b>              | 2013265920 | 1610612736 | 644245094 |
| <b>Exp. sfrb12</b>           | 27         | 30         | 31        |
| <b>Exp. sfra12</b>           | 27         | 30         | 31        |
| <b>Exp. sfrb11</b>           | 31         | 31         | 31        |
| <b>Exp. sfrb22</b>           | 26         | 29         | 31        |
| <b>Exp. sfra11</b>           | 31         | 31         | 31        |
| <b>Exp. sfra22</b>           | 26         | 29         | 31        |
| <b>Exp. sfrb21</b>           | 26         | 29         | 31        |
| <b>Exp. sfra21</b>           | 26         | 29         | 31        |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 0,0000e+00$ |
| Tolerance a22    | $\pm 0,0000e+00$ |
| Tolerance b21    | $\pm 0,0000e+00$ |
| Tolerance a21    | $\pm 0,0000e+00$ |
| Tolerance b12    | $\pm 0,0000e+00$ |
| Tolerance a12    | $\pm 0,0000e+00$ |
| Tolerance b11    | $\pm 0,0000e+00$ |
| Tolerance b22    | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |

**Verification: TDSysmO2 FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block TDSysmO2.

| Test results    |             |             |     |             |
|-----------------|-------------|-------------|-----|-------------|
| Time step       | 1           | 2           | ... | 174         |
| CPU cycles      | 341         | 341         | ... | 341         |
| Inputs          |             |             |     |             |
| In1 (DSP)       | 0           | -214390630  | ... | -1288490189 |
| In2 (DSP)       | -2147483648 | -2136755175 | ... | -1288490189 |
| In1             | -0          | -0.1        | ... | -0.6        |
| In2             | -1          | -0.995      | ... | -0.6        |
| Parameters      |             |             |     |             |
| A               | [1x4]       |             |     |             |
| B               | [1x4]       |             |     |             |
| Outputs         |             |             |     |             |
| Out1            | 0           | -0.28       | ... | -0.898      |
| Out2            | 0           | -0.08       | ... | -0.432      |
| Exp. Out1       | 0           | -0.28       | ... | -0.898      |
| Exp. Out2       | 0           | -0.08       | ... | -0.432      |
| Out1 (DSP)      | 0           | -601295421  | ... | -1927381242 |
| Out2 (DSP)      | 0           | -171798692  | ... | -927641873  |
| Exp. Out1 (DSP) | 0           | -601295421  | ... | -1927381237 |
| Exp. Out2 (DSP) | 0           | -171798692  | ... | -927641869  |

| Test settings  |                                 |
|----------------|---------------------------------|
| Tolerance Out1 | $\pm 3,7253e-09$ ( $\pm 8$ LSB) |
| Tolerance Out2 | $\pm 3,7253e-09$ ( $\pm 8$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 341 |
| Max CPU cycles  | 341 |
| Avg CPU cycles  | 341 |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysmO2.

| Test results                 |            |            |           |
|------------------------------|------------|------------|-----------|
| Time step                    | 1          | 2          | 3         |
| <i>Mask parameters</i>       |            |            |           |
| <b>A</b>                     | [1x4]      | [1x4]      | [1x4]     |
| <b>B</b>                     | [1x4]      | [1x4]      | [1x4]     |
| <i>Controller parameters</i> |            |            |           |
| <b>a11</b>                   | 0          | 0          | 0         |
| <b>a22</b>                   | 2013265920 | 1610612736 | 644245094 |
| <b>b21</b>                   | 1342177280 | 1073741824 | 429496730 |
| <b>a21</b>                   | 1342177280 | 1073741824 | 429496730 |
| <b>b12</b>                   | 1342177280 | 1073741824 | 214748365 |
| <b>a12</b>                   | 1342177280 | 1073741824 | 214748365 |
| <b>b11</b>                   | 0          | 0          | 0         |
| <b>b22</b>                   | 2013265920 | 1610612736 | 644245094 |
| <b>sfrb12</b>                | 27         | 30         | 31        |
| <b>sfra12</b>                | 27         | 30         | 31        |
| <b>sfrb11</b>                | 31         | 31         | 31        |
| <b>sfrb22</b>                | 26         | 29         | 31        |
| <b>sfra11</b>                | 31         | 31         | 31        |
| <b>sfra22</b>                | 26         | 29         | 31        |
| <b>sfrb21</b>                | 26         | 29         | 31        |
| <b>sfra21</b>                | 26         | 29         | 31        |
| <b>Exp. a11</b>              | 0          | 0          | 0         |
| <b>Exp. a22</b>              | 2013265920 | 1610612736 | 644245094 |
| <b>Exp. b21</b>              | 1342177280 | 1073741824 | 429496730 |
| <b>Exp. a21</b>              | 1342177280 | 1073741824 | 429496730 |
| <b>Exp. b12</b>              | 1342177280 | 1073741824 | 214748365 |
| <b>Exp. a12</b>              | 1342177280 | 1073741824 | 214748365 |
| <b>Exp. b11</b>              | 0          | 0          | 0         |
| <b>Exp. b22</b>              | 2013265920 | 1610612736 | 644245094 |
| <b>Exp. sfrb12</b>           | 27         | 30         | 31        |
| <b>Exp. sfra12</b>           | 27         | 30         | 31        |
| <b>Exp. sfrb11</b>           | 31         | 31         | 31        |
| <b>Exp. sfrb22</b>           | 26         | 29         | 31        |
| <b>Exp. sfra11</b>           | 31         | 31         | 31        |
| <b>Exp. sfra22</b>           | 26         | 29         | 31        |
| <b>Exp. sfrb21</b>           | 26         | 29         | 31        |
| <b>Exp. sfra21</b>           | 26         | 29         | 31        |



| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 0,0000e+00$ |
| Tolerance a22    | $\pm 0,0000e+00$ |
| Tolerance b21    | $\pm 0,0000e+00$ |
| Tolerance a21    | $\pm 0,0000e+00$ |
| Tolerance b12    | $\pm 0,0000e+00$ |
| Tolerance a12    | $\pm 0,0000e+00$ |
| Tolerance b11    | $\pm 0,0000e+00$ |
| Tolerance b22    | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |

**Verification: TDSysmO2 FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block TDSysmO2.

| Test results    |             |             |     |             |
|-----------------|-------------|-------------|-----|-------------|
| Time step       | 1           | 2           | ... | 174         |
| CPU cycles      | 997         | 998         | ... | 997         |
| Inputs          |             |             |     |             |
| In1 (DSP)       | 0           | -214390630  | ... | -1288490189 |
| In2 (DSP)       | -2147483648 | -2136755175 | ... | -1288490189 |
| In1             | -0          | -0.1        | ... | -0.6        |
| In2             | -1          | -0.995      | ... | -0.6        |
| Parameters      |             |             |     |             |
| A               | [1x4]       |             |     |             |
| B               | [1x4]       |             |     |             |
| Outputs         |             |             |     |             |
| Out1            | 0           | -0.28       | ... | -0.898      |
| Out2            | 0           | -0.08       | ... | -0.432      |
| Exp. Out1       | 0           | -0.28       | ... | -0.898      |
| Exp. Out2       | 0           | -0.08       | ... | -0.432      |
| Out1 (DSP)      | 0           | -601295421  | ... | -1927381242 |
| Out2 (DSP)      | 0           | -171798692  | ... | -927641873  |
| Exp. Out1 (DSP) | 0           | -601295421  | ... | -1927381237 |
| Exp. Out2 (DSP) | 0           | -171798692  | ... | -927641869  |

| Test settings  |                                 |
|----------------|---------------------------------|
| Tolerance Out1 | $\pm 3,7253e-09$ ( $\pm 8$ LSB) |
| Tolerance Out2 | $\pm 3,7253e-09$ ( $\pm 8$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 986  |
| Max CPU cycles  | 1057 |
| Avg CPU cycles  | 994  |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysmO2.

| Test results                 |            |            |           |
|------------------------------|------------|------------|-----------|
| Time step                    | 1          | 2          | 3         |
| <i>Mask parameters</i>       |            |            |           |
| <b>A</b>                     | [1x4]      | [1x4]      | [1x4]     |
| <b>B</b>                     | [1x4]      | [1x4]      | [1x4]     |
| <i>Controller parameters</i> |            |            |           |
| <b>a11</b>                   | 0          | 0          | 0         |
| <b>a22</b>                   | 2013265920 | 1610612736 | 644245094 |
| <b>b21</b>                   | 1342177280 | 1073741824 | 429496730 |
| <b>a21</b>                   | 1342177280 | 1073741824 | 429496730 |
| <b>b12</b>                   | 1342177280 | 1073741824 | 214748365 |
| <b>a12</b>                   | 1342177280 | 1073741824 | 214748365 |
| <b>b11</b>                   | 0          | 0          | 0         |
| <b>b22</b>                   | 2013265920 | 1610612736 | 644245094 |
| <b>sfrb12</b>                | 27         | 30         | 31        |
| <b>sfra12</b>                | 27         | 30         | 31        |
| <b>sfrb11</b>                | 31         | 31         | 31        |
| <b>sfrb22</b>                | 26         | 29         | 31        |
| <b>sfra11</b>                | 31         | 31         | 31        |
| <b>sfra22</b>                | 26         | 29         | 31        |
| <b>sfrb21</b>                | 26         | 29         | 31        |
| <b>sfra21</b>                | 26         | 29         | 31        |
| <b>Exp. a11</b>              | 0          | 0          | 0         |
| <b>Exp. a22</b>              | 2013265920 | 1610612736 | 644245094 |
| <b>Exp. b21</b>              | 1342177280 | 1073741824 | 429496730 |
| <b>Exp. a21</b>              | 1342177280 | 1073741824 | 429496730 |
| <b>Exp. b12</b>              | 1342177280 | 1073741824 | 214748365 |
| <b>Exp. a12</b>              | 1342177280 | 1073741824 | 214748365 |
| <b>Exp. b11</b>              | 0          | 0          | 0         |
| <b>Exp. b22</b>              | 2013265920 | 1610612736 | 644245094 |
| <b>Exp. sfrb12</b>           | 27         | 30         | 31        |
| <b>Exp. sfra12</b>           | 27         | 30         | 31        |
| <b>Exp. sfrb11</b>           | 31         | 31         | 31        |
| <b>Exp. sfrb22</b>           | 26         | 29         | 31        |
| <b>Exp. sfra11</b>           | 31         | 31         | 31        |
| <b>Exp. sfra22</b>           | 26         | 29         | 31        |
| <b>Exp. sfrb21</b>           | 26         | 29         | 31        |
| <b>Exp. sfra21</b>           | 26         | 29         | 31        |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 0,0000e+00$ |
| Tolerance a22    | $\pm 0,0000e+00$ |
| Tolerance b21    | $\pm 0,0000e+00$ |
| Tolerance a21    | $\pm 0,0000e+00$ |
| Tolerance b12    | $\pm 0,0000e+00$ |
| Tolerance a12    | $\pm 0,0000e+00$ |
| Tolerance b11    | $\pm 0,0000e+00$ |
| Tolerance b22    | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |

**Verification: TDSysmO2 FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block TDSysmO2.

| Test results    |             |             |     |             |
|-----------------|-------------|-------------|-----|-------------|
| Time step       | 1           | 2           | ... | 174         |
| CPU cycles      | 274         | 274         | ... | 274         |
| Inputs          |             |             |     |             |
| In1 (DSP)       | 0           | -214390630  | ... | -1288490189 |
| In2 (DSP)       | -2147483648 | -2136755175 | ... | -1288490189 |
| In1             | -0          | -0.1        | ... | -0.6        |
| In2             | -1          | -0.995      | ... | -0.6        |
| Parameters      |             |             |     |             |
| A               | [1x4]       |             |     |             |
| B               | [1x4]       |             |     |             |
| Outputs         |             |             |     |             |
| Out1            | 0           | -0.28       | ... | -0.898      |
| Out2            | 0           | -0.08       | ... | -0.432      |
| Exp. Out1       | 0           | -0.28       | ... | -0.898      |
| Exp. Out2       | 0           | -0.08       | ... | -0.432      |
| Out1 (DSP)      | 0           | -601295421  | ... | -1927381242 |
| Out2 (DSP)      | 0           | -171798692  | ... | -927641873  |
| Exp. Out1 (DSP) | 0           | -601295421  | ... | -1927381237 |
| Exp. Out2 (DSP) | 0           | -171798692  | ... | -927641869  |

| Test settings  |                                 |
|----------------|---------------------------------|
| Tolerance Out1 | $\pm 3,7253e-09$ ( $\pm 8$ LSB) |
| Tolerance Out2 | $\pm 3,7253e-09$ ( $\pm 8$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 274 |
| Max CPU cycles  | 280 |
| Avg CPU cycles  | 275 |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysmO2.

| Test results                 |            |            |           |
|------------------------------|------------|------------|-----------|
| Time step                    | 1          | 2          | 3         |
| <i>Mask parameters</i>       |            |            |           |
| <b>A</b>                     | [1x4]      | [1x4]      | [1x4]     |
| <b>B</b>                     | [1x4]      | [1x4]      | [1x4]     |
| <i>Controller parameters</i> |            |            |           |
| <b>a11</b>                   | 0          | 0          | 0         |
| <b>a22</b>                   | 2013265920 | 1610612736 | 644245094 |
| <b>b21</b>                   | 1342177280 | 1073741824 | 429496730 |
| <b>a21</b>                   | 1342177280 | 1073741824 | 429496730 |
| <b>b12</b>                   | 1342177280 | 1073741824 | 214748365 |
| <b>a12</b>                   | 1342177280 | 1073741824 | 214748365 |
| <b>b11</b>                   | 0          | 0          | 0         |
| <b>b22</b>                   | 2013265920 | 1610612736 | 644245094 |
| <b>sfrb12</b>                | 27         | 30         | 31        |
| <b>sfra12</b>                | 27         | 30         | 31        |
| <b>sfrb11</b>                | 31         | 31         | 31        |
| <b>sfrb22</b>                | 26         | 29         | 31        |
| <b>sfra11</b>                | 31         | 31         | 31        |
| <b>sfra22</b>                | 26         | 29         | 31        |
| <b>sfrb21</b>                | 26         | 29         | 31        |
| <b>sfra21</b>                | 26         | 29         | 31        |
| <b>Exp. a11</b>              | 0          | 0          | 0         |
| <b>Exp. a22</b>              | 2013265920 | 1610612736 | 644245094 |
| <b>Exp. b21</b>              | 1342177280 | 1073741824 | 429496730 |
| <b>Exp. a21</b>              | 1342177280 | 1073741824 | 429496730 |
| <b>Exp. b12</b>              | 1342177280 | 1073741824 | 214748365 |
| <b>Exp. a12</b>              | 1342177280 | 1073741824 | 214748365 |
| <b>Exp. b11</b>              | 0          | 0          | 0         |
| <b>Exp. b22</b>              | 2013265920 | 1610612736 | 644245094 |
| <b>Exp. sfrb12</b>           | 27         | 30         | 31        |
| <b>Exp. sfra12</b>           | 27         | 30         | 31        |
| <b>Exp. sfrb11</b>           | 31         | 31         | 31        |
| <b>Exp. sfrb22</b>           | 26         | 29         | 31        |
| <b>Exp. sfra11</b>           | 31         | 31         | 31        |
| <b>Exp. sfra22</b>           | 26         | 29         | 31        |
| <b>Exp. sfrb21</b>           | 26         | 29         | 31        |
| <b>Exp. sfra21</b>           | 26         | 29         | 31        |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 0,0000e+00$ |
| Tolerance a22    | $\pm 0,0000e+00$ |
| Tolerance b21    | $\pm 0,0000e+00$ |
| Tolerance a21    | $\pm 0,0000e+00$ |
| Tolerance b12    | $\pm 0,0000e+00$ |
| Tolerance a12    | $\pm 0,0000e+00$ |
| Tolerance b11    | $\pm 0,0000e+00$ |
| Tolerance b22    | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |

**Verification: TDSysmO2 FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block TDSysmO2.

| Test results    |             |             |     |             |
|-----------------|-------------|-------------|-----|-------------|
| Time step       | 1           | 2           | ... | 174         |
| CPU cycles      | 364         | 289         | ... | 289         |
| Inputs          |             |             |     |             |
| In1 (DSP)       | 0           | -214390630  | ... | -1288490189 |
| In2 (DSP)       | -2147483648 | -2136755175 | ... | -1288490189 |
| In1             | -0          | -0.1        | ... | -0.6        |
| In2             | -1          | -0.995      | ... | -0.6        |
| Parameters      |             |             |     |             |
| A               | [1x4]       |             |     |             |
| B               | [1x4]       |             |     |             |
| Outputs         |             |             |     |             |
| Out1            | 0           | -0.28       | ... | -0.898      |
| Out2            | 0           | -0.08       | ... | -0.432      |
| Exp. Out1       | 0           | -0.28       | ... | -0.898      |
| Exp. Out2       | 0           | -0.08       | ... | -0.432      |
| Out1 (DSP)      | 0           | -601295421  | ... | -1927381242 |
| Out2 (DSP)      | 0           | -171798692  | ... | -927641873  |
| Exp. Out1 (DSP) | 0           | -601295421  | ... | -1927381237 |
| Exp. Out2 (DSP) | 0           | -171798692  | ... | -927641869  |

| Test settings  |                                 |
|----------------|---------------------------------|
| Tolerance Out1 | $\pm 3,7253e-09$ ( $\pm 8$ LSB) |
| Tolerance Out2 | $\pm 3,7253e-09$ ( $\pm 8$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 289 |
| Max CPU cycles  | 364 |
| Avg CPU cycles  | 289 |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysmO2.



| Test results                 |            |            |           |
|------------------------------|------------|------------|-----------|
| Time step                    | 1          | 2          | 3         |
| <i>Mask parameters</i>       |            |            |           |
| <b>A</b>                     | [1x4]      | [1x4]      | [1x4]     |
| <b>B</b>                     | [1x4]      | [1x4]      | [1x4]     |
| <i>Controller parameters</i> |            |            |           |
| <b>a11</b>                   | 0          | 0          | 0         |
| <b>a22</b>                   | 2013265920 | 1610612736 | 644245094 |
| <b>b21</b>                   | 1342177280 | 1073741824 | 429496730 |
| <b>a21</b>                   | 1342177280 | 1073741824 | 429496730 |
| <b>b12</b>                   | 1342177280 | 1073741824 | 214748365 |
| <b>a12</b>                   | 1342177280 | 1073741824 | 214748365 |
| <b>b11</b>                   | 0          | 0          | 0         |
| <b>b22</b>                   | 2013265920 | 1610612736 | 644245094 |
| <b>sfrb12</b>                | 27         | 30         | 31        |
| <b>sfra12</b>                | 27         | 30         | 31        |
| <b>sfrb11</b>                | 31         | 31         | 31        |
| <b>sfrb22</b>                | 26         | 29         | 31        |
| <b>sfra11</b>                | 31         | 31         | 31        |
| <b>sfra22</b>                | 26         | 29         | 31        |
| <b>sfrb21</b>                | 26         | 29         | 31        |
| <b>sfra21</b>                | 26         | 29         | 31        |
| <b>Exp. a11</b>              | 0          | 0          | 0         |
| <b>Exp. a22</b>              | 2013265920 | 1610612736 | 644245094 |
| <b>Exp. b21</b>              | 1342177280 | 1073741824 | 429496730 |
| <b>Exp. a21</b>              | 1342177280 | 1073741824 | 429496730 |
| <b>Exp. b12</b>              | 1342177280 | 1073741824 | 214748365 |
| <b>Exp. a12</b>              | 1342177280 | 1073741824 | 214748365 |
| <b>Exp. b11</b>              | 0          | 0          | 0         |
| <b>Exp. b22</b>              | 2013265920 | 1610612736 | 644245094 |
| <b>Exp. sfrb12</b>           | 27         | 30         | 31        |
| <b>Exp. sfra12</b>           | 27         | 30         | 31        |
| <b>Exp. sfrb11</b>           | 31         | 31         | 31        |
| <b>Exp. sfrb22</b>           | 26         | 29         | 31        |
| <b>Exp. sfra11</b>           | 31         | 31         | 31        |
| <b>Exp. sfra22</b>           | 26         | 29         | 31        |
| <b>Exp. sfrb21</b>           | 26         | 29         | 31        |
| <b>Exp. sfra21</b>           | 26         | 29         | 31        |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 0,0000e+00$ |
| Tolerance a22    | $\pm 0,0000e+00$ |
| Tolerance b21    | $\pm 0,0000e+00$ |
| Tolerance a21    | $\pm 0,0000e+00$ |
| Tolerance b12    | $\pm 0,0000e+00$ |
| Tolerance a12    | $\pm 0,0000e+00$ |
| Tolerance b11    | $\pm 0,0000e+00$ |
| Tolerance b22    | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |

**Verification: TDSysmO2 FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block TDSysmO2.

| Test results    |             |             |     |             |
|-----------------|-------------|-------------|-----|-------------|
| Time step       | 1           | 2           | ... | 174         |
| CPU cycles      | 417         | 417         | ... | 417         |
| Inputs          |             |             |     |             |
| In1 (DSP)       | 0           | -214390630  | ... | -1288490189 |
| In2 (DSP)       | -2147483648 | -2136755175 | ... | -1288490189 |
| In1             | -0          | -0.1        | ... | -0.6        |
| In2             | -1          | -0.995      | ... | -0.6        |
| Parameters      |             |             |     |             |
| A               | [1x4]       |             |     |             |
| B               | [1x4]       |             |     |             |
| Outputs         |             |             |     |             |
| Out1            | 0           | -0.28       | ... | -0.898      |
| Out2            | 0           | -0.08       | ... | -0.432      |
| Exp. Out1       | 0           | -0.28       | ... | -0.898      |
| Exp. Out2       | 0           | -0.08       | ... | -0.432      |
| Out1 (DSP)      | 0           | -601295421  | ... | -1927381242 |
| Out2 (DSP)      | 0           | -171798692  | ... | -927641873  |
| Exp. Out1 (DSP) | 0           | -601295421  | ... | -1927381237 |
| Exp. Out2 (DSP) | 0           | -171798692  | ... | -927641869  |

| Test settings  |                                 |
|----------------|---------------------------------|
| Tolerance Out1 | $\pm 3,7253e-09$ ( $\pm 8$ LSB) |
| Tolerance Out2 | $\pm 3,7253e-09$ ( $\pm 8$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 368 |
| Max CPU cycles  | 422 |
| Avg CPU cycles  | 407 |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysmO2.

| Test results                 |            |            |           |
|------------------------------|------------|------------|-----------|
| Time step                    | 1          | 2          | 3         |
| <i>Mask parameters</i>       |            |            |           |
| <b>A</b>                     | [1x4]      | [1x4]      | [1x4]     |
| <b>B</b>                     | [1x4]      | [1x4]      | [1x4]     |
| <i>Controller parameters</i> |            |            |           |
| <b>a11</b>                   | 0          | 0          | 0         |
| <b>a22</b>                   | 2013265920 | 1610612736 | 644245094 |
| <b>b21</b>                   | 1342177280 | 1073741824 | 429496730 |
| <b>a21</b>                   | 1342177280 | 1073741824 | 429496730 |
| <b>b12</b>                   | 1342177280 | 1073741824 | 214748365 |
| <b>a12</b>                   | 1342177280 | 1073741824 | 214748365 |
| <b>b11</b>                   | 0          | 0          | 0         |
| <b>b22</b>                   | 2013265920 | 1610612736 | 644245094 |
| <b>sfrb12</b>                | 27         | 30         | 31        |
| <b>sfra12</b>                | 27         | 30         | 31        |
| <b>sfrb11</b>                | 31         | 31         | 31        |
| <b>sfrb22</b>                | 26         | 29         | 31        |
| <b>sfra11</b>                | 31         | 31         | 31        |
| <b>sfra22</b>                | 26         | 29         | 31        |
| <b>sfrb21</b>                | 26         | 29         | 31        |
| <b>sfra21</b>                | 26         | 29         | 31        |
| <b>Exp. a11</b>              | 0          | 0          | 0         |
| <b>Exp. a22</b>              | 2013265920 | 1610612736 | 644245094 |
| <b>Exp. b21</b>              | 1342177280 | 1073741824 | 429496730 |
| <b>Exp. a21</b>              | 1342177280 | 1073741824 | 429496730 |
| <b>Exp. b12</b>              | 1342177280 | 1073741824 | 214748365 |
| <b>Exp. a12</b>              | 1342177280 | 1073741824 | 214748365 |
| <b>Exp. b11</b>              | 0          | 0          | 0         |
| <b>Exp. b22</b>              | 2013265920 | 1610612736 | 644245094 |
| <b>Exp. sfrb12</b>           | 27         | 30         | 31        |
| <b>Exp. sfra12</b>           | 27         | 30         | 31        |
| <b>Exp. sfrb11</b>           | 31         | 31         | 31        |
| <b>Exp. sfrb22</b>           | 26         | 29         | 31        |
| <b>Exp. sfra11</b>           | 31         | 31         | 31        |
| <b>Exp. sfra22</b>           | 26         | 29         | 31        |
| <b>Exp. sfrb21</b>           | 26         | 29         | 31        |
| <b>Exp. sfra21</b>           | 26         | 29         | 31        |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 0,0000e+00$ |
| Tolerance a22    | $\pm 0,0000e+00$ |
| Tolerance b21    | $\pm 0,0000e+00$ |
| Tolerance a21    | $\pm 0,0000e+00$ |
| Tolerance b12    | $\pm 0,0000e+00$ |
| Tolerance a12    | $\pm 0,0000e+00$ |
| Tolerance b11    | $\pm 0,0000e+00$ |
| Tolerance b22    | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |

**Verification: TDSysmO2 FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block TDSysmO2.

| Test results    |             |             |     |             |
|-----------------|-------------|-------------|-----|-------------|
| Time step       | 1           | 2           | ... | 174         |
| CPU cycles      | 3572        | 3608        | ... | 3608        |
| Inputs          |             |             |     |             |
| In1 (DSP)       | 0           | -214390630  | ... | -1288490189 |
| In2 (DSP)       | -2147483648 | -2136755175 | ... | -1288490189 |
| In1             | -0          | -0.1        | ... | -0.6        |
| In2             | -1          | -0.995      | ... | -0.6        |
| Parameters      |             |             |     |             |
| A               | [1x4]       |             |     |             |
| B               | [1x4]       |             |     |             |
| Outputs         |             |             |     |             |
| Out1            | 0           | -0.28       | ... | -0.898      |
| Out2            | 0           | -0.08       | ... | -0.432      |
| Exp. Out1       | 0           | -0.28       | ... | -0.898      |
| Exp. Out2       | 0           | -0.08       | ... | -0.432      |
| Out1 (DSP)      | 0           | -601295421  | ... | -1927381242 |
| Out2 (DSP)      | 0           | -171798692  | ... | -927641873  |
| Exp. Out1 (DSP) | 0           | -601295421  | ... | -1927381237 |
| Exp. Out2 (DSP) | 0           | -171798692  | ... | -927641869  |

| Test settings  |                                 |
|----------------|---------------------------------|
| Tolerance Out1 | $\pm 3,7253e-09$ ( $\pm 8$ LSB) |
| Tolerance Out2 | $\pm 3,7253e-09$ ( $\pm 8$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3558 |
| Max CPU cycles  | 3609 |
| Avg CPU cycles  | 3585 |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysmO2.

| Test results                 |            |            |           |
|------------------------------|------------|------------|-----------|
| Time step                    | 1          | 2          | 3         |
| <i>Mask parameters</i>       |            |            |           |
| <b>A</b>                     | [1x4]      | [1x4]      | [1x4]     |
| <b>B</b>                     | [1x4]      | [1x4]      | [1x4]     |
| <i>Controller parameters</i> |            |            |           |
| <b>a11</b>                   | 0          | 0          | 0         |
| <b>a22</b>                   | 2013265920 | 1610612736 | 644245094 |
| <b>b21</b>                   | 1342177280 | 1073741824 | 429496730 |
| <b>a21</b>                   | 1342177280 | 1073741824 | 429496730 |
| <b>b12</b>                   | 1342177280 | 1073741824 | 214748365 |
| <b>a12</b>                   | 1342177280 | 1073741824 | 214748365 |
| <b>b11</b>                   | 0          | 0          | 0         |
| <b>b22</b>                   | 2013265920 | 1610612736 | 644245094 |
| <b>sfrb12</b>                | 27         | 30         | 31        |
| <b>sfra12</b>                | 27         | 30         | 31        |
| <b>sfrb11</b>                | 31         | 31         | 31        |
| <b>sfrb22</b>                | 26         | 29         | 31        |
| <b>sfra11</b>                | 31         | 31         | 31        |
| <b>sfra22</b>                | 26         | 29         | 31        |
| <b>sfrb21</b>                | 26         | 29         | 31        |
| <b>sfra21</b>                | 26         | 29         | 31        |
| <b>Exp. a11</b>              | 0          | 0          | 0         |
| <b>Exp. a22</b>              | 2013265920 | 1610612736 | 644245094 |
| <b>Exp. b21</b>              | 1342177280 | 1073741824 | 429496730 |
| <b>Exp. a21</b>              | 1342177280 | 1073741824 | 429496730 |
| <b>Exp. b12</b>              | 1342177280 | 1073741824 | 214748365 |
| <b>Exp. a12</b>              | 1342177280 | 1073741824 | 214748365 |
| <b>Exp. b11</b>              | 0          | 0          | 0         |
| <b>Exp. b22</b>              | 2013265920 | 1610612736 | 644245094 |
| <b>Exp. sfrb12</b>           | 27         | 30         | 31        |
| <b>Exp. sfra12</b>           | 27         | 30         | 31        |
| <b>Exp. sfrb11</b>           | 31         | 31         | 31        |
| <b>Exp. sfrb22</b>           | 26         | 29         | 31        |
| <b>Exp. sfra11</b>           | 31         | 31         | 31        |
| <b>Exp. sfra22</b>           | 26         | 29         | 31        |
| <b>Exp. sfrb21</b>           | 26         | 29         | 31        |
| <b>Exp. sfra21</b>           | 26         | 29         | 31        |

| Test settings    |                  |
|------------------|------------------|
| Tolerance a11    | $\pm 0,0000e+00$ |
| Tolerance a22    | $\pm 0,0000e+00$ |
| Tolerance b21    | $\pm 0,0000e+00$ |
| Tolerance a21    | $\pm 0,0000e+00$ |
| Tolerance b12    | $\pm 0,0000e+00$ |
| Tolerance a12    | $\pm 0,0000e+00$ |
| Tolerance b11    | $\pm 0,0000e+00$ |
| Tolerance b22    | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb12 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb11 | $\pm 0,0000e+00$ |
| Tolerance sfrb22 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |
| Tolerance sfrb21 | $\pm 0,0000e+00$ |



**Verification: TDSysO2 Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block TDSysO2.

| Test results    |       |        |     |        |
|-----------------|-------|--------|-----|--------|
| Time step       | 1     | 2      | ... | 174    |
| CPU cycles      | 102   | 102    | ... | 102    |
| Inputs          |       |        |     |        |
| In1 (DSP)       | -0    | -0.1   | ... | -0.6   |
| In2 (DSP)       | -1    | -0.995 | ... | -0.6   |
| In1             | -0    | -0.1   | ... | -0.6   |
| In2             | -1    | -0.995 | ... | -0.6   |
| Parameters      |       |        |     |        |
| A               | [1x4] |        |     |        |
| B               | [1x4] |        |     |        |
| Outputs         |       |        |     |        |
| Out1            | 0     | -0.28  | ... | -0.898 |
| Out2            | 0     | -0.08  | ... | -0.432 |
| Exp. Out1       | 0     | -0.28  | ... | -0.898 |
| Exp. Out2       | 0     | -0.08  | ... | -0.432 |
| Out1 (DSP)      | 0     | -0.28  | ... | -0.898 |
| Out2 (DSP)      | 0     | -0.08  | ... | -0.432 |
| Exp. Out1 (DSP) | 0     | -0.28  | ... | -0.898 |
| Exp. Out2 (DSP) | 0     | -0.08  | ... | -0.432 |

| Test settings  |                                   |
|----------------|-----------------------------------|
| Tolerance Out1 | $\pm 2,3283e-07$ ( $\pm 500$ LSB) |
| Tolerance Out2 | $\pm 2,3283e-07$ ( $\pm 500$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 102 |
| Max CPU cycles  | 102 |
| Avg CPU cycles  | 102 |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysO2.

| Test results                 |       |       |       |
|------------------------------|-------|-------|-------|
| Time step                    | 1     | 2     | 3     |
| <i>Mask parameters</i>       |       |       |       |
| <b>A</b>                     | [1x4] | [1x4] | [1x4] |
| <b>B</b>                     | [1x4] | [1x4] | [1x4] |
| <i>Controller parameters</i> |       |       |       |
| <b>a11</b>                   | 0     | 0     | 0     |
| <b>a22</b>                   | 30    | 3     | 0.3   |
| <b>b21</b>                   | 20    | 2     | 0.2   |
| <b>a21</b>                   | 20    | 2     | 0.2   |
| <b>b12</b>                   | 10    | 1     | 0.1   |
| <b>a12</b>                   | 10    | 1     | 0.1   |
| <b>b11</b>                   | 0     | 0     | 0     |
| <b>b22</b>                   | 30    | 3     | 0.3   |
| <b>Exp. a11</b>              | 0     | 0     | 0     |
| <b>Exp. a22</b>              | 30    | 3     | 0.3   |
| <b>Exp. b21</b>              | 20    | 2     | 0.2   |
| <b>Exp. a21</b>              | 20    | 2     | 0.2   |
| <b>Exp. b12</b>              | 10    | 1     | 0.1   |
| <b>Exp. a12</b>              | 10    | 1     | 0.1   |
| <b>Exp. b11</b>              | 0     | 0     | 0     |
| <b>Exp. b22</b>              | 30    | 3     | 0.3   |

| Test settings |                  |
|---------------|------------------|
| Tolerance a11 | $\pm 0,0000e+00$ |
| Tolerance a22 | $\pm 0,0000e+00$ |
| Tolerance b21 | $\pm 0,0000e+00$ |
| Tolerance a21 | $\pm 0,0000e+00$ |
| Tolerance b12 | $\pm 0,0000e+00$ |
| Tolerance a12 | $\pm 0,0000e+00$ |
| Tolerance b11 | $\pm 0,0000e+00$ |
| Tolerance b22 | $\pm 0,0000e+00$ |

**Verification: TDSysystemO2 Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block TDSysystemO2.

| Test results    |       |        |     |        |
|-----------------|-------|--------|-----|--------|
| Time step       | 1     | 2      | ... | 174    |
| CPU cycles      | 71    | 71     | ... | 71     |
| Inputs          |       |        |     |        |
| In1 (DSP)       | -0    | -0.1   | ... | -0.6   |
| In2 (DSP)       | -1    | -0.995 | ... | -0.6   |
| In1             | -0    | -0.1   | ... | -0.6   |
| In2             | -1    | -0.995 | ... | -0.6   |
| Parameters      |       |        |     |        |
| A               | [1x4] |        |     |        |
| B               | [1x4] |        |     |        |
| Outputs         |       |        |     |        |
| Out1            | 0     | -0.28  | ... | -0.898 |
| Out2            | 0     | -0.08  | ... | -0.432 |
| Exp. Out1       | 0     | -0.28  | ... | -0.898 |
| Exp. Out2       | 0     | -0.08  | ... | -0.432 |
| Out1 (DSP)      | 0     | -0.28  | ... | -0.898 |
| Out2 (DSP)      | 0     | -0.08  | ... | -0.432 |
| Exp. Out1 (DSP) | 0     | -0.28  | ... | -0.898 |
| Exp. Out2 (DSP) | 0     | -0.08  | ... | -0.432 |

| Test settings  |                                   |
|----------------|-----------------------------------|
| Tolerance Out1 | $\pm 2,3283e-07$ ( $\pm 500$ LSB) |
| Tolerance Out2 | $\pm 2,3283e-07$ ( $\pm 500$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 71 |
| Max CPU cycles  | 71 |
| Avg CPU cycles  | 71 |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysystemO2.

| Test results                 |       |       |       |
|------------------------------|-------|-------|-------|
| Time step                    | 1     | 2     | 3     |
| <i>Mask parameters</i>       |       |       |       |
| <b>A</b>                     | [1x4] | [1x4] | [1x4] |
| <b>B</b>                     | [1x4] | [1x4] | [1x4] |
| <i>Controller parameters</i> |       |       |       |
| <b>a11</b>                   | 0     | 0     | 0     |
| <b>a22</b>                   | 30    | 3     | 0.3   |
| <b>b21</b>                   | 20    | 2     | 0.2   |
| <b>a21</b>                   | 20    | 2     | 0.2   |
| <b>b12</b>                   | 10    | 1     | 0.1   |
| <b>a12</b>                   | 10    | 1     | 0.1   |
| <b>b11</b>                   | 0     | 0     | 0     |
| <b>b22</b>                   | 30    | 3     | 0.3   |
| <b>Exp. a11</b>              | 0     | 0     | 0     |
| <b>Exp. a22</b>              | 30    | 3     | 0.3   |
| <b>Exp. b21</b>              | 20    | 2     | 0.2   |
| <b>Exp. a21</b>              | 20    | 2     | 0.2   |
| <b>Exp. b12</b>              | 10    | 1     | 0.1   |
| <b>Exp. a12</b>              | 10    | 1     | 0.1   |
| <b>Exp. b11</b>              | 0     | 0     | 0     |
| <b>Exp. b22</b>              | 30    | 3     | 0.3   |

| Test settings |                  |
|---------------|------------------|
| Tolerance a11 | $\pm 0,0000e+00$ |
| Tolerance a22 | $\pm 0,0000e+00$ |
| Tolerance b21 | $\pm 0,0000e+00$ |
| Tolerance a21 | $\pm 0,0000e+00$ |
| Tolerance b12 | $\pm 0,0000e+00$ |
| Tolerance a12 | $\pm 0,0000e+00$ |
| Tolerance b11 | $\pm 0,0000e+00$ |
| Tolerance b22 | $\pm 0,0000e+00$ |

**Verification: TDSysO2 Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block TDSysO2.

| Test results    |       |        |     |        |
|-----------------|-------|--------|-----|--------|
| Time step       | 1     | 2      | ... | 174    |
| CPU cycles      | 113   | 113    | ... | 113    |
| Inputs          |       |        |     |        |
| In1 (DSP)       | -0    | -0.1   | ... | -0.6   |
| In2 (DSP)       | -1    | -0.995 | ... | -0.6   |
| In1             | -0    | -0.1   | ... | -0.6   |
| In2             | -1    | -0.995 | ... | -0.6   |
| Parameters      |       |        |     |        |
| A               | [1x4] |        |     |        |
| B               | [1x4] |        |     |        |
| Outputs         |       |        |     |        |
| Out1            | 0     | -0.28  | ... | -0.898 |
| Out2            | 0     | -0.08  | ... | -0.432 |
| Exp. Out1       | 0     | -0.28  | ... | -0.898 |
| Exp. Out2       | 0     | -0.08  | ... | -0.432 |
| Out1 (DSP)      | 0     | -0.28  | ... | -0.898 |
| Out2 (DSP)      | 0     | -0.08  | ... | -0.432 |
| Exp. Out1 (DSP) | 0     | -0.28  | ... | -0.898 |
| Exp. Out2 (DSP) | 0     | -0.08  | ... | -0.432 |

| Test settings  |                                   |
|----------------|-----------------------------------|
| Tolerance Out1 | $\pm 2,3283e-07$ ( $\pm 500$ LSB) |
| Tolerance Out2 | $\pm 2,3283e-07$ ( $\pm 500$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 113 |
| Max CPU cycles  | 113 |
| Avg CPU cycles  | 113 |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysO2.

| Test results                 |       |       |       |
|------------------------------|-------|-------|-------|
| Time step                    | 1     | 2     | 3     |
| <i>Mask parameters</i>       |       |       |       |
| <b>A</b>                     | [1x4] | [1x4] | [1x4] |
| <b>B</b>                     | [1x4] | [1x4] | [1x4] |
| <i>Controller parameters</i> |       |       |       |
| <b>a11</b>                   | 0     | 0     | 0     |
| <b>a22</b>                   | 30    | 3     | 0.3   |
| <b>b21</b>                   | 20    | 2     | 0.2   |
| <b>a21</b>                   | 20    | 2     | 0.2   |
| <b>b12</b>                   | 10    | 1     | 0.1   |
| <b>a12</b>                   | 10    | 1     | 0.1   |
| <b>b11</b>                   | 0     | 0     | 0     |
| <b>b22</b>                   | 30    | 3     | 0.3   |
| <b>Exp. a11</b>              | 0     | 0     | 0     |
| <b>Exp. a22</b>              | 30    | 3     | 0.3   |
| <b>Exp. b21</b>              | 20    | 2     | 0.2   |
| <b>Exp. a21</b>              | 20    | 2     | 0.2   |
| <b>Exp. b12</b>              | 10    | 1     | 0.1   |
| <b>Exp. a12</b>              | 10    | 1     | 0.1   |
| <b>Exp. b11</b>              | 0     | 0     | 0     |
| <b>Exp. b22</b>              | 30    | 3     | 0.3   |

| Test settings |                  |
|---------------|------------------|
| Tolerance a11 | $\pm 0,0000e+00$ |
| Tolerance a22 | $\pm 0,0000e+00$ |
| Tolerance b21 | $\pm 0,0000e+00$ |
| Tolerance a21 | $\pm 0,0000e+00$ |
| Tolerance b12 | $\pm 0,0000e+00$ |
| Tolerance a12 | $\pm 0,0000e+00$ |
| Tolerance b11 | $\pm 0,0000e+00$ |
| Tolerance b22 | $\pm 0,0000e+00$ |

**Verification: TDSysSystemO2 Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block TDSysSystemO2.

| Test results    |       |        |     |        |
|-----------------|-------|--------|-----|--------|
| Time step       | 1     | 2      | ... | 174    |
| CPU cycles      | 1821  | 2339   | ... | 2302   |
| Inputs          |       |        |     |        |
| In1 (DSP)       | -0    | -0.1   | ... | -0.6   |
| In2 (DSP)       | -1    | -0.995 | ... | -0.6   |
| In1             | -0    | -0.1   | ... | -0.6   |
| In2             | -1    | -0.995 | ... | -0.6   |
| Parameters      |       |        |     |        |
| A               | [1x4] |        |     |        |
| B               | [1x4] |        |     |        |
| Outputs         |       |        |     |        |
| Out1            | 0     | -0.28  | ... | -0.898 |
| Out2            | 0     | -0.08  | ... | -0.432 |
| Exp. Out1       | 0     | -0.28  | ... | -0.898 |
| Exp. Out2       | 0     | -0.08  | ... | -0.432 |
| Out1 (DSP)      | 0     | -0.28  | ... | -0.898 |
| Out2 (DSP)      | 0     | -0.08  | ... | -0.432 |
| Exp. Out1 (DSP) | 0     | -0.28  | ... | -0.898 |
| Exp. Out2 (DSP) | 0     | -0.08  | ... | -0.432 |

| Test settings  |                                   |
|----------------|-----------------------------------|
| Tolerance Out1 | $\pm 2,3283e-07$ ( $\pm 500$ LSB) |
| Tolerance Out2 | $\pm 2,3283e-07$ ( $\pm 500$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1821 |
| Max CPU cycles  | 2444 |
| Avg CPU cycles  | 2265 |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysSystemO2.

| Test results                 |       |       |       |
|------------------------------|-------|-------|-------|
| Time step                    | 1     | 2     | 3     |
| <i>Mask parameters</i>       |       |       |       |
| <b>A</b>                     | [1x4] | [1x4] | [1x4] |
| <b>B</b>                     | [1x4] | [1x4] | [1x4] |
| <i>Controller parameters</i> |       |       |       |
| <b>a11</b>                   | 0     | 0     | 0     |
| <b>a22</b>                   | 30    | 3     | 0.3   |
| <b>b21</b>                   | 20    | 2     | 0.2   |
| <b>a21</b>                   | 20    | 2     | 0.2   |
| <b>b12</b>                   | 10    | 1     | 0.1   |
| <b>a12</b>                   | 10    | 1     | 0.1   |
| <b>b11</b>                   | 0     | 0     | 0     |
| <b>b22</b>                   | 30    | 3     | 0.3   |
| <b>Exp. a11</b>              | 0     | 0     | 0     |
| <b>Exp. a22</b>              | 30    | 3     | 0.3   |
| <b>Exp. b21</b>              | 20    | 2     | 0.2   |
| <b>Exp. a21</b>              | 20    | 2     | 0.2   |
| <b>Exp. b12</b>              | 10    | 1     | 0.1   |
| <b>Exp. a12</b>              | 10    | 1     | 0.1   |
| <b>Exp. b11</b>              | 0     | 0     | 0     |
| <b>Exp. b22</b>              | 30    | 3     | 0.3   |

| Test settings |                  |
|---------------|------------------|
| Tolerance a11 | $\pm 0,0000e+00$ |
| Tolerance a22 | $\pm 0,0000e+00$ |
| Tolerance b21 | $\pm 0,0000e+00$ |
| Tolerance a21 | $\pm 0,0000e+00$ |
| Tolerance b12 | $\pm 0,0000e+00$ |
| Tolerance a12 | $\pm 0,0000e+00$ |
| Tolerance b11 | $\pm 0,0000e+00$ |
| Tolerance b22 | $\pm 0,0000e+00$ |



**Verification: TDSysmO2 Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block TDSysmO2.

| Test results    |       |        |     |        |
|-----------------|-------|--------|-----|--------|
| Time step       | 1     | 2      | ... | 174    |
| CPU cycles      | 652   | 848    | ... | 846    |
| Inputs          |       |        |     |        |
| In1 (DSP)       | -0    | -0.1   | ... | -0.6   |
| In2 (DSP)       | -1    | -0.995 | ... | -0.6   |
| In1             | -0    | -0.1   | ... | -0.6   |
| In2             | -1    | -0.995 | ... | -0.6   |
| Parameters      |       |        |     |        |
| A               | [1x4] |        |     |        |
| B               | [1x4] |        |     |        |
| Outputs         |       |        |     |        |
| Out1            | 0     | -0.28  | ... | -0.898 |
| Out2            | 0     | -0.08  | ... | -0.432 |
| Exp. Out1       | 0     | -0.28  | ... | -0.898 |
| Exp. Out2       | 0     | -0.08  | ... | -0.432 |
| Out1 (DSP)      | 0     | -0.28  | ... | -0.898 |
| Out2 (DSP)      | 0     | -0.08  | ... | -0.432 |
| Exp. Out1 (DSP) | 0     | -0.28  | ... | -0.898 |
| Exp. Out2 (DSP) | 0     | -0.08  | ... | -0.432 |

| Test settings  |                                   |
|----------------|-----------------------------------|
| Tolerance Out1 | $\pm 2,3283e-07$ ( $\pm 500$ LSB) |
| Tolerance Out2 | $\pm 2,3283e-07$ ( $\pm 500$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 652 |
| Max CPU cycles  | 878 |
| Avg CPU cycles  | 837 |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysmO2.

| Test results                 |       |       |       |
|------------------------------|-------|-------|-------|
| Time step                    | 1     | 2     | 3     |
| <i>Mask parameters</i>       |       |       |       |
| <b>A</b>                     | [1x4] | [1x4] | [1x4] |
| <b>B</b>                     | [1x4] | [1x4] | [1x4] |
| <i>Controller parameters</i> |       |       |       |
| <b>a11</b>                   | 0     | 0     | 0     |
| <b>a22</b>                   | 30    | 3     | 0.3   |
| <b>b21</b>                   | 20    | 2     | 0.2   |
| <b>a21</b>                   | 20    | 2     | 0.2   |
| <b>b12</b>                   | 10    | 1     | 0.1   |
| <b>a12</b>                   | 10    | 1     | 0.1   |
| <b>b11</b>                   | 0     | 0     | 0     |
| <b>b22</b>                   | 30    | 3     | 0.3   |
| <b>Exp. a11</b>              | 0     | 0     | 0     |
| <b>Exp. a22</b>              | 30    | 3     | 0.3   |
| <b>Exp. b21</b>              | 20    | 2     | 0.2   |
| <b>Exp. a21</b>              | 20    | 2     | 0.2   |
| <b>Exp. b12</b>              | 10    | 1     | 0.1   |
| <b>Exp. a12</b>              | 10    | 1     | 0.1   |
| <b>Exp. b11</b>              | 0     | 0     | 0     |
| <b>Exp. b22</b>              | 30    | 3     | 0.3   |

| Test settings |                  |
|---------------|------------------|
| Tolerance a11 | $\pm 0,0000e+00$ |
| Tolerance a22 | $\pm 0,0000e+00$ |
| Tolerance b21 | $\pm 0,0000e+00$ |
| Tolerance a21 | $\pm 0,0000e+00$ |
| Tolerance b12 | $\pm 0,0000e+00$ |
| Tolerance a12 | $\pm 0,0000e+00$ |
| Tolerance b11 | $\pm 0,0000e+00$ |
| Tolerance b22 | $\pm 0,0000e+00$ |

**Verification: TDSysmO2 Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block TDSysmO2.

| Test results    |       |        |     |        |
|-----------------|-------|--------|-----|--------|
| Time step       | 1     | 2      | ... | 174    |
| CPU cycles      | 125   | 108    | ... | 108    |
| Inputs          |       |        |     |        |
| In1 (DSP)       | -0    | -0.1   | ... | -0.6   |
| In2 (DSP)       | -1    | -0.995 | ... | -0.6   |
| In1             | -0    | -0.1   | ... | -0.6   |
| In2             | -1    | -0.995 | ... | -0.6   |
| Parameters      |       |        |     |        |
| A               | [1x4] |        |     |        |
| B               | [1x4] |        |     |        |
| Outputs         |       |        |     |        |
| Out1            | 0     | -0.28  | ... | -0.898 |
| Out2            | 0     | -0.08  | ... | -0.432 |
| Exp. Out1       | 0     | -0.28  | ... | -0.898 |
| Exp. Out2       | 0     | -0.08  | ... | -0.432 |
| Out1 (DSP)      | 0     | -0.28  | ... | -0.898 |
| Out2 (DSP)      | 0     | -0.08  | ... | -0.432 |
| Exp. Out1 (DSP) | 0     | -0.28  | ... | -0.898 |
| Exp. Out2 (DSP) | 0     | -0.08  | ... | -0.432 |

| Test settings  |                                   |
|----------------|-----------------------------------|
| Tolerance Out1 | $\pm 2,3283e-07$ ( $\pm 500$ LSB) |
| Tolerance Out2 | $\pm 2,3283e-07$ ( $\pm 500$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 108 |
| Max CPU cycles  | 125 |
| Avg CPU cycles  | 108 |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysmO2.

| Test results                 |       |       |       |
|------------------------------|-------|-------|-------|
| Time step                    | 1     | 2     | 3     |
| <i>Mask parameters</i>       |       |       |       |
| <b>A</b>                     | [1x4] | [1x4] | [1x4] |
| <b>B</b>                     | [1x4] | [1x4] | [1x4] |
| <i>Controller parameters</i> |       |       |       |
| <b>a11</b>                   | 0     | 0     | 0     |
| <b>a22</b>                   | 30    | 3     | 0.3   |
| <b>b21</b>                   | 20    | 2     | 0.2   |
| <b>a21</b>                   | 20    | 2     | 0.2   |
| <b>b12</b>                   | 10    | 1     | 0.1   |
| <b>a12</b>                   | 10    | 1     | 0.1   |
| <b>b11</b>                   | 0     | 0     | 0     |
| <b>b22</b>                   | 30    | 3     | 0.3   |
| <b>Exp. a11</b>              | 0     | 0     | 0     |
| <b>Exp. a22</b>              | 30    | 3     | 0.3   |
| <b>Exp. b21</b>              | 20    | 2     | 0.2   |
| <b>Exp. a21</b>              | 20    | 2     | 0.2   |
| <b>Exp. b12</b>              | 10    | 1     | 0.1   |
| <b>Exp. a12</b>              | 10    | 1     | 0.1   |
| <b>Exp. b11</b>              | 0     | 0     | 0     |
| <b>Exp. b22</b>              | 30    | 3     | 0.3   |

| Test settings |                  |
|---------------|------------------|
| Tolerance a11 | $\pm 0,0000e+00$ |
| Tolerance a22 | $\pm 0,0000e+00$ |
| Tolerance b21 | $\pm 0,0000e+00$ |
| Tolerance a21 | $\pm 0,0000e+00$ |
| Tolerance b12 | $\pm 0,0000e+00$ |
| Tolerance a12 | $\pm 0,0000e+00$ |
| Tolerance b11 | $\pm 0,0000e+00$ |
| Tolerance b22 | $\pm 0,0000e+00$ |

**Verification: TDSysmO2 Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block TDSysmO2.

| Test results    |       |        |     |        |
|-----------------|-------|--------|-----|--------|
| Time step       | 1     | 2      | ... | 174    |
| CPU cycles      | 90    | 90     | ... | 90     |
| Inputs          |       |        |     |        |
| In1 (DSP)       | -0    | -0.1   | ... | -0.6   |
| In2 (DSP)       | -1    | -0.995 | ... | -0.6   |
| In1             | -0    | -0.1   | ... | -0.6   |
| In2             | -1    | -0.995 | ... | -0.6   |
| Parameters      |       |        |     |        |
| A               | [1x4] |        |     |        |
| B               | [1x4] |        |     |        |
| Outputs         |       |        |     |        |
| Out1            | 0     | -0.28  | ... | -0.898 |
| Out2            | 0     | -0.08  | ... | -0.432 |
| Exp. Out1       | 0     | -0.28  | ... | -0.898 |
| Exp. Out2       | 0     | -0.08  | ... | -0.432 |
| Out1 (DSP)      | 0     | -0.28  | ... | -0.898 |
| Out2 (DSP)      | 0     | -0.08  | ... | -0.432 |
| Exp. Out1 (DSP) | 0     | -0.28  | ... | -0.898 |
| Exp. Out2 (DSP) | 0     | -0.08  | ... | -0.432 |

| Test settings  |                                   |
|----------------|-----------------------------------|
| Tolerance Out1 | $\pm 2,3283e-07$ ( $\pm 500$ LSB) |
| Tolerance Out2 | $\pm 2,3283e-07$ ( $\pm 500$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 90 |
| Max CPU cycles  | 90 |
| Avg CPU cycles  | 90 |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysmO2.

| Test results                 |       |       |       |
|------------------------------|-------|-------|-------|
| Time step                    | 1     | 2     | 3     |
| <i>Mask parameters</i>       |       |       |       |
| <b>A</b>                     | [1x4] | [1x4] | [1x4] |
| <b>B</b>                     | [1x4] | [1x4] | [1x4] |
| <i>Controller parameters</i> |       |       |       |
| <b>a11</b>                   | 0     | 0     | 0     |
| <b>a22</b>                   | 30    | 3     | 0.3   |
| <b>b21</b>                   | 20    | 2     | 0.2   |
| <b>a21</b>                   | 20    | 2     | 0.2   |
| <b>b12</b>                   | 10    | 1     | 0.1   |
| <b>a12</b>                   | 10    | 1     | 0.1   |
| <b>b11</b>                   | 0     | 0     | 0     |
| <b>b22</b>                   | 30    | 3     | 0.3   |
| <b>Exp. a11</b>              | 0     | 0     | 0     |
| <b>Exp. a22</b>              | 30    | 3     | 0.3   |
| <b>Exp. b21</b>              | 20    | 2     | 0.2   |
| <b>Exp. a21</b>              | 20    | 2     | 0.2   |
| <b>Exp. b12</b>              | 10    | 1     | 0.1   |
| <b>Exp. a12</b>              | 10    | 1     | 0.1   |
| <b>Exp. b11</b>              | 0     | 0     | 0     |
| <b>Exp. b22</b>              | 30    | 3     | 0.3   |

| Test settings |                  |
|---------------|------------------|
| Tolerance a11 | $\pm 0,0000e+00$ |
| Tolerance a22 | $\pm 0,0000e+00$ |
| Tolerance b21 | $\pm 0,0000e+00$ |
| Tolerance a21 | $\pm 0,0000e+00$ |
| Tolerance b12 | $\pm 0,0000e+00$ |
| Tolerance a12 | $\pm 0,0000e+00$ |
| Tolerance b11 | $\pm 0,0000e+00$ |
| Tolerance b22 | $\pm 0,0000e+00$ |

**Verification: TDSysO2 Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block TDSysO2.

| Test results    |       |        |     |        |
|-----------------|-------|--------|-----|--------|
| Time step       | 1     | 2      | ... | 174    |
| CPU cycles      | 1940  | 2366   | ... | 2397   |
| Inputs          |       |        |     |        |
| In1 (DSP)       | -0    | -0.1   | ... | -0.6   |
| In2 (DSP)       | -1    | -0.995 | ... | -0.6   |
| In1             | -0    | -0.1   | ... | -0.6   |
| In2             | -1    | -0.995 | ... | -0.6   |
| Parameters      |       |        |     |        |
| A               | [1x4] |        |     |        |
| B               | [1x4] |        |     |        |
| Outputs         |       |        |     |        |
| Out1            | 0     | -0.28  | ... | -0.898 |
| Out2            | 0     | -0.08  | ... | -0.432 |
| Exp. Out1       | 0     | -0.28  | ... | -0.898 |
| Exp. Out2       | 0     | -0.08  | ... | -0.432 |
| Out1 (DSP)      | 0     | -0.28  | ... | -0.898 |
| Out2 (DSP)      | 0     | -0.08  | ... | -0.432 |
| Exp. Out1 (DSP) | 0     | -0.28  | ... | -0.898 |
| Exp. Out2 (DSP) | 0     | -0.08  | ... | -0.432 |

| Test settings  |                                   |
|----------------|-----------------------------------|
| Tolerance Out1 | $\pm 2,3283e-07$ ( $\pm 500$ LSB) |
| Tolerance Out2 | $\pm 2,3283e-07$ ( $\pm 500$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1940 |
| Max CPU cycles  | 2469 |
| Avg CPU cycles  | 2331 |

**Test case: Conversion test****OK**

Conversion test for Control block TDSysO2.


| Test results                 |       |       |       |
|------------------------------|-------|-------|-------|
| Time step                    | 1     | 2     | 3     |
| <i>Mask parameters</i>       |       |       |       |
| <b>A</b>                     | [1x4] | [1x4] | [1x4] |
| <b>B</b>                     | [1x4] | [1x4] | [1x4] |
| <i>Controller parameters</i> |       |       |       |
| <b>a11</b>                   | 0     | 0     | 0     |
| <b>a22</b>                   | 30    | 3     | 0.3   |
| <b>b21</b>                   | 20    | 2     | 0.2   |
| <b>a21</b>                   | 20    | 2     | 0.2   |
| <b>b12</b>                   | 10    | 1     | 0.1   |
| <b>a12</b>                   | 10    | 1     | 0.1   |
| <b>b11</b>                   | 0     | 0     | 0     |
| <b>b22</b>                   | 30    | 3     | 0.3   |
| <b>Exp. a11</b>              | 0     | 0     | 0     |
| <b>Exp. a22</b>              | 30    | 3     | 0.3   |
| <b>Exp. b21</b>              | 20    | 2     | 0.2   |
| <b>Exp. a21</b>              | 20    | 2     | 0.2   |
| <b>Exp. b12</b>              | 10    | 1     | 0.1   |
| <b>Exp. a12</b>              | 10    | 1     | 0.1   |
| <b>Exp. b11</b>              | 0     | 0     | 0     |
| <b>Exp. b22</b>              | 30    | 3     | 0.3   |

| Test settings |                  |
|---------------|------------------|
| Tolerance a11 | $\pm 0,0000e+00$ |
| Tolerance a22 | $\pm 0,0000e+00$ |
| Tolerance b21 | $\pm 0,0000e+00$ |
| Tolerance a21 | $\pm 0,0000e+00$ |
| Tolerance b12 | $\pm 0,0000e+00$ |
| Tolerance a12 | $\pm 0,0000e+00$ |
| Tolerance b11 | $\pm 0,0000e+00$ |
| Tolerance b22 | $\pm 0,0000e+00$ |



## Block: TF1

---



First order transfer function:

$$G(z) = (b1 \cdot z + b0) / (z + a0)$$

| Inports |             |
|---------|-------------|
| In      | Input In(k) |

| Outports |               |
|----------|---------------|
| Out      | Output Out(k) |

| Mask Parameters |    |                                                                 |
|-----------------|----|-----------------------------------------------------------------|
| Name            | ID | Description                                                     |
| b1              | 1  | b1                                                              |
| b0              | 2  | b0                                                              |
| a0              | 3  | a0                                                              |
| ts_fact         | 4  | Multiplication factor of base sampling time (in integer format) |

### Description:

Due to limited value range in the 8 bit fixed point implementation rather high deviations from expected output values may occur.

**Developer note:** The source code of this block is used for blocks *DT1* and *PT1*.

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | int8 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |


### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

## Block: TF2



Second order transfer function:

$$G(z) = (b_2.z^2 + b_1.z + b_0) / (z^2 + a_1.z + a_0)$$

| Inports |             |
|---------|-------------|
| In      | Input In(k) |

| Outports |               |
|----------|---------------|
| Out      | Output Out(k) |

| Mask Parameters |    |                                                                 |
|-----------------|----|-----------------------------------------------------------------|
| Name            | ID | Description                                                     |
| b2              | 1  | b2                                                              |
| b1              | 2  | b1                                                              |
| b0              | 3  | b0                                                              |
| a1              | 4  | a1                                                              |
| a0              | 5  | a0                                                              |
| ts_fact         | 6  | Multiplication factor of base sampling time (in integer format) |

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP16

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | int8 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP32

---

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

---

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64


---

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

## Block: ul



Integrator for angle signals:

$$G(s) = K_i/s = 1/(T_i*s)$$

| Inports |                                                                                                                                    |
|---------|------------------------------------------------------------------------------------------------------------------------------------|
| In      | Control error input                                                                                                                |
| Init    | Value which is loaded at initialization function call                                                                              |
| Enable  | Enable == 0: Deactivation of block; Out is set to 0.<br>Enable 0->1: Preload of integral part.<br>Enable == 1: Activation of block |

| Outputs |                   |
|---------|-------------------|
| Out     | Integrator output |

| Mask Parameters |    |                                                                 |
|-----------------|----|-----------------------------------------------------------------|
| Name            | ID | Description                                                     |
| Ki              | 1  | Integral Factor                                                 |
| ts_fact         | 2  | Multiplication factor of base sampling time (in integer format) |

### Description:

Each fixed point implementation uses the next higher integer datatype for the integrational value storage variable.

A rising flank at the *Enable* inport will preload the integrational part with the value present on the *Init* inport.

Transfer function (zero-order hold discretization method):

$$G(z) = K_i T_s \frac{1}{z - 1}$$

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | int8 |
| Init              | int8 |
| Enable            | bool |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |
| Init              | int16 |
| Enable            | bool  |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

---

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |
| Init              | int32 |
| Enable            | bool  |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

---

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |
| Init              | float32 |
| Enable            | bool    |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

---

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |
| Init              | float64 |
| Enable            | bool    |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |



**Verification: ul FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block ul.

| Test results   |      |      |      |      |     |        |
|----------------|------|------|------|------|-----|--------|
| Time step      | 1    | 2    | 3    | 4    | ... | 351    |
| CPU cycles     | 67   | 67   | 67   | 99   | ... | 94     |
| Inputs         |      |      |      |      |     |        |
| In (DSP)       | 0    | 0    | 0    | 0    | ... | -8192  |
| Init (DSP)     | 3604 | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0    | 0    | 0    | 1    | ... | 1      |
| In             | 0    | 0    | 0    | 0    | ... | -0.25  |
| Init           | 0.11 | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0    | 0    | 0    | 1    | ... | 1      |
| Parameters     |      |      |      |      |     |        |
| Ki             | 500  |      |      |      |     |        |
| ts_fact        | 1    |      |      |      |     |        |
| Outputs        |      |      |      |      |     |        |
| Out            | 0    | 0    | 0    | 0.11 | ... | -0.779 |
| Exp. Out       | 0    | 0    | 0    | 0.11 | ... | -0.78  |
| Out (DSP)      | 0    | 0    | 0    | 3604 | ... | -25539 |
| Exp. Out (DSP) | 0    | 0    | 0    | 3604 | ... | -25559 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 7,6294e-04$ ( $\pm 25$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 67 |
| Max CPU cycles  | 99 |
| Avg CPU cycles  | 93 |

**Test case: Conversion test****OK**

Conversion test for Control block ul.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ul.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1333 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2076 |
| Max CPU cycles  | 2170 |
| Avg CPU cycles  | 2160 |

**Verification: ul FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block ul.

| Test results   |      |      |      |      |     |        |
|----------------|------|------|------|------|-----|--------|
| Time step      | 1    | 2    | 3    | 4    | ... | 351    |
| CPU cycles     | 43   | 43   | 43   | 61   | ... | 59     |
| Inputs         |      |      |      |      |     |        |
| In (DSP)       | 0    | 0    | 0    | 0    | ... | -8192  |
| Init (DSP)     | 3604 | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0    | 0    | 0    | 1    | ... | 1      |
| In             | 0    | 0    | 0    | 0    | ... | -0.25  |
| Init           | 0.11 | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0    | 0    | 0    | 1    | ... | 1      |
| Parameters     |      |      |      |      |     |        |
| Ki             | 500  |      |      |      |     |        |
| ts_fact        | 1    |      |      |      |     |        |
| Outputs        |      |      |      |      |     |        |
| Out            | 0    | 0    | 0    | 0.11 | ... | -0.779 |
| Exp. Out       | 0    | 0    | 0    | 0.11 | ... | -0.78  |
| Out (DSP)      | 0    | 0    | 0    | 3604 | ... | -25539 |
| Exp. Out (DSP) | 0    | 0    | 0    | 3604 | ... | -25559 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 7,6294e-04$ ( $\pm 25$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 43 |
| Max CPU cycles  | 61 |
| Avg CPU cycles  | 58 |

**Test case: Conversion test****OK**

Conversion test for Control block ul.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ul.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1333 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1071 |
| Max CPU cycles  | 1141 |
| Avg CPU cycles  | 1139 |

**Verification: ul FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block ul.

| Test results   |      |      |      |      |     |        |
|----------------|------|------|------|------|-----|--------|
| Time step      | 1    | 2    | 3    | 4    | ... | 351    |
| CPU cycles     | 68   | 68   | 68   | 98   | ... | 83     |
| Inputs         |      |      |      |      |     |        |
| In (DSP)       | 0    | 0    | 0    | 0    | ... | -8192  |
| Init (DSP)     | 3604 | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0    | 0    | 0    | 1    | ... | 1      |
| In             | 0    | 0    | 0    | 0    | ... | -0.25  |
| Init           | 0.11 | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0    | 0    | 0    | 1    | ... | 1      |
| Parameters     |      |      |      |      |     |        |
| Ki             | 500  |      |      |      |     |        |
| ts_fact        | 1    |      |      |      |     |        |
| Outputs        |      |      |      |      |     |        |
| Out            | 0    | 0    | 0    | 0.11 | ... | -0.779 |
| Exp. Out       | 0    | 0    | 0    | 0.11 | ... | -0.78  |
| Out (DSP)      | 0    | 0    | 0    | 3604 | ... | -25539 |
| Exp. Out (DSP) | 0    | 0    | 0    | 3604 | ... | -25559 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 7,6294e-04$ ( $\pm 25$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 68 |
| Max CPU cycles  | 98 |
| Avg CPU cycles  | 82 |

**Test case: Conversion test****OK**

Conversion test for Control block ul.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ul.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1333 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1180 |
| Max CPU cycles  | 1235 |
| Avg CPU cycles  | 1217 |

**Verification: ul FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block ul.

| Test results   |      |      |      |      |     |        |
|----------------|------|------|------|------|-----|--------|
| Time step      | 1    | 2    | 3    | 4    | ... | 351    |
| CPU cycles     | 61   | 61   | 61   | 96   | ... | 85     |
| Inputs         |      |      |      |      |     |        |
| In (DSP)       | 0    | 0    | 0    | 0    | ... | -8192  |
| Init (DSP)     | 3604 | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0    | 0    | 0    | 1    | ... | 1      |
| In             | 0    | 0    | 0    | 0    | ... | -0.25  |
| Init           | 0.11 | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0    | 0    | 0    | 1    | ... | 1      |
| Parameters     |      |      |      |      |     |        |
| Ki             | 500  |      |      |      |     |        |
| ts_fact        | 1    |      |      |      |     |        |
| Outputs        |      |      |      |      |     |        |
| Out            | 0    | 0    | 0    | 0.11 | ... | -0.779 |
| Exp. Out       | 0    | 0    | 0    | 0.11 | ... | -0.78  |
| Out (DSP)      | 0    | 0    | 0    | 3604 | ... | -25539 |
| Exp. Out (DSP) | 0    | 0    | 0    | 3604 | ... | -25559 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 7,6294e-04$ ( $\pm 25$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 61  |
| Max CPU cycles  | 147 |
| Avg CPU cycles  | 85  |

**Test case: Conversion test****OK**

Conversion test for Control block ul.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ul.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1333 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2537 |
| Max CPU cycles  | 3018 |
| Avg CPU cycles  | 2948 |



**Verification: ul FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block ul.

| Test results   |      |      |      |      |     |        |
|----------------|------|------|------|------|-----|--------|
| Time step      | 1    | 2    | 3    | 4    | ... | 351    |
| CPU cycles     | 31   | 31   | 31   | 59   | ... | 55     |
| Inputs         |      |      |      |      |     |        |
| In (DSP)       | 0    | 0    | 0    | 0    | ... | -8192  |
| Init (DSP)     | 3604 | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0    | 0    | 0    | 1    | ... | 1      |
| In             | 0    | 0    | 0    | 0    | ... | -0.25  |
| Init           | 0.11 | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0    | 0    | 0    | 1    | ... | 1      |
| Parameters     |      |      |      |      |     |        |
| Ki             | 500  |      |      |      |     |        |
| ts_fact        | 1    |      |      |      |     |        |
| Outputs        |      |      |      |      |     |        |
| Out            | 0    | 0    | 0    | 0.11 | ... | -0.779 |
| Exp. Out       | 0    | 0    | 0    | 0.11 | ... | -0.78  |
| Out (DSP)      | 0    | 0    | 0    | 3604 | ... | -25539 |
| Exp. Out (DSP) | 0    | 0    | 0    | 3604 | ... | -25559 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 7,6294e-04$ ( $\pm 25$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 59 |
| Avg CPU cycles  | 54 |

**Test case: Conversion test****OK**

Conversion test for Control block ul.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ul.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1333 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1072 |
| Max CPU cycles  | 1188 |
| Avg CPU cycles  | 1179 |

**Verification: ul FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block ul.

| Test results   |      |      |      |      |     |        |
|----------------|------|------|------|------|-----|--------|
| Time step      | 1    | 2    | 3    | 4    | ... | 351    |
| CPU cycles     | 72   | 59   | 59   | 86   | ... | 86     |
| Inputs         |      |      |      |      |     |        |
| In (DSP)       | 0    | 0    | 0    | 0    | ... | -8192  |
| Init (DSP)     | 3604 | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0    | 0    | 0    | 1    | ... | 1      |
| In             | 0    | 0    | 0    | 0    | ... | -0.25  |
| Init           | 0.11 | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0    | 0    | 0    | 1    | ... | 1      |
| Parameters     |      |      |      |      |     |        |
| Ki             | 500  |      |      |      |     |        |
| ts_fact        | 1    |      |      |      |     |        |
| Outputs        |      |      |      |      |     |        |
| Out            | 0    | 0    | 0    | 0.11 | ... | -0.779 |
| Exp. Out       | 0    | 0    | 0    | 0.11 | ... | -0.78  |
| Out (DSP)      | 0    | 0    | 0    | 3604 | ... | -25539 |
| Exp. Out (DSP) | 0    | 0    | 0    | 3604 | ... | -25559 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 7,6294e-04$ ( $\pm 25$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 86 |
| Avg CPU cycles  | 85 |

**Test case: Conversion test****OK**

Conversion test for Control block ul.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ul.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1333 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 857 |
| Max CPU cycles  | 985 |
| Avg CPU cycles  | 878 |

**Verification: ul FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block ul.

| Test results   |      |      |      |      |     |        |
|----------------|------|------|------|------|-----|--------|
| Time step      | 1    | 2    | 3    | 4    | ... | 351    |
| CPU cycles     | 57   | 57   | 57   | 100  | ... | 93     |
| Inputs         |      |      |      |      |     |        |
| In (DSP)       | 0    | 0    | 0    | 0    | ... | -8192  |
| Init (DSP)     | 3604 | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0    | 0    | 0    | 1    | ... | 1      |
| In             | 0    | 0    | 0    | 0    | ... | -0.25  |
| Init           | 0.11 | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0    | 0    | 0    | 1    | ... | 1      |
| Parameters     |      |      |      |      |     |        |
| Ki             | 500  |      |      |      |     |        |
| ts_fact        | 1    |      |      |      |     |        |
| Outputs        |      |      |      |      |     |        |
| Out            | 0    | 0    | 0    | 0.11 | ... | -0.779 |
| Exp. Out       | 0    | 0    | 0    | 0.11 | ... | -0.78  |
| Out (DSP)      | 0    | 0    | 0    | 3604 | ... | -25539 |
| Exp. Out (DSP) | 0    | 0    | 0    | 3604 | ... | -25559 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 7,6294e-04$ ( $\pm 25$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 57  |
| Max CPU cycles  | 100 |
| Avg CPU cycles  | 92  |

**Test case: Conversion test****OK**

Conversion test for Control block ul.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ul.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1333 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1595 |
| Max CPU cycles  | 1665 |
| Avg CPU cycles  | 1660 |

**Verification: ul FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block ul.

| Test results   |      |      |      |      |     |        |
|----------------|------|------|------|------|-----|--------|
| Time step      | 1    | 2    | 3    | 4    | ... | 351    |
| CPU cycles     | 48   | 48   | 48   | 80   | ... | 79     |
| Inputs         |      |      |      |      |     |        |
| In (DSP)       | 0    | 0    | 0    | 0    | ... | -8192  |
| Init (DSP)     | 3604 | 3604 | 3604 | 3604 | ... | 3604   |
| Enable (DSP)   | 0    | 0    | 0    | 1    | ... | 1      |
| In             | 0    | 0    | 0    | 0    | ... | -0.25  |
| Init           | 0.11 | 0.11 | 0.11 | 0.11 | ... | 0.11   |
| Enable         | 0    | 0    | 0    | 1    | ... | 1      |
| Parameters     |      |      |      |      |     |        |
| Ki             | 500  |      |      |      |     |        |
| ts_fact        | 1    |      |      |      |     |        |
| Outputs        |      |      |      |      |     |        |
| Out            | 0    | 0    | 0    | 0.11 | ... | -0.779 |
| Exp. Out       | 0    | 0    | 0    | 0.11 | ... | -0.78  |
| Out (DSP)      | 0    | 0    | 0    | 3604 | ... | -25539 |
| Exp. Out (DSP) | 0    | 0    | 0    | 3604 | ... | -25559 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 7,6294e-04$ ( $\pm 25$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 48 |
| Max CPU cycles  | 80 |
| Avg CPU cycles  | 78 |

**Test case: Conversion test****OK**

Conversion test for Control block ul.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ul.

| Test results                 |     |         |        |        |     |      |
|------------------------------|-----|---------|--------|--------|-----|------|
| <b>Time step</b>             | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Mask parameters</i>       |     |         |        |        |     |      |
| <b>Ki</b>                    | -11 | -10.389 | -9.778 | -9.167 | ... | 11   |
| <b>ts_fact</b>               | 1   | 2       | 3      | 4      | ... | 37   |
| <i>Controller parameters</i> |     |         |        |        |     |      |
| <b>b0</b>                    | -36 | -68     | -96    | -120   | ... | 1333 |
| <b>sfr</b>                   | 15  | 15      | 15     | 15     | ... | 15   |
| <b>Exp. b0</b>               | -36 | -68     | -96    | -120   | ... | 1334 |
| <b>Exp. sfr</b>              | 15  | 15      | 15     | 15     | ... | 15   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 4133 |
| Max CPU cycles  | 5289 |
| Avg CPU cycles  | 5242 |



**Verification: ul FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block ul.

| Test results   |           |           |     |             |
|----------------|-----------|-----------|-----|-------------|
| Time step      | 1         | 2         | ... | 351         |
| CPU cycles     | 74        | 74        | ... | 124         |
| Inputs         |           |           |     |             |
| In (DSP)       | 0         | 0         | ... | -536870912  |
| Init (DSP)     | 236223201 | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0         | 0         | ... | 1           |
| In             | 0         | 0         | ... | -0.25       |
| Init           | 0.11      | 0.11      | ... | 0.11        |
| Enable         | 0         | 0         | ... | 1           |
| Parameters     |           |           |     |             |
| Ki             | 500       |           |     |             |
| ts_fact        | 1         |           |     |             |
| Outputs        |           |           |     |             |
| Out            | 0         | 0         | ... | -0.78       |
| Exp. Out       | 0         | 0         | ... | -0.78       |
| Out (DSP)      | 0         | 0         | ... | -1675037225 |
| Exp. Out (DSP) | 0         | 0         | ... | -1675037245 |

| Test settings |                                         |
|---------------|-----------------------------------------|
| Tolerance Out | $\pm 1,1642\text{e-}08$ ( $\pm 25$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 74  |
| Max CPU cycles  | 131 |
| Avg CPU cycles  | 123 |

**Test case: Conversion test****OK**

Conversion test for Control block ul.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ul.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 8,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2254 |
| Max CPU cycles  | 2396 |
| Avg CPU cycles  | 2381 |

**Verification: ul FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block ul.

| Test results   |           |           |     |             |
|----------------|-----------|-----------|-----|-------------|
| Time step      | 1         | 2         | ... | 351         |
| CPU cycles     | 51        | 51        | ... | 101         |
| Inputs         |           |           |     |             |
| In (DSP)       | 0         | 0         | ... | -536870912  |
| Init (DSP)     | 236223201 | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0         | 0         | ... | 1           |
| In             | 0         | 0         | ... | -0.25       |
| Init           | 0.11      | 0.11      | ... | 0.11        |
| Enable         | 0         | 0         | ... | 1           |
| Parameters     |           |           |     |             |
| Ki             | 500       |           |     |             |
| ts_fact        | 1         |           |     |             |
| Outputs        |           |           |     |             |
| Out            | 0         | 0         | ... | -0.78       |
| Exp. Out       | 0         | 0         | ... | -0.78       |
| Out (DSP)      | 0         | 0         | ... | -1675037225 |
| Exp. Out (DSP) | 0         | 0         | ... | -1675037245 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 1,1642e-08$ ( $\pm 25$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 51  |
| Max CPU cycles  | 109 |
| Avg CPU cycles  | 100 |

**Test case: Conversion test****OK**

Conversion test for Control block ul.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ul.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 8,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1027 |
| Max CPU cycles  | 1125 |
| Avg CPU cycles  | 1121 |

**Verification: ul FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block ul.

| Test results   |           |           |     |             |
|----------------|-----------|-----------|-----|-------------|
| Time step      | 1         | 2         | ... | 351         |
| CPU cycles     | 79        | 79        | ... | 109         |
| Inputs         |           |           |     |             |
| In (DSP)       | 0         | 0         | ... | -536870912  |
| Init (DSP)     | 236223201 | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0         | 0         | ... | 1           |
| In             | 0         | 0         | ... | -0.25       |
| Init           | 0.11      | 0.11      | ... | 0.11        |
| Enable         | 0         | 0         | ... | 1           |
| Parameters     |           |           |     |             |
| Ki             | 500       |           |     |             |
| ts_fact        | 1         |           |     |             |
| Outputs        |           |           |     |             |
| Out            | 0         | 0         | ... | -0.78       |
| Exp. Out       | 0         | 0         | ... | -0.78       |
| Out (DSP)      | 0         | 0         | ... | -1675037225 |
| Exp. Out (DSP) | 0         | 0         | ... | -1675037245 |

| Test settings |                                         |
|---------------|-----------------------------------------|
| Tolerance Out | $\pm 1,1642\text{e-}08$ ( $\pm 25$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 79  |
| Max CPU cycles  | 127 |
| Avg CPU cycles  | 108 |

**Test case: Conversion test****OK**

Conversion test for Control block ul.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ul.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 8,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1555 |
| Max CPU cycles  | 1614 |
| Avg CPU cycles  | 1599 |

**Verification: ul FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block ul.

| Test results   |           |           |     |             |
|----------------|-----------|-----------|-----|-------------|
| Time step      | 1         | 2         | ... | 351         |
| CPU cycles     | 82        | 82        | ... | 205         |
| Inputs         |           |           |     |             |
| In (DSP)       | 0         | 0         | ... | -536870912  |
| Init (DSP)     | 236223201 | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0         | 0         | ... | 1           |
| In             | 0         | 0         | ... | -0.25       |
| Init           | 0.11      | 0.11      | ... | 0.11        |
| Enable         | 0         | 0         | ... | 1           |
| Parameters     |           |           |     |             |
| Ki             | 500       |           |     |             |
| ts_fact        | 1         |           |     |             |
| Outputs        |           |           |     |             |
| Out            | 0         | 0         | ... | -0.78       |
| Exp. Out       | 0         | 0         | ... | -0.78       |
| Out (DSP)      | 0         | 0         | ... | -1675037225 |
| Exp. Out (DSP) | 0         | 0         | ... | -1675037245 |

| Test settings |                                         |
|---------------|-----------------------------------------|
| Tolerance Out | $\pm 1,1642\text{e-}08$ ( $\pm 25$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 82  |
| Max CPU cycles  | 265 |
| Avg CPU cycles  | 204 |

**Test case: Conversion test****OK**

Conversion test for Control block ul.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ul.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 8,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3570 |
| Max CPU cycles  | 4304 |
| Avg CPU cycles  | 4226 |



**Verification: ul FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block ul.

| Test results   |           |           |     |             |
|----------------|-----------|-----------|-----|-------------|
| Time step      | 1         | 2         | ... | 351         |
| CPU cycles     | 31        | 31        | ... | 77          |
| Inputs         |           |           |     |             |
| In (DSP)       | 0         | 0         | ... | -536870912  |
| Init (DSP)     | 236223201 | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0         | 0         | ... | 1           |
| In             | 0         | 0         | ... | -0.25       |
| Init           | 0.11      | 0.11      | ... | 0.11        |
| Enable         | 0         | 0         | ... | 1           |
| Parameters     |           |           |     |             |
| Ki             | 500       |           |     |             |
| ts_fact        | 1         |           |     |             |
| Outputs        |           |           |     |             |
| Out            | 0         | 0         | ... | -0.78       |
| Exp. Out       | 0         | 0         | ... | -0.78       |
| Out (DSP)      | 0         | 0         | ... | -1675037225 |
| Exp. Out (DSP) | 0         | 0         | ... | -1675037245 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 1,1642e-08$ ( $\pm 25$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 80 |
| Avg CPU cycles  | 76 |

**Test case: Conversion test****OK**

Conversion test for Control block ul.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ul.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 8,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1528 |
| Max CPU cycles  | 1722 |
| Avg CPU cycles  | 1707 |

**Verification: ul FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block ul.

| Test results   |           |           |     |             |
|----------------|-----------|-----------|-----|-------------|
| Time step      | 1         | 2         | ... | 351         |
| CPU cycles     | 77        | 59        | ... | 113         |
| Inputs         |           |           |     |             |
| In (DSP)       | 0         | 0         | ... | -536870912  |
| Init (DSP)     | 236223201 | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0         | 0         | ... | 1           |
| In             | 0         | 0         | ... | -0.25       |
| Init           | 0.11      | 0.11      | ... | 0.11        |
| Enable         | 0         | 0         | ... | 1           |
| Parameters     |           |           |     |             |
| Ki             | 500       |           |     |             |
| ts_fact        | 1         |           |     |             |
| Outputs        |           |           |     |             |
| Out            | 0         | 0         | ... | -0.78       |
| Exp. Out       | 0         | 0         | ... | -0.78       |
| Out (DSP)      | 0         | 0         | ... | -1675037225 |
| Exp. Out (DSP) | 0         | 0         | ... | -1675037245 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 1,1642e-08$ ( $\pm 25$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 59  |
| Max CPU cycles  | 119 |
| Avg CPU cycles  | 112 |

**Test case: Conversion test****OK**

Conversion test for Control block ul.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ul.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 8,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1178 |
| Max CPU cycles  | 1381 |
| Avg CPU cycles  | 1209 |

**Verification: ul FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block ul.

| Test results   |           |           |     |             |
|----------------|-----------|-----------|-----|-------------|
| Time step      | 1         | 2         | ... | 351         |
| CPU cycles     | 66        | 66        | ... | 122         |
| Inputs         |           |           |     |             |
| In (DSP)       | 0         | 0         | ... | -536870912  |
| Init (DSP)     | 236223201 | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0         | 0         | ... | 1           |
| In             | 0         | 0         | ... | -0.25       |
| Init           | 0.11      | 0.11      | ... | 0.11        |
| Enable         | 0         | 0         | ... | 1           |
| Parameters     |           |           |     |             |
| Ki             | 500       |           |     |             |
| ts_fact        | 1         |           |     |             |
| Outputs        |           |           |     |             |
| Out            | 0         | 0         | ... | -0.78       |
| Exp. Out       | 0         | 0         | ... | -0.78       |
| Out (DSP)      | 0         | 0         | ... | -1675037225 |
| Exp. Out (DSP) | 0         | 0         | ... | -1675037245 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 1,1642e-08$ ( $\pm 25$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 66  |
| Max CPU cycles  | 129 |
| Avg CPU cycles  | 121 |

**Test case: Conversion test****OK**

Conversion test for Control block ul.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ul.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 8,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1691 |
| Max CPU cycles  | 1804 |
| Avg CPU cycles  | 1794 |

**Verification: ul FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block ul.

| Test results   |           |           |     |             |
|----------------|-----------|-----------|-----|-------------|
| Time step      | 1         | 2         | ... | 351         |
| CPU cycles     | 53        | 53        | ... | 207         |
| Inputs         |           |           |     |             |
| In (DSP)       | 0         | 0         | ... | -536870912  |
| Init (DSP)     | 236223201 | 236223201 | ... | 236223201   |
| Enable (DSP)   | 0         | 0         | ... | 1           |
| In             | 0         | 0         | ... | -0.25       |
| Init           | 0.11      | 0.11      | ... | 0.11        |
| Enable         | 0         | 0         | ... | 1           |
| Parameters     |           |           |     |             |
| Ki             | 500       |           |     |             |
| ts_fact        | 1         |           |     |             |
| Outputs        |           |           |     |             |
| Out            | 0         | 0         | ... | -0.78       |
| Exp. Out       | 0         | 0         | ... | -0.78       |
| Out (DSP)      | 0         | 0         | ... | -1675037225 |
| Exp. Out (DSP) | 0         | 0         | ... | -1675037245 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 1,1642e-08$ ( $\pm 25$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 53  |
| Max CPU cycles  | 207 |
| Avg CPU cycles  | 203 |

**Test case: Conversion test****OK**

Conversion test for Control block ul.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ul.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 37       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>Ki</b>                    | -11      | -10.389  | ... | 11       |
| <b>ts_fact</b>               | 1        | 2        | ... | 37       |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b0</b>                    | -2362232 | -4461994 | ... | 87402584 |
| <b>sfr</b>                   | 31       | 31       | ... | 31       |
| <b>Exp. b0</b>               | -2362232 | -4461994 | ... | 87402584 |
| <b>Exp. sfr</b>              | 31       | 31       | ... | 31       |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 8,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 4539 |
| Max CPU cycles  | 5609 |
| Avg CPU cycles  | 5551 |



**Verification: ul Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Control block ul.

| Test results   |      |      |     |       |
|----------------|------|------|-----|-------|
| Time step      | 1    | 2    | ... | 401   |
| CPU cycles     | 74   | 74   | ... | 117   |
| Inputs         |      |      |     |       |
| In (DSP)       | 0    | 0    | ... | -0.2  |
| Init (DSP)     | 0.11 | 0.11 | ... | 0.11  |
| Enable (DSP)   | 0    | 0    | ... | 1     |
| In             | 0    | 0    | ... | -0.2  |
| Init           | 0.11 | 0.11 | ... | 0.11  |
| Enable         | 0    | 0    | ... | 1     |
| Parameters     |      |      |     |       |
| Ki             | 500  |      |     |       |
| ts_fact        | 1    |      |     |       |
| Outputs        |      |      |     |       |
| Out            | 0    | 0    | ... | -1.82 |
| Exp. Out       | 0    | 0    | ... | -1.82 |
| Out (DSP)      | 0    | 0    | ... | -1.82 |
| Exp. Out (DSP) | 0    | 0    | ... | -1.82 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 1,3970e-06$ ( $\pm 3000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 74  |
| Max CPU cycles  | 117 |
| Avg CPU cycles  | 116 |

**Test case: Conversion test****OK**

Conversion test for Control block ul.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ul.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 3,0000e-08$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1495 |
| Max CPU cycles  | 1518 |
| Avg CPU cycles  | 1500 |

**Verification: ul Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Control block ul.

| Test results   |      |      |     |       |
|----------------|------|------|-----|-------|
| Time step      | 1    | 2    | ... | 401   |
| CPU cycles     | 41   | 41   | ... | 79    |
| Inputs         |      |      |     |       |
| In (DSP)       | 0    | 0    | ... | -0.2  |
| Init (DSP)     | 0.11 | 0.11 | ... | 0.11  |
| Enable (DSP)   | 0    | 0    | ... | 1     |
| In             | 0    | 0    | ... | -0.2  |
| Init           | 0.11 | 0.11 | ... | 0.11  |
| Enable         | 0    | 0    | ... | 1     |
| Parameters     |      |      |     |       |
| Ki             | 500  |      |     |       |
| ts_fact        | 1    |      |     |       |
| Outputs        |      |      |     |       |
| Out            | 0    | 0    | ... | -1.82 |
| Exp. Out       | 0    | 0    | ... | -1.82 |
| Out (DSP)      | 0    | 0    | ... | -1.82 |
| Exp. Out (DSP) | 0    | 0    | ... | -1.82 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 1,3970e-06$ ( $\pm 3000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 41 |
| Max CPU cycles  | 89 |
| Avg CPU cycles  | 78 |

**Test case: Conversion test****OK**

Conversion test for Control block ul.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ul.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 3,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 741 |
| Max CPU cycles  | 741 |
| Avg CPU cycles  | 741 |

**Verification: ul Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Control block ul.

| Test results   |      |      |     |       |
|----------------|------|------|-----|-------|
| Time step      | 1    | 2    | ... | 401   |
| CPU cycles     | 73   | 73   | ... | 123   |
| Inputs         |      |      |     |       |
| In (DSP)       | 0    | 0    | ... | -0.2  |
| Init (DSP)     | 0.11 | 0.11 | ... | 0.11  |
| Enable (DSP)   | 0    | 0    | ... | 1     |
| In             | 0    | 0    | ... | -0.2  |
| Init           | 0.11 | 0.11 | ... | 0.11  |
| Enable         | 0    | 0    | ... | 1     |
| Parameters     |      |      |     |       |
| Ki             | 500  |      |     |       |
| ts_fact        | 1    |      |     |       |
| Outputs        |      |      |     |       |
| Out            | 0    | 0    | ... | -1.82 |
| Exp. Out       | 0    | 0    | ... | -1.82 |
| Out (DSP)      | 0    | 0    | ... | -1.82 |
| Exp. Out (DSP) | 0    | 0    | ... | -1.82 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 1,3970e-06$ ( $\pm 3000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 73  |
| Max CPU cycles  | 136 |
| Avg CPU cycles  | 122 |

**Test case: Conversion test****OK**

Conversion test for Control block ul.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ul.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 3,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 789 |
| Max CPU cycles  | 834 |
| Avg CPU cycles  | 822 |

**Verification: ul Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Control block ul.

| Test results   |      |      |     |       |
|----------------|------|------|-----|-------|
| Time step      | 1    | 2    | ... | 401   |
| CPU cycles     | 66   | 66   | ... | 562   |
| Inputs         |      |      |     |       |
| In (DSP)       | 0    | 0    | ... | -0.2  |
| Init (DSP)     | 0.11 | 0.11 | ... | 0.11  |
| Enable (DSP)   | 0    | 0    | ... | 1     |
| In             | 0    | 0    | ... | -0.2  |
| Init           | 0.11 | 0.11 | ... | 0.11  |
| Enable         | 0    | 0    | ... | 1     |
| Parameters     |      |      |     |       |
| Ki             | 500  |      |     |       |
| ts_fact        | 1    |      |     |       |
| Outputs        |      |      |     |       |
| Out            | 0    | 0    | ... | -1.82 |
| Exp. Out       | 0    | 0    | ... | -1.82 |
| Out (DSP)      | 0    | 0    | ... | -1.82 |
| Exp. Out (DSP) | 0    | 0    | ... | -1.82 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 1,3970e-06$ ( $\pm 3000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 66  |
| Max CPU cycles  | 628 |
| Avg CPU cycles  | 560 |

**Test case: Conversion test****OK**

Conversion test for Control block ul.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ul.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 3,0000e-08$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1589 |
| Max CPU cycles  | 1724 |
| Avg CPU cycles  | 1670 |



**Verification: ul Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Control block ul.

| Test results   |      |      |     |       |
|----------------|------|------|-----|-------|
| Time step      | 1    | 2    | ... | 401   |
| CPU cycles     | 57   | 57   | ... | 256   |
| Inputs         |      |      |     |       |
| In (DSP)       | 0    | 0    | ... | -0.2  |
| Init (DSP)     | 0.11 | 0.11 | ... | 0.11  |
| Enable (DSP)   | 0    | 0    | ... | 1     |
| In             | 0    | 0    | ... | -0.2  |
| Init           | 0.11 | 0.11 | ... | 0.11  |
| Enable         | 0    | 0    | ... | 1     |
| Parameters     |      |      |     |       |
| Ki             | 500  |      |     |       |
| ts_fact        | 1    |      |     |       |
| Outputs        |      |      |     |       |
| Out            | 0    | 0    | ... | -1.82 |
| Exp. Out       | 0    | 0    | ... | -1.82 |
| Out (DSP)      | 0    | 0    | ... | -1.82 |
| Exp. Out (DSP) | 0    | 0    | ... | -1.82 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 1,3970e-06$ ( $\pm 3000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 57  |
| Max CPU cycles  | 264 |
| Avg CPU cycles  | 254 |

**Test case: Conversion test****OK**

Conversion test for Control block ul.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ul.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 3,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 583 |
| Max CPU cycles  | 602 |
| Avg CPU cycles  | 597 |

**Verification: ul Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Control block ul.

| Test results   |      |      |     |       |
|----------------|------|------|-----|-------|
| Time step      | 1    | 2    | ... | 401   |
| CPU cycles     | 77   | 60   | ... | 95    |
| Inputs         |      |      |     |       |
| In (DSP)       | 0    | 0    | ... | -0.2  |
| Init (DSP)     | 0.11 | 0.11 | ... | 0.11  |
| Enable (DSP)   | 0    | 0    | ... | 1     |
| In             | 0    | 0    | ... | -0.2  |
| Init           | 0.11 | 0.11 | ... | 0.11  |
| Enable         | 0    | 0    | ... | 1     |
| Parameters     |      |      |     |       |
| Ki             | 500  |      |     |       |
| ts_fact        | 1    |      |     |       |
| Outputs        |      |      |     |       |
| Out            | 0    | 0    | ... | -1.82 |
| Exp. Out       | 0    | 0    | ... | -1.82 |
| Out (DSP)      | 0    | 0    | ... | -1.82 |
| Exp. Out (DSP) | 0    | 0    | ... | -1.82 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 1,3970e-06$ ( $\pm 3000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 60  |
| Max CPU cycles  | 122 |
| Avg CPU cycles  | 94  |

**Test case: Conversion test****OK**

Conversion test for Control block ul.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ul.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 3,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 595 |
| Max CPU cycles  | 715 |
| Avg CPU cycles  | 615 |

**Verification: ul Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Control block ul.

| Test results   |      |      |     |       |
|----------------|------|------|-----|-------|
| Time step      | 1    | 2    | ... | 401   |
| CPU cycles     | 62   | 62   | ... | 121   |
| Inputs         |      |      |     |       |
| In (DSP)       | 0    | 0    | ... | -0.2  |
| Init (DSP)     | 0.11 | 0.11 | ... | 0.11  |
| Enable (DSP)   | 0    | 0    | ... | 1     |
| In             | 0    | 0    | ... | -0.2  |
| Init           | 0.11 | 0.11 | ... | 0.11  |
| Enable         | 0    | 0    | ... | 1     |
| Parameters     |      |      |     |       |
| Ki             | 500  |      |     |       |
| ts_fact        | 1    |      |     |       |
| Outputs        |      |      |     |       |
| Out            | 0    | 0    | ... | -1.82 |
| Exp. Out       | 0    | 0    | ... | -1.82 |
| Out (DSP)      | 0    | 0    | ... | -1.82 |
| Exp. Out (DSP) | 0    | 0    | ... | -1.82 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 1,3970e-06$ ( $\pm 3000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 62  |
| Max CPU cycles  | 121 |
| Avg CPU cycles  | 120 |

**Test case: Conversion test****OK**

Conversion test for Control block ul.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ul.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 3,0000e-08$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1156 |
| Max CPU cycles  | 1172 |
| Avg CPU cycles  | 1158 |

**Verification: ul Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-23  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Control block ul.

| Test results   |      |      |     |       |
|----------------|------|------|-----|-------|
| Time step      | 1    | 2    | ... | 401   |
| CPU cycles     | 55   | 55   | ... | 655   |
| Inputs         |      |      |     |       |
| In (DSP)       | 0    | 0    | ... | -0.2  |
| Init (DSP)     | 0.11 | 0.11 | ... | 0.11  |
| Enable (DSP)   | 0    | 0    | ... | 1     |
| In             | 0    | 0    | ... | -0.2  |
| Init           | 0.11 | 0.11 | ... | 0.11  |
| Enable         | 0    | 0    | ... | 1     |
| Parameters     |      |      |     |       |
| Ki             | 500  |      |     |       |
| ts_fact        | 1    |      |     |       |
| Outputs        |      |      |     |       |
| Out            | 0    | 0    | ... | -1.82 |
| Exp. Out       | 0    | 0    | ... | -1.82 |
| Out (DSP)      | 0    | 0    | ... | -1.82 |
| Exp. Out (DSP) | 0    | 0    | ... | -1.82 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 1,3970e-06$ ( $\pm 3000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 55  |
| Max CPU cycles  | 803 |
| Avg CPU cycles  | 639 |

**Test case: Conversion test****OK**

Conversion test for Control block ul.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Control block ul.

| Test results                 |        |         |     |       |
|------------------------------|--------|---------|-----|-------|
| <b>Time step</b>             | 1      | 2       | ... | 37    |
| <i>Mask parameters</i>       |        |         |     |       |
| <b>Ki</b>                    | -11    | -10.389 | ... | 11    |
| <b>ts_fact</b>               | 1      | 2       | ... | 37    |
| <i>Controller parameters</i> |        |         |     |       |
| <b>b0</b>                    | -0.001 | -0.002  | ... | 0.041 |
| <b>Exp. b0</b>               | -0.001 | -0.002  | ... | 0.041 |


| Test settings |                  |
|---------------|------------------|
| Tolerance b0  | $\pm 3,0000e-08$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2155 |
| Max CPU cycles  | 2551 |
| Avg CPU cycles  | 2531 |




## 4 Filter

Library with various kinds of digital filter blocks.



## Block: ACDC

---



Calculation of AC and DC part of input signal.

| Inports |              |
|---------|--------------|
| In      | Input signal |
| phi     | Angle signal |

| Outports |                         |
|----------|-------------------------|
| AC       | AC part of input signal |
| DC       | DC part of input signal |

| Mask Parameters |    |                                                                 |
|-----------------|----|-----------------------------------------------------------------|
| Name            | ID | Description                                                     |
| ts_fact         | 1  | Multiplication factor of base sampling time (in integer format) |

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |
| phi               | int16 |

| Outports Data Type |       |
|--------------------|-------|
| AC                 | int16 |
| DC                 | int16 |

### Implementation: FiP32

---

### 32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |
| phi               | int32 |

| Outports Data Type |       |
|--------------------|-------|
| AC                 | int32 |
| DC                 | int32 |

### Implementation: Float32

---

#### 32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |
| phi               | float32 |

| Outports Data Type |         |
|--------------------|---------|
| AC                 | float32 |
| DC                 | float32 |

### Implementation: Float64

---

#### 64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |
| phi               | float64 |

| Outports Data Type |         |
|--------------------|---------|
| AC                 | float64 |
| DC                 | float64 |

**Verification: ACDC FiP16 CPU TMS320F28335**

Date of Test 2026-06-25  
Target controller TMS320F28335

**Test case: Inport test****OK**

Inport test for Filter block ACDC.

| Test results  |        |        |        |        |     |       |
|---------------|--------|--------|--------|--------|-----|-------|
| Time step     | 1      | 2      | 3      | 4      | ... | 111   |
| CPU cycles    | 134    | 134    | 134    | 134    | ... | 134   |
| Inputs        |        |        |        |        |     |       |
| In (DSP)      | 9830   | 7061   | 4372   | 1840   | ... | 12599 |
| phi (DSP)     | -32768 | -30997 | -29226 | -27454 | ... | 30997 |
| In            | 0.3    | 0.215  | 0.133  | 0.056  | ... | 0.385 |
| phi           | -1     | -0.946 | -0.892 | -0.838 | ... | 0.946 |
| Parameters    |        |        |        |        |     |       |
| ts_fact       | 1      |        |        |        |     |       |
| Outputs       |        |        |        |        |     |       |
| AC            | 0.3    | 0.215  | 0.133  | 0.056  | ... | 0.085 |
| DC            | 0      | 0      | 0      | 0      | ... | 0.3   |
| Exp. AC       | 0.3    | 0.215  | 0.133  | 0.056  | ... | 0.085 |
| Exp. DC       | 0      | 0      | 0      | 0      | ... | 0.3   |
| AC (DSP)      | 9830   | 7061   | 4372   | 1840   | ... | 2769  |
| DC (DSP)      | 0      | 0      | 0      | 0      | ... | 9830  |
| Exp. AC (DSP) | 9830   | 7061   | 4372   | 1840   | ... | 2769  |
| Exp. DC (DSP) | 0      | 0      | 0      | 0      | ... | 9830  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance AC  | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |
| Tolerance DC  | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 134 |
| Max CPU cycles  | 228 |
| Avg CPU cycles  | 135 |

**Verification: ACDC FiP16 CPU TM4C123GH6**

Date of Test 2026-06-25  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for Filter block ACDC.

| Test results  |        |        |        |        |     |       |
|---------------|--------|--------|--------|--------|-----|-------|
| Time step     | 1      | 2      | 3      | 4      | ... | 111   |
| CPU cycles    | 81     | 81     | 81     | 81     | ... | 81    |
| Inputs        |        |        |        |        |     |       |
| In (DSP)      | 9830   | 7061   | 4372   | 1840   | ... | 12599 |
| phi (DSP)     | -32768 | -30997 | -29226 | -27454 | ... | 30997 |
| In            | 0.3    | 0.215  | 0.133  | 0.056  | ... | 0.385 |
| phi           | -1     | -0.946 | -0.892 | -0.838 | ... | 0.946 |
| Parameters    |        |        |        |        |     |       |
| ts_fact       | 1      |        |        |        |     |       |
| Outputs       |        |        |        |        |     |       |
| AC            | 0.3    | 0.215  | 0.133  | 0.056  | ... | 0.085 |
| DC            | 0      | 0      | 0      | 0      | ... | 0.3   |
| Exp. AC       | 0.3    | 0.215  | 0.133  | 0.056  | ... | 0.085 |
| Exp. DC       | 0      | 0      | 0      | 0      | ... | 0.3   |
| AC (DSP)      | 9830   | 7061   | 4372   | 1840   | ... | 2769  |
| DC (DSP)      | 0      | 0      | 0      | 0      | ... | 9830  |
| Exp. AC (DSP) | 9830   | 7061   | 4372   | 1840   | ... | 2769  |
| Exp. DC (DSP) | 0      | 0      | 0      | 0      | ... | 9830  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance AC  | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |
| Tolerance DC  | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 81  |
| Max CPU cycles  | 101 |
| Avg CPU cycles  | 81  |

**Verification: ACDC FiP16 CPU STM32G474RE**

Date of Test 2026-06-25  
Target controller STM32G474RE

**Test case: Inport test****OK**

Inport test for Filter block ACDC.

| Test results  |        |        |        |        |     |       |
|---------------|--------|--------|--------|--------|-----|-------|
| Time step     | 1      | 2      | 3      | 4      | ... | 111   |
| CPU cycles    | 114    | 114    | 114    | 114    | ... | 114   |
| Inputs        |        |        |        |        |     |       |
| In (DSP)      | 9830   | 7061   | 4372   | 1840   | ... | 12599 |
| phi (DSP)     | -32768 | -30997 | -29226 | -27454 | ... | 30997 |
| In            | 0.3    | 0.215  | 0.133  | 0.056  | ... | 0.385 |
| phi           | -1     | -0.946 | -0.892 | -0.838 | ... | 0.946 |
| Parameters    |        |        |        |        |     |       |
| ts_fact       | 1      |        |        |        |     |       |
| Outputs       |        |        |        |        |     |       |
| AC            | 0.3    | 0.215  | 0.133  | 0.056  | ... | 0.085 |
| DC            | 0      | 0      | 0      | 0      | ... | 0.3   |
| Exp. AC       | 0.3    | 0.215  | 0.133  | 0.056  | ... | 0.085 |
| Exp. DC       | 0      | 0      | 0      | 0      | ... | 0.3   |
| AC (DSP)      | 9830   | 7061   | 4372   | 1840   | ... | 2769  |
| DC (DSP)      | 0      | 0      | 0      | 0      | ... | 9830  |
| Exp. AC (DSP) | 9830   | 7061   | 4372   | 1840   | ... | 2769  |
| Exp. DC (DSP) | 0      | 0      | 0      | 0      | ... | 9830  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance AC  | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |
| Tolerance DC  | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 114 |
| Max CPU cycles  | 149 |
| Avg CPU cycles  | 114 |

**Verification: ACDC FiP16 CPU STM32F072RB**

Date of Test 2026-06-25  
Target controller STM32F072RB

**Test case: Inport test****OK**

Inport test for Filter block ACDC.

| Test results  |        |        |        |        |     |       |
|---------------|--------|--------|--------|--------|-----|-------|
| Time step     | 1      | 2      | 3      | 4      | ... | 111   |
| CPU cycles    | 114    | 114    | 114    | 114    | ... | 114   |
| Inputs        |        |        |        |        |     |       |
| In (DSP)      | 9830   | 7061   | 4372   | 1840   | ... | 12599 |
| phi (DSP)     | -32768 | -30997 | -29226 | -27454 | ... | 30997 |
| In            | 0.3    | 0.215  | 0.133  | 0.056  | ... | 0.385 |
| phi           | -1     | -0.946 | -0.892 | -0.838 | ... | 0.946 |
| Parameters    |        |        |        |        |     |       |
| ts_fact       | 1      |        |        |        |     |       |
| Outputs       |        |        |        |        |     |       |
| AC            | 0.3    | 0.215  | 0.133  | 0.056  | ... | 0.085 |
| DC            | 0      | 0      | 0      | 0      | ... | 0.3   |
| Exp. AC       | 0.3    | 0.215  | 0.133  | 0.056  | ... | 0.085 |
| Exp. DC       | 0      | 0      | 0      | 0      | ... | 0.3   |
| AC (DSP)      | 9830   | 7061   | 4372   | 1840   | ... | 2769  |
| DC (DSP)      | 0      | 0      | 0      | 0      | ... | 9830  |
| Exp. AC (DSP) | 9830   | 7061   | 4372   | 1840   | ... | 2769  |
| Exp. DC (DSP) | 0      | 0      | 0      | 0      | ... | 9830  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance AC  | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |
| Tolerance DC  | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 114 |
| Max CPU cycles  | 268 |
| Avg CPU cycles  | 117 |

**Verification: ACDC FiP16 CPU PIC32MX170F256**

Date of Test 2026-06-25  
Target controller PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Filter block ACDC.

| Test results  |        |        |        |        |     |       |
|---------------|--------|--------|--------|--------|-----|-------|
| Time step     | 1      | 2      | 3      | 4      | ... | 111   |
| CPU cycles    | 70     | 70     | 70     | 70     | ... | 70    |
| Inputs        |        |        |        |        |     |       |
| In (DSP)      | 9830   | 7061   | 4372   | 1840   | ... | 12599 |
| phi (DSP)     | -32768 | -30997 | -29226 | -27454 | ... | 30997 |
| In            | 0.3    | 0.215  | 0.133  | 0.056  | ... | 0.385 |
| phi           | -1     | -0.946 | -0.892 | -0.838 | ... | 0.946 |
| Parameters    |        |        |        |        |     |       |
| ts_fact       | 1      |        |        |        |     |       |
| Outputs       |        |        |        |        |     |       |
| AC            | 0.3    | 0.215  | 0.133  | 0.056  | ... | 0.085 |
| DC            | 0      | 0      | 0      | 0      | ... | 0.3   |
| Exp. AC       | 0.3    | 0.215  | 0.133  | 0.056  | ... | 0.085 |
| Exp. DC       | 0      | 0      | 0      | 0      | ... | 0.3   |
| AC (DSP)      | 9830   | 7061   | 4372   | 1840   | ... | 2769  |
| DC (DSP)      | 0      | 0      | 0      | 0      | ... | 9830  |
| Exp. AC (DSP) | 9830   | 7061   | 4372   | 1840   | ... | 2769  |
| Exp. DC (DSP) | 0      | 0      | 0      | 0      | ... | 9830  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance AC  | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |
| Tolerance DC  | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 70  |
| Max CPU cycles  | 111 |
| Avg CPU cycles  | 70  |



**Verification: ACDC FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-25  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Filter block ACDC.

| Test results  |        |        |        |        |     |       |
|---------------|--------|--------|--------|--------|-----|-------|
| Time step     | 1      | 2      | 3      | 4      | ... | 111   |
| CPU cycles    | 106    | 97     | 97     | 97     | ... | 97    |
| Inputs        |        |        |        |        |     |       |
| In (DSP)      | 9830   | 7061   | 4372   | 1840   | ... | 12599 |
| phi (DSP)     | -32768 | -30997 | -29226 | -27454 | ... | 30997 |
| In            | 0.3    | 0.215  | 0.133  | 0.056  | ... | 0.385 |
| phi           | -1     | -0.946 | -0.892 | -0.838 | ... | 0.946 |
| Parameters    |        |        |        |        |     |       |
| ts_fact       | 1      |        |        |        |     |       |
| Outputs       |        |        |        |        |     |       |
| AC            | 0.3    | 0.215  | 0.133  | 0.056  | ... | 0.085 |
| DC            | 0      | 0      | 0      | 0      | ... | 0.3   |
| Exp. AC       | 0.3    | 0.215  | 0.133  | 0.056  | ... | 0.085 |
| Exp. DC       | 0      | 0      | 0      | 0      | ... | 0.3   |
| AC (DSP)      | 9830   | 7061   | 4372   | 1840   | ... | 2769  |
| DC (DSP)      | 0      | 0      | 0      | 0      | ... | 9830  |
| Exp. AC (DSP) | 9830   | 7061   | 4372   | 1840   | ... | 2769  |
| Exp. DC (DSP) | 0      | 0      | 0      | 0      | ... | 9830  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance AC  | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |
| Tolerance DC  | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 97  |
| Max CPU cycles  | 683 |
| Avg CPU cycles  | 107 |

**Verification: ACDC FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-25  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Filter block ACDC.

| Test results  |        |        |        |        |     |       |
|---------------|--------|--------|--------|--------|-----|-------|
| Time step     | 1      | 2      | 3      | 4      | ... | 111   |
| CPU cycles    | 115    | 102    | 102    | 102    | ... | 102   |
| Inputs        |        |        |        |        |     |       |
| In (DSP)      | 9830   | 7061   | 4372   | 1840   | ... | 12599 |
| phi (DSP)     | -32768 | -30997 | -29226 | -27454 | ... | 30997 |
| In            | 0.3    | 0.215  | 0.133  | 0.056  | ... | 0.385 |
| phi           | -1     | -0.946 | -0.892 | -0.838 | ... | 0.946 |
| Parameters    |        |        |        |        |     |       |
| ts_fact       | 1      |        |        |        |     |       |
| Outputs       |        |        |        |        |     |       |
| AC            | 0.3    | 0.215  | 0.133  | 0.056  | ... | 0.085 |
| DC            | 0      | 0      | 0      | 0      | ... | 0.3   |
| Exp. AC       | 0.3    | 0.215  | 0.133  | 0.056  | ... | 0.085 |
| Exp. DC       | 0      | 0      | 0      | 0      | ... | 0.3   |
| AC (DSP)      | 9830   | 7061   | 4372   | 1840   | ... | 2769  |
| DC (DSP)      | 0      | 0      | 0      | 0      | ... | 9830  |
| Exp. AC (DSP) | 9830   | 7061   | 4372   | 1840   | ... | 2769  |
| Exp. DC (DSP) | 0      | 0      | 0      | 0      | ... | 9830  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance AC  | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |
| Tolerance DC  | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 102 |
| Max CPU cycles  | 131 |
| Avg CPU cycles  | 102 |

**Verification: ACDC FiP16 CPU TMS320F28379D**

Date of Test 2026-06-25  
Target controller TMS320F28379D

**Test case: Inport test****OK**

Inport test for Filter block ACDC.

| Test results  |        |        |        |        |     |       |
|---------------|--------|--------|--------|--------|-----|-------|
| Time step     | 1      | 2      | 3      | 4      | ... | 111   |
| CPU cycles    | 140    | 137    | 137    | 137    | ... | 137   |
| Inputs        |        |        |        |        |     |       |
| In (DSP)      | 9830   | 7061   | 4372   | 1840   | ... | 12599 |
| phi (DSP)     | -32768 | -30997 | -29226 | -27454 | ... | 30997 |
| In            | 0.3    | 0.215  | 0.133  | 0.056  | ... | 0.385 |
| phi           | -1     | -0.946 | -0.892 | -0.838 | ... | 0.946 |
| Parameters    |        |        |        |        |     |       |
| ts_fact       | 1      |        |        |        |     |       |
| Outputs       |        |        |        |        |     |       |
| AC            | 0.3    | 0.215  | 0.133  | 0.056  | ... | 0.085 |
| DC            | 0      | 0      | 0      | 0      | ... | 0.3   |
| Exp. AC       | 0.3    | 0.215  | 0.133  | 0.056  | ... | 0.085 |
| Exp. DC       | 0      | 0      | 0      | 0      | ... | 0.3   |
| AC (DSP)      | 9830   | 7061   | 4372   | 1840   | ... | 2769  |
| DC (DSP)      | 0      | 0      | 0      | 0      | ... | 9830  |
| Exp. AC (DSP) | 9830   | 7061   | 4372   | 1840   | ... | 2769  |
| Exp. DC (DSP) | 0      | 0      | 0      | 0      | ... | 9830  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance AC  | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |
| Tolerance DC  | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 137 |
| Max CPU cycles  | 234 |
| Avg CPU cycles  | 138 |

**Verification: ACDC FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-25  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Filter block ACDC.

| Test results  |             |             |     |            |
|---------------|-------------|-------------|-----|------------|
| Time step     | 1           | 2           | ... | 111        |
| CPU cycles    | 290         | 289         | ... | 289        |
| Inputs        |             |             |     |            |
| In (DSP)      | 644245094   | 462781845   | ... | 825708343  |
| phi (DSP)     | -2147483648 | -2031403451 | ... | 2031403451 |
| In            | 0.3         | 0.215       | ... | 0.385      |
| phi           | -1          | -0.946      | ... | 0.946      |
| Parameters    |             |             |     |            |
| ts_fact       | 1           |             |     |            |
| Outputs       |             |             |     |            |
| AC            | 0.3         | 0.215       | ... | 0.085      |
| DC            | 0           | 0           | ... | 0.3        |
| Exp. AC       | 0.3         | 0.215       | ... | 0.085      |
| Exp. DC       | 0           | 0           | ... | 0.3        |
| AC (DSP)      | 644245094   | 462781845   | ... | 181463249  |
| DC (DSP)      | 0           | 0           | ... | 644245094  |
| Exp. AC (DSP) | 644245094   | 462781845   | ... | 181463249  |
| Exp. DC (DSP) | 0           | 0           | ... | 644245094  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance AC  | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |
| Tolerance DC  | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 289 |
| Max CPU cycles  | 635 |
| Avg CPU cycles  | 295 |

**Verification: ACDC FiP32 CPU TM4C123GH6**

Date of Test 2026-06-25  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for Filter block ACDC.

| Test results  |             |             |     |            |
|---------------|-------------|-------------|-----|------------|
| Time step     | 1           | 2           | ... | 111        |
| CPU cycles    | 119         | 119         | ... | 119        |
| Inputs        |             |             |     |            |
| In (DSP)      | 644245094   | 462781845   | ... | 825708343  |
| phi (DSP)     | -2147483648 | -2031403451 | ... | 2031403451 |
| In            | 0.3         | 0.215       | ... | 0.385      |
| phi           | -1          | -0.946      | ... | 0.946      |
| Parameters    |             |             |     |            |
| ts_fact       | 1           |             |     |            |
| Outputs       |             |             |     |            |
| AC            | 0.3         | 0.215       | ... | 0.085      |
| DC            | 0           | 0           | ... | 0.3        |
| Exp. AC       | 0.3         | 0.215       | ... | 0.085      |
| Exp. DC       | 0           | 0           | ... | 0.3        |
| AC (DSP)      | 644245094   | 462781845   | ... | 181463249  |
| DC (DSP)      | 0           | 0           | ... | 644245094  |
| Exp. AC (DSP) | 644245094   | 462781845   | ... | 181463249  |
| Exp. DC (DSP) | 0           | 0           | ... | 644245094  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance AC  | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |
| Tolerance DC  | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 119 |
| Max CPU cycles  | 641 |
| Avg CPU cycles  | 128 |

**Verification: ACDC FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-25  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Filter block ACDC.

| Test results  |             |             |     |            |
|---------------|-------------|-------------|-----|------------|
| Time step     | 1           | 2           | ... | 111        |
| CPU cycles    | 138         | 138         | ... | 138        |
| Inputs        |             |             |     |            |
| In (DSP)      | 644245094   | 462781845   | ... | 825708343  |
| phi (DSP)     | -2147483648 | -2031403451 | ... | 2031403451 |
| In            | 0.3         | 0.215       | ... | 0.385      |
| phi           | -1          | -0.946      | ... | 0.946      |
| Parameters    |             |             |     |            |
| ts_fact       | 1           |             |     |            |
| Outputs       |             |             |     |            |
| AC            | 0.3         | 0.215       | ... | 0.085      |
| DC            | 0           | 0           | ... | 0.3        |
| Exp. AC       | 0.3         | 0.215       | ... | 0.085      |
| Exp. DC       | 0           | 0           | ... | 0.3        |
| AC (DSP)      | 644245094   | 462781845   | ... | 181463249  |
| DC (DSP)      | 0           | 0           | ... | 644245094  |
| Exp. AC (DSP) | 644245094   | 462781845   | ... | 181463249  |
| Exp. DC (DSP) | 0           | 0           | ... | 644245094  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance AC  | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |
| Tolerance DC  | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 138 |
| Max CPU cycles  | 363 |
| Avg CPU cycles  | 142 |

**Verification: ACDC FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-25  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Filter block ACDC.

| Test results  |             |             |     |            |
|---------------|-------------|-------------|-----|------------|
| Time step     | 1           | 2           | ... | 111        |
| CPU cycles    | 169         | 169         | ... | 169        |
| Inputs        |             |             |     |            |
| In (DSP)      | 644245094   | 462781845   | ... | 825708343  |
| phi (DSP)     | -2147483648 | -2031403451 | ... | 2031403451 |
| In            | 0.3         | 0.215       | ... | 0.385      |
| phi           | -1          | -0.946      | ... | 0.946      |
| Parameters    |             |             |     |            |
| ts_fact       | 1           |             |     |            |
| Outputs       |             |             |     |            |
| AC            | 0.3         | 0.215       | ... | 0.085      |
| DC            | 0           | 0           | ... | 0.3        |
| Exp. AC       | 0.3         | 0.215       | ... | 0.085      |
| Exp. DC       | 0           | 0           | ... | 0.3        |
| AC (DSP)      | 644245094   | 462781845   | ... | 181463249  |
| DC (DSP)      | 0           | 0           | ... | 644245094  |
| Exp. AC (DSP) | 644245094   | 462781845   | ... | 181463249  |
| Exp. DC (DSP) | 0           | 0           | ... | 644245094  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance AC  | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |
| Tolerance DC  | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 169  |
| Max CPU cycles  | 1092 |
| Avg CPU cycles  | 188  |

**Verification: ACDC FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-25  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Filter block ACDC.

| Test results  |             |             |     |            |
|---------------|-------------|-------------|-----|------------|
| Time step     | 1           | 2           | ... | 111        |
| CPU cycles    | 118         | 114         | ... | 114        |
| Inputs        |             |             |     |            |
| In (DSP)      | 644245094   | 462781845   | ... | 825708343  |
| phi (DSP)     | -2147483648 | -2031403451 | ... | 2031403451 |
| In            | 0.3         | 0.215       | ... | 0.385      |
| phi           | -1          | -0.946      | ... | 0.946      |
| Parameters    |             |             |     |            |
| ts_fact       | 1           |             |     |            |
| Outputs       |             |             |     |            |
| AC            | 0.3         | 0.215       | ... | 0.085      |
| DC            | 0           | 0           | ... | 0.3        |
| Exp. AC       | 0.3         | 0.215       | ... | 0.085      |
| Exp. DC       | 0           | 0           | ... | 0.3        |
| AC (DSP)      | 644245094   | 462781845   | ... | 181463249  |
| DC (DSP)      | 0           | 0           | ... | 644245094  |
| Exp. AC (DSP) | 644245094   | 462781845   | ... | 181463249  |
| Exp. DC (DSP) | 0           | 0           | ... | 644245094  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance AC  | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |
| Tolerance DC  | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 113 |
| Max CPU cycles  | 258 |
| Avg CPU cycles  | 116 |



**Verification: ACDC FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-25  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Filter block ACDC.

| Test results  |             |             |     |            |
|---------------|-------------|-------------|-----|------------|
| Time step     | 1           | 2           | ... | 111        |
| CPU cycles    | 148         | 135         | ... | 135        |
| Inputs        |             |             |     |            |
| In (DSP)      | 644245094   | 462781845   | ... | 825708343  |
| phi (DSP)     | -2147483648 | -2031403451 | ... | 2031403451 |
| In            | 0.3         | 0.215       | ... | 0.385      |
| phi           | -1          | -0.946      | ... | 0.946      |
| Parameters    |             |             |     |            |
| ts_fact       | 1           |             |     |            |
| Outputs       |             |             |     |            |
| AC            | 0.3         | 0.215       | ... | 0.085      |
| DC            | 0           | 0           | ... | 0.3        |
| Exp. AC       | 0.3         | 0.215       | ... | 0.085      |
| Exp. DC       | 0           | 0           | ... | 0.3        |
| AC (DSP)      | 644245094   | 462781845   | ... | 181463249  |
| DC (DSP)      | 0           | 0           | ... | 644245094  |
| Exp. AC (DSP) | 644245094   | 462781845   | ... | 181463249  |
| Exp. DC (DSP) | 0           | 0           | ... | 644245094  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance AC  | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |
| Tolerance DC  | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 135  |
| Max CPU cycles  | 9778 |
| Avg CPU cycles  | 308  |

**Verification: ACDC FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-25  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Filter block ACDC.

| Test results  |             |             |     |            |
|---------------|-------------|-------------|-----|------------|
| Time step     | 1           | 2           | ... | 111        |
| CPU cycles    | 173         | 133         | ... | 133        |
| Inputs        |             |             |     |            |
| In (DSP)      | 644245094   | 462781845   | ... | 825708343  |
| phi (DSP)     | -2147483648 | -2031403451 | ... | 2031403451 |
| In            | 0.3         | 0.215       | ... | 0.385      |
| phi           | -1          | -0.946      | ... | 0.946      |
| Parameters    |             |             |     |            |
| ts_fact       | 1           |             |     |            |
| Outputs       |             |             |     |            |
| AC            | 0.3         | 0.215       | ... | 0.085      |
| DC            | 0           | 0           | ... | 0.3        |
| Exp. AC       | 0.3         | 0.215       | ... | 0.085      |
| Exp. DC       | 0           | 0           | ... | 0.3        |
| AC (DSP)      | 644245094   | 462781845   | ... | 181463249  |
| DC (DSP)      | 0           | 0           | ... | 644245094  |
| Exp. AC (DSP) | 644245094   | 462781845   | ... | 181463249  |
| Exp. DC (DSP) | 0           | 0           | ... | 644245094  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance AC  | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |
| Tolerance DC  | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 133 |
| Max CPU cycles  | 423 |
| Avg CPU cycles  | 137 |

**Verification: ACDC FiP32 CPU TMS320F28379D**

Date of Test 2026-06-25  
Target controller TMS320F28379D

**Test case: Inport test****OK**

Inport test for Filter block ACDC.

| Test results  |             |             |     |            |
|---------------|-------------|-------------|-----|------------|
| Time step     | 1           | 2           | ... | 111        |
| CPU cycles    | 277         | 274         | ... | 274        |
| Inputs        |             |             |     |            |
| In (DSP)      | 644245094   | 462781845   | ... | 825708343  |
| phi (DSP)     | -2147483648 | -2031403451 | ... | 2031403451 |
| In            | 0.3         | 0.215       | ... | 0.385      |
| phi           | -1          | -0.946      | ... | 0.946      |
| Parameters    |             |             |     |            |
| ts_fact       | 1           |             |     |            |
| Outputs       |             |             |     |            |
| AC            | 0.3         | 0.215       | ... | 0.085      |
| DC            | 0           | 0           | ... | 0.3        |
| Exp. AC       | 0.3         | 0.215       | ... | 0.085      |
| Exp. DC       | 0           | 0           | ... | 0.3        |
| AC (DSP)      | 644245094   | 462781845   | ... | 181463249  |
| DC (DSP)      | 0           | 0           | ... | 644245094  |
| Exp. AC (DSP) | 644245094   | 462781845   | ... | 181463249  |
| Exp. DC (DSP) | 0           | 0           | ... | 644245094  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance AC  | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |
| Tolerance DC  | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 274 |
| Max CPU cycles  | 581 |
| Avg CPU cycles  | 279 |

**Verification: ACDC Float32 CPU TMS320F28335**

Date of Test 2026-06-25  
Target controller TMS320F28335

**Test case: Inport test****OK**

Inport test for Filter block ACDC.

| Test results  |        |        |     |       |
|---------------|--------|--------|-----|-------|
| Time step     | 1      | 2      | ... | 111   |
| CPU cycles    | 112    | 112    | ... | 112   |
| Inputs        |        |        |     |       |
| In (DSP)      | 1.59   | 1.142  | ... | 2.038 |
| phi (DSP)     | -3.142 | -2.972 | ... | 2.972 |
| In            | 1.59   | 1.142  | ... | 2.038 |
| phi           | -3.142 | -2.972 | ... | 2.972 |
| Parameters    |        |        |     |       |
| ts_fact       | 1      |        |     |       |
| Outputs       |        |        |     |       |
| AC            | 1.59   | 1.142  | ... | 0.448 |
| DC            | 0      | 0      | ... | 1.59  |
| Exp. AC       | 1.59   | 1.142  | ... | 0.448 |
| Exp. DC       | 0      | 0      | ... | 1.59  |
| AC (DSP)      | 1.59   | 1.142  | ... | 0.448 |
| DC (DSP)      | 0      | 0      | ... | 1.59  |
| Exp. AC (DSP) | 1.59   | 1.142  | ... | 0.448 |
| Exp. DC (DSP) | 0      | 0      | ... | 1.59  |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance AC  | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |
| Tolerance DC  | $\pm 2,3283e-07$ ( $\pm 500$ LSB)  |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 112 |
| Max CPU cycles  | 377 |
| Avg CPU cycles  | 116 |

**Verification: ACDC Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-25  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Filter block ACDC.

| Test results  |        |        |     |       |
|---------------|--------|--------|-----|-------|
| Time step     | 1      | 2      | ... | 111   |
| CPU cycles    | 81     | 81     | ... | 81    |
| Inputs        |        |        |     |       |
| In (DSP)      | 1.59   | 1.142  | ... | 2.038 |
| phi (DSP)     | -3.142 | -2.972 | ... | 2.972 |
| In            | 1.59   | 1.142  | ... | 2.038 |
| phi           | -3.142 | -2.972 | ... | 2.972 |
| Parameters    |        |        |     |       |
| ts_fact       | 1      |        |     |       |
| Outputs       |        |        |     |       |
| AC            | 1.59   | 1.142  | ... | 0.448 |
| DC            | 0      | 0      | ... | 1.59  |
| Exp. AC       | 1.59   | 1.142  | ... | 0.448 |
| Exp. DC       | 0      | 0      | ... | 1.59  |
| AC (DSP)      | 1.59   | 1.142  | ... | 0.448 |
| DC (DSP)      | 0      | 0      | ... | 1.59  |
| Exp. AC (DSP) | 1.59   | 1.142  | ... | 0.448 |
| Exp. DC (DSP) | 0      | 0      | ... | 1.59  |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance AC  | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |
| Tolerance DC  | $\pm 2,3283e-07$ ( $\pm 500$ LSB)  |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 81  |
| Max CPU cycles  | 101 |
| Avg CPU cycles  | 81  |

**Verification: ACDC Float32 CPU STM32G474RE**

**Date of Test** 2026-06-25  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Filter block ACDC.

| Test results  |        |        |     |       |
|---------------|--------|--------|-----|-------|
| Time step     | 1      | 2      | ... | 111   |
| CPU cycles    | 113    | 113    | ... | 113   |
| Inputs        |        |        |     |       |
| In (DSP)      | 1.59   | 1.142  | ... | 2.038 |
| phi (DSP)     | -3.142 | -2.972 | ... | 2.972 |
| In            | 1.59   | 1.142  | ... | 2.038 |
| phi           | -3.142 | -2.972 | ... | 2.972 |
| Parameters    |        |        |     |       |
| ts_fact       | 1      |        |     |       |
| Outputs       |        |        |     |       |
| AC            | 1.59   | 1.142  | ... | 0.448 |
| DC            | 0      | 0      | ... | 1.59  |
| Exp. AC       | 1.59   | 1.142  | ... | 0.448 |
| Exp. DC       | 0      | 0      | ... | 1.59  |
| AC (DSP)      | 1.59   | 1.142  | ... | 0.448 |
| DC (DSP)      | 0      | 0      | ... | 1.59  |
| Exp. AC (DSP) | 1.59   | 1.142  | ... | 0.448 |
| Exp. DC (DSP) | 0      | 0      | ... | 1.59  |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance AC  | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |
| Tolerance DC  | $\pm 2,3283e-07$ ( $\pm 500$ LSB)  |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 113 |
| Max CPU cycles  | 143 |
| Avg CPU cycles  | 113 |

**Verification: ACDC Float32 CPU STM32F072RB**

Date of Test 2026-06-25  
Target controller STM32F072RB

**Test case: Inport test****OK**

Inport test for Filter block ACDC.

| Test results  |        |        |     |       |
|---------------|--------|--------|-----|-------|
| Time step     | 1      | 2      | ... | 111   |
| CPU cycles    | 525    | 612    | ... | 696   |
| Inputs        |        |        |     |       |
| In (DSP)      | 1.59   | 1.142  | ... | 2.038 |
| phi (DSP)     | -3.142 | -2.972 | ... | 2.972 |
| In            | 1.59   | 1.142  | ... | 2.038 |
| phi           | -3.142 | -2.972 | ... | 2.972 |
| Parameters    |        |        |     |       |
| ts_fact       | 1      |        |     |       |
| Outputs       |        |        |     |       |
| AC            | 1.59   | 1.142  | ... | 0.448 |
| DC            | 0      | 0      | ... | 1.59  |
| Exp. AC       | 1.59   | 1.142  | ... | 0.448 |
| Exp. DC       | 0      | 0      | ... | 1.59  |
| AC (DSP)      | 1.59   | 1.142  | ... | 0.448 |
| DC (DSP)      | 0      | 0      | ... | 1.59  |
| Exp. AC (DSP) | 1.59   | 1.142  | ... | 0.448 |
| Exp. DC (DSP) | 0      | 0      | ... | 1.59  |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance AC  | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |
| Tolerance DC  | $\pm 2,3283e-07$ ( $\pm 500$ LSB)  |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 525  |
| Max CPU cycles  | 1298 |
| Avg CPU cycles  | 684  |

**Verification: ACDC Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-25  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Filter block ACDC.

| Test results  |        |        |     |       |
|---------------|--------|--------|-----|-------|
| Time step     | 1      | 2      | ... | 111   |
| CPU cycles    | 242    | 301    | ... | 320   |
| Inputs        |        |        |     |       |
| In (DSP)      | 1.59   | 1.142  | ... | 2.038 |
| phi (DSP)     | -3.142 | -2.972 | ... | 2.972 |
| In            | 1.59   | 1.142  | ... | 2.038 |
| phi           | -3.142 | -2.972 | ... | 2.972 |
| Parameters    |        |        |     |       |
| ts_fact       | 1      |        |     |       |
| Outputs       |        |        |     |       |
| AC            | 1.59   | 1.142  | ... | 0.448 |
| DC            | 0      | 0      | ... | 1.59  |
| Exp. AC       | 1.59   | 1.142  | ... | 0.448 |
| Exp. DC       | 0      | 0      | ... | 1.59  |
| AC (DSP)      | 1.59   | 1.142  | ... | 0.448 |
| DC (DSP)      | 0      | 0      | ... | 1.59  |
| Exp. AC (DSP) | 1.59   | 1.142  | ... | 0.448 |
| Exp. DC (DSP) | 0      | 0      | ... | 1.59  |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance AC  | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |
| Tolerance DC  | $\pm 2,3283e-07$ ( $\pm 500$ LSB)  |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 242 |
| Max CPU cycles  | 514 |
| Avg CPU cycles  | 318 |



**Verification: ACDC Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-25  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Filter block ACDC.

| Test results  |        |        |     |       |
|---------------|--------|--------|-----|-------|
| Time step     | 1      | 2      | ... | 111   |
| CPU cycles    | 640    | 781    | ... | 911   |
| Inputs        |        |        |     |       |
| In (DSP)      | 1.59   | 1.142  | ... | 2.038 |
| phi (DSP)     | -3.142 | -2.972 | ... | 2.972 |
| In            | 1.59   | 1.142  | ... | 2.038 |
| phi           | -3.142 | -2.972 | ... | 2.972 |
| Parameters    |        |        |     |       |
| ts_fact       | 1      |        |     |       |
| Outputs       |        |        |     |       |
| AC            | 1.59   | 1.142  | ... | 0.448 |
| DC            | 0      | 0      | ... | 1.59  |
| Exp. AC       | 1.59   | 1.142  | ... | 0.448 |
| Exp. DC       | 0      | 0      | ... | 1.59  |
| AC (DSP)      | 1.59   | 1.142  | ... | 0.448 |
| DC (DSP)      | 0      | 0      | ... | 1.59  |
| Exp. AC (DSP) | 1.59   | 1.142  | ... | 0.448 |
| Exp. DC (DSP) | 0      | 0      | ... | 1.59  |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance AC  | $\pm 4,6566\text{e-}07$ ( $\pm 1000$ LSB) |
| Tolerance DC  | $\pm 2,3283\text{e-}07$ ( $\pm 500$ LSB)  |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 640  |
| Max CPU cycles  | 1870 |
| Avg CPU cycles  | 852  |

**Verification: ACDC Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-25  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Filter block ACDC.

| Test results  |        |        |     |       |
|---------------|--------|--------|-----|-------|
| Time step     | 1      | 2      | ... | 111   |
| CPU cycles    | 126    | 104    | ... | 104   |
| Inputs        |        |        |     |       |
| In (DSP)      | 1.59   | 1.142  | ... | 2.038 |
| phi (DSP)     | -3.142 | -2.972 | ... | 2.972 |
| In            | 1.59   | 1.142  | ... | 2.038 |
| phi           | -3.142 | -2.972 | ... | 2.972 |
| Parameters    |        |        |     |       |
| ts_fact       | 1      |        |     |       |
| Outputs       |        |        |     |       |
| AC            | 1.59   | 1.142  | ... | 0.448 |
| DC            | 0      | 0      | ... | 1.59  |
| Exp. AC       | 1.59   | 1.142  | ... | 0.448 |
| Exp. DC       | 0      | 0      | ... | 1.59  |
| AC (DSP)      | 1.59   | 1.142  | ... | 0.448 |
| DC (DSP)      | 0      | 0      | ... | 1.59  |
| Exp. AC (DSP) | 1.59   | 1.142  | ... | 0.448 |
| Exp. DC (DSP) | 0      | 0      | ... | 1.59  |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance AC  | $\pm 4,6566\text{e-}07$ ( $\pm 1000$ LSB) |
| Tolerance DC  | $\pm 2,3283\text{e-}07$ ( $\pm 500$ LSB)  |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 104 |
| Max CPU cycles  | 126 |
| Avg CPU cycles  | 104 |

**Verification: ACDC Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-25  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**


Inport test for Filter block ACDC.

| Test results  |        |        |     |       |
|---------------|--------|--------|-----|-------|
| Time step     | 1      | 2      | ... | 111   |
| CPU cycles    | 114    | 114    | ... | 114   |
| Inputs        |        |        |     |       |
| In (DSP)      | 1.59   | 1.142  | ... | 2.038 |
| phi (DSP)     | -3.142 | -2.972 | ... | 2.972 |
| In            | 1.59   | 1.142  | ... | 2.038 |
| phi           | -3.142 | -2.972 | ... | 2.972 |
| Parameters    |        |        |     |       |
| ts_fact       | 1      |        |     |       |
| Outputs       |        |        |     |       |
| AC            | 1.59   | 1.142  | ... | 0.448 |
| DC            | 0      | 0      | ... | 1.59  |
| Exp. AC       | 1.59   | 1.142  | ... | 0.448 |
| Exp. DC       | 0      | 0      | ... | 1.59  |
| AC (DSP)      | 1.59   | 1.142  | ... | 0.448 |
| DC (DSP)      | 0      | 0      | ... | 1.59  |
| Exp. AC (DSP) | 1.59   | 1.142  | ... | 0.448 |
| Exp. DC (DSP) | 0      | 0      | ... | 1.59  |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance AC  | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |
| Tolerance DC  | $\pm 2,3283e-07$ ( $\pm 500$ LSB)  |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 114 |
| Max CPU cycles  | 361 |
| Avg CPU cycles  | 118 |

## Block: AdaptiveNotch



Notch filter with variable notch frequency

| Inports |                               |
|---------|-------------------------------|
| In      | Input signal                  |
| n       | Speed input = notch frequency |

| Outputs |                        |
|---------|------------------------|
| Out     | Filtered output signal |

| Mask Parameters |    |                                                                                |
|-----------------|----|--------------------------------------------------------------------------------|
| Name            | ID | Description                                                                    |
| Q               | 1  | Q-Factor of the notch filter                                                   |
| n_thresh        | 2  | Speed threshold for activating the filter                                      |
| n_max           | 3  | Maximum revolutions per minute<br>(Not used in floating point implementations) |
| p               | 4  | Number of pole pairs                                                           |
| ts_fact         | 5  | Multiplication factor of base sampling time (in integer format)                |
| method          | 6  | Discretization method                                                          |

### Description:

Calculation:

$$\text{Out}(k) = \begin{cases} \text{In}(k) & n(k) \leq n_{\text{thresh}} \\ \text{In}(k) \cdot H(z) & n(k) > n_{\text{thresh}} \end{cases}$$

The transfer function  $H(z)$  of the filter is

$$H(z) = \frac{b_0 + b_1 z^{-1} + b_2 z^{-2}}{1 + a_1 z^{-1} + a_2 z^{-2}}$$

with coefficients derived from the transfer function

$$H(s) = \frac{s^2 + \omega_0^2}{s^2 + \frac{\omega_0}{Q} + \omega_0^2}$$

by a matched Z-transformation.

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP16

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |
| n                 | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |
| n                 | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |
| n                 | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |
| n                 | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

## Block: BandpassBiQ



Calculates the filter coefficients for a second order bandpass and performs filtering on input signal.

Second order transfer function used:

$$H(z) = (b0.z^2 + b1.z + b2) / (z^2 + a1.z + a2)$$

| Inports |             |
|---------|-------------|
| In      | Input In(k) |

| Outports |               |
|----------|---------------|
| Out      | Output Out(k) |

| Mask Parameters |    |                                                                        |
|-----------------|----|------------------------------------------------------------------------|
| Name            | ID | Description                                                            |
| characteristic  | 1  | The filter characteristic is one of Butterworth (=Bessel) or Chebyshev |
| fc1             | 2  | Lower cut-off frequency in Hz                                          |
| fc2             | 3  | Upper cut-off frequency in Hz                                          |
| rc              | 4  | Attenuation at cut-off frequencies                                     |
| ts_fact         | 5  | Multiplication factor of base sampling time (in integer format)        |

### Description:

#### Butterworth

- center frequency  $f_c$ 
  - center frequency  $f_c$  is given by  $f_c^2 = f_{c1}^2 * f_{c2}^2$
  - zero phaseshift @center frequency  $f_c$
- @lower cut-off frequency  $f_{c1}$ 
  - -3dB attenuation
  - 45 degree phaseshift
- @upper cut-off frequency  $f_{c2}$ 
  - -3dB attenuation
  - -45 degree phaseshift
- stopband
  - monotonic -20dB decline per decade
  - roll-off dynamics are constant and not adjustable

E.g.:

The cut-off frequencies are  $f_{c1} = 10\text{Hz}$  and  $f_{c2} = 100\text{Hz}$ .

The bodeplot is shown in the figure 1 below.




Figure 1: Bodeplot Butterworth bandpass.

### Chebyshev

*Note:* A second order Chebyshev I bandpass has the same bodeplot as a second order Chebyshev II bandpass. Hence, only the 'Chebyshev' option is given.

- center frequency  $f_c$ 
  - center frequency  $f_c$  is given by  $f_c^2 = f_{c1}^2 * f_{c2}^2$
  - zero phaseshift @center frequency  $f_c$
- @lower cut-off frequency  $f_{c1}$ 
  - $-rc\text{dB}$  attenuation
  - phaseshift proportional to  $rc$
- @upper cut-off frequency  $f_{c2}$ 
  - $-rc\text{dB}$  attenuation
  - -phaseshift proportional to  $rc$
- stopband
  - monotonic  $-20\text{dB}$  decline per decade
  - roll-off dynamics are adjustable using parameter  $rc$

E.g.:

The cut-off frequencies are  $f_{c1} = 10\text{Hz}$  and  $f_{c2} = 100\text{Hz}$ .

The parameter  $rc$  is set to  $10\text{dB}$ .

The bodeplot is shown in the figure 2 below.

### Bessel

*Note:* A second order Bessel bandpass behaves exactly like a second order Butterworth bandpass. Hence, no 'Bessel' option is given.

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |






Figure 2: Bodeplot Chebyshev bandpass.  $rc = 10\text{dB}$

### Implementation: FiP16

16 Bit Fixed Point Implementation

| Inports Data Type  |       |
|--------------------|-------|
| In                 | int16 |
| Outports Data Type |       |
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type  |       |
|--------------------|-------|
| In                 | int32 |
| Outports Data Type |       |
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type  |         |
|--------------------|---------|
| In                 | float32 |
| Outports Data Type |         |
| Out                | float32 |

### Implementation: Float64

## 64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

## Block: BandstopBiQ



Calculates the filter coefficients for a second order bandstop and performs filtering on input signal.

Second order transfer function used:

$$H(z) = (b0.z^2 + b1.z + b2) / (z^2 + a1.z + a2)$$

### Inports

|    |             |
|----|-------------|
| In | Input In(k) |
|----|-------------|

### Outports

|     |               |
|-----|---------------|
| Out | Output Out(k) |
|-----|---------------|

### Mask Parameters

| Name           | ID | Description                                                            |
|----------------|----|------------------------------------------------------------------------|
| characteristic | 1  | The filter characteristic is one of Butterworth (=Bessel) or Chebyshev |
| fc1            | 2  | Lower cut-off frequency in Hz                                          |
| fc2            | 3  | Upper cut-off frequency in Hz                                          |
| rc             | 4  | Attenuation at cut-off frequencies                                     |
| ts_fact        | 5  | Multiplication factor of base sampling time (in integer format)        |

### Description:

#### Butterworth

- center frequency  $f_c$ 
  - center frequency  $f_c$  is given by  $f_c^2 = f_{c1}^2 * f_{c2}^2$
  - phase discontinuity @center frequency  $f_c$
- @lower cut-off frequency  $f_{c1}$ 
  - -3dB attenuation
  - -45 degree phaseshift
- @upper cut-off frequency  $f_{c2}$ 
  - -3dB attenuation
  - 45 degree phaseshift
- passband
  - roll-off dynamics are constant and not adjustable




Figure 3: Bodeplot Butterworth bandstop.

E.g.:

The cut-off frequencies are  $f_{c1} = 100\text{Hz}$  and  $f_{c2} = 300\text{Hz}$ .

The bodeplot is shown in the figure 3 below.

### Chebyshev

*Note:* A second order Chebyshev I bandstop has the same bodeplot as a second order Chebyshev II bandstop. Hence, only the 'Chebyshev' option is given.

- center frequency  $f_c$ 
  - center frequency  $f_c$  is given by  $f_c^2 = f_{c1}^2 * f_{c2}^2$
  - phase discontinuity @center frequency  $f_c$
- @lower cut-off frequency  $f_{c1}$ 
  - $-rc\text{dB}$  attenuation
  - -phaseshift proportional to  $rc$
- @upper cut-off frequency  $f_{c2}$ 
  - $-rc\text{dB}$  attenuation
  - phaseshift proportional to  $rc$
- passband
  - roll-off dynamics are adjustable using parameter  $rc$

E.g.:

The cut-off frequencies are  $f_{c1} = 100\text{Hz}$  and  $f_{c2} = 300\text{Hz}$ .

The parameter  $rc$  is set to 10dB.

The bodeplot is shown in the figure 4 below.

### Bessel

*Note:* A second order Bessel bandstop behaves exactly like a second order Butterworth bandstop. Hence, no 'Bessel' option is given.

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |




Figure 4: Bodeplot Chebyshev bandstop.  $rc = 10\text{dB}$

### Implementation: FiP16

16 Bit Fixed Point Implementation

| Inports Data Type  |       |
|--------------------|-------|
| In                 | int16 |
| Outports Data Type |       |
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type  |       |
|--------------------|-------|
| In                 | int32 |
| Outports Data Type |       |
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type  |         |
|--------------------|---------|
| In                 | float32 |
| Outports Data Type |         |
| Out                | float32 |


### Implementation: Float64

## 64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

## Block: Bilin



First order transfer function:

$$H(z) = (b_0.z + b_1) / (a_0.z + a_1)$$

| Inports |             |
|---------|-------------|
| In      | Input In(k) |

| Outputs |               |
|---------|---------------|
| Out     | Output Out(k) |

| Mask Parameters |    |                                                                 |
|-----------------|----|-----------------------------------------------------------------|
| Name            | ID | Description                                                     |
| b0              | 1  | Filter coefficient b0                                           |
| b1              | 2  | Filter coefficient b1                                           |
| a0              | 3  | Filter coefficient a0                                           |
| a1              | 4  | Filter coefficient a1                                           |
| ts_fact         | 5  | Multiplication factor of base sampling time (in integer format) |

### Description:

Alternative representation of the same transfer function:

$$H(z) = \frac{b_0 + b_1 z^{-1}}{a_0 + a_1 z^{-1}}$$

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP16

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |

| Outputs Data Type |       |
|-------------------|-------|
| Out               | int16 |

### Implementation: FiP32

---

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

---

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

---

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |



**Verification: Bilin FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-25  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Filter block Bilin.

| Test results   |        |        |       |       |     |       |
|----------------|--------|--------|-------|-------|-----|-------|
| Time step      | 1      | 2      | 3     | 4     | ... | 73    |
| CPU cycles     | 87     | 87     | 87    | 87    | ... | 87    |
| Inputs         |        |        |       |       |     |       |
| In (DSP)       | -1842  | -679   | 5729  | 7954  | ... | 15256 |
| In             | -0.056 | -0.021 | 0.175 | 0.243 | ... | 0.466 |
| Parameters     |        |        |       |       |     |       |
| b0             | 0.2    |        |       |       |     |       |
| b1             | 0.1    |        |       |       |     |       |
| a0             | 1.1    |        |       |       |     |       |
| a1             | -0.7   |        |       |       |     |       |
| ts_fact        | 1      |        |       |       |     |       |
| Outputs        |        |        |       |       |     |       |
| Out            | -0.01  | -0.015 | 0.02  | 0.073 | ... | 0.338 |
| Exp. Out       | -0.01  | -0.015 | 0.02  | 0.073 | ... | 0.338 |
| Out (DSP)      | -335   | -505   | 658   | 2385  | ... | 11070 |
| Exp. Out (DSP) | -335   | -504   | 659   | 2387  | ... | 11073 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}04$ ( $\pm 5$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 87 |
| Max CPU cycles  | 87 |
| Avg CPU cycles  | 87 |

**Test case: Conversion test****OK**

Conversion test for Filter block Bilin.

| Test results          |     |       |       |       |     |       |
|-----------------------|-----|-------|-------|-------|-----|-------|
| Time step             | 1   | 2     | 3     | 4     | ... | 8     |
| Mask parameters       |     |       |       |       |     |       |
| <b>b0</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>             | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>        | 1   | 1     | 1     | 1     | ... | 1     |
| Controller parameters |     |       |       |       |     |       |
| <b>a1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfrb0</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfrb0</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Bilin.

| Test results          |     |       |       |       |     |       |
|-----------------------|-----|-------|-------|-------|-----|-------|
| Time step             | 1   | 2     | 3     | 4     | ... | 8     |
| Mask parameters       |     |       |       |       |     |       |
| <b>b0</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>             | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>        | 1   | 1     | 1     | 1     | ... | 1     |
| Controller parameters |     |       |       |       |     |       |
| <b>a1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfrb0</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfrb0</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 4658  |
| Max CPU cycles  | 18605 |
| Avg CPU cycles  | 10505 |

**Verification: Bilin FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-25  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Filter block Bilin.

| Test results   |        |        |       |       |     |       |
|----------------|--------|--------|-------|-------|-----|-------|
| Time step      | 1      | 2      | 3     | 4     | ... | 73    |
| CPU cycles     | 71     | 71     | 71    | 71    | ... | 71    |
| Inputs         |        |        |       |       |     |       |
| In (DSP)       | -1842  | -679   | 5729  | 7954  | ... | 15256 |
| In             | -0.056 | -0.021 | 0.175 | 0.243 | ... | 0.466 |
| Parameters     |        |        |       |       |     |       |
| b0             | 0.2    |        |       |       |     |       |
| b1             | 0.1    |        |       |       |     |       |
| a0             | 1.1    |        |       |       |     |       |
| a1             | -0.7   |        |       |       |     |       |
| ts_fact        | 1      |        |       |       |     |       |
| Outputs        |        |        |       |       |     |       |
| Out            | -0.01  | -0.015 | 0.02  | 0.073 | ... | 0.338 |
| Exp. Out       | -0.01  | -0.015 | 0.02  | 0.073 | ... | 0.338 |
| Out (DSP)      | -335   | -505   | 658   | 2385  | ... | 11070 |
| Exp. Out (DSP) | -335   | -504   | 659   | 2387  | ... | 11073 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}04$ ( $\pm 5$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 71 |
| Max CPU cycles  | 71 |
| Avg CPU cycles  | 71 |

**Test case: Conversion test****OK**

Conversion test for Filter block Bilin.

| Test results          |     |       |       |       |     |       |
|-----------------------|-----|-------|-------|-------|-----|-------|
| Time step             | 1   | 2     | 3     | 4     | ... | 8     |
| Mask parameters       |     |       |       |       |     |       |
| <b>b0</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>             | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>        | 1   | 1     | 1     | 1     | ... | 1     |
| Controller parameters |     |       |       |       |     |       |
| <b>a1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfrb0</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfrb0</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Bilin.

| Test results          |     |       |       |       |     |       |
|-----------------------|-----|-------|-------|-------|-----|-------|
| Time step             | 1   | 2     | 3     | 4     | ... | 8     |
| Mask parameters       |     |       |       |       |     |       |
| <b>b0</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>             | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>        | 1   | 1     | 1     | 1     | ... | 1     |
| Controller parameters |     |       |       |       |     |       |
| <b>a1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfrb0</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfrb0</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2383 |
| Max CPU cycles  | 8683 |
| Avg CPU cycles  | 5255 |

**Verification: Bilin FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-25  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Filter block Bilin.

| Test results   |        |        |       |       |     |       |
|----------------|--------|--------|-------|-------|-----|-------|
| Time step      | 1      | 2      | 3     | 4     | ... | 73    |
| CPU cycles     | 112    | 112    | 112   | 112   | ... | 112   |
| Inputs         |        |        |       |       |     |       |
| In (DSP)       | -1842  | -679   | 5729  | 7954  | ... | 15256 |
| In             | -0.056 | -0.021 | 0.175 | 0.243 | ... | 0.466 |
| Parameters     |        |        |       |       |     |       |
| b0             | 0.2    |        |       |       |     |       |
| b1             | 0.1    |        |       |       |     |       |
| a0             | 1.1    |        |       |       |     |       |
| a1             | -0.7   |        |       |       |     |       |
| ts_fact        | 1      |        |       |       |     |       |
| Outputs        |        |        |       |       |     |       |
| Out            | -0.01  | -0.015 | 0.02  | 0.073 | ... | 0.338 |
| Exp. Out       | -0.01  | -0.015 | 0.02  | 0.073 | ... | 0.338 |
| Out (DSP)      | -335   | -505   | 658   | 2385  | ... | 11070 |
| Exp. Out (DSP) | -335   | -504   | 659   | 2387  | ... | 11073 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}04$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 112 |
| Max CPU cycles  | 112 |
| Avg CPU cycles  | 112 |

**Test case: Conversion test****OK**

Conversion test for Filter block Bilin.

| Test results          |     |       |       |       |     |       |
|-----------------------|-----|-------|-------|-------|-----|-------|
| Time step             | 1   | 2     | 3     | 4     | ... | 8     |
| Mask parameters       |     |       |       |       |     |       |
| <b>b0</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>             | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>        | 1   | 1     | 1     | 1     | ... | 1     |
| Controller parameters |     |       |       |       |     |       |
| <b>a1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfrb0</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfrb0</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Bilin.



| Test results          |     |       |       |       |     |       |
|-----------------------|-----|-------|-------|-------|-----|-------|
| Time step             | 1   | 2     | 3     | 4     | ... | 8     |
| Mask parameters       |     |       |       |       |     |       |
| <b>b0</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>             | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>        | 1   | 1     | 1     | 1     | ... | 1     |
| Controller parameters |     |       |       |       |     |       |
| <b>a1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfrb0</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfrb0</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2150 |
| Max CPU cycles  | 4735 |
| Avg CPU cycles  | 3228 |

**Verification: Bilin FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-25  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Filter block Bilin.

| Test results   |        |        |       |       |     |       |
|----------------|--------|--------|-------|-------|-----|-------|
| Time step      | 1      | 2      | 3     | 4     | ... | 73    |
| CPU cycles     | 99     | 99     | 99    | 99    | ... | 99    |
| Inputs         |        |        |       |       |     |       |
| In (DSP)       | -1842  | -679   | 5729  | 7954  | ... | 15256 |
| In             | -0.056 | -0.021 | 0.175 | 0.243 | ... | 0.466 |
| Parameters     |        |        |       |       |     |       |
| b0             | 0.2    |        |       |       |     |       |
| b1             | 0.1    |        |       |       |     |       |
| a0             | 1.1    |        |       |       |     |       |
| a1             | -0.7   |        |       |       |     |       |
| ts_fact        | 1      |        |       |       |     |       |
| Outputs        |        |        |       |       |     |       |
| Out            | -0.01  | -0.015 | 0.02  | 0.073 | ... | 0.338 |
| Exp. Out       | -0.01  | -0.015 | 0.02  | 0.073 | ... | 0.338 |
| Out (DSP)      | -335   | -505   | 658   | 2385  | ... | 11070 |
| Exp. Out (DSP) | -335   | -504   | 659   | 2387  | ... | 11073 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}04$ ( $\pm 5$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 99 |
| Max CPU cycles  | 99 |
| Avg CPU cycles  | 99 |

**Test case: Conversion test****OK**

Conversion test for Filter block Bilin.

| Test results          |     |       |       |       |     |       |
|-----------------------|-----|-------|-------|-------|-----|-------|
| Time step             | 1   | 2     | 3     | 4     | ... | 8     |
| Mask parameters       |     |       |       |       |     |       |
| <b>b0</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>             | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>        | 1   | 1     | 1     | 1     | ... | 1     |
| Controller parameters |     |       |       |       |     |       |
| <b>a1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfrb0</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfrb0</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Bilin.

| Test results          |     |       |       |       |     |       |
|-----------------------|-----|-------|-------|-------|-----|-------|
| Time step             | 1   | 2     | 3     | 4     | ... | 8     |
| Mask parameters       |     |       |       |       |     |       |
| <b>b0</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>             | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>        | 1   | 1     | 1     | 1     | ... | 1     |
| Controller parameters |     |       |       |       |     |       |
| <b>a1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfrb0</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfrb0</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 5338  |
| Max CPU cycles  | 15205 |
| Avg CPU cycles  | 10684 |

**Verification: Bilin FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-25  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Filter block Bilin.

| Test results   |        |        |       |       |     |       |
|----------------|--------|--------|-------|-------|-----|-------|
| Time step      | 1      | 2      | 3     | 4     | ... | 73    |
| CPU cycles     | 60     | 60     | 60    | 60    | ... | 60    |
| Inputs         |        |        |       |       |     |       |
| In (DSP)       | -1842  | -679   | 5729  | 7954  | ... | 15256 |
| In             | -0.056 | -0.021 | 0.175 | 0.243 | ... | 0.466 |
| Parameters     |        |        |       |       |     |       |
| b0             | 0.2    |        |       |       |     |       |
| b1             | 0.1    |        |       |       |     |       |
| a0             | 1.1    |        |       |       |     |       |
| a1             | -0.7   |        |       |       |     |       |
| ts_fact        | 1      |        |       |       |     |       |
| Outputs        |        |        |       |       |     |       |
| Out            | -0.01  | -0.015 | 0.02  | 0.073 | ... | 0.338 |
| Exp. Out       | -0.01  | -0.015 | 0.02  | 0.073 | ... | 0.338 |
| Out (DSP)      | -335   | -505   | 658   | 2385  | ... | 11070 |
| Exp. Out (DSP) | -335   | -504   | 659   | 2387  | ... | 11073 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}04$ ( $\pm 5$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 60 |
| Max CPU cycles  | 60 |
| Avg CPU cycles  | 60 |

**Test case: Conversion test****OK**

Conversion test for Filter block Bilin.

| Test results          |     |       |       |       |     |       |
|-----------------------|-----|-------|-------|-------|-----|-------|
| Time step             | 1   | 2     | 3     | 4     | ... | 8     |
| Mask parameters       |     |       |       |       |     |       |
| <b>b0</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>             | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>        | 1   | 1     | 1     | 1     | ... | 1     |
| Controller parameters |     |       |       |       |     |       |
| <b>a1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfrb0</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfrb0</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Bilin.

| Test results          |     |       |       |       |     |       |
|-----------------------|-----|-------|-------|-------|-----|-------|
| Time step             | 1   | 2     | 3     | 4     | ... | 8     |
| Mask parameters       |     |       |       |       |     |       |
| <b>b0</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>             | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>        | 1   | 1     | 1     | 1     | ... | 1     |
| Controller parameters |     |       |       |       |     |       |
| <b>a1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfrb0</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfrb0</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2432 |
| Max CPU cycles  | 6430 |
| Avg CPU cycles  | 4480 |

**Verification: Bilin FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-25  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Filter block Bilin.

| Test results   |        |        |       |       |     |       |
|----------------|--------|--------|-------|-------|-----|-------|
| Time step      | 1      | 2      | 3     | 4     | ... | 73    |
| CPU cycles     | 110    | 110    | 110   | 110   | ... | 110   |
| Inputs         |        |        |       |       |     |       |
| In (DSP)       | -1842  | -679   | 5729  | 7954  | ... | 15256 |
| In             | -0.056 | -0.021 | 0.175 | 0.243 | ... | 0.466 |
| Parameters     |        |        |       |       |     |       |
| b0             | 0.2    |        |       |       |     |       |
| b1             | 0.1    |        |       |       |     |       |
| a0             | 1.1    |        |       |       |     |       |
| a1             | -0.7   |        |       |       |     |       |
| ts_fact        | 1      |        |       |       |     |       |
| Outputs        |        |        |       |       |     |       |
| Out            | -0.01  | -0.015 | 0.02  | 0.073 | ... | 0.338 |
| Exp. Out       | -0.01  | -0.015 | 0.02  | 0.073 | ... | 0.338 |
| Out (DSP)      | -335   | -505   | 658   | 2385  | ... | 11070 |
| Exp. Out (DSP) | -335   | -504   | 659   | 2387  | ... | 11073 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,5259e-04$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 110 |
| Max CPU cycles  | 110 |
| Avg CPU cycles  | 110 |

**Test case: Conversion test****OK**

Conversion test for Filter block Bilin.



| Test results          |     |       |       |       |     |       |
|-----------------------|-----|-------|-------|-------|-----|-------|
| Time step             | 1   | 2     | 3     | 4     | ... | 8     |
| Mask parameters       |     |       |       |       |     |       |
| <b>b0</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>             | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>        | 1   | 1     | 1     | 1     | ... | 1     |
| Controller parameters |     |       |       |       |     |       |
| <b>a1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfrb0</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfrb0</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Bilin.

| Test results          |     |       |       |       |     |       |
|-----------------------|-----|-------|-------|-------|-----|-------|
| Time step             | 1   | 2     | 3     | 4     | ... | 8     |
| Mask parameters       |     |       |       |       |     |       |
| <b>b0</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>             | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>        | 1   | 1     | 1     | 1     | ... | 1     |
| Controller parameters |     |       |       |       |     |       |
| <b>a1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfrb0</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfrb0</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 8952  |
| Max CPU cycles  | 36527 |
| Avg CPU cycles  | 23341 |

**Verification: Bilin FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-25  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Filter block Bilin.

| Test results   |        |        |       |       |     |       |
|----------------|--------|--------|-------|-------|-----|-------|
| Time step      | 1      | 2      | 3     | 4     | ... | 73    |
| CPU cycles     | 119    | 102    | 102   | 102   | ... | 102   |
| Inputs         |        |        |       |       |     |       |
| In (DSP)       | -1842  | -679   | 5729  | 7954  | ... | 15256 |
| In             | -0.056 | -0.021 | 0.175 | 0.243 | ... | 0.466 |
| Parameters     |        |        |       |       |     |       |
| b0             | 0.2    |        |       |       |     |       |
| b1             | 0.1    |        |       |       |     |       |
| a0             | 1.1    |        |       |       |     |       |
| a1             | -0.7   |        |       |       |     |       |
| ts_fact        | 1      |        |       |       |     |       |
| Outputs        |        |        |       |       |     |       |
| Out            | -0.01  | -0.015 | 0.02  | 0.073 | ... | 0.338 |
| Exp. Out       | -0.01  | -0.015 | 0.02  | 0.073 | ... | 0.338 |
| Out (DSP)      | -335   | -505   | 658   | 2385  | ... | 11070 |
| Exp. Out (DSP) | -335   | -504   | 659   | 2387  | ... | 11073 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,5259e-04$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 102 |
| Max CPU cycles  | 119 |
| Avg CPU cycles  | 102 |

**Test case: Conversion test****OK**

Conversion test for Filter block Bilin.

| Test results          |     |       |       |       |     |       |
|-----------------------|-----|-------|-------|-------|-----|-------|
| Time step             | 1   | 2     | 3     | 4     | ... | 8     |
| Mask parameters       |     |       |       |       |     |       |
| <b>b0</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>             | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>        | 1   | 1     | 1     | 1     | ... | 1     |
| Controller parameters |     |       |       |       |     |       |
| <b>a1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfrb0</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfrb0</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Bilin.

| Test results          |     |       |       |       |     |       |
|-----------------------|-----|-------|-------|-------|-----|-------|
| Time step             | 1   | 2     | 3     | 4     | ... | 8     |
| Mask parameters       |     |       |       |       |     |       |
| <b>b0</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>             | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>        | 1   | 1     | 1     | 1     | ... | 1     |
| Controller parameters |     |       |       |       |     |       |
| <b>a1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfrb0</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfrb0</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1804 |
| Max CPU cycles  | 4279 |
| Avg CPU cycles  | 2888 |

**Verification: Bilin FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-25  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Filter block Bilin.

| Test results   |        |        |       |       |     |       |
|----------------|--------|--------|-------|-------|-----|-------|
| Time step      | 1      | 2      | 3     | 4     | ... | 73    |
| CPU cycles     | 86     | 86     | 86    | 86    | ... | 86    |
| Inputs         |        |        |       |       |     |       |
| In (DSP)       | -1842  | -679   | 5729  | 7954  | ... | 15256 |
| In             | -0.056 | -0.021 | 0.175 | 0.243 | ... | 0.466 |
| Parameters     |        |        |       |       |     |       |
| b0             | 0.2    |        |       |       |     |       |
| b1             | 0.1    |        |       |       |     |       |
| a0             | 1.1    |        |       |       |     |       |
| a1             | -0.7   |        |       |       |     |       |
| ts_fact        | 1      |        |       |       |     |       |
| Outputs        |        |        |       |       |     |       |
| Out            | -0.01  | -0.015 | 0.02  | 0.073 | ... | 0.338 |
| Exp. Out       | -0.01  | -0.015 | 0.02  | 0.073 | ... | 0.338 |
| Out (DSP)      | -335   | -505   | 658   | 2385  | ... | 11070 |
| Exp. Out (DSP) | -335   | -504   | 659   | 2387  | ... | 11073 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,5259e-04$ ( $\pm 5$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 86 |
| Max CPU cycles  | 86 |
| Avg CPU cycles  | 86 |

**Test case: Conversion test****OK**

Conversion test for Filter block Bilin.

| Test results          |     |       |       |       |     |       |
|-----------------------|-----|-------|-------|-------|-----|-------|
| Time step             | 1   | 2     | 3     | 4     | ... | 8     |
| Mask parameters       |     |       |       |       |     |       |
| <b>b0</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>             | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>        | 1   | 1     | 1     | 1     | ... | 1     |
| Controller parameters |     |       |       |       |     |       |
| <b>a1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfrb0</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfrb0</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Bilin.

| Test results          |     |       |       |       |     |       |
|-----------------------|-----|-------|-------|-------|-----|-------|
| Time step             | 1   | 2     | 3     | 4     | ... | 8     |
| Mask parameters       |     |       |       |       |     |       |
| <b>b0</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>             | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>             | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>        | 1   | 1     | 1     | 1     | ... | 1     |
| Controller parameters |     |       |       |       |     |       |
| <b>a1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfrb0</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>          | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>             | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfrb0</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>     | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>        | 0   | 16384 | 16384 | 16384 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 3363  |
| Max CPU cycles  | 13695 |
| Avg CPU cycles  | 7751  |



**Verification: Bilin FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-25  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Filter block Bilin.

| Test results   |            |           |     |           |
|----------------|------------|-----------|-----|-----------|
| Time step      | 1          | 2         | ... | 73        |
| CPU cycles     | 216        | 216       | ... | 216       |
| Inputs         |            |           |     |           |
| In (DSP)       | -120706110 | -44469415 | ... | 999834674 |
| In             | -0.056     | -0.021    | ... | 0.466     |
| Parameters     |            |           |     |           |
| b0             | 0.2        |           |     |           |
| b1             | 0.1        |           |     |           |
| a0             | 1.1        |           |     |           |
| a1             | -0.7       |           |     |           |
| ts_fact        | 1          |           |     |           |
| Outputs        |            |           |     |           |
| Out            | -0.01      | -0.015    | ... | 0.338     |
| Exp. Out       | -0.01      | -0.015    | ... | 0.338     |
| Out (DSP)      | -21946566  | -33024628 | ... | 725708721 |
| Exp. Out (DSP) | -21946566  | -33024627 | ... | 725708723 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 216 |
| Max CPU cycles  | 216 |
| Avg CPU cycles  | 216 |

**Test case: Conversion test****OK**

Conversion test for Filter block Bilin.

| Test results                 |     |            |     |            |
|------------------------------|-----|------------|-----|------------|
| <b>Time step</b>             | 1   | 2          | ... | 8          |
| <i>Mask parameters</i>       |     |            |     |            |
| <b>b0</b>                    | 0   | 0.1        | ... | 10         |
| <b>b1</b>                    | 0   | 0.1        | ... | 10         |
| <b>a0</b>                    | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>                    | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>               | 1   | 1          | ... | 1          |
| <i>Controller parameters</i> |     |            |     |            |
| <b>a1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>sfrb0</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb1</b>                 | 31  | 30         | ... | 27         |
| <b>sfra1</b>                 | 31  | 30         | ... | 27         |
| <b>b0</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfrb0</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>               | 0   | 1073741824 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Bilin.

| Test results                 |     |            |     |            |
|------------------------------|-----|------------|-----|------------|
| <b>Time step</b>             | 1   | 2          | ... | 8          |
| <i>Mask parameters</i>       |     |            |     |            |
| <b>b0</b>                    | 0   | 0.1        | ... | 10         |
| <b>b1</b>                    | 0   | 0.1        | ... | 10         |
| <b>a0</b>                    | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>                    | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>               | 1   | 1          | ... | 1          |
| <i>Controller parameters</i> |     |            |     |            |
| <b>a1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>sfrb0</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb1</b>                 | 31  | 30         | ... | 27         |
| <b>sfra1</b>                 | 31  | 30         | ... | 27         |
| <b>b0</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfrb0</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>               | 0   | 1073741824 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 5170  |
| Max CPU cycles  | 19264 |
| Avg CPU cycles  | 11146 |

**Verification: Bilin FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-25  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Filter block Bilin.

| Test results   |            |           |     |           |
|----------------|------------|-----------|-----|-----------|
| Time step      | 1          | 2         | ... | 73        |
| CPU cycles     | 155        | 155       | ... | 155       |
| Inputs         |            |           |     |           |
| In (DSP)       | -120706110 | -44469415 | ... | 999834674 |
| In             | -0.056     | -0.021    | ... | 0.466     |
| Parameters     |            |           |     |           |
| b0             | 0.2        |           |     |           |
| b1             | 0.1        |           |     |           |
| a0             | 1.1        |           |     |           |
| a1             | -0.7       |           |     |           |
| ts_fact        | 1          |           |     |           |
| Outputs        |            |           |     |           |
| Out            | -0.01      | -0.015    | ... | 0.338     |
| Exp. Out       | -0.01      | -0.015    | ... | 0.338     |
| Out (DSP)      | -21946566  | -33024628 | ... | 725708721 |
| Exp. Out (DSP) | -21946566  | -33024627 | ... | 725708723 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 155 |
| Max CPU cycles  | 155 |
| Avg CPU cycles  | 155 |

**Test case: Conversion test****OK**

Conversion test for Filter block Bilin.

| Test results                 |     |            |     |            |
|------------------------------|-----|------------|-----|------------|
| <b>Time step</b>             | 1   | 2          | ... | 8          |
| <i>Mask parameters</i>       |     |            |     |            |
| <b>b0</b>                    | 0   | 0.1        | ... | 10         |
| <b>b1</b>                    | 0   | 0.1        | ... | 10         |
| <b>a0</b>                    | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>                    | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>               | 1   | 1          | ... | 1          |
| <i>Controller parameters</i> |     |            |     |            |
| <b>a1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>sfrb0</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb1</b>                 | 31  | 30         | ... | 27         |
| <b>sfra1</b>                 | 31  | 30         | ... | 27         |
| <b>b0</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfrb0</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>               | 0   | 1073741824 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Bilin.

| Test results                 |     |            |     |            |
|------------------------------|-----|------------|-----|------------|
| <b>Time step</b>             | 1   | 2          | ... | 8          |
| <i>Mask parameters</i>       |     |            |     |            |
| <b>b0</b>                    | 0   | 0.1        | ... | 10         |
| <b>b1</b>                    | 0   | 0.1        | ... | 10         |
| <b>a0</b>                    | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>                    | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>               | 1   | 1          | ... | 1          |
| <i>Controller parameters</i> |     |            |     |            |
| <b>a1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>sfrb0</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb1</b>                 | 31  | 30         | ... | 27         |
| <b>sfra1</b>                 | 31  | 30         | ... | 27         |
| <b>b0</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfrb0</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>               | 0   | 1073741824 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2229 |
| Max CPU cycles  | 8031 |
| Avg CPU cycles  | 4701 |

**Verification: Bilin FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-25  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Filter block Bilin.

| Test results   |            |           |     |           |
|----------------|------------|-----------|-----|-----------|
| Time step      | 1          | 2         | ... | 73        |
| CPU cycles     | 167        | 167       | ... | 167       |
| Inputs         |            |           |     |           |
| In (DSP)       | -120706110 | -44469415 | ... | 999834674 |
| In             | -0.056     | -0.021    | ... | 0.466     |
| Parameters     |            |           |     |           |
| b0             | 0.2        |           |     |           |
| b1             | 0.1        |           |     |           |
| a0             | 1.1        |           |     |           |
| a1             | -0.7       |           |     |           |
| ts_fact        | 1          |           |     |           |
| Outputs        |            |           |     |           |
| Out            | -0.01      | -0.015    | ... | 0.338     |
| Exp. Out       | -0.01      | -0.015    | ... | 0.338     |
| Out (DSP)      | -21946566  | -33024628 | ... | 725708721 |
| Exp. Out (DSP) | -21946566  | -33024627 | ... | 725708723 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 167 |
| Max CPU cycles  | 167 |
| Avg CPU cycles  | 167 |

**Test case: Conversion test****OK**

Conversion test for Filter block Bilin.

| Test results                 |     |            |     |            |
|------------------------------|-----|------------|-----|------------|
| <b>Time step</b>             | 1   | 2          | ... | 8          |
| <i>Mask parameters</i>       |     |            |     |            |
| <b>b0</b>                    | 0   | 0.1        | ... | 10         |
| <b>b1</b>                    | 0   | 0.1        | ... | 10         |
| <b>a0</b>                    | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>                    | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>               | 1   | 1          | ... | 1          |
| <i>Controller parameters</i> |     |            |     |            |
| <b>a1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>sfrb0</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb1</b>                 | 31  | 30         | ... | 27         |
| <b>sfra1</b>                 | 31  | 30         | ... | 27         |
| <b>b0</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfrb0</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>               | 0   | 1073741824 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Bilin.



| Test results                 |     |            |     |            |
|------------------------------|-----|------------|-----|------------|
| <b>Time step</b>             | 1   | 2          | ... | 8          |
| <i>Mask parameters</i>       |     |            |     |            |
| <b>b0</b>                    | 0   | 0.1        | ... | 10         |
| <b>b1</b>                    | 0   | 0.1        | ... | 10         |
| <b>a0</b>                    | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>                    | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>               | 1   | 1          | ... | 1          |
| <i>Controller parameters</i> |     |            |     |            |
| <b>a1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>sfrb0</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb1</b>                 | 31  | 30         | ... | 27         |
| <b>sfra1</b>                 | 31  | 30         | ... | 27         |
| <b>b0</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfrb0</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>               | 0   | 1073741824 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2931 |
| Max CPU cycles  | 5516 |
| Avg CPU cycles  | 4004 |

**Verification: Bilin FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-25  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Filter block Bilin.

| Test results   |            |           |     |           |
|----------------|------------|-----------|-----|-----------|
| Time step      | 1          | 2         | ... | 73        |
| CPU cycles     | 410        | 410       | ... | 405       |
| Inputs         |            |           |     |           |
| In (DSP)       | -120706110 | -44469415 | ... | 999834674 |
| In             | -0.056     | -0.021    | ... | 0.466     |
| Parameters     |            |           |     |           |
| b0             | 0.2        |           |     |           |
| b1             | 0.1        |           |     |           |
| a0             | 1.1        |           |     |           |
| a1             | -0.7       |           |     |           |
| ts_fact        | 1          |           |     |           |
| Outputs        |            |           |     |           |
| Out            | -0.01      | -0.015    | ... | 0.338     |
| Exp. Out       | -0.01      | -0.015    | ... | 0.338     |
| Out (DSP)      | -21946566  | -33024628 | ... | 725708721 |
| Exp. Out (DSP) | -21946566  | -33024627 | ... | 725708723 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 405 |
| Max CPU cycles  | 411 |
| Avg CPU cycles  | 407 |

**Test case: Conversion test****OK**

Conversion test for Filter block Bilin.

| Test results                 |     |            |     |            |
|------------------------------|-----|------------|-----|------------|
| <b>Time step</b>             | 1   | 2          | ... | 8          |
| <i>Mask parameters</i>       |     |            |     |            |
| <b>b0</b>                    | 0   | 0.1        | ... | 10         |
| <b>b1</b>                    | 0   | 0.1        | ... | 10         |
| <b>a0</b>                    | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>                    | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>               | 1   | 1          | ... | 1          |
| <i>Controller parameters</i> |     |            |     |            |
| <b>a1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>sfrb0</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb1</b>                 | 31  | 30         | ... | 27         |
| <b>sfra1</b>                 | 31  | 30         | ... | 27         |
| <b>b0</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfrb0</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>               | 0   | 1073741824 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Bilin.

| Test results                 |     |            |     |            |
|------------------------------|-----|------------|-----|------------|
| <b>Time step</b>             | 1   | 2          | ... | 8          |
| <i>Mask parameters</i>       |     |            |     |            |
| <b>b0</b>                    | 0   | 0.1        | ... | 10         |
| <b>b1</b>                    | 0   | 0.1        | ... | 10         |
| <b>a0</b>                    | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>                    | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>               | 1   | 1          | ... | 1          |
| <i>Controller parameters</i> |     |            |     |            |
| <b>a1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>sfrb0</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb1</b>                 | 31  | 30         | ... | 27         |
| <b>sfra1</b>                 | 31  | 30         | ... | 27         |
| <b>b0</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfrb0</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>               | 0   | 1073741824 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 8462  |
| Max CPU cycles  | 19060 |
| Avg CPU cycles  | 14421 |

**Verification: Bilin FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-25  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Filter block Bilin.

| Test results   |            |           |     |           |
|----------------|------------|-----------|-----|-----------|
| Time step      | 1          | 2         | ... | 73        |
| CPU cycles     | 121        | 121       | ... | 123       |
| Inputs         |            |           |     |           |
| In (DSP)       | -120706110 | -44469415 | ... | 999834674 |
| In             | -0.056     | -0.021    | ... | 0.466     |
| Parameters     |            |           |     |           |
| b0             | 0.2        |           |     |           |
| b1             | 0.1        |           |     |           |
| a0             | 1.1        |           |     |           |
| a1             | -0.7       |           |     |           |
| ts_fact        | 1          |           |     |           |
| Outputs        |            |           |     |           |
| Out            | -0.01      | -0.015    | ... | 0.338     |
| Exp. Out       | -0.01      | -0.015    | ... | 0.338     |
| Out (DSP)      | -21946566  | -33024628 | ... | 725708721 |
| Exp. Out (DSP) | -21946566  | -33024627 | ... | 725708723 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 121 |
| Max CPU cycles  | 123 |
| Avg CPU cycles  | 122 |

**Test case: Conversion test****OK**

Conversion test for Filter block Bilin.

| Test results                 |     |            |     |            |
|------------------------------|-----|------------|-----|------------|
| <b>Time step</b>             | 1   | 2          | ... | 8          |
| <i>Mask parameters</i>       |     |            |     |            |
| <b>b0</b>                    | 0   | 0.1        | ... | 10         |
| <b>b1</b>                    | 0   | 0.1        | ... | 10         |
| <b>a0</b>                    | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>                    | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>               | 1   | 1          | ... | 1          |
| <i>Controller parameters</i> |     |            |     |            |
| <b>a1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>sfrb0</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb1</b>                 | 31  | 30         | ... | 27         |
| <b>sfra1</b>                 | 31  | 30         | ... | 27         |
| <b>b0</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfrb0</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>               | 0   | 1073741824 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Bilin.

| Test results                 |     |            |     |            |
|------------------------------|-----|------------|-----|------------|
| <b>Time step</b>             | 1   | 2          | ... | 8          |
| <i>Mask parameters</i>       |     |            |     |            |
| <b>b0</b>                    | 0   | 0.1        | ... | 10         |
| <b>b1</b>                    | 0   | 0.1        | ... | 10         |
| <b>a0</b>                    | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>                    | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>               | 1   | 1          | ... | 1          |
| <i>Controller parameters</i> |     |            |     |            |
| <b>a1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>sfrb0</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb1</b>                 | 31  | 30         | ... | 27         |
| <b>sfra1</b>                 | 31  | 30         | ... | 27         |
| <b>b0</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfrb0</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>               | 0   | 1073741824 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3804 |
| Max CPU cycles  | 7820 |
| Avg CPU cycles  | 5893 |

**Verification: Bilin FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-25  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Filter block Bilin.

| Test results   |            |           |     |           |
|----------------|------------|-----------|-----|-----------|
| Time step      | 1          | 2         | ... | 73        |
| CPU cycles     | 1378       | 1386      | ... | 1371      |
| Inputs         |            |           |     |           |
| In (DSP)       | -120706110 | -44469415 | ... | 999834674 |
| In             | -0.056     | -0.021    | ... | 0.466     |
| Parameters     |            |           |     |           |
| b0             | 0.2        |           |     |           |
| b1             | 0.1        |           |     |           |
| a0             | 1.1        |           |     |           |
| a1             | -0.7       |           |     |           |
| ts_fact        | 1          |           |     |           |
| Outputs        |            |           |     |           |
| Out            | -0.01      | -0.015    | ... | 0.338     |
| Exp. Out       | -0.01      | -0.015    | ... | 0.338     |
| Out (DSP)      | -21946566  | -33024628 | ... | 725708721 |
| Exp. Out (DSP) | -21946566  | -33024627 | ... | 725708723 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1371 |
| Max CPU cycles  | 1386 |
| Avg CPU cycles  | 1377 |

**Test case: Conversion test****OK**

Conversion test for Filter block Bilin.



| Test results                 |     |            |     |            |
|------------------------------|-----|------------|-----|------------|
| <b>Time step</b>             | 1   | 2          | ... | 8          |
| <i>Mask parameters</i>       |     |            |     |            |
| <b>b0</b>                    | 0   | 0.1        | ... | 10         |
| <b>b1</b>                    | 0   | 0.1        | ... | 10         |
| <b>a0</b>                    | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>                    | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>               | 1   | 1          | ... | 1          |
| <i>Controller parameters</i> |     |            |     |            |
| <b>a1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>sfrb0</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb1</b>                 | 31  | 30         | ... | 27         |
| <b>sfra1</b>                 | 31  | 30         | ... | 27         |
| <b>b0</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfrb0</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>               | 0   | 1073741824 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Bilin.

| Test results                 |     |            |     |            |
|------------------------------|-----|------------|-----|------------|
| <b>Time step</b>             | 1   | 2          | ... | 8          |
| <i>Mask parameters</i>       |     |            |     |            |
| <b>b0</b>                    | 0   | 0.1        | ... | 10         |
| <b>b1</b>                    | 0   | 0.1        | ... | 10         |
| <b>a0</b>                    | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>                    | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>               | 1   | 1          | ... | 1          |
| <i>Controller parameters</i> |     |            |     |            |
| <b>a1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>sfrb0</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb1</b>                 | 31  | 30         | ... | 27         |
| <b>sfra1</b>                 | 31  | 30         | ... | 27         |
| <b>b0</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfrb0</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>               | 0   | 1073741824 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 10170 |
| Max CPU cycles  | 36947 |
| Avg CPU cycles  | 24237 |

**Verification: Bilin FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-25  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Filter block Bilin.

| Test results   |            |           |     |           |
|----------------|------------|-----------|-----|-----------|
| Time step      | 1          | 2         | ... | 73        |
| CPU cycles     | 164        | 142       | ... | 142       |
| Inputs         |            |           |     |           |
| In (DSP)       | -120706110 | -44469415 | ... | 999834674 |
| In             | -0.056     | -0.021    | ... | 0.466     |
| Parameters     |            |           |     |           |
| b0             | 0.2        |           |     |           |
| b1             | 0.1        |           |     |           |
| a0             | 1.1        |           |     |           |
| a1             | -0.7       |           |     |           |
| ts_fact        | 1          |           |     |           |
| Outputs        |            |           |     |           |
| Out            | -0.01      | -0.015    | ... | 0.338     |
| Exp. Out       | -0.01      | -0.015    | ... | 0.338     |
| Out (DSP)      | -21946566  | -33024628 | ... | 725708721 |
| Exp. Out (DSP) | -21946566  | -33024627 | ... | 725708723 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 142 |
| Max CPU cycles  | 164 |
| Avg CPU cycles  | 142 |

**Test case: Conversion test****OK**

Conversion test for Filter block Bilin.

| Test results                 |     |            |     |            |
|------------------------------|-----|------------|-----|------------|
| <b>Time step</b>             | 1   | 2          | ... | 8          |
| <i>Mask parameters</i>       |     |            |     |            |
| <b>b0</b>                    | 0   | 0.1        | ... | 10         |
| <b>b1</b>                    | 0   | 0.1        | ... | 10         |
| <b>a0</b>                    | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>                    | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>               | 1   | 1          | ... | 1          |
| <i>Controller parameters</i> |     |            |     |            |
| <b>a1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>sfrb0</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb1</b>                 | 31  | 30         | ... | 27         |
| <b>sfra1</b>                 | 31  | 30         | ... | 27         |
| <b>b0</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfrb0</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>               | 0   | 1073741824 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Bilin.

| Test results                 |     |            |     |            |
|------------------------------|-----|------------|-----|------------|
| <b>Time step</b>             | 1   | 2          | ... | 8          |
| <i>Mask parameters</i>       |     |            |     |            |
| <b>b0</b>                    | 0   | 0.1        | ... | 10         |
| <b>b1</b>                    | 0   | 0.1        | ... | 10         |
| <b>a0</b>                    | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>                    | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>               | 1   | 1          | ... | 1          |
| <i>Controller parameters</i> |     |            |     |            |
| <b>a1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>sfrb0</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb1</b>                 | 31  | 30         | ... | 27         |
| <b>sfra1</b>                 | 31  | 30         | ... | 27         |
| <b>b0</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfrb0</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>               | 0   | 1073741824 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2588 |
| Max CPU cycles  | 5130 |
| Avg CPU cycles  | 3663 |

**Verification: Bilin FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-25  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Filter block Bilin.

| Test results   |            |           |     |           |
|----------------|------------|-----------|-----|-----------|
| Time step      | 1          | 2         | ... | 73        |
| CPU cycles     | 193        | 193       | ... | 193       |
| Inputs         |            |           |     |           |
| In (DSP)       | -120706110 | -44469415 | ... | 999834674 |
| In             | -0.056     | -0.021    | ... | 0.466     |
| Parameters     |            |           |     |           |
| b0             | 0.2        |           |     |           |
| b1             | 0.1        |           |     |           |
| a0             | 1.1        |           |     |           |
| a1             | -0.7       |           |     |           |
| ts_fact        | 1          |           |     |           |
| Outputs        |            |           |     |           |
| Out            | -0.01      | -0.015    | ... | 0.338     |
| Exp. Out       | -0.01      | -0.015    | ... | 0.338     |
| Out (DSP)      | -21946566  | -33024628 | ... | 725708721 |
| Exp. Out (DSP) | -21946566  | -33024627 | ... | 725708723 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 193 |
| Max CPU cycles  | 193 |
| Avg CPU cycles  | 193 |

**Test case: Conversion test****OK**

Conversion test for Filter block Bilin.

| Test results                 |     |            |     |            |
|------------------------------|-----|------------|-----|------------|
| <b>Time step</b>             | 1   | 2          | ... | 8          |
| <i>Mask parameters</i>       |     |            |     |            |
| <b>b0</b>                    | 0   | 0.1        | ... | 10         |
| <b>b1</b>                    | 0   | 0.1        | ... | 10         |
| <b>a0</b>                    | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>                    | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>               | 1   | 1          | ... | 1          |
| <i>Controller parameters</i> |     |            |     |            |
| <b>a1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>sfrb0</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb1</b>                 | 31  | 30         | ... | 27         |
| <b>sfra1</b>                 | 31  | 30         | ... | 27         |
| <b>b0</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfrb0</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>               | 0   | 1073741824 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Bilin.

| Test results                 |     |            |     |            |
|------------------------------|-----|------------|-----|------------|
| <b>Time step</b>             | 1   | 2          | ... | 8          |
| <i>Mask parameters</i>       |     |            |     |            |
| <b>b0</b>                    | 0   | 0.1        | ... | 10         |
| <b>b1</b>                    | 0   | 0.1        | ... | 10         |
| <b>a0</b>                    | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>                    | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>               | 1   | 1          | ... | 1          |
| <i>Controller parameters</i> |     |            |     |            |
| <b>a1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>sfrb0</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb1</b>                 | 31  | 30         | ... | 27         |
| <b>sfra1</b>                 | 31  | 30         | ... | 27         |
| <b>b0</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfrb0</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>               | 0   | 1073741824 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 3707  |
| Max CPU cycles  | 14159 |
| Avg CPU cycles  | 8200  |



**Verification: Bilin Float32 CPU TMS320F28335**

**Date of Test** 2026-06-25  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Filter block Bilin.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 73    |
| CPU cycles     | 65     | 65     | ... | 65    |
| Inputs         |        |        |     |       |
| In (DSP)       | -0.056 | -0.021 | ... | 0.466 |
| In             | -0.056 | -0.021 | ... | 0.466 |
| Parameters     |        |        |     |       |
| b0             | 0.2    |        |     |       |
| b1             | 0.1    |        |     |       |
| a0             | 1.1    |        |     |       |
| a1             | -0.7   |        |     |       |
| ts_fact        | 1      |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -0.01  | -0.015 | ... | 0.338 |
| Exp. Out       | -0.01  | -0.015 | ... | 0.338 |
| Out (DSP)      | -0.01  | -0.015 | ... | 0.338 |
| Exp. Out (DSP) | -0.01  | -0.015 | ... | 0.338 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 9,3132e-08$ ( $\pm 200$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 65 |
| Max CPU cycles  | 65 |
| Avg CPU cycles  | 65 |

**Test case: Conversion test****OK**

Conversion test for Filter block Bilin.

| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| <b>Time step</b>             | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Bilin.

| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| <b>Time step</b>             | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 2974  |
| Max CPU cycles  | 13480 |
| Avg CPU cycles  | 6004  |

**Verification: Bilin Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-25  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Filter block Bilin.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 73    |
| CPU cycles     | 41     | 41     | ... | 41    |
| Inputs         |        |        |     |       |
| In (DSP)       | -0.056 | -0.021 | ... | 0.466 |
| In             | -0.056 | -0.021 | ... | 0.466 |
| Parameters     |        |        |     |       |
| b0             | 0.2    |        |     |       |
| b1             | 0.1    |        |     |       |
| a0             | 1.1    |        |     |       |
| a1             | -0.7   |        |     |       |
| ts_fact        | 1      |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -0.01  | -0.015 | ... | 0.338 |
| Exp. Out       | -0.01  | -0.015 | ... | 0.338 |
| Out (DSP)      | -0.01  | -0.015 | ... | 0.338 |
| Exp. Out (DSP) | -0.01  | -0.015 | ... | 0.338 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 9,3132e-08$ ( $\pm 200$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 41 |
| Max CPU cycles  | 41 |
| Avg CPU cycles  | 41 |

**Test case: Conversion test****OK**

Conversion test for Filter block Bilin.

| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| <b>Time step</b>             | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Bilin.

| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| <b>Time step</b>             | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1381 |
| Max CPU cycles  | 5719 |
| Avg CPU cycles  | 2632 |

**Verification: Bilin Float32 CPU STM32G474RE**

**Date of Test** 2026-06-25  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Filter block Bilin.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 73    |
| CPU cycles     | 82     | 82     | ... | 82    |
| Inputs         |        |        |     |       |
| In (DSP)       | -0.056 | -0.021 | ... | 0.466 |
| In             | -0.056 | -0.021 | ... | 0.466 |
| Parameters     |        |        |     |       |
| b0             | 0.2    |        |     |       |
| b1             | 0.1    |        |     |       |
| a0             | 1.1    |        |     |       |
| a1             | -0.7   |        |     |       |
| ts_fact        | 1      |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -0.01  | -0.015 | ... | 0.338 |
| Exp. Out       | -0.01  | -0.015 | ... | 0.338 |
| Out (DSP)      | -0.01  | -0.015 | ... | 0.338 |
| Exp. Out (DSP) | -0.01  | -0.015 | ... | 0.338 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 9,3132e-08$ ( $\pm 200$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 82 |
| Max CPU cycles  | 82 |
| Avg CPU cycles  | 82 |

**Test case: Conversion test****OK**

Conversion test for Filter block Bilin.

| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| <b>Time step</b>             | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Bilin.

| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| <b>Time step</b>             | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |



| Test settings |                  |
|---------------|------------------|
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1165 |
| Max CPU cycles  | 2994 |
| Avg CPU cycles  | 1633 |

**Verification: Bilin Float32 CPU STM32F072RB**

**Date of Test** 2026-06-25  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Filter block Bilin.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 73    |
| CPU cycles     | 650    | 859    | ... | 836   |
| Inputs         |        |        |     |       |
| In (DSP)       | -0.056 | -0.021 | ... | 0.466 |
| In             | -0.056 | -0.021 | ... | 0.466 |
| Parameters     |        |        |     |       |
| b0             | 0.2    |        |     |       |
| b1             | 0.1    |        |     |       |
| a0             | 1.1    |        |     |       |
| a1             | -0.7   |        |     |       |
| ts_fact        | 1      |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -0.01  | -0.015 | ... | 0.338 |
| Exp. Out       | -0.01  | -0.015 | ... | 0.338 |
| Out (DSP)      | -0.01  | -0.015 | ... | 0.338 |
| Exp. Out (DSP) | -0.01  | -0.015 | ... | 0.338 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 9,3132e-08$ ( $\pm 200$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 650 |
| Max CPU cycles  | 912 |
| Avg CPU cycles  | 848 |

**Test case: Conversion test****OK**

Conversion test for Filter block Bilin.

| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| <b>Time step</b>             | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Bilin.

| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| <b>Time step</b>             | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2424 |
| Max CPU cycles  | 4811 |
| Avg CPU cycles  | 3781 |

**Verification: Bilin Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-25  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Filter block Bilin.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 73    |
| CPU cycles     | 230    | 328    | ... | 334   |
| Inputs         |        |        |     |       |
| In (DSP)       | -0.056 | -0.021 | ... | 0.466 |
| In             | -0.056 | -0.021 | ... | 0.466 |
| Parameters     |        |        |     |       |
| b0             | 0.2    |        |     |       |
| b1             | 0.1    |        |     |       |
| a0             | 1.1    |        |     |       |
| a1             | -0.7   |        |     |       |
| ts_fact        | 1      |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -0.01  | -0.015 | ... | 0.338 |
| Exp. Out       | -0.01  | -0.015 | ... | 0.338 |
| Out (DSP)      | -0.01  | -0.015 | ... | 0.338 |
| Exp. Out (DSP) | -0.01  | -0.015 | ... | 0.338 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 9,3132e-08$ ( $\pm 200$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 230 |
| Max CPU cycles  | 338 |
| Avg CPU cycles  | 326 |

**Test case: Conversion test****OK**

Conversion test for Filter block Bilin.

| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| <b>Time step</b>             | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Bilin.

| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| <b>Time step</b>             | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 930  |
| Max CPU cycles  | 1659 |
| Avg CPU cycles  | 1424 |

**Verification: Bilin Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-25  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Filter block Bilin.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 73    |
| CPU cycles     | 668    | 861    | ... | 854   |
| Inputs         |        |        |     |       |
| In (DSP)       | -0.056 | -0.021 | ... | 0.466 |
| In             | -0.056 | -0.021 | ... | 0.466 |
| Parameters     |        |        |     |       |
| b0             | 0.2    |        |     |       |
| b1             | 0.1    |        |     |       |
| a0             | 1.1    |        |     |       |
| a1             | -0.7   |        |     |       |
| ts_fact        | 1      |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -0.01  | -0.015 | ... | 0.338 |
| Exp. Out       | -0.01  | -0.015 | ... | 0.338 |
| Out (DSP)      | -0.01  | -0.015 | ... | 0.338 |
| Exp. Out (DSP) | -0.01  | -0.015 | ... | 0.338 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 9,3132e-08$ ( $\pm 200$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 668 |
| Max CPU cycles  | 958 |
| Avg CPU cycles  | 868 |

**Test case: Conversion test****OK**

Conversion test for Filter block Bilin.



| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| <b>Time step</b>             | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Bilin.

| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| <b>Time step</b>             | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2988 |
| Max CPU cycles  | 7784 |
| Avg CPU cycles  | 7124 |

**Verification: Bilin Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-25  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Filter block Bilin.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 73    |
| CPU cycles     | 88     | 76     | ... | 76    |
| Inputs         |        |        |     |       |
| In (DSP)       | -0.056 | -0.021 | ... | 0.466 |
| In             | -0.056 | -0.021 | ... | 0.466 |
| Parameters     |        |        |     |       |
| b0             | 0.2    |        |     |       |
| b1             | 0.1    |        |     |       |
| a0             | 1.1    |        |     |       |
| a1             | -0.7   |        |     |       |
| ts_fact        | 1      |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -0.01  | -0.015 | ... | 0.338 |
| Exp. Out       | -0.01  | -0.015 | ... | 0.338 |
| Out (DSP)      | -0.01  | -0.015 | ... | 0.338 |
| Exp. Out (DSP) | -0.01  | -0.015 | ... | 0.338 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 9,3132e-08$ ( $\pm 200$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 76 |
| Max CPU cycles  | 88 |
| Avg CPU cycles  | 76 |

**Test case: Conversion test****OK**

Conversion test for Filter block Bilin.

| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| <b>Time step</b>             | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Bilin.

| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| <b>Time step</b>             | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1037 |
| Max CPU cycles  | 2847 |
| Avg CPU cycles  | 1512 |

**Verification: Bilin Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-25  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Filter block Bilin.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 73    |
| CPU cycles     | 58     | 58     | ... | 58    |
| Inputs         |        |        |     |       |
| In (DSP)       | -0.056 | -0.021 | ... | 0.466 |
| In             | -0.056 | -0.021 | ... | 0.466 |
| Parameters     |        |        |     |       |
| b0             | 0.2    |        |     |       |
| b1             | 0.1    |        |     |       |
| a0             | 1.1    |        |     |       |
| a1             | -0.7   |        |     |       |
| ts_fact        | 1      |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -0.01  | -0.015 | ... | 0.338 |
| Exp. Out       | -0.01  | -0.015 | ... | 0.338 |
| Out (DSP)      | -0.01  | -0.015 | ... | 0.338 |
| Exp. Out (DSP) | -0.01  | -0.015 | ... | 0.338 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 9,3132e-08$ ( $\pm 200$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 58 |
| Max CPU cycles  | 58 |
| Avg CPU cycles  | 58 |

**Test case: Conversion test****OK**

Conversion test for Filter block Bilin.

| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| <b>Time step</b>             | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Bilin.


| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| <b>Time step</b>             | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2123 |
| Max CPU cycles  | 9827 |
| Avg CPU cycles  | 4360 |



## Block: Biquad



Second order transfer function:

$$H(z) = (b_0.z^2 + b_1.z + b_2) / (a_0.z^2 + a_1.z + a_2)$$

| Inports |             |
|---------|-------------|
| In      | Input In(k) |

| Outports |               |
|----------|---------------|
| Out      | Output Out(k) |

| Mask Parameters |    |                                                                 |
|-----------------|----|-----------------------------------------------------------------|
| Name            | ID | Description                                                     |
| b0              | 1  | Filter coefficient b0                                           |
| b1              | 2  | Filter coefficient b1                                           |
| b2              | 3  | Filter coefficient b2                                           |
| a0              | 4  | Filter coefficient a0                                           |
| a1              | 5  | Filter coefficient a1                                           |
| a2              | 6  | Filter coefficient a2                                           |
| ts_fact         | 7  | Multiplication factor of base sampling time (in integer format) |

### Description:

Alternative representation of the same transfer function:

$$H(z) = \frac{b_0 + b_1 z^{-1} + b_2 z^{-2}}{a_0 + a_1 z^{-1} + a_2 z^{-2}}$$

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP16

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: Biquad FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-25  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Filter block Biquad.

| Test results   |        |        |       |       |     |       |
|----------------|--------|--------|-------|-------|-----|-------|
| Time step      | 1      | 2      | 3     | 4     | ... | 73    |
| CPU cycles     | 116    | 116    | 116   | 116   | ... | 116   |
| Inputs         |        |        |       |       |     |       |
| In (DSP)       | -1842  | -679   | 5729  | 7954  | ... | 15256 |
| In             | -0.056 | -0.021 | 0.175 | 0.243 | ... | 0.466 |
| Parameters     |        |        |       |       |     |       |
| b0             | 0.2    |        |       |       |     |       |
| b1             | 0.1    |        |       |       |     |       |
| b2             | 0.3    |        |       |       |     |       |
| a0             | 1.1    |        |       |       |     |       |
| a1             | -0.7   |        |       |       |     |       |
| a2             | 0.8    |        |       |       |     |       |
| ts_fact        | 1      |        |       |       |     |       |
| Outputs        |        |        |       |       |     |       |
| Out            | -0.01  | -0.015 | 0.012 | 0.073 | ... | 0.257 |
| Exp. Out       | -0.01  | -0.015 | 0.012 | 0.073 | ... | 0.257 |
| Out (DSP)      | -335   | -505   | 399   | 2402  | ... | 8434  |
| Exp. Out (DSP) | -335   | -504   | 401   | 2403  | ... | 8434  |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}04$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 116 |
| Max CPU cycles  | 116 |
| Avg CPU cycles  | 116 |

**Test case: Conversion test****OK**

Conversion test for Filter block Biquad.

| Test results                 |     |       |       |       |     |       |
|------------------------------|-----|-------|-------|-------|-----|-------|
| Time step                    | 1   | 2     | 3     | 4     | ... | 8     |
| <i>Mask parameters</i>       |     |       |       |       |     |       |
| <b>b0</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>                    | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>               | 1   | 1     | 1     | 1     | ... | 1     |
| <i>Controller parameters</i> |     |       |       |       |     |       |
| <b>b2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfra2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb0</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfra2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb0</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Biquad.

| Test results                 |     |       |       |       |     |       |
|------------------------------|-----|-------|-------|-------|-----|-------|
| Time step                    | 1   | 2     | 3     | 4     | ... | 8     |
| <i>Mask parameters</i>       |     |       |       |       |     |       |
| <b>b0</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>                    | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>               | 1   | 1     | 1     | 1     | ... | 1     |
| <i>Controller parameters</i> |     |       |       |       |     |       |
| <b>b2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfra2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb0</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfra2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb0</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 6789  |
| Max CPU cycles  | 30034 |
| Avg CPU cycles  | 16535 |

**Verification: Biquad FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-25  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Filter block Biquad.

| Test results   |        |        |       |       |     |       |
|----------------|--------|--------|-------|-------|-----|-------|
| Time step      | 1      | 2      | 3     | 4     | ... | 73    |
| CPU cycles     | 93     | 93     | 93    | 93    | ... | 93    |
| Inputs         |        |        |       |       |     |       |
| In (DSP)       | -1842  | -679   | 5729  | 7954  | ... | 15256 |
| In             | -0.056 | -0.021 | 0.175 | 0.243 | ... | 0.466 |
| Parameters     |        |        |       |       |     |       |
| b0             | 0.2    |        |       |       |     |       |
| b1             | 0.1    |        |       |       |     |       |
| b2             | 0.3    |        |       |       |     |       |
| a0             | 1.1    |        |       |       |     |       |
| a1             | -0.7   |        |       |       |     |       |
| a2             | 0.8    |        |       |       |     |       |
| ts_fact        | 1      |        |       |       |     |       |
| Outputs        |        |        |       |       |     |       |
| Out            | -0.01  | -0.015 | 0.012 | 0.073 | ... | 0.257 |
| Exp. Out       | -0.01  | -0.015 | 0.012 | 0.073 | ... | 0.257 |
| Out (DSP)      | -335   | -505   | 399   | 2402  | ... | 8434  |
| Exp. Out (DSP) | -335   | -504   | 401   | 2403  | ... | 8434  |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}04$ ( $\pm 5$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 93 |
| Max CPU cycles  | 93 |
| Avg CPU cycles  | 93 |

**Test case: Conversion test****OK**

Conversion test for Filter block Biquad.



| Test results                 |     |       |       |       |     |       |
|------------------------------|-----|-------|-------|-------|-----|-------|
| Time step                    | 1   | 2     | 3     | 4     | ... | 8     |
| <i>Mask parameters</i>       |     |       |       |       |     |       |
| <b>b0</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>                    | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>               | 1   | 1     | 1     | 1     | ... | 1     |
| <i>Controller parameters</i> |     |       |       |       |     |       |
| <b>b2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfra2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb0</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfra2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb0</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Biquad.

| Test results                 |     |       |       |       |     |       |
|------------------------------|-----|-------|-------|-------|-----|-------|
| Time step                    | 1   | 2     | 3     | 4     | ... | 8     |
| <i>Mask parameters</i>       |     |       |       |       |     |       |
| <b>b0</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>                    | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>               | 1   | 1     | 1     | 1     | ... | 1     |
| <i>Controller parameters</i> |     |       |       |       |     |       |
| <b>b2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfra2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb0</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfra2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb0</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 3473  |
| Max CPU cycles  | 13973 |
| Avg CPU cycles  | 8260  |

**Verification: Biquad FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-25  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Filter block Biquad.

| Test results   |        |        |       |       |     |       |
|----------------|--------|--------|-------|-------|-----|-------|
| Time step      | 1      | 2      | 3     | 4     | ... | 73    |
| CPU cycles     | 147    | 147    | 147   | 147   | ... | 147   |
| Inputs         |        |        |       |       |     |       |
| In (DSP)       | -1842  | -679   | 5729  | 7954  | ... | 15256 |
| In             | -0.056 | -0.021 | 0.175 | 0.243 | ... | 0.466 |
| Parameters     |        |        |       |       |     |       |
| b0             | 0.2    |        |       |       |     |       |
| b1             | 0.1    |        |       |       |     |       |
| b2             | 0.3    |        |       |       |     |       |
| a0             | 1.1    |        |       |       |     |       |
| a1             | -0.7   |        |       |       |     |       |
| a2             | 0.8    |        |       |       |     |       |
| ts_fact        | 1      |        |       |       |     |       |
| Outputs        |        |        |       |       |     |       |
| Out            | -0.01  | -0.015 | 0.012 | 0.073 | ... | 0.257 |
| Exp. Out       | -0.01  | -0.015 | 0.012 | 0.073 | ... | 0.257 |
| Out (DSP)      | -335   | -505   | 399   | 2402  | ... | 8434  |
| Exp. Out (DSP) | -335   | -504   | 401   | 2403  | ... | 8434  |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}04$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 147 |
| Max CPU cycles  | 147 |
| Avg CPU cycles  | 147 |

**Test case: Conversion test****OK**

Conversion test for Filter block Biquad.

| Test results                 |     |       |       |       |     |       |
|------------------------------|-----|-------|-------|-------|-----|-------|
| Time step                    | 1   | 2     | 3     | 4     | ... | 8     |
| <i>Mask parameters</i>       |     |       |       |       |     |       |
| <b>b0</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>                    | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>               | 1   | 1     | 1     | 1     | ... | 1     |
| <i>Controller parameters</i> |     |       |       |       |     |       |
| <b>b2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfra2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb0</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfra2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb0</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Biquad.

| Test results                 |     |       |       |       |     |       |
|------------------------------|-----|-------|-------|-------|-----|-------|
| Time step                    | 1   | 2     | 3     | 4     | ... | 8     |
| <i>Mask parameters</i>       |     |       |       |       |     |       |
| <b>b0</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>                    | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>               | 1   | 1     | 1     | 1     | ... | 1     |
| <i>Controller parameters</i> |     |       |       |       |     |       |
| <b>b2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfra2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb0</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfra2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb0</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |



| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2955 |
| Max CPU cycles  | 7208 |
| Avg CPU cycles  | 4737 |

**Verification: Biquad FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-25  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Filter block Biquad.

| Test results   |        |        |       |       |     |       |
|----------------|--------|--------|-------|-------|-----|-------|
| Time step      | 1      | 2      | 3     | 4     | ... | 73    |
| CPU cycles     | 133    | 133    | 133   | 133   | ... | 133   |
| Inputs         |        |        |       |       |     |       |
| In (DSP)       | -1842  | -679   | 5729  | 7954  | ... | 15256 |
| In             | -0.056 | -0.021 | 0.175 | 0.243 | ... | 0.466 |
| Parameters     |        |        |       |       |     |       |
| b0             | 0.2    |        |       |       |     |       |
| b1             | 0.1    |        |       |       |     |       |
| b2             | 0.3    |        |       |       |     |       |
| a0             | 1.1    |        |       |       |     |       |
| a1             | -0.7   |        |       |       |     |       |
| a2             | 0.8    |        |       |       |     |       |
| ts_fact        | 1      |        |       |       |     |       |
| Outputs        |        |        |       |       |     |       |
| Out            | -0.01  | -0.015 | 0.012 | 0.073 | ... | 0.257 |
| Exp. Out       | -0.01  | -0.015 | 0.012 | 0.073 | ... | 0.257 |
| Out (DSP)      | -335   | -505   | 399   | 2402  | ... | 8434  |
| Exp. Out (DSP) | -335   | -504   | 401   | 2403  | ... | 8434  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,5259e-04$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 133 |
| Max CPU cycles  | 133 |
| Avg CPU cycles  | 133 |

**Test case: Conversion test****OK**

Conversion test for Filter block Biquad.

| Test results                 |     |       |       |       |     |       |
|------------------------------|-----|-------|-------|-------|-----|-------|
| Time step                    | 1   | 2     | 3     | 4     | ... | 8     |
| <i>Mask parameters</i>       |     |       |       |       |     |       |
| <b>b0</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>                    | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>               | 1   | 1     | 1     | 1     | ... | 1     |
| <i>Controller parameters</i> |     |       |       |       |     |       |
| <b>b2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfra2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb0</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfra2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb0</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Biquad.

| Test results                 |     |       |       |       |     |       |
|------------------------------|-----|-------|-------|-------|-----|-------|
| Time step                    | 1   | 2     | 3     | 4     | ... | 8     |
| <i>Mask parameters</i>       |     |       |       |       |     |       |
| <b>b0</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>                    | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>               | 1   | 1     | 1     | 1     | ... | 1     |
| <i>Controller parameters</i> |     |       |       |       |     |       |
| <b>b2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfra2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb0</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfra2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb0</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 8245  |
| Max CPU cycles  | 24696 |
| Avg CPU cycles  | 17166 |

**Verification: Biquad FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-25  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Filter block Biquad.

| Test results   |        |        |       |       |     |       |
|----------------|--------|--------|-------|-------|-----|-------|
| Time step      | 1      | 2      | 3     | 4     | ... | 73    |
| CPU cycles     | 90     | 90     | 90    | 90    | ... | 90    |
| Inputs         |        |        |       |       |     |       |
| In (DSP)       | -1842  | -679   | 5729  | 7954  | ... | 15256 |
| In             | -0.056 | -0.021 | 0.175 | 0.243 | ... | 0.466 |
| Parameters     |        |        |       |       |     |       |
| b0             | 0.2    |        |       |       |     |       |
| b1             | 0.1    |        |       |       |     |       |
| b2             | 0.3    |        |       |       |     |       |
| a0             | 1.1    |        |       |       |     |       |
| a1             | -0.7   |        |       |       |     |       |
| a2             | 0.8    |        |       |       |     |       |
| ts_fact        | 1      |        |       |       |     |       |
| Outputs        |        |        |       |       |     |       |
| Out            | -0.01  | -0.015 | 0.012 | 0.073 | ... | 0.257 |
| Exp. Out       | -0.01  | -0.015 | 0.012 | 0.073 | ... | 0.257 |
| Out (DSP)      | -335   | -505   | 399   | 2402  | ... | 8434  |
| Exp. Out (DSP) | -335   | -504   | 401   | 2403  | ... | 8434  |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}04$ ( $\pm 5$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 90 |
| Max CPU cycles  | 90 |
| Avg CPU cycles  | 90 |

**Test case: Conversion test****OK**

Conversion test for Filter block Biquad.

| Test results                 |     |       |       |       |     |       |
|------------------------------|-----|-------|-------|-------|-----|-------|
| Time step                    | 1   | 2     | 3     | 4     | ... | 8     |
| <i>Mask parameters</i>       |     |       |       |       |     |       |
| <b>b0</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>                    | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>               | 1   | 1     | 1     | 1     | ... | 1     |
| <i>Controller parameters</i> |     |       |       |       |     |       |
| <b>b2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfra2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb0</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfra2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb0</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |



| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Biquad.

| Test results                 |     |       |       |       |     |       |
|------------------------------|-----|-------|-------|-------|-----|-------|
| Time step                    | 1   | 2     | 3     | 4     | ... | 8     |
| <i>Mask parameters</i>       |     |       |       |       |     |       |
| <b>b0</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>                    | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>               | 1   | 1     | 1     | 1     | ... | 1     |
| <i>Controller parameters</i> |     |       |       |       |     |       |
| <b>b2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfra2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb0</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfra2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb0</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 3765  |
| Max CPU cycles  | 10429 |
| Avg CPU cycles  | 7178  |

**Verification: Biquad FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-25  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Filter block Biquad.

| Test results   |        |        |       |       |     |       |
|----------------|--------|--------|-------|-------|-----|-------|
| Time step      | 1      | 2      | 3     | 4     | ... | 73    |
| CPU cycles     | 144    | 144    | 144   | 144   | ... | 144   |
| Inputs         |        |        |       |       |     |       |
| In (DSP)       | -1842  | -679   | 5729  | 7954  | ... | 15256 |
| In             | -0.056 | -0.021 | 0.175 | 0.243 | ... | 0.466 |
| Parameters     |        |        |       |       |     |       |
| b0             | 0.2    |        |       |       |     |       |
| b1             | 0.1    |        |       |       |     |       |
| b2             | 0.3    |        |       |       |     |       |
| a0             | 1.1    |        |       |       |     |       |
| a1             | -0.7   |        |       |       |     |       |
| a2             | 0.8    |        |       |       |     |       |
| ts_fact        | 1      |        |       |       |     |       |
| Outputs        |        |        |       |       |     |       |
| Out            | -0.01  | -0.015 | 0.012 | 0.073 | ... | 0.257 |
| Exp. Out       | -0.01  | -0.015 | 0.012 | 0.073 | ... | 0.257 |
| Out (DSP)      | -335   | -505   | 399   | 2402  | ... | 8434  |
| Exp. Out (DSP) | -335   | -504   | 401   | 2403  | ... | 8434  |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}04$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 144 |
| Max CPU cycles  | 144 |
| Avg CPU cycles  | 144 |

**Test case: Conversion test****OK**

Conversion test for Filter block Biquad.

| Test results                 |     |       |       |       |     |       |
|------------------------------|-----|-------|-------|-------|-----|-------|
| Time step                    | 1   | 2     | 3     | 4     | ... | 8     |
| <i>Mask parameters</i>       |     |       |       |       |     |       |
| <b>b0</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>                    | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>               | 1   | 1     | 1     | 1     | ... | 1     |
| <i>Controller parameters</i> |     |       |       |       |     |       |
| <b>b2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfra2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb0</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfra2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb0</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Biquad.

| Test results                 |     |       |       |       |     |       |
|------------------------------|-----|-------|-------|-------|-----|-------|
| Time step                    | 1   | 2     | 3     | 4     | ... | 8     |
| <i>Mask parameters</i>       |     |       |       |       |     |       |
| <b>b0</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>                    | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>               | 1   | 1     | 1     | 1     | ... | 1     |
| <i>Controller parameters</i> |     |       |       |       |     |       |
| <b>b2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfra2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb0</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfra2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb0</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 13829 |
| Max CPU cycles  | 59790 |
| Avg CPU cycles  | 37812 |



**Verification: Biquad FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-25  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Filter block Biquad.

| Test results   |        |        |       |       |     |       |
|----------------|--------|--------|-------|-------|-----|-------|
| Time step      | 1      | 2      | 3     | 4     | ... | 73    |
| CPU cycles     | 153    | 127    | 127   | 127   | ... | 127   |
| Inputs         |        |        |       |       |     |       |
| In (DSP)       | -1842  | -679   | 5729  | 7954  | ... | 15256 |
| In             | -0.056 | -0.021 | 0.175 | 0.243 | ... | 0.466 |
| Parameters     |        |        |       |       |     |       |
| b0             | 0.2    |        |       |       |     |       |
| b1             | 0.1    |        |       |       |     |       |
| b2             | 0.3    |        |       |       |     |       |
| a0             | 1.1    |        |       |       |     |       |
| a1             | -0.7   |        |       |       |     |       |
| a2             | 0.8    |        |       |       |     |       |
| ts_fact        | 1      |        |       |       |     |       |
| Outputs        |        |        |       |       |     |       |
| Out            | -0.01  | -0.015 | 0.012 | 0.073 | ... | 0.257 |
| Exp. Out       | -0.01  | -0.015 | 0.012 | 0.073 | ... | 0.257 |
| Out (DSP)      | -335   | -505   | 399   | 2402  | ... | 8434  |
| Exp. Out (DSP) | -335   | -504   | 401   | 2403  | ... | 8434  |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}04$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 127 |
| Max CPU cycles  | 153 |
| Avg CPU cycles  | 127 |

**Test case: Conversion test****OK**

Conversion test for Filter block Biquad.

| Test results                 |     |       |       |       |     |       |
|------------------------------|-----|-------|-------|-------|-----|-------|
| Time step                    | 1   | 2     | 3     | 4     | ... | 8     |
| <i>Mask parameters</i>       |     |       |       |       |     |       |
| <b>b0</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>                    | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>               | 1   | 1     | 1     | 1     | ... | 1     |
| <i>Controller parameters</i> |     |       |       |       |     |       |
| <b>b2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfra2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb0</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfra2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb0</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Biquad.

| Test results                 |     |       |       |       |     |       |
|------------------------------|-----|-------|-------|-------|-----|-------|
| Time step                    | 1   | 2     | 3     | 4     | ... | 8     |
| <i>Mask parameters</i>       |     |       |       |       |     |       |
| <b>b0</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>                    | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>               | 1   | 1     | 1     | 1     | ... | 1     |
| <i>Controller parameters</i> |     |       |       |       |     |       |
| <b>b2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfra2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb0</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfra2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb0</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2662 |
| Max CPU cycles  | 6839 |
| Avg CPU cycles  | 4414 |

**Verification: Biquad FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-25  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Filter block Biquad.

| Test results   |        |        |       |       |     |       |
|----------------|--------|--------|-------|-------|-----|-------|
| Time step      | 1      | 2      | 3     | 4     | ... | 73    |
| CPU cycles     | 111    | 111    | 111   | 111   | ... | 111   |
| Inputs         |        |        |       |       |     |       |
| In (DSP)       | -1842  | -679   | 5729  | 7954  | ... | 15256 |
| In             | -0.056 | -0.021 | 0.175 | 0.243 | ... | 0.466 |
| Parameters     |        |        |       |       |     |       |
| b0             | 0.2    |        |       |       |     |       |
| b1             | 0.1    |        |       |       |     |       |
| b2             | 0.3    |        |       |       |     |       |
| a0             | 1.1    |        |       |       |     |       |
| a1             | -0.7   |        |       |       |     |       |
| a2             | 0.8    |        |       |       |     |       |
| ts_fact        | 1      |        |       |       |     |       |
| Outputs        |        |        |       |       |     |       |
| Out            | -0.01  | -0.015 | 0.012 | 0.073 | ... | 0.257 |
| Exp. Out       | -0.01  | -0.015 | 0.012 | 0.073 | ... | 0.257 |
| Out (DSP)      | -335   | -505   | 399   | 2402  | ... | 8434  |
| Exp. Out (DSP) | -335   | -504   | 401   | 2403  | ... | 8434  |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}04$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 111 |
| Max CPU cycles  | 111 |
| Avg CPU cycles  | 111 |

**Test case: Conversion test****OK**

Conversion test for Filter block Biquad.

| Test results                 |     |       |       |       |     |       |
|------------------------------|-----|-------|-------|-------|-----|-------|
| Time step                    | 1   | 2     | 3     | 4     | ... | 8     |
| <i>Mask parameters</i>       |     |       |       |       |     |       |
| <b>b0</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>                    | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>               | 1   | 1     | 1     | 1     | ... | 1     |
| <i>Controller parameters</i> |     |       |       |       |     |       |
| <b>b2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfra2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb0</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfra2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb0</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Biquad.



| Test results                 |     |       |       |       |     |       |
|------------------------------|-----|-------|-------|-------|-----|-------|
| Time step                    | 1   | 2     | 3     | 4     | ... | 8     |
| <i>Mask parameters</i>       |     |       |       |       |     |       |
| <b>b0</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>b2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a0</b>                    | 0.1 | 0.1   | 0.1   | 1     | ... | 1     |
| <b>a1</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>a2</b>                    | 0   | 0.1   | 0.2   | 0.5   | ... | 10    |
| <b>ts_fact</b>               | 1   | 1     | 1     | 1     | ... | 1     |
| <i>Controller parameters</i> |     |       |       |       |     |       |
| <b>b2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>a2</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>sfra2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb0</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfrb2</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>sfra1</b>                 | 15  | 14    | 13    | 15    | ... | 11    |
| <b>b0</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>b1</b>                    | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. a2</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. sfra2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb0</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfrb2</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. sfra1</b>            | 15  | 14    | 13    | 15    | ... | 11    |
| <b>Exp. b0</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |
| <b>Exp. b1</b>               | 0   | 16384 | 16384 | 16384 | ... | 20480 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 4877  |
| Max CPU cycles  | 22097 |
| Avg CPU cycles  | 12191 |

**Verification: Biquad FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-25  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Filter block Biquad.

| Test results   |            |           |     |           |
|----------------|------------|-----------|-----|-----------|
| Time step      | 1          | 2         | ... | 73        |
| CPU cycles     | 266        | 266       | ... | 266       |
| Inputs         |            |           |     |           |
| In (DSP)       | -120706110 | -44469415 | ... | 999834674 |
| In             | -0.056     | -0.021    | ... | 0.466     |
| Parameters     |            |           |     |           |
| b0             | 0.2        |           |     |           |
| b1             | 0.1        |           |     |           |
| b2             | 0.3        |           |     |           |
| a0             | 1.1        |           |     |           |
| a1             | -0.7       |           |     |           |
| a2             | 0.8        |           |     |           |
| ts_fact        | 1          |           |     |           |
| Outputs        |            |           |     |           |
| Out            | -0.01      | -0.015    | ... | 0.257     |
| Exp. Out       | -0.01      | -0.015    | ... | 0.257     |
| Out (DSP)      | -21946566  | -33024628 | ... | 552726178 |
| Exp. Out (DSP) | -21946566  | -33024627 | ... | 552726179 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 266 |
| Max CPU cycles  | 266 |
| Avg CPU cycles  | 266 |

**Test case: Conversion test****OK**

Conversion test for Filter block Biquad.

| Test results          |     |            |     |            |
|-----------------------|-----|------------|-----|------------|
| Time step             | 1   | 2          | ... | 8          |
| Mask parameters       |     |            |     |            |
| <b>b0</b>             | 0   | 0.1        | ... | 10         |
| <b>b1</b>             | 0   | 0.1        | ... | 10         |
| <b>b2</b>             | 0   | 0.1        | ... | 10         |
| <b>a0</b>             | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>             | 0   | 0.1        | ... | 10         |
| <b>a2</b>             | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>        | 1   | 1          | ... | 1          |
| Controller parameters |     |            |     |            |
| <b>b2</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>a1</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>a2</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>sfra2</b>          | 31  | 30         | ... | 27         |
| <b>sfrb0</b>          | 31  | 30         | ... | 27         |
| <b>sfrb1</b>          | 31  | 30         | ... | 27         |
| <b>sfrb2</b>          | 31  | 30         | ... | 27         |
| <b>sfra1</b>          | 31  | 30         | ... | 27         |
| <b>b0</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b2</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a2</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfra2</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfrb0</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfrb2</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>     | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>        | 0   | 1073741824 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Biquad.

| Test results          |     |            |     |            |
|-----------------------|-----|------------|-----|------------|
| Time step             | 1   | 2          | ... | 8          |
| Mask parameters       |     |            |     |            |
| <b>b0</b>             | 0   | 0.1        | ... | 10         |
| <b>b1</b>             | 0   | 0.1        | ... | 10         |
| <b>b2</b>             | 0   | 0.1        | ... | 10         |
| <b>a0</b>             | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>             | 0   | 0.1        | ... | 10         |
| <b>a2</b>             | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>        | 1   | 1          | ... | 1          |
| Controller parameters |     |            |     |            |
| <b>b2</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>a1</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>a2</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>sfra2</b>          | 31  | 30         | ... | 27         |
| <b>sfrb0</b>          | 31  | 30         | ... | 27         |
| <b>sfrb1</b>          | 31  | 30         | ... | 27         |
| <b>sfrb2</b>          | 31  | 30         | ... | 27         |
| <b>sfra1</b>          | 31  | 30         | ... | 27         |
| <b>b0</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b2</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a2</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfra2</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfrb0</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfrb2</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>     | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>        | 0   | 1073741824 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 7639  |
| Max CPU cycles  | 31129 |
| Avg CPU cycles  | 17599 |

**Verification: Biquad FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-25  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Filter block Biquad.

| Test results   |            |           |     |           |
|----------------|------------|-----------|-----|-----------|
| Time step      | 1          | 2         | ... | 73        |
| CPU cycles     | 243        | 243       | ... | 243       |
| Inputs         |            |           |     |           |
| In (DSP)       | -120706110 | -44469415 | ... | 999834674 |
| In             | -0.056     | -0.021    | ... | 0.466     |
| Parameters     |            |           |     |           |
| b0             | 0.2        |           |     |           |
| b1             | 0.1        |           |     |           |
| b2             | 0.3        |           |     |           |
| a0             | 1.1        |           |     |           |
| a1             | -0.7       |           |     |           |
| a2             | 0.8        |           |     |           |
| ts_fact        | 1          |           |     |           |
| Outputs        |            |           |     |           |
| Out            | -0.01      | -0.015    | ... | 0.257     |
| Exp. Out       | -0.01      | -0.015    | ... | 0.257     |
| Out (DSP)      | -21946566  | -33024628 | ... | 552726178 |
| Exp. Out (DSP) | -21946566  | -33024627 | ... | 552726179 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 243 |
| Max CPU cycles  | 243 |
| Avg CPU cycles  | 243 |

**Test case: Conversion test****OK**

Conversion test for Filter block Biquad.



| Test results          |     |            |     |            |
|-----------------------|-----|------------|-----|------------|
| Time step             | 1   | 2          | ... | 8          |
| Mask parameters       |     |            |     |            |
| <b>b0</b>             | 0   | 0.1        | ... | 10         |
| <b>b1</b>             | 0   | 0.1        | ... | 10         |
| <b>b2</b>             | 0   | 0.1        | ... | 10         |
| <b>a0</b>             | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>             | 0   | 0.1        | ... | 10         |
| <b>a2</b>             | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>        | 1   | 1          | ... | 1          |
| Controller parameters |     |            |     |            |
| <b>b2</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>a1</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>a2</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>sfra2</b>          | 31  | 30         | ... | 27         |
| <b>sfrb0</b>          | 31  | 30         | ... | 27         |
| <b>sfrb1</b>          | 31  | 30         | ... | 27         |
| <b>sfrb2</b>          | 31  | 30         | ... | 27         |
| <b>sfra1</b>          | 31  | 30         | ... | 27         |
| <b>b0</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b2</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a2</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfra2</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfrb0</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfrb2</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>     | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>        | 0   | 1073741824 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Biquad.

| Test results          |     |            |     |            |
|-----------------------|-----|------------|-----|------------|
| Time step             | 1   | 2          | ... | 8          |
| Mask parameters       |     |            |     |            |
| <b>b0</b>             | 0   | 0.1        | ... | 10         |
| <b>b1</b>             | 0   | 0.1        | ... | 10         |
| <b>b2</b>             | 0   | 0.1        | ... | 10         |
| <b>a0</b>             | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>             | 0   | 0.1        | ... | 10         |
| <b>a2</b>             | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>        | 1   | 1          | ... | 1          |
| Controller parameters |     |            |     |            |
| <b>b2</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>a1</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>a2</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>sfra2</b>          | 31  | 30         | ... | 27         |
| <b>sfrb0</b>          | 31  | 30         | ... | 27         |
| <b>sfrb1</b>          | 31  | 30         | ... | 27         |
| <b>sfrb2</b>          | 31  | 30         | ... | 27         |
| <b>sfra1</b>          | 31  | 30         | ... | 27         |
| <b>b0</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b2</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a2</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfra2</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfrb0</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfrb2</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>     | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>        | 0   | 1073741824 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 3217  |
| Max CPU cycles  | 12887 |
| Avg CPU cycles  | 7338  |

**Verification: Biquad FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-25  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Filter block Biquad.

| Test results   |            |           |     |           |
|----------------|------------|-----------|-----|-----------|
| Time step      | 1          | 2         | ... | 73        |
| CPU cycles     | 235        | 235       | ... | 235       |
| Inputs         |            |           |     |           |
| In (DSP)       | -120706110 | -44469415 | ... | 999834674 |
| In             | -0.056     | -0.021    | ... | 0.466     |
| Parameters     |            |           |     |           |
| b0             | 0.2        |           |     |           |
| b1             | 0.1        |           |     |           |
| b2             | 0.3        |           |     |           |
| a0             | 1.1        |           |     |           |
| a1             | -0.7       |           |     |           |
| a2             | 0.8        |           |     |           |
| ts_fact        | 1          |           |     |           |
| Outputs        |            |           |     |           |
| Out            | -0.01      | -0.015    | ... | 0.257     |
| Exp. Out       | -0.01      | -0.015    | ... | 0.257     |
| Out (DSP)      | -21946566  | -33024628 | ... | 552726178 |
| Exp. Out (DSP) | -21946566  | -33024627 | ... | 552726179 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 235 |
| Max CPU cycles  | 299 |
| Avg CPU cycles  | 235 |

**Test case: Conversion test****OK**

Conversion test for Filter block Biquad.

| Test results          |     |            |     |            |
|-----------------------|-----|------------|-----|------------|
| Time step             | 1   | 2          | ... | 8          |
| Mask parameters       |     |            |     |            |
| <b>b0</b>             | 0   | 0.1        | ... | 10         |
| <b>b1</b>             | 0   | 0.1        | ... | 10         |
| <b>b2</b>             | 0   | 0.1        | ... | 10         |
| <b>a0</b>             | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>             | 0   | 0.1        | ... | 10         |
| <b>a2</b>             | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>        | 1   | 1          | ... | 1          |
| Controller parameters |     |            |     |            |
| <b>b2</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>a1</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>a2</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>sfra2</b>          | 31  | 30         | ... | 27         |
| <b>sfrb0</b>          | 31  | 30         | ... | 27         |
| <b>sfrb1</b>          | 31  | 30         | ... | 27         |
| <b>sfrb2</b>          | 31  | 30         | ... | 27         |
| <b>sfra1</b>          | 31  | 30         | ... | 27         |
| <b>b0</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b2</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a2</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfra2</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfrb0</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfrb2</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>     | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>        | 0   | 1073741824 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Biquad.

| Test results          |     |            |     |            |
|-----------------------|-----|------------|-----|------------|
| Time step             | 1   | 2          | ... | 8          |
| Mask parameters       |     |            |     |            |
| <b>b0</b>             | 0   | 0.1        | ... | 10         |
| <b>b1</b>             | 0   | 0.1        | ... | 10         |
| <b>b2</b>             | 0   | 0.1        | ... | 10         |
| <b>a0</b>             | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>             | 0   | 0.1        | ... | 10         |
| <b>a2</b>             | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>        | 1   | 1          | ... | 1          |
| Controller parameters |     |            |     |            |
| <b>b2</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>a1</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>a2</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>sfra2</b>          | 31  | 30         | ... | 27         |
| <b>sfrb0</b>          | 31  | 30         | ... | 27         |
| <b>sfrb1</b>          | 31  | 30         | ... | 27         |
| <b>sfrb2</b>          | 31  | 30         | ... | 27         |
| <b>sfra1</b>          | 31  | 30         | ... | 27         |
| <b>b0</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b2</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a2</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfra2</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfrb0</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfrb2</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>     | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>        | 0   | 1073741824 | ... | 1342177280 |



| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 4225 |
| Max CPU cycles  | 8478 |
| Avg CPU cycles  | 6000 |

**Verification: Biquad FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-25  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Filter block Biquad.

| Test results   |            |           |     |           |
|----------------|------------|-----------|-----|-----------|
| Time step      | 1          | 2         | ... | 73        |
| CPU cycles     | 699        | 637       | ... | 633       |
| Inputs         |            |           |     |           |
| In (DSP)       | -120706110 | -44469415 | ... | 999834674 |
| In             | -0.056     | -0.021    | ... | 0.466     |
| Parameters     |            |           |     |           |
| b0             | 0.2        |           |     |           |
| b1             | 0.1        |           |     |           |
| b2             | 0.3        |           |     |           |
| a0             | 1.1        |           |     |           |
| a1             | -0.7       |           |     |           |
| a2             | 0.8        |           |     |           |
| ts_fact        | 1          |           |     |           |
| Outputs        |            |           |     |           |
| Out            | -0.01      | -0.015    | ... | 0.257     |
| Exp. Out       | -0.01      | -0.015    | ... | 0.257     |
| Out (DSP)      | -21946566  | -33024628 | ... | 552726178 |
| Exp. Out (DSP) | -21946566  | -33024627 | ... | 552726179 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 633 |
| Max CPU cycles  | 699 |
| Avg CPU cycles  | 636 |

**Test case: Conversion test****OK**

Conversion test for Filter block Biquad.

| Test results          |     |            |     |            |
|-----------------------|-----|------------|-----|------------|
| Time step             | 1   | 2          | ... | 8          |
| Mask parameters       |     |            |     |            |
| <b>b0</b>             | 0   | 0.1        | ... | 10         |
| <b>b1</b>             | 0   | 0.1        | ... | 10         |
| <b>b2</b>             | 0   | 0.1        | ... | 10         |
| <b>a0</b>             | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>             | 0   | 0.1        | ... | 10         |
| <b>a2</b>             | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>        | 1   | 1          | ... | 1          |
| Controller parameters |     |            |     |            |
| <b>b2</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>a1</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>a2</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>sfra2</b>          | 31  | 30         | ... | 27         |
| <b>sfrb0</b>          | 31  | 30         | ... | 27         |
| <b>sfrb1</b>          | 31  | 30         | ... | 27         |
| <b>sfrb2</b>          | 31  | 30         | ... | 27         |
| <b>sfra1</b>          | 31  | 30         | ... | 27         |
| <b>b0</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b2</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a2</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfra2</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfrb0</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfrb2</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>     | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>        | 0   | 1073741824 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Biquad.

| Test results                 |     |            |     |            |
|------------------------------|-----|------------|-----|------------|
| <b>Time step</b>             | 1   | 2          | ... | 8          |
| <i>Mask parameters</i>       |     |            |     |            |
| <b>b0</b>                    | 0   | 0.1        | ... | 10         |
| <b>b1</b>                    | 0   | 0.1        | ... | 10         |
| <b>b2</b>                    | 0   | 0.1        | ... | 10         |
| <b>a0</b>                    | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>                    | 0   | 0.1        | ... | 10         |
| <b>a2</b>                    | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>               | 1   | 1          | ... | 1          |
| <i>Controller parameters</i> |     |            |     |            |
| <b>b2</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>a1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>a2</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>sfra2</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb0</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb1</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb2</b>                 | 31  | 30         | ... | 27         |
| <b>sfra1</b>                 | 31  | 30         | ... | 27         |
| <b>b0</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b2</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a2</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfra2</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb0</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb2</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>               | 0   | 1073741824 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 13455 |
| Max CPU cycles  | 31085 |
| Avg CPU cycles  | 23389 |

**Verification: Biquad FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-25  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Filter block Biquad.

| Test results   |            |           |     |           |
|----------------|------------|-----------|-----|-----------|
| Time step      | 1          | 2         | ... | 73        |
| CPU cycles     | 208        | 208       | ... | 208       |
| Inputs         |            |           |     |           |
| In (DSP)       | -120706110 | -44469415 | ... | 999834674 |
| In             | -0.056     | -0.021    | ... | 0.466     |
| Parameters     |            |           |     |           |
| b0             | 0.2        |           |     |           |
| b1             | 0.1        |           |     |           |
| b2             | 0.3        |           |     |           |
| a0             | 1.1        |           |     |           |
| a1             | -0.7       |           |     |           |
| a2             | 0.8        |           |     |           |
| ts_fact        | 1          |           |     |           |
| Outputs        |            |           |     |           |
| Out            | -0.01      | -0.015    | ... | 0.257     |
| Exp. Out       | -0.01      | -0.015    | ... | 0.257     |
| Out (DSP)      | -21946566  | -33024628 | ... | 552726178 |
| Exp. Out (DSP) | -21946566  | -33024627 | ... | 552726179 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 208 |
| Max CPU cycles  | 208 |
| Avg CPU cycles  | 208 |

**Test case: Conversion test****OK**

Conversion test for Filter block Biquad.

| Test results          |     |            |     |            |
|-----------------------|-----|------------|-----|------------|
| Time step             | 1   | 2          | ... | 8          |
| Mask parameters       |     |            |     |            |
| <b>b0</b>             | 0   | 0.1        | ... | 10         |
| <b>b1</b>             | 0   | 0.1        | ... | 10         |
| <b>b2</b>             | 0   | 0.1        | ... | 10         |
| <b>a0</b>             | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>             | 0   | 0.1        | ... | 10         |
| <b>a2</b>             | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>        | 1   | 1          | ... | 1          |
| Controller parameters |     |            |     |            |
| <b>b2</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>a1</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>a2</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>sfra2</b>          | 31  | 30         | ... | 27         |
| <b>sfrb0</b>          | 31  | 30         | ... | 27         |
| <b>sfrb1</b>          | 31  | 30         | ... | 27         |
| <b>sfrb2</b>          | 31  | 30         | ... | 27         |
| <b>sfra1</b>          | 31  | 30         | ... | 27         |
| <b>b0</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b2</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a2</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfra2</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfrb0</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfrb2</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>     | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>        | 0   | 1073741824 | ... | 1342177280 |



| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Biquad.

| Test results                 |     |            |     |            |
|------------------------------|-----|------------|-----|------------|
| <b>Time step</b>             | 1   | 2          | ... | 8          |
| <i>Mask parameters</i>       |     |            |     |            |
| <b>b0</b>                    | 0   | 0.1        | ... | 10         |
| <b>b1</b>                    | 0   | 0.1        | ... | 10         |
| <b>b2</b>                    | 0   | 0.1        | ... | 10         |
| <b>a0</b>                    | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>                    | 0   | 0.1        | ... | 10         |
| <b>a2</b>                    | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>               | 1   | 1          | ... | 1          |
| <i>Controller parameters</i> |     |            |     |            |
| <b>b2</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>a1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>a2</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>sfra2</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb0</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb1</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb2</b>                 | 31  | 30         | ... | 27         |
| <b>sfra1</b>                 | 31  | 30         | ... | 27         |
| <b>b0</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b2</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a2</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfra2</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb0</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb2</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>               | 0   | 1073741824 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 6035  |
| Max CPU cycles  | 12729 |
| Avg CPU cycles  | 9517  |

**Verification: Biquad FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-25  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Filter block Biquad.

| Test results   |            |           |     |           |
|----------------|------------|-----------|-----|-----------|
| Time step      | 1          | 2         | ... | 73        |
| CPU cycles     | 2239       | 2247      | ... | 2232      |
| Inputs         |            |           |     |           |
| In (DSP)       | -120706110 | -44469415 | ... | 999834674 |
| In             | -0.056     | -0.021    | ... | 0.466     |
| Parameters     |            |           |     |           |
| b0             | 0.2        |           |     |           |
| b1             | 0.1        |           |     |           |
| b2             | 0.3        |           |     |           |
| a0             | 1.1        |           |     |           |
| a1             | -0.7       |           |     |           |
| a2             | 0.8        |           |     |           |
| ts_fact        | 1          |           |     |           |
| Outputs        |            |           |     |           |
| Out            | -0.01      | -0.015    | ... | 0.257     |
| Exp. Out       | -0.01      | -0.015    | ... | 0.257     |
| Out (DSP)      | -21946566  | -33024628 | ... | 552726178 |
| Exp. Out (DSP) | -21946566  | -33024627 | ... | 552726179 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2232 |
| Max CPU cycles  | 2261 |
| Avg CPU cycles  | 2245 |

**Test case: Conversion test****OK**

Conversion test for Filter block Biquad.

| Test results                 |     |            |     |            |
|------------------------------|-----|------------|-----|------------|
| <b>Time step</b>             | 1   | 2          | ... | 8          |
| <i>Mask parameters</i>       |     |            |     |            |
| <b>b0</b>                    | 0   | 0.1        | ... | 10         |
| <b>b1</b>                    | 0   | 0.1        | ... | 10         |
| <b>b2</b>                    | 0   | 0.1        | ... | 10         |
| <b>a0</b>                    | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>                    | 0   | 0.1        | ... | 10         |
| <b>a2</b>                    | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>               | 1   | 1          | ... | 1          |
| <i>Controller parameters</i> |     |            |     |            |
| <b>b2</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>a1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>a2</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>sfra2</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb0</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb1</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb2</b>                 | 31  | 30         | ... | 27         |
| <b>sfra1</b>                 | 31  | 30         | ... | 27         |
| <b>b0</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b2</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a2</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfra2</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb0</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb2</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>               | 0   | 1073741824 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Biquad.

| Test results                 |     |            |     |            |
|------------------------------|-----|------------|-----|------------|
| <b>Time step</b>             | 1   | 2          | ... | 8          |
| <i>Mask parameters</i>       |     |            |     |            |
| <b>b0</b>                    | 0   | 0.1        | ... | 10         |
| <b>b1</b>                    | 0   | 0.1        | ... | 10         |
| <b>b2</b>                    | 0   | 0.1        | ... | 10         |
| <b>a0</b>                    | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>                    | 0   | 0.1        | ... | 10         |
| <b>a2</b>                    | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>               | 1   | 1          | ... | 1          |
| <i>Controller parameters</i> |     |            |     |            |
| <b>b2</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>a1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>a2</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>sfra2</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb0</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb1</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb2</b>                 | 31  | 30         | ... | 27         |
| <b>sfra1</b>                 | 31  | 30         | ... | 27         |
| <b>b0</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b2</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a2</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfra2</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb0</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb2</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>               | 0   | 1073741824 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 15859 |
| Max CPU cycles  | 60490 |
| Avg CPU cycles  | 39307 |



**Verification: Biquad FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-25  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Filter block Biquad.

| Test results   |            |           |     |           |
|----------------|------------|-----------|-----|-----------|
| Time step      | 1          | 2         | ... | 73        |
| CPU cycles     | 265        | 224       | ... | 224       |
| Inputs         |            |           |     |           |
| In (DSP)       | -120706110 | -44469415 | ... | 999834674 |
| In             | -0.056     | -0.021    | ... | 0.466     |
| Parameters     |            |           |     |           |
| b0             | 0.2        |           |     |           |
| b1             | 0.1        |           |     |           |
| b2             | 0.3        |           |     |           |
| a0             | 1.1        |           |     |           |
| a1             | -0.7       |           |     |           |
| a2             | 0.8        |           |     |           |
| ts_fact        | 1          |           |     |           |
| Outputs        |            |           |     |           |
| Out            | -0.01      | -0.015    | ... | 0.257     |
| Exp. Out       | -0.01      | -0.015    | ... | 0.257     |
| Out (DSP)      | -21946566  | -33024628 | ... | 552726178 |
| Exp. Out (DSP) | -21946566  | -33024627 | ... | 552726179 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 224 |
| Max CPU cycles  | 265 |
| Avg CPU cycles  | 224 |

**Test case: Conversion test****OK**

Conversion test for Filter block Biquad.

| Test results                 |     |            |     |            |
|------------------------------|-----|------------|-----|------------|
| <b>Time step</b>             | 1   | 2          | ... | 8          |
| <i>Mask parameters</i>       |     |            |     |            |
| <b>b0</b>                    | 0   | 0.1        | ... | 10         |
| <b>b1</b>                    | 0   | 0.1        | ... | 10         |
| <b>b2</b>                    | 0   | 0.1        | ... | 10         |
| <b>a0</b>                    | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>                    | 0   | 0.1        | ... | 10         |
| <b>a2</b>                    | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>               | 1   | 1          | ... | 1          |
| <i>Controller parameters</i> |     |            |     |            |
| <b>b2</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>a1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>a2</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>sfra2</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb0</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb1</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb2</b>                 | 31  | 30         | ... | 27         |
| <b>sfra1</b>                 | 31  | 30         | ... | 27         |
| <b>b0</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b2</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a2</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfra2</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb0</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb2</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>               | 0   | 1073741824 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Biquad.

| Test results          |     |            |     |            |
|-----------------------|-----|------------|-----|------------|
| Time step             | 1   | 2          | ... | 8          |
| Mask parameters       |     |            |     |            |
| <b>b0</b>             | 0   | 0.1        | ... | 10         |
| <b>b1</b>             | 0   | 0.1        | ... | 10         |
| <b>b2</b>             | 0   | 0.1        | ... | 10         |
| <b>a0</b>             | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>             | 0   | 0.1        | ... | 10         |
| <b>a2</b>             | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>        | 1   | 1          | ... | 1          |
| Controller parameters |     |            |     |            |
| <b>b2</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>a1</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>a2</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>sfra2</b>          | 31  | 30         | ... | 27         |
| <b>sfrb0</b>          | 31  | 30         | ... | 27         |
| <b>sfrb1</b>          | 31  | 30         | ... | 27         |
| <b>sfrb2</b>          | 31  | 30         | ... | 27         |
| <b>sfra1</b>          | 31  | 30         | ... | 27         |
| <b>b0</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>             | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b2</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a2</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfra2</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfrb0</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfrb2</b>     | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>     | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>        | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>        | 0   | 1073741824 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3975 |
| Max CPU cycles  | 8100 |
| Avg CPU cycles  | 5727 |

**Verification: Biquad FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-25  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Filter block Biquad.

| Test results   |            |           |     |           |
|----------------|------------|-----------|-----|-----------|
| Time step      | 1          | 2         | ... | 73        |
| CPU cycles     | 247        | 247       | ... | 247       |
| Inputs         |            |           |     |           |
| In (DSP)       | -120706110 | -44469415 | ... | 999834674 |
| In             | -0.056     | -0.021    | ... | 0.466     |
| Parameters     |            |           |     |           |
| b0             | 0.2        |           |     |           |
| b1             | 0.1        |           |     |           |
| b2             | 0.3        |           |     |           |
| a0             | 1.1        |           |     |           |
| a1             | -0.7       |           |     |           |
| a2             | 0.8        |           |     |           |
| ts_fact        | 1          |           |     |           |
| Outputs        |            |           |     |           |
| Out            | -0.01      | -0.015    | ... | 0.257     |
| Exp. Out       | -0.01      | -0.015    | ... | 0.257     |
| Out (DSP)      | -21946566  | -33024628 | ... | 552726178 |
| Exp. Out (DSP) | -21946566  | -33024627 | ... | 552726179 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 247 |
| Max CPU cycles  | 247 |
| Avg CPU cycles  | 247 |

**Test case: Conversion test****OK**

Conversion test for Filter block Biquad.

| Test results                 |     |            |     |            |
|------------------------------|-----|------------|-----|------------|
| <b>Time step</b>             | 1   | 2          | ... | 8          |
| <i>Mask parameters</i>       |     |            |     |            |
| <b>b0</b>                    | 0   | 0.1        | ... | 10         |
| <b>b1</b>                    | 0   | 0.1        | ... | 10         |
| <b>b2</b>                    | 0   | 0.1        | ... | 10         |
| <b>a0</b>                    | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>                    | 0   | 0.1        | ... | 10         |
| <b>a2</b>                    | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>               | 1   | 1          | ... | 1          |
| <i>Controller parameters</i> |     |            |     |            |
| <b>b2</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>a1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>a2</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>sfra2</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb0</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb1</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb2</b>                 | 31  | 30         | ... | 27         |
| <b>sfra1</b>                 | 31  | 30         | ... | 27         |
| <b>b0</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b2</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a2</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfra2</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb0</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb2</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>               | 0   | 1073741824 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Biquad.



| Test results                 |     |            |     |            |
|------------------------------|-----|------------|-----|------------|
| <b>Time step</b>             | 1   | 2          | ... | 8          |
| <i>Mask parameters</i>       |     |            |     |            |
| <b>b0</b>                    | 0   | 0.1        | ... | 10         |
| <b>b1</b>                    | 0   | 0.1        | ... | 10         |
| <b>b2</b>                    | 0   | 0.1        | ... | 10         |
| <b>a0</b>                    | 0.1 | 0.1        | ... | 1          |
| <b>a1</b>                    | 0   | 0.1        | ... | 10         |
| <b>a2</b>                    | 0   | 0.1        | ... | 10         |
| <b>ts_fact</b>               | 1   | 1          | ... | 1          |
| <i>Controller parameters</i> |     |            |     |            |
| <b>b2</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>a1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>a2</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>sfra2</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb0</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb1</b>                 | 31  | 30         | ... | 27         |
| <b>sfrb2</b>                 | 31  | 30         | ... | 27         |
| <b>sfra1</b>                 | 31  | 30         | ... | 27         |
| <b>b0</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>b1</b>                    | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b2</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a1</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. a2</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. sfra2</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb0</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfrb2</b>            | 31  | 30         | ... | 27         |
| <b>Exp. sfra1</b>            | 31  | 30         | ... | 27         |
| <b>Exp. b0</b>               | 0   | 1073741824 | ... | 1342177280 |
| <b>Exp. b1</b>               | 0   | 1073741824 | ... | 1342177280 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 5424  |
| Max CPU cycles  | 22844 |
| Avg CPU cycles  | 12913 |

**Verification: Biquad Float32 CPU TMS320F28335**

**Date of Test** 2026-06-25  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Filter block Biquad.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 73    |
| CPU cycles     | 93     | 93     | ... | 93    |
| Inputs         |        |        |     |       |
| In (DSP)       | -0.056 | -0.021 | ... | 0.466 |
| In             | -0.056 | -0.021 | ... | 0.466 |
| Parameters     |        |        |     |       |
| b0             | 0.2    |        |     |       |
| b1             | 0.1    |        |     |       |
| b2             | 0.3    |        |     |       |
| a0             | 1.1    |        |     |       |
| a1             | -0.7   |        |     |       |
| a2             | 0.8    |        |     |       |
| ts_fact        | 1      |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -0.01  | -0.015 | ... | 0.257 |
| Exp. Out       | -0.01  | -0.015 | ... | 0.257 |
| Out (DSP)      | -0.01  | -0.015 | ... | 0.257 |
| Exp. Out (DSP) | -0.01  | -0.015 | ... | 0.257 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 9,3132e-08$ ( $\pm 200$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 93 |
| Max CPU cycles  | 93 |
| Avg CPU cycles  | 93 |

**Test case: Conversion test****OK**

Conversion test for Filter block Biquad.

| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| Time step                    | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>b2</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a2</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>b2</b>                    | 0   | 1   | ... | 10 |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>a2</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. b2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b2  | $\pm 0,0000e+00$ |
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance a2  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Biquad.

| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| <b>Time step</b>             | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>b2</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a2</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>b2</b>                    | 0   | 1   | ... | 10 |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>a2</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. b2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b2  | $\pm 0,0000e+00$ |
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance a2  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 3955  |
| Max CPU cycles  | 21465 |
| Avg CPU cycles  | 9005  |

**Verification: Biquad Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-25  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Filter block Biquad.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 73    |
| CPU cycles     | 61     | 61     | ... | 61    |
| Inputs         |        |        |     |       |
| In (DSP)       | -0.056 | -0.021 | ... | 0.466 |
| In             | -0.056 | -0.021 | ... | 0.466 |
| Parameters     |        |        |     |       |
| b0             | 0.2    |        |     |       |
| b1             | 0.1    |        |     |       |
| b2             | 0.3    |        |     |       |
| a0             | 1.1    |        |     |       |
| a1             | -0.7   |        |     |       |
| a2             | 0.8    |        |     |       |
| ts_fact        | 1      |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -0.01  | -0.015 | ... | 0.257 |
| Exp. Out       | -0.01  | -0.015 | ... | 0.257 |
| Out (DSP)      | -0.01  | -0.015 | ... | 0.257 |
| Exp. Out (DSP) | -0.01  | -0.015 | ... | 0.257 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 9,3132e-08$ ( $\pm 200$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 61 |
| Max CPU cycles  | 61 |
| Avg CPU cycles  | 61 |

**Test case: Conversion test****OK**

Conversion test for Filter block Biquad.

| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| <b>Time step</b>             | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>b2</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a2</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>b2</b>                    | 0   | 1   | ... | 10 |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>a2</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. b2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b2  | $\pm 0,0000e+00$ |
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance a2  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Biquad.

| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| Time step                    | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>b2</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a2</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>b2</b>                    | 0   | 1   | ... | 10 |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>a2</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. b2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b2  | $\pm 0,0000e+00$ |
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance a2  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1789 |
| Max CPU cycles  | 9019 |
| Avg CPU cycles  | 3874 |



**Verification: Biquad Float32 CPU STM32G474RE**

**Date of Test** 2026-06-25  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Filter block Biquad.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 73    |
| CPU cycles     | 103    | 103    | ... | 103   |
| Inputs         |        |        |     |       |
| In (DSP)       | -0.056 | -0.021 | ... | 0.466 |
| In             | -0.056 | -0.021 | ... | 0.466 |
| Parameters     |        |        |     |       |
| b0             | 0.2    |        |     |       |
| b1             | 0.1    |        |     |       |
| b2             | 0.3    |        |     |       |
| a0             | 1.1    |        |     |       |
| a1             | -0.7   |        |     |       |
| a2             | 0.8    |        |     |       |
| ts_fact        | 1      |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -0.01  | -0.015 | ... | 0.257 |
| Exp. Out       | -0.01  | -0.015 | ... | 0.257 |
| Out (DSP)      | -0.01  | -0.015 | ... | 0.257 |
| Exp. Out (DSP) | -0.01  | -0.015 | ... | 0.257 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 9,3132e-08$ ( $\pm 200$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 103 |
| Max CPU cycles  | 103 |
| Avg CPU cycles  | 103 |

**Test case: Conversion test****OK**

Conversion test for Filter block Biquad.

| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| Time step                    | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>b2</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a2</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>b2</b>                    | 0   | 1   | ... | 10 |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>a2</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. b2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b2  | $\pm 0,0000e+00$ |
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance a2  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Biquad.

| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| <b>Time step</b>             | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>b2</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a2</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>b2</b>                    | 0   | 1   | ... | 10 |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>a2</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. b2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b2  | $\pm 0,0000e+00$ |
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance a2  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1482 |
| Max CPU cycles  | 4479 |
| Avg CPU cycles  | 2246 |

**Verification: Biquad Float32 CPU STM32F072RB**

**Date of Test** 2026-06-25  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Filter block Biquad.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 73    |
| CPU cycles     | 1092   | 1300   | ... | 1589  |
| Inputs         |        |        |     |       |
| In (DSP)       | -0.056 | -0.021 | ... | 0.466 |
| In             | -0.056 | -0.021 | ... | 0.466 |
| Parameters     |        |        |     |       |
| b0             | 0.2    |        |     |       |
| b1             | 0.1    |        |     |       |
| b2             | 0.3    |        |     |       |
| a0             | 1.1    |        |     |       |
| a1             | -0.7   |        |     |       |
| a2             | 0.8    |        |     |       |
| ts_fact        | 1      |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -0.01  | -0.015 | ... | 0.257 |
| Exp. Out       | -0.01  | -0.015 | ... | 0.257 |
| Out (DSP)      | -0.01  | -0.015 | ... | 0.257 |
| Exp. Out (DSP) | -0.01  | -0.015 | ... | 0.257 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 9,3132e-08$ ( $\pm 200$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1092 |
| Max CPU cycles  | 1635 |
| Avg CPU cycles  | 1530 |

**Test case: Conversion test****OK**

Conversion test for Filter block Biquad.

| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| <b>Time step</b>             | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>b2</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a2</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>b2</b>                    | 0   | 1   | ... | 10 |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>a2</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. b2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b2  | $\pm 0,0000e+00$ |
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance a2  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Biquad.

| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| <b>Time step</b>             | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>b2</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a2</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>b2</b>                    | 0   | 1   | ... | 10 |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>a2</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. b2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b2  | $\pm 0,0000e+00$ |
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance a2  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3401 |
| Max CPU cycles  | 7281 |
| Avg CPU cycles  | 5669 |

**Verification: Biquad Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-25  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Filter block Biquad.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 73    |
| CPU cycles     | 383    | 477    | ... | 590   |
| Inputs         |        |        |     |       |
| In (DSP)       | -0.056 | -0.021 | ... | 0.466 |
| In             | -0.056 | -0.021 | ... | 0.466 |
| Parameters     |        |        |     |       |
| b0             | 0.2    |        |     |       |
| b1             | 0.1    |        |     |       |
| b2             | 0.3    |        |     |       |
| a0             | 1.1    |        |     |       |
| a1             | -0.7   |        |     |       |
| a2             | 0.8    |        |     |       |
| ts_fact        | 1      |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -0.01  | -0.015 | ... | 0.257 |
| Exp. Out       | -0.01  | -0.015 | ... | 0.257 |
| Out (DSP)      | -0.01  | -0.015 | ... | 0.257 |
| Exp. Out (DSP) | -0.01  | -0.015 | ... | 0.257 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 9,3132e-08$ ( $\pm 200$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 383 |
| Max CPU cycles  | 590 |
| Avg CPU cycles  | 573 |

**Test case: Conversion test****OK**

Conversion test for Filter block Biquad.

| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| <b>Time step</b>             | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>b2</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a2</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>b2</b>                    | 0   | 1   | ... | 10 |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>a2</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. b2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b2  | $\pm 0,0000e+00$ |
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance a2  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Biquad.



| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| <b>Time step</b>             | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>b2</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a2</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>b2</b>                    | 0   | 1   | ... | 10 |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>a2</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. b2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b2  | $\pm 0,0000e+00$ |
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance a2  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1279 |
| Max CPU cycles  | 2494 |
| Avg CPU cycles  | 2104 |

**Verification: Biquad Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-25  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Filter block Biquad.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 73    |
| CPU cycles     | 1200   | 1341   | ... | 1568  |
| Inputs         |        |        |     |       |
| In (DSP)       | -0.056 | -0.021 | ... | 0.466 |
| In             | -0.056 | -0.021 | ... | 0.466 |
| Parameters     |        |        |     |       |
| b0             | 0.2    |        |     |       |
| b1             | 0.1    |        |     |       |
| b2             | 0.3    |        |     |       |
| a0             | 1.1    |        |     |       |
| a1             | -0.7   |        |     |       |
| a2             | 0.8    |        |     |       |
| ts_fact        | 1      |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -0.01  | -0.015 | ... | 0.257 |
| Exp. Out       | -0.01  | -0.015 | ... | 0.257 |
| Out (DSP)      | -0.01  | -0.015 | ... | 0.257 |
| Exp. Out (DSP) | -0.01  | -0.015 | ... | 0.257 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 9,3132e-08$ ( $\pm 200$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1200 |
| Max CPU cycles  | 1687 |
| Avg CPU cycles  | 1566 |

**Test case: Conversion test****OK**

Conversion test for Filter block Biquad.

| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| <b>Time step</b>             | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>b2</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a2</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>b2</b>                    | 0   | 1   | ... | 10 |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>a2</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. b2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b2  | $\pm 0,0000e+00$ |
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance a2  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Biquad.

| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| Time step                    | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>b2</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a2</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>b2</b>                    | 0   | 1   | ... | 10 |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>a2</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. b2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b2  | $\pm 0,0000e+00$ |
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance a2  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 3904  |
| Max CPU cycles  | 11900 |
| Avg CPU cycles  | 10800 |

**Verification: Biquad Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-25  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Filter block Biquad.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 73    |
| CPU cycles     | 115    | 99     | ... | 99    |
| Inputs         |        |        |     |       |
| In (DSP)       | -0.056 | -0.021 | ... | 0.466 |
| In             | -0.056 | -0.021 | ... | 0.466 |
| Parameters     |        |        |     |       |
| b0             | 0.2    |        |     |       |
| b1             | 0.1    |        |     |       |
| b2             | 0.3    |        |     |       |
| a0             | 1.1    |        |     |       |
| a1             | -0.7   |        |     |       |
| a2             | 0.8    |        |     |       |
| ts_fact        | 1      |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -0.01  | -0.015 | ... | 0.257 |
| Exp. Out       | -0.01  | -0.015 | ... | 0.257 |
| Out (DSP)      | -0.01  | -0.015 | ... | 0.257 |
| Exp. Out (DSP) | -0.01  | -0.015 | ... | 0.257 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 9,3132e-08$ ( $\pm 200$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 99  |
| Max CPU cycles  | 115 |
| Avg CPU cycles  | 99  |

**Test case: Conversion test****OK**

Conversion test for Filter block Biquad.

| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| <b>Time step</b>             | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>b2</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a2</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>b2</b>                    | 0   | 1   | ... | 10 |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>a2</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. b2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b2  | $\pm 0,0000e+00$ |
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance a2  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Biquad.

| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| <b>Time step</b>             | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>b2</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a2</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>b2</b>                    | 0   | 1   | ... | 10 |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>a2</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. b2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b2  | $\pm 0,0000e+00$ |
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance a2  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1407 |
| Max CPU cycles  | 4356 |
| Avg CPU cycles  | 2173 |

**Verification: Biquad Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-25  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Filter block Biquad.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 73    |
| CPU cycles     | 86     | 86     | ... | 86    |
| Inputs         |        |        |     |       |
| In (DSP)       | -0.056 | -0.021 | ... | 0.466 |
| In             | -0.056 | -0.021 | ... | 0.466 |
| Parameters     |        |        |     |       |
| b0             | 0.2    |        |     |       |
| b1             | 0.1    |        |     |       |
| b2             | 0.3    |        |     |       |
| a0             | 1.1    |        |     |       |
| a1             | -0.7   |        |     |       |
| a2             | 0.8    |        |     |       |
| ts_fact        | 1      |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -0.01  | -0.015 | ... | 0.257 |
| Exp. Out       | -0.01  | -0.015 | ... | 0.257 |
| Out (DSP)      | -0.01  | -0.015 | ... | 0.257 |
| Exp. Out (DSP) | -0.01  | -0.015 | ... | 0.257 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 9,3132e-08$ ( $\pm 200$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 86 |
| Max CPU cycles  | 86 |
| Avg CPU cycles  | 86 |

**Test case: Conversion test****OK**

Conversion test for Filter block Biquad.



| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| <b>Time step</b>             | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>b2</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a2</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>b2</b>                    | 0   | 1   | ... | 10 |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>a2</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. b2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b2  | $\pm 0,0000e+00$ |
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance a2  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block Biquad.


| Test results                 |     |     |     |    |
|------------------------------|-----|-----|-----|----|
| <b>Time step</b>             | 1   | 2   | ... | 8  |
| <i>Mask parameters</i>       |     |     |     |    |
| <b>b0</b>                    | 0   | 0.1 | ... | 10 |
| <b>b1</b>                    | 0   | 0.1 | ... | 10 |
| <b>b2</b>                    | 0   | 0.1 | ... | 10 |
| <b>a0</b>                    | 0.1 | 0.1 | ... | 1  |
| <b>a1</b>                    | 0   | 0.1 | ... | 10 |
| <b>a2</b>                    | 0   | 0.1 | ... | 10 |
| <b>ts_fact</b>               | 1   | 1   | ... | 1  |
| <i>Controller parameters</i> |     |     |     |    |
| <b>b2</b>                    | 0   | 1   | ... | 10 |
| <b>a1</b>                    | 0   | 1   | ... | 10 |
| <b>a2</b>                    | 0   | 1   | ... | 10 |
| <b>b0</b>                    | 0   | 1   | ... | 10 |
| <b>b1</b>                    | 0   | 1   | ... | 10 |
| <b>Exp. b2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a1</b>               | 0   | 1   | ... | 10 |
| <b>Exp. a2</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b0</b>               | 0   | 1   | ... | 10 |
| <b>Exp. b1</b>               | 0   | 1   | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance b2  | $\pm 0,0000e+00$ |
| Tolerance a1  | $\pm 0,0000e+00$ |
| Tolerance a2  | $\pm 0,0000e+00$ |
| Tolerance b0  | $\pm 0,0000e+00$ |
| Tolerance b1  | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 2779  |
| Max CPU cycles  | 15619 |
| Avg CPU cycles  | 6508  |

## Block: FundFreq

---



Calculation of the first harmonic (fundamental frequency) of the input signal.

| Inports |              |
|---------|--------------|
| In      | Input signal |
| phi     | Angle signal |

| Outports |                |
|----------|----------------|
| Out      | First harmonic |

| Mask Parameters |    |                                                                 |
|-----------------|----|-----------------------------------------------------------------|
| Name            | ID | Description                                                     |
| ts_fact         | 1  | Multiplication factor of base sampling time (in integer format) |

### Implementations:

- FiP16** 16 Bit Fixed Point Implementation
- FiP32** 32 Bit Fixed Point Implementation
- Float32** 32 Bit Floating Point Implementation
- Float64** 64 Bit Floating Point Implementation

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |
| phi               | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

---

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |
| phi               | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |
| phi               | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |
| phi               | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: FundFreq FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-25  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Filter block FundFreq.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 111   |
| CPU cycles     | 201    | 202    | 202    | 202    | ... | 202   |
| Inputs         |        |        |        |        |     |       |
| In (DSP)       | 6554   | -705   | -6595  | -10422 | ... | 13812 |
| phi (DSP)      | -32768 | -30997 | -29226 | -27454 | ... | 30997 |
| In             | 0.2    | -0.022 | -0.201 | -0.318 | ... | 0.422 |
| phi            | -1     | -0.946 | -0.892 | -0.838 | ... | 0.946 |
| Parameters     |        |        |        |        |     |       |
| ts_fact        | 1      |        |        |        |     |       |
| Outputs        |        |        |        |        |     |       |
| Out            | 0      | 0      | 0      | 0      | ... | 0.135 |
| Exp. Out       | 0      | 0      | 0      | 0      | ... | 0.135 |
| Out (DSP)      | 0      | 0      | 0      | 0      | ... | 4428  |
| Exp. Out (DSP) | 0      | 0      | 0      | 0      | ... | 4430  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 201 |
| Max CPU cycles  | 372 |
| Avg CPU cycles  | 205 |

**Verification: FundFreq FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-25  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Filter block FundFreq.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 111   |
| CPU cycles     | 129    | 129    | 129    | 129    | ... | 129   |
| Inputs         |        |        |        |        |     |       |
| In (DSP)       | 6554   | -705   | -6595  | -10422 | ... | 13812 |
| phi (DSP)      | -32768 | -30997 | -29226 | -27454 | ... | 30997 |
| In             | 0.2    | -0.022 | -0.201 | -0.318 | ... | 0.422 |
| phi            | -1     | -0.946 | -0.892 | -0.838 | ... | 0.946 |
| Parameters     |        |        |        |        |     |       |
| ts_fact        | 1      |        |        |        |     |       |
| Outputs        |        |        |        |        |     |       |
| Out            | 0      | 0      | 0      | 0      | ... | 0.135 |
| Exp. Out       | 0      | 0      | 0      | 0      | ... | 0.135 |
| Out (DSP)      | 0      | 0      | 0      | 0      | ... | 4428  |
| Exp. Out (DSP) | 0      | 0      | 0      | 0      | ... | 4430  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 129 |
| Max CPU cycles  | 157 |
| Avg CPU cycles  | 129 |

**Verification: FundFreq FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-25  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Filter block FundFreq.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 111   |
| CPU cycles     | 225    | 230    | 230    | 225    | ... | 230   |
| Inputs         |        |        |        |        |     |       |
| In (DSP)       | 6554   | -705   | -6595  | -10422 | ... | 13812 |
| phi (DSP)      | -32768 | -30997 | -29226 | -27454 | ... | 30997 |
| In             | 0.2    | -0.022 | -0.201 | -0.318 | ... | 0.422 |
| phi            | -1     | -0.946 | -0.892 | -0.838 | ... | 0.946 |
| Parameters     |        |        |        |        |     |       |
| ts_fact        | 1      |        |        |        |     |       |
| Outputs        |        |        |        |        |     |       |
| Out            | 0      | 0      | 0      | 0      | ... | 0.135 |
| Exp. Out       | 0      | 0      | 0      | 0      | ... | 0.135 |
| Out (DSP)      | 0      | 0      | 0      | 0      | ... | 4428  |
| Exp. Out (DSP) | 0      | 0      | 0      | 0      | ... | 4430  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 213 |
| Max CPU cycles  | 230 |
| Avg CPU cycles  | 227 |

**Verification: FundFreq FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-25  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Filter block FundFreq.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 111   |
| CPU cycles     | 208    | 208    | 208    | 208    | ... | 208   |
| Inputs         |        |        |        |        |     |       |
| In (DSP)       | 6554   | -705   | -6595  | -10422 | ... | 13812 |
| phi (DSP)      | -32768 | -30997 | -29226 | -27454 | ... | 30997 |
| In             | 0.2    | -0.022 | -0.201 | -0.318 | ... | 0.422 |
| phi            | -1     | -0.946 | -0.892 | -0.838 | ... | 0.946 |
| Parameters     |        |        |        |        |     |       |
| ts_fact        | 1      |        |        |        |     |       |
| Outputs        |        |        |        |        |     |       |
| Out            | 0      | 0      | 0      | 0      | ... | 0.135 |
| Exp. Out       | 0      | 0      | 0      | 0      | ... | 0.135 |
| Out (DSP)      | 0      | 0      | 0      | 0      | ... | 4428  |
| Exp. Out (DSP) | 0      | 0      | 0      | 0      | ... | 4430  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 208 |
| Max CPU cycles  | 407 |
| Avg CPU cycles  | 211 |



**Verification: FundFreq FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-25  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Filter block FundFreq.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 111   |
| CPU cycles     | 124    | 123    | 123    | 123    | ... | 123   |
| Inputs         |        |        |        |        |     |       |
| In (DSP)       | 6554   | -705   | -6595  | -10422 | ... | 13812 |
| phi (DSP)      | -32768 | -30997 | -29226 | -27454 | ... | 30997 |
| In             | 0.2    | -0.022 | -0.201 | -0.318 | ... | 0.422 |
| phi            | -1     | -0.946 | -0.892 | -0.838 | ... | 0.946 |
| Parameters     |        |        |        |        |     |       |
| ts_fact        | 1      |        |        |        |     |       |
| Outputs        |        |        |        |        |     |       |
| Out            | 0      | 0      | 0      | 0      | ... | 0.135 |
| Exp. Out       | 0      | 0      | 0      | 0      | ... | 0.135 |
| Out (DSP)      | 0      | 0      | 0      | 0      | ... | 4428  |
| Exp. Out (DSP) | 0      | 0      | 0      | 0      | ... | 4430  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 123 |
| Max CPU cycles  | 173 |
| Avg CPU cycles  | 123 |

**Verification: FundFreq FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-25  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Filter block FundFreq.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 111   |
| CPU cycles     | 190    | 181    | 181    | 181    | ... | 181   |
| Inputs         |        |        |        |        |     |       |
| In (DSP)       | 6554   | -705   | -6595  | -10422 | ... | 13812 |
| phi (DSP)      | -32768 | -30997 | -29226 | -27454 | ... | 30997 |
| In             | 0.2    | -0.022 | -0.201 | -0.318 | ... | 0.422 |
| phi            | -1     | -0.946 | -0.892 | -0.838 | ... | 0.946 |
| Parameters     |        |        |        |        |     |       |
| ts_fact        | 1      |        |        |        |     |       |
| Outputs        |        |        |        |        |     |       |
| Out            | 0      | 0      | 0      | 0      | ... | 0.135 |
| Exp. Out       | 0      | 0      | 0      | 0      | ... | 0.135 |
| Out (DSP)      | 0      | 0      | 0      | 0      | ... | 4428  |
| Exp. Out (DSP) | 0      | 0      | 0      | 0      | ... | 4430  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 181  |
| Max CPU cycles  | 1314 |
| Avg CPU cycles  | 201  |

**Verification: FundFreq FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-25  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Filter block FundFreq.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 111   |
| CPU cycles     | 212    | 179    | 174    | 174    | ... | 176   |
| Inputs         |        |        |        |        |     |       |
| In (DSP)       | 6554   | -705   | -6595  | -10422 | ... | 13812 |
| phi (DSP)      | -32768 | -30997 | -29226 | -27454 | ... | 30997 |
| In             | 0.2    | -0.022 | -0.201 | -0.318 | ... | 0.422 |
| phi            | -1     | -0.946 | -0.892 | -0.838 | ... | 0.946 |
| Parameters     |        |        |        |        |     |       |
| ts_fact        | 1      |        |        |        |     |       |
| Outputs        |        |        |        |        |     |       |
| Out            | 0      | 0      | 0      | 0      | ... | 0.135 |
| Exp. Out       | 0      | 0      | 0      | 0      | ... | 0.135 |
| Out (DSP)      | 0      | 0      | 0      | 0      | ... | 4428  |
| Exp. Out (DSP) | 0      | 0      | 0      | 0      | ... | 4430  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 165 |
| Max CPU cycles  | 212 |
| Avg CPU cycles  | 174 |

**Verification: FundFreq FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-25  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Filter block FundFreq.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 111   |
| CPU cycles     | 194    | 198    | 195    | 195    | ... | 198   |
| Inputs         |        |        |        |        |     |       |
| In (DSP)       | 6554   | -705   | -6595  | -10422 | ... | 13812 |
| phi (DSP)      | -32768 | -30997 | -29226 | -27454 | ... | 30997 |
| In             | 0.2    | -0.022 | -0.201 | -0.318 | ... | 0.422 |
| phi            | -1     | -0.946 | -0.892 | -0.838 | ... | 0.946 |
| Parameters     |        |        |        |        |     |       |
| ts_fact        | 1      |        |        |        |     |       |
| Outputs        |        |        |        |        |     |       |
| Out            | 0      | 0      | 0      | 0      | ... | 0.135 |
| Exp. Out       | 0      | 0      | 0      | 0      | ... | 0.135 |
| Out (DSP)      | 0      | 0      | 0      | 0      | ... | 4428  |
| Exp. Out (DSP) | 0      | 0      | 0      | 0      | ... | 4430  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 190 |
| Max CPU cycles  | 357 |
| Avg CPU cycles  | 198 |

**Verification: FundFreq FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-25  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Filter block FundFreq.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 111        |
| CPU cycles     | 453         | 451         | ... | 451        |
| Inputs         |             |             |     |            |
| In (DSP)       | 429496730   | -46178986   | ... | 905172445  |
| phi (DSP)      | -2147483648 | -2031403451 | ... | 2031403451 |
| In             | 0.2         | -0.022      | ... | 0.422      |
| phi            | -1          | -0.946      | ... | 0.946      |
| Parameters     |             |             |     |            |
| ts_fact        | 1           |             |     |            |
| Outputs        |             |             |     |            |
| Out            | 0           | 0           | ... | 0.135      |
| Exp. Out       | 0           | 0           | ... | 0.135      |
| Out (DSP)      | 0           | 0           | ... | 290320398  |
| Exp. Out (DSP) | 0           | 0           | ... | 290341199  |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 2,3283e-04$ ( $\pm 500000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 451 |
| Max CPU cycles  | 897 |
| Avg CPU cycles  | 459 |

**Verification: FundFreq FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-25  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Filter block FundFreq.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 111        |
| CPU cycles     | 175         | 179         | ... | 179        |
| Inputs         |             |             |     |            |
| In (DSP)       | 429496730   | -46178986   | ... | 905172445  |
| phi (DSP)      | -2147483648 | -2031403451 | ... | 2031403451 |
| In             | 0.2         | -0.022      | ... | 0.422      |
| phi            | -1          | -0.946      | ... | 0.946      |
| Parameters     |             |             |     |            |
| ts_fact        | 1           |             |     |            |
| Outputs        |             |             |     |            |
| Out            | 0           | 0           | ... | 0.135      |
| Exp. Out       | 0           | 0           | ... | 0.135      |
| Out (DSP)      | 0           | 0           | ... | 290320398  |
| Exp. Out (DSP) | 0           | 0           | ... | 290341199  |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 2,3283e-04$ ( $\pm 500000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 175 |
| Max CPU cycles  | 935 |
| Avg CPU cycles  | 192 |

**Verification: FundFreq FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-25  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Filter block FundFreq.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 111        |
| CPU cycles     | 296         | 301         | ... | 301        |
| Inputs         |             |             |     |            |
| In (DSP)       | 429496730   | -46178986   | ... | 905172445  |
| phi (DSP)      | -2147483648 | -2031403451 | ... | 2031403451 |
| In             | 0.2         | -0.022      | ... | 0.422      |
| phi            | -1          | -0.946      | ... | 0.946      |
| Parameters     |             |             |     |            |
| ts_fact        | 1           |             |     |            |
| Outputs        |             |             |     |            |
| Out            | 0           | 0           | ... | 0.135      |
| Exp. Out       | 0           | 0           | ... | 0.135      |
| Out (DSP)      | 0           | 0           | ... | 290320398  |
| Exp. Out (DSP) | 0           | 0           | ... | 290341199  |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 2,3283e-04$ ( $\pm 500000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 296 |
| Max CPU cycles  | 602 |
| Avg CPU cycles  | 306 |

**Verification: FundFreq FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-25  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Filter block FundFreq.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 111        |
| CPU cycles     | 701         | 701         | ... | 701        |
| Inputs         |             |             |     |            |
| In (DSP)       | 429496730   | -46178986   | ... | 905172445  |
| phi (DSP)      | -2147483648 | -2031403451 | ... | 2031403451 |
| In             | 0.2         | -0.022      | ... | 0.422      |
| phi            | -1          | -0.946      | ... | 0.946      |
| Parameters     |             |             |     |            |
| ts_fact        | 1           |             |     |            |
| Outputs        |             |             |     |            |
| Out            | 0           | 0           | ... | 0.135      |
| Exp. Out       | 0           | 0           | ... | 0.135      |
| Out (DSP)      | 0           | 0           | ... | 290320398  |
| Exp. Out (DSP) | 0           | 0           | ... | 290341199  |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 2,3283e-04$ ( $\pm 500000$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 699  |
| Max CPU cycles  | 2222 |
| Avg CPU cycles  | 729  |



**Verification: FundFreq FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-25  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Filter block FundFreq.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 111        |
| CPU cycles     | 237         | 233         | ... | 235        |
| Inputs         |             |             |     |            |
| In (DSP)       | 429496730   | -46178986   | ... | 905172445  |
| phi (DSP)      | -2147483648 | -2031403451 | ... | 2031403451 |
| In             | 0.2         | -0.022      | ... | 0.422      |
| phi            | -1          | -0.946      | ... | 0.946      |
| Parameters     |             |             |     |            |
| ts_fact        | 1           |             |     |            |
| Outputs        |             |             |     |            |
| Out            | 0           | 0           | ... | 0.135      |
| Exp. Out       | 0           | 0           | ... | 0.135      |
| Out (DSP)      | 0           | 0           | ... | 290320398  |
| Exp. Out (DSP) | 0           | 0           | ... | 290341199  |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 2,3283e-04$ ( $\pm 500000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 233 |
| Max CPU cycles  | 461 |
| Avg CPU cycles  | 238 |

**Verification: FundFreq FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-25  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Filter block FundFreq.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 111        |
| CPU cycles     | 964         | 974         | ... | 952        |
| Inputs         |             |             |     |            |
| In (DSP)       | 429496730   | -46178986   | ... | 905172445  |
| phi (DSP)      | -2147483648 | -2031403451 | ... | 2031403451 |
| In             | 0.2         | -0.022      | ... | 0.422      |
| phi            | -1          | -0.946      | ... | 0.946      |
| Parameters     |             |             |     |            |
| ts_fact        | 1           |             |     |            |
| Outputs        |             |             |     |            |
| Out            | 0           | 0           | ... | 0.135      |
| Exp. Out       | 0           | 0           | ... | 0.135      |
| Out (DSP)      | 0           | 0           | ... | 290320398  |
| Exp. Out (DSP) | 0           | 0           | ... | 290341199  |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 2,3283e-04$ ( $\pm 500000$ LSB) |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 930   |
| Max CPU cycles  | 19683 |
| Avg CPU cycles  | 1293  |

**Verification: FundFreq FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-25  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Filter block FundFreq.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 111        |
| CPU cycles     | 332         | 266         | ... | 266        |
| Inputs         |             |             |     |            |
| In (DSP)       | 429496730   | -46178986   | ... | 905172445  |
| phi (DSP)      | -2147483648 | -2031403451 | ... | 2031403451 |
| In             | 0.2         | -0.022      | ... | 0.422      |
| phi            | -1          | -0.946      | ... | 0.946      |
| Parameters     |             |             |     |            |
| ts_fact        | 1           |             |     |            |
| Outputs        |             |             |     |            |
| Out            | 0           | 0           | ... | 0.135      |
| Exp. Out       | 0           | 0           | ... | 0.135      |
| Out (DSP)      | 0           | 0           | ... | 290320398  |
| Exp. Out (DSP) | 0           | 0           | ... | 290341199  |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 2,3283e-04$ ( $\pm 500000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 257 |
| Max CPU cycles  | 701 |
| Avg CPU cycles  | 273 |

**Verification: FundFreq FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-25  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Filter block FundFreq.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 111        |
| CPU cycles     | 426         | 412         | ... | 412        |
| Inputs         |             |             |     |            |
| In (DSP)       | 429496730   | -46178986   | ... | 905172445  |
| phi (DSP)      | -2147483648 | -2031403451 | ... | 2031403451 |
| In             | 0.2         | -0.022      | ... | 0.422      |
| phi            | -1          | -0.946      | ... | 0.946      |
| Parameters     |             |             |     |            |
| ts_fact        | 1           |             |     |            |
| Outputs        |             |             |     |            |
| Out            | 0           | 0           | ... | 0.135      |
| Exp. Out       | 0           | 0           | ... | 0.135      |
| Out (DSP)      | 0           | 0           | ... | 290320398  |
| Exp. Out (DSP) | 0           | 0           | ... | 290341199  |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 2,3283e-04$ ( $\pm 500000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 412 |
| Max CPU cycles  | 838 |
| Avg CPU cycles  | 421 |

**Verification: FundFreq Float32 CPU TMS320F28335**

**Date of Test** 2026-06-25  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Filter block FundFreq.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 111   |
| CPU cycles     | 475    | 463    | ... | 451   |
| Inputs         |        |        |     |       |
| In (DSP)       | 1.06   | -0.114 | ... | 2.234 |
| phi (DSP)      | -3.142 | -2.972 | ... | 2.972 |
| In             | 1.06   | -0.114 | ... | 2.234 |
| phi            | -3.142 | -2.972 | ... | 2.972 |
| Parameters     |        |        |     |       |
| ts_fact        | 1      |        |     |       |
| Outputs        |        |        |     |       |
| Out            | 0      | -0     | ... | 0.717 |
| Exp. Out       | 0      | 0      | ... | 0.717 |
| Out (DSP)      | 0      | -0     | ... | 0.717 |
| Exp. Out (DSP) | 0      | 0      | ... | 0.717 |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance Out | $\pm 1,1642\text{e-}06$ ( $\pm 2500$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 451 |
| Max CPU cycles  | 993 |
| Avg CPU cycles  | 466 |

**Verification: FundFreq Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-25  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Filter block FundFreq.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 111   |
| CPU cycles     | 257    | 257    | ... | 257   |
| Inputs         |        |        |     |       |
| In (DSP)       | 1.06   | -0.114 | ... | 2.234 |
| phi (DSP)      | -3.142 | -2.972 | ... | 2.972 |
| In             | 1.06   | -0.114 | ... | 2.234 |
| phi            | -3.142 | -2.972 | ... | 2.972 |
| Parameters     |        |        |     |       |
| ts_fact        | 1      |        |     |       |
| Outputs        |        |        |     |       |
| Out            | 0      | -0     | ... | 0.717 |
| Exp. Out       | 0      | 0      | ... | 0.717 |
| Out (DSP)      | 0      | -0     | ... | 0.717 |
| Exp. Out (DSP) | 0      | 0      | ... | 0.717 |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance Out | $\pm 1,1642\text{e-}06$ ( $\pm 2500$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 257 |
| Max CPU cycles  | 295 |
| Avg CPU cycles  | 257 |

**Verification: FundFreq Float32 CPU STM32G474RE**

**Date of Test** 2026-06-25  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Filter block FundFreq.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 111   |
| CPU cycles     | 976    | 898    | ... | 880   |
| Inputs         |        |        |     |       |
| In (DSP)       | 1.06   | -0.114 | ... | 2.234 |
| phi (DSP)      | -3.142 | -2.972 | ... | 2.972 |
| In             | 1.06   | -0.114 | ... | 2.234 |
| phi            | -3.142 | -2.972 | ... | 2.972 |
| Parameters     |        |        |     |       |
| ts_fact        | 1      |        |     |       |
| Outputs        |        |        |     |       |
| Out            | 0      | -0     | ... | 0.717 |
| Exp. Out       | 0      | 0      | ... | 0.717 |
| Out (DSP)      | 0      | -0     | ... | 0.717 |
| Exp. Out (DSP) | 0      | 0      | ... | 0.717 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 1,1642e-06$ ( $\pm 2500$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 449 |
| Max CPU cycles  | 988 |
| Avg CPU cycles  | 716 |

**Verification: FundFreq Float32 CPU STM32F072RB**

**Date of Test** 2026-06-25  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Filter block FundFreq.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 111   |
| CPU cycles     | 12071  | 10500  | ... | 10547 |
| Inputs         |        |        |     |       |
| In (DSP)       | 1.06   | -0.114 | ... | 2.234 |
| phi (DSP)      | -3.142 | -2.972 | ... | 2.972 |
| In             | 1.06   | -0.114 | ... | 2.234 |
| phi            | -3.142 | -2.972 | ... | 2.972 |
| Parameters     |        |        |     |       |
| ts_fact        | 1      |        |     |       |
| Outputs        |        |        |     |       |
| Out            | 0      | -0     | ... | 0.717 |
| Exp. Out       | 0      | 0      | ... | 0.717 |
| Out (DSP)      | 0      | -0     | ... | 0.717 |
| Exp. Out (DSP) | 0      | 0      | ... | 0.717 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 1,1642e-06$ ( $\pm 2500$ LSB) |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 6544  |
| Max CPU cycles  | 13543 |
| Avg CPU cycles  | 8938  |



**Verification: FundFreq Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-25  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Filter block FundFreq.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 111   |
| CPU cycles     | 1275   | 985    | ... | 1044  |
| Inputs         |        |        |     |       |
| In (DSP)       | 1.06   | -0.114 | ... | 2.234 |
| phi (DSP)      | -3.142 | -2.972 | ... | 2.972 |
| In             | 1.06   | -0.114 | ... | 2.234 |
| phi            | -3.142 | -2.972 | ... | 2.972 |
| Parameters     |        |        |     |       |
| ts_fact        | 1      |        |     |       |
| Outputs        |        |        |     |       |
| Out            | 0      | -0     | ... | 0.717 |
| Exp. Out       | 0      | 0      | ... | 0.717 |
| Out (DSP)      | 0      | -0     | ... | 0.717 |
| Exp. Out (DSP) | 0      | 0      | ... | 0.717 |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance Out | $\pm 1,1642\text{e-}06$ ( $\pm 2500$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 755  |
| Max CPU cycles  | 1814 |
| Avg CPU cycles  | 960  |

**Verification: FundFreq Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-25  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Filter block FundFreq.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 111   |
| CPU cycles     | 7204   | 9394   | ... | 9847  |
| Inputs         |        |        |     |       |
| In (DSP)       | 1.06   | -0.114 | ... | 2.234 |
| phi (DSP)      | -3.142 | -2.972 | ... | 2.972 |
| In             | 1.06   | -0.114 | ... | 2.234 |
| phi            | -3.142 | -2.972 | ... | 2.972 |
| Parameters     |        |        |     |       |
| ts_fact        | 1      |        |     |       |
| Outputs        |        |        |     |       |
| Out            | 0      | -0     | ... | 0.717 |
| Exp. Out       | 0      | 0      | ... | 0.717 |
| Out (DSP)      | 0      | -0     | ... | 0.717 |
| Exp. Out (DSP) | 0      | 0      | ... | 0.717 |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance Out | $\pm 1,1642\text{e-}06$ ( $\pm 2500$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 7204 |
| Max CPU cycles  | 9847 |
| Avg CPU cycles  | 8883 |

**Verification: FundFreq Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-25  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Filter block FundFreq.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 111   |
| CPU cycles     | 1009   | 669    | ... | 653   |
| Inputs         |        |        |     |       |
| In (DSP)       | 1.06   | -0.114 | ... | 2.234 |
| phi (DSP)      | -3.142 | -2.972 | ... | 2.972 |
| In             | 1.06   | -0.114 | ... | 2.234 |
| phi            | -3.142 | -2.972 | ... | 2.972 |
| Parameters     |        |        |     |       |
| ts_fact        | 1      |        |     |       |
| Outputs        |        |        |     |       |
| Out            | 0      | -0     | ... | 0.717 |
| Exp. Out       | 0      | 0      | ... | 0.717 |
| Out (DSP)      | 0      | -0     | ... | 0.717 |
| Exp. Out (DSP) | 0      | 0      | ... | 0.717 |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance Out | $\pm 1,1642\text{e-}06$ ( $\pm 2500$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 342  |
| Max CPU cycles  | 1009 |
| Avg CPU cycles  | 530  |

**Verification: FundFreq Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-25  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Filter block FundFreq.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 111   |
| CPU cycles     | 315    | 312    | ... | 302   |
| Inputs         |        |        |     |       |
| In (DSP)       | 1.06   | -0.114 | ... | 2.234 |
| phi (DSP)      | -3.142 | -2.972 | ... | 2.972 |
| In             | 1.06   | -0.114 | ... | 2.234 |
| phi            | -3.142 | -2.972 | ... | 2.972 |
| Parameters     |        |        |     |       |
| ts_fact        | 1      |        |     |       |
| Outputs        |        |        |     |       |
| Out            | 0      | -0     | ... | 0.717 |
| Exp. Out       | 0      | 0      | ... | 0.717 |
| Out (DSP)      | 0      | -0     | ... | 0.717 |
| Exp. Out (DSP) | 0      | 0      | ... | 0.717 |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance Out | $\pm 1,1642\text{e-}06$ ( $\pm 2500$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 302 |
| Max CPU cycles  | 806 |
| Avg CPU cycles  | 316 |

## Block: HighpassBiQ



Calculates the filter coefficients for a second order highpass and performs filtering on input signal.

Second order transfer function used:

$$H(z) = (b0.z^2 + b1.z + b2) / (z^2 + a1.z + a2)$$

| Inports |             |
|---------|-------------|
| In      | Input In(k) |

| Outports |               |
|----------|---------------|
| Out      | Output Out(k) |

| Mask Parameters |    |                                                                                                                        |
|-----------------|----|------------------------------------------------------------------------------------------------------------------------|
| Name            | ID | Description                                                                                                            |
| characteristic  | 1  | The filter characteristic is one of Butterworth, Chebyshev I, Chebyshev II (also known as inverse Chebyshev) or Bessel |
| fc              | 2  | Cut-off frequency in Hz                                                                                                |
| rp              | 3  | The passband ripple is only used and verified with 'Chebyshev I' filters.<br>Must be a positive number                 |
| rs              | 4  | The stopband ripple is only used and verified with 'Chebyshev II' filters.<br>Must be a positive number                |
| ts_fact         | 5  | Multiplication factor of base sampling time (in integer format)                                                        |

### Description:

#### Butterworth

- passband
  - maximal flat
- @cut-off frequency:
  - -3dB attenuation
  - -90 degree phaseshift
- stopband
  - monotonic -40dB decline per decade
  - approx. -37dB decline within first decade

E.g.: Cut-off frequency is 10Hz. The bodeplot is shown in the figure 5 below.

#### Chebyshev I




Figure 5: Bodeplot Butterworth highpass.

- passband:
  - $N/2=1$  ripple in the passband.
  - attenuation from 0 to  $rp$  [dB].
- @cut-off frequency: attenuation is bigger than or equal  $rp$  [dB].
- stopband:
  - monotonic -40dB decline per decade
- Trade-off:
  - the bigger passband ripple  $rp$  is chosen, the steeper is the magnitude cut-off within the first decade in stopband
  - the bigger the passband ripple  $rp$  is chosen, the bigger is the overall passband attenuation!

E.g.:

Cut-off frequency is 10Hz.

The maximal ripple in the passband  $rp$  must be given in [dB].

To show the mentioned trade-off, two bodeplots are shown. One with a small and one with a bigger  $rp$ . The bodeplot is shown in the figures 6 and 7 below.




Figure 6: Bodeplot Chebyshev I highpass.  $rp = 5\text{dB}$

## Chebyshev II

Also known as inverse Chebyshev filter.

- passband
  - flat, no ripples




Figure 7: Bodeplot Chebyshev I highpass.  $r_p = 20\text{dB}$

- @cut-off frequency: attenuation is  $r_s$  [dB].
- stopband
  - $N/2=1$  ripple in the stopband
  - attenuation is smaller than or equal  $r_s$  [dB].
- Trade-off:
  - the lower  $r_s$  is chosen, the sharper is the magnitude cut-off
  - the lower  $r_s$  is chosen, the lower is the over all stopband attenuation

E.g.:

Cut-off frequency is 10Hz.

The maximal ripple in the stopband  $r_s$  must be given in [dB].

To show the mentioned trade-off, two bodeplots are shown. One with a small and one with a bigger  $r_s$ . The bodeplot is shown in the figures 8 and 9 below.




Figure 8: Bodeplot Chebyshev II highpass.  $r_s = 5\text{dB}$

## Bessel

- passband
  - constant group-delay in passband.
  - least sharp magnitude roll-off.
- @cut-off frequency:
  - approx. -1.6 dB attenuation
  - approx. -56 degree phaseshift




Figure 9: Bodeplot Chebyshev II highpass.  $r_s = 20\text{dB}$

- stopband
  - monotonic -40dB decline per decade
  - approx. -30dB decline within first decade

E.g.:

Cut-off frequency is 10Hz.

The bodeplot is shown in the figure 10 below.




Figure 10: Bodeplot Bessel highpass.

### Implementations:

- FiP16** 16 Bit Fixed Point Implementation
- FiP32** 32 Bit Fixed Point Implementation
- Float32** 32 Bit Floating Point Implementation
- Float64** 64 Bit Floating Point Implementation

### Implementation: FiP16

16 Bit Fixed Point Implementation

| Inports Data Type  |       |
|--------------------|-------|
| In                 | int16 |
| Outports Data Type |       |
| Out                | int16 |



### Implementation: FiP32

---

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

---

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

---

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

## Block: IIR

---



Transfer function:

$$H(z) = (b_0.z^n + b_1.z + \dots + b_n) / (a_0.z^n + a_1.z + \dots + a_n)$$

The maximum filter order is 32.

The order of the denominator has to be greater than or equal to the order of the numerator.

| Inports |             |
|---------|-------------|
| In      | Input In(k) |

| Outports |               |
|----------|---------------|
| Out      | Output Out(k) |

| Mask Parameters |    |                                                                 |
|-----------------|----|-----------------------------------------------------------------|
| Name            | ID | Description                                                     |
| CoeffB          | 1  | Array with filter coefficients of numerator                     |
| CoeffA          | 2  | Array with filter coefficients of denominator                   |
| ts_fact         | 3  | Multiplication factor of base sampling time (in integer format) |

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

---

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

## Block: LowpassBiQ



Calculates the filter coefficients for a second order lowpass and performs filtering on input signal.

Second order transfer function used:

$$H(z) = (b0.z^2 + b1.z + b2) / (z^2 + a1.z + a2)$$

### Inports

|    |             |
|----|-------------|
| In | Input In(k) |
|----|-------------|

### Outports

|     |               |
|-----|---------------|
| Out | Output Out(k) |
|-----|---------------|

### Mask Parameters

| Name           | ID | Description                                                                                                            |
|----------------|----|------------------------------------------------------------------------------------------------------------------------|
| characteristic | 1  | The filter characteristic is one of Butterworth, Chebyshev I, Chebyshev II (also known as inverse Chebyshev) or Bessel |
| fc             | 2  | Cut-off frequency in Hz                                                                                                |
| rp             | 3  | The passband ripple is only used and verified with 'Chebyshev I' filters.<br>Must be a positive number                 |
| rs             | 4  | The stopband ripple is only used and verified with 'Chebyshev II' filters.<br>Must be a positive number                |
| ts_fact        | 5  | Multiplication factor of base sampling time (in integer format)                                                        |

### Description:

#### Butterworth

- passband
  - maximal flat
- @cut-off frequency:
  - -3dB attenuation
  - -90 degree phaseshift
- stopband
  - monotonic -40dB decline per decade
  - approx. -37dB decline within first decade

E.g.: Cut-off frequency is 10Hz. The bodeplot is shown in the figure 11 below.

#### Chebyshev I




Figure 11: Bodeplot Butterworth lowpass.

- passband:
  - $N/2=1$  ripple in the passband.
  - attenuation from 0 to  $r_p$  [dB].
- @cut-off frequency: attenuation is bigger than or equal  $r_p$  [dB].
- stopband:
  - monotonic -40dB decline per decade
- Trade-off:
  - the bigger passband ripple  $r_p$  is chosen, the steeper is the magnitude cut-off within the first decade in stopband
  - the bigger the passband ripple  $r_p$  is chosen, the bigger is the overall passband attenuation!

E.g.:

Cut-off frequency is 10Hz.

The maximal ripple in the passband  $r_p$  must be given in [dB].

To show the mentioned trade-off, two bodeplots are shown. One with a small and one with a bigger  $r_p$ . The bodeplot is shown in the figures 12 and 13 below.




Figure 12: Bodeplot Chebyshev I lowpass.  $r_p = 5\text{dB}$

## Chebyshev II

Also known as inverse Chebyshev filter.

- passband
  - flat, no ripples




Figure 13: Bodeplot Chebyshev I lowpass.  $r_p = 20\text{dB}$

- @cut-off frequency: attenuation is  $r_s$  [dB].
- stopband
  - $N/2=1$  ripple in the stopband
  - attenuation is smaller than or equal  $r_s$  [dB].
- Trade-off:
  - the lower  $r_s$  is chosen, the sharper is the magnitude cut-off
  - the lower  $r_s$  is chosen, the lower is the over all stopband attenuation

E.g.:

Cut-off frequency is 10Hz.

The maximal ripple in the stopband  $r_s$  must be given in [dB].

To show the mentioned trade-off, two bodeplots are shown. One with a small and one with a bigger  $r_s$ . The bodeplot is shown in the figures 14 and 15 below.




Figure 14: Bodeplot Chebyshev II lowpass.  $r_s = 20\text{dB}$

## Bessel

- passband
  - constant group-delay in passband.
  - least sharp magnitude roll-off.
- @cut-off frequency:
  - approx. -1.6 dB attenuation
  - approx. -56 degree phaseshift




Figure 15: Bodeplot Chebyshev II lowpass.  $r_s = 5\text{dB}$

- stopband
  - monotonic -40dB decline per decade
  - approx. -30dB decline within first decade

E.g.:

Cut-off frequency is 10Hz.

The bodeplot is shown in the figure 16 below.




Figure 16: Bodeplot Bessel lowpass.

### Implementations:

- FiP16** 16 Bit Fixed Point Implementation
- FiP32** 32 Bit Fixed Point Implementation
- Float32** 32 Bit Floating Point Implementation
- Float64** 64 Bit Floating Point Implementation

### Implementation: FiP16

16 Bit Fixed Point Implementation

| Inports Data Type  |       |
|--------------------|-------|
| In                 | int16 |
| Outports Data Type |       |
| Out                | int16 |

### Implementation: FiP32

---

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

---

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

---


64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |



## Block: MinMaxPeriodic




Outputs the minimum and maximum of the input signal over one period of the (angle) signal phi.

| Inports |              |
|---------|--------------|
| In      | Input signal |
| phi     | Angle signal |

| Outputs |                         |
|---------|-------------------------|
| max     | Maximum of input signal |
| min     | Minimum of input signal |

### Description:

Exemplary signal waveforms:



**Implementations:**

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

**Implementation: FiP16**

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |
| phi               | int16 |

| Outports Data Type |       |
|--------------------|-------|
| max                | int16 |
| min                | int16 |

**Implementation: FiP32**

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |
| phi               | int32 |

| Outports Data Type |       |
|--------------------|-------|
| max                | int32 |
| min                | int32 |

**Implementation: Float32**

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |
| phi               | float32 |

| Outports Data Type |         |
|--------------------|---------|
| max                | float32 |
| min                | float32 |

## Implementation: Float64

---

### 64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |
| phi               | float64 |

| Outports Data Type |         |
|--------------------|---------|
| max                | float64 |
| min                | float64 |

**Verification: MinMaxPeriodic FiP16 CPU TMS320F28335**

Date of Test 2026-06-25  
Target controller TMS320F28335

**Test case: Inport test****OK**

Inport test for Filter block MinMaxPeriodic.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 112    |
| CPU cycles     | 97     | 97     | 97     | 97     | ... | 90     |
| Inputs         |        |        |        |        |     |        |
| In (DSP)       | 0      | -4552  | -8966  | -13107 | ... | 0      |
| phi (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | -32768 |
| In             | -0     | -0.139 | -0.274 | -0.4   | ... | 0      |
| phi            | -1     | -0.944 | -0.889 | -0.833 | ... | -1     |
| Outputs        |        |        |        |        |     |        |
| max            | 0      | 0      | 0      | 0      | ... | 0.9    |
| min            | 0      | 0      | 0      | 0      | ... | 0.1    |
| Exp. max       | 0      | 0      | 0      | 0      | ... | 0.9    |
| Exp. min       | 0      | 0      | 0      | 0      | ... | 0.1    |
| max (DSP)      | 0      | 0      | 0      | 0      | ... | 29491  |
| min (DSP)      | 0      | 0      | 0      | 0      | ... | 3277   |
| Exp. max (DSP) | 0      | 0      | 0      | 0      | ... | 29491  |
| Exp. min (DSP) | 0      | 0      | 0      | 0      | ... | 3277   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance max | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |
| Tolerance min | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 90 |
| Max CPU cycles  | 97 |
| Avg CPU cycles  | 96 |

**Verification: MinMaxPeriodic FiP16 CPU TM4C123GH6**

Date of Test 2026-06-25  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for Filter block MinMaxPeriodic.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 112    |
| CPU cycles     | 57     | 53     | 53     | 53     | ... | 49     |
| Inputs         |        |        |        |        |     |        |
| In (DSP)       | 0      | -4552  | -8966  | -13107 | ... | 0      |
| phi (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | -32768 |
| In             | -0     | -0.139 | -0.274 | -0.4   | ... | 0      |
| phi            | -1     | -0.944 | -0.889 | -0.833 | ... | -1     |
| Outputs        |        |        |        |        |     |        |
| max            | 0      | 0      | 0      | 0      | ... | 0.9    |
| min            | 0      | 0      | 0      | 0      | ... | 0.1    |
| Exp. max       | 0      | 0      | 0      | 0      | ... | 0.9    |
| Exp. min       | 0      | 0      | 0      | 0      | ... | 0.1    |
| max (DSP)      | 0      | 0      | 0      | 0      | ... | 29491  |
| min (DSP)      | 0      | 0      | 0      | 0      | ... | 3277   |
| Exp. max (DSP) | 0      | 0      | 0      | 0      | ... | 29491  |
| Exp. min (DSP) | 0      | 0      | 0      | 0      | ... | 3277   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance max | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |
| Tolerance min | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 49 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 52 |

**Verification: MinMaxPeriodic FiP16 CPU STM32G474RE**

Date of Test 2026-06-25  
Target controller STM32G474RE

**Test case: Inport test****OK**

Inport test for Filter block MinMaxPeriodic.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 112    |
| CPU cycles     | 91     | 91     | 91     | 91     | ... | 83     |
| Inputs         |        |        |        |        |     |        |
| In (DSP)       | 0      | -4552  | -8966  | -13107 | ... | 0      |
| phi (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | -32768 |
| In             | -0     | -0.139 | -0.274 | -0.4   | ... | 0      |
| phi            | -1     | -0.944 | -0.889 | -0.833 | ... | -1     |
| Outputs        |        |        |        |        |     |        |
| max            | 0      | 0      | 0      | 0      | ... | 0.9    |
| min            | 0      | 0      | 0      | 0      | ... | 0.1    |
| Exp. max       | 0      | 0      | 0      | 0      | ... | 0.9    |
| Exp. min       | 0      | 0      | 0      | 0      | ... | 0.1    |
| max (DSP)      | 0      | 0      | 0      | 0      | ... | 29491  |
| min (DSP)      | 0      | 0      | 0      | 0      | ... | 3277   |
| Exp. max (DSP) | 0      | 0      | 0      | 0      | ... | 29491  |
| Exp. min (DSP) | 0      | 0      | 0      | 0      | ... | 3277   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance max | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |
| Tolerance min | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 83 |
| Max CPU cycles  | 91 |
| Avg CPU cycles  | 90 |

**Verification: MinMaxPeriodic FiP16 CPU STM32F072RB**

Date of Test 2026-06-25  
Target controller STM32F072RB

**Test case: Inport test****OK**

Inport test for Filter block MinMaxPeriodic.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 112    |
| CPU cycles     | 93     | 90     | 90     | 90     | ... | 80     |
| Inputs         |        |        |        |        |     |        |
| In (DSP)       | 0      | -4552  | -8966  | -13107 | ... | 0      |
| phi (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | -32768 |
| In             | -0     | -0.139 | -0.274 | -0.4   | ... | 0      |
| phi            | -1     | -0.944 | -0.889 | -0.833 | ... | -1     |
| Outputs        |        |        |        |        |     |        |
| max            | 0      | 0      | 0      | 0      | ... | 0.9    |
| min            | 0      | 0      | 0      | 0      | ... | 0.1    |
| Exp. max       | 0      | 0      | 0      | 0      | ... | 0.9    |
| Exp. min       | 0      | 0      | 0      | 0      | ... | 0.1    |
| max (DSP)      | 0      | 0      | 0      | 0      | ... | 29491  |
| min (DSP)      | 0      | 0      | 0      | 0      | ... | 3277   |
| Exp. max (DSP) | 0      | 0      | 0      | 0      | ... | 29491  |
| Exp. min (DSP) | 0      | 0      | 0      | 0      | ... | 3277   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance max | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |
| Tolerance min | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 80  |
| Max CPU cycles  | 155 |
| Avg CPU cycles  | 91  |

**Verification: MinMaxPeriodic FiP16 CPU PIC32MX170F256**

Date of Test 2026-06-25  
Target controller PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Filter block MinMaxPeriodic.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 112    |
| CPU cycles     | 60     | 57     | 57     | 57     | ... | 49     |
| Inputs         |        |        |        |        |     |        |
| In (DSP)       | 0      | -4552  | -8966  | -13107 | ... | 0      |
| phi (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | -32768 |
| In             | -0     | -0.139 | -0.274 | -0.4   | ... | 0      |
| phi            | -1     | -0.944 | -0.889 | -0.833 | ... | -1     |
| Outputs        |        |        |        |        |     |        |
| max            | 0      | 0      | 0      | 0      | ... | 0.9    |
| min            | 0      | 0      | 0      | 0      | ... | 0.1    |
| Exp. max       | 0      | 0      | 0      | 0      | ... | 0.9    |
| Exp. min       | 0      | 0      | 0      | 0      | ... | 0.1    |
| max (DSP)      | 0      | 0      | 0      | 0      | ... | 29491  |
| min (DSP)      | 0      | 0      | 0      | 0      | ... | 3277   |
| Exp. max (DSP) | 0      | 0      | 0      | 0      | ... | 29491  |
| Exp. min (DSP) | 0      | 0      | 0      | 0      | ... | 3277   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance max | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |
| Tolerance min | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 49 |
| Max CPU cycles  | 60 |
| Avg CPU cycles  | 53 |



**Verification: MinMaxPeriodic FiP16 CPU dsPIC33EP256MC502**

Date of Test 2026-06-25  
Target controller dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Filter block MinMaxPeriodic.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 112    |
| CPU cycles     | 72     | 66     | 66     | 66     | ... | 65     |
| Inputs         |        |        |        |        |     |        |
| In (DSP)       | 0      | -4552  | -8966  | -13107 | ... | 0      |
| phi (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | -32768 |
| In             | -0     | -0.139 | -0.274 | -0.4   | ... | 0      |
| phi            | -1     | -0.944 | -0.889 | -0.833 | ... | -1     |
| Outputs        |        |        |        |        |     |        |
| max            | 0      | 0      | 0      | 0      | ... | 0.9    |
| min            | 0      | 0      | 0      | 0      | ... | 0.1    |
| Exp. max       | 0      | 0      | 0      | 0      | ... | 0.9    |
| Exp. min       | 0      | 0      | 0      | 0      | ... | 0.1    |
| max (DSP)      | 0      | 0      | 0      | 0      | ... | 29491  |
| min (DSP)      | 0      | 0      | 0      | 0      | ... | 3277   |
| Exp. max (DSP) | 0      | 0      | 0      | 0      | ... | 29491  |
| Exp. min (DSP) | 0      | 0      | 0      | 0      | ... | 3277   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance max | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |
| Tolerance min | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 64 |
| Max CPU cycles  | 72 |
| Avg CPU cycles  | 66 |

**Verification: MinMaxPeriodic FiP16 CPU XMC4800-F144K2048**

Date of Test 2026-06-25  
Target controller XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Filter block MinMaxPeriodic.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 112    |
| CPU cycles     | 103    | 88     | 88     | 88     | ... | 77     |
| Inputs         |        |        |        |        |     |        |
| In (DSP)       | 0      | -4552  | -8966  | -13107 | ... | 0      |
| phi (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | -32768 |
| In             | -0     | -0.139 | -0.274 | -0.4   | ... | 0      |
| phi            | -1     | -0.944 | -0.889 | -0.833 | ... | -1     |
| Outputs        |        |        |        |        |     |        |
| max            | 0      | 0      | 0      | 0      | ... | 0.9    |
| min            | 0      | 0      | 0      | 0      | ... | 0.1    |
| Exp. max       | 0      | 0      | 0      | 0      | ... | 0.9    |
| Exp. min       | 0      | 0      | 0      | 0      | ... | 0.1    |
| max (DSP)      | 0      | 0      | 0      | 0      | ... | 29491  |
| min (DSP)      | 0      | 0      | 0      | 0      | ... | 3277   |
| Exp. max (DSP) | 0      | 0      | 0      | 0      | ... | 29491  |
| Exp. min (DSP) | 0      | 0      | 0      | 0      | ... | 3277   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance max | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |
| Tolerance min | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 77  |
| Max CPU cycles  | 103 |
| Avg CPU cycles  | 82  |

**Verification: MinMaxPeriodic FiP16 CPU TMS320F28379D**

Date of Test 2026-06-25  
Target controller TMS320F28379D

**Test case: Inport test****OK**

Inport test for Filter block MinMaxPeriodic.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 112    |
| CPU cycles     | 96     | 97     | 97     | 97     | ... | 87     |
| Inputs         |        |        |        |        |     |        |
| In (DSP)       | 0      | -4552  | -8966  | -13107 | ... | 0      |
| phi (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | -32768 |
| In             | -0     | -0.139 | -0.274 | -0.4   | ... | 0      |
| phi            | -1     | -0.944 | -0.889 | -0.833 | ... | -1     |
| Outputs        |        |        |        |        |     |        |
| max            | 0      | 0      | 0      | 0      | ... | 0.9    |
| min            | 0      | 0      | 0      | 0      | ... | 0.1    |
| Exp. max       | 0      | 0      | 0      | 0      | ... | 0.9    |
| Exp. min       | 0      | 0      | 0      | 0      | ... | 0.1    |
| max (DSP)      | 0      | 0      | 0      | 0      | ... | 29491  |
| min (DSP)      | 0      | 0      | 0      | 0      | ... | 3277   |
| Exp. max (DSP) | 0      | 0      | 0      | 0      | ... | 29491  |
| Exp. min (DSP) | 0      | 0      | 0      | 0      | ... | 3277   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance max | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |
| Tolerance min | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 87 |
| Max CPU cycles  | 97 |
| Avg CPU cycles  | 96 |

**Verification: MinMaxPeriodic FiP32 CPU TMS320F28335**

Date of Test 2026-06-25  
Target controller TMS320F28335

**Test case: Inport test****OK**

Inport test for Filter block MinMaxPeriodic.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 112         |
| CPU cycles     | 145         | 140         | ... | 137         |
| Inputs         |             |             |     |             |
| In (DSP)       | 0           | -298325298  | ... | 0           |
| phi (DSP)      | -2147483648 | -2028179001 | ... | -2147483648 |
| In             | -0          | -0.139      | ... | 0           |
| phi            | -1          | -0.944      | ... | -1          |
| Outputs        |             |             |     |             |
| max            | 0           | 0           | ... | 0.9         |
| min            | 0           | 0           | ... | 0.1         |
| Exp. max       | 0           | 0           | ... | 0.9         |
| Exp. min       | 0           | 0           | ... | 0.1         |
| max (DSP)      | 0           | 0           | ... | 1932735283  |
| min (DSP)      | 0           | 0           | ... | 214748365   |
| Exp. max (DSP) | 0           | 0           | ... | 1932735283  |
| Exp. min (DSP) | 0           | 0           | ... | 214748365   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance max | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |
| Tolerance min | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 137 |
| Max CPU cycles  | 145 |
| Avg CPU cycles  | 140 |

**Verification: MinMaxPeriodic FiP32 CPU TM4C123GH6**

Date of Test 2026-06-25  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for Filter block MinMaxPeriodic.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 112         |
| CPU cycles     | 67          | 67          | ... | 63          |
| <i>Inputs</i>  |             |             |     |             |
| In (DSP)       | 0           | -298325298  | ... | 0           |
| phi (DSP)      | -2147483648 | -2028179001 | ... | -2147483648 |
| In             | -0          | -0.139      | ... | 0           |
| phi            | -1          | -0.944      | ... | -1          |
| <i>Outputs</i> |             |             |     |             |
| max            | 0           | 0           | ... | 0.9         |
| min            | 0           | 0           | ... | 0.1         |
| Exp. max       | 0           | 0           | ... | 0.9         |
| Exp. min       | 0           | 0           | ... | 0.1         |
| max (DSP)      | 0           | 0           | ... | 1932735283  |
| min (DSP)      | 0           | 0           | ... | 214748365   |
| Exp. max (DSP) | 0           | 0           | ... | 1932735283  |
| Exp. min (DSP) | 0           | 0           | ... | 214748365   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance max | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |
| Tolerance min | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 63 |
| Max CPU cycles  | 71 |
| Avg CPU cycles  | 68 |

**Verification: MinMaxPeriodic FiP32 CPU STM32G474RE**

Date of Test 2026-06-25  
Target controller STM32G474RE

**Test case: Inport test****OK**

Inport test for Filter block MinMaxPeriodic.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 112         |
| CPU cycles     | 104         | 104         | ... | 99          |
| Inputs         |             |             |     |             |
| In (DSP)       | 0           | -298325298  | ... | 0           |
| phi (DSP)      | -2147483648 | -2028179001 | ... | -2147483648 |
| In             | -0          | -0.139      | ... | 0           |
| phi            | -1          | -0.944      | ... | -1          |
| Outputs        |             |             |     |             |
| max            | 0           | 0           | ... | 0.9         |
| min            | 0           | 0           | ... | 0.1         |
| Exp. max       | 0           | 0           | ... | 0.9         |
| Exp. min       | 0           | 0           | ... | 0.1         |
| max (DSP)      | 0           | 0           | ... | 1932735283  |
| min (DSP)      | 0           | 0           | ... | 214748365   |
| Exp. max (DSP) | 0           | 0           | ... | 1932735283  |
| Exp. min (DSP) | 0           | 0           | ... | 214748365   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance max | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |
| Tolerance min | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 99  |
| Max CPU cycles  | 104 |
| Avg CPU cycles  | 103 |

**Verification: MinMaxPeriodic FiP32 CPU STM32F072RB**

Date of Test 2026-06-25  
Target controller STM32F072RB

**Test case: Inport test****OK**

Inport test for Filter block MinMaxPeriodic.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 112         |
| CPU cycles     | 109         | 109         | ... | 113         |
| Inputs         |             |             |     |             |
| In (DSP)       | 0           | -298325298  | ... | 0           |
| phi (DSP)      | -2147483648 | -2028179001 | ... | -2147483648 |
| In             | -0          | -0.139      | ... | 0           |
| phi            | -1          | -0.944      | ... | -1          |
| Outputs        |             |             |     |             |
| max            | 0           | 0           | ... | 0.9         |
| min            | 0           | 0           | ... | 0.1         |
| Exp. max       | 0           | 0           | ... | 0.9         |
| Exp. min       | 0           | 0           | ... | 0.1         |
| max (DSP)      | 0           | 0           | ... | 1932735283  |
| min (DSP)      | 0           | 0           | ... | 214748365   |
| Exp. max (DSP) | 0           | 0           | ... | 1932735283  |
| Exp. min (DSP) | 0           | 0           | ... | 214748365   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance max | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |
| Tolerance min | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 109 |
| Max CPU cycles  | 113 |
| Avg CPU cycles  | 109 |

**Verification: MinMaxPeriodic FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-25  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Filter block MinMaxPeriodic.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>      | 1           | 2           | ... | 112         |
| <b>CPU cycles</b>     | 70          | 64          | ... | 65          |
| <i>Inputs</i>         |             |             |     |             |
| <b>In (DSP)</b>       | 0           | -298325298  | ... | 0           |
| <b>phi (DSP)</b>      | -2147483648 | -2028179001 | ... | -2147483648 |
| <b>In</b>             | -0          | -0.139      | ... | 0           |
| <b>phi</b>            | -1          | -0.944      | ... | -1          |
| <i>Outputs</i>        |             |             |     |             |
| <b>max</b>            | 0           | 0           | ... | 0.9         |
| <b>min</b>            | 0           | 0           | ... | 0.1         |
| <b>Exp. max</b>       | 0           | 0           | ... | 0.9         |
| <b>Exp. min</b>       | 0           | 0           | ... | 0.1         |
| <b>max (DSP)</b>      | 0           | 0           | ... | 1932735283  |
| <b>min (DSP)</b>      | 0           | 0           | ... | 214748365   |
| <b>Exp. max (DSP)</b> | 0           | 0           | ... | 1932735283  |
| <b>Exp. min (DSP)</b> | 0           | 0           | ... | 214748365   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance max | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |
| Tolerance min | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 58 |
| Max CPU cycles  | 70 |
| Avg CPU cycles  | 60 |



**Verification: MinMaxPeriodic FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-25  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Filter block MinMaxPeriodic.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>      | 1           | 2           | ... | 112         |
| <b>CPU cycles</b>     | 103         | 92          | ... | 96          |
| <i>Inputs</i>         |             |             |     |             |
| <b>In (DSP)</b>       | 0           | -298325298  | ... | 0           |
| <b>phi (DSP)</b>      | -2147483648 | -2028179001 | ... | -2147483648 |
| <b>In</b>             | -0          | -0.139      | ... | 0           |
| <b>phi</b>            | -1          | -0.944      | ... | -1          |
| <i>Outputs</i>        |             |             |     |             |
| <b>max</b>            | 0           | 0           | ... | 0.9         |
| <b>min</b>            | 0           | 0           | ... | 0.1         |
| <b>Exp. max</b>       | 0           | 0           | ... | 0.9         |
| <b>Exp. min</b>       | 0           | 0           | ... | 0.1         |
| <b>max (DSP)</b>      | 0           | 0           | ... | 1932735283  |
| <b>min (DSP)</b>      | 0           | 0           | ... | 214748365   |
| <b>Exp. max (DSP)</b> | 0           | 0           | ... | 1932735283  |
| <b>Exp. min (DSP)</b> | 0           | 0           | ... | 214748365   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance max | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |
| Tolerance min | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 90  |
| Max CPU cycles  | 103 |
| Avg CPU cycles  | 91  |

**Verification: MinMaxPeriodic FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-25  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Filter block MinMaxPeriodic.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>      | 1           | 2           | ... | 112         |
| <b>CPU cycles</b>     | 108         | 88          | ... | 96          |
| <i>Inputs</i>         |             |             |     |             |
| <b>In (DSP)</b>       | 0           | -298325298  | ... | 0           |
| <b>phi (DSP)</b>      | -2147483648 | -2028179001 | ... | -2147483648 |
| <b>In</b>             | -0          | -0.139      | ... | 0           |
| <b>phi</b>            | -1          | -0.944      | ... | -1          |
| <i>Outputs</i>        |             |             |     |             |
| <b>max</b>            | 0           | 0           | ... | 0.9         |
| <b>min</b>            | 0           | 0           | ... | 0.1         |
| <b>Exp. max</b>       | 0           | 0           | ... | 0.9         |
| <b>Exp. min</b>       | 0           | 0           | ... | 0.1         |
| <b>max (DSP)</b>      | 0           | 0           | ... | 1932735283  |
| <b>min (DSP)</b>      | 0           | 0           | ... | 214748365   |
| <b>Exp. max (DSP)</b> | 0           | 0           | ... | 1932735283  |
| <b>Exp. min (DSP)</b> | 0           | 0           | ... | 214748365   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance max | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |
| Tolerance min | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 88  |
| Max CPU cycles  | 108 |
| Avg CPU cycles  | 88  |

**Verification: MinMaxPeriodic FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-25  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Filter block MinMaxPeriodic.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>      | 1           | 2           | ... | 112         |
| <b>CPU cycles</b>     | 142         | 138         | ... | 135         |
| <i>Inputs</i>         |             |             |     |             |
| <b>In (DSP)</b>       | 0           | -298325298  | ... | 0           |
| <b>phi (DSP)</b>      | -2147483648 | -2028179001 | ... | -2147483648 |
| <b>In</b>             | -0          | -0.139      | ... | 0           |
| <b>phi</b>            | -1          | -0.944      | ... | -1          |
| <i>Outputs</i>        |             |             |     |             |
| <b>max</b>            | 0           | 0           | ... | 0.9         |
| <b>min</b>            | 0           | 0           | ... | 0.1         |
| <b>Exp. max</b>       | 0           | 0           | ... | 0.9         |
| <b>Exp. min</b>       | 0           | 0           | ... | 0.1         |
| <b>max (DSP)</b>      | 0           | 0           | ... | 1932735283  |
| <b>min (DSP)</b>      | 0           | 0           | ... | 214748365   |
| <b>Exp. max (DSP)</b> | 0           | 0           | ... | 1932735283  |
| <b>Exp. min (DSP)</b> | 0           | 0           | ... | 214748365   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance max | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |
| Tolerance min | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 135 |
| Max CPU cycles  | 143 |
| Avg CPU cycles  | 140 |

**Verification: MinMaxPeriodic Float32 CPU TMS320F28335**

**Date of Test** 2026-06-25  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Filter block MinMaxPeriodic.

| Test results          |        |        |     |        |
|-----------------------|--------|--------|-----|--------|
| <b>Time step</b>      | 1      | 2      | ... | 112    |
| <b>CPU cycles</b>     | 81     | 81     | ... | 82     |
| <i>Inputs</i>         |        |        |     |        |
| <b>In (DSP)</b>       | -0     | -0.139 | ... | 0      |
| <b>phi (DSP)</b>      | -3.142 | -2.967 | ... | -3.142 |
| <b>In</b>             | -0     | -0.139 | ... | 0      |
| <b>phi</b>            | -3.142 | -2.967 | ... | -3.142 |
| <i>Outputs</i>        |        |        |     |        |
| <b>max</b>            | 0      | 0      | ... | 0.9    |
| <b>min</b>            | 0      | 0      | ... | 0.1    |
| <b>Exp. max</b>       | 0      | 0      | ... | 0.9    |
| <b>Exp. min</b>       | 0      | 0      | ... | 0.1    |
| <b>max (DSP)</b>      | 0      | 0      | ... | 0.9    |
| <b>min (DSP)</b>      | 0      | 0      | ... | 0.1    |
| <b>Exp. max (DSP)</b> | 0      | 0      | ... | 0.9    |
| <b>Exp. min (DSP)</b> | 0      | 0      | ... | 0.1    |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance max | $\pm 4,6566e-08$ ( $\pm 100$ LSB) |
| Tolerance min | $\pm 4,6566e-08$ ( $\pm 100$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 81 |
| Max CPU cycles  | 82 |
| Avg CPU cycles  | 81 |

**Verification: MinMaxPeriodic Float32 CPU TM4C123GH6**

Date of Test 2026-06-25  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for Filter block MinMaxPeriodic.

| Test results   |        |        |     |        |
|----------------|--------|--------|-----|--------|
| Time step      | 1      | 2      | ... | 112    |
| CPU cycles     | 67     | 61     | ... | 55     |
| Inputs         |        |        |     |        |
| In (DSP)       | -0     | -0.139 | ... | 0      |
| phi (DSP)      | -3.142 | -2.967 | ... | -3.142 |
| In             | -0     | -0.139 | ... | 0      |
| phi            | -3.142 | -2.967 | ... | -3.142 |
| Outputs        |        |        |     |        |
| max            | 0      | 0      | ... | 0.9    |
| min            | 0      | 0      | ... | 0.1    |
| Exp. max       | 0      | 0      | ... | 0.9    |
| Exp. min       | 0      | 0      | ... | 0.1    |
| max (DSP)      | 0      | 0      | ... | 0.9    |
| min (DSP)      | 0      | 0      | ... | 0.1    |
| Exp. max (DSP) | 0      | 0      | ... | 0.9    |
| Exp. min (DSP) | 0      | 0      | ... | 0.1    |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance max | $\pm 4,6566e-08$ ( $\pm 100$ LSB) |
| Tolerance min | $\pm 4,6566e-08$ ( $\pm 100$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 55 |
| Max CPU cycles  | 67 |
| Avg CPU cycles  | 62 |

**Verification: MinMaxPeriodic Float32 CPU STM32G474RE**

**Date of Test** 2026-06-25  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Filter block MinMaxPeriodic.

| Test results          |        |        |     |        |
|-----------------------|--------|--------|-----|--------|
| <b>Time step</b>      | 1      | 2      | ... | 112    |
| <b>CPU cycles</b>     | 123    | 123    | ... | 98     |
| <i>Inputs</i>         |        |        |     |        |
| <b>In (DSP)</b>       | -0     | -0.139 | ... | 0      |
| <b>phi (DSP)</b>      | -3.142 | -2.967 | ... | -3.142 |
| <b>In</b>             | -0     | -0.139 | ... | 0      |
| <b>phi</b>            | -3.142 | -2.967 | ... | -3.142 |
| <i>Outputs</i>        |        |        |     |        |
| <b>max</b>            | 0      | 0      | ... | 0.9    |
| <b>min</b>            | 0      | 0      | ... | 0.1    |
| <b>Exp. max</b>       | 0      | 0      | ... | 0.9    |
| <b>Exp. min</b>       | 0      | 0      | ... | 0.1    |
| <b>max (DSP)</b>      | 0      | 0      | ... | 0.9    |
| <b>min (DSP)</b>      | 0      | 0      | ... | 0.1    |
| <b>Exp. max (DSP)</b> | 0      | 0      | ... | 0.9    |
| <b>Exp. min (DSP)</b> | 0      | 0      | ... | 0.1    |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance max | $\pm 4,6566e-08$ ( $\pm 100$ LSB) |
| Tolerance min | $\pm 4,6566e-08$ ( $\pm 100$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 98  |
| Max CPU cycles  | 123 |
| Avg CPU cycles  | 122 |

**Verification: MinMaxPeriodic Float32 CPU STM32F072RB**

**Date of Test** 2026-06-25  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Filter block MinMaxPeriodic.

| Test results          |        |        |     |        |
|-----------------------|--------|--------|-----|--------|
| <b>Time step</b>      | 1      | 2      | ... | 112    |
| <b>CPU cycles</b>     | 514    | 591    | ... | 359    |
| <i>Inputs</i>         |        |        |     |        |
| <b>In (DSP)</b>       | -0     | -0.139 | ... | 0      |
| <b>phi (DSP)</b>      | -3.142 | -2.967 | ... | -3.142 |
| <b>In</b>             | -0     | -0.139 | ... | 0      |
| <b>phi</b>            | -3.142 | -2.967 | ... | -3.142 |
| <i>Outputs</i>        |        |        |     |        |
| <b>max</b>            | 0      | 0      | ... | 0.9    |
| <b>min</b>            | 0      | 0      | ... | 0.1    |
| <b>Exp. max</b>       | 0      | 0      | ... | 0.9    |
| <b>Exp. min</b>       | 0      | 0      | ... | 0.1    |
| <b>max (DSP)</b>      | 0      | 0      | ... | 0.9    |
| <b>min (DSP)</b>      | 0      | 0      | ... | 0.1    |
| <b>Exp. max (DSP)</b> | 0      | 0      | ... | 0.9    |
| <b>Exp. min (DSP)</b> | 0      | 0      | ... | 0.1    |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance max | $\pm 4,6566e-08$ ( $\pm 100$ LSB) |
| Tolerance min | $\pm 4,6566e-08$ ( $\pm 100$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 359 |
| Max CPU cycles  | 669 |
| Avg CPU cycles  | 581 |

**Verification: MinMaxPeriodic Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-25  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Filter block MinMaxPeriodic.

| Test results          |        |        |     |        |
|-----------------------|--------|--------|-----|--------|
| <b>Time step</b>      | 1      | 2      | ... | 112    |
| <b>CPU cycles</b>     | 252    | 276    | ... | 216    |
| <i>Inputs</i>         |        |        |     |        |
| <b>In (DSP)</b>       | -0     | -0.139 | ... | 0      |
| <b>phi (DSP)</b>      | -3.142 | -2.967 | ... | -3.142 |
| <b>In</b>             | -0     | -0.139 | ... | 0      |
| <b>phi</b>            | -3.142 | -2.967 | ... | -3.142 |
| <i>Outputs</i>        |        |        |     |        |
| <b>max</b>            | 0      | 0      | ... | 0.9    |
| <b>min</b>            | 0      | 0      | ... | 0.1    |
| <b>Exp. max</b>       | 0      | 0      | ... | 0.9    |
| <b>Exp. min</b>       | 0      | 0      | ... | 0.1    |
| <b>max (DSP)</b>      | 0      | 0      | ... | 0.9    |
| <b>min (DSP)</b>      | 0      | 0      | ... | 0.1    |
| <b>Exp. max (DSP)</b> | 0      | 0      | ... | 0.9    |
| <b>Exp. min (DSP)</b> | 0      | 0      | ... | 0.1    |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance max | $\pm 4,6566e-08$ ( $\pm 100$ LSB) |
| Tolerance min | $\pm 4,6566e-08$ ( $\pm 100$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 216 |
| Max CPU cycles  | 281 |
| Avg CPU cycles  | 271 |



**Verification: MinMaxPeriodic Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-25  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Filter block MinMaxPeriodic.

| Test results          |        |        |     |        |
|-----------------------|--------|--------|-----|--------|
| <b>Time step</b>      | 1      | 2      | ... | 112    |
| <b>CPU cycles</b>     | 585    | 691    | ... | 441    |
| <i>Inputs</i>         |        |        |     |        |
| <b>In (DSP)</b>       | -0     | -0.139 | ... | 0      |
| <b>phi (DSP)</b>      | -3.142 | -2.967 | ... | -3.142 |
| <b>In</b>             | -0     | -0.139 | ... | 0      |
| <b>phi</b>            | -3.142 | -2.967 | ... | -3.142 |
| <i>Outputs</i>        |        |        |     |        |
| <b>max</b>            | 0      | 0      | ... | 0.9    |
| <b>min</b>            | 0      | 0      | ... | 0.1    |
| <b>Exp. max</b>       | 0      | 0      | ... | 0.9    |
| <b>Exp. min</b>       | 0      | 0      | ... | 0.1    |
| <b>max (DSP)</b>      | 0      | 0      | ... | 0.9    |
| <b>min (DSP)</b>      | 0      | 0      | ... | 0.1    |
| <b>Exp. max (DSP)</b> | 0      | 0      | ... | 0.9    |
| <b>Exp. min (DSP)</b> | 0      | 0      | ... | 0.1    |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance max | $\pm 4,6566e-08$ ( $\pm 100$ LSB) |
| Tolerance min | $\pm 4,6566e-08$ ( $\pm 100$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 441 |
| Max CPU cycles  | 703 |
| Avg CPU cycles  | 666 |

**Verification: MinMaxPeriodic Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-25  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Filter block MinMaxPeriodic.

| Test results          |        |        |     |        |
|-----------------------|--------|--------|-----|--------|
| <b>Time step</b>      | 1      | 2      | ... | 112    |
| <b>CPU cycles</b>     | 119    | 91     | ... | 90     |
| <i>Inputs</i>         |        |        |     |        |
| <b>In (DSP)</b>       | -0     | -0.139 | ... | 0      |
| <b>phi (DSP)</b>      | -3.142 | -2.967 | ... | -3.142 |
| <b>In</b>             | -0     | -0.139 | ... | 0      |
| <b>phi</b>            | -3.142 | -2.967 | ... | -3.142 |
| <i>Outputs</i>        |        |        |     |        |
| <b>max</b>            | 0      | 0      | ... | 0.9    |
| <b>min</b>            | 0      | 0      | ... | 0.1    |
| <b>Exp. max</b>       | 0      | 0      | ... | 0.9    |
| <b>Exp. min</b>       | 0      | 0      | ... | 0.1    |
| <b>max (DSP)</b>      | 0      | 0      | ... | 0.9    |
| <b>min (DSP)</b>      | 0      | 0      | ... | 0.1    |
| <b>Exp. max (DSP)</b> | 0      | 0      | ... | 0.9    |
| <b>Exp. min (DSP)</b> | 0      | 0      | ... | 0.1    |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance max | $\pm 4,6566e-08$ ( $\pm 100$ LSB) |
| Tolerance min | $\pm 4,6566e-08$ ( $\pm 100$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 89  |
| Max CPU cycles  | 119 |
| Avg CPU cycles  | 90  |

**Verification: MinMaxPeriodic Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-25  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Filter block MinMaxPeriodic.

| Test results          |        |        |     |        |
|-----------------------|--------|--------|-----|--------|
| <b>Time step</b>      | 1      | 2      | ... | 112    |
| <b>CPU cycles</b>     | 77     | 77     | ... | 78     |
| <i>Inputs</i>         |        |        |     |        |
| <b>In (DSP)</b>       | -0     | -0.139 | ... | 0      |
| <b>phi (DSP)</b>      | -3.142 | -2.967 | ... | -3.142 |
| <b>In</b>             | -0     | -0.139 | ... | 0      |
| <b>phi</b>            | -3.142 | -2.967 | ... | -3.142 |
| <i>Outputs</i>        |        |        |     |        |
| <b>max</b>            | 0      | 0      | ... | 0.9    |
| <b>min</b>            | 0      | 0      | ... | 0.1    |
| <b>Exp. max</b>       | 0      | 0      | ... | 0.9    |
| <b>Exp. min</b>       | 0      | 0      | ... | 0.1    |
| <b>max (DSP)</b>      | 0      | 0      | ... | 0.9    |
| <b>min (DSP)</b>      | 0      | 0      | ... | 0.1    |
| <b>Exp. max (DSP)</b> | 0      | 0      | ... | 0.9    |
| <b>Exp. min (DSP)</b> | 0      | 0      | ... | 0.1    |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance max | $\pm 4,6566e-08$ ( $\pm 100$ LSB) |
| Tolerance min | $\pm 4,6566e-08$ ( $\pm 100$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 77 |
| Max CPU cycles  | 78 |
| Avg CPU cycles  | 77 |

## Block: NotchBiQ



Calculates the filter coefficients for a second order notch filter and performs filtering on input signal.

Second order transfer function used:

$$H(z) = (b_0 \cdot z^2 + b_1 \cdot z + b_2) / (z^2 + a_1 \cdot z + a_2)$$

| Inports |             |
|---------|-------------|
| In      | Input In(k) |

| Outports |               |
|----------|---------------|
| Out      | Output Out(k) |

| Mask Parameters |    |                                                                          |
|-----------------|----|--------------------------------------------------------------------------|
| Name            | ID | Description                                                              |
| method          | 1  | Selection between bilinear and matched Z-transform discretization method |
| fn              | 2  | Notching frequency in Hz                                                 |
| Q               | 3  | Defines a quality factor of the filter                                   |
| ts_fact         | 4  | Multiplication factor of base sampling time (in integer format)          |

### Description:

Calculation:

$$\text{Out}(k) = \text{In}(k) \cdot H(z)$$

The transfer function  $H(z)$  of the filter is

$$H(z) = \frac{b_0 + b_1 z^{-1} + b_2 z^{-2}}{1 + a_1 z^{-1} + a_2 z^{-2}}$$

with coefficients derived from the transfer function

$$H(s) = \frac{s^2 + \omega_0^2}{s^2 + \frac{\omega_0}{Q} s + \omega_0^2}$$

Two methods of discretizing a continuous transfer function are available: bilinear and matching.

Warning: In some cases, the function is very sensitive to the accuracy of the coefficients. Therefore, using a fixed-point implementation can sometimes give inaccurate results.

To illustrate this issue, see step responses in figures 17 and 18 below. Filter settings are  $f_n = 50$  Hz,  $Q = 10$ ,  $f_s = 10$  kHz.




Figure 17: Step response for  $ts\_fact = 1$ .




Figure 18: Step response for  $t\_fact = 10$ .

### Implementations:

- FiP16**      16 Bit Fixed Point Implementation
- FiP32**      32 Bit Fixed Point Implementation
- Float32**    32 Bit Floating Point Implementation
- Float64**    64 Bit Floating Point Implementation

### Implementation: FiP16

16 Bit Fixed Point Implementation

| Inports Data Type  |       |
|--------------------|-------|
| In                 | int16 |
| Outports Data Type |       |
| Out                | int16 |

### Implementation: FiP32

---

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

---

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

---

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: NotchBiQ FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-25  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Filter block NotchBiQ.

| Test results   |          |    |    |      |     |       |
|----------------|----------|----|----|------|-----|-------|
| Time step      | 1        | 2  | 3  | 4    | ... | 101   |
| CPU cycles     | 93       | 93 | 93 | 93   | ... | 93    |
| Inputs         |          |    |    |      |     |       |
| In (DSP)       | 0        | 0  | 0  | 4915 | ... | 3277  |
| In             | 0        | 0  | 0  | 0.15 | ... | 0.1   |
| Parameters     |          |    |    |      |     |       |
| method         | bilinear |    |    |      |     |       |
| fn             | 50       |    |    |      |     |       |
| Q              | 25       |    |    |      |     |       |
| ts_fact        | 1        |    |    |      |     |       |
| Outputs        |          |    |    |      |     |       |
| Out            | 0        | 0  | 0  | 0.15 | ... | 0.072 |
| Exp. Out       | 0        | 0  | 0  | 0.15 | ... | 0.098 |
| Out (DSP)      | 0        | 0  | 0  | 4911 | ... | 2356  |
| Exp. Out (DSP) | 0        | 0  | 0  | 4912 | ... | 3214  |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 2,7466e-02$ ( $\pm 900$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 93 |
| Max CPU cycles  | 93 |
| Avg CPU cycles  | 93 |

**Test case: Conversion test****OK**

Conversion test for Filter block NotchBiQ.

| Test results          |          |          |          |          |     |          |
|-----------------------|----------|----------|----------|----------|-----|----------|
| Time step             | 1        | 2        | 3        | 4        | ... | 10       |
| Mask parameters       |          |          |          |          |     |          |
| method                | bilinear | bilinear | bilinear | bilinear | ... | bilinear |
| fn                    | 10       | 231.111  | 452.222  | 673.333  | ... | 2000     |
| Q                     | 10       | 20       | 30       | 40       | ... | 100      |
| ts_fact               | 1        | 1        | 1        | 1        | ... | 1        |
| Controller parameters |          |          |          |          |     |          |
| b2                    | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| a1                    | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| a2                    | 32747    | 32532    | 32463    | 32433    | ... | 32458    |
| sfra2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb0                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb1                 | 14       | 14       | 14       | 14       | ... | 15       |
| sfrb2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfra1                 | 14       | 14       | 14       | 14       | ... | 15       |
| b0                    | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| b1                    | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| Exp. b2               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. a1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| Exp. a2               | 32747    | 32532    | 32463    | 32433    | ... | 32458    |
| Exp. sfra2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb0            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. sfrb2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfra1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. b0               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. b1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |



| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block NotchBiQ.

| Test results          |          |          |          |          |     |          |
|-----------------------|----------|----------|----------|----------|-----|----------|
| Time step             | 1        | 2        | 3        | 4        | ... | 10       |
| Mask parameters       |          |          |          |          |     |          |
| method                | bilinear | bilinear | bilinear | bilinear | ... | bilinear |
| fn                    | 10       | 231.111  | 452.222  | 673.333  | ... | 2000     |
| Q                     | 10       | 20       | 30       | 40       | ... | 100      |
| ts_fact               | 1        | 1        | 1        | 1        | ... | 1        |
| Controller parameters |          |          |          |          |     |          |
| b2                    | 32757    | 32649    | 32615    | 32600    | ... | 32612    |
| a1                    | -32757   | -32306   | -31307   | -29726   | ... | -20155   |
| a2                    | 32747    | 32531    | 32463    | 32433    | ... | 32457    |
| sfra2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb0                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb1                 | 14       | 14       | 14       | 14       | ... | 15       |
| sfrb2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfra1                 | 14       | 14       | 14       | 14       | ... | 15       |
| b0                    | 32757    | 32649    | 32615    | 32600    | ... | 32612    |
| b1                    | -32757   | -32306   | -31307   | -29726   | ... | -20155   |
| Exp. b2               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. a1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| Exp. a2               | 32747    | 32532    | 32463    | 32433    | ... | 32458    |
| Exp. sfra2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb0            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. sfrb2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfra1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. b0               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. b1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 1,0000e+00$ |
| Tolerance a1    | $\pm 1,0000e+00$ |
| Tolerance a2    | $\pm 1,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 1,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3267 |
| Max CPU cycles  | 3843 |
| Avg CPU cycles  | 3727 |

**Verification: NotchBiQ FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-25  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Filter block NotchBiQ.

| Test results   |          |     |     |      |     |       |
|----------------|----------|-----|-----|------|-----|-------|
| Time step      | 1        | 2   | 3   | 4    | ... | 101   |
| CPU cycles     | 116      | 116 | 116 | 116  | ... | 116   |
| Inputs         |          |     |     |      |     |       |
| In (DSP)       | 0        | 0   | 0   | 4915 | ... | 3277  |
| In             | 0        | 0   | 0   | 0.15 | ... | 0.1   |
| Parameters     |          |     |     |      |     |       |
| method         | bilinear |     |     |      |     |       |
| fn             | 50       |     |     |      |     |       |
| Q              | 25       |     |     |      |     |       |
| ts_fact        | 1        |     |     |      |     |       |
| Outputs        |          |     |     |      |     |       |
| Out            | 0        | 0   | 0   | 0.15 | ... | 0.072 |
| Exp. Out       | 0        | 0   | 0   | 0.15 | ... | 0.098 |
| Out (DSP)      | 0        | 0   | 0   | 4911 | ... | 2356  |
| Exp. Out (DSP) | 0        | 0   | 0   | 4912 | ... | 3214  |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 2,7466e-02$ ( $\pm 900$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 116 |
| Max CPU cycles  | 116 |
| Avg CPU cycles  | 116 |

**Test case: Conversion test****OK**

Conversion test for Filter block NotchBiQ.

| Test results          |          |          |          |          |     |          |
|-----------------------|----------|----------|----------|----------|-----|----------|
| Time step             | 1        | 2        | 3        | 4        | ... | 10       |
| Mask parameters       |          |          |          |          |     |          |
| method                | bilinear | bilinear | bilinear | bilinear | ... | bilinear |
| fn                    | 10       | 231.111  | 452.222  | 673.333  | ... | 2000     |
| Q                     | 10       | 20       | 30       | 40       | ... | 100      |
| ts_fact               | 1        | 1        | 1        | 1        | ... | 1        |
| Controller parameters |          |          |          |          |     |          |
| b2                    | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| a1                    | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| a2                    | 32747    | 32532    | 32463    | 32433    | ... | 32458    |
| sfra2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb0                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb1                 | 14       | 14       | 14       | 14       | ... | 15       |
| sfrb2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfra1                 | 14       | 14       | 14       | 14       | ... | 15       |
| b0                    | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| b1                    | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| Exp. b2               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. a1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| Exp. a2               | 32747    | 32532    | 32463    | 32433    | ... | 32458    |
| Exp. sfra2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb0            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. sfrb2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfra1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. b0               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. b1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block NotchBiQ.

| Test results          |          |          |          |          |     |          |
|-----------------------|----------|----------|----------|----------|-----|----------|
| Time step             | 1        | 2        | 3        | 4        | ... | 10       |
| Mask parameters       |          |          |          |          |     |          |
| method                | bilinear | bilinear | bilinear | bilinear | ... | bilinear |
| fn                    | 10       | 231.111  | 452.222  | 673.333  | ... | 2000     |
| Q                     | 10       | 20       | 30       | 40       | ... | 100      |
| ts_fact               | 1        | 1        | 1        | 1        | ... | 1        |
| Controller parameters |          |          |          |          |     |          |
| b2                    | 32757    | 32649    | 32615    | 32600    | ... | 32612    |
| a1                    | -32757   | -32306   | -31307   | -29726   | ... | -20155   |
| a2                    | 32747    | 32531    | 32463    | 32433    | ... | 32457    |
| sfra2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb0                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb1                 | 14       | 14       | 14       | 14       | ... | 15       |
| sfrb2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfra1                 | 14       | 14       | 14       | 14       | ... | 15       |
| b0                    | 32757    | 32649    | 32615    | 32600    | ... | 32612    |
| b1                    | -32757   | -32306   | -31307   | -29726   | ... | -20155   |
| Exp. b2               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. a1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| Exp. a2               | 32747    | 32532    | 32463    | 32433    | ... | 32458    |
| Exp. sfra2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb0            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. sfrb2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfra1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. b0               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. b1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 1,0000e+00$ |
| Tolerance a1    | $\pm 1,0000e+00$ |
| Tolerance a2    | $\pm 1,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 1,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 7494 |
| Max CPU cycles  | 8524 |
| Avg CPU cycles  | 8318 |



**Verification: NotchBiQ FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-25  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Filter block NotchBiQ.

| Test results   |          |     |     |      |     |       |
|----------------|----------|-----|-----|------|-----|-------|
| Time step      | 1        | 2   | 3   | 4    | ... | 101   |
| CPU cycles     | 113      | 113 | 113 | 113  | ... | 113   |
| Inputs         |          |     |     |      |     |       |
| In (DSP)       | 0        | 0   | 0   | 4915 | ... | 3277  |
| In             | 0        | 0   | 0   | 0.15 | ... | 0.1   |
| Parameters     |          |     |     |      |     |       |
| method         | bilinear |     |     |      |     |       |
| fn             | 50       |     |     |      |     |       |
| Q              | 25       |     |     |      |     |       |
| ts_fact        | 1        |     |     |      |     |       |
| Outputs        |          |     |     |      |     |       |
| Out            | 0        | 0   | 0   | 0.15 | ... | 0.072 |
| Exp. Out       | 0        | 0   | 0   | 0.15 | ... | 0.098 |
| Out (DSP)      | 0        | 0   | 0   | 4911 | ... | 2356  |
| Exp. Out (DSP) | 0        | 0   | 0   | 4912 | ... | 3214  |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 2,7466e-02$ ( $\pm 900$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 113 |
| Max CPU cycles  | 113 |
| Avg CPU cycles  | 113 |

**Test case: Conversion test****OK**

Conversion test for Filter block NotchBiQ.

| Test results          |          |          |          |          |     |          |
|-----------------------|----------|----------|----------|----------|-----|----------|
| Time step             | 1        | 2        | 3        | 4        | ... | 10       |
| Mask parameters       |          |          |          |          |     |          |
| method                | bilinear | bilinear | bilinear | bilinear | ... | bilinear |
| fn                    | 10       | 231.111  | 452.222  | 673.333  | ... | 2000     |
| Q                     | 10       | 20       | 30       | 40       | ... | 100      |
| ts_fact               | 1        | 1        | 1        | 1        | ... | 1        |
| Controller parameters |          |          |          |          |     |          |
| b2                    | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| a1                    | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| a2                    | 32747    | 32532    | 32463    | 32433    | ... | 32458    |
| sfra2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb0                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb1                 | 14       | 14       | 14       | 14       | ... | 15       |
| sfrb2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfra1                 | 14       | 14       | 14       | 14       | ... | 15       |
| b0                    | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| b1                    | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| Exp. b2               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. a1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| Exp. a2               | 32747    | 32532    | 32463    | 32433    | ... | 32458    |
| Exp. sfra2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb0            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. sfrb2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfra1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. b0               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. b1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block NotchBiQ.

| Test results          |          |          |          |          |     |          |
|-----------------------|----------|----------|----------|----------|-----|----------|
| Time step             | 1        | 2        | 3        | 4        | ... | 10       |
| Mask parameters       |          |          |          |          |     |          |
| method                | bilinear | bilinear | bilinear | bilinear | ... | bilinear |
| fn                    | 10       | 231.111  | 452.222  | 673.333  | ... | 2000     |
| Q                     | 10       | 20       | 30       | 40       | ... | 100      |
| ts_fact               | 1        | 1        | 1        | 1        | ... | 1        |
| Controller parameters |          |          |          |          |     |          |
| b2                    | 32757    | 32649    | 32615    | 32600    | ... | 32612    |
| a1                    | -32757   | -32306   | -31307   | -29726   | ... | -20155   |
| a2                    | 32747    | 32531    | 32463    | 32433    | ... | 32457    |
| sfra2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb0                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb1                 | 14       | 14       | 14       | 14       | ... | 15       |
| sfrb2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfra1                 | 14       | 14       | 14       | 14       | ... | 15       |
| b0                    | 32757    | 32649    | 32615    | 32600    | ... | 32612    |
| b1                    | -32757   | -32306   | -31307   | -29726   | ... | -20155   |
| Exp. b2               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. a1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| Exp. a2               | 32747    | 32532    | 32463    | 32433    | ... | 32458    |
| Exp. sfra2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb0            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. sfrb2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfra1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. b0               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. b1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 1,0000e+00$ |
| Tolerance a1    | $\pm 1,0000e+00$ |
| Tolerance a2    | $\pm 1,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 1,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 5706 |
| Max CPU cycles  | 6498 |
| Avg CPU cycles  | 6339 |

**Verification: NotchBiQ FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-25  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Filter block NotchBiQ.

| Test results   |          |     |     |      |     |       |
|----------------|----------|-----|-----|------|-----|-------|
| Time step      | 1        | 2   | 3   | 4    | ... | 101   |
| CPU cycles     | 144      | 144 | 144 | 144  | ... | 144   |
| Inputs         |          |     |     |      |     |       |
| In (DSP)       | 0        | 0   | 0   | 4915 | ... | 3277  |
| In             | 0        | 0   | 0   | 0.15 | ... | 0.1   |
| Parameters     |          |     |     |      |     |       |
| method         | bilinear |     |     |      |     |       |
| fn             | 50       |     |     |      |     |       |
| Q              | 25       |     |     |      |     |       |
| ts_fact        | 1        |     |     |      |     |       |
| Outputs        |          |     |     |      |     |       |
| Out            | 0        | 0   | 0   | 0.15 | ... | 0.072 |
| Exp. Out       | 0        | 0   | 0   | 0.15 | ... | 0.098 |
| Out (DSP)      | 0        | 0   | 0   | 4911 | ... | 2356  |
| Exp. Out (DSP) | 0        | 0   | 0   | 4912 | ... | 3214  |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 2,7466e-02$ ( $\pm 900$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 144 |
| Max CPU cycles  | 144 |
| Avg CPU cycles  | 144 |

**Test case: Conversion test****OK**

Conversion test for Filter block NotchBiQ.

| Test results          |          |          |          |          |     |          |
|-----------------------|----------|----------|----------|----------|-----|----------|
| Time step             | 1        | 2        | 3        | 4        | ... | 10       |
| Mask parameters       |          |          |          |          |     |          |
| method                | bilinear | bilinear | bilinear | bilinear | ... | bilinear |
| fn                    | 10       | 231.111  | 452.222  | 673.333  | ... | 2000     |
| Q                     | 10       | 20       | 30       | 40       | ... | 100      |
| ts_fact               | 1        | 1        | 1        | 1        | ... | 1        |
| Controller parameters |          |          |          |          |     |          |
| b2                    | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| a1                    | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| a2                    | 32747    | 32532    | 32463    | 32433    | ... | 32458    |
| sfra2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb0                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb1                 | 14       | 14       | 14       | 14       | ... | 15       |
| sfrb2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfra1                 | 14       | 14       | 14       | 14       | ... | 15       |
| b0                    | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| b1                    | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| Exp. b2               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. a1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| Exp. a2               | 32747    | 32532    | 32463    | 32433    | ... | 32458    |
| Exp. sfra2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb0            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. sfrb2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfra1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. b0               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. b1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Filter block NotchBiQ.



| Test results          |          |          |          |          |     |          |
|-----------------------|----------|----------|----------|----------|-----|----------|
| Time step             | 1        | 2        | 3        | 4        | ... | 10       |
| Mask parameters       |          |          |          |          |     |          |
| method                | bilinear | bilinear | bilinear | bilinear | ... | bilinear |
| fn                    | 10       | 231.111  | 452.222  | 673.333  | ... | 2000     |
| Q                     | 10       | 20       | 30       | 40       | ... | 100      |
| ts_fact               | 1        | 1        | 1        | 1        | ... | 1        |
| Controller parameters |          |          |          |          |     |          |
| b2                    | 32757    | 32649    | 32615    | 32600    | ... | 32612    |
| a1                    | -32757   | -32306   | -31307   | -29726   | ... | -20155   |
| a2                    | 32747    | 32531    | 32463    | 32433    | ... | 32457    |
| sfra2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb0                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb1                 | 14       | 14       | 14       | 14       | ... | 15       |
| sfrb2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfra1                 | 14       | 14       | 14       | 14       | ... | 15       |
| b0                    | 32757    | 32649    | 32615    | 32600    | ... | 32612    |
| b1                    | -32757   | -32306   | -31307   | -29726   | ... | -20155   |
| Exp. b2               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. a1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| Exp. a2               | 32747    | 32532    | 32463    | 32433    | ... | 32458    |
| Exp. sfra2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb0            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. sfrb2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfra1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. b0               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. b1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 1,0000e+00$ |
| Tolerance a1    | $\pm 1,0000e+00$ |
| Tolerance a2    | $\pm 1,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 1,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 26082 |
| Max CPU cycles  | 30598 |
| Avg CPU cycles  | 29068 |

**Verification: NotchBiQ FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-25  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Filter block NotchBiQ.

| Test results   |          |     |     |      |     |       |
|----------------|----------|-----|-----|------|-----|-------|
| Time step      | 1        | 2   | 3   | 4    | ... | 101   |
| CPU cycles     | 133      | 133 | 133 | 133  | ... | 133   |
| Inputs         |          |     |     |      |     |       |
| In (DSP)       | 0        | 0   | 0   | 4915 | ... | 3277  |
| In             | 0        | 0   | 0   | 0.15 | ... | 0.1   |
| Parameters     |          |     |     |      |     |       |
| method         | bilinear |     |     |      |     |       |
| fn             | 50       |     |     |      |     |       |
| Q              | 25       |     |     |      |     |       |
| ts_fact        | 1        |     |     |      |     |       |
| Outputs        |          |     |     |      |     |       |
| Out            | 0        | 0   | 0   | 0.15 | ... | 0.072 |
| Exp. Out       | 0        | 0   | 0   | 0.15 | ... | 0.098 |
| Out (DSP)      | 0        | 0   | 0   | 4911 | ... | 2356  |
| Exp. Out (DSP) | 0        | 0   | 0   | 4912 | ... | 3214  |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 2,7466e-02$ ( $\pm 900$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 133 |
| Max CPU cycles  | 133 |
| Avg CPU cycles  | 133 |

**Test case: Conversion test****OK**

Conversion test for Filter block NotchBiQ.

| Test results          |          |          |          |          |     |          |
|-----------------------|----------|----------|----------|----------|-----|----------|
| Time step             | 1        | 2        | 3        | 4        | ... | 10       |
| Mask parameters       |          |          |          |          |     |          |
| method                | bilinear | bilinear | bilinear | bilinear | ... | bilinear |
| fn                    | 10       | 231.111  | 452.222  | 673.333  | ... | 2000     |
| Q                     | 10       | 20       | 30       | 40       | ... | 100      |
| ts_fact               | 1        | 1        | 1        | 1        | ... | 1        |
| Controller parameters |          |          |          |          |     |          |
| b2                    | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| a1                    | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| a2                    | 32747    | 32532    | 32463    | 32433    | ... | 32458    |
| sfra2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb0                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb1                 | 14       | 14       | 14       | 14       | ... | 15       |
| sfrb2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfra1                 | 14       | 14       | 14       | 14       | ... | 15       |
| b0                    | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| b1                    | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| Exp. b2               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. a1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| Exp. a2               | 32747    | 32532    | 32463    | 32433    | ... | 32458    |
| Exp. sfra2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb0            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. sfrb2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfra1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. b0               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. b1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block NotchBiQ.

| Test results          |          |          |          |          |     |          |
|-----------------------|----------|----------|----------|----------|-----|----------|
| Time step             | 1        | 2        | 3        | 4        | ... | 10       |
| Mask parameters       |          |          |          |          |     |          |
| method                | bilinear | bilinear | bilinear | bilinear | ... | bilinear |
| fn                    | 10       | 231.111  | 452.222  | 673.333  | ... | 2000     |
| Q                     | 10       | 20       | 30       | 40       | ... | 100      |
| ts_fact               | 1        | 1        | 1        | 1        | ... | 1        |
| Controller parameters |          |          |          |          |     |          |
| b2                    | 32757    | 32649    | 32615    | 32600    | ... | 32612    |
| a1                    | -32757   | -32306   | -31307   | -29726   | ... | -20155   |
| a2                    | 32747    | 32531    | 32463    | 32433    | ... | 32457    |
| sfra2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb0                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb1                 | 14       | 14       | 14       | 14       | ... | 15       |
| sfrb2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfra1                 | 14       | 14       | 14       | 14       | ... | 15       |
| b0                    | 32757    | 32649    | 32615    | 32600    | ... | 32612    |
| b1                    | -32757   | -32306   | -31307   | -29726   | ... | -20155   |
| Exp. b2               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. a1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| Exp. a2               | 32747    | 32532    | 32463    | 32433    | ... | 32458    |
| Exp. sfra2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb0            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. sfrb2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfra1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. b0               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. b1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 1,0000e+00$ |
| Tolerance a1    | $\pm 1,0000e+00$ |
| Tolerance a2    | $\pm 1,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 1,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 20698 |
| Max CPU cycles  | 22002 |
| Avg CPU cycles  | 21690 |

**Verification: NotchBiQ FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-25  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Filter block NotchBiQ.

| Test results   |          |     |     |      |     |       |
|----------------|----------|-----|-----|------|-----|-------|
| Time step      | 1        | 2   | 3   | 4    | ... | 101   |
| CPU cycles     | 147      | 147 | 147 | 147  | ... | 147   |
| Inputs         |          |     |     |      |     |       |
| In (DSP)       | 0        | 0   | 0   | 4915 | ... | 3277  |
| In             | 0        | 0   | 0   | 0.15 | ... | 0.1   |
| Parameters     |          |     |     |      |     |       |
| method         | bilinear |     |     |      |     |       |
| fn             | 50       |     |     |      |     |       |
| Q              | 25       |     |     |      |     |       |
| ts_fact        | 1        |     |     |      |     |       |
| Outputs        |          |     |     |      |     |       |
| Out            | 0        | 0   | 0   | 0.15 | ... | 0.072 |
| Exp. Out       | 0        | 0   | 0   | 0.15 | ... | 0.098 |
| Out (DSP)      | 0        | 0   | 0   | 4911 | ... | 2356  |
| Exp. Out (DSP) | 0        | 0   | 0   | 4912 | ... | 3214  |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 2,7466e-02$ ( $\pm 900$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 147 |
| Max CPU cycles  | 206 |
| Avg CPU cycles  | 147 |

**Test case: Conversion test****OK**

Conversion test for Filter block NotchBiQ.



| Test results          |          |          |          |          |     |          |
|-----------------------|----------|----------|----------|----------|-----|----------|
| Time step             | 1        | 2        | 3        | 4        | ... | 10       |
| Mask parameters       |          |          |          |          |     |          |
| method                | bilinear | bilinear | bilinear | bilinear | ... | bilinear |
| fn                    | 10       | 231.111  | 452.222  | 673.333  | ... | 2000     |
| Q                     | 10       | 20       | 30       | 40       | ... | 100      |
| ts_fact               | 1        | 1        | 1        | 1        | ... | 1        |
| Controller parameters |          |          |          |          |     |          |
| b2                    | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| a1                    | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| a2                    | 32747    | 32532    | 32463    | 32433    | ... | 32458    |
| sfra2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb0                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb1                 | 14       | 14       | 14       | 14       | ... | 15       |
| sfrb2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfra1                 | 14       | 14       | 14       | 14       | ... | 15       |
| b0                    | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| b1                    | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| Exp. b2               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. a1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| Exp. a2               | 32747    | 32532    | 32463    | 32433    | ... | 32458    |
| Exp. sfra2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb0            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. sfrb2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfra1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. b0               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. b1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block NotchBiQ.

| Test results          |          |          |          |          |     |          |
|-----------------------|----------|----------|----------|----------|-----|----------|
| Time step             | 1        | 2        | 3        | 4        | ... | 10       |
| Mask parameters       |          |          |          |          |     |          |
| method                | bilinear | bilinear | bilinear | bilinear | ... | bilinear |
| fn                    | 10       | 231.111  | 452.222  | 673.333  | ... | 2000     |
| Q                     | 10       | 20       | 30       | 40       | ... | 100      |
| ts_fact               | 1        | 1        | 1        | 1        | ... | 1        |
| Controller parameters |          |          |          |          |     |          |
| b2                    | 32757    | 32649    | 32615    | 32600    | ... | 32612    |
| a1                    | -32757   | -32306   | -31307   | -29726   | ... | -20155   |
| a2                    | 32747    | 32531    | 32463    | 32433    | ... | 32457    |
| sfra2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb0                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb1                 | 14       | 14       | 14       | 14       | ... | 15       |
| sfrb2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfra1                 | 14       | 14       | 14       | 14       | ... | 15       |
| b0                    | 32757    | 32649    | 32615    | 32600    | ... | 32612    |
| b1                    | -32757   | -32306   | -31307   | -29726   | ... | -20155   |
| Exp. b2               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. a1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| Exp. a2               | 32747    | 32532    | 32463    | 32433    | ... | 32458    |
| Exp. sfra2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb0            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. sfrb2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfra1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. b0               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. b1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 1,0000e+00$ |
| Tolerance a1    | $\pm 1,0000e+00$ |
| Tolerance a2    | $\pm 1,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 1,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2887 |
| Max CPU cycles  | 3139 |
| Avg CPU cycles  | 3088 |

**Verification: NotchBiQ FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-25  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Filter block NotchBiQ.

| Test results   |          |     |     |      |     |       |
|----------------|----------|-----|-----|------|-----|-------|
| Time step      | 1        | 2   | 3   | 4    | ... | 101   |
| CPU cycles     | 153      | 127 | 127 | 127  | ... | 127   |
| Inputs         |          |     |     |      |     |       |
| In (DSP)       | 0        | 0   | 0   | 4915 | ... | 3277  |
| In             | 0        | 0   | 0   | 0.15 | ... | 0.1   |
| Parameters     |          |     |     |      |     |       |
| method         | bilinear |     |     |      |     |       |
| fn             | 50       |     |     |      |     |       |
| Q              | 25       |     |     |      |     |       |
| ts_fact        | 1        |     |     |      |     |       |
| Outputs        |          |     |     |      |     |       |
| Out            | 0        | 0   | 0   | 0.15 | ... | 0.072 |
| Exp. Out       | 0        | 0   | 0   | 0.15 | ... | 0.098 |
| Out (DSP)      | 0        | 0   | 0   | 4911 | ... | 2356  |
| Exp. Out (DSP) | 0        | 0   | 0   | 4912 | ... | 3214  |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 2,7466e-02$ ( $\pm 900$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 127 |
| Max CPU cycles  | 153 |
| Avg CPU cycles  | 127 |

**Test case: Conversion test****OK**

Conversion test for Filter block NotchBiQ.

| Test results          |          |          |          |          |     |          |
|-----------------------|----------|----------|----------|----------|-----|----------|
| Time step             | 1        | 2        | 3        | 4        | ... | 10       |
| Mask parameters       |          |          |          |          |     |          |
| method                | bilinear | bilinear | bilinear | bilinear | ... | bilinear |
| fn                    | 10       | 231.111  | 452.222  | 673.333  | ... | 2000     |
| Q                     | 10       | 20       | 30       | 40       | ... | 100      |
| ts_fact               | 1        | 1        | 1        | 1        | ... | 1        |
| Controller parameters |          |          |          |          |     |          |
| b2                    | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| a1                    | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| a2                    | 32747    | 32532    | 32463    | 32433    | ... | 32458    |
| sfra2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb0                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb1                 | 14       | 14       | 14       | 14       | ... | 15       |
| sfrb2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfra1                 | 14       | 14       | 14       | 14       | ... | 15       |
| b0                    | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| b1                    | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| Exp. b2               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. a1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| Exp. a2               | 32747    | 32532    | 32463    | 32433    | ... | 32458    |
| Exp. sfra2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb0            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. sfrb2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfra1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. b0               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. b1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block NotchBiQ.

| Test results          |          |          |          |          |     |          |
|-----------------------|----------|----------|----------|----------|-----|----------|
| Time step             | 1        | 2        | 3        | 4        | ... | 10       |
| Mask parameters       |          |          |          |          |     |          |
| method                | bilinear | bilinear | bilinear | bilinear | ... | bilinear |
| fn                    | 10       | 231.111  | 452.222  | 673.333  | ... | 2000     |
| Q                     | 10       | 20       | 30       | 40       | ... | 100      |
| ts_fact               | 1        | 1        | 1        | 1        | ... | 1        |
| Controller parameters |          |          |          |          |     |          |
| b2                    | 32757    | 32649    | 32615    | 32600    | ... | 32612    |
| a1                    | -32757   | -32306   | -31307   | -29726   | ... | -20155   |
| a2                    | 32747    | 32531    | 32463    | 32433    | ... | 32457    |
| sfra2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb0                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb1                 | 14       | 14       | 14       | 14       | ... | 15       |
| sfrb2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfra1                 | 14       | 14       | 14       | 14       | ... | 15       |
| b0                    | 32757    | 32649    | 32615    | 32600    | ... | 32612    |
| b1                    | -32757   | -32306   | -31307   | -29726   | ... | -20155   |
| Exp. b2               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. a1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| Exp. a2               | 32747    | 32532    | 32463    | 32433    | ... | 32458    |
| Exp. sfra2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb0            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. sfrb2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfra1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. b0               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. b1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |



| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 1,0000e+00$ |
| Tolerance a1    | $\pm 1,0000e+00$ |
| Tolerance a2    | $\pm 1,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 1,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2543 |
| Max CPU cycles  | 3059 |
| Avg CPU cycles  | 2765 |

**Verification: NotchBiQ FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-25  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Filter block NotchBiQ.

| Test results   |          |    |    |      |     |       |
|----------------|----------|----|----|------|-----|-------|
| Time step      | 1        | 2  | 3  | 4    | ... | 101   |
| CPU cycles     | 90       | 90 | 90 | 90   | ... | 90    |
| Inputs         |          |    |    |      |     |       |
| In (DSP)       | 0        | 0  | 0  | 4915 | ... | 3277  |
| In             | 0        | 0  | 0  | 0.15 | ... | 0.1   |
| Parameters     |          |    |    |      |     |       |
| method         | bilinear |    |    |      |     |       |
| fn             | 50       |    |    |      |     |       |
| Q              | 25       |    |    |      |     |       |
| ts_fact        | 1        |    |    |      |     |       |
| Outputs        |          |    |    |      |     |       |
| Out            | 0        | 0  | 0  | 0.15 | ... | 0.072 |
| Exp. Out       | 0        | 0  | 0  | 0.15 | ... | 0.098 |
| Out (DSP)      | 0        | 0  | 0  | 4911 | ... | 2356  |
| Exp. Out (DSP) | 0        | 0  | 0  | 4912 | ... | 3214  |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 2,7466e-02$ ( $\pm 900$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 90 |
| Max CPU cycles  | 90 |
| Avg CPU cycles  | 90 |

**Test case: Conversion test****OK**

Conversion test for Filter block NotchBiQ.

| Test results          |          |          |          |          |     |          |
|-----------------------|----------|----------|----------|----------|-----|----------|
| Time step             | 1        | 2        | 3        | 4        | ... | 10       |
| Mask parameters       |          |          |          |          |     |          |
| method                | bilinear | bilinear | bilinear | bilinear | ... | bilinear |
| fn                    | 10       | 231.111  | 452.222  | 673.333  | ... | 2000     |
| Q                     | 10       | 20       | 30       | 40       | ... | 100      |
| ts_fact               | 1        | 1        | 1        | 1        | ... | 1        |
| Controller parameters |          |          |          |          |     |          |
| b2                    | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| a1                    | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| a2                    | 32747    | 32532    | 32463    | 32433    | ... | 32458    |
| sfra2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb0                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb1                 | 14       | 14       | 14       | 14       | ... | 15       |
| sfrb2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfra1                 | 14       | 14       | 14       | 14       | ... | 15       |
| b0                    | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| b1                    | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| Exp. b2               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. a1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| Exp. a2               | 32747    | 32532    | 32463    | 32433    | ... | 32458    |
| Exp. sfra2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb0            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. sfrb2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfra1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. b0               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. b1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block NotchBiQ.

| Test results          |          |          |          |          |     |          |
|-----------------------|----------|----------|----------|----------|-----|----------|
| Time step             | 1        | 2        | 3        | 4        | ... | 10       |
| Mask parameters       |          |          |          |          |     |          |
| method                | bilinear | bilinear | bilinear | bilinear | ... | bilinear |
| fn                    | 10       | 231.111  | 452.222  | 673.333  | ... | 2000     |
| Q                     | 10       | 20       | 30       | 40       | ... | 100      |
| ts_fact               | 1        | 1        | 1        | 1        | ... | 1        |
| Controller parameters |          |          |          |          |     |          |
| b2                    | 32757    | 32649    | 32615    | 32600    | ... | 32612    |
| a1                    | -32757   | -32306   | -31307   | -29726   | ... | -20155   |
| a2                    | 32747    | 32531    | 32463    | 32433    | ... | 32457    |
| sfra2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb0                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfrb1                 | 14       | 14       | 14       | 14       | ... | 15       |
| sfrb2                 | 15       | 15       | 15       | 15       | ... | 15       |
| sfra1                 | 14       | 14       | 14       | 14       | ... | 15       |
| b0                    | 32757    | 32649    | 32615    | 32600    | ... | 32612    |
| b1                    | -32757   | -32306   | -31307   | -29726   | ... | -20155   |
| Exp. b2               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. a1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |
| Exp. a2               | 32747    | 32532    | 32463    | 32433    | ... | 32458    |
| Exp. sfra2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb0            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfrb1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. sfrb2            | 15       | 15       | 15       | 15       | ... | 15       |
| Exp. sfra1            | 14       | 14       | 14       | 14       | ... | 15       |
| Exp. b0               | 32758    | 32650    | 32616    | 32601    | ... | 32613    |
| Exp. b1               | -32757   | -32306   | -31308   | -29726   | ... | -20156   |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 1,0000e+00$ |
| Tolerance a1    | $\pm 1,0000e+00$ |
| Tolerance a2    | $\pm 1,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 1,0000e+00$ |
| Tolerance b1    | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 6067 |
| Max CPU cycles  | 6586 |
| Avg CPU cycles  | 6471 |

**Verification: NotchBiQ FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-25  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Filter block NotchBiQ.

| Test results   |          |     |     |           |
|----------------|----------|-----|-----|-----------|
| Time step      | 1        | 2   | ... | 101       |
| CPU cycles     | 243      | 243 | ... | 243       |
| Inputs         |          |     |     |           |
| In (DSP)       | 0        | 0   | ... | 214748365 |
| In             | 0        | 0   | ... | 0.1       |
| Parameters     |          |     |     |           |
| method         | bilinear |     |     |           |
| fn             | 50       |     |     |           |
| Q              | 25       |     |     |           |
| ts_fact        | 1        |     |     |           |
| Outputs        |          |     |     |           |
| Out            | 0        | 0   | ... | 0.098     |
| Exp. Out       | 0        | 0   | ... | 0.098     |
| Out (DSP)      | 0        | 0   | ... | 210653100 |
| Exp. Out (DSP) | 0        | 0   | ... | 210653187 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 243 |
| Max CPU cycles  | 243 |
| Avg CPU cycles  | 243 |

**Test case: Conversion test****OK**

Conversion test for Filter block NotchBiQ.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| Time step             | 1           | 2           | ... | 10          |
| Mask parameters       |             |             |     |             |
| method                | bilinear    | bilinear    | ... | bilinear    |
| fn                    | 10          | 231.111     | ... | 2000        |
| Q                     | 10          | 20          | ... | 100         |
| ts_fact               | 1           | 1           | ... | 1           |
| Controller parameters |             |             |     |             |
| b2                    | 2146809212  | 2139743042  | ... | 2137320087  |
| a1                    | -2146766836 | -2117222972 | ... | -1320936459 |
| a2                    | 2146134777  | 2132002436  | ... | 2127156526  |
| sfra2                 | 31          | 31          | ... | 31          |
| sfrb0                 | 31          | 31          | ... | 31          |
| sfrb1                 | 30          | 30          | ... | 31          |
| sfrb2                 | 31          | 31          | ... | 31          |
| sfra1                 | 30          | 30          | ... | 31          |
| b0                    | 2146809212  | 2139743042  | ... | 2137320087  |
| b1                    | -2146766836 | -2117222972 | ... | -1320936459 |
| Exp. b2               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. a1               | -2146766836 | -2117222972 | ... | -1320936459 |
| Exp. a2               | 2146134777  | 2132002436  | ... | 2127156526  |
| Exp. sfra2            | 31          | 31          | ... | 31          |
| Exp. sfrb0            | 31          | 31          | ... | 31          |
| Exp. sfrb1            | 30          | 30          | ... | 31          |
| Exp. sfrb2            | 31          | 31          | ... | 31          |
| Exp. sfra1            | 30          | 30          | ... | 31          |
| Exp. b0               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. b1               | -2146766836 | -2117222972 | ... | -1320936459 |



| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block NotchBiQ.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| Time step             | 1           | 2           | ... | 10          |
| Mask parameters       |             |             |     |             |
| method                | bilinear    | bilinear    | ... | bilinear    |
| fn                    | 10          | 231.111     | ... | 2000        |
| Q                     | 10          | 20          | ... | 100         |
| ts_fact               | 1           | 1           | ... | 1           |
| Controller parameters |             |             |     |             |
| b2                    | 2146809088  | 2139742848  | ... | 2137320064  |
| a1                    | -2146766848 | -2117223040 | ... | -1320936320 |
| a2                    | 2146134656  | 2132002304  | ... | 2127156352  |
| sfra2                 | 31          | 31          | ... | 31          |
| sfrb0                 | 31          | 31          | ... | 31          |
| sfrb1                 | 30          | 30          | ... | 31          |
| sfrb2                 | 31          | 31          | ... | 31          |
| sfra1                 | 30          | 30          | ... | 31          |
| b0                    | 2146809088  | 2139742848  | ... | 2137320064  |
| b1                    | -2146766848 | -2117223040 | ... | -1320936320 |
| Exp. b2               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. a1               | -2146766836 | -2117222972 | ... | -1320936459 |
| Exp. a2               | 2146134777  | 2132002436  | ... | 2127156526  |
| Exp. sfra2            | 31          | 31          | ... | 31          |
| Exp. sfrb0            | 31          | 31          | ... | 31          |
| Exp. sfrb1            | 30          | 30          | ... | 31          |
| Exp. sfrb2            | 31          | 31          | ... | 31          |
| Exp. sfra1            | 30          | 30          | ... | 31          |
| Exp. b0               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. b1               | -2146766836 | -2117222972 | ... | -1320936459 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 2,0000e+02$ |
| Tolerance a1    | $\pm 5,0000e+02$ |
| Tolerance a2    | $\pm 2,0000e+02$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 2,0000e+02$ |
| Tolerance b1    | $\pm 5,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3139 |
| Max CPU cycles  | 3523 |
| Avg CPU cycles  | 3446 |

**Verification: NotchBiQ FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-25  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Filter block NotchBiQ.

| Test results   |          |     |     |           |
|----------------|----------|-----|-----|-----------|
| Time step      | 1        | 2   | ... | 101       |
| CPU cycles     | 266      | 266 | ... | 266       |
| Inputs         |          |     |     |           |
| In (DSP)       | 0        | 0   | ... | 214748365 |
| In             | 0        | 0   | ... | 0.1       |
| Parameters     |          |     |     |           |
| method         | bilinear |     |     |           |
| fn             | 50       |     |     |           |
| Q              | 25       |     |     |           |
| ts_fact        | 1        |     |     |           |
| Outputs        |          |     |     |           |
| Out            | 0        | 0   | ... | 0.098     |
| Exp. Out       | 0        | 0   | ... | 0.098     |
| Out (DSP)      | 0        | 0   | ... | 210653100 |
| Exp. Out (DSP) | 0        | 0   | ... | 210653187 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 266 |
| Max CPU cycles  | 266 |
| Avg CPU cycles  | 266 |

**Test case: Conversion test****OK**

Conversion test for Filter block NotchBiQ.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| Time step             | 1           | 2           | ... | 10          |
| Mask parameters       |             |             |     |             |
| method                | bilinear    | bilinear    | ... | bilinear    |
| fn                    | 10          | 231.111     | ... | 2000        |
| Q                     | 10          | 20          | ... | 100         |
| ts_fact               | 1           | 1           | ... | 1           |
| Controller parameters |             |             |     |             |
| b2                    | 2146809212  | 2139743042  | ... | 2137320087  |
| a1                    | -2146766836 | -2117222972 | ... | -1320936459 |
| a2                    | 2146134777  | 2132002436  | ... | 2127156526  |
| sfra2                 | 31          | 31          | ... | 31          |
| sfrb0                 | 31          | 31          | ... | 31          |
| sfrb1                 | 30          | 30          | ... | 31          |
| sfrb2                 | 31          | 31          | ... | 31          |
| sfra1                 | 30          | 30          | ... | 31          |
| b0                    | 2146809212  | 2139743042  | ... | 2137320087  |
| b1                    | -2146766836 | -2117222972 | ... | -1320936459 |
| Exp. b2               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. a1               | -2146766836 | -2117222972 | ... | -1320936459 |
| Exp. a2               | 2146134777  | 2132002436  | ... | 2127156526  |
| Exp. sfra2            | 31          | 31          | ... | 31          |
| Exp. sfrb0            | 31          | 31          | ... | 31          |
| Exp. sfrb1            | 30          | 30          | ... | 31          |
| Exp. sfrb2            | 31          | 31          | ... | 31          |
| Exp. sfra1            | 30          | 30          | ... | 31          |
| Exp. b0               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. b1               | -2146766836 | -2117222972 | ... | -1320936459 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block NotchBiQ.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| Time step             | 1           | 2           | ... | 10          |
| Mask parameters       |             |             |     |             |
| method                | bilinear    | bilinear    | ... | bilinear    |
| fn                    | 10          | 231.111     | ... | 2000        |
| Q                     | 10          | 20          | ... | 100         |
| ts_fact               | 1           | 1           | ... | 1           |
| Controller parameters |             |             |     |             |
| b2                    | 2146808960  | 2139742848  | ... | 2137319936  |
| a1                    | -2146766848 | -2117223040 | ... | -1320936704 |
| a2                    | 2146134656  | 2132002304  | ... | 2127156352  |
| sfra2                 | 31          | 31          | ... | 31          |
| sfrb0                 | 31          | 31          | ... | 31          |
| sfrb1                 | 30          | 30          | ... | 31          |
| sfrb2                 | 31          | 31          | ... | 31          |
| sfra1                 | 30          | 30          | ... | 31          |
| b0                    | 2146808960  | 2139742848  | ... | 2137319936  |
| b1                    | -2146766848 | -2117223040 | ... | -1320936704 |
| Exp. b2               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. a1               | -2146766836 | -2117222972 | ... | -1320936459 |
| Exp. a2               | 2146134777  | 2132002436  | ... | 2127156526  |
| Exp. sfra2            | 31          | 31          | ... | 31          |
| Exp. sfrb0            | 31          | 31          | ... | 31          |
| Exp. sfrb1            | 30          | 30          | ... | 31          |
| Exp. sfrb2            | 31          | 31          | ... | 31          |
| Exp. sfra1            | 30          | 30          | ... | 31          |
| Exp. b0               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. b1               | -2146766836 | -2117222972 | ... | -1320936459 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 2,5200e+02$ |
| Tolerance a1    | $\pm 5,0000e+02$ |
| Tolerance a2    | $\pm 2,0000e+02$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 2,5200e+02$ |
| Tolerance b1    | $\pm 5,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 8601 |
| Max CPU cycles  | 9631 |
| Avg CPU cycles  | 9425 |



**Verification: NotchBiQ FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-25  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Filter block NotchBiQ.

| Test results   |          |     |     |           |
|----------------|----------|-----|-----|-----------|
| Time step      | 1        | 2   | ... | 101       |
| CPU cycles     | 248      | 248 | ... | 248       |
| Inputs         |          |     |     |           |
| In (DSP)       | 0        | 0   | ... | 214748365 |
| In             | 0        | 0   | ... | 0.1       |
| Parameters     |          |     |     |           |
| method         | bilinear |     |     |           |
| fn             | 50       |     |     |           |
| Q              | 25       |     |     |           |
| ts_fact        | 1        |     |     |           |
| Outputs        |          |     |     |           |
| Out            | 0        | 0   | ... | 0.098     |
| Exp. Out       | 0        | 0   | ... | 0.098     |
| Out (DSP)      | 0        | 0   | ... | 210653100 |
| Exp. Out (DSP) | 0        | 0   | ... | 210653187 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 248 |
| Max CPU cycles  | 248 |
| Avg CPU cycles  | 248 |

**Test case: Conversion test****OK**

Conversion test for Filter block NotchBiQ.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| Time step             | 1           | 2           | ... | 10          |
| Mask parameters       |             |             |     |             |
| method                | bilinear    | bilinear    | ... | bilinear    |
| fn                    | 10          | 231.111     | ... | 2000        |
| Q                     | 10          | 20          | ... | 100         |
| ts_fact               | 1           | 1           | ... | 1           |
| Controller parameters |             |             |     |             |
| b2                    | 2146809212  | 2139743042  | ... | 2137320087  |
| a1                    | -2146766836 | -2117222972 | ... | -1320936459 |
| a2                    | 2146134777  | 2132002436  | ... | 2127156526  |
| sfra2                 | 31          | 31          | ... | 31          |
| sfrb0                 | 31          | 31          | ... | 31          |
| sfrb1                 | 30          | 30          | ... | 31          |
| sfrb2                 | 31          | 31          | ... | 31          |
| sfra1                 | 30          | 30          | ... | 31          |
| b0                    | 2146809212  | 2139743042  | ... | 2137320087  |
| b1                    | -2146766836 | -2117222972 | ... | -1320936459 |
| Exp. b2               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. a1               | -2146766836 | -2117222972 | ... | -1320936459 |
| Exp. a2               | 2146134777  | 2132002436  | ... | 2127156526  |
| Exp. sfra2            | 31          | 31          | ... | 31          |
| Exp. sfrb0            | 31          | 31          | ... | 31          |
| Exp. sfrb1            | 30          | 30          | ... | 31          |
| Exp. sfrb2            | 31          | 31          | ... | 31          |
| Exp. sfra1            | 30          | 30          | ... | 31          |
| Exp. b0               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. b1               | -2146766836 | -2117222972 | ... | -1320936459 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block NotchBiQ.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| Time step             | 1           | 2           | ... | 10          |
| Mask parameters       |             |             |     |             |
| method                | bilinear    | bilinear    | ... | bilinear    |
| fn                    | 10          | 231.111     | ... | 2000        |
| Q                     | 10          | 20          | ... | 100         |
| ts_fact               | 1           | 1           | ... | 1           |
| Controller parameters |             |             |     |             |
| b2                    | 2146808960  | 2139742848  | ... | 2137319936  |
| a1                    | -2146766848 | -2117223040 | ... | -1320936704 |
| a2                    | 2146134656  | 2132002304  | ... | 2127156352  |
| sfra2                 | 31          | 31          | ... | 31          |
| sfrb0                 | 31          | 31          | ... | 31          |
| sfrb1                 | 30          | 30          | ... | 31          |
| sfrb2                 | 31          | 31          | ... | 31          |
| sfra1                 | 30          | 30          | ... | 31          |
| b0                    | 2146808960  | 2139742848  | ... | 2137319936  |
| b1                    | -2146766848 | -2117223040 | ... | -1320936704 |
| Exp. b2               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. a1               | -2146766836 | -2117222972 | ... | -1320936459 |
| Exp. a2               | 2146134777  | 2132002436  | ... | 2127156526  |
| Exp. sfra2            | 31          | 31          | ... | 31          |
| Exp. sfrb0            | 31          | 31          | ... | 31          |
| Exp. sfrb1            | 30          | 30          | ... | 31          |
| Exp. sfrb2            | 31          | 31          | ... | 31          |
| Exp. sfra1            | 30          | 30          | ... | 31          |
| Exp. b0               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. b1               | -2146766836 | -2117222972 | ... | -1320936459 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 2,5200e+02$ |
| Tolerance a1    | $\pm 5,0000e+02$ |
| Tolerance a2    | $\pm 2,0000e+02$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 2,5200e+02$ |
| Tolerance b1    | $\pm 5,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 6452 |
| Max CPU cycles  | 7244 |
| Avg CPU cycles  | 7085 |

**Verification: NotchBiQ FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-25  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Filter block NotchBiQ.

| Test results   |          |      |     |           |
|----------------|----------|------|-----|-----------|
| Time step      | 1        | 2    | ... | 101       |
| CPU cycles     | 2219     | 2219 | ... | 2219      |
| Inputs         |          |      |     |           |
| In (DSP)       | 0        | 0    | ... | 214748365 |
| In             | 0        | 0    | ... | 0.1       |
| Parameters     |          |      |     |           |
| method         | bilinear |      |     |           |
| fn             | 50       |      |     |           |
| Q              | 25       |      |     |           |
| ts_fact        | 1        |      |     |           |
| Outputs        |          |      |     |           |
| Out            | 0        | 0    | ... | 0.098     |
| Exp. Out       | 0        | 0    | ... | 0.098     |
| Out (DSP)      | 0        | 0    | ... | 210653100 |
| Exp. Out (DSP) | 0        | 0    | ... | 210653187 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2219 |
| Max CPU cycles  | 2242 |
| Avg CPU cycles  | 2230 |

**Test case: Conversion test****OK**

Conversion test for Filter block NotchBiQ.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| Time step             | 1           | 2           | ... | 10          |
| Mask parameters       |             |             |     |             |
| method                | bilinear    | bilinear    | ... | bilinear    |
| fn                    | 10          | 231.111     | ... | 2000        |
| Q                     | 10          | 20          | ... | 100         |
| ts_fact               | 1           | 1           | ... | 1           |
| Controller parameters |             |             |     |             |
| b2                    | 2146809212  | 2139743042  | ... | 2137320087  |
| a1                    | -2146766836 | -2117222972 | ... | -1320936459 |
| a2                    | 2146134777  | 2132002436  | ... | 2127156526  |
| sfra2                 | 31          | 31          | ... | 31          |
| sfrb0                 | 31          | 31          | ... | 31          |
| sfrb1                 | 30          | 30          | ... | 31          |
| sfrb2                 | 31          | 31          | ... | 31          |
| sfra1                 | 30          | 30          | ... | 31          |
| b0                    | 2146809212  | 2139743042  | ... | 2137320087  |
| b1                    | -2146766836 | -2117222972 | ... | -1320936459 |
| Exp. b2               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. a1               | -2146766836 | -2117222972 | ... | -1320936459 |
| Exp. a2               | 2146134777  | 2132002436  | ... | 2127156526  |
| Exp. sfra2            | 31          | 31          | ... | 31          |
| Exp. sfrb0            | 31          | 31          | ... | 31          |
| Exp. sfrb1            | 30          | 30          | ... | 31          |
| Exp. sfrb2            | 31          | 31          | ... | 31          |
| Exp. sfra1            | 30          | 30          | ... | 31          |
| Exp. b0               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. b1               | -2146766836 | -2117222972 | ... | -1320936459 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block NotchBiQ.



| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| Time step             | 1           | 2           | ... | 10          |
| Mask parameters       |             |             |     |             |
| method                | bilinear    | bilinear    | ... | bilinear    |
| fn                    | 10          | 231.111     | ... | 2000        |
| Q                     | 10          | 20          | ... | 100         |
| ts_fact               | 1           | 1           | ... | 1           |
| Controller parameters |             |             |     |             |
| b2                    | 2146809088  | 2139742848  | ... | 2137320064  |
| a1                    | -2146766848 | -2117223040 | ... | -1320936320 |
| a2                    | 2146134656  | 2132002304  | ... | 2127156352  |
| sfra2                 | 31          | 31          | ... | 31          |
| sfrb0                 | 31          | 31          | ... | 31          |
| sfrb1                 | 30          | 30          | ... | 31          |
| sfrb2                 | 31          | 31          | ... | 31          |
| sfra1                 | 30          | 30          | ... | 31          |
| b0                    | 2146809088  | 2139742848  | ... | 2137320064  |
| b1                    | -2146766848 | -2117223040 | ... | -1320936320 |
| Exp. b2               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. a1               | -2146766836 | -2117222972 | ... | -1320936459 |
| Exp. a2               | 2146134777  | 2132002436  | ... | 2127156526  |
| Exp. sfra2            | 31          | 31          | ... | 31          |
| Exp. sfrb0            | 31          | 31          | ... | 31          |
| Exp. sfrb1            | 30          | 30          | ... | 31          |
| Exp. sfrb2            | 31          | 31          | ... | 31          |
| Exp. sfra1            | 30          | 30          | ... | 31          |
| Exp. b0               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. b1               | -2146766836 | -2117222972 | ... | -1320936459 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 2,0000e+02$ |
| Tolerance a1    | $\pm 5,0000e+02$ |
| Tolerance a2    | $\pm 2,0000e+02$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 2,0000e+02$ |
| Tolerance b1    | $\pm 5,0000e+02$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 28126 |
| Max CPU cycles  | 32508 |
| Avg CPU cycles  | 31004 |

**Verification: NotchBiQ FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-25  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Filter block NotchBiQ.

| Test results   |          |     |     |           |
|----------------|----------|-----|-----|-----------|
| Time step      | 1        | 2   | ... | 101       |
| CPU cycles     | 633      | 633 | ... | 633       |
| Inputs         |          |     |     |           |
| In (DSP)       | 0        | 0   | ... | 214748365 |
| In             | 0        | 0   | ... | 0.1       |
| Parameters     |          |     |     |           |
| method         | bilinear |     |     |           |
| fn             | 50       |     |     |           |
| Q              | 25       |     |     |           |
| ts_fact        | 1        |     |     |           |
| Outputs        |          |     |     |           |
| Out            | 0        | 0   | ... | 0.098     |
| Exp. Out       | 0        | 0   | ... | 0.098     |
| Out (DSP)      | 0        | 0   | ... | 210653100 |
| Exp. Out (DSP) | 0        | 0   | ... | 210653187 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 633 |
| Max CPU cycles  | 699 |
| Avg CPU cycles  | 637 |

**Test case: Conversion test****OK**

Conversion test for Filter block NotchBiQ.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| Time step             | 1           | 2           | ... | 10          |
| Mask parameters       |             |             |     |             |
| method                | bilinear    | bilinear    | ... | bilinear    |
| fn                    | 10          | 231.111     | ... | 2000        |
| Q                     | 10          | 20          | ... | 100         |
| ts_fact               | 1           | 1           | ... | 1           |
| Controller parameters |             |             |     |             |
| b2                    | 2146809212  | 2139743042  | ... | 2137320087  |
| a1                    | -2146766836 | -2117222972 | ... | -1320936459 |
| a2                    | 2146134777  | 2132002436  | ... | 2127156526  |
| sfra2                 | 31          | 31          | ... | 31          |
| sfrb0                 | 31          | 31          | ... | 31          |
| sfrb1                 | 30          | 30          | ... | 31          |
| sfrb2                 | 31          | 31          | ... | 31          |
| sfra1                 | 30          | 30          | ... | 31          |
| b0                    | 2146809212  | 2139743042  | ... | 2137320087  |
| b1                    | -2146766836 | -2117222972 | ... | -1320936459 |
| Exp. b2               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. a1               | -2146766836 | -2117222972 | ... | -1320936459 |
| Exp. a2               | 2146134777  | 2132002436  | ... | 2127156526  |
| Exp. sfra2            | 31          | 31          | ... | 31          |
| Exp. sfrb0            | 31          | 31          | ... | 31          |
| Exp. sfrb1            | 30          | 30          | ... | 31          |
| Exp. sfrb2            | 31          | 31          | ... | 31          |
| Exp. sfra1            | 30          | 30          | ... | 31          |
| Exp. b0               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. b1               | -2146766836 | -2117222972 | ... | -1320936459 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block NotchBiQ.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| Time step             | 1           | 2           | ... | 10          |
| Mask parameters       |             |             |     |             |
| method                | bilinear    | bilinear    | ... | bilinear    |
| fn                    | 10          | 231.111     | ... | 2000        |
| Q                     | 10          | 20          | ... | 100         |
| ts_fact               | 1           | 1           | ... | 1           |
| Controller parameters |             |             |     |             |
| b2                    | 2146809088  | 2139742848  | ... | 2137320064  |
| a1                    | -2146766848 | -2117223040 | ... | -1320936320 |
| a2                    | 2146134656  | 2132002304  | ... | 2127156352  |
| sfra2                 | 31          | 31          | ... | 31          |
| sfrb0                 | 31          | 31          | ... | 31          |
| sfrb1                 | 30          | 30          | ... | 31          |
| sfrb2                 | 31          | 31          | ... | 31          |
| sfra1                 | 30          | 30          | ... | 31          |
| b0                    | 2146809088  | 2139742848  | ... | 2137320064  |
| b1                    | -2146766848 | -2117223040 | ... | -1320936320 |
| Exp. b2               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. a1               | -2146766836 | -2117222972 | ... | -1320936459 |
| Exp. a2               | 2146134777  | 2132002436  | ... | 2127156526  |
| Exp. sfra2            | 31          | 31          | ... | 31          |
| Exp. sfrb0            | 31          | 31          | ... | 31          |
| Exp. sfrb1            | 30          | 30          | ... | 31          |
| Exp. sfrb2            | 31          | 31          | ... | 31          |
| Exp. sfra1            | 30          | 30          | ... | 31          |
| Exp. b0               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. b1               | -2146766836 | -2117222972 | ... | -1320936459 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 2,0000e+02$ |
| Tolerance a1    | $\pm 5,0000e+02$ |
| Tolerance a2    | $\pm 2,0000e+02$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 2,0000e+02$ |
| Tolerance b1    | $\pm 5,0000e+02$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 27074 |
| Max CPU cycles  | 28443 |
| Avg CPU cycles  | 28116 |

**Verification: NotchBiQ FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-25  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Filter block NotchBiQ.

| Test results   |          |     |     |           |
|----------------|----------|-----|-----|-----------|
| Time step      | 1        | 2   | ... | 101       |
| CPU cycles     | 235      | 235 | ... | 235       |
| Inputs         |          |     |     |           |
| In (DSP)       | 0        | 0   | ... | 214748365 |
| In             | 0        | 0   | ... | 0.1       |
| Parameters     |          |     |     |           |
| method         | bilinear |     |     |           |
| fn             | 50       |     |     |           |
| Q              | 25       |     |     |           |
| ts_fact        | 1        |     |     |           |
| Outputs        |          |     |     |           |
| Out            | 0        | 0   | ... | 0.098     |
| Exp. Out       | 0        | 0   | ... | 0.098     |
| Out (DSP)      | 0        | 0   | ... | 210653100 |
| Exp. Out (DSP) | 0        | 0   | ... | 210653187 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 235 |
| Max CPU cycles  | 235 |
| Avg CPU cycles  | 235 |

**Test case: Conversion test****OK**

Conversion test for Filter block NotchBiQ.



| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| Time step             | 1           | 2           | ... | 10          |
| Mask parameters       |             |             |     |             |
| method                | bilinear    | bilinear    | ... | bilinear    |
| fn                    | 10          | 231.111     | ... | 2000        |
| Q                     | 10          | 20          | ... | 100         |
| ts_fact               | 1           | 1           | ... | 1           |
| Controller parameters |             |             |     |             |
| b2                    | 2146809212  | 2139743042  | ... | 2137320087  |
| a1                    | -2146766836 | -2117222972 | ... | -1320936459 |
| a2                    | 2146134777  | 2132002436  | ... | 2127156526  |
| sfra2                 | 31          | 31          | ... | 31          |
| sfrb0                 | 31          | 31          | ... | 31          |
| sfrb1                 | 30          | 30          | ... | 31          |
| sfrb2                 | 31          | 31          | ... | 31          |
| sfra1                 | 30          | 30          | ... | 31          |
| b0                    | 2146809212  | 2139743042  | ... | 2137320087  |
| b1                    | -2146766836 | -2117222972 | ... | -1320936459 |
| Exp. b2               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. a1               | -2146766836 | -2117222972 | ... | -1320936459 |
| Exp. a2               | 2146134777  | 2132002436  | ... | 2127156526  |
| Exp. sfra2            | 31          | 31          | ... | 31          |
| Exp. sfrb0            | 31          | 31          | ... | 31          |
| Exp. sfrb1            | 30          | 30          | ... | 31          |
| Exp. sfrb2            | 31          | 31          | ... | 31          |
| Exp. sfra1            | 30          | 30          | ... | 31          |
| Exp. b0               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. b1               | -2146766836 | -2117222972 | ... | -1320936459 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Filter block NotchBiQ.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| Time step             | 1           | 2           | ... | 10          |
| Mask parameters       |             |             |     |             |
| method                | bilinear    | bilinear    | ... | bilinear    |
| fn                    | 10          | 231.111     | ... | 2000        |
| Q                     | 10          | 20          | ... | 100         |
| ts_fact               | 1           | 1           | ... | 1           |
| Controller parameters |             |             |     |             |
| b2                    | 2146809088  | 2139742848  | ... | 2137320192  |
| a1                    | -2146766848 | -2117223040 | ... | -1320936448 |
| a2                    | 2146134656  | 2132002304  | ... | 2127156608  |
| sfra2                 | 31          | 31          | ... | 31          |
| sfrb0                 | 31          | 31          | ... | 31          |
| sfrb1                 | 30          | 30          | ... | 31          |
| sfrb2                 | 31          | 31          | ... | 31          |
| sfra1                 | 30          | 30          | ... | 31          |
| b0                    | 2146809088  | 2139742848  | ... | 2137320192  |
| b1                    | -2146766848 | -2117223040 | ... | -1320936448 |
| Exp. b2               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. a1               | -2146766836 | -2117222972 | ... | -1320936459 |
| Exp. a2               | 2146134777  | 2132002436  | ... | 2127156526  |
| Exp. sfra2            | 31          | 31          | ... | 31          |
| Exp. sfrb0            | 31          | 31          | ... | 31          |
| Exp. sfrb1            | 30          | 30          | ... | 31          |
| Exp. sfrb2            | 31          | 31          | ... | 31          |
| Exp. sfra1            | 30          | 30          | ... | 31          |
| Exp. b0               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. b1               | -2146766836 | -2117222972 | ... | -1320936459 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 2,5200e+02$ |
| Tolerance a1    | $\pm 5,0000e+02$ |
| Tolerance a2    | $\pm 2,0000e+02$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 2,5200e+02$ |
| Tolerance b1    | $\pm 5,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 4208 |
| Max CPU cycles  | 4460 |
| Avg CPU cycles  | 4409 |

**Verification: NotchBiQ FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-25  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Filter block NotchBiQ.

| Test results   |          |     |     |           |
|----------------|----------|-----|-----|-----------|
| Time step      | 1        | 2   | ... | 101       |
| CPU cycles     | 282      | 224 | ... | 224       |
| Inputs         |          |     |     |           |
| In (DSP)       | 0        | 0   | ... | 214748365 |
| In             | 0        | 0   | ... | 0.1       |
| Parameters     |          |     |     |           |
| method         | bilinear |     |     |           |
| fn             | 50       |     |     |           |
| Q              | 25       |     |     |           |
| ts_fact        | 1        |     |     |           |
| Outputs        |          |     |     |           |
| Out            | 0        | 0   | ... | 0.098     |
| Exp. Out       | 0        | 0   | ... | 0.098     |
| Out (DSP)      | 0        | 0   | ... | 210653100 |
| Exp. Out (DSP) | 0        | 0   | ... | 210653187 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 224 |
| Max CPU cycles  | 282 |
| Avg CPU cycles  | 224 |

**Test case: Conversion test****OK**

Conversion test for Filter block NotchBiQ.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| Time step             | 1           | 2           | ... | 10          |
| Mask parameters       |             |             |     |             |
| method                | bilinear    | bilinear    | ... | bilinear    |
| fn                    | 10          | 231.111     | ... | 2000        |
| Q                     | 10          | 20          | ... | 100         |
| ts_fact               | 1           | 1           | ... | 1           |
| Controller parameters |             |             |     |             |
| b2                    | 2146809212  | 2139743042  | ... | 2137320087  |
| a1                    | -2146766836 | -2117222972 | ... | -1320936459 |
| a2                    | 2146134777  | 2132002436  | ... | 2127156526  |
| sfra2                 | 31          | 31          | ... | 31          |
| sfrb0                 | 31          | 31          | ... | 31          |
| sfrb1                 | 30          | 30          | ... | 31          |
| sfrb2                 | 31          | 31          | ... | 31          |
| sfra1                 | 30          | 30          | ... | 31          |
| b0                    | 2146809212  | 2139743042  | ... | 2137320087  |
| b1                    | -2146766836 | -2117222972 | ... | -1320936459 |
| Exp. b2               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. a1               | -2146766836 | -2117222972 | ... | -1320936459 |
| Exp. a2               | 2146134777  | 2132002436  | ... | 2127156526  |
| Exp. sfra2            | 31          | 31          | ... | 31          |
| Exp. sfrb0            | 31          | 31          | ... | 31          |
| Exp. sfrb1            | 30          | 30          | ... | 31          |
| Exp. sfrb2            | 31          | 31          | ... | 31          |
| Exp. sfra1            | 30          | 30          | ... | 31          |
| Exp. b0               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. b1               | -2146766836 | -2117222972 | ... | -1320936459 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block NotchBiQ.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| Time step             | 1           | 2           | ... | 10          |
| Mask parameters       |             |             |     |             |
| method                | bilinear    | bilinear    | ... | bilinear    |
| fn                    | 10          | 231.111     | ... | 2000        |
| Q                     | 10          | 20          | ... | 100         |
| ts_fact               | 1           | 1           | ... | 1           |
| Controller parameters |             |             |     |             |
| b2                    | 2146809088  | 2139742848  | ... | 2137320192  |
| a1                    | -2146766848 | -2117223040 | ... | -1320936448 |
| a2                    | 2146134656  | 2132002304  | ... | 2127156608  |
| sfra2                 | 31          | 31          | ... | 31          |
| sfrb0                 | 31          | 31          | ... | 31          |
| sfrb1                 | 30          | 30          | ... | 31          |
| sfrb2                 | 31          | 31          | ... | 31          |
| sfra1                 | 30          | 30          | ... | 31          |
| b0                    | 2146809088  | 2139742848  | ... | 2137320192  |
| b1                    | -2146766848 | -2117223040 | ... | -1320936448 |
| Exp. b2               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. a1               | -2146766836 | -2117222972 | ... | -1320936459 |
| Exp. a2               | 2146134777  | 2132002436  | ... | 2127156526  |
| Exp. sfra2            | 31          | 31          | ... | 31          |
| Exp. sfrb0            | 31          | 31          | ... | 31          |
| Exp. sfrb1            | 30          | 30          | ... | 31          |
| Exp. sfrb2            | 31          | 31          | ... | 31          |
| Exp. sfra1            | 30          | 30          | ... | 31          |
| Exp. b0               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. b1               | -2146766836 | -2117222972 | ... | -1320936459 |



| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 2,5200e+02$ |
| Tolerance a1    | $\pm 5,0000e+02$ |
| Tolerance a2    | $\pm 2,0000e+02$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 2,5200e+02$ |
| Tolerance b1    | $\pm 5,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3930 |
| Max CPU cycles  | 4405 |
| Avg CPU cycles  | 4148 |

**Verification: NotchBiQ FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-25  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Filter block NotchBiQ.

| Test results   |          |     |     |           |
|----------------|----------|-----|-----|-----------|
| Time step      | 1        | 2   | ... | 101       |
| CPU cycles     | 208      | 208 | ... | 208       |
| Inputs         |          |     |     |           |
| In (DSP)       | 0        | 0   | ... | 214748365 |
| In             | 0        | 0   | ... | 0.1       |
| Parameters     |          |     |     |           |
| method         | bilinear |     |     |           |
| fn             | 50       |     |     |           |
| Q              | 25       |     |     |           |
| ts_fact        | 1        |     |     |           |
| Outputs        |          |     |     |           |
| Out            | 0        | 0   | ... | 0.098     |
| Exp. Out       | 0        | 0   | ... | 0.098     |
| Out (DSP)      | 0        | 0   | ... | 210653100 |
| Exp. Out (DSP) | 0        | 0   | ... | 210653187 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 208 |
| Max CPU cycles  | 208 |
| Avg CPU cycles  | 208 |

**Test case: Conversion test****OK**

Conversion test for Filter block NotchBiQ.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| Time step             | 1           | 2           | ... | 10          |
| Mask parameters       |             |             |     |             |
| method                | bilinear    | bilinear    | ... | bilinear    |
| fn                    | 10          | 231.111     | ... | 2000        |
| Q                     | 10          | 20          | ... | 100         |
| ts_fact               | 1           | 1           | ... | 1           |
| Controller parameters |             |             |     |             |
| b2                    | 2146809212  | 2139743042  | ... | 2137320087  |
| a1                    | -2146766836 | -2117222972 | ... | -1320936459 |
| a2                    | 2146134777  | 2132002436  | ... | 2127156526  |
| sfra2                 | 31          | 31          | ... | 31          |
| sfrb0                 | 31          | 31          | ... | 31          |
| sfrb1                 | 30          | 30          | ... | 31          |
| sfrb2                 | 31          | 31          | ... | 31          |
| sfra1                 | 30          | 30          | ... | 31          |
| b0                    | 2146809212  | 2139743042  | ... | 2137320087  |
| b1                    | -2146766836 | -2117222972 | ... | -1320936459 |
| Exp. b2               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. a1               | -2146766836 | -2117222972 | ... | -1320936459 |
| Exp. a2               | 2146134777  | 2132002436  | ... | 2127156526  |
| Exp. sfra2            | 31          | 31          | ... | 31          |
| Exp. sfrb0            | 31          | 31          | ... | 31          |
| Exp. sfrb1            | 30          | 30          | ... | 31          |
| Exp. sfrb2            | 31          | 31          | ... | 31          |
| Exp. sfra1            | 30          | 30          | ... | 31          |
| Exp. b0               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. b1               | -2146766836 | -2117222972 | ... | -1320936459 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 0,0000e+00$ |
| Tolerance a1    | $\pm 0,0000e+00$ |
| Tolerance a2    | $\pm 0,0000e+00$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 0,0000e+00$ |
| Tolerance b1    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block NotchBiQ.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| Time step             | 1           | 2           | ... | 10          |
| Mask parameters       |             |             |     |             |
| method                | bilinear    | bilinear    | ... | bilinear    |
| fn                    | 10          | 231.111     | ... | 2000        |
| Q                     | 10          | 20          | ... | 100         |
| ts_fact               | 1           | 1           | ... | 1           |
| Controller parameters |             |             |     |             |
| b2                    | 2146809088  | 2139742848  | ... | 2137320064  |
| a1                    | -2146766848 | -2117223040 | ... | -1320936704 |
| a2                    | 2146134656  | 2132002304  | ... | 2127156352  |
| sfra2                 | 31          | 31          | ... | 31          |
| sfrb0                 | 31          | 31          | ... | 31          |
| sfrb1                 | 30          | 30          | ... | 31          |
| sfrb2                 | 31          | 31          | ... | 31          |
| sfra1                 | 30          | 30          | ... | 31          |
| b0                    | 2146809088  | 2139742848  | ... | 2137320064  |
| b1                    | -2146766848 | -2117223040 | ... | -1320936704 |
| Exp. b2               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. a1               | -2146766836 | -2117222972 | ... | -1320936459 |
| Exp. a2               | 2146134777  | 2132002436  | ... | 2127156526  |
| Exp. sfra2            | 31          | 31          | ... | 31          |
| Exp. sfrb0            | 31          | 31          | ... | 31          |
| Exp. sfrb1            | 30          | 30          | ... | 31          |
| Exp. sfrb2            | 31          | 31          | ... | 31          |
| Exp. sfra1            | 30          | 30          | ... | 31          |
| Exp. b0               | 2146809212  | 2139743042  | ... | 2137320087  |
| Exp. b1               | -2146766836 | -2117222972 | ... | -1320936459 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance b2    | $\pm 2,5200e+02$ |
| Tolerance a1    | $\pm 5,0000e+02$ |
| Tolerance a2    | $\pm 2,0000e+02$ |
| Tolerance sfra2 | $\pm 0,0000e+00$ |
| Tolerance sfrb0 | $\pm 0,0000e+00$ |
| Tolerance sfrb1 | $\pm 0,0000e+00$ |
| Tolerance sfrb2 | $\pm 0,0000e+00$ |
| Tolerance sfra1 | $\pm 0,0000e+00$ |
| Tolerance b0    | $\pm 2,5200e+02$ |
| Tolerance b1    | $\pm 5,0000e+02$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 8707 |
| Max CPU cycles  | 9098 |
| Avg CPU cycles  | 9008 |

**Verification: NotchBiQ Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-25  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Filter block NotchBiQ.

| Test results   |          |    |     |       |
|----------------|----------|----|-----|-------|
| Time step      | 1        | 2  | ... | 101   |
| CPU cycles     | 61       | 61 | ... | 61    |
| Inputs         |          |    |     |       |
| In (DSP)       | 0        | 0  | ... | 0.1   |
| In             | 0        | 0  | ... | 0.1   |
| Parameters     |          |    |     |       |
| method         | bilinear |    |     |       |
| fn             | 50       |    |     |       |
| Q              | 25       |    |     |       |
| ts_fact        | 1        |    |     |       |
| Outputs        |          |    |     |       |
| Out            | 0        | 0  | ... | 0.098 |
| Exp. Out       | 0        | 0  | ... | 0.098 |
| Out (DSP)      | 0        | 0  | ... | 0.098 |
| Exp. Out (DSP) | 0        | 0  | ... | 0.098 |

| Test settings |                                            |
|---------------|--------------------------------------------|
| Tolerance Out | $\pm 4,6566\text{e-}06$ ( $\pm 10000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 61 |
| Max CPU cycles  | 61 |
| Avg CPU cycles  | 61 |

**Test case: Conversion test****OK**

Conversion test for Filter block NotchBiQ.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 10       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>method</b>                | bilinear | bilinear | ... | bilinear |
| <b>fn</b>                    | 10       | 231.111  | ... | 2000     |
| <b>Q</b>                     | 10       | 20       | ... | 100      |
| <b>ts_fact</b>               | 1        | 1        | ... | 1        |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b2</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>a1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>a2</b>                    | 0.999    | 0.993    | ... | 0.991    |
| <b>b0</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>b1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. b2</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. a1</b>               | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. a2</b>               | 0.999    | 0.993    | ... | 0.991    |
| <b>Exp. b0</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. b1</b>               | -1.999   | -1.972   | ... | -0.615   |

| Test settings |                         |
|---------------|-------------------------|
| Tolerance b2  | $\pm 8,8818\text{e-}16$ |
| Tolerance a1  | $\pm 8,8818\text{e-}16$ |
| Tolerance a2  | $\pm 8,8818\text{e-}16$ |
| Tolerance b0  | $\pm 8,8818\text{e-}16$ |
| Tolerance b1  | $\pm 8,8818\text{e-}16$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block NotchBiQ.



| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 10       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>method</b>                | bilinear | bilinear | ... | bilinear |
| <b>fn</b>                    | 10       | 231.111  | ... | 2000     |
| <b>Q</b>                     | 10       | 20       | ... | 100      |
| <b>ts_fact</b>               | 1        | 1        | ... | 1        |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b2</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>a1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>a2</b>                    | 0.999    | 0.993    | ... | 0.991    |
| <b>b0</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>b1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. b2</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. a1</b>               | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. a2</b>               | 0.999    | 0.993    | ... | 0.991    |
| <b>Exp. b0</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. b1</b>               | -1.999   | -1.972   | ... | -0.615   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b2  | $\pm 1,0000e-07$ |
| Tolerance a1  | $\pm 5,0000e-07$ |
| Tolerance a2  | $\pm 1,0000e-07$ |
| Tolerance b0  | $\pm 1,0000e-07$ |
| Tolerance b1  | $\pm 5,0000e-07$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1235 |
| Max CPU cycles  | 1235 |
| Avg CPU cycles  | 1235 |

**Verification: NotchBiQ Float32 CPU TMS320F28335**

**Date of Test** 2026-06-25  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Filter block NotchBiQ.

| Test results   |          |    |     |       |
|----------------|----------|----|-----|-------|
| Time step      | 1        | 2  | ... | 101   |
| CPU cycles     | 93       | 93 | ... | 93    |
| Inputs         |          |    |     |       |
| In (DSP)       | 0        | 0  | ... | 0.1   |
| In             | 0        | 0  | ... | 0.1   |
| Parameters     |          |    |     |       |
| method         | bilinear |    |     |       |
| fn             | 50       |    |     |       |
| Q              | 25       |    |     |       |
| ts_fact        | 1        |    |     |       |
| Outputs        |          |    |     |       |
| Out            | 0        | 0  | ... | 0.098 |
| Exp. Out       | 0        | 0  | ... | 0.098 |
| Out (DSP)      | 0        | 0  | ... | 0.098 |
| Exp. Out (DSP) | 0        | 0  | ... | 0.098 |

| Test settings |                                            |
|---------------|--------------------------------------------|
| Tolerance Out | $\pm 8,3819\text{e-}06$ ( $\pm 18000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 93 |
| Max CPU cycles  | 93 |
| Avg CPU cycles  | 93 |

**Test case: Conversion test****OK**

Conversion test for Filter block NotchBiQ.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 10       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>method</b>                | bilinear | bilinear | ... | bilinear |
| <b>fn</b>                    | 10       | 231.111  | ... | 2000     |
| <b>Q</b>                     | 10       | 20       | ... | 100      |
| <b>ts_fact</b>               | 1        | 1        | ... | 1        |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b2</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>a1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>a2</b>                    | 0.999    | 0.993    | ... | 0.991    |
| <b>b0</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>b1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. b2</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. a1</b>               | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. a2</b>               | 0.999    | 0.993    | ... | 0.991    |
| <b>Exp. b0</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. b1</b>               | -1.999   | -1.972   | ... | -0.615   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b2  | $\pm 8,8818e-16$ |
| Tolerance a1  | $\pm 8,8818e-16$ |
| Tolerance a2  | $\pm 8,8818e-16$ |
| Tolerance b0  | $\pm 8,8818e-16$ |
| Tolerance b1  | $\pm 8,8818e-16$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block NotchBiQ.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 10       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>method</b>                | bilinear | bilinear | ... | bilinear |
| <b>fn</b>                    | 10       | 231.111  | ... | 2000     |
| <b>Q</b>                     | 10       | 20       | ... | 100      |
| <b>ts_fact</b>               | 1        | 1        | ... | 1        |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b2</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>a1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>a2</b>                    | 0.999    | 0.993    | ... | 0.991    |
| <b>b0</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>b1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. b2</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. a1</b>               | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. a2</b>               | 0.999    | 0.993    | ... | 0.991    |
| <b>Exp. b0</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. b1</b>               | -1.999   | -1.972   | ... | -0.615   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b2  | $\pm 2,0000e-07$ |
| Tolerance a1  | $\pm 5,0000e-07$ |
| Tolerance a2  | $\pm 1,0000e-07$ |
| Tolerance b0  | $\pm 2,0000e-07$ |
| Tolerance b1  | $\pm 5,0000e-07$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 4104 |
| Max CPU cycles  | 4104 |
| Avg CPU cycles  | 4104 |

**Verification: NotchBiQ Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-25  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Filter block NotchBiQ.

| Test results   |          |    |     |       |
|----------------|----------|----|-----|-------|
| Time step      | 1        | 2  | ... | 101   |
| CPU cycles     | 86       | 86 | ... | 86    |
| Inputs         |          |    |     |       |
| In (DSP)       | 0        | 0  | ... | 0.1   |
| In             | 0        | 0  | ... | 0.1   |
| Parameters     |          |    |     |       |
| method         | bilinear |    |     |       |
| fn             | 50       |    |     |       |
| Q              | 25       |    |     |       |
| ts_fact        | 1        |    |     |       |
| Outputs        |          |    |     |       |
| Out            | 0        | 0  | ... | 0.098 |
| Exp. Out       | 0        | 0  | ... | 0.098 |
| Out (DSP)      | 0        | 0  | ... | 0.098 |
| Exp. Out (DSP) | 0        | 0  | ... | 0.098 |

| Test settings |                                            |
|---------------|--------------------------------------------|
| Tolerance Out | $\pm 8,3819\text{e-}06$ ( $\pm 18000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 86 |
| Max CPU cycles  | 86 |
| Avg CPU cycles  | 86 |

**Test case: Conversion test****OK**

Conversion test for Filter block NotchBiQ.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 10       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>method</b>                | bilinear | bilinear | ... | bilinear |
| <b>fn</b>                    | 10       | 231.111  | ... | 2000     |
| <b>Q</b>                     | 10       | 20       | ... | 100      |
| <b>ts_fact</b>               | 1        | 1        | ... | 1        |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b2</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>a1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>a2</b>                    | 0.999    | 0.993    | ... | 0.991    |
| <b>b0</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>b1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. b2</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. a1</b>               | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. a2</b>               | 0.999    | 0.993    | ... | 0.991    |
| <b>Exp. b0</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. b1</b>               | -1.999   | -1.972   | ... | -0.615   |

| Test settings |                         |
|---------------|-------------------------|
| Tolerance b2  | $\pm 8,8818\text{e-}16$ |
| Tolerance a1  | $\pm 8,8818\text{e-}16$ |
| Tolerance a2  | $\pm 8,8818\text{e-}16$ |
| Tolerance b0  | $\pm 8,8818\text{e-}16$ |
| Tolerance b1  | $\pm 8,8818\text{e-}16$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block NotchBiQ.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 10       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>method</b>                | bilinear | bilinear | ... | bilinear |
| <b>fn</b>                    | 10       | 231.111  | ... | 2000     |
| <b>Q</b>                     | 10       | 20       | ... | 100      |
| <b>ts_fact</b>               | 1        | 1        | ... | 1        |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b2</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>a1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>a2</b>                    | 0.999    | 0.993    | ... | 0.991    |
| <b>b0</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>b1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. b2</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. a1</b>               | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. a2</b>               | 0.999    | 0.993    | ... | 0.991    |
| <b>Exp. b0</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. b1</b>               | -1.999   | -1.972   | ... | -0.615   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b2  | $\pm 2,0000e-07$ |
| Tolerance a1  | $\pm 5,0000e-07$ |
| Tolerance a2  | $\pm 1,0000e-07$ |
| Tolerance b0  | $\pm 2,0000e-07$ |
| Tolerance b1  | $\pm 5,0000e-07$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3207 |
| Max CPU cycles  | 3207 |
| Avg CPU cycles  | 3207 |

**Verification: NotchBiQ Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-25  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Filter block NotchBiQ.

| Test results   |          |      |     |       |
|----------------|----------|------|-----|-------|
| Time step      | 1        | 2    | ... | 101   |
| CPU cycles     | 1324     | 1324 | ... | 1774  |
| Inputs         |          |      |     |       |
| In (DSP)       | 0        | 0    | ... | 0.1   |
| In             | 0        | 0    | ... | 0.1   |
| Parameters     |          |      |     |       |
| method         | bilinear |      |     |       |
| fn             | 50       |      |     |       |
| Q              | 25       |      |     |       |
| ts_fact        | 1        |      |     |       |
| Outputs        |          |      |     |       |
| Out            | 0        | 0    | ... | 0.098 |
| Exp. Out       | 0        | 0    | ... | 0.098 |
| Out (DSP)      | 0        | 0    | ... | 0.098 |
| Exp. Out (DSP) | 0        | 0    | ... | 0.098 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 4,6566e-06$ ( $\pm 10000$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1201 |
| Max CPU cycles  | 1778 |
| Avg CPU cycles  | 1736 |

**Test case: Conversion test****OK**

Conversion test for Filter block NotchBiQ.



| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 10       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>method</b>                | bilinear | bilinear | ... | bilinear |
| <b>fn</b>                    | 10       | 231.111  | ... | 2000     |
| <b>Q</b>                     | 10       | 20       | ... | 100      |
| <b>ts_fact</b>               | 1        | 1        | ... | 1        |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b2</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>a1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>a2</b>                    | 0.999    | 0.993    | ... | 0.991    |
| <b>b0</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>b1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. b2</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. a1</b>               | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. a2</b>               | 0.999    | 0.993    | ... | 0.991    |
| <b>Exp. b0</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. b1</b>               | -1.999   | -1.972   | ... | -0.615   |

| Test settings |                         |
|---------------|-------------------------|
| Tolerance b2  | $\pm 8,8818\text{e-}16$ |
| Tolerance a1  | $\pm 8,8818\text{e-}16$ |
| Tolerance a2  | $\pm 8,8818\text{e-}16$ |
| Tolerance b0  | $\pm 8,8818\text{e-}16$ |
| Tolerance b1  | $\pm 8,8818\text{e-}16$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block NotchBiQ.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 10       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>method</b>                | bilinear | bilinear | ... | bilinear |
| <b>fn</b>                    | 10       | 231.111  | ... | 2000     |
| <b>Q</b>                     | 10       | 20       | ... | 100      |
| <b>ts_fact</b>               | 1        | 1        | ... | 1        |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b2</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>a1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>a2</b>                    | 0.999    | 0.993    | ... | 0.991    |
| <b>b0</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>b1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. b2</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. a1</b>               | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. a2</b>               | 0.999    | 0.993    | ... | 0.991    |
| <b>Exp. b0</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. b1</b>               | -1.999   | -1.972   | ... | -0.615   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b2  | $\pm 1,0000e-07$ |
| Tolerance a1  | $\pm 5,0000e-07$ |
| Tolerance a2  | $\pm 1,0000e-07$ |
| Tolerance b0  | $\pm 1,0000e-07$ |
| Tolerance b1  | $\pm 5,0000e-07$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 12660 |
| Max CPU cycles  | 13740 |
| Avg CPU cycles  | 12897 |

**Verification: NotchBiQ Float32 CPU STM32F072RB**

**Date of Test** 2026-06-25  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Filter block NotchBiQ.

| Test results   |          |      |     |       |
|----------------|----------|------|-----|-------|
| Time step      | 1        | 2    | ... | 101   |
| CPU cycles     | 1073     | 1073 | ... | 1572  |
| Inputs         |          |      |     |       |
| In (DSP)       | 0        | 0    | ... | 0.1   |
| In             | 0        | 0    | ... | 0.1   |
| Parameters     |          |      |     |       |
| method         | bilinear |      |     |       |
| fn             | 50       |      |     |       |
| Q              | 25       |      |     |       |
| ts_fact        | 1        |      |     |       |
| Outputs        |          |      |     |       |
| Out            | 0        | 0    | ... | 0.098 |
| Exp. Out       | 0        | 0    | ... | 0.098 |
| Out (DSP)      | 0        | 0    | ... | 0.098 |
| Exp. Out (DSP) | 0        | 0    | ... | 0.098 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 4,6566e-06$ ( $\pm 10000$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1073 |
| Max CPU cycles  | 1633 |
| Avg CPU cycles  | 1550 |

**Test case: Conversion test****OK**

Conversion test for Filter block NotchBiQ.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 10       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>method</b>                | bilinear | bilinear | ... | bilinear |
| <b>fn</b>                    | 10       | 231.111  | ... | 2000     |
| <b>Q</b>                     | 10       | 20       | ... | 100      |
| <b>ts_fact</b>               | 1        | 1        | ... | 1        |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b2</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>a1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>a2</b>                    | 0.999    | 0.993    | ... | 0.991    |
| <b>b0</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>b1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. b2</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. a1</b>               | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. a2</b>               | 0.999    | 0.993    | ... | 0.991    |
| <b>Exp. b0</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. b1</b>               | -1.999   | -1.972   | ... | -0.615   |

| Test settings |                         |
|---------------|-------------------------|
| Tolerance b2  | $\pm 8,8818\text{e-}16$ |
| Tolerance a1  | $\pm 8,8818\text{e-}16$ |
| Tolerance a2  | $\pm 8,8818\text{e-}16$ |
| Tolerance b0  | $\pm 8,8818\text{e-}16$ |
| Tolerance b1  | $\pm 8,8818\text{e-}16$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block NotchBiQ.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 10       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>method</b>                | bilinear | bilinear | ... | bilinear |
| <b>fn</b>                    | 10       | 231.111  | ... | 2000     |
| <b>Q</b>                     | 10       | 20       | ... | 100      |
| <b>ts_fact</b>               | 1        | 1        | ... | 1        |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b2</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>a1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>a2</b>                    | 0.999    | 0.993    | ... | 0.991    |
| <b>b0</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>b1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. b2</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. a1</b>               | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. a2</b>               | 0.999    | 0.993    | ... | 0.991    |
| <b>Exp. b0</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. b1</b>               | -1.999   | -1.972   | ... | -0.615   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b2  | $\pm 1,0000e-07$ |
| Tolerance a1  | $\pm 5,0000e-07$ |
| Tolerance a2  | $\pm 1,0000e-07$ |
| Tolerance b0  | $\pm 1,0000e-07$ |
| Tolerance b1  | $\pm 5,0000e-07$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 14055 |
| Max CPU cycles  | 14260 |
| Avg CPU cycles  | 14190 |

**Verification: NotchBiQ Float32 CPU STM32G474RE**

**Date of Test** 2026-06-25  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Filter block NotchBiQ.

| Test results   |          |     |     |       |
|----------------|----------|-----|-----|-------|
| Time step      | 1        | 2   | ... | 101   |
| CPU cycles     | 103      | 103 | ... | 103   |
| Inputs         |          |     |     |       |
| In (DSP)       | 0        | 0   | ... | 0.1   |
| In             | 0        | 0   | ... | 0.1   |
| Parameters     |          |     |     |       |
| method         | bilinear |     |     |       |
| fn             | 50       |     |     |       |
| Q              | 25       |     |     |       |
| ts_fact        | 1        |     |     |       |
| Outputs        |          |     |     |       |
| Out            | 0        | 0   | ... | 0.098 |
| Exp. Out       | 0        | 0   | ... | 0.098 |
| Out (DSP)      | 0        | 0   | ... | 0.098 |
| Exp. Out (DSP) | 0        | 0   | ... | 0.098 |

| Test settings |                                            |
|---------------|--------------------------------------------|
| Tolerance Out | $\pm 8,3819\text{e-}06$ ( $\pm 18000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 103 |
| Max CPU cycles  | 103 |
| Avg CPU cycles  | 103 |

**Test case: Conversion test****OK**

Conversion test for Filter block NotchBiQ.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 10       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>method</b>                | bilinear | bilinear | ... | bilinear |
| <b>fn</b>                    | 10       | 231.111  | ... | 2000     |
| <b>Q</b>                     | 10       | 20       | ... | 100      |
| <b>ts_fact</b>               | 1        | 1        | ... | 1        |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b2</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>a1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>a2</b>                    | 0.999    | 0.993    | ... | 0.991    |
| <b>b0</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>b1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. b2</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. a1</b>               | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. a2</b>               | 0.999    | 0.993    | ... | 0.991    |
| <b>Exp. b0</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. b1</b>               | -1.999   | -1.972   | ... | -0.615   |

| Test settings |                         |
|---------------|-------------------------|
| Tolerance b2  | $\pm 8,8818\text{e-}16$ |
| Tolerance a1  | $\pm 8,8818\text{e-}16$ |
| Tolerance a2  | $\pm 8,8818\text{e-}16$ |
| Tolerance b0  | $\pm 8,8818\text{e-}16$ |
| Tolerance b1  | $\pm 8,8818\text{e-}16$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block NotchBiQ.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 10       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>method</b>                | bilinear | bilinear | ... | bilinear |
| <b>fn</b>                    | 10       | 231.111  | ... | 2000     |
| <b>Q</b>                     | 10       | 20       | ... | 100      |
| <b>ts_fact</b>               | 1        | 1        | ... | 1        |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b2</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>a1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>a2</b>                    | 0.999    | 0.993    | ... | 0.991    |
| <b>b0</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>b1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. b2</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. a1</b>               | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. a2</b>               | 0.999    | 0.993    | ... | 0.991    |
| <b>Exp. b0</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. b1</b>               | -1.999   | -1.972   | ... | -0.615   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b2  | $\pm 2,0000e-07$ |
| Tolerance a1  | $\pm 5,0000e-07$ |
| Tolerance a2  | $\pm 1,0000e-07$ |
| Tolerance b0  | $\pm 2,0000e-07$ |
| Tolerance b1  | $\pm 5,0000e-07$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1430 |
| Max CPU cycles  | 1430 |
| Avg CPU cycles  | 1430 |



**Verification: NotchBiQ Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-25  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Filter block NotchBiQ.

| Test results   |          |    |     |       |
|----------------|----------|----|-----|-------|
| Time step      | 1        | 2  | ... | 101   |
| CPU cycles     | 111      | 99 | ... | 99    |
| Inputs         |          |    |     |       |
| In (DSP)       | 0        | 0  | ... | 0.1   |
| In             | 0        | 0  | ... | 0.1   |
| Parameters     |          |    |     |       |
| method         | bilinear |    |     |       |
| fn             | 50       |    |     |       |
| Q              | 25       |    |     |       |
| ts_fact        | 1        |    |     |       |
| Outputs        |          |    |     |       |
| Out            | 0        | 0  | ... | 0.098 |
| Exp. Out       | 0        | 0  | ... | 0.098 |
| Out (DSP)      | 0        | 0  | ... | 0.098 |
| Exp. Out (DSP) | 0        | 0  | ... | 0.098 |

| Test settings |                                            |
|---------------|--------------------------------------------|
| Tolerance Out | $\pm 8,3819\text{e-}06$ ( $\pm 18000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 99  |
| Max CPU cycles  | 111 |
| Avg CPU cycles  | 99  |

**Test case: Conversion test****OK**

Conversion test for Filter block NotchBiQ.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 10       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>method</b>                | bilinear | bilinear | ... | bilinear |
| <b>fn</b>                    | 10       | 231.111  | ... | 2000     |
| <b>Q</b>                     | 10       | 20       | ... | 100      |
| <b>ts_fact</b>               | 1        | 1        | ... | 1        |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b2</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>a1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>a2</b>                    | 0.999    | 0.993    | ... | 0.991    |
| <b>b0</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>b1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. b2</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. a1</b>               | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. a2</b>               | 0.999    | 0.993    | ... | 0.991    |
| <b>Exp. b0</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. b1</b>               | -1.999   | -1.972   | ... | -0.615   |

| Test settings |                         |
|---------------|-------------------------|
| Tolerance b2  | $\pm 8,8818\text{e-}16$ |
| Tolerance a1  | $\pm 8,8818\text{e-}16$ |
| Tolerance a2  | $\pm 8,8818\text{e-}16$ |
| Tolerance b0  | $\pm 8,8818\text{e-}16$ |
| Tolerance b1  | $\pm 8,8818\text{e-}16$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block NotchBiQ.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 10       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>method</b>                | bilinear | bilinear | ... | bilinear |
| <b>fn</b>                    | 10       | 231.111  | ... | 2000     |
| <b>Q</b>                     | 10       | 20       | ... | 100      |
| <b>ts_fact</b>               | 1        | 1        | ... | 1        |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b2</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>a1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>a2</b>                    | 0.999    | 0.993    | ... | 0.991    |
| <b>b0</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>b1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. b2</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. a1</b>               | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. a2</b>               | 0.999    | 0.993    | ... | 0.991    |
| <b>Exp. b0</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. b1</b>               | -1.999   | -1.972   | ... | -0.615   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b2  | $\pm 2,0000e-07$ |
| Tolerance a1  | $\pm 5,0000e-07$ |
| Tolerance a2  | $\pm 1,0000e-07$ |
| Tolerance b0  | $\pm 2,0000e-07$ |
| Tolerance b1  | $\pm 5,0000e-07$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1323 |
| Max CPU cycles  | 1579 |
| Avg CPU cycles  | 1348 |

**Verification: NotchBiQ Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-25  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Filter block NotchBiQ.

| Test results   |          |     |     |       |
|----------------|----------|-----|-----|-------|
| Time step      | 1        | 2   | ... | 101   |
| CPU cycles     | 377      | 377 | ... | 575   |
| Inputs         |          |     |     |       |
| In (DSP)       | 0        | 0   | ... | 0.1   |
| In             | 0        | 0   | ... | 0.1   |
| Parameters     |          |     |     |       |
| method         | bilinear |     |     |       |
| fn             | 50       |     |     |       |
| Q              | 25       |     |     |       |
| ts_fact        | 1        |     |     |       |
| Outputs        |          |     |     |       |
| Out            | 0        | 0   | ... | 0.098 |
| Exp. Out       | 0        | 0   | ... | 0.098 |
| Out (DSP)      | 0        | 0   | ... | 0.098 |
| Exp. Out (DSP) | 0        | 0   | ... | 0.098 |

| Test settings |                                            |
|---------------|--------------------------------------------|
| Tolerance Out | $\pm 8,3819\text{e-}06$ ( $\pm 18000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 377 |
| Max CPU cycles  | 578 |
| Avg CPU cycles  | 566 |

**Test case: Conversion test****OK**

Conversion test for Filter block NotchBiQ.

| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 10       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>method</b>                | bilinear | bilinear | ... | bilinear |
| <b>fn</b>                    | 10       | 231.111  | ... | 2000     |
| <b>Q</b>                     | 10       | 20       | ... | 100      |
| <b>ts_fact</b>               | 1        | 1        | ... | 1        |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b2</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>a1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>a2</b>                    | 0.999    | 0.993    | ... | 0.991    |
| <b>b0</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>b1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. b2</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. a1</b>               | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. a2</b>               | 0.999    | 0.993    | ... | 0.991    |
| <b>Exp. b0</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. b1</b>               | -1.999   | -1.972   | ... | -0.615   |

| Test settings |                         |
|---------------|-------------------------|
| Tolerance b2  | $\pm 8,8818\text{e-}16$ |
| Tolerance a1  | $\pm 8,8818\text{e-}16$ |
| Tolerance a2  | $\pm 8,8818\text{e-}16$ |
| Tolerance b0  | $\pm 8,8818\text{e-}16$ |
| Tolerance b1  | $\pm 8,8818\text{e-}16$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Filter block NotchBiQ.


| Test results                 |          |          |     |          |
|------------------------------|----------|----------|-----|----------|
| <b>Time step</b>             | 1        | 2        | ... | 10       |
| <i>Mask parameters</i>       |          |          |     |          |
| <b>method</b>                | bilinear | bilinear | ... | bilinear |
| <b>fn</b>                    | 10       | 231.111  | ... | 2000     |
| <b>Q</b>                     | 10       | 20       | ... | 100      |
| <b>ts_fact</b>               | 1        | 1        | ... | 1        |
| <i>Controller parameters</i> |          |          |     |          |
| <b>b2</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>a1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>a2</b>                    | 0.999    | 0.993    | ... | 0.991    |
| <b>b0</b>                    | 1        | 0.996    | ... | 0.995    |
| <b>b1</b>                    | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. b2</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. a1</b>               | -1.999   | -1.972   | ... | -0.615   |
| <b>Exp. a2</b>               | 0.999    | 0.993    | ... | 0.991    |
| <b>Exp. b0</b>               | 1        | 0.996    | ... | 0.995    |
| <b>Exp. b1</b>               | -1.999   | -1.972   | ... | -0.615   |

| Test settings |                  |
|---------------|------------------|
| Tolerance b2  | $\pm 2,0000e-07$ |
| Tolerance a1  | $\pm 5,0000e-07$ |
| Tolerance a2  | $\pm 1,0000e-07$ |
| Tolerance b0  | $\pm 2,0000e-07$ |
| Tolerance b1  | $\pm 5,0000e-07$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3093 |
| Max CPU cycles  | 3166 |
| Avg CPU cycles  | 3116 |


## 5 General

Library with general purpose blocks.



## Block: And

---



Logical AND block.

| Inports |  |
|---------|--|
| In1     |  |
| In2     |  |

| Outports |  |
|----------|--|
| Out      |  |

### Implementations:

**Bool**     Boolean Implementation

### Implementation: Bool

---

Boolean Implementation

| Inports Data Type |      |
|-------------------|------|
| In1               | bool |
| In2               | bool |

| Outports Data Type |      |
|--------------------|------|
| Out                | bool |



**Verification: And Bool CPU TMS320F28335****Date of Test** 2026-06-19**Target controller** TMS320F28335**Test case: Inport test****OK**

Inport test for General block And.

| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 25 |
| <b>CPU cycles</b>     | 64 | 64 | 64   | 64   | ... | 67 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In1 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In2 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In1</b>            | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <b>In2</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Exp. Out</b>       | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Out (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Exp. Out (DSP)</b> | 0  | 0  | 0    | 0    | ... | 1  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 64 |
| Max CPU cycles  | 67 |
| Avg CPU cycles  | 64 |

**Verification: And Bool CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block And.

| Test results   |    |    |      |      |     |    |
|----------------|----|----|------|------|-----|----|
| Time step      | 1  | 2  | 3    | 4    | ... | 25 |
| CPU cycles     | 31 | 31 | 31   | 31   | ... | 33 |
| Inputs         |    |    |      |      |     |    |
| In1 (DSP)      | 0  | 0  | 0    | 0    | ... | 1  |
| In2 (DSP)      | 0  | 0  | 0    | 0    | ... | 1  |
| In1            | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| In2            | 0  | 0  | 0    | 0    | ... | 1  |
| Outputs        |    |    |      |      |     |    |
| Out            | 0  | 0  | 0    | 0    | ... | 1  |
| Exp. Out       | 0  | 0  | 0    | 0    | ... | 1  |
| Out (DSP)      | 0  | 0  | 0    | 0    | ... | 1  |
| Exp. Out (DSP) | 0  | 0  | 0    | 0    | ... | 1  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 33 |
| Avg CPU cycles  | 31 |

**Verification: And Bool CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block And.

| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 25 |
| <b>CPU cycles</b>     | 57 | 57 | 57   | 57   | ... | 57 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In1 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In2 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In1</b>            | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <b>In2</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Exp. Out</b>       | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Out (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Exp. Out (DSP)</b> | 0  | 0  | 0    | 0    | ... | 1  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 57 |

**Verification: And Bool CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block And.

| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 25 |
| <b>CPU cycles</b>     | 50 | 50 | 50   | 50   | ... | 52 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In1 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In2 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In1</b>            | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <b>In2</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Exp. Out</b>       | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Out (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Exp. Out (DSP)</b> | 0  | 0  | 0    | 0    | ... | 1  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 50 |
| Max CPU cycles  | 52 |
| Avg CPU cycles  | 50 |

**Verification: And Bool CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block And.

| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 25 |
| <b>CPU cycles</b>     | 30 | 30 | 30   | 30   | ... | 35 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In1 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In2 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In1</b>            | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <b>In2</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Exp. Out</b>       | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Out (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Exp. Out (DSP)</b> | 0  | 0  | 0    | 0    | ... | 1  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 30 |
| Max CPU cycles  | 35 |
| Avg CPU cycles  | 30 |

**Verification: And Bool CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block And.

| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 25 |
| <b>CPU cycles</b>     | 45 | 45 | 45   | 45   | ... | 45 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In1 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In2 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In1</b>            | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <b>In2</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Exp. Out</b>       | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Out (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Exp. Out (DSP)</b> | 0  | 0  | 0    | 0    | ... | 1  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 45 |
| Max CPU cycles  | 45 |
| Avg CPU cycles  | 45 |

**Verification: And Bool CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block And.

| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 25 |
| <b>CPU cycles</b>     | 58 | 58 | 58   | 58   | ... | 60 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In1 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In2 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In1</b>            | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <b>In2</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Exp. Out</b>       | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Out (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Exp. Out (DSP)</b> | 0  | 0  | 0    | 0    | ... | 1  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 58 |
| Max CPU cycles  | 60 |
| Avg CPU cycles  | 58 |

**Verification: And Bool CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block And.

| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 25 |
| <b>CPU cycles</b>     | 47 | 47 | 47   | 47   | ... | 49 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In1 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In2 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In1</b>            | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <b>In2</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Exp. Out</b>       | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Out (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Exp. Out (DSP)</b> | 0  | 0  | 0    | 0    | ... | 1  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 47 |
| Max CPU cycles  | 49 |
| Avg CPU cycles  | 47 |



## Block: AutoSwitch

---



Switch between In1 and In3 dependent on Switch signal:

Switch signal rising: Switch  $\geq$  Threshold up  $\rightarrow$  Out = In1

Switch signal falling: Switch  $<$  Threshold down  $\rightarrow$  Out = In3

| Inports |                            |
|---------|----------------------------|
| In1     | Input #1                   |
| Switch  | Input #2: Threshold signal |
| In3     | Input #3                   |

| Outputs |                                                                     |
|---------|---------------------------------------------------------------------|
| Out     | Either value of input #1 or input #3 dependent on value of input #2 |

| Mask Parameters |    |                                           |
|-----------------|----|-------------------------------------------|
| Name            | ID | Description                               |
| Thresh_up       | 1  | Threshold level for rising switch signal  |
| Thresh_down     | 2  | Threshold level for falling switch signal |

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In1               | int16 |
| Switch            | int16 |
| In3               | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In1               | int32 |
| Switch            | int32 |
| In3               | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In1               | float32 |
| Switch            | float32 |
| In3               | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In1               | float64 |
| Switch            | float64 |
| In3               | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: AutoSwitch FiP16 CPU TMS320F28335**

Date of Test 2026-06-19  
Target controller TMS320F28335

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 137    |
| CPU cycles     | 71     | 71     | 71     | 71     | ... | 71     |
| Inputs         |        |        |        |        |     |        |
| In1 (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Switch (DSP)   | 30005  | 28152  | 32440  | 32440  | ... | 14425  |
| In3 (DSP)      | 32767  | 32293  | 31818  | 31343  | ... | -32293 |
| In1            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Switch         | 0.916  | 0.859  | 0.99   | 0.99   | ... | 0.44   |
| In3            | 1      | 0.986  | 0.971  | 0.957  | ... | -0.986 |
| Parameters     |        |        |        |        |     |        |
| Thresh_up      | 0.3    |        |        |        |     |        |
| Thresh_down    | -0.1   |        |        |        |     |        |
| Outputs        |        |        |        |        |     |        |
| Out            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Exp. Out       | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Out (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Exp. Out (DSP) | -32768 | -32293 | -31818 | -31343 | ... | 32293  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 71 |
| Max CPU cycles  | 79 |
| Avg CPU cycles  | 74 |

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 137    |
| CPU cycles     | 71     | 71     | 71     | 71     | ... | 71     |
| Inputs         |        |        |        |        |     |        |
| In1 (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Switch (DSP)   | 30005  | 28152  | 32440  | 32440  | ... | 14425  |
| In3 (DSP)      | 32767  | 32293  | 31818  | 31343  | ... | -32293 |
| In1            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Switch         | 0.916  | 0.859  | 0.99   | 0.99   | ... | 0.44   |
| In3            | 1      | 0.986  | 0.971  | 0.957  | ... | -0.986 |
| Parameters     |        |        |        |        |     |        |
| Thresh_up      | 0      |        |        |        |     |        |
| Thresh_down    | 0      |        |        |        |     |        |
| Outputs        |        |        |        |        |     |        |
| Out            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Exp. Out       | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Out (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Exp. Out (DSP) | -32768 | -32293 | -31818 | -31343 | ... | 32293  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 71 |
| Max CPU cycles  | 79 |
| Avg CPU cycles  | 74 |

#### Test case: Conversion test

OK

Conversion test for General block AutoSwitch.

| Test results                 |   |      |      |       |     |        |
|------------------------------|---|------|------|-------|-----|--------|
| <b>Time step</b>             | 1 | 2    | 3    | 4     | ... | 11     |
| <i>Mask parameters</i>       |   |      |      |       |     |        |
| <b>Thresh_up</b>             | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <b>Thresh_down</b>           | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <i>Controller parameters</i> |   |      |      |       |     |        |
| <b>Thresh_down</b>           | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Thresh_up</b>             | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Exp. Thresh_down</b>      | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Exp. Thresh_up</b>        | 0 | 3277 | 6554 | 16384 | ... | -32767 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 0,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block AutoSwitch.

| Test results                 |   |      |      |       |     |        |
|------------------------------|---|------|------|-------|-----|--------|
| <b>Time step</b>             | 1 | 2    | 3    | 4     | ... | 11     |
| <i>Mask parameters</i>       |   |      |      |       |     |        |
| <b>Thresh_up</b>             | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <b>Thresh_down</b>           | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <i>Controller parameters</i> |   |      |      |       |     |        |
| <b>Thresh_down</b>           | 0 | 3276 | 6553 | 16384 | ... | -32767 |
| <b>Thresh_up</b>             | 0 | 3276 | 6553 | 16384 | ... | -32767 |
| <b>Exp. Thresh_down</b>      | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Exp. Thresh_up</b>        | 0 | 3277 | 6554 | 16384 | ... | -32767 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 1,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1350 |
| Max CPU cycles  | 1384 |
| Avg CPU cycles  | 1353 |

**Verification: AutoSwitch FiP16 CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 137    |
| CPU cycles     | 31     | 31     | 31     | 31     | ... | 31     |
| Inputs         |        |        |        |        |     |        |
| In1 (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Switch (DSP)   | 30005  | 28152  | 32440  | 32440  | ... | 14425  |
| In3 (DSP)      | 32767  | 32293  | 31818  | 31343  | ... | -32293 |
| In1            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Switch         | 0.916  | 0.859  | 0.99   | 0.99   | ... | 0.44   |
| In3            | 1      | 0.986  | 0.971  | 0.957  | ... | -0.986 |
| Parameters     |        |        |        |        |     |        |
| Thresh_up      | 0.3    |        |        |        |     |        |
| Thresh_down    | -0.1   |        |        |        |     |        |
| Outputs        |        |        |        |        |     |        |
| Out            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Exp. Out       | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Out (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Exp. Out (DSP) | -32768 | -32293 | -31818 | -31343 | ... | 32293  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 39 |
| Avg CPU cycles  | 34 |

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 137    |
| CPU cycles     | 31     | 31     | 31     | 31     | ... | 31     |
| Inputs         |        |        |        |        |     |        |
| In1 (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Switch (DSP)   | 30005  | 28152  | 32440  | 32440  | ... | 14425  |
| In3 (DSP)      | 32767  | 32293  | 31818  | 31343  | ... | -32293 |
| In1            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Switch         | 0.916  | 0.859  | 0.99   | 0.99   | ... | 0.44   |
| In3            | 1      | 0.986  | 0.971  | 0.957  | ... | -0.986 |
| Parameters     |        |        |        |        |     |        |
| Thresh_up      | 0      |        |        |        |     |        |
| Thresh_down    | 0      |        |        |        |     |        |
| Outputs        |        |        |        |        |     |        |
| Out            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Exp. Out       | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Out (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Exp. Out (DSP) | -32768 | -32293 | -31818 | -31343 | ... | 32293  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 39 |
| Avg CPU cycles  | 34 |

#### Test case: Conversion test

OK

Conversion test for General block AutoSwitch.



| Test results                 |   |      |      |       |     |        |
|------------------------------|---|------|------|-------|-----|--------|
| <b>Time step</b>             | 1 | 2    | 3    | 4     | ... | 11     |
| <i>Mask parameters</i>       |   |      |      |       |     |        |
| <b>Thresh_up</b>             | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <b>Thresh_down</b>           | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <i>Controller parameters</i> |   |      |      |       |     |        |
| <b>Thresh_down</b>           | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Thresh_up</b>             | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Exp. Thresh_down</b>      | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Exp. Thresh_up</b>        | 0 | 3277 | 6554 | 16384 | ... | -32767 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 0,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block AutoSwitch.

| Test results                 |   |      |      |       |     |        |
|------------------------------|---|------|------|-------|-----|--------|
| <b>Time step</b>             | 1 | 2    | 3    | 4     | ... | 11     |
| <i>Mask parameters</i>       |   |      |      |       |     |        |
| <b>Thresh_up</b>             | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <b>Thresh_down</b>           | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <i>Controller parameters</i> |   |      |      |       |     |        |
| <b>Thresh_down</b>           | 0 | 3276 | 6553 | 16384 | ... | -32767 |
| <b>Thresh_up</b>             | 0 | 3276 | 6553 | 16384 | ... | -32767 |
| <b>Exp. Thresh_down</b>      | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Exp. Thresh_up</b>        | 0 | 3277 | 6554 | 16384 | ... | -32767 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 1,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 1,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 637 |
| Max CPU cycles  | 649 |
| Avg CPU cycles  | 644 |

**Verification: AutoSwitch FiP16 CPU STM32G474RE**

Date of Test 2026-06-19  
Target controller STM32G474RE

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 137    |
| CPU cycles     | 62     | 62     | 62     | 62     | ... | 62     |
| Inputs         |        |        |        |        |     |        |
| In1 (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Switch (DSP)   | 30005  | 28152  | 32440  | 32440  | ... | 14425  |
| In3 (DSP)      | 32767  | 32293  | 31818  | 31343  | ... | -32293 |
| In1            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Switch         | 0.916  | 0.859  | 0.99   | 0.99   | ... | 0.44   |
| In3            | 1      | 0.986  | 0.971  | 0.957  | ... | -0.986 |
| Parameters     |        |        |        |        |     |        |
| Thresh_up      | 0.3    |        |        |        |     |        |
| Thresh_down    | -0.1   |        |        |        |     |        |
| Outputs        |        |        |        |        |     |        |
| Out            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Exp. Out       | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Out (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Exp. Out (DSP) | -32768 | -32293 | -31818 | -31343 | ... | 32293  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 77 |
| Avg CPU cycles  | 70 |

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 137    |
| CPU cycles     | 62     | 62     | 62     | 62     | ... | 62     |
| Inputs         |        |        |        |        |     |        |
| In1 (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Switch (DSP)   | 30005  | 28152  | 32440  | 32440  | ... | 14425  |
| In3 (DSP)      | 32767  | 32293  | 31818  | 31343  | ... | -32293 |
| In1            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Switch         | 0.916  | 0.859  | 0.99   | 0.99   | ... | 0.44   |
| In3            | 1      | 0.986  | 0.971  | 0.957  | ... | -0.986 |
| Parameters     |        |        |        |        |     |        |
| Thresh_up      | 0      |        |        |        |     |        |
| Thresh_down    | 0      |        |        |        |     |        |
| Outputs        |        |        |        |        |     |        |
| Out            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Exp. Out       | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Out (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Exp. Out (DSP) | -32768 | -32293 | -31818 | -31343 | ... | 32293  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 77 |
| Avg CPU cycles  | 68 |

#### Test case: Conversion test

OK

Conversion test for General block AutoSwitch.

| Test results                 |   |      |      |       |     |        |
|------------------------------|---|------|------|-------|-----|--------|
| <b>Time step</b>             | 1 | 2    | 3    | 4     | ... | 11     |
| <i>Mask parameters</i>       |   |      |      |       |     |        |
| <b>Thresh_up</b>             | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <b>Thresh_down</b>           | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <i>Controller parameters</i> |   |      |      |       |     |        |
| <b>Thresh_down</b>           | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Thresh_up</b>             | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Exp. Thresh_down</b>      | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Exp. Thresh_up</b>        | 0 | 3277 | 6554 | 16384 | ... | -32767 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 0,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block AutoSwitch.

| Test results                 |   |      |      |       |     |        |
|------------------------------|---|------|------|-------|-----|--------|
| <b>Time step</b>             | 1 | 2    | 3    | 4     | ... | 11     |
| <i>Mask parameters</i>       |   |      |      |       |     |        |
| <b>Thresh_up</b>             | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <b>Thresh_down</b>           | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <i>Controller parameters</i> |   |      |      |       |     |        |
| <b>Thresh_down</b>           | 0 | 3276 | 6553 | 16384 | ... | -32767 |
| <b>Thresh_up</b>             | 0 | 3276 | 6553 | 16384 | ... | -32767 |
| <b>Exp. Thresh_down</b>      | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Exp. Thresh_up</b>        | 0 | 3277 | 6554 | 16384 | ... | -32767 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 1,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 1,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 800 |
| Max CPU cycles  | 848 |
| Avg CPU cycles  | 804 |

**Verification: AutoSwitch FiP16 CPU STM32F072RB**

Date of Test 2026-06-19  
Target controller STM32F072RB

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 137    |
| CPU cycles     | 59     | 59     | 59     | 59     | ... | 59     |
| Inputs         |        |        |        |        |     |        |
| In1 (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Switch (DSP)   | 30005  | 28152  | 32440  | 32440  | ... | 14425  |
| In3 (DSP)      | 32767  | 32293  | 31818  | 31343  | ... | -32293 |
| In1            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Switch         | 0.916  | 0.859  | 0.99   | 0.99   | ... | 0.44   |
| In3            | 1      | 0.986  | 0.971  | 0.957  | ... | -0.986 |
| Parameters     |        |        |        |        |     |        |
| Thresh_up      | 0.3    |        |        |        |     |        |
| Thresh_down    | -0.1   |        |        |        |     |        |
| Outputs        |        |        |        |        |     |        |
| Out            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Exp. Out       | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Out (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Exp. Out (DSP) | -32768 | -32293 | -31818 | -31343 | ... | 32293  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 73 |
| Avg CPU cycles  | 66 |

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 137    |
| CPU cycles     | 59     | 59     | 59     | 59     | ... | 59     |
| Inputs         |        |        |        |        |     |        |
| In1 (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Switch (DSP)   | 30005  | 28152  | 32440  | 32440  | ... | 14425  |
| In3 (DSP)      | 32767  | 32293  | 31818  | 31343  | ... | -32293 |
| In1            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Switch         | 0.916  | 0.859  | 0.99   | 0.99   | ... | 0.44   |
| In3            | 1      | 0.986  | 0.971  | 0.957  | ... | -0.986 |
| Parameters     |        |        |        |        |     |        |
| Thresh_up      | 0      |        |        |        |     |        |
| Thresh_down    | 0      |        |        |        |     |        |
| Outputs        |        |        |        |        |     |        |
| Out            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Exp. Out       | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Out (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Exp. Out (DSP) | -32768 | -32293 | -31818 | -31343 | ... | 32293  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 73 |
| Avg CPU cycles  | 65 |

#### Test case: Conversion test

OK

Conversion test for General block AutoSwitch.



| Test results                 |   |      |      |       |     |        |
|------------------------------|---|------|------|-------|-----|--------|
| <b>Time step</b>             | 1 | 2    | 3    | 4     | ... | 11     |
| <i>Mask parameters</i>       |   |      |      |       |     |        |
| <b>Thresh_up</b>             | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <b>Thresh_down</b>           | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <i>Controller parameters</i> |   |      |      |       |     |        |
| <b>Thresh_down</b>           | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Thresh_up</b>             | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Exp. Thresh_down</b>      | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Exp. Thresh_up</b>        | 0 | 3277 | 6554 | 16384 | ... | -32767 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 0,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block AutoSwitch.

| Test results                 |   |      |      |       |     |        |
|------------------------------|---|------|------|-------|-----|--------|
| <b>Time step</b>             | 1 | 2    | 3    | 4     | ... | 11     |
| <i>Mask parameters</i>       |   |      |      |       |     |        |
| <b>Thresh_up</b>             | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <b>Thresh_down</b>           | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <i>Controller parameters</i> |   |      |      |       |     |        |
| <b>Thresh_down</b>           | 0 | 3276 | 6553 | 16384 | ... | -32767 |
| <b>Thresh_up</b>             | 0 | 3276 | 6553 | 16384 | ... | -32767 |
| <b>Exp. Thresh_down</b>      | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Exp. Thresh_up</b>        | 0 | 3277 | 6554 | 16384 | ... | -32767 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 1,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1429 |
| Max CPU cycles  | 1657 |
| Avg CPU cycles  | 1626 |

**Verification: AutoSwitch FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 137    |
| CPU cycles     | 39     | 39     | 39     | 39     | ... | 39     |
| Inputs         |        |        |        |        |     |        |
| In1 (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Switch (DSP)   | 30005  | 28152  | 32440  | 32440  | ... | 14425  |
| In3 (DSP)      | 32767  | 32293  | 31818  | 31343  | ... | -32293 |
| In1            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Switch         | 0.916  | 0.859  | 0.99   | 0.99   | ... | 0.44   |
| In3            | 1      | 0.986  | 0.971  | 0.957  | ... | -0.986 |
| Parameters     |        |        |        |        |     |        |
| Thresh_up      | 0.3    |        |        |        |     |        |
| Thresh_down    | -0.1   |        |        |        |     |        |
| Outputs        |        |        |        |        |     |        |
| Out            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Exp. Out       | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Out (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Exp. Out (DSP) | -32768 | -32293 | -31818 | -31343 | ... | 32293  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 39 |
| Max CPU cycles  | 43 |
| Avg CPU cycles  | 41 |

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 137    |
| CPU cycles     | 39     | 39     | 39     | 39     | ... | 39     |
| Inputs         |        |        |        |        |     |        |
| In1 (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Switch (DSP)   | 30005  | 28152  | 32440  | 32440  | ... | 14425  |
| In3 (DSP)      | 32767  | 32293  | 31818  | 31343  | ... | -32293 |
| In1            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Switch         | 0.916  | 0.859  | 0.99   | 0.99   | ... | 0.44   |
| In3            | 1      | 0.986  | 0.971  | 0.957  | ... | -0.986 |
| Parameters     |        |        |        |        |     |        |
| Thresh_up      | 0      |        |        |        |     |        |
| Thresh_down    | 0      |        |        |        |     |        |
| Outputs        |        |        |        |        |     |        |
| Out            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Exp. Out       | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Out (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Exp. Out (DSP) | -32768 | -32293 | -31818 | -31343 | ... | 32293  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 39 |
| Max CPU cycles  | 43 |
| Avg CPU cycles  | 40 |

#### Test case: Conversion test

OK

Conversion test for General block AutoSwitch.

| Test results                 |   |      |      |       |     |        |
|------------------------------|---|------|------|-------|-----|--------|
| <b>Time step</b>             | 1 | 2    | 3    | 4     | ... | 11     |
| <i>Mask parameters</i>       |   |      |      |       |     |        |
| <b>Thresh_up</b>             | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <b>Thresh_down</b>           | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <i>Controller parameters</i> |   |      |      |       |     |        |
| <b>Thresh_down</b>           | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Thresh_up</b>             | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Exp. Thresh_down</b>      | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Exp. Thresh_up</b>        | 0 | 3277 | 6554 | 16384 | ... | -32767 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 0,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block AutoSwitch.

| Test results                 |   |      |      |       |     |        |
|------------------------------|---|------|------|-------|-----|--------|
| <b>Time step</b>             | 1 | 2    | 3    | 4     | ... | 11     |
| <i>Mask parameters</i>       |   |      |      |       |     |        |
| <b>Thresh_up</b>             | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <b>Thresh_down</b>           | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <i>Controller parameters</i> |   |      |      |       |     |        |
| <b>Thresh_down</b>           | 0 | 3276 | 6553 | 16384 | ... | -32767 |
| <b>Thresh_up</b>             | 0 | 3276 | 6553 | 16384 | ... | -32767 |
| <b>Exp. Thresh_down</b>      | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Exp. Thresh_up</b>        | 0 | 3277 | 6554 | 16384 | ... | -32767 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 1,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 1,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 648 |
| Max CPU cycles  | 724 |
| Avg CPU cycles  | 713 |

**Verification: AutoSwitch FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 137    |
| CPU cycles     | 50     | 50     | 50     | 50     | ... | 50     |
| Inputs         |        |        |        |        |     |        |
| In1 (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Switch (DSP)   | 30005  | 28152  | 32440  | 32440  | ... | 14425  |
| In3 (DSP)      | 32767  | 32293  | 31818  | 31343  | ... | -32293 |
| In1            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Switch         | 0.916  | 0.859  | 0.99   | 0.99   | ... | 0.44   |
| In3            | 1      | 0.986  | 0.971  | 0.957  | ... | -0.986 |
| Parameters     |        |        |        |        |     |        |
| Thresh_up      | 0.3    |        |        |        |     |        |
| Thresh_down    | -0.1   |        |        |        |     |        |
| Outputs        |        |        |        |        |     |        |
| Out            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Exp. Out       | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Out (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Exp. Out (DSP) | -32768 | -32293 | -31818 | -31343 | ... | 32293  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 50 |
| Max CPU cycles  | 53 |
| Avg CPU cycles  | 50 |

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 137    |
| CPU cycles     | 50     | 50     | 50     | 50     | ... | 50     |
| Inputs         |        |        |        |        |     |        |
| In1 (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Switch (DSP)   | 30005  | 28152  | 32440  | 32440  | ... | 14425  |
| In3 (DSP)      | 32767  | 32293  | 31818  | 31343  | ... | -32293 |
| In1            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Switch         | 0.916  | 0.859  | 0.99   | 0.99   | ... | 0.44   |
| In3            | 1      | 0.986  | 0.971  | 0.957  | ... | -0.986 |
| Parameters     |        |        |        |        |     |        |
| Thresh_up      | 0      |        |        |        |     |        |
| Thresh_down    | 0      |        |        |        |     |        |
| Outputs        |        |        |        |        |     |        |
| Out            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Exp. Out       | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Out (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Exp. Out (DSP) | -32768 | -32293 | -31818 | -31343 | ... | 32293  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 50 |
| Max CPU cycles  | 50 |
| Avg CPU cycles  | 50 |

#### Test case: Conversion test

OK

Conversion test for General block AutoSwitch.



| Test results                 |   |      |      |       |     |        |
|------------------------------|---|------|------|-------|-----|--------|
| <b>Time step</b>             | 1 | 2    | 3    | 4     | ... | 11     |
| <i>Mask parameters</i>       |   |      |      |       |     |        |
| <b>Thresh_up</b>             | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <b>Thresh_down</b>           | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <i>Controller parameters</i> |   |      |      |       |     |        |
| <b>Thresh_down</b>           | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Thresh_up</b>             | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Exp. Thresh_down</b>      | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Exp. Thresh_up</b>        | 0 | 3277 | 6554 | 16384 | ... | -32767 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 0,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block AutoSwitch.

| Test results                 |   |      |      |       |     |        |
|------------------------------|---|------|------|-------|-----|--------|
| <b>Time step</b>             | 1 | 2    | 3    | 4     | ... | 11     |
| <i>Mask parameters</i>       |   |      |      |       |     |        |
| <b>Thresh_up</b>             | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <b>Thresh_down</b>           | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <i>Controller parameters</i> |   |      |      |       |     |        |
| <b>Thresh_down</b>           | 0 | 3276 | 6553 | 16384 | ... | -32767 |
| <b>Thresh_up</b>             | 0 | 3276 | 6553 | 16384 | ... | -32767 |
| <b>Exp. Thresh_down</b>      | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Exp. Thresh_up</b>        | 0 | 3277 | 6554 | 16384 | ... | -32767 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 1,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1623 |
| Max CPU cycles  | 2545 |
| Avg CPU cycles  | 2426 |

**Verification: AutoSwitch FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 137    |
| CPU cycles     | 61     | 61     | 61     | 61     | ... | 61     |
| Inputs         |        |        |        |        |     |        |
| In1 (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Switch (DSP)   | 30005  | 28152  | 32440  | 32440  | ... | 14425  |
| In3 (DSP)      | 32767  | 32293  | 31818  | 31343  | ... | -32293 |
| In1            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Switch         | 0.916  | 0.859  | 0.99   | 0.99   | ... | 0.44   |
| In3            | 1      | 0.986  | 0.971  | 0.957  | ... | -0.986 |
| Parameters     |        |        |        |        |     |        |
| Thresh_up      | 0.3    |        |        |        |     |        |
| Thresh_down    | -0.1   |        |        |        |     |        |
| Outputs        |        |        |        |        |     |        |
| Out            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Exp. Out       | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Out (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Exp. Out (DSP) | -32768 | -32293 | -31818 | -31343 | ... | 32293  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 61 |
| Max CPU cycles  | 66 |
| Avg CPU cycles  | 63 |

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 137    |
| CPU cycles     | 61     | 61     | 61     | 61     | ... | 61     |
| Inputs         |        |        |        |        |     |        |
| In1 (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Switch (DSP)   | 30005  | 28152  | 32440  | 32440  | ... | 14425  |
| In3 (DSP)      | 32767  | 32293  | 31818  | 31343  | ... | -32293 |
| In1            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Switch         | 0.916  | 0.859  | 0.99   | 0.99   | ... | 0.44   |
| In3            | 1      | 0.986  | 0.971  | 0.957  | ... | -0.986 |
| Parameters     |        |        |        |        |     |        |
| Thresh_up      | 0      |        |        |        |     |        |
| Thresh_down    | 0      |        |        |        |     |        |
| Outputs        |        |        |        |        |     |        |
| Out            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Exp. Out       | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Out (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Exp. Out (DSP) | -32768 | -32293 | -31818 | -31343 | ... | 32293  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 61 |
| Max CPU cycles  | 66 |
| Avg CPU cycles  | 63 |

#### Test case: Conversion test

OK

Conversion test for General block AutoSwitch.

| Test results                 |   |      |      |       |     |        |
|------------------------------|---|------|------|-------|-----|--------|
| <b>Time step</b>             | 1 | 2    | 3    | 4     | ... | 11     |
| <i>Mask parameters</i>       |   |      |      |       |     |        |
| <b>Thresh_up</b>             | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <b>Thresh_down</b>           | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <i>Controller parameters</i> |   |      |      |       |     |        |
| <b>Thresh_down</b>           | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Thresh_up</b>             | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Exp. Thresh_down</b>      | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Exp. Thresh_up</b>        | 0 | 3277 | 6554 | 16384 | ... | -32767 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 0,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block AutoSwitch.

| Test results                 |   |      |      |       |     |        |
|------------------------------|---|------|------|-------|-----|--------|
| <b>Time step</b>             | 1 | 2    | 3    | 4     | ... | 11     |
| <i>Mask parameters</i>       |   |      |      |       |     |        |
| <b>Thresh_up</b>             | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <b>Thresh_down</b>           | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <i>Controller parameters</i> |   |      |      |       |     |        |
| <b>Thresh_down</b>           | 0 | 3276 | 6553 | 16384 | ... | -32767 |
| <b>Thresh_up</b>             | 0 | 3276 | 6553 | 16384 | ... | -32767 |
| <b>Exp. Thresh_down</b>      | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Exp. Thresh_up</b>        | 0 | 3277 | 6554 | 16384 | ... | -32767 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 1,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 1,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 613 |
| Max CPU cycles  | 757 |
| Avg CPU cycles  | 626 |

**Verification: AutoSwitch FiP16 CPU TMS320F28379D**

Date of Test 2026-06-22  
Target controller TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 137    |
| CPU cycles     | 54     | 54     | 54     | 54     | ... | 54     |
| Inputs         |        |        |        |        |     |        |
| In1 (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Switch (DSP)   | 30005  | 28152  | 32440  | 32440  | ... | 14425  |
| In3 (DSP)      | 32767  | 32293  | 31818  | 31343  | ... | -32293 |
| In1            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Switch         | 0.916  | 0.859  | 0.99   | 0.99   | ... | 0.44   |
| In3            | 1      | 0.986  | 0.971  | 0.957  | ... | -0.986 |
| Parameters     |        |        |        |        |     |        |
| Thresh_up      | 0.3    |        |        |        |     |        |
| Thresh_down    | -0.1   |        |        |        |     |        |
| Outputs        |        |        |        |        |     |        |
| Out            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Exp. Out       | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Out (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Exp. Out (DSP) | -32768 | -32293 | -31818 | -31343 | ... | 32293  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 54 |
| Max CPU cycles  | 69 |
| Avg CPU cycles  | 61 |

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 137    |
| CPU cycles     | 54     | 54     | 54     | 54     | ... | 54     |
| Inputs         |        |        |        |        |     |        |
| In1 (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Switch (DSP)   | 30005  | 28152  | 32440  | 32440  | ... | 14425  |
| In3 (DSP)      | 32767  | 32293  | 31818  | 31343  | ... | -32293 |
| In1            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Switch         | 0.916  | 0.859  | 0.99   | 0.99   | ... | 0.44   |
| In3            | 1      | 0.986  | 0.971  | 0.957  | ... | -0.986 |
| Parameters     |        |        |        |        |     |        |
| Thresh_up      | 0      |        |        |        |     |        |
| Thresh_down    | 0      |        |        |        |     |        |
| Outputs        |        |        |        |        |     |        |
| Out            | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Exp. Out       | -1     | -0.986 | -0.971 | -0.957 | ... | 0.986  |
| Out (DSP)      | -32768 | -32293 | -31818 | -31343 | ... | 32293  |
| Exp. Out (DSP) | -32768 | -32293 | -31818 | -31343 | ... | 32293  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 54 |
| Max CPU cycles  | 69 |
| Avg CPU cycles  | 60 |

#### Test case: Conversion test

OK

Conversion test for General block AutoSwitch.



| Test results                 |   |      |      |       |     |        |
|------------------------------|---|------|------|-------|-----|--------|
| <b>Time step</b>             | 1 | 2    | 3    | 4     | ... | 11     |
| <i>Mask parameters</i>       |   |      |      |       |     |        |
| <b>Thresh_up</b>             | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <b>Thresh_down</b>           | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <i>Controller parameters</i> |   |      |      |       |     |        |
| <b>Thresh_down</b>           | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Thresh_up</b>             | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Exp. Thresh_down</b>      | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Exp. Thresh_up</b>        | 0 | 3277 | 6554 | 16384 | ... | -32767 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 0,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block AutoSwitch.

| Test results                 |   |      |      |       |     |        |
|------------------------------|---|------|------|-------|-----|--------|
| <b>Time step</b>             | 1 | 2    | 3    | 4     | ... | 11     |
| <i>Mask parameters</i>       |   |      |      |       |     |        |
| <b>Thresh_up</b>             | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <b>Thresh_down</b>           | 0 | 0.1  | 0.2  | 0.5   | ... | -1.1   |
| <i>Controller parameters</i> |   |      |      |       |     |        |
| <b>Thresh_down</b>           | 0 | 3276 | 6553 | 16384 | ... | -32767 |
| <b>Thresh_up</b>             | 0 | 3276 | 6553 | 16384 | ... | -32767 |
| <b>Exp. Thresh_down</b>      | 0 | 3277 | 6554 | 16384 | ... | -32767 |
| <b>Exp. Thresh_up</b>        | 0 | 3277 | 6554 | 16384 | ... | -32767 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 1,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 1,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 976 |
| Max CPU cycles  | 984 |
| Avg CPU cycles  | 978 |

**Verification: AutoSwitch FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 137         |
| CPU cycles     | 70          | 70          | ... | 70          |
| Inputs         |             |             |     |             |
| In1 (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Switch (DSP)   | 1966424482  | 1844940891  | ... | 945361786   |
| In3 (DSP)      | 2147483647  | 2116360697  | ... | -2116360697 |
| In1            | -1          | -0.986      | ... | 0.986       |
| Switch         | 0.916       | 0.859       | ... | 0.44        |
| In3            | 1           | 0.986       | ... | -0.986      |
| Parameters     |             |             |     |             |
| Thresh_up      | 0.3         |             |     |             |
| Thresh_down    | -0.1        |             |     |             |
| Outputs        |             |             |     |             |
| Out            | -1          | -0.986      | ... | 0.986       |
| Exp. Out       | -1          | -0.986      | ... | 0.986       |
| Out (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Exp. Out (DSP) | -2147483648 | -2116360697 | ... | 2116360697  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 70 |
| Max CPU cycles  | 79 |
| Avg CPU cycles  | 74 |

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 137         |
| CPU cycles     | 70          | 70          | ... | 70          |
| Inputs         |             |             |     |             |
| In1 (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Switch (DSP)   | 1966424482  | 1844940891  | ... | 945361786   |
| In3 (DSP)      | 2147483647  | 2116360697  | ... | -2116360697 |
| In1            | -1          | -0.986      | ... | 0.986       |
| Switch         | 0.916       | 0.859       | ... | 0.44        |
| In3            | 1           | 0.986       | ... | -0.986      |
| Parameters     |             |             |     |             |
| Thresh_up      | 0           |             |     |             |
| Thresh_down    | 0           |             |     |             |
| Outputs        |             |             |     |             |
| Out            | -1          | -0.986      | ... | 0.986       |
| Exp. Out       | -1          | -0.986      | ... | 0.986       |
| Out (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Exp. Out (DSP) | -2147483648 | -2116360697 | ... | 2116360697  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 70 |
| Max CPU cycles  | 79 |
| Avg CPU cycles  | 74 |

#### Test case: Conversion test

OK

Conversion test for General block AutoSwitch.

| Test results                 |   |           |     |             |
|------------------------------|---|-----------|-----|-------------|
| <b>Time step</b>             | 1 | 2         | ... | 11          |
| <i>Mask parameters</i>       |   |           |     |             |
| <b>Thresh_up</b>             | 0 | 0.1       | ... | -1.1        |
| <b>Thresh_down</b>           | 0 | 0.1       | ... | -1.1        |
| <i>Controller parameters</i> |   |           |     |             |
| <b>Thresh_down</b>           | 0 | 214748365 | ... | -2147483647 |
| <b>Thresh_up</b>             | 0 | 214748365 | ... | -2147483647 |
| <b>Exp. Thresh_down</b>      | 0 | 214748365 | ... | -2147483647 |
| <b>Exp. Thresh_up</b>        | 0 | 214748365 | ... | -2147483647 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 0,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block AutoSwitch.

| Test results                 |   |           |     |             |
|------------------------------|---|-----------|-----|-------------|
| <b>Time step</b>             | 1 | 2         | ... | 11          |
| <i>Mask parameters</i>       |   |           |     |             |
| <b>Thresh_up</b>             | 0 | 0.1       | ... | -1.1        |
| <b>Thresh_down</b>           | 0 | 0.1       | ... | -1.1        |
| <i>Controller parameters</i> |   |           |     |             |
| <b>Thresh_down</b>           | 0 | 214748368 | ... | -2147483647 |
| <b>Thresh_up</b>             | 0 | 214748368 | ... | -2147483647 |
| <b>Exp. Thresh_down</b>      | 0 | 214748365 | ... | -2147483647 |
| <b>Exp. Thresh_up</b>        | 0 | 214748365 | ... | -2147483647 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 6,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 6,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1671 |
| Max CPU cycles  | 1791 |
| Avg CPU cycles  | 1753 |

**Verification: AutoSwitch FiP32 CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 137         |
| CPU cycles     | 31          | 31          | ... | 31          |
| Inputs         |             |             |     |             |
| In1 (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Switch (DSP)   | 1966424482  | 1844940891  | ... | 945361786   |
| In3 (DSP)      | 2147483647  | 2116360697  | ... | -2116360697 |
| In1            | -1          | -0.986      | ... | 0.986       |
| Switch         | 0.916       | 0.859       | ... | 0.44        |
| In3            | 1           | 0.986       | ... | -0.986      |
| Parameters     |             |             |     |             |
| Thresh_up      | 0.3         |             |     |             |
| Thresh_down    | -0.1        |             |     |             |
| Outputs        |             |             |     |             |
| Out            | -1          | -0.986      | ... | 0.986       |
| Exp. Out       | -1          | -0.986      | ... | 0.986       |
| Out (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Exp. Out (DSP) | -2147483648 | -2116360697 | ... | 2116360697  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 37 |
| Avg CPU cycles  | 34 |

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 137         |
| CPU cycles     | 31          | 31          | ... | 31          |
| Inputs         |             |             |     |             |
| In1 (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Switch (DSP)   | 1966424482  | 1844940891  | ... | 945361786   |
| In3 (DSP)      | 2147483647  | 2116360697  | ... | -2116360697 |
| In1            | -1          | -0.986      | ... | 0.986       |
| Switch         | 0.916       | 0.859       | ... | 0.44        |
| In3            | 1           | 0.986       | ... | -0.986      |
| Parameters     |             |             |     |             |
| Thresh_up      | 0           |             |     |             |
| Thresh_down    | 0           |             |     |             |
| Outputs        |             |             |     |             |
| Out            | -1          | -0.986      | ... | 0.986       |
| Exp. Out       | -1          | -0.986      | ... | 0.986       |
| Out (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Exp. Out (DSP) | -2147483648 | -2116360697 | ... | 2116360697  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 37 |
| Avg CPU cycles  | 33 |

#### Test case: Conversion test

OK

Conversion test for General block AutoSwitch.



| Test results                 |   |           |     |             |
|------------------------------|---|-----------|-----|-------------|
| <b>Time step</b>             | 1 | 2         | ... | 11          |
| <i>Mask parameters</i>       |   |           |     |             |
| <b>Thresh_up</b>             | 0 | 0.1       | ... | -1.1        |
| <b>Thresh_down</b>           | 0 | 0.1       | ... | -1.1        |
| <i>Controller parameters</i> |   |           |     |             |
| <b>Thresh_down</b>           | 0 | 214748365 | ... | -2147483647 |
| <b>Thresh_up</b>             | 0 | 214748365 | ... | -2147483647 |
| <b>Exp. Thresh_down</b>      | 0 | 214748365 | ... | -2147483647 |
| <b>Exp. Thresh_up</b>        | 0 | 214748365 | ... | -2147483647 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 0,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block AutoSwitch.

| Test results                 |   |           |     |             |
|------------------------------|---|-----------|-----|-------------|
| <b>Time step</b>             | 1 | 2         | ... | 11          |
| <i>Mask parameters</i>       |   |           |     |             |
| <b>Thresh_up</b>             | 0 | 0.1       | ... | -1.1        |
| <b>Thresh_down</b>           | 0 | 0.1       | ... | -1.1        |
| <i>Controller parameters</i> |   |           |     |             |
| <b>Thresh_down</b>           | 0 | 214748368 | ... | -2147483647 |
| <b>Thresh_up</b>             | 0 | 214748368 | ... | -2147483647 |
| <b>Exp. Thresh_down</b>      | 0 | 214748365 | ... | -2147483647 |
| <b>Exp. Thresh_up</b>        | 0 | 214748365 | ... | -2147483647 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 6,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 6,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 737 |
| Max CPU cycles  | 793 |
| Avg CPU cycles  | 783 |

**Verification: AutoSwitch FiP32 CPU STM32G474RE**

Date of Test 2026-06-19  
Target controller STM32G474RE

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 137         |
| CPU cycles     | 62          | 62          | ... | 62          |
| Inputs         |             |             |     |             |
| In1 (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Switch (DSP)   | 1966424482  | 1844940891  | ... | 945361786   |
| In3 (DSP)      | 2147483647  | 2116360697  | ... | -2116360697 |
| In1            | -1          | -0.986      | ... | 0.986       |
| Switch         | 0.916       | 0.859       | ... | 0.44        |
| In3            | 1           | 0.986       | ... | -0.986      |
| Parameters     |             |             |     |             |
| Thresh_up      | 0.3         |             |     |             |
| Thresh_down    | -0.1        |             |     |             |
| Outputs        |             |             |     |             |
| Out            | -1          | -0.986      | ... | 0.986       |
| Exp. Out       | -1          | -0.986      | ... | 0.986       |
| Out (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Exp. Out (DSP) | -2147483648 | -2116360697 | ... | 2116360697  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 72 |
| Avg CPU cycles  | 67 |

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 137         |
| CPU cycles     | 62          | 62          | ... | 62          |
| Inputs         |             |             |     |             |
| In1 (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Switch (DSP)   | 1966424482  | 1844940891  | ... | 945361786   |
| In3 (DSP)      | 2147483647  | 2116360697  | ... | -2116360697 |
| In1            | -1          | -0.986      | ... | 0.986       |
| Switch         | 0.916       | 0.859       | ... | 0.44        |
| In3            | 1           | 0.986       | ... | -0.986      |
| Parameters     |             |             |     |             |
| Thresh_up      | 0           |             |     |             |
| Thresh_down    | 0           |             |     |             |
| Outputs        |             |             |     |             |
| Out            | -1          | -0.986      | ... | 0.986       |
| Exp. Out       | -1          | -0.986      | ... | 0.986       |
| Out (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Exp. Out (DSP) | -2147483648 | -2116360697 | ... | 2116360697  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 72 |
| Avg CPU cycles  | 66 |

#### Test case: Conversion test

OK

Conversion test for General block AutoSwitch.

| Test results                 |   |           |     |             |
|------------------------------|---|-----------|-----|-------------|
| <b>Time step</b>             | 1 | 2         | ... | 11          |
| <i>Mask parameters</i>       |   |           |     |             |
| <b>Thresh_up</b>             | 0 | 0.1       | ... | -1.1        |
| <b>Thresh_down</b>           | 0 | 0.1       | ... | -1.1        |
| <i>Controller parameters</i> |   |           |     |             |
| <b>Thresh_down</b>           | 0 | 214748365 | ... | -2147483647 |
| <b>Thresh_up</b>             | 0 | 214748365 | ... | -2147483647 |
| <b>Exp. Thresh_down</b>      | 0 | 214748365 | ... | -2147483647 |
| <b>Exp. Thresh_up</b>        | 0 | 214748365 | ... | -2147483647 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 0,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block AutoSwitch.

| Test results                 |   |           |     |             |
|------------------------------|---|-----------|-----|-------------|
| <b>Time step</b>             | 1 | 2         | ... | 11          |
| <i>Mask parameters</i>       |   |           |     |             |
| <b>Thresh_up</b>             | 0 | 0.1       | ... | -1.1        |
| <b>Thresh_down</b>           | 0 | 0.1       | ... | -1.1        |
| <i>Controller parameters</i> |   |           |     |             |
| <b>Thresh_down</b>           | 0 | 214748368 | ... | -2147483647 |
| <b>Thresh_up</b>             | 0 | 214748368 | ... | -2147483647 |
| <b>Exp. Thresh_down</b>      | 0 | 214748365 | ... | -2147483647 |
| <b>Exp. Thresh_up</b>        | 0 | 214748365 | ... | -2147483647 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 6,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 6,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1418 |
| Max CPU cycles  | 1503 |
| Avg CPU cycles  | 1481 |

**Verification: AutoSwitch FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 137         |
| CPU cycles     | 56          | 56          | ... | 56          |
| Inputs         |             |             |     |             |
| In1 (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Switch (DSP)   | 1966424482  | 1844940891  | ... | 945361786   |
| In3 (DSP)      | 2147483647  | 2116360697  | ... | -2116360697 |
| In1            | -1          | -0.986      | ... | 0.986       |
| Switch         | 0.916       | 0.859       | ... | 0.44        |
| In3            | 1           | 0.986       | ... | -0.986      |
| Parameters     |             |             |     |             |
| Thresh_up      | 0.3         |             |     |             |
| Thresh_down    | -0.1        |             |     |             |
| Outputs        |             |             |     |             |
| Out            | -1          | -0.986      | ... | 0.986       |
| Exp. Out       | -1          | -0.986      | ... | 0.986       |
| Out (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Exp. Out (DSP) | -2147483648 | -2116360697 | ... | 2116360697  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 68 |
| Avg CPU cycles  | 62 |

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 137         |
| CPU cycles     | 56          | 56          | ... | 56          |
| Inputs         |             |             |     |             |
| In1 (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Switch (DSP)   | 1966424482  | 1844940891  | ... | 945361786   |
| In3 (DSP)      | 2147483647  | 2116360697  | ... | -2116360697 |
| In1            | -1          | -0.986      | ... | 0.986       |
| Switch         | 0.916       | 0.859       | ... | 0.44        |
| In3            | 1           | 0.986       | ... | -0.986      |
| Parameters     |             |             |     |             |
| Thresh_up      | 0           |             |     |             |
| Thresh_down    | 0           |             |     |             |
| Outputs        |             |             |     |             |
| Out            | -1          | -0.986      | ... | 0.986       |
| Exp. Out       | -1          | -0.986      | ... | 0.986       |
| Out (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Exp. Out (DSP) | -2147483648 | -2116360697 | ... | 2116360697  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 68 |
| Avg CPU cycles  | 61 |

#### Test case: Conversion test

OK

Conversion test for General block AutoSwitch.



| Test results                 |   |           |     |             |
|------------------------------|---|-----------|-----|-------------|
| <b>Time step</b>             | 1 | 2         | ... | 11          |
| <i>Mask parameters</i>       |   |           |     |             |
| <b>Thresh_up</b>             | 0 | 0.1       | ... | -1.1        |
| <b>Thresh_down</b>           | 0 | 0.1       | ... | -1.1        |
| <i>Controller parameters</i> |   |           |     |             |
| <b>Thresh_down</b>           | 0 | 214748365 | ... | -2147483647 |
| <b>Thresh_up</b>             | 0 | 214748365 | ... | -2147483647 |
| <b>Exp. Thresh_down</b>      | 0 | 214748365 | ... | -2147483647 |
| <b>Exp. Thresh_up</b>        | 0 | 214748365 | ... | -2147483647 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 0,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block AutoSwitch.

| Test results                 |   |           |     |             |
|------------------------------|---|-----------|-----|-------------|
| <b>Time step</b>             | 1 | 2         | ... | 11          |
| <i>Mask parameters</i>       |   |           |     |             |
| <b>Thresh_up</b>             | 0 | 0.1       | ... | -1.1        |
| <b>Thresh_down</b>           | 0 | 0.1       | ... | -1.1        |
| <i>Controller parameters</i> |   |           |     |             |
| <b>Thresh_down</b>           | 0 | 214748368 | ... | -2147483647 |
| <b>Thresh_up</b>             | 0 | 214748368 | ... | -2147483647 |
| <b>Exp. Thresh_down</b>      | 0 | 214748365 | ... | -2147483647 |
| <b>Exp. Thresh_up</b>        | 0 | 214748365 | ... | -2147483647 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 6,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 6,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3451 |
| Max CPU cycles  | 4689 |
| Avg CPU cycles  | 4252 |

**Verification: AutoSwitch FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 137         |
| CPU cycles     | 39          | 39          | ... | 39          |
| Inputs         |             |             |     |             |
| In1 (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Switch (DSP)   | 1966424482  | 1844940891  | ... | 945361786   |
| In3 (DSP)      | 2147483647  | 2116360697  | ... | -2116360697 |
| In1            | -1          | -0.986      | ... | 0.986       |
| Switch         | 0.916       | 0.859       | ... | 0.44        |
| In3            | 1           | 0.986       | ... | -0.986      |
| Parameters     |             |             |     |             |
| Thresh_up      | 0.3         |             |     |             |
| Thresh_down    | -0.1        |             |     |             |
| Outputs        |             |             |     |             |
| Out            | -1          | -0.986      | ... | 0.986       |
| Exp. Out       | -1          | -0.986      | ... | 0.986       |
| Out (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Exp. Out (DSP) | -2147483648 | -2116360697 | ... | 2116360697  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 39 |
| Max CPU cycles  | 43 |
| Avg CPU cycles  | 41 |

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 137         |
| CPU cycles     | 39          | 39          | ... | 39          |
| Inputs         |             |             |     |             |
| In1 (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Switch (DSP)   | 1966424482  | 1844940891  | ... | 945361786   |
| In3 (DSP)      | 2147483647  | 2116360697  | ... | -2116360697 |
| In1            | -1          | -0.986      | ... | 0.986       |
| Switch         | 0.916       | 0.859       | ... | 0.44        |
| In3            | 1           | 0.986       | ... | -0.986      |
| Parameters     |             |             |     |             |
| Thresh_up      | 0           |             |     |             |
| Thresh_down    | 0           |             |     |             |
| Outputs        |             |             |     |             |
| Out            | -1          | -0.986      | ... | 0.986       |
| Exp. Out       | -1          | -0.986      | ... | 0.986       |
| Out (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Exp. Out (DSP) | -2147483648 | -2116360697 | ... | 2116360697  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 39 |
| Max CPU cycles  | 43 |
| Avg CPU cycles  | 40 |

#### Test case: Conversion test

OK

Conversion test for General block AutoSwitch.

| Test results                 |   |           |     |             |
|------------------------------|---|-----------|-----|-------------|
| <b>Time step</b>             | 1 | 2         | ... | 11          |
| <i>Mask parameters</i>       |   |           |     |             |
| <b>Thresh_up</b>             | 0 | 0.1       | ... | -1.1        |
| <b>Thresh_down</b>           | 0 | 0.1       | ... | -1.1        |
| <i>Controller parameters</i> |   |           |     |             |
| <b>Thresh_down</b>           | 0 | 214748365 | ... | -2147483647 |
| <b>Thresh_up</b>             | 0 | 214748365 | ... | -2147483647 |
| <b>Exp. Thresh_down</b>      | 0 | 214748365 | ... | -2147483647 |
| <b>Exp. Thresh_up</b>        | 0 | 214748365 | ... | -2147483647 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 0,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block AutoSwitch.

| Test results                 |   |           |     |             |
|------------------------------|---|-----------|-----|-------------|
| <b>Time step</b>             | 1 | 2         | ... | 11          |
| <i>Mask parameters</i>       |   |           |     |             |
| <b>Thresh_up</b>             | 0 | 0.1       | ... | -1.1        |
| <b>Thresh_down</b>           | 0 | 0.1       | ... | -1.1        |
| <i>Controller parameters</i> |   |           |     |             |
| <b>Thresh_down</b>           | 0 | 214748368 | ... | -2147483647 |
| <b>Thresh_up</b>             | 0 | 214748368 | ... | -2147483647 |
| <b>Exp. Thresh_down</b>      | 0 | 214748365 | ... | -2147483647 |
| <b>Exp. Thresh_up</b>        | 0 | 214748365 | ... | -2147483647 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 6,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 6,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1334 |
| Max CPU cycles  | 1572 |
| Avg CPU cycles  | 1536 |

**Verification: AutoSwitch FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 137         |
| CPU cycles     | 55          | 55          | ... | 55          |
| Inputs         |             |             |     |             |
| In1 (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Switch (DSP)   | 1966424482  | 1844940891  | ... | 945361786   |
| In3 (DSP)      | 2147483647  | 2116360697  | ... | -2116360697 |
| In1            | -1          | -0.986      | ... | 0.986       |
| Switch         | 0.916       | 0.859       | ... | 0.44        |
| In3            | 1           | 0.986       | ... | -0.986      |
| Parameters     |             |             |     |             |
| Thresh_up      | 0.3         |             |     |             |
| Thresh_down    | -0.1        |             |     |             |
| Outputs        |             |             |     |             |
| Out            | -1          | -0.986      | ... | 0.986       |
| Exp. Out       | -1          | -0.986      | ... | 0.986       |
| Out (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Exp. Out (DSP) | -2147483648 | -2116360697 | ... | 2116360697  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 55 |
| Max CPU cycles  | 60 |
| Avg CPU cycles  | 56 |

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 137         |
| CPU cycles     | 55          | 55          | ... | 55          |
| Inputs         |             |             |     |             |
| In1 (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Switch (DSP)   | 1966424482  | 1844940891  | ... | 945361786   |
| In3 (DSP)      | 2147483647  | 2116360697  | ... | -2116360697 |
| In1            | -1          | -0.986      | ... | 0.986       |
| Switch         | 0.916       | 0.859       | ... | 0.44        |
| In3            | 1           | 0.986       | ... | -0.986      |
| Parameters     |             |             |     |             |
| Thresh_up      | 0           |             |     |             |
| Thresh_down    | 0           |             |     |             |
| Outputs        |             |             |     |             |
| Out            | -1          | -0.986      | ... | 0.986       |
| Exp. Out       | -1          | -0.986      | ... | 0.986       |
| Out (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Exp. Out (DSP) | -2147483648 | -2116360697 | ... | 2116360697  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 55 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 55 |

#### Test case: Conversion test

OK

Conversion test for General block AutoSwitch.



| Test results                 |   |           |     |             |
|------------------------------|---|-----------|-----|-------------|
| <b>Time step</b>             | 1 | 2         | ... | 11          |
| <i>Mask parameters</i>       |   |           |     |             |
| <b>Thresh_up</b>             | 0 | 0.1       | ... | -1.1        |
| <b>Thresh_down</b>           | 0 | 0.1       | ... | -1.1        |
| <i>Controller parameters</i> |   |           |     |             |
| <b>Thresh_down</b>           | 0 | 214748365 | ... | -2147483647 |
| <b>Thresh_up</b>             | 0 | 214748365 | ... | -2147483647 |
| <b>Exp. Thresh_down</b>      | 0 | 214748365 | ... | -2147483647 |
| <b>Exp. Thresh_up</b>        | 0 | 214748365 | ... | -2147483647 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 0,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block AutoSwitch.

| Test results                 |   |           |     |             |
|------------------------------|---|-----------|-----|-------------|
| <b>Time step</b>             | 1 | 2         | ... | 11          |
| <i>Mask parameters</i>       |   |           |     |             |
| <b>Thresh_up</b>             | 0 | 0.1       | ... | -1.1        |
| <b>Thresh_down</b>           | 0 | 0.1       | ... | -1.1        |
| <i>Controller parameters</i> |   |           |     |             |
| <b>Thresh_down</b>           | 0 | 214748368 | ... | -2147483647 |
| <b>Thresh_up</b>             | 0 | 214748368 | ... | -2147483647 |
| <b>Exp. Thresh_down</b>      | 0 | 214748365 | ... | -2147483647 |
| <b>Exp. Thresh_up</b>        | 0 | 214748365 | ... | -2147483647 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 6,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 6,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2253 |
| Max CPU cycles  | 3159 |
| Avg CPU cycles  | 3045 |

**Verification: AutoSwitch FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 137         |
| CPU cycles     | 61          | 61          | ... | 61          |
| Inputs         |             |             |     |             |
| In1 (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Switch (DSP)   | 1966424482  | 1844940891  | ... | 945361786   |
| In3 (DSP)      | 2147483647  | 2116360697  | ... | -2116360697 |
| In1            | -1          | -0.986      | ... | 0.986       |
| Switch         | 0.916       | 0.859       | ... | 0.44        |
| In3            | 1           | 0.986       | ... | -0.986      |
| Parameters     |             |             |     |             |
| Thresh_up      | 0.3         |             |     |             |
| Thresh_down    | -0.1        |             |     |             |
| Outputs        |             |             |     |             |
| Out            | -1          | -0.986      | ... | 0.986       |
| Exp. Out       | -1          | -0.986      | ... | 0.986       |
| Out (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Exp. Out (DSP) | -2147483648 | -2116360697 | ... | 2116360697  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 61 |
| Max CPU cycles  | 66 |
| Avg CPU cycles  | 63 |

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 137         |
| CPU cycles     | 61          | 61          | ... | 61          |
| Inputs         |             |             |     |             |
| In1 (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Switch (DSP)   | 1966424482  | 1844940891  | ... | 945361786   |
| In3 (DSP)      | 2147483647  | 2116360697  | ... | -2116360697 |
| In1            | -1          | -0.986      | ... | 0.986       |
| Switch         | 0.916       | 0.859       | ... | 0.44        |
| In3            | 1           | 0.986       | ... | -0.986      |
| Parameters     |             |             |     |             |
| Thresh_up      | 0           |             |     |             |
| Thresh_down    | 0           |             |     |             |
| Outputs        |             |             |     |             |
| Out            | -1          | -0.986      | ... | 0.986       |
| Exp. Out       | -1          | -0.986      | ... | 0.986       |
| Out (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Exp. Out (DSP) | -2147483648 | -2116360697 | ... | 2116360697  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 61 |
| Max CPU cycles  | 66 |
| Avg CPU cycles  | 63 |

#### Test case: Conversion test

OK

Conversion test for General block AutoSwitch.

| Test results                 |   |           |     |             |
|------------------------------|---|-----------|-----|-------------|
| <b>Time step</b>             | 1 | 2         | ... | 11          |
| <i>Mask parameters</i>       |   |           |     |             |
| <b>Thresh_up</b>             | 0 | 0.1       | ... | -1.1        |
| <b>Thresh_down</b>           | 0 | 0.1       | ... | -1.1        |
| <i>Controller parameters</i> |   |           |     |             |
| <b>Thresh_down</b>           | 0 | 214748365 | ... | -2147483647 |
| <b>Thresh_up</b>             | 0 | 214748365 | ... | -2147483647 |
| <b>Exp. Thresh_down</b>      | 0 | 214748365 | ... | -2147483647 |
| <b>Exp. Thresh_up</b>        | 0 | 214748365 | ... | -2147483647 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 0,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block AutoSwitch.

| Test results                 |   |           |     |             |
|------------------------------|---|-----------|-----|-------------|
| <b>Time step</b>             | 1 | 2         | ... | 11          |
| <i>Mask parameters</i>       |   |           |     |             |
| <b>Thresh_up</b>             | 0 | 0.1       | ... | -1.1        |
| <b>Thresh_down</b>           | 0 | 0.1       | ... | -1.1        |
| <i>Controller parameters</i> |   |           |     |             |
| <b>Thresh_down</b>           | 0 | 214748368 | ... | -2147483647 |
| <b>Thresh_up</b>             | 0 | 214748368 | ... | -2147483647 |
| <b>Exp. Thresh_down</b>      | 0 | 214748365 | ... | -2147483647 |
| <b>Exp. Thresh_up</b>        | 0 | 214748365 | ... | -2147483647 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 6,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 6,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1155 |
| Max CPU cycles  | 1287 |
| Avg CPU cycles  | 1182 |

**Verification: AutoSwitch FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 137         |
| CPU cycles     | 55          | 55          | ... | 55          |
| Inputs         |             |             |     |             |
| In1 (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Switch (DSP)   | 1966424482  | 1844940891  | ... | 945361786   |
| In3 (DSP)      | 2147483647  | 2116360697  | ... | -2116360697 |
| In1            | -1          | -0.986      | ... | 0.986       |
| Switch         | 0.916       | 0.859       | ... | 0.44        |
| In3            | 1           | 0.986       | ... | -0.986      |
| Parameters     |             |             |     |             |
| Thresh_up      | 0.3         |             |     |             |
| Thresh_down    | -0.1        |             |     |             |
| Outputs        |             |             |     |             |
| Out            | -1          | -0.986      | ... | 0.986       |
| Exp. Out       | -1          | -0.986      | ... | 0.986       |
| Out (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Exp. Out (DSP) | -2147483648 | -2116360697 | ... | 2116360697  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 55 |
| Max CPU cycles  | 69 |
| Avg CPU cycles  | 61 |

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 137         |
| CPU cycles     | 55          | 55          | ... | 55          |
| Inputs         |             |             |     |             |
| In1 (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Switch (DSP)   | 1966424482  | 1844940891  | ... | 945361786   |
| In3 (DSP)      | 2147483647  | 2116360697  | ... | -2116360697 |
| In1            | -1          | -0.986      | ... | 0.986       |
| Switch         | 0.916       | 0.859       | ... | 0.44        |
| In3            | 1           | 0.986       | ... | -0.986      |
| Parameters     |             |             |     |             |
| Thresh_up      | 0           |             |     |             |
| Thresh_down    | 0           |             |     |             |
| Outputs        |             |             |     |             |
| Out            | -1          | -0.986      | ... | 0.986       |
| Exp. Out       | -1          | -0.986      | ... | 0.986       |
| Out (DSP)      | -2147483648 | -2116360697 | ... | 2116360697  |
| Exp. Out (DSP) | -2147483648 | -2116360697 | ... | 2116360697  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 55 |
| Max CPU cycles  | 69 |
| Avg CPU cycles  | 61 |

#### Test case: Conversion test

OK

Conversion test for General block AutoSwitch.



| Test results                 |   |           |     |             |
|------------------------------|---|-----------|-----|-------------|
| <b>Time step</b>             | 1 | 2         | ... | 11          |
| <i>Mask parameters</i>       |   |           |     |             |
| <b>Thresh_up</b>             | 0 | 0.1       | ... | -1.1        |
| <b>Thresh_down</b>           | 0 | 0.1       | ... | -1.1        |
| <i>Controller parameters</i> |   |           |     |             |
| <b>Thresh_down</b>           | 0 | 214748365 | ... | -2147483647 |
| <b>Thresh_up</b>             | 0 | 214748365 | ... | -2147483647 |
| <b>Exp. Thresh_down</b>      | 0 | 214748365 | ... | -2147483647 |
| <b>Exp. Thresh_up</b>        | 0 | 214748365 | ... | -2147483647 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 0,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block AutoSwitch.

| Test results                 |   |           |     |             |
|------------------------------|---|-----------|-----|-------------|
| <b>Time step</b>             | 1 | 2         | ... | 11          |
| <i>Mask parameters</i>       |   |           |     |             |
| <b>Thresh_up</b>             | 0 | 0.1       | ... | -1.1        |
| <b>Thresh_down</b>           | 0 | 0.1       | ... | -1.1        |
| <i>Controller parameters</i> |   |           |     |             |
| <b>Thresh_down</b>           | 0 | 214748368 | ... | -2147483647 |
| <b>Thresh_up</b>             | 0 | 214748368 | ... | -2147483647 |
| <b>Exp. Thresh_down</b>      | 0 | 214748365 | ... | -2147483647 |
| <b>Exp. Thresh_up</b>        | 0 | 214748365 | ... | -2147483647 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 6,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 6,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1235 |
| Max CPU cycles  | 1315 |
| Avg CPU cycles  | 1288 |

**Verification: AutoSwitch Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |       |        |     |        |
|----------------|-------|--------|-----|--------|
| Time step      | 1     | 2      | ... | 137    |
| CPU cycles     | 73    | 73     | ... | 73     |
| Inputs         |       |        |     |        |
| In1 (DSP)      | -1    | -0.986 | ... | 0.986  |
| Switch (DSP)   | 0.916 | 0.859  | ... | 0.44   |
| In3 (DSP)      | 1     | 0.986  | ... | -0.986 |
| In1            | -1    | -0.986 | ... | 0.986  |
| Switch         | 0.916 | 0.859  | ... | 0.44   |
| In3            | 1     | 0.986  | ... | -0.986 |
| Parameters     |       |        |     |        |
| Thresh_up      | 0.3   |        |     |        |
| Thresh_down    | -0.1  |        |     |        |
| Outputs        |       |        |     |        |
| Out            | -1    | -0.986 | ... | 0.986  |
| Exp. Out       | -1    | -0.986 | ... | 0.986  |
| Out (DSP)      | -1    | -0.986 | ... | 0.986  |
| Exp. Out (DSP) | -1    | -0.986 | ... | 0.986  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0268e-08$ ( $\pm 65$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 73 |
| Max CPU cycles  | 83 |
| Avg CPU cycles  | 78 |

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |       |        |     |        |
|----------------|-------|--------|-----|--------|
| Time step      | 1     | 2      | ... | 137    |
| CPU cycles     | 73    | 73     | ... | 73     |
| Inputs         |       |        |     |        |
| In1 (DSP)      | -1    | -0.986 | ... | 0.986  |
| Switch (DSP)   | 0.916 | 0.859  | ... | 0.44   |
| In3 (DSP)      | 1     | 0.986  | ... | -0.986 |
| In1            | -1    | -0.986 | ... | 0.986  |
| Switch         | 0.916 | 0.859  | ... | 0.44   |
| In3            | 1     | 0.986  | ... | -0.986 |
| Parameters     |       |        |     |        |
| Thresh_up      | 0     |        |     |        |
| Thresh_down    | 0     |        |     |        |
| Outputs        |       |        |     |        |
| Out            | -1    | -0.986 | ... | 0.986  |
| Exp. Out       | -1    | -0.986 | ... | 0.986  |
| Out (DSP)      | -1    | -0.986 | ... | 0.986  |
| Exp. Out (DSP) | -1    | -0.986 | ... | 0.986  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0268e-08$ ( $\pm 65$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 73 |
| Max CPU cycles  | 83 |
| Avg CPU cycles  | 77 |

#### Test case: Conversion test

OK

Conversion test for General block AutoSwitch.

| Test results                 |   |     |     |      |
|------------------------------|---|-----|-----|------|
| <b>Time step</b>             | 1 | 2   | ... | 11   |
| <i>Mask parameters</i>       |   |     |     |      |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <i>Controller parameters</i> |   |     |     |      |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_down</b>      | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_up</b>        | 0 | 0.1 | ... | -1.1 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 0,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block AutoSwitch.

| Test results                 |   |     |     |      |
|------------------------------|---|-----|-----|------|
| <b>Time step</b>             | 1 | 2   | ... | 11   |
| <i>Mask parameters</i>       |   |     |     |      |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <i>Controller parameters</i> |   |     |     |      |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_down</b>      | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_up</b>        | 0 | 0.1 | ... | -1.1 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 3,0000e-08$ |
| Tolerance<br>Thresh_up   | $\pm 3,0000e-08$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1265 |
| Max CPU cycles  | 1299 |
| Avg CPU cycles  | 1268 |

**Verification: AutoSwitch Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |       |        |     |        |
|----------------|-------|--------|-----|--------|
| Time step      | 1     | 2      | ... | 137    |
| CPU cycles     | 35    | 35     | ... | 35     |
| Inputs         |       |        |     |        |
| In1 (DSP)      | -1    | -0.986 | ... | 0.986  |
| Switch (DSP)   | 0.916 | 0.859  | ... | 0.44   |
| In3 (DSP)      | 1     | 0.986  | ... | -0.986 |
| In1            | -1    | -0.986 | ... | 0.986  |
| Switch         | 0.916 | 0.859  | ... | 0.44   |
| In3            | 1     | 0.986  | ... | -0.986 |
| Parameters     |       |        |     |        |
| Thresh_up      | 0.3   |        |     |        |
| Thresh_down    | -0.1  |        |     |        |
| Outputs        |       |        |     |        |
| Out            | -1    | -0.986 | ... | 0.986  |
| Exp. Out       | -1    | -0.986 | ... | 0.986  |
| Out (DSP)      | -1    | -0.986 | ... | 0.986  |
| Exp. Out (DSP) | -1    | -0.986 | ... | 0.986  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0268e-08$ ( $\pm 65$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 35 |
| Max CPU cycles  | 43 |
| Avg CPU cycles  | 39 |

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |       |        |     |        |
|----------------|-------|--------|-----|--------|
| Time step      | 1     | 2      | ... | 137    |
| CPU cycles     | 35    | 35     | ... | 35     |
| Inputs         |       |        |     |        |
| In1 (DSP)      | -1    | -0.986 | ... | 0.986  |
| Switch (DSP)   | 0.916 | 0.859  | ... | 0.44   |
| In3 (DSP)      | 1     | 0.986  | ... | -0.986 |
| In1            | -1    | -0.986 | ... | 0.986  |
| Switch         | 0.916 | 0.859  | ... | 0.44   |
| In3            | 1     | 0.986  | ... | -0.986 |
| Parameters     |       |        |     |        |
| Thresh_up      | 0     |        |     |        |
| Thresh_down    | 0     |        |     |        |
| Outputs        |       |        |     |        |
| Out            | -1    | -0.986 | ... | 0.986  |
| Exp. Out       | -1    | -0.986 | ... | 0.986  |
| Out (DSP)      | -1    | -0.986 | ... | 0.986  |
| Exp. Out (DSP) | -1    | -0.986 | ... | 0.986  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0268e-08$ ( $\pm 65$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 35 |
| Max CPU cycles  | 43 |
| Avg CPU cycles  | 38 |

#### Test case: Conversion test

OK

Conversion test for General block AutoSwitch.



| Test results                 |   |     |     |      |
|------------------------------|---|-----|-----|------|
| <b>Time step</b>             | 1 | 2   | ... | 11   |
| <i>Mask parameters</i>       |   |     |     |      |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <i>Controller parameters</i> |   |     |     |      |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_down</b>      | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_up</b>        | 0 | 0.1 | ... | -1.1 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 0,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block AutoSwitch.

| Test results                 |   |     |     |      |
|------------------------------|---|-----|-----|------|
| <b>Time step</b>             | 1 | 2   | ... | 11   |
| <i>Mask parameters</i>       |   |     |     |      |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <i>Controller parameters</i> |   |     |     |      |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_down</b>      | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_up</b>        | 0 | 0.1 | ... | -1.1 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 3,0000e-08$ |
| Tolerance<br>Thresh_up   | $\pm 3,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 613 |
| Max CPU cycles  | 613 |
| Avg CPU cycles  | 613 |

**Verification: AutoSwitch Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |       |        |     |        |
|----------------|-------|--------|-----|--------|
| Time step      | 1     | 2      | ... | 137    |
| CPU cycles     | 67    | 67     | ... | 67     |
| Inputs         |       |        |     |        |
| In1 (DSP)      | -1    | -0.986 | ... | 0.986  |
| Switch (DSP)   | 0.916 | 0.859  | ... | 0.44   |
| In3 (DSP)      | 1     | 0.986  | ... | -0.986 |
| In1            | -1    | -0.986 | ... | 0.986  |
| Switch         | 0.916 | 0.859  | ... | 0.44   |
| In3            | 1     | 0.986  | ... | -0.986 |
| Parameters     |       |        |     |        |
| Thresh_up      | 0.3   |        |     |        |
| Thresh_down    | -0.1  |        |     |        |
| Outputs        |       |        |     |        |
| Out            | -1    | -0.986 | ... | 0.986  |
| Exp. Out       | -1    | -0.986 | ... | 0.986  |
| Out (DSP)      | -1    | -0.986 | ... | 0.986  |
| Exp. Out (DSP) | -1    | -0.986 | ... | 0.986  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0268e-08$ ( $\pm 65$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 67 |
| Max CPU cycles  | 87 |
| Avg CPU cycles  | 78 |

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |       |        |     |        |
|----------------|-------|--------|-----|--------|
| Time step      | 1     | 2      | ... | 137    |
| CPU cycles     | 67    | 67     | ... | 67     |
| Inputs         |       |        |     |        |
| In1 (DSP)      | -1    | -0.986 | ... | 0.986  |
| Switch (DSP)   | 0.916 | 0.859  | ... | 0.44   |
| In3 (DSP)      | 1     | 0.986  | ... | -0.986 |
| In1            | -1    | -0.986 | ... | 0.986  |
| Switch         | 0.916 | 0.859  | ... | 0.44   |
| In3            | 1     | 0.986  | ... | -0.986 |
| Parameters     |       |        |     |        |
| Thresh_up      | 0     |        |     |        |
| Thresh_down    | 0     |        |     |        |
| Outputs        |       |        |     |        |
| Out            | -1    | -0.986 | ... | 0.986  |
| Exp. Out       | -1    | -0.986 | ... | 0.986  |
| Out (DSP)      | -1    | -0.986 | ... | 0.986  |
| Exp. Out (DSP) | -1    | -0.986 | ... | 0.986  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0268e-08$ ( $\pm 65$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 67 |
| Max CPU cycles  | 87 |
| Avg CPU cycles  | 75 |

#### Test case: Conversion test

OK

Conversion test for General block AutoSwitch.

| Test results                 |   |     |     |      |
|------------------------------|---|-----|-----|------|
| <b>Time step</b>             | 1 | 2   | ... | 11   |
| <i>Mask parameters</i>       |   |     |     |      |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <i>Controller parameters</i> |   |     |     |      |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_down</b>      | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_up</b>        | 0 | 0.1 | ... | -1.1 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 0,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block AutoSwitch.

| Test results                 |   |     |     |      |
|------------------------------|---|-----|-----|------|
| <b>Time step</b>             | 1 | 2   | ... | 11   |
| <i>Mask parameters</i>       |   |     |     |      |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <i>Controller parameters</i> |   |     |     |      |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_down</b>      | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_up</b>        | 0 | 0.1 | ... | -1.1 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 3,0000e-08$ |
| Tolerance<br>Thresh_up   | $\pm 3,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 718 |
| Max CPU cycles  | 718 |
| Avg CPU cycles  | 718 |

**Verification: AutoSwitch Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |       |        |     |        |
|----------------|-------|--------|-----|--------|
| Time step      | 1     | 2      | ... | 137    |
| CPU cycles     | 153   | 153    | ... | 156    |
| Inputs         |       |        |     |        |
| In1 (DSP)      | -1    | -0.986 | ... | 0.986  |
| Switch (DSP)   | 0.916 | 0.859  | ... | 0.44   |
| In3 (DSP)      | 1     | 0.986  | ... | -0.986 |
| In1            | -1    | -0.986 | ... | 0.986  |
| Switch         | 0.916 | 0.859  | ... | 0.44   |
| In3            | 1     | 0.986  | ... | -0.986 |
| Parameters     |       |        |     |        |
| Thresh_up      | 0.3   |        |     |        |
| Thresh_down    | -0.1  |        |     |        |
| Outputs        |       |        |     |        |
| Out            | -1    | -0.986 | ... | 0.986  |
| Exp. Out       | -1    | -0.986 | ... | 0.986  |
| Out (DSP)      | -1    | -0.986 | ... | 0.986  |
| Exp. Out (DSP) | -1    | -0.986 | ... | 0.986  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0268e-08$ ( $\pm 65$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 153 |
| Max CPU cycles  | 243 |
| Avg CPU cycles  | 200 |

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |       |        |     |        |
|----------------|-------|--------|-----|--------|
| Time step      | 1     | 2      | ... | 137    |
| CPU cycles     | 141   | 141    | ... | 141    |
| Inputs         |       |        |     |        |
| In1 (DSP)      | -1    | -0.986 | ... | 0.986  |
| Switch (DSP)   | 0.916 | 0.859  | ... | 0.44   |
| In3 (DSP)      | 1     | 0.986  | ... | -0.986 |
| In1            | -1    | -0.986 | ... | 0.986  |
| Switch         | 0.916 | 0.859  | ... | 0.44   |
| In3            | 1     | 0.986  | ... | -0.986 |
| Parameters     |       |        |     |        |
| Thresh_up      | 0     |        |     |        |
| Thresh_down    | 0     |        |     |        |
| Outputs        |       |        |     |        |
| Out            | -1    | -0.986 | ... | 0.986  |
| Exp. Out       | -1    | -0.986 | ... | 0.986  |
| Out (DSP)      | -1    | -0.986 | ... | 0.986  |
| Exp. Out (DSP) | -1    | -0.986 | ... | 0.986  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0268e-08$ ( $\pm 65$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 141 |
| Max CPU cycles  | 229 |
| Avg CPU cycles  | 180 |

#### Test case: Conversion test

OK

Conversion test for General block AutoSwitch.



| Test results                 |   |     |     |      |
|------------------------------|---|-----|-----|------|
| <b>Time step</b>             | 1 | 2   | ... | 11   |
| <i>Mask parameters</i>       |   |     |     |      |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <i>Controller parameters</i> |   |     |     |      |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_down</b>      | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_up</b>        | 0 | 0.1 | ... | -1.1 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 0,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block AutoSwitch.

| Test results                 |   |     |     |      |
|------------------------------|---|-----|-----|------|
| <b>Time step</b>             | 1 | 2   | ... | 11   |
| <i>Mask parameters</i>       |   |     |     |      |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <i>Controller parameters</i> |   |     |     |      |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_down</b>      | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_up</b>        | 0 | 0.1 | ... | -1.1 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 3,0000e-08$ |
| Tolerance<br>Thresh_up   | $\pm 3,0000e-08$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1150 |
| Max CPU cycles  | 1232 |
| Avg CPU cycles  | 1218 |

**Verification: AutoSwitch Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |       |        |     |        |
|----------------|-------|--------|-----|--------|
| Time step      | 1     | 2      | ... | 137    |
| CPU cycles     | 87    | 87     | ... | 87     |
| Inputs         |       |        |     |        |
| In1 (DSP)      | -1    | -0.986 | ... | 0.986  |
| Switch (DSP)   | 0.916 | 0.859  | ... | 0.44   |
| In3 (DSP)      | 1     | 0.986  | ... | -0.986 |
| In1            | -1    | -0.986 | ... | 0.986  |
| Switch         | 0.916 | 0.859  | ... | 0.44   |
| In3            | 1     | 0.986  | ... | -0.986 |
| Parameters     |       |        |     |        |
| Thresh_up      | 0.3   |        |     |        |
| Thresh_down    | -0.1  |        |     |        |
| Outputs        |       |        |     |        |
| Out            | -1    | -0.986 | ... | 0.986  |
| Exp. Out       | -1    | -0.986 | ... | 0.986  |
| Out (DSP)      | -1    | -0.986 | ... | 0.986  |
| Exp. Out (DSP) | -1    | -0.986 | ... | 0.986  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0268e-08$ ( $\pm 65$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 87  |
| Max CPU cycles  | 123 |
| Avg CPU cycles  | 106 |

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |       |        |     |        |
|----------------|-------|--------|-----|--------|
| Time step      | 1     | 2      | ... | 137    |
| CPU cycles     | 87    | 87     | ... | 87     |
| Inputs         |       |        |     |        |
| In1 (DSP)      | -1    | -0.986 | ... | 0.986  |
| Switch (DSP)   | 0.916 | 0.859  | ... | 0.44   |
| In3 (DSP)      | 1     | 0.986  | ... | -0.986 |
| In1            | -1    | -0.986 | ... | 0.986  |
| Switch         | 0.916 | 0.859  | ... | 0.44   |
| In3            | 1     | 0.986  | ... | -0.986 |
| Parameters     |       |        |     |        |
| Thresh_up      | 0     |        |     |        |
| Thresh_down    | 0     |        |     |        |
| Outputs        |       |        |     |        |
| Out            | -1    | -0.986 | ... | 0.986  |
| Exp. Out       | -1    | -0.986 | ... | 0.986  |
| Out (DSP)      | -1    | -0.986 | ... | 0.986  |
| Exp. Out (DSP) | -1    | -0.986 | ... | 0.986  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0268e-08$ ( $\pm 65$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 87  |
| Max CPU cycles  | 120 |
| Avg CPU cycles  | 101 |

#### Test case: Conversion test

OK

Conversion test for General block AutoSwitch.

| Test results                 |   |     |     |      |
|------------------------------|---|-----|-----|------|
| <b>Time step</b>             | 1 | 2   | ... | 11   |
| <i>Mask parameters</i>       |   |     |     |      |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <i>Controller parameters</i> |   |     |     |      |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_down</b>      | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_up</b>        | 0 | 0.1 | ... | -1.1 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 0,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block AutoSwitch.

| Test results                 |   |     |     |      |
|------------------------------|---|-----|-----|------|
| <b>Time step</b>             | 1 | 2   | ... | 11   |
| <i>Mask parameters</i>       |   |     |     |      |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <i>Controller parameters</i> |   |     |     |      |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_down</b>      | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_up</b>        | 0 | 0.1 | ... | -1.1 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 3,0000e-08$ |
| Tolerance<br>Thresh_up   | $\pm 3,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 434 |
| Max CPU cycles  | 468 |
| Avg CPU cycles  | 462 |

**Verification: AutoSwitch Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |       |        |     |        |
|----------------|-------|--------|-----|--------|
| Time step      | 1     | 2      | ... | 137    |
| CPU cycles     | 160   | 160    | ... | 160    |
| Inputs         |       |        |     |        |
| In1 (DSP)      | -1    | -0.986 | ... | 0.986  |
| Switch (DSP)   | 0.916 | 0.859  | ... | 0.44   |
| In3 (DSP)      | 1     | 0.986  | ... | -0.986 |
| In1            | -1    | -0.986 | ... | 0.986  |
| Switch         | 0.916 | 0.859  | ... | 0.44   |
| In3            | 1     | 0.986  | ... | -0.986 |
| Parameters     |       |        |     |        |
| Thresh_up      | 0.3   |        |     |        |
| Thresh_down    | -0.1  |        |     |        |
| Outputs        |       |        |     |        |
| Out            | -1    | -0.986 | ... | 0.986  |
| Exp. Out       | -1    | -0.986 | ... | 0.986  |
| Out (DSP)      | -1    | -0.986 | ... | 0.986  |
| Exp. Out (DSP) | -1    | -0.986 | ... | 0.986  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0268e-08$ ( $\pm 65$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 160 |
| Max CPU cycles  | 256 |
| Avg CPU cycles  | 213 |

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |       |        |     |        |
|----------------|-------|--------|-----|--------|
| Time step      | 1     | 2      | ... | 137    |
| CPU cycles     | 162   | 162    | ... | 162    |
| Inputs         |       |        |     |        |
| In1 (DSP)      | -1    | -0.986 | ... | 0.986  |
| Switch (DSP)   | 0.916 | 0.859  | ... | 0.44   |
| In3 (DSP)      | 1     | 0.986  | ... | -0.986 |
| In1            | -1    | -0.986 | ... | 0.986  |
| Switch         | 0.916 | 0.859  | ... | 0.44   |
| In3            | 1     | 0.986  | ... | -0.986 |
| Parameters     |       |        |     |        |
| Thresh_up      | 0     |        |     |        |
| Thresh_down    | 0     |        |     |        |
| Outputs        |       |        |     |        |
| Out            | -1    | -0.986 | ... | 0.986  |
| Exp. Out       | -1    | -0.986 | ... | 0.986  |
| Out (DSP)      | -1    | -0.986 | ... | 0.986  |
| Exp. Out (DSP) | -1    | -0.986 | ... | 0.986  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0268e-08$ ( $\pm 65$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 162 |
| Max CPU cycles  | 255 |
| Avg CPU cycles  | 203 |

#### Test case: Conversion test

OK

Conversion test for General block AutoSwitch.



| Test results                 |   |     |     |      |
|------------------------------|---|-----|-----|------|
| <b>Time step</b>             | 1 | 2   | ... | 11   |
| <i>Mask parameters</i>       |   |     |     |      |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <i>Controller parameters</i> |   |     |     |      |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_down</b>      | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_up</b>        | 0 | 0.1 | ... | -1.1 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 0,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block AutoSwitch.

| Test results                 |   |     |     |      |
|------------------------------|---|-----|-----|------|
| <b>Time step</b>             | 1 | 2   | ... | 11   |
| <i>Mask parameters</i>       |   |     |     |      |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <i>Controller parameters</i> |   |     |     |      |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_down</b>      | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_up</b>        | 0 | 0.1 | ... | -1.1 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 3,0000e-08$ |
| Tolerance<br>Thresh_up   | $\pm 3,0000e-08$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 983  |
| Max CPU cycles  | 1641 |
| Avg CPU cycles  | 1578 |

**Verification: AutoSwitch Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |       |        |     |        |
|----------------|-------|--------|-----|--------|
| Time step      | 1     | 2      | ... | 137    |
| CPU cycles     | 78    | 62     | ... | 62     |
| Inputs         |       |        |     |        |
| In1 (DSP)      | -1    | -0.986 | ... | 0.986  |
| Switch (DSP)   | 0.916 | 0.859  | ... | 0.44   |
| In3 (DSP)      | 1     | 0.986  | ... | -0.986 |
| In1            | -1    | -0.986 | ... | 0.986  |
| Switch         | 0.916 | 0.859  | ... | 0.44   |
| In3            | 1     | 0.986  | ... | -0.986 |
| Parameters     |       |        |     |        |
| Thresh_up      | 0.3   |        |     |        |
| Thresh_down    | -0.1  |        |     |        |
| Outputs        |       |        |     |        |
| Out            | -1    | -0.986 | ... | 0.986  |
| Exp. Out       | -1    | -0.986 | ... | 0.986  |
| Out (DSP)      | -1    | -0.986 | ... | 0.986  |
| Exp. Out (DSP) | -1    | -0.986 | ... | 0.986  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0268e-08$ ( $\pm 65$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 78 |
| Avg CPU cycles  | 65 |

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |       |        |     |        |
|----------------|-------|--------|-----|--------|
| Time step      | 1     | 2      | ... | 137    |
| CPU cycles     | 78    | 62     | ... | 62     |
| Inputs         |       |        |     |        |
| In1 (DSP)      | -1    | -0.986 | ... | 0.986  |
| Switch (DSP)   | 0.916 | 0.859  | ... | 0.44   |
| In3 (DSP)      | 1     | 0.986  | ... | -0.986 |
| In1            | -1    | -0.986 | ... | 0.986  |
| Switch         | 0.916 | 0.859  | ... | 0.44   |
| In3            | 1     | 0.986  | ... | -0.986 |
| Parameters     |       |        |     |        |
| Thresh_up      | 0     |        |     |        |
| Thresh_down    | 0     |        |     |        |
| Outputs        |       |        |     |        |
| Out            | -1    | -0.986 | ... | 0.986  |
| Exp. Out       | -1    | -0.986 | ... | 0.986  |
| Out (DSP)      | -1    | -0.986 | ... | 0.986  |
| Exp. Out (DSP) | -1    | -0.986 | ... | 0.986  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0268e-08$ ( $\pm 65$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 78 |
| Avg CPU cycles  | 65 |

#### Test case: Conversion test

OK

Conversion test for General block AutoSwitch.

| Test results                 |   |     |     |      |
|------------------------------|---|-----|-----|------|
| <b>Time step</b>             | 1 | 2   | ... | 11   |
| <i>Mask parameters</i>       |   |     |     |      |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <i>Controller parameters</i> |   |     |     |      |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_down</b>      | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_up</b>        | 0 | 0.1 | ... | -1.1 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 0,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block AutoSwitch.

| Test results                 |   |     |     |      |
|------------------------------|---|-----|-----|------|
| <b>Time step</b>             | 1 | 2   | ... | 11   |
| <i>Mask parameters</i>       |   |     |     |      |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <i>Controller parameters</i> |   |     |     |      |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_down</b>      | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_up</b>        | 0 | 0.1 | ... | -1.1 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 3,0000e-08$ |
| Tolerance<br>Thresh_up   | $\pm 3,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 627 |
| Max CPU cycles  | 703 |
| Avg CPU cycles  | 633 |

**Verification: AutoSwitch Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |       |        |     |        |
|----------------|-------|--------|-----|--------|
| Time step      | 1     | 2      | ... | 137    |
| CPU cycles     | 58    | 58     | ... | 58     |
| Inputs         |       |        |     |        |
| In1 (DSP)      | -1    | -0.986 | ... | 0.986  |
| Switch (DSP)   | 0.916 | 0.859  | ... | 0.44   |
| In3 (DSP)      | 1     | 0.986  | ... | -0.986 |
| In1            | -1    | -0.986 | ... | 0.986  |
| Switch         | 0.916 | 0.859  | ... | 0.44   |
| In3            | 1     | 0.986  | ... | -0.986 |
| Parameters     |       |        |     |        |
| Thresh_up      | 0.3   |        |     |        |
| Thresh_down    | -0.1  |        |     |        |
| Outputs        |       |        |     |        |
| Out            | -1    | -0.986 | ... | 0.986  |
| Exp. Out       | -1    | -0.986 | ... | 0.986  |
| Out (DSP)      | -1    | -0.986 | ... | 0.986  |
| Exp. Out (DSP) | -1    | -0.986 | ... | 0.986  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0268e-08$ ( $\pm 65$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 58 |
| Max CPU cycles  | 73 |
| Avg CPU cycles  | 66 |

**Test case: Inport test****OK**

Inport test for General block AutoSwitch.

| Test results   |       |        |     |        |
|----------------|-------|--------|-----|--------|
| Time step      | 1     | 2      | ... | 137    |
| CPU cycles     | 58    | 58     | ... | 58     |
| Inputs         |       |        |     |        |
| In1 (DSP)      | -1    | -0.986 | ... | 0.986  |
| Switch (DSP)   | 0.916 | 0.859  | ... | 0.44   |
| In3 (DSP)      | 1     | 0.986  | ... | -0.986 |
| In1            | -1    | -0.986 | ... | 0.986  |
| Switch         | 0.916 | 0.859  | ... | 0.44   |
| In3            | 1     | 0.986  | ... | -0.986 |
| Parameters     |       |        |     |        |
| Thresh_up      | 0     |        |     |        |
| Thresh_down    | 0     |        |     |        |
| Outputs        |       |        |     |        |
| Out            | -1    | -0.986 | ... | 0.986  |
| Exp. Out       | -1    | -0.986 | ... | 0.986  |
| Out (DSP)      | -1    | -0.986 | ... | 0.986  |
| Exp. Out (DSP) | -1    | -0.986 | ... | 0.986  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0268e-08$ ( $\pm 65$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 58 |
| Max CPU cycles  | 73 |
| Avg CPU cycles  | 64 |

#### Test case: Conversion test

OK

Conversion test for General block AutoSwitch.



| Test results                 |   |     |     |      |
|------------------------------|---|-----|-----|------|
| <b>Time step</b>             | 1 | 2   | ... | 11   |
| <i>Mask parameters</i>       |   |     |     |      |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <i>Controller parameters</i> |   |     |     |      |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_down</b>      | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_up</b>        | 0 | 0.1 | ... | -1.1 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 0,0000e+00$ |
| Tolerance<br>Thresh_up   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block AutoSwitch.

| Test results                 |   |     |     |      |
|------------------------------|---|-----|-----|------|
| <b>Time step</b>             | 1 | 2   | ... | 11   |
| <i>Mask parameters</i>       |   |     |     |      |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <i>Controller parameters</i> |   |     |     |      |
| <b>Thresh_down</b>           | 0 | 0.1 | ... | -1.1 |
| <b>Thresh_up</b>             | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_down</b>      | 0 | 0.1 | ... | -1.1 |
| <b>Exp. Thresh_up</b>        | 0 | 0.1 | ... | -1.1 |

| Test settings            |                  |
|--------------------------|------------------|
| Tolerance<br>Thresh_down | $\pm 3,0000e-08$ |
| Tolerance<br>Thresh_up   | $\pm 3,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 942 |
| Max CPU cycles  | 948 |
| Avg CPU cycles  | 942 |

## Block: Constant

---



Constant value.

| Outputs |                 |
|---------|-----------------|
| Out     | Constant output |

| Mask Parameters |    |                 |
|-----------------|----|-----------------|
| Name            | ID | Description     |
| Value           | 1  | Constant factor |

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>Bool</b>    | Boolean Implementation               |
| <b>Int8</b>    | 8 Bit Integer Implementation         |
| <b>Int16</b>   | 16 Bit Integer Implementation        |
| <b>Int32</b>   | 32 Bit Integer Implementation        |
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: Bool

---

Boolean Implementation

| Outputs Data Type |      |
|-------------------|------|
| Out               | bool |

### Implementation: Int8

---

8 Bit Integer Implementation

| Outputs Data Type |      |
|-------------------|------|
| Out               | int8 |

### Implementation: Int16

---

16 Bit Integer Implementation

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: Int32

32 Bit Integer Implementation

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: FiP8

8 Bit Fixed Point Implementation

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

16 Bit Fixed Point Implementation

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

## Implementation: Float64

---

64 Bit Floating Point Implementation

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: Constant Bool CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results                 |   |    |   |     |     |  |      |
|------------------------------|---|----|---|-----|-----|--|------|
| <b>Time step</b>             | 1 | 2  | 3 | 4   | ... |  | 7    |
| <i>Mask parameters</i>       |   |    |   |     |     |  |      |
| <b>Value</b>                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| <i>Controller parameters</i> |   |    |   |     |     |  |      |
| <b>K</b>                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| <b>Exp. K</b>                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results                 |   |    |   |     |     |  |      |
|------------------------------|---|----|---|-----|-----|--|------|
| <b>Time step</b>             | 1 | 2  | 3 | 4   | ... |  | 7    |
| <i>Mask parameters</i>       |   |    |   |     |     |  |      |
| <b>Value</b>                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| <i>Controller parameters</i> |   |    |   |     |     |  |      |
| <b>K</b>                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| <b>Exp. K</b>                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 776 |
| Max CPU cycles  | 813 |
| Avg CPU cycles  | 807 |

**Verification: Constant Bool CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results                 |   |    |   |     |     |  |      |
|------------------------------|---|----|---|-----|-----|--|------|
| <b>Time step</b>             | 1 | 2  | 3 | 4   | ... |  | 7    |
| <i>Mask parameters</i>       |   |    |   |     |     |  |      |
| <b>Value</b>                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| <i>Controller parameters</i> |   |    |   |     |     |  |      |
| <b>K</b>                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| <b>Exp. K</b>                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results                 |   |    |   |     |     |  |      |
|------------------------------|---|----|---|-----|-----|--|------|
| <b>Time step</b>             | 1 | 2  | 3 | 4   | ... |  | 7    |
| <i>Mask parameters</i>       |   |    |   |     |     |  |      |
| <b>Value</b>                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| <i>Controller parameters</i> |   |    |   |     |     |  |      |
| <b>K</b>                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| <b>Exp. K</b>                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 373 |
| Max CPU cycles  | 399 |
| Avg CPU cycles  | 393 |

**Verification: Constant Bool CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results                 |   |    |   |     |     |  |      |
|------------------------------|---|----|---|-----|-----|--|------|
| <b>Time step</b>             | 1 | 2  | 3 | 4   | ... |  | 7    |
| <i>Mask parameters</i>       |   |    |   |     |     |  |      |
| <b>Value</b>                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| <i>Controller parameters</i> |   |    |   |     |     |  |      |
| <b>K</b>                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| <b>Exp. K</b>                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results                 |   |    |   |     |     |  |      |
|------------------------------|---|----|---|-----|-----|--|------|
| <b>Time step</b>             | 1 | 2  | 3 | 4   | ... |  | 7    |
| <i>Mask parameters</i>       |   |    |   |     |     |  |      |
| <b>Value</b>                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| <i>Controller parameters</i> |   |    |   |     |     |  |      |
| <b>K</b>                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| <b>Exp. K</b>                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 518 |
| Max CPU cycles  | 538 |
| Avg CPU cycles  | 535 |



**Verification: Constant Bool CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results                 |   |    |   |     |     |  |      |
|------------------------------|---|----|---|-----|-----|--|------|
| <b>Time step</b>             | 1 | 2  | 3 | 4   | ... |  | 7    |
| <i>Mask parameters</i>       |   |    |   |     |     |  |      |
| <b>Value</b>                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| <i>Controller parameters</i> |   |    |   |     |     |  |      |
| <b>K</b>                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| <b>Exp. K</b>                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results                 |   |    |   |     |     |  |      |
|------------------------------|---|----|---|-----|-----|--|------|
| <b>Time step</b>             | 1 | 2  | 3 | 4   | ... |  | 7    |
| <i>Mask parameters</i>       |   |    |   |     |     |  |      |
| <b>Value</b>                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| <i>Controller parameters</i> |   |    |   |     |     |  |      |
| <b>K</b>                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| <b>Exp. K</b>                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 593 |
| Max CPU cycles  | 606 |
| Avg CPU cycles  | 594 |

**Verification: Constant Bool CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results                 |   |    |   |     |     |  |      |
|------------------------------|---|----|---|-----|-----|--|------|
| <b>Time step</b>             | 1 | 2  | 3 | 4   | ... |  | 7    |
| <i>Mask parameters</i>       |   |    |   |     |     |  |      |
| <b>Value</b>                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| <i>Controller parameters</i> |   |    |   |     |     |  |      |
| <b>K</b>                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| <b>Exp. K</b>                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results                 |   |    |   |     |     |  |      |
|------------------------------|---|----|---|-----|-----|--|------|
| <b>Time step</b>             | 1 | 2  | 3 | 4   | ... |  | 7    |
| <i>Mask parameters</i>       |   |    |   |     |     |  |      |
| <b>Value</b>                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| <i>Controller parameters</i> |   |    |   |     |     |  |      |
| <b>K</b>                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| <b>Exp. K</b>                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 243 |
| Max CPU cycles  | 276 |
| Avg CPU cycles  | 265 |

**Verification: Constant Bool CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results                 |   |    |   |     |     |  |      |
|------------------------------|---|----|---|-----|-----|--|------|
| <b>Time step</b>             | 1 | 2  | 3 | 4   | ... |  | 7    |
| <i>Mask parameters</i>       |   |    |   |     |     |  |      |
| <b>Value</b>                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| <i>Controller parameters</i> |   |    |   |     |     |  |      |
| <b>K</b>                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| <b>Exp. K</b>                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results                 |   |    |   |     |     |  |      |
|------------------------------|---|----|---|-----|-----|--|------|
| <b>Time step</b>             | 1 | 2  | 3 | 4   | ... |  | 7    |
| <i>Mask parameters</i>       |   |    |   |     |     |  |      |
| <b>Value</b>                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| <i>Controller parameters</i> |   |    |   |     |     |  |      |
| <b>K</b>                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| <b>Exp. K</b>                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 521 |
| Max CPU cycles  | 552 |
| Avg CPU cycles  | 528 |

**Verification: Constant Bool CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results          |   |    |   |     |     |  |      |
|-----------------------|---|----|---|-----|-----|--|------|
| Time step             | 1 | 2  | 3 | 4   | ... |  | 7    |
| Mask parameters       |   |    |   |     |     |  |      |
| Value                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| Controller parameters |   |    |   |     |     |  |      |
| K                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| Exp. K                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results          |   |    |   |     |     |  |      |
|-----------------------|---|----|---|-----|-----|--|------|
| Time step             | 1 | 2  | 3 | 4   | ... |  | 7    |
| Mask parameters       |   |    |   |     |     |  |      |
| Value                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| Controller parameters |   |    |   |     |     |  |      |
| K                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| Exp. K                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 439 |
| Max CPU cycles  | 497 |
| Avg CPU cycles  | 453 |

**Verification: Constant Bool CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results                 |   |    |   |     |     |  |      |
|------------------------------|---|----|---|-----|-----|--|------|
| <b>Time step</b>             | 1 | 2  | 3 | 4   | ... |  | 7    |
| <i>Mask parameters</i>       |   |    |   |     |     |  |      |
| <b>Value</b>                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| <i>Controller parameters</i> |   |    |   |     |     |  |      |
| <b>K</b>                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| <b>Exp. K</b>                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results                 |   |    |   |     |     |  |      |
|------------------------------|---|----|---|-----|-----|--|------|
| <b>Time step</b>             | 1 | 2  | 3 | 4   | ... |  | 7    |
| <i>Mask parameters</i>       |   |    |   |     |     |  |      |
| <b>Value</b>                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| <i>Controller parameters</i> |   |    |   |     |     |  |      |
| <b>K</b>                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| <b>Exp. K</b>                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 616 |
| Max CPU cycles  | 645 |
| Avg CPU cycles  | 640 |

**Verification: Constant Int16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results          |       |       |       |       |     |        |
|-----------------------|-------|-------|-------|-------|-----|--------|
| Time step             | 1     | 2     | 3     | 4     | ... | 17     |
| Mask parameters       |       |       |       |       |     |        |
| Value                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| Controller parameters |       |       |       |       |     |        |
| K                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| Exp. K                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results          |       |       |       |       |     |        |
|-----------------------|-------|-------|-------|-------|-----|--------|
| Time step             | 1     | 2     | 3     | 4     | ... | 17     |
| Mask parameters       |       |       |       |       |     |        |
| Value                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| Controller parameters |       |       |       |       |     |        |
| K                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| Exp. K                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1191 |
| Max CPU cycles  | 1436 |
| Avg CPU cycles  | 1406 |

**Verification: Constant Int16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results          |       |       |       |       |     |        |
|-----------------------|-------|-------|-------|-------|-----|--------|
| Time step             | 1     | 2     | 3     | 4     | ... | 17     |
| Mask parameters       |       |       |       |       |     |        |
| Value                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| Controller parameters |       |       |       |       |     |        |
| K                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| Exp. K                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results          |       |       |       |       |     |        |
|-----------------------|-------|-------|-------|-------|-----|--------|
| Time step             | 1     | 2     | 3     | 4     | ... | 17     |
| Mask parameters       |       |       |       |       |     |        |
| Value                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| Controller parameters |       |       |       |       |     |        |
| K                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| Exp. K                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 653 |
| Max CPU cycles  | 889 |
| Avg CPU cycles  | 842 |

**Verification: Constant Int16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results          |       |       |       |       |     |        |
|-----------------------|-------|-------|-------|-------|-----|--------|
| Time step             | 1     | 2     | 3     | 4     | ... | 17     |
| Mask parameters       |       |       |       |       |     |        |
| Value                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| Controller parameters |       |       |       |       |     |        |
| K                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| Exp. K                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results          |       |       |       |       |     |        |
|-----------------------|-------|-------|-------|-------|-----|--------|
| Time step             | 1     | 2     | 3     | 4     | ... | 17     |
| Mask parameters       |       |       |       |       |     |        |
| Value                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| Controller parameters |       |       |       |       |     |        |
| K                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| Exp. K                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 841  |
| Max CPU cycles  | 1086 |
| Avg CPU cycles  | 1038 |



**Verification: Constant Int16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results                 |       |       |       |       |     |        |
|------------------------------|-------|-------|-------|-------|-----|--------|
| <b>Time step</b>             | 1     | 2     | 3     | 4     | ... | 17     |
| <i>Mask parameters</i>       |       |       |       |       |     |        |
| <b>Value</b>                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| <i>Controller parameters</i> |       |       |       |       |     |        |
| <b>K</b>                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| <b>Exp. K</b>                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results                 |       |       |       |       |     |        |
|------------------------------|-------|-------|-------|-------|-----|--------|
| <b>Time step</b>             | 1     | 2     | 3     | 4     | ... | 17     |
| <i>Mask parameters</i>       |       |       |       |       |     |        |
| <b>Value</b>                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| <i>Controller parameters</i> |       |       |       |       |     |        |
| <b>K</b>                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| <b>Exp. K</b>                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 923  |
| Max CPU cycles  | 1246 |
| Avg CPU cycles  | 1199 |

**Verification: Constant Int16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results          |       |       |       |       |     |        |
|-----------------------|-------|-------|-------|-------|-----|--------|
| Time step             | 1     | 2     | 3     | 4     | ... | 17     |
| Mask parameters       |       |       |       |       |     |        |
| Value                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| Controller parameters |       |       |       |       |     |        |
| K                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| Exp. K                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results          |       |       |       |       |     |        |
|-----------------------|-------|-------|-------|-------|-----|--------|
| Time step             | 1     | 2     | 3     | 4     | ... | 17     |
| Mask parameters       |       |       |       |       |     |        |
| Value                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| Controller parameters |       |       |       |       |     |        |
| K                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| Exp. K                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 399 |
| Max CPU cycles  | 473 |
| Avg CPU cycles  | 465 |

**Verification: Constant Int16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results          |       |       |       |       |     |        |
|-----------------------|-------|-------|-------|-------|-----|--------|
| Time step             | 1     | 2     | 3     | 4     | ... | 17     |
| Mask parameters       |       |       |       |       |     |        |
| Value                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| Controller parameters |       |       |       |       |     |        |
| K                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| Exp. K                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results          |       |       |       |       |     |        |
|-----------------------|-------|-------|-------|-------|-----|--------|
| Time step             | 1     | 2     | 3     | 4     | ... | 17     |
| Mask parameters       |       |       |       |       |     |        |
| Value                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| Controller parameters |       |       |       |       |     |        |
| K                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| Exp. K                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1300 |
| Max CPU cycles  | 1729 |
| Avg CPU cycles  | 1607 |

**Verification: Constant Int16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results          |       |       |       |       |     |        |
|-----------------------|-------|-------|-------|-------|-----|--------|
| Time step             | 1     | 2     | 3     | 4     | ... | 17     |
| Mask parameters       |       |       |       |       |     |        |
| Value                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| Controller parameters |       |       |       |       |     |        |
| K                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| Exp. K                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results          |       |       |       |       |     |        |
|-----------------------|-------|-------|-------|-------|-----|--------|
| Time step             | 1     | 2     | 3     | 4     | ... | 17     |
| Mask parameters       |       |       |       |       |     |        |
| Value                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| Controller parameters |       |       |       |       |     |        |
| K                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| Exp. K                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 688  |
| Max CPU cycles  | 1026 |
| Avg CPU cycles  | 863  |

**Verification: Constant Int16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results          |       |       |       |       |     |        |
|-----------------------|-------|-------|-------|-------|-----|--------|
| Time step             | 1     | 2     | 3     | 4     | ... | 17     |
| Mask parameters       |       |       |       |       |     |        |
| Value                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| Controller parameters |       |       |       |       |     |        |
| K                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| Exp. K                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results          |       |       |       |       |     |        |
|-----------------------|-------|-------|-------|-------|-----|--------|
| Time step             | 1     | 2     | 3     | 4     | ... | 17     |
| Mask parameters       |       |       |       |       |     |        |
| Value                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| Controller parameters |       |       |       |       |     |        |
| K                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| Exp. K                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1091 |
| Max CPU cycles  | 1473 |
| Avg CPU cycles  | 1406 |

**Verification: Constant Int32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 3,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1210 |
| Max CPU cycles  | 1456 |
| Avg CPU cycles  | 1385 |

**Verification: Constant Int32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 3,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 677 |
| Max CPU cycles  | 893 |
| Avg CPU cycles  | 859 |

**Verification: Constant Int32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 3,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 855  |
| Max CPU cycles  | 1100 |
| Avg CPU cycles  | 1059 |



**Verification: Constant Int32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 3,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 953  |
| Max CPU cycles  | 1314 |
| Avg CPU cycles  | 1231 |

**Verification: Constant Int32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 3,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 395 |
| Max CPU cycles  | 475 |
| Avg CPU cycles  | 461 |

**Verification: Constant Int32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 3,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1321 |
| Max CPU cycles  | 1731 |
| Avg CPU cycles  | 1611 |

**Verification: Constant Int32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 3,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 678 |
| Max CPU cycles  | 960 |
| Avg CPU cycles  | 844 |

**Verification: Constant Int32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 3,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1116 |
| Max CPU cycles  | 1485 |
| Avg CPU cycles  | 1438 |

**Verification: Constant FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results          |       |        |   |       |     |        |
|-----------------------|-------|--------|---|-------|-----|--------|
| Time step             | 1     | 2      | 3 | 4     | ... | 7      |
| Mask parameters       |       |        |   |       |     |        |
| Value                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| Controller parameters |       |        |   |       |     |        |
| K                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| Exp. K                | 32767 | -32767 | 0 | 16384 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results          |       |        |   |       |     |        |
|-----------------------|-------|--------|---|-------|-----|--------|
| Time step             | 1     | 2      | 3 | 4     | ... | 7      |
| Mask parameters       |       |        |   |       |     |        |
| Value                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| Controller parameters |       |        |   |       |     |        |
| K                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| Exp. K                | 32767 | -32767 | 0 | 16384 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 854 |
| Max CPU cycles  | 871 |
| Avg CPU cycles  | 856 |

**Verification: Constant FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results          |       |        |   |       |     |        |
|-----------------------|-------|--------|---|-------|-----|--------|
| Time step             | 1     | 2      | 3 | 4     | ... | 7      |
| Mask parameters       |       |        |   |       |     |        |
| Value                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| Controller parameters |       |        |   |       |     |        |
| K                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| Exp. K                | 32767 | -32767 | 0 | 16384 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results          |       |        |   |       |     |        |
|-----------------------|-------|--------|---|-------|-----|--------|
| Time step             | 1     | 2      | 3 | 4     | ... | 7      |
| Mask parameters       |       |        |   |       |     |        |
| Value                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| Controller parameters |       |        |   |       |     |        |
| K                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| Exp. K                | 32767 | -32767 | 0 | 16384 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 401 |
| Max CPU cycles  | 407 |
| Avg CPU cycles  | 404 |

**Verification: Constant FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results          |       |        |   |       |     |        |
|-----------------------|-------|--------|---|-------|-----|--------|
| Time step             | 1     | 2      | 3 | 4     | ... | 7      |
| Mask parameters       |       |        |   |       |     |        |
| Value                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| Controller parameters |       |        |   |       |     |        |
| K                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| Exp. K                | 32767 | -32767 | 0 | 16384 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results          |       |        |   |       |     |        |
|-----------------------|-------|--------|---|-------|-----|--------|
| Time step             | 1     | 2      | 3 | 4     | ... | 7      |
| Mask parameters       |       |        |   |       |     |        |
| Value                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| Controller parameters |       |        |   |       |     |        |
| K                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| Exp. K                | 32767 | -32767 | 0 | 16384 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 532 |
| Max CPU cycles  | 532 |
| Avg CPU cycles  | 532 |



**Verification: Constant FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results          |       |        |   |       |     |        |
|-----------------------|-------|--------|---|-------|-----|--------|
| Time step             | 1     | 2      | 3 | 4     | ... | 7      |
| Mask parameters       |       |        |   |       |     |        |
| Value                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| Controller parameters |       |        |   |       |     |        |
| K                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| Exp. K                | 32767 | -32767 | 0 | 16384 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results          |       |        |   |       |     |        |
|-----------------------|-------|--------|---|-------|-----|--------|
| Time step             | 1     | 2      | 3 | 4     | ... | 7      |
| Mask parameters       |       |        |   |       |     |        |
| Value                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| Controller parameters |       |        |   |       |     |        |
| K                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| Exp. K                | 32767 | -32767 | 0 | 16384 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 810 |
| Max CPU cycles  | 912 |
| Avg CPU cycles  | 890 |

**Verification: Constant FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results                 |       |        |   |       |     |        |
|------------------------------|-------|--------|---|-------|-----|--------|
| <b>Time step</b>             | 1     | 2      | 3 | 4     | ... | 7      |
| <i>Mask parameters</i>       |       |        |   |       |     |        |
| <b>Value</b>                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| <i>Controller parameters</i> |       |        |   |       |     |        |
| <b>K</b>                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| <b>Exp. K</b>                | 32767 | -32767 | 0 | 16384 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results                 |       |        |   |       |     |        |
|------------------------------|-------|--------|---|-------|-----|--------|
| <b>Time step</b>             | 1     | 2      | 3 | 4     | ... | 7      |
| <i>Mask parameters</i>       |       |        |   |       |     |        |
| <b>Value</b>                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| <i>Controller parameters</i> |       |        |   |       |     |        |
| <b>K</b>                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| <b>Exp. K</b>                | 32767 | -32767 | 0 | 16384 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 384 |
| Max CPU cycles  | 405 |
| Avg CPU cycles  | 401 |

**Verification: Constant FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results                 |       |        |   |       |     |        |
|------------------------------|-------|--------|---|-------|-----|--------|
| <b>Time step</b>             | 1     | 2      | 3 | 4     | ... | 7      |
| <i>Mask parameters</i>       |       |        |   |       |     |        |
| <b>Value</b>                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| <i>Controller parameters</i> |       |        |   |       |     |        |
| <b>K</b>                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| <b>Exp. K</b>                | 32767 | -32767 | 0 | 16384 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results                 |       |        |   |       |     |        |
|------------------------------|-------|--------|---|-------|-----|--------|
| <b>Time step</b>             | 1     | 2      | 3 | 4     | ... | 7      |
| <i>Mask parameters</i>       |       |        |   |       |     |        |
| <b>Value</b>                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| <i>Controller parameters</i> |       |        |   |       |     |        |
| <b>K</b>                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| <b>Exp. K</b>                | 32767 | -32767 | 0 | 16384 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 839  |
| Max CPU cycles  | 1291 |
| Avg CPU cycles  | 1219 |

**Verification: Constant FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results          |       |        |   |       |     |        |
|-----------------------|-------|--------|---|-------|-----|--------|
| Time step             | 1     | 2      | 3 | 4     | ... | 7      |
| Mask parameters       |       |        |   |       |     |        |
| Value                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| Controller parameters |       |        |   |       |     |        |
| K                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| Exp. K                | 32767 | -32767 | 0 | 16384 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results          |       |        |   |       |     |        |
|-----------------------|-------|--------|---|-------|-----|--------|
| Time step             | 1     | 2      | 3 | 4     | ... | 7      |
| Mask parameters       |       |        |   |       |     |        |
| Value                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| Controller parameters |       |        |   |       |     |        |
| K                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| Exp. K                | 32767 | -32767 | 0 | 16384 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 385 |
| Max CPU cycles  | 470 |
| Avg CPU cycles  | 399 |

**Verification: Constant FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results          |       |        |   |       |     |        |
|-----------------------|-------|--------|---|-------|-----|--------|
| Time step             | 1     | 2      | 3 | 4     | ... | 7      |
| Mask parameters       |       |        |   |       |     |        |
| Value                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| Controller parameters |       |        |   |       |     |        |
| K                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| Exp. K                | 32767 | -32767 | 0 | 16384 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results          |       |        |   |       |     |        |
|-----------------------|-------|--------|---|-------|-----|--------|
| Time step             | 1     | 2      | 3 | 4     | ... | 7      |
| Mask parameters       |       |        |   |       |     |        |
| Value                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| Controller parameters |       |        |   |       |     |        |
| K                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| Exp. K                | 32767 | -32767 | 0 | 16384 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 661 |
| Max CPU cycles  | 665 |
| Avg CPU cycles  | 662 |

**Verification: Constant FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results          |            |             |     |             |
|-----------------------|------------|-------------|-----|-------------|
| Time step             | 1          | 2           | ... | 7           |
| Mask parameters       |            |             |     |             |
| Value                 | 1          | -1          | ... | -2.3        |
| Controller parameters |            |             |     |             |
| K                     | 2147483647 | -2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | -2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results          |            |             |     |             |
|-----------------------|------------|-------------|-----|-------------|
| Time step             | 1          | 2           | ... | 7           |
| Mask parameters       |            |             |     |             |
| Value                 | 1          | -1          | ... | -2.3        |
| Controller parameters |            |             |     |             |
| K                     | 2147483647 | -2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | -2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1018 |
| Max CPU cycles  | 1085 |
| Avg CPU cycles  | 1055 |

**Verification: Constant FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results                 |            |             |     |             |
|------------------------------|------------|-------------|-----|-------------|
| <b>Time step</b>             | 1          | 2           | ... | 7           |
| <i>Mask parameters</i>       |            |             |     |             |
| <b>Value</b>                 | 1          | -1          | ... | -2.3        |
| <i>Controller parameters</i> |            |             |     |             |
| <b>K</b>                     | 2147483647 | -2147483647 | ... | -2147483647 |
| <b>Exp. K</b>                | 2147483647 | -2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results                 |            |             |     |             |
|------------------------------|------------|-------------|-----|-------------|
| <b>Time step</b>             | 1          | 2           | ... | 7           |
| <i>Mask parameters</i>       |            |             |     |             |
| <b>Value</b>                 | 1          | -1          | ... | -2.3        |
| <i>Controller parameters</i> |            |             |     |             |
| <b>K</b>                     | 2147483647 | -2147483647 | ... | -2147483647 |
| <b>Exp. K</b>                | 2147483647 | -2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 457 |
| Max CPU cycles  | 485 |
| Avg CPU cycles  | 477 |

**Verification: Constant FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results                 |            |             |     |             |
|------------------------------|------------|-------------|-----|-------------|
| <b>Time step</b>             | 1          | 2           | ... | 7           |
| <i>Mask parameters</i>       |            |             |     |             |
| <b>Value</b>                 | 1          | -1          | ... | -2.3        |
| <i>Controller parameters</i> |            |             |     |             |
| <b>K</b>                     | 2147483647 | -2147483647 | ... | -2147483647 |
| <b>Exp. K</b>                | 2147483647 | -2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results                 |            |             |     |             |
|------------------------------|------------|-------------|-----|-------------|
| <b>Time step</b>             | 1          | 2           | ... | 7           |
| <i>Mask parameters</i>       |            |             |     |             |
| <b>Value</b>                 | 1          | -1          | ... | -2.3        |
| <i>Controller parameters</i> |            |             |     |             |
| <b>K</b>                     | 2147483647 | -2147483647 | ... | -2147483647 |
| <b>Exp. K</b>                | 2147483647 | -2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 924  |
| Max CPU cycles  | 1169 |
| Avg CPU cycles  | 1021 |



**Verification: Constant FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results                 |            |             |     |             |
|------------------------------|------------|-------------|-----|-------------|
| <b>Time step</b>             | 1          | 2           | ... | 7           |
| <i>Mask parameters</i>       |            |             |     |             |
| <b>Value</b>                 | 1          | -1          | ... | -2.3        |
| <i>Controller parameters</i> |            |             |     |             |
| <b>K</b>                     | 2147483647 | -2147483647 | ... | -2147483647 |
| <b>Exp. K</b>                | 2147483647 | -2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results                 |            |             |     |             |
|------------------------------|------------|-------------|-----|-------------|
| <b>Time step</b>             | 1          | 2           | ... | 7           |
| <i>Mask parameters</i>       |            |             |     |             |
| <b>Value</b>                 | 1          | -1          | ... | -2.3        |
| <i>Controller parameters</i> |            |             |     |             |
| <b>K</b>                     | 2147483647 | -2147483647 | ... | -2147483647 |
| <b>Exp. K</b>                | 2147483647 | -2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1819 |
| Max CPU cycles  | 2575 |
| Avg CPU cycles  | 2263 |

**Verification: Constant FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results          |            |             |     |             |
|-----------------------|------------|-------------|-----|-------------|
| Time step             | 1          | 2           | ... | 7           |
| Mask parameters       |            |             |     |             |
| Value                 | 1          | -1          | ... | -2.3        |
| Controller parameters |            |             |     |             |
| K                     | 2147483647 | -2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | -2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results          |            |             |     |             |
|-----------------------|------------|-------------|-----|-------------|
| Time step             | 1          | 2           | ... | 7           |
| Mask parameters       |            |             |     |             |
| Value                 | 1          | -1          | ... | -2.3        |
| Controller parameters |            |             |     |             |
| K                     | 2147483647 | -2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | -2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 729 |
| Max CPU cycles  | 922 |
| Avg CPU cycles  | 837 |

**Verification: Constant FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results                 |            |             |     |             |
|------------------------------|------------|-------------|-----|-------------|
| <b>Time step</b>             | 1          | 2           | ... | 7           |
| <i>Mask parameters</i>       |            |             |     |             |
| <b>Value</b>                 | 1          | -1          | ... | -2.3        |
| <i>Controller parameters</i> |            |             |     |             |
| <b>K</b>                     | 2147483647 | -2147483647 | ... | -2147483647 |
| <b>Exp. K</b>                | 2147483647 | -2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results                 |            |             |     |             |
|------------------------------|------------|-------------|-----|-------------|
| <b>Time step</b>             | 1          | 2           | ... | 7           |
| <i>Mask parameters</i>       |            |             |     |             |
| <b>Value</b>                 | 1          | -1          | ... | -2.3        |
| <i>Controller parameters</i> |            |             |     |             |
| <b>K</b>                     | 2147483647 | -2147483647 | ... | -2147483647 |
| <b>Exp. K</b>                | 2147483647 | -2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1155 |
| Max CPU cycles  | 1629 |
| Avg CPU cycles  | 1552 |

**Verification: Constant FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results                 |            |             |     |             |
|------------------------------|------------|-------------|-----|-------------|
| <b>Time step</b>             | 1          | 2           | ... | 7           |
| <i>Mask parameters</i>       |            |             |     |             |
| <b>Value</b>                 | 1          | -1          | ... | -2.3        |
| <i>Controller parameters</i> |            |             |     |             |
| <b>K</b>                     | 2147483647 | -2147483647 | ... | -2147483647 |
| <b>Exp. K</b>                | 2147483647 | -2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results                 |            |             |     |             |
|------------------------------|------------|-------------|-----|-------------|
| <b>Time step</b>             | 1          | 2           | ... | 7           |
| <i>Mask parameters</i>       |            |             |     |             |
| <b>Value</b>                 | 1          | -1          | ... | -2.3        |
| <i>Controller parameters</i> |            |             |     |             |
| <b>K</b>                     | 2147483647 | -2147483647 | ... | -2147483647 |
| <b>Exp. K</b>                | 2147483647 | -2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 670 |
| Max CPU cycles  | 806 |
| Avg CPU cycles  | 729 |

**Verification: Constant FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results          |            |             |     |             |
|-----------------------|------------|-------------|-----|-------------|
| Time step             | 1          | 2           | ... | 7           |
| Mask parameters       |            |             |     |             |
| Value                 | 1          | -1          | ... | -2.3        |
| Controller parameters |            |             |     |             |
| K                     | 2147483647 | -2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | -2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results          |            |             |     |             |
|-----------------------|------------|-------------|-----|-------------|
| Time step             | 1          | 2           | ... | 7           |
| Mask parameters       |            |             |     |             |
| Value                 | 1          | -1          | ... | -2.3        |
| Controller parameters |            |             |     |             |
| K                     | 2147483647 | -2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | -2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 800 |
| Max CPU cycles  | 846 |
| Avg CPU cycles  | 823 |

**Verification: Constant Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 5,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 819 |
| Max CPU cycles  | 836 |
| Avg CPU cycles  | 821 |

**Verification: Constant Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 5,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 401 |
| Max CPU cycles  | 401 |
| Avg CPU cycles  | 401 |

**Verification: Constant Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 5,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 471 |
| Max CPU cycles  | 471 |
| Avg CPU cycles  | 471 |



**Verification: Constant Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 5,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 673 |
| Max CPU cycles  | 752 |
| Avg CPU cycles  | 701 |

**Verification: Constant Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 5,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 279 |
| Max CPU cycles  | 280 |
| Avg CPU cycles  | 279 |

**Verification: Constant Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 5,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 527 |
| Max CPU cycles  | 868 |
| Avg CPU cycles  | 819 |

**Verification: Constant Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 5,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 397 |
| Max CPU cycles  | 444 |
| Avg CPU cycles  | 405 |

**Verification: Constant Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Conversion test****OK**

Conversion test for General block Constant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block Constant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 5,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 649 |
| Max CPU cycles  | 652 |
| Avg CPU cycles  | 649 |

## Block: Gain

---



Amplification of input by gain factor.

| Inports |       |
|---------|-------|
| In      | Input |

| Outports |                 |
|----------|-----------------|
| Out      | Amplified input |

| Mask Parameters |    |                                      |
|-----------------|----|--------------------------------------|
| Name            | ID | Description                          |
| Gain            | 1  | Gain factor in floating point format |

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | int8 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: Gain FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block Gain.

| Test results   |        |        |        |       |     |       |
|----------------|--------|--------|--------|-------|-----|-------|
| Time step      | 1      | 2      | 3      | 4     | ... | 9     |
| CPU cycles     | 76     | 76     | 76     | 76    | ... | 72    |
| Inputs         |        |        |        |       |     |       |
| In (DSP)       | -32768 | -16384 | -6554  | -3277 | ... | 32767 |
| In             | -1     | -0.5   | -0.2   | -0.1  | ... | 1     |
| Parameters     |        |        |        |       |     |       |
| Gain           | 2.2    |        |        |       |     |       |
| Outputs        |        |        |        |       |     |       |
| Out            | -1     | -1     | -0.44  | -0.22 | ... | 1     |
| Exp. Out       | -1     | -1     | -0.44  | -0.22 | ... | 1     |
| Out (DSP)      | -32767 | -32767 | -14419 | -7210 | ... | 32767 |
| Exp. Out (DSP) | -32768 | -32768 | -14418 | -7209 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 72 |
| Max CPU cycles  | 76 |
| Avg CPU cycles  | 75 |

**Test case: Parameter test****OK**

Parameter test for General block Gain.



| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 21    |
| CPU cycles     | 76     | 76     | 76     | 76     | ... | 72    |
| Inputs         |        |        |        |        |     |       |
| In (DSP)       | 3277   |        |        |        |     |       |
| In             | 0.1    |        |        |        |     |       |
| Parameters     |        |        |        |        |     |       |
| Gain           | -100   | -50    | -20    | -10    | ... | 100   |
| Outputs        |        |        |        |        |     |       |
| Out            | -1     | -1     | -1     | -1     | ... | 1     |
| Exp. Out       | -1     | -1     | -1     | -1     | ... | 1     |
| Out (DSP)      | -32767 | -32767 | -32767 | -32767 | ... | 32767 |
| Exp. Out (DSP) | -32768 | -32768 | -32768 | -32768 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 72 |
| Max CPU cycles  | 76 |
| Avg CPU cycles  | 75 |

### Test case: Conversion test

OK

Conversion test for General block Gain.

| Test results                 |        |        |        |        |     |       |
|------------------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |        |        |        |     |       |
| <b>Gain</b>                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| <i>Controller parameters</i> |        |        |        |        |     |       |
| <b>V</b>                     | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>sfr</b>                   | 11     | 11     | 11     | 11     | ... | 11    |
| <b>Exp. V</b>                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>Exp. sfr</b>              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block Gain.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| Time step             | 1      | 2      | 3      | 4      | ... | 37    |
| Mask parameters       |        |        |        |        |     |       |
| Gain                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| Controller parameters |        |        |        |        |     |       |
| V                     | -20480 | -19342 | -18204 | -17066 | ... | 20480 |
| sfr                   | 11     | 11     | 11     | 11     | ... | 11    |
| Exp. V                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| Exp. sfr              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1494 |
| Max CPU cycles  | 3602 |
| Avg CPU cycles  | 2854 |

**Verification: Gain FiP16 CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block Gain.

| Test results   |        |        |        |       |     |       |
|----------------|--------|--------|--------|-------|-----|-------|
| Time step      | 1      | 2      | 3      | 4     | ... | 9     |
| CPU cycles     | 41     | 41     | 39     | 39    | ... | 33    |
| Inputs         |        |        |        |       |     |       |
| In (DSP)       | -32768 | -16384 | -6554  | -3277 | ... | 32767 |
| In             | -1     | -0.5   | -0.2   | -0.1  | ... | 1     |
| Parameters     |        |        |        |       |     |       |
| Gain           | 2.2    |        |        |       |     |       |
| Outputs        |        |        |        |       |     |       |
| Out            | -1     | -1     | -0.44  | -0.22 | ... | 1     |
| Exp. Out       | -1     | -1     | -0.44  | -0.22 | ... | 1     |
| Out (DSP)      | -32767 | -32767 | -14419 | -7210 | ... | 32767 |
| Exp. Out (DSP) | -32768 | -32768 | -14418 | -7209 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 33 |
| Max CPU cycles  | 41 |
| Avg CPU cycles  | 38 |

**Test case: Parameter test****OK**

Parameter test for General block Gain.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 21    |
| CPU cycles     | 41     | 41     | 41     | 41     | ... | 33    |
| Inputs         |        |        |        |        |     |       |
| In (DSP)       | 3277   |        |        |        |     |       |
| In             | 0.1    |        |        |        |     |       |
| Parameters     |        |        |        |        |     |       |
| Gain           | -100   | -50    | -20    | -10    | ... | 100   |
| Outputs        |        |        |        |        |     |       |
| Out            | -1     | -1     | -1     | -1     | ... | 1     |
| Exp. Out       | -1     | -1     | -1     | -1     | ... | 1     |
| Out (DSP)      | -32767 | -32767 | -32767 | -32767 | ... | 32767 |
| Exp. Out (DSP) | -32768 | -32768 | -32768 | -32768 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 33 |
| Max CPU cycles  | 41 |
| Avg CPU cycles  | 38 |

### Test case: Conversion test

OK

Conversion test for General block Gain.

| Test results                 |        |        |        |        |     |       |
|------------------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |        |        |        |     |       |
| <b>Gain</b>                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| <i>Controller parameters</i> |        |        |        |        |     |       |
| <b>V</b>                     | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>sfr</b>                   | 11     | 11     | 11     | 11     | ... | 11    |
| <b>Exp. V</b>                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>Exp. sfr</b>              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block Gain.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| Time step             | 1      | 2      | 3      | 4      | ... | 37    |
| Mask parameters       |        |        |        |        |     |       |
| Gain                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| Controller parameters |        |        |        |        |     |       |
| V                     | -20480 | -19342 | -18204 | -17066 | ... | 20480 |
| sfr                   | 11     | 11     | 11     | 11     | ... | 11    |
| Exp. V                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| Exp. sfr              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 771  |
| Max CPU cycles  | 2031 |
| Avg CPU cycles  | 1585 |

**Verification: Gain FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block Gain.

| Test results   |        |        |        |       |     |       |
|----------------|--------|--------|--------|-------|-----|-------|
| Time step      | 1      | 2      | 3      | 4     | ... | 9     |
| CPU cycles     | 77     | 77     | 77     | 77    | ... | 77    |
| Inputs         |        |        |        |       |     |       |
| In (DSP)       | -32768 | -16384 | -6554  | -3277 | ... | 32767 |
| In             | -1     | -0.5   | -0.2   | -0.1  | ... | 1     |
| Parameters     |        |        |        |       |     |       |
| Gain           | 2.2    |        |        |       |     |       |
| Outputs        |        |        |        |       |     |       |
| Out            | -1     | -1     | -0.44  | -0.22 | ... | 1     |
| Exp. Out       | -1     | -1     | -0.44  | -0.22 | ... | 1     |
| Out (DSP)      | -32767 | -32767 | -14419 | -7210 | ... | 32767 |
| Exp. Out (DSP) | -32768 | -32768 | -14418 | -7209 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 77 |
| Max CPU cycles  | 77 |
| Avg CPU cycles  | 77 |

**Test case: Parameter test****OK**

Parameter test for General block Gain.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 21    |
| CPU cycles     | 77     | 77     | 77     | 77     | ... | 77    |
| Inputs         |        |        |        |        |     |       |
| In (DSP)       | 3277   |        |        |        |     |       |
| In             | 0.1    |        |        |        |     |       |
| Parameters     |        |        |        |        |     |       |
| Gain           | -100   | -50    | -20    | -10    | ... | 100   |
| Outputs        |        |        |        |        |     |       |
| Out            | -1     | -1     | -1     | -1     | ... | 1     |
| Exp. Out       | -1     | -1     | -1     | -1     | ... | 1     |
| Out (DSP)      | -32767 | -32767 | -32767 | -32767 | ... | 32767 |
| Exp. Out (DSP) | -32768 | -32768 | -32768 | -32768 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 77 |
| Max CPU cycles  | 77 |
| Avg CPU cycles  | 77 |

### Test case: Conversion test

OK

Conversion test for General block Gain.

| Test results                 |        |        |        |        |     |       |
|------------------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |        |        |        |     |       |
| <b>Gain</b>                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| <i>Controller parameters</i> |        |        |        |        |     |       |
| <b>V</b>                     | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>sfr</b>                   | 11     | 11     | 11     | 11     | ... | 11    |
| <b>Exp. V</b>                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>Exp. sfr</b>              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block Gain.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| Time step             | 1      | 2      | 3      | 4      | ... | 37    |
| Mask parameters       |        |        |        |        |     |       |
| Gain                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| Controller parameters |        |        |        |        |     |       |
| V                     | -20480 | -19342 | -18204 | -17066 | ... | 20480 |
| sfr                   | 11     | 11     | 11     | 11     | ... | 11    |
| Exp. V                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| Exp. sfr              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 948  |
| Max CPU cycles  | 1471 |
| Avg CPU cycles  | 1288 |



**Verification: Gain FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block Gain.

| Test results   |        |        |        |       |     |       |
|----------------|--------|--------|--------|-------|-----|-------|
| Time step      | 1      | 2      | 3      | 4     | ... | 9     |
| CPU cycles     | 66     | 66     | 67     | 67    | ... | 68    |
| Inputs         |        |        |        |       |     |       |
| In (DSP)       | -32768 | -16384 | -6554  | -3277 | ... | 32767 |
| In             | -1     | -0.5   | -0.2   | -0.1  | ... | 1     |
| Parameters     |        |        |        |       |     |       |
| Gain           | 2.2    |        |        |       |     |       |
| Outputs        |        |        |        |       |     |       |
| Out            | -1     | -1     | -0.44  | -0.22 | ... | 1     |
| Exp. Out       | -1     | -1     | -0.44  | -0.22 | ... | 1     |
| Out (DSP)      | -32767 | -32767 | -14419 | -7210 | ... | 32767 |
| Exp. Out (DSP) | -32768 | -32768 | -14418 | -7209 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 66 |
| Max CPU cycles  | 68 |
| Avg CPU cycles  | 67 |

**Test case: Parameter test****OK**

Parameter test for General block Gain.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 21    |
| CPU cycles     | 66     | 66     | 66     | 66     | ... | 68    |
| Inputs         |        |        |        |        |     |       |
| In (DSP)       | 3277   |        |        |        |     |       |
| In             | 0.1    |        |        |        |     |       |
| Parameters     |        |        |        |        |     |       |
| Gain           | -100   | -50    | -20    | -10    | ... | 100   |
| Outputs        |        |        |        |        |     |       |
| Out            | -1     | -1     | -1     | -1     | ... | 1     |
| Exp. Out       | -1     | -1     | -1     | -1     | ... | 1     |
| Out (DSP)      | -32767 | -32767 | -32767 | -32767 | ... | 32767 |
| Exp. Out (DSP) | -32768 | -32768 | -32768 | -32768 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 66 |
| Max CPU cycles  | 68 |
| Avg CPU cycles  | 67 |

### Test case: Conversion test

OK

Conversion test for General block Gain.

| Test results                 |        |        |        |        |     |       |
|------------------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |        |        |        |     |       |
| <b>Gain</b>                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| <i>Controller parameters</i> |        |        |        |        |     |       |
| <b>V</b>                     | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>sfr</b>                   | 11     | 11     | 11     | 11     | ... | 11    |
| <b>Exp. V</b>                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>Exp. sfr</b>              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block Gain.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| Time step             | 1      | 2      | 3      | 4      | ... | 37    |
| Mask parameters       |        |        |        |        |     |       |
| Gain                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| Controller parameters |        |        |        |        |     |       |
| V                     | -20480 | -19342 | -18204 | -17066 | ... | 20480 |
| sfr                   | 11     | 11     | 11     | 11     | ... | 11    |
| Exp. V                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| Exp. sfr              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1708 |
| Max CPU cycles  | 4701 |
| Avg CPU cycles  | 3713 |

**Verification: Gain FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block Gain.

| Test results   |        |        |        |       |     |       |
|----------------|--------|--------|--------|-------|-----|-------|
| Time step      | 1      | 2      | 3      | 4     | ... | 9     |
| CPU cycles     | 42     | 42     | 42     | 42    | ... | 42    |
| Inputs         |        |        |        |       |     |       |
| In (DSP)       | -32768 | -16384 | -6554  | -3277 | ... | 32767 |
| In             | -1     | -0.5   | -0.2   | -0.1  | ... | 1     |
| Parameters     |        |        |        |       |     |       |
| Gain           | 2.2    |        |        |       |     |       |
| Outputs        |        |        |        |       |     |       |
| Out            | -1     | -1     | -0.44  | -0.22 | ... | 1     |
| Exp. Out       | -1     | -1     | -0.44  | -0.22 | ... | 1     |
| Out (DSP)      | -32767 | -32767 | -14419 | -7210 | ... | 32767 |
| Exp. Out (DSP) | -32768 | -32768 | -14418 | -7209 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 42 |
| Max CPU cycles  | 42 |
| Avg CPU cycles  | 42 |

**Test case: Parameter test****OK**

Parameter test for General block Gain.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 21    |
| CPU cycles     | 42     | 42     | 42     | 42     | ... | 42    |
| Inputs         |        |        |        |        |     |       |
| In (DSP)       | 3277   |        |        |        |     |       |
| In             | 0.1    |        |        |        |     |       |
| Parameters     |        |        |        |        |     |       |
| Gain           | -100   | -50    | -20    | -10    | ... | 100   |
| Outputs        |        |        |        |        |     |       |
| Out            | -1     | -1     | -1     | -1     | ... | 1     |
| Exp. Out       | -1     | -1     | -1     | -1     | ... | 1     |
| Out (DSP)      | -32767 | -32767 | -32767 | -32767 | ... | 32767 |
| Exp. Out (DSP) | -32768 | -32768 | -32768 | -32768 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 42 |
| Max CPU cycles  | 42 |
| Avg CPU cycles  | 42 |

### Test case: Conversion test

OK

Conversion test for General block Gain.

| Test results                 |        |        |        |        |     |       |
|------------------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |        |        |        |     |       |
| <b>Gain</b>                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| <i>Controller parameters</i> |        |        |        |        |     |       |
| <b>V</b>                     | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>sfr</b>                   | 11     | 11     | 11     | 11     | ... | 11    |
| <b>Exp. V</b>                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>Exp. sfr</b>              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block Gain.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| Time step             | 1      | 2      | 3      | 4      | ... | 37    |
| Mask parameters       |        |        |        |        |     |       |
| Gain                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| Controller parameters |        |        |        |        |     |       |
| V                     | -20480 | -19342 | -18204 | -17066 | ... | 20480 |
| sfr                   | 11     | 11     | 11     | 11     | ... | 11    |
| Exp. V                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| Exp. sfr              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 815  |
| Max CPU cycles  | 1984 |
| Avg CPU cycles  | 1588 |

**Verification: Gain FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block Gain.

| Test results   |        |        |        |       |     |       |
|----------------|--------|--------|--------|-------|-----|-------|
| Time step      | 1      | 2      | 3      | 4     | ... | 9     |
| CPU cycles     | 68     | 68     | 69     | 69    | ... | 68    |
| Inputs         |        |        |        |       |     |       |
| In (DSP)       | -32768 | -16384 | -6554  | -3277 | ... | 32767 |
| In             | -1     | -0.5   | -0.2   | -0.1  | ... | 1     |
| Parameters     |        |        |        |       |     |       |
| Gain           | 2.2    |        |        |       |     |       |
| Outputs        |        |        |        |       |     |       |
| Out            | -1     | -1     | -0.44  | -0.22 | ... | 1     |
| Exp. Out       | -1     | -1     | -0.44  | -0.22 | ... | 1     |
| Out (DSP)      | -32767 | -32767 | -14419 | -7210 | ... | 32767 |
| Exp. Out (DSP) | -32768 | -32768 | -14418 | -7209 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 68 |
| Max CPU cycles  | 69 |
| Avg CPU cycles  | 68 |

**Test case: Parameter test****OK**

Parameter test for General block Gain.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 21    |
| CPU cycles     | 68     | 68     | 68     | 68     | ... | 68    |
| Inputs         |        |        |        |        |     |       |
| In (DSP)       | 3277   |        |        |        |     |       |
| In             | 0.1    |        |        |        |     |       |
| Parameters     |        |        |        |        |     |       |
| Gain           | -100   | -50    | -20    | -10    | ... | 100   |
| Outputs        |        |        |        |        |     |       |
| Out            | -1     | -1     | -1     | -1     | ... | 1     |
| Exp. Out       | -1     | -1     | -1     | -1     | ... | 1     |
| Out (DSP)      | -32767 | -32767 | -32767 | -32767 | ... | 32767 |
| Exp. Out (DSP) | -32768 | -32768 | -32768 | -32768 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 68 |
| Max CPU cycles  | 69 |
| Avg CPU cycles  | 68 |

### Test case: Conversion test

OK

Conversion test for General block Gain.

| Test results                 |        |        |        |        |     |       |
|------------------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |        |        |        |     |       |
| <b>Gain</b>                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| <i>Controller parameters</i> |        |        |        |        |     |       |
| <b>V</b>                     | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>sfr</b>                   | 11     | 11     | 11     | 11     | ... | 11    |
| <b>Exp. V</b>                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>Exp. sfr</b>              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |



**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block Gain.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| Time step             | 1      | 2      | 3      | 4      | ... | 37    |
| Mask parameters       |        |        |        |        |     |       |
| Gain                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| Controller parameters |        |        |        |        |     |       |
| V                     | -20480 | -19342 | -18204 | -17066 | ... | 20480 |
| sfr                   | 11     | 11     | 11     | 11     | ... | 11    |
| Exp. V                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| Exp. sfr              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 2593  |
| Max CPU cycles  | 10879 |
| Avg CPU cycles  | 8317  |

**Verification: Gain FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block Gain.

| Test results   |        |        |        |       |     |       |
|----------------|--------|--------|--------|-------|-----|-------|
| Time step      | 1      | 2      | 3      | 4     | ... | 9     |
| CPU cycles     | 86     | 77     | 77     | 77    | ... | 77    |
| Inputs         |        |        |        |       |     |       |
| In (DSP)       | -32768 | -16384 | -6554  | -3277 | ... | 32767 |
| In             | -1     | -0.5   | -0.2   | -0.1  | ... | 1     |
| Parameters     |        |        |        |       |     |       |
| Gain           | 2.2    |        |        |       |     |       |
| Outputs        |        |        |        |       |     |       |
| Out            | -1     | -1     | -0.44  | -0.22 | ... | 1     |
| Exp. Out       | -1     | -1     | -0.44  | -0.22 | ... | 1     |
| Out (DSP)      | -32767 | -32767 | -14419 | -7210 | ... | 32767 |
| Exp. Out (DSP) | -32768 | -32768 | -14418 | -7209 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 77 |
| Max CPU cycles  | 86 |
| Avg CPU cycles  | 78 |

**Test case: Parameter test****OK**

Parameter test for General block Gain.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 21    |
| CPU cycles     | 77     | 77     | 77     | 77     | ... | 77    |
| Inputs         |        |        |        |        |     |       |
| In (DSP)       | 3277   |        |        |        |     |       |
| In             | 0.1    |        |        |        |     |       |
| Parameters     |        |        |        |        |     |       |
| Gain           | -100   | -50    | -20    | -10    | ... | 100   |
| Outputs        |        |        |        |        |     |       |
| Out            | -1     | -1     | -1     | -1     | ... | 1     |
| Exp. Out       | -1     | -1     | -1     | -1     | ... | 1     |
| Out (DSP)      | -32767 | -32767 | -32767 | -32767 | ... | 32767 |
| Exp. Out (DSP) | -32768 | -32768 | -32768 | -32768 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 77 |
| Max CPU cycles  | 77 |
| Avg CPU cycles  | 77 |

### Test case: Conversion test

OK

Conversion test for General block Gain.

| Test results                 |        |        |        |        |     |       |
|------------------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |        |        |        |     |       |
| <b>Gain</b>                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| <i>Controller parameters</i> |        |        |        |        |     |       |
| <b>V</b>                     | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>sfr</b>                   | 11     | 11     | 11     | 11     | ... | 11    |
| <b>Exp. V</b>                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>Exp. sfr</b>              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block Gain.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| Time step             | 1      | 2      | 3      | 4      | ... | 37    |
| Mask parameters       |        |        |        |        |     |       |
| Gain                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| Controller parameters |        |        |        |        |     |       |
| V                     | -20480 | -19342 | -18204 | -17066 | ... | 20480 |
| sfr                   | 11     | 11     | 11     | 11     | ... | 11    |
| Exp. V                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| Exp. sfr              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 633  |
| Max CPU cycles  | 1281 |
| Avg CPU cycles  | 948  |

**Verification: Gain FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block Gain.

| Test results   |        |        |        |       |     |       |
|----------------|--------|--------|--------|-------|-----|-------|
| Time step      | 1      | 2      | 3      | 4     | ... | 9     |
| CPU cycles     | 60     | 60     | 60     | 60    | ... | 59    |
| Inputs         |        |        |        |       |     |       |
| In (DSP)       | -32768 | -16384 | -6554  | -3277 | ... | 32767 |
| In             | -1     | -0.5   | -0.2   | -0.1  | ... | 1     |
| Parameters     |        |        |        |       |     |       |
| Gain           | 2.2    |        |        |       |     |       |
| Outputs        |        |        |        |       |     |       |
| Out            | -1     | -1     | -0.44  | -0.22 | ... | 1     |
| Exp. Out       | -1     | -1     | -0.44  | -0.22 | ... | 1     |
| Out (DSP)      | -32767 | -32767 | -14419 | -7210 | ... | 32767 |
| Exp. Out (DSP) | -32768 | -32768 | -14418 | -7209 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 60 |
| Avg CPU cycles  | 59 |

**Test case: Parameter test****OK**

Parameter test for General block Gain.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 21    |
| CPU cycles     | 60     | 60     | 60     | 60     | ... | 59    |
| Inputs         |        |        |        |        |     |       |
| In (DSP)       | 3277   |        |        |        |     |       |
| In             | 0.1    |        |        |        |     |       |
| Parameters     |        |        |        |        |     |       |
| Gain           | -100   | -50    | -20    | -10    | ... | 100   |
| Outputs        |        |        |        |        |     |       |
| Out            | -1     | -1     | -1     | -1     | ... | 1     |
| Exp. Out       | -1     | -1     | -1     | -1     | ... | 1     |
| Out (DSP)      | -32767 | -32767 | -32767 | -32767 | ... | 32767 |
| Exp. Out (DSP) | -32768 | -32768 | -32768 | -32768 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 60 |
| Avg CPU cycles  | 59 |

### Test case: Conversion test

OK

Conversion test for General block Gain.

| Test results                 |        |        |        |        |     |       |
|------------------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |        |        |        |     |       |
| <b>Gain</b>                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| <i>Controller parameters</i> |        |        |        |        |     |       |
| <b>V</b>                     | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>sfr</b>                   | 11     | 11     | 11     | 11     | ... | 11    |
| <b>Exp. V</b>                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>Exp. sfr</b>              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block Gain.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| Time step             | 1      | 2      | 3      | 4      | ... | 37    |
| Mask parameters       |        |        |        |        |     |       |
| Gain                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| Controller parameters |        |        |        |        |     |       |
| V                     | -20480 | -19342 | -18204 | -17066 | ... | 20480 |
| sfr                   | 11     | 11     | 11     | 11     | ... | 11    |
| Exp. V                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| Exp. sfr              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1113 |
| Max CPU cycles  | 2817 |
| Avg CPU cycles  | 2222 |

**Verification: Gain FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block Gain.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 9          |
| CPU cycles     | 179         | 172         | ... | 124        |
| Inputs         |             |             |     |            |
| In (DSP)       | -2147483648 | -1073741824 | ... | 2147483647 |
| In             | -1          | -0.5        | ... | 1          |
| Parameters     |             |             |     |            |
| Gain           | 2.2         |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -1          | -1          | ... | 1          |
| Exp. Out       | -1          | -1          | ... | 1          |
| Out (DSP)      | -2147483647 | -2147483647 | ... | 2147483647 |
| Exp. Out (DSP) | -2147483648 | -2147483648 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 117 |
| Max CPU cycles  | 179 |
| Avg CPU cycles  | 158 |

**Test case: Parameter test****OK**

Parameter test for General block Gain.



| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 21         |
| CPU cycles     | 179         | 179         | ... | 124        |
| Inputs         |             |             |     |            |
| In (DSP)       | 214748365   |             |     |            |
| In             | 0.1         |             |     |            |
| Parameters     |             |             |     |            |
| Gain           | -100        | -50         | ... | 100        |
| Outputs        |             |             |     |            |
| Out            | -1          | -1          | ... | 1          |
| Exp. Out       | -1          | -1          | ... | 1          |
| Out (DSP)      | -2147483647 | -2147483647 | ... | 2147483647 |
| Exp. Out (DSP) | -2147483648 | -2147483648 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 117 |
| Max CPU cycles  | 179 |
| Avg CPU cycles  | 159 |

### Test case: Conversion test

OK

Conversion test for General block Gain.

| Test results                 |             |             |     |            |
|------------------------------|-------------|-------------|-----|------------|
| <b>Time step</b>             | 1           | 2           | ... | 37         |
| <i>Mask parameters</i>       |             |             |     |            |
| <b>Gain</b>                  | -10         | -9.444      | ... | 10         |
| <i>Controller parameters</i> |             |             |     |            |
| <b>V</b>                     | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>sfr</b>                   | 27          | 27          | ... | 27         |
| <b>Exp. V</b>                | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>Exp. sfr</b>              | 27          | 27          | ... | 27         |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block Gain.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Gain                  | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| V                     | -1342177280 | -1267611904 | ... | 1342177280 |
| sfr                   | 27          | 27          | ... | 27         |
| Exp. V                | -1342177280 | -1267611876 | ... | 1342177280 |
| Exp. sfr              | 27          | 27          | ... | 27         |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 7,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1646 |
| Max CPU cycles  | 3803 |
| Avg CPU cycles  | 3050 |

**Verification: Gain FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block Gain.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 9          |
| CPU cycles     | 85          | 85          | ... | 75         |
| Inputs         |             |             |     |            |
| In (DSP)       | -2147483648 | -1073741824 | ... | 2147483647 |
| In             | -1          | -0.5        | ... | 1          |
| Parameters     |             |             |     |            |
| Gain           | 2.2         |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -1          | -1          | ... | 1          |
| Exp. Out       | -1          | -1          | ... | 1          |
| Out (DSP)      | -2147483647 | -2147483647 | ... | 2147483647 |
| Exp. Out (DSP) | -2147483648 | -2147483648 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 75 |
| Max CPU cycles  | 85 |
| Avg CPU cycles  | 80 |

**Test case: Parameter test****OK**

Parameter test for General block Gain.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 21         |
| CPU cycles     | 85          | 85          | ... | 75         |
| Inputs         |             |             |     |            |
| In (DSP)       | 214748365   |             |     |            |
| In             | 0.1         |             |     |            |
| Parameters     |             |             |     |            |
| Gain           | -100        | -50         | ... | 100        |
| Outputs        |             |             |     |            |
| Out            | -1          | -1          | ... | 1          |
| Exp. Out       | -1          | -1          | ... | 1          |
| Out (DSP)      | -2147483647 | -2147483647 | ... | 2147483647 |
| Exp. Out (DSP) | -2147483648 | -2147483648 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 75 |
| Max CPU cycles  | 85 |
| Avg CPU cycles  | 80 |

### Test case: Conversion test

OK

Conversion test for General block Gain.

| Test results                 |             |             |     |            |
|------------------------------|-------------|-------------|-----|------------|
| <b>Time step</b>             | 1           | 2           | ... | 37         |
| <i>Mask parameters</i>       |             |             |     |            |
| <b>Gain</b>                  | -10         | -9.444      | ... | 10         |
| <i>Controller parameters</i> |             |             |     |            |
| <b>V</b>                     | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>sfr</b>                   | 27          | 27          | ... | 27         |
| <b>Exp. V</b>                | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>Exp. sfr</b>              | 27          | 27          | ... | 27         |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block Gain.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Gain                  | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| V                     | -1342177280 | -1267611904 | ... | 1342177280 |
| sfr                   | 27          | 27          | ... | 27         |
| Exp. V                | -1342177280 | -1267611876 | ... | 1342177280 |
| Exp. sfr              | 27          | 27          | ... | 27         |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 7,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 725  |
| Max CPU cycles  | 1629 |
| Avg CPU cycles  | 1322 |

**Verification: Gain FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block Gain.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 9          |
| CPU cycles     | 107         | 107         | ... | 107        |
| Inputs         |             |             |     |            |
| In (DSP)       | -2147483648 | -1073741824 | ... | 2147483647 |
| In             | -1          | -0.5        | ... | 1          |
| Parameters     |             |             |     |            |
| Gain           | 2.2         |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -1          | -1          | ... | 1          |
| Exp. Out       | -1          | -1          | ... | 1          |
| Out (DSP)      | -2147483647 | -2147483647 | ... | 2147483647 |
| Exp. Out (DSP) | -2147483648 | -2147483648 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 107 |
| Max CPU cycles  | 107 |
| Avg CPU cycles  | 107 |

**Test case: Parameter test****OK**

Parameter test for General block Gain.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 21         |
| CPU cycles     | 107         | 107         | ... | 107        |
| Inputs         |             |             |     |            |
| In (DSP)       | 214748365   |             |     |            |
| In             | 0.1         |             |     |            |
| Parameters     |             |             |     |            |
| Gain           | -100        | -50         | ... | 100        |
| Outputs        |             |             |     |            |
| Out            | -1          | -1          | ... | 1          |
| Exp. Out       | -1          | -1          | ... | 1          |
| Out (DSP)      | -2147483647 | -2147483647 | ... | 2147483647 |
| Exp. Out (DSP) | -2147483648 | -2147483648 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 107 |
| Max CPU cycles  | 107 |
| Avg CPU cycles  | 107 |

### Test case: Conversion test

OK

Conversion test for General block Gain.

| Test results                 |             |             |     |            |
|------------------------------|-------------|-------------|-----|------------|
| <b>Time step</b>             | 1           | 2           | ... | 37         |
| <i>Mask parameters</i>       |             |             |     |            |
| <b>Gain</b>                  | -10         | -9.444      | ... | 10         |
| <i>Controller parameters</i> |             |             |     |            |
| <b>V</b>                     | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>sfr</b>                   | 27          | 27          | ... | 27         |
| <b>Exp. V</b>                | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>Exp. sfr</b>              | 27          | 27          | ... | 27         |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block Gain.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Gain                  | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| V                     | -1342177280 | -1267611904 | ... | 1342177280 |
| sfr                   | 27          | 27          | ... | 27         |
| Exp. V                | -1342177280 | -1267611876 | ... | 1342177280 |
| Exp. sfr              | 27          | 27          | ... | 27         |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 7,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1300 |
| Max CPU cycles  | 1868 |
| Avg CPU cycles  | 1676 |



**Verification: Gain FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block Gain.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 9          |
| CPU cycles     | 162         | 168         | ... | 156        |
| Inputs         |             |             |     |            |
| In (DSP)       | -2147483648 | -1073741824 | ... | 2147483647 |
| In             | -1          | -0.5        | ... | 1          |
| Parameters     |             |             |     |            |
| Gain           | 2.2         |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -1          | -1          | ... | 1          |
| Exp. Out       | -1          | -1          | ... | 1          |
| Out (DSP)      | -2147483647 | -2147483647 | ... | 2147483647 |
| Exp. Out (DSP) | -2147483648 | -2147483648 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 156 |
| Max CPU cycles  | 170 |
| Avg CPU cycles  | 164 |

**Test case: Parameter test****OK**

Parameter test for General block Gain.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 21         |
| CPU cycles     | 162         | 162         | ... | 156        |
| Inputs         |             |             |     |            |
| In (DSP)       | 214748365   |             |     |            |
| In             | 0.1         |             |     |            |
| Parameters     |             |             |     |            |
| Gain           | -100        | -50         | ... | 100        |
| Outputs        |             |             |     |            |
| Out            | -1          | -1          | ... | 1          |
| Exp. Out       | -1          | -1          | ... | 1          |
| Out (DSP)      | -2147483647 | -2147483647 | ... | 2147483647 |
| Exp. Out (DSP) | -2147483648 | -2147483648 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 156 |
| Max CPU cycles  | 170 |
| Avg CPU cycles  | 163 |

### Test case: Conversion test

OK

Conversion test for General block Gain.

| Test results                 |             |             |     |            |
|------------------------------|-------------|-------------|-----|------------|
| <b>Time step</b>             | 1           | 2           | ... | 37         |
| <i>Mask parameters</i>       |             |             |     |            |
| <b>Gain</b>                  | -10         | -9.444      | ... | 10         |
| <i>Controller parameters</i> |             |             |     |            |
| <b>V</b>                     | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>sfr</b>                   | 27          | 27          | ... | 27         |
| <b>Exp. V</b>                | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>Exp. sfr</b>              | 27          | 27          | ... | 27         |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block Gain.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Gain                  | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| V                     | -1342177280 | -1267611904 | ... | 1342177280 |
| sfr                   | 27          | 27          | ... | 27         |
| Exp. V                | -1342177280 | -1267611876 | ... | 1342177280 |
| Exp. sfr              | 27          | 27          | ... | 27         |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 7,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2741 |
| Max CPU cycles  | 5965 |
| Avg CPU cycles  | 4976 |

**Verification: Gain FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block Gain.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 9          |
| CPU cycles     | 54          | 60          | ... | 54         |
| Inputs         |             |             |     |            |
| In (DSP)       | -2147483648 | -1073741824 | ... | 2147483647 |
| In             | -1          | -0.5        | ... | 1          |
| Parameters     |             |             |     |            |
| Gain           | 2.2         |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -1          | -1          | ... | 1          |
| Exp. Out       | -1          | -1          | ... | 1          |
| Out (DSP)      | -2147483647 | -2147483647 | ... | 2147483647 |
| Exp. Out (DSP) | -2147483648 | -2147483648 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 54 |
| Max CPU cycles  | 60 |
| Avg CPU cycles  | 57 |

**Test case: Parameter test****OK**

Parameter test for General block Gain.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 21         |
| CPU cycles     | 54          | 54          | ... | 54         |
| Inputs         |             |             |     |            |
| In (DSP)       | 214748365   |             |     |            |
| In             | 0.1         |             |     |            |
| Parameters     |             |             |     |            |
| Gain           | -100        | -50         | ... | 100        |
| Outputs        |             |             |     |            |
| Out            | -1          | -1          | ... | 1          |
| Exp. Out       | -1          | -1          | ... | 1          |
| Out (DSP)      | -2147483647 | -2147483647 | ... | 2147483647 |
| Exp. Out (DSP) | -2147483648 | -2147483648 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 54 |
| Max CPU cycles  | 60 |
| Avg CPU cycles  | 56 |

### Test case: Conversion test

OK

Conversion test for General block Gain.

| Test results                 |             |             |     |            |
|------------------------------|-------------|-------------|-----|------------|
| <b>Time step</b>             | 1           | 2           | ... | 37         |
| <i>Mask parameters</i>       |             |             |     |            |
| <b>Gain</b>                  | -10         | -9.444      | ... | 10         |
| <i>Controller parameters</i> |             |             |     |            |
| <b>V</b>                     | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>sfr</b>                   | 27          | 27          | ... | 27         |
| <b>Exp. V</b>                | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>Exp. sfr</b>              | 27          | 27          | ... | 27         |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block Gain.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Gain                  | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| V                     | -1342177280 | -1267611904 | ... | 1342177280 |
| sfr                   | 27          | 27          | ... | 27         |
| Exp. V                | -1342177280 | -1267611876 | ... | 1342177280 |
| Exp. sfr              | 27          | 27          | ... | 27         |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 7,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1271 |
| Max CPU cycles  | 2454 |
| Avg CPU cycles  | 2057 |

**Verification: Gain FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block Gain.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 9          |
| CPU cycles     | 474         | 474         | ... | 467        |
| Inputs         |             |             |     |            |
| In (DSP)       | -2147483648 | -1073741824 | ... | 2147483647 |
| In             | -1          | -0.5        | ... | 1          |
| Parameters     |             |             |     |            |
| Gain           | 2.2         |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -1          | -1          | ... | 1          |
| Exp. Out       | -1          | -1          | ... | 1          |
| Out (DSP)      | -2147483647 | -2147483647 | ... | 2147483647 |
| Exp. Out (DSP) | -2147483648 | -2147483648 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 466 |
| Max CPU cycles  | 474 |
| Avg CPU cycles  | 469 |

**Test case: Parameter test****OK**

Parameter test for General block Gain.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 21         |
| CPU cycles     | 424         | 434         | ... | 417        |
| Inputs         |             |             |     |            |
| In (DSP)       | 214748365   |             |     |            |
| In             | 0.1         |             |     |            |
| Parameters     |             |             |     |            |
| Gain           | -100        | -50         | ... | 100        |
| Outputs        |             |             |     |            |
| Out            | -1          | -1          | ... | 1          |
| Exp. Out       | -1          | -1          | ... | 1          |
| Out (DSP)      | -2147483647 | -2147483647 | ... | 2147483647 |
| Exp. Out (DSP) | -2147483648 | -2147483648 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 417 |
| Max CPU cycles  | 493 |
| Avg CPU cycles  | 463 |

### Test case: Conversion test

OK

Conversion test for General block Gain.

| Test results                 |             |             |     |            |
|------------------------------|-------------|-------------|-----|------------|
| <b>Time step</b>             | 1           | 2           | ... | 37         |
| <i>Mask parameters</i>       |             |             |     |            |
| <b>Gain</b>                  | -10         | -9.444      | ... | 10         |
| <i>Controller parameters</i> |             |             |     |            |
| <b>V</b>                     | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>sfr</b>                   | 27          | 27          | ... | 27         |
| <b>Exp. V</b>                | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>Exp. sfr</b>              | 27          | 27          | ... | 27         |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |



**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block Gain.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Gain                  | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| V                     | -1342177280 | -1267611904 | ... | 1342177280 |
| sfr                   | 27          | 27          | ... | 27         |
| Exp. V                | -1342177280 | -1267611876 | ... | 1342177280 |
| Exp. sfr              | 27          | 27          | ... | 27         |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 7,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 2999  |
| Max CPU cycles  | 11019 |
| Avg CPU cycles  | 8556  |

**Verification: Gain FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block Gain.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 9          |
| CPU cycles     | 122         | 100         | ... | 100        |
| Inputs         |             |             |     |            |
| In (DSP)       | -2147483648 | -1073741824 | ... | 2147483647 |
| In             | -1          | -0.5        | ... | 1          |
| Parameters     |             |             |     |            |
| Gain           | 2.2         |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -1          | -1          | ... | 1          |
| Exp. Out       | -1          | -1          | ... | 1          |
| Out (DSP)      | -2147483647 | -2147483647 | ... | 2147483647 |
| Exp. Out (DSP) | -2147483648 | -2147483648 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 100 |
| Max CPU cycles  | 122 |
| Avg CPU cycles  | 102 |

**Test case: Parameter test****OK**

Parameter test for General block Gain.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 21         |
| CPU cycles     | 100         | 100         | ... | 100        |
| Inputs         |             |             |     |            |
| In (DSP)       | 214748365   |             |     |            |
| In             | 0.1         |             |     |            |
| Parameters     |             |             |     |            |
| Gain           | -100        | -50         | ... | 100        |
| Outputs        |             |             |     |            |
| Out            | -1          | -1          | ... | 1          |
| Exp. Out       | -1          | -1          | ... | 1          |
| Out (DSP)      | -2147483647 | -2147483647 | ... | 2147483647 |
| Exp. Out (DSP) | -2147483648 | -2147483648 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 100 |
| Max CPU cycles  | 100 |
| Avg CPU cycles  | 100 |

### Test case: Conversion test

OK

Conversion test for General block Gain.

| Test results                 |             |             |     |            |
|------------------------------|-------------|-------------|-----|------------|
| <b>Time step</b>             | 1           | 2           | ... | 37         |
| <i>Mask parameters</i>       |             |             |     |            |
| <b>Gain</b>                  | -10         | -9.444      | ... | 10         |
| <i>Controller parameters</i> |             |             |     |            |
| <b>V</b>                     | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>sfr</b>                   | 27          | 27          | ... | 27         |
| <b>Exp. V</b>                | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>Exp. sfr</b>              | 27          | 27          | ... | 27         |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block Gain.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Gain                  | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| V                     | -1342177280 | -1267611904 | ... | 1342177280 |
| sfr                   | 27          | 27          | ... | 27         |
| Exp. V                | -1342177280 | -1267611876 | ... | 1342177280 |
| Exp. sfr              | 27          | 27          | ... | 27         |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 7,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 941  |
| Max CPU cycles  | 1559 |
| Avg CPU cycles  | 1263 |

**Verification: Gain FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block Gain.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 9          |
| CPU cycles     | 150         | 144         | ... | 103        |
| Inputs         |             |             |     |            |
| In (DSP)       | -2147483648 | -1073741824 | ... | 2147483647 |
| In             | -1          | -0.5        | ... | 1          |
| Parameters     |             |             |     |            |
| Gain           | 2.2         |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -1          | -1          | ... | 1          |
| Exp. Out       | -1          | -1          | ... | 1          |
| Out (DSP)      | -2147483647 | -2147483647 | ... | 2147483647 |
| Exp. Out (DSP) | -2147483648 | -2147483648 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 97  |
| Max CPU cycles  | 150 |
| Avg CPU cycles  | 130 |

**Test case: Parameter test****OK**

Parameter test for General block Gain.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 21         |
| CPU cycles     | 150         | 150         | ... | 103        |
| Inputs         |             |             |     |            |
| In (DSP)       | 214748365   |             |     |            |
| In             | 0.1         |             |     |            |
| Parameters     |             |             |     |            |
| Gain           | -100        | -50         | ... | 100        |
| Outputs        |             |             |     |            |
| Out            | -1          | -1          | ... | 1          |
| Exp. Out       | -1          | -1          | ... | 1          |
| Out (DSP)      | -2147483647 | -2147483647 | ... | 2147483647 |
| Exp. Out (DSP) | -2147483648 | -2147483648 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 97  |
| Max CPU cycles  | 150 |
| Avg CPU cycles  | 131 |

### Test case: Conversion test

OK

Conversion test for General block Gain.

| Test results                 |             |             |     |            |
|------------------------------|-------------|-------------|-----|------------|
| <b>Time step</b>             | 1           | 2           | ... | 37         |
| <i>Mask parameters</i>       |             |             |     |            |
| <b>Gain</b>                  | -10         | -9.444      | ... | 10         |
| <i>Controller parameters</i> |             |             |     |            |
| <b>V</b>                     | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>sfr</b>                   | 27          | 27          | ... | 27         |
| <b>Exp. V</b>                | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>Exp. sfr</b>              | 27          | 27          | ... | 27         |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block Gain.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Gain                  | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| V                     | -1342177280 | -1267611904 | ... | 1342177280 |
| sfr                   | 27          | 27          | ... | 27         |
| Exp. V                | -1342177280 | -1267611876 | ... | 1342177280 |
| Exp. sfr              | 27          | 27          | ... | 27         |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 7,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1227 |
| Max CPU cycles  | 2971 |
| Avg CPU cycles  | 2371 |

**Verification: Gain Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block Gain.

| Test results   |      |      |     |     |
|----------------|------|------|-----|-----|
| Time step      | 1    | 2    | ... | 9   |
| CPU cycles     | 58   | 58   | ... | 58  |
| Inputs         |      |      |     |     |
| In (DSP)       | -1   | -0.5 | ... | 1   |
| In             | -1   | -0.5 | ... | 1   |
| Parameters     |      |      |     |     |
| Gain           | 2.2  |      |     |     |
| Outputs        |      |      |     |     |
| Out            | -2.2 | -1.1 | ... | 2.2 |
| Exp. Out       | -2.2 | -1.1 | ... | 2.2 |
| Out (DSP)      | -2.2 | -1.1 | ... | 2.2 |
| Exp. Out (DSP) | -2.2 | -1.1 | ... | 2.2 |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 5,5879\text{e-}08$ ( $\pm 120$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 58 |
| Max CPU cycles  | 58 |
| Avg CPU cycles  | 58 |

**Test case: Parameter test****OK**

Parameter test for General block Gain.



| Test results   |      |     |     |     |
|----------------|------|-----|-----|-----|
| Time step      | 1    | 2   | ... | 21  |
| CPU cycles     | 58   | 58  | ... | 58  |
| Inputs         |      |     |     |     |
| In (DSP)       | 0.1  |     |     |     |
| In             | 0.1  |     |     |     |
| Parameters     |      |     |     |     |
| Gain           | -100 | -50 | ... | 100 |
| Outputs        |      |     |     |     |
| Out            | -10  | -5  | ... | 10  |
| Exp. Out       | -10  | -5  | ... | 10  |
| Out (DSP)      | -10  | -5  | ... | 10  |
| Exp. Out (DSP) | -10  | -5  | ... | 10  |

| Test settings |                                         |
|---------------|-----------------------------------------|
| Tolerance Out | $\pm 9,3132\text{e-}09$ ( $\pm 20$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 58 |
| Max CPU cycles  | 58 |
| Avg CPU cycles  | 58 |

#### Test case: Conversion test

OK

Conversion test for General block Gain.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Gain</b>                  | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>V</b>                     | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>                | -10 | -9.444 | ... | 10 |

| Test settings |                         |
|---------------|-------------------------|
| Tolerance V   | $\pm 0,0000\text{e}+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Gain.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Gain</b>                  | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>V</b>                     | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>                | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 821 |
| Max CPU cycles  | 838 |
| Avg CPU cycles  | 821 |

**Verification: Gain Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block Gain.

| Test results   |      |      |     |     |
|----------------|------|------|-----|-----|
| Time step      | 1    | 2    | ... | 9   |
| CPU cycles     | 27   | 27   | ... | 27  |
| Inputs         |      |      |     |     |
| In (DSP)       | -1   | -0.5 | ... | 1   |
| In             | -1   | -0.5 | ... | 1   |
| Parameters     |      |      |     |     |
| Gain           | 2.2  |      |     |     |
| Outputs        |      |      |     |     |
| Out            | -2.2 | -1.1 | ... | 2.2 |
| Exp. Out       | -2.2 | -1.1 | ... | 2.2 |
| Out (DSP)      | -2.2 | -1.1 | ... | 2.2 |
| Exp. Out (DSP) | -2.2 | -1.1 | ... | 2.2 |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 5,5879\text{e-}08$ ( $\pm 120$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 27 |
| Max CPU cycles  | 27 |
| Avg CPU cycles  | 27 |

**Test case: Parameter test****OK**

Parameter test for General block Gain.

| Test results   |      |     |     |     |
|----------------|------|-----|-----|-----|
| Time step      | 1    | 2   | ... | 21  |
| CPU cycles     | 27   | 27  | ... | 27  |
| Inputs         |      |     |     |     |
| In (DSP)       | 0.1  |     |     |     |
| In             | 0.1  |     |     |     |
| Parameters     |      |     |     |     |
| Gain           | -100 | -50 | ... | 100 |
| Outputs        |      |     |     |     |
| Out            | -10  | -5  | ... | 10  |
| Exp. Out       | -10  | -5  | ... | 10  |
| Out (DSP)      | -10  | -5  | ... | 10  |
| Exp. Out (DSP) | -10  | -5  | ... | 10  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 9,3132e-09$ ( $\pm 20$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 27 |
| Max CPU cycles  | 27 |
| Avg CPU cycles  | 27 |

#### Test case: Conversion test

OK

Conversion test for General block Gain.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Gain</b>                  | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>V</b>                     | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>                | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Gain.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Gain</b>                  | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>V</b>                     | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>                | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 397 |
| Max CPU cycles  | 397 |
| Avg CPU cycles  | 397 |

**Verification: Gain Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block Gain.

| Test results   |      |      |     |     |
|----------------|------|------|-----|-----|
| Time step      | 1    | 2    | ... | 9   |
| CPU cycles     | 62   | 62   | ... | 62  |
| Inputs         |      |      |     |     |
| In (DSP)       | -1   | -0.5 | ... | 1   |
| In             | -1   | -0.5 | ... | 1   |
| Parameters     |      |      |     |     |
| Gain           | 2.2  |      |     |     |
| Outputs        |      |      |     |     |
| Out            | -2.2 | -1.1 | ... | 2.2 |
| Exp. Out       | -2.2 | -1.1 | ... | 2.2 |
| Out (DSP)      | -2.2 | -1.1 | ... | 2.2 |
| Exp. Out (DSP) | -2.2 | -1.1 | ... | 2.2 |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 5,5879\text{e-}08$ ( $\pm 120$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 62 |
| Avg CPU cycles  | 62 |

**Test case: Parameter test****OK**

Parameter test for General block Gain.

| Test results   |      |     |     |     |
|----------------|------|-----|-----|-----|
| Time step      | 1    | 2   | ... | 21  |
| CPU cycles     | 62   | 62  | ... | 62  |
| Inputs         |      |     |     |     |
| In (DSP)       | 0.1  |     |     |     |
| In             | 0.1  |     |     |     |
| Parameters     |      |     |     |     |
| Gain           | -100 | -50 | ... | 100 |
| Outputs        |      |     |     |     |
| Out            | -10  | -5  | ... | 10  |
| Exp. Out       | -10  | -5  | ... | 10  |
| Out (DSP)      | -10  | -5  | ... | 10  |
| Exp. Out (DSP) | -10  | -5  | ... | 10  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 9,3132e-09$ ( $\pm 20$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 62 |
| Avg CPU cycles  | 62 |

#### Test case: Conversion test

OK

Conversion test for General block Gain.

| Test results          |     |        |     |    |
|-----------------------|-----|--------|-----|----|
| <b>Time step</b>      | 1   | 2      | ... | 37 |
| Mask parameters       |     |        |     |    |
| <b>Gain</b>           | -10 | -9.444 | ... | 10 |
| Controller parameters |     |        |     |    |
| <b>V</b>              | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>         | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Gain.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Gain</b>                  | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>V</b>                     | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>                | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 467 |
| Max CPU cycles  | 467 |
| Avg CPU cycles  | 467 |



**Verification: Gain Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block Gain.

| Test results   |      |      |     |     |
|----------------|------|------|-----|-----|
| Time step      | 1    | 2    | ... | 9   |
| CPU cycles     | 228  | 228  | ... | 228 |
| Inputs         |      |      |     |     |
| In (DSP)       | -1   | -0.5 | ... | 1   |
| In             | -1   | -0.5 | ... | 1   |
| Parameters     |      |      |     |     |
| Gain           | 2.2  |      |     |     |
| Outputs        |      |      |     |     |
| Out            | -2.2 | -1.1 | ... | 2.2 |
| Exp. Out       | -2.2 | -1.1 | ... | 2.2 |
| Out (DSP)      | -2.2 | -1.1 | ... | 2.2 |
| Exp. Out (DSP) | -2.2 | -1.1 | ... | 2.2 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 5,5879e-08$ ( $\pm 120$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 170 |
| Max CPU cycles  | 229 |
| Avg CPU cycles  | 222 |

**Test case: Parameter test****OK**

Parameter test for General block Gain.

| Test results   |      |     |     |     |
|----------------|------|-----|-----|-----|
| Time step      | 1    | 2   | ... | 21  |
| CPU cycles     | 225  | 225 | ... | 225 |
| Inputs         |      |     |     |     |
| In (DSP)       | 0.1  |     |     |     |
| In             | 0.1  |     |     |     |
| Parameters     |      |     |     |     |
| Gain           | -100 | -50 | ... | 100 |
| Outputs        |      |     |     |     |
| Out            | -10  | -5  | ... | 10  |
| Exp. Out       | -10  | -5  | ... | 10  |
| Out (DSP)      | -10  | -5  | ... | 10  |
| Exp. Out (DSP) | -10  | -5  | ... | 10  |

| Test settings |                                         |
|---------------|-----------------------------------------|
| Tolerance Out | $\pm 9,3132\text{e-}09$ ( $\pm 20$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 174 |
| Max CPU cycles  | 228 |
| Avg CPU cycles  | 223 |

#### Test case: Conversion test

OK

Conversion test for General block Gain.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Gain</b>                  | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>V</b>                     | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>                | -10 | -9.444 | ... | 10 |

| Test settings |                         |
|---------------|-------------------------|
| Tolerance V   | $\pm 0,0000\text{e}+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Gain.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Gain</b>                  | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>V</b>                     | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>                | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 667 |
| Max CPU cycles  | 696 |
| Avg CPU cycles  | 694 |

**Verification: Gain Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block Gain.

| Test results   |      |      |     |     |
|----------------|------|------|-----|-----|
| Time step      | 1    | 2    | ... | 9   |
| CPU cycles     | 89   | 89   | ... | 89  |
| Inputs         |      |      |     |     |
| In (DSP)       | -1   | -0.5 | ... | 1   |
| In             | -1   | -0.5 | ... | 1   |
| Parameters     |      |      |     |     |
| Gain           | 2.2  |      |     |     |
| Outputs        |      |      |     |     |
| Out            | -2.2 | -1.1 | ... | 2.2 |
| Exp. Out       | -2.2 | -1.1 | ... | 2.2 |
| Out (DSP)      | -2.2 | -1.1 | ... | 2.2 |
| Exp. Out (DSP) | -2.2 | -1.1 | ... | 2.2 |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 5,5879\text{e-}08$ ( $\pm 120$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 71 |
| Max CPU cycles  | 90 |
| Avg CPU cycles  | 87 |

**Test case: Parameter test****OK**

Parameter test for General block Gain.

| Test results   |      |     |     |     |
|----------------|------|-----|-----|-----|
| Time step      | 1    | 2   | ... | 21  |
| CPU cycles     | 87   | 87  | ... | 87  |
| Inputs         |      |     |     |     |
| In (DSP)       | 0.1  |     |     |     |
| In             | 0.1  |     |     |     |
| Parameters     |      |     |     |     |
| Gain           | -100 | -50 | ... | 100 |
| Outputs        |      |     |     |     |
| Out            | -10  | -5  | ... | 10  |
| Exp. Out       | -10  | -5  | ... | 10  |
| Out (DSP)      | -10  | -5  | ... | 10  |
| Exp. Out (DSP) | -10  | -5  | ... | 10  |

| Test settings |                                         |
|---------------|-----------------------------------------|
| Tolerance Out | $\pm 9,3132\text{e-}09$ ( $\pm 20$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 70 |
| Max CPU cycles  | 89 |
| Avg CPU cycles  | 86 |

#### Test case: Conversion test

OK

Conversion test for General block Gain.

| Test results          |     |        |     |    |
|-----------------------|-----|--------|-----|----|
| Time step             | 1   | 2      | ... | 37 |
| Mask parameters       |     |        |     |    |
| Gain                  | -10 | -9.444 | ... | 10 |
| Controller parameters |     |        |     |    |
| V                     | -10 | -9.444 | ... | 10 |
| Exp. V                | -10 | -9.444 | ... | 10 |

| Test settings |                         |
|---------------|-------------------------|
| Tolerance V   | $\pm 0,0000\text{e}+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Gain.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Gain</b>                  | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>V</b>                     | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>                | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 277 |
| Max CPU cycles  | 278 |
| Avg CPU cycles  | 277 |

**Verification: Gain Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block Gain.

| Test results   |      |      |     |     |
|----------------|------|------|-----|-----|
| Time step      | 1    | 2    | ... | 9   |
| CPU cycles     | 195  | 195  | ... | 195 |
| Inputs         |      |      |     |     |
| In (DSP)       | -1   | -0.5 | ... | 1   |
| In             | -1   | -0.5 | ... | 1   |
| Parameters     |      |      |     |     |
| Gain           | 2.2  |      |     |     |
| Outputs        |      |      |     |     |
| Out            | -2.2 | -1.1 | ... | 2.2 |
| Exp. Out       | -2.2 | -1.1 | ... | 2.2 |
| Out (DSP)      | -2.2 | -1.1 | ... | 2.2 |
| Exp. Out (DSP) | -2.2 | -1.1 | ... | 2.2 |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 5,5879\text{e-}08$ ( $\pm 120$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 149 |
| Max CPU cycles  | 197 |
| Avg CPU cycles  | 190 |

**Test case: Parameter test****OK**

Parameter test for General block Gain.

| Test results   |      |     |     |     |
|----------------|------|-----|-----|-----|
| Time step      | 1    | 2   | ... | 21  |
| CPU cycles     | 192  | 192 | ... | 192 |
| Inputs         |      |     |     |     |
| In (DSP)       | 0.1  |     |     |     |
| In             | 0.1  |     |     |     |
| Parameters     |      |     |     |     |
| Gain           | -100 | -50 | ... | 100 |
| Outputs        |      |     |     |     |
| Out            | -10  | -5  | ... | 10  |
| Exp. Out       | -10  | -5  | ... | 10  |
| Out (DSP)      | -10  | -5  | ... | 10  |
| Exp. Out (DSP) | -10  | -5  | ... | 10  |

| Test settings |                                         |
|---------------|-----------------------------------------|
| Tolerance Out | $\pm 9,3132\text{e-}09$ ( $\pm 20$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 149 |
| Max CPU cycles  | 196 |
| Avg CPU cycles  | 191 |

#### Test case: Conversion test

OK

Conversion test for General block Gain.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Gain</b>                  | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>V</b>                     | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>                | -10 | -9.444 | ... | 10 |

| Test settings |                         |
|---------------|-------------------------|
| Tolerance V   | $\pm 0,0000\text{e}+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Gain.



| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Gain</b>                  | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>V</b>                     | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>                | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 523 |
| Max CPU cycles  | 868 |
| Avg CPU cycles  | 856 |

**Verification: Gain Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block Gain.

| Test results   |      |      |     |     |
|----------------|------|------|-----|-----|
| Time step      | 1    | 2    | ... | 9   |
| CPU cycles     | 68   | 56   | ... | 56  |
| Inputs         |      |      |     |     |
| In (DSP)       | -1   | -0.5 | ... | 1   |
| In             | -1   | -0.5 | ... | 1   |
| Parameters     |      |      |     |     |
| Gain           | 2.2  |      |     |     |
| Outputs        |      |      |     |     |
| Out            | -2.2 | -1.1 | ... | 2.2 |
| Exp. Out       | -2.2 | -1.1 | ... | 2.2 |
| Out (DSP)      | -2.2 | -1.1 | ... | 2.2 |
| Exp. Out (DSP) | -2.2 | -1.1 | ... | 2.2 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 5,5879e-08$ ( $\pm 120$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 68 |
| Avg CPU cycles  | 57 |

**Test case: Parameter test****OK**

Parameter test for General block Gain.

| Test results   |      |     |     |     |
|----------------|------|-----|-----|-----|
| Time step      | 1    | 2   | ... | 21  |
| CPU cycles     | 56   | 56  | ... | 56  |
| Inputs         |      |     |     |     |
| In (DSP)       | 0.1  |     |     |     |
| In             | 0.1  |     |     |     |
| Parameters     |      |     |     |     |
| Gain           | -100 | -50 | ... | 100 |
| Outputs        |      |     |     |     |
| Out            | -10  | -5  | ... | 10  |
| Exp. Out       | -10  | -5  | ... | 10  |
| Out (DSP)      | -10  | -5  | ... | 10  |
| Exp. Out (DSP) | -10  | -5  | ... | 10  |

| Test settings |                                         |
|---------------|-----------------------------------------|
| Tolerance Out | $\pm 9,3132\text{e-}09$ ( $\pm 20$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 56 |
| Avg CPU cycles  | 56 |

#### Test case: Conversion test

OK

Conversion test for General block Gain.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Gain</b>                  | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>V</b>                     | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>                | -10 | -9.444 | ... | 10 |

| Test settings |                         |
|---------------|-------------------------|
| Tolerance V   | $\pm 0,0000\text{e+}00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Gain.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Gain</b>                  | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>V</b>                     | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>                | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 385 |
| Max CPU cycles  | 437 |
| Avg CPU cycles  | 386 |

**Verification: Gain Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block Gain.

| Test results   |      |      |     |     |
|----------------|------|------|-----|-----|
| Time step      | 1    | 2    | ... | 9   |
| CPU cycles     | 44   | 44   | ... | 44  |
| Inputs         |      |      |     |     |
| In (DSP)       | -1   | -0.5 | ... | 1   |
| In             | -1   | -0.5 | ... | 1   |
| Parameters     |      |      |     |     |
| Gain           | 2.2  |      |     |     |
| Outputs        |      |      |     |     |
| Out            | -2.2 | -1.1 | ... | 2.2 |
| Exp. Out       | -2.2 | -1.1 | ... | 2.2 |
| Out (DSP)      | -2.2 | -1.1 | ... | 2.2 |
| Exp. Out (DSP) | -2.2 | -1.1 | ... | 2.2 |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 5,5879\text{e-}08$ ( $\pm 120$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 44 |
| Max CPU cycles  | 44 |
| Avg CPU cycles  | 44 |

**Test case: Parameter test****OK**

Parameter test for General block Gain.

| Test results   |      |     |     |     |
|----------------|------|-----|-----|-----|
| Time step      | 1    | 2   | ... | 21  |
| CPU cycles     | 44   | 44  | ... | 44  |
| Inputs         |      |     |     |     |
| In (DSP)       | 0.1  |     |     |     |
| In             | 0.1  |     |     |     |
| Parameters     |      |     |     |     |
| Gain           | -100 | -50 | ... | 100 |
| Outputs        |      |     |     |     |
| Out            | -10  | -5  | ... | 10  |
| Exp. Out       | -10  | -5  | ... | 10  |
| Out (DSP)      | -10  | -5  | ... | 10  |
| Exp. Out (DSP) | -10  | -5  | ... | 10  |

| Test settings |                                         |
|---------------|-----------------------------------------|
| Tolerance Out | $\pm 9,3132\text{e-}09$ ( $\pm 20$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 44 |
| Max CPU cycles  | 44 |
| Avg CPU cycles  | 44 |

#### Test case: Conversion test

OK

Conversion test for General block Gain.

| Test results          |     |        |     |    |
|-----------------------|-----|--------|-----|----|
| <b>Time step</b>      | 1   | 2      | ... | 37 |
| Mask parameters       |     |        |     |    |
| <b>Gain</b>           | -10 | -9.444 | ... | 10 |
| Controller parameters |     |        |     |    |
| <b>V</b>              | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>         | -10 | -9.444 | ... | 10 |

| Test settings |                         |
|---------------|-------------------------|
| Tolerance V   | $\pm 0,0000\text{e}+00$ |

#### Test case: Conversion-on-Target test

OK


Conversion-on-Target test for General block Gain.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Gain</b>                  | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>V</b>                     | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>                | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 1,0000e-06$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 637 |
| Max CPU cycles  | 640 |
| Avg CPU cycles  | 637 |

## Block: Inport




| Inports |                           |
|---------|---------------------------|
| IN      | Signal from frame program |

| Mask Parameters |                                                                 |
|-----------------|-----------------------------------------------------------------|
| ts_fact         | Multiplication factor of base sampling time (in integer format) |
| Gain            | Gain value used in simulation                                   |
| Offset          | Offset value used in simulation                                 |

### Description:

Serves as interface to the frame program. The input of this block is intended for simulation purposes and can be left unconnected if not used. Also the parameters *Gain* and *Offset* are only used during simulation. The schematic for simulation can be seen in the figure below.

**Note:** Currently, *Gain* and *Offset* parameters are only available in Matlab/Simulink.




### Data Types:

|                |                       |
|----------------|-----------------------|
| <b>bool</b>    | Boolean               |
| <b>int8</b>    | 8 Bit Fixed Point     |
| <b>int16</b>   | 16 Bit Fixed Point    |
| <b>int32</b>   | 32 Bit Fixed Point    |
| <b>float32</b> | 32 Bit Floating Point |
| <b>float64</b> | 64 Bit Floating Point |



## Block: Int2Real

---



Conversion block from integer (fixed point) datatypes to real (floating point) datatypes.

$\text{Out} = \text{In} * \text{Scale}$

| Inports |               |
|---------|---------------|
| In      | Integer input |

| Outports |             |
|----------|-------------|
| Out      | Real output |

| Mask Parameters |    |                                     |
|-----------------|----|-------------------------------------|
| Name            | ID | Description                         |
| Scale           | 1  | Scaling factor from integer to real |

### Implementations:

|                      |                                                            |
|----------------------|------------------------------------------------------------|
| <b>FiP8_Float32</b>  | 8 Bit Fixed Point to 32 Bit Floating Point Implementation  |
| <b>FiP16_Float32</b> | 16 Bit Fixed Point to 32 Bit Floating Point Implementation |
| <b>FiP32_Float32</b> | 32 Bit Fixed Point to 32 Bit Floating Point Implementation |
| <b>FiP8_Float64</b>  | 8 Bit Fixed Point to 64 Bit Floating Point Implementation  |
| <b>FiP16_Float64</b> | 16 Bit Fixed Point to 64 Bit Floating Point Implementation |
| <b>FiP32_Float64</b> | 32 Bit Fixed Point to 64 Bit Floating Point Implementation |
| <b>Bool_Float32</b>  | Boolean to 32 Bit Floating Point Implementation            |
| <b>Bool_Float64</b>  | Boolean to 64 Bit Floating Point Implementation            |

### Implementation: FiP8\_Float32

---

8 Bit Fixed Point to 32 Bit Floating Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | int8 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: FiP16\_Float32

---

16 Bit Fixed Point to 32 Bit Floating Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: FiP32\_Float32

32 Bit Fixed Point to 32 Bit Floating Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: FiP8\_Float64

8 Bit Fixed Point to 64 Bit Floating Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | int8 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

### Implementation: FiP16\_Float64

16 Bit Fixed Point to 64 Bit Floating Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

### Implementation: FiP32\_Float64

32 Bit Fixed Point to 64 Bit Floating Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

### Implementation: Bool\_Float32

Boolean to 32 Bit Floating Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | bool |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Bool\_Float64

Boolean to 64 Bit Floating Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | bool |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: Int2Real FiP16\_Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block Int2Real.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 113   |
| CPU cycles     | 59     | 59     | ... | 59    |
| Inputs         |        |        |     |       |
| In (DSP)       | -32768 | -32183 | ... | 32767 |
| In             | -1     | -0.982 | ... | 1     |
| Parameters     |        |        |     |       |
| Scale          | 7.3    |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -7.3   | -7.17  | ... | 7.3   |
| Exp. Out       | -7.3   | -7.17  | ... | 7.3   |
| Out (DSP)      | -7.3   | -7.17  | ... | 7.3   |
| Exp. Out (DSP) | -7.3   | -7.17  | ... | 7.3   |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 655360$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 59 |
| Avg CPU cycles  | 59 |

**Test case: Parameter test****OK**

Parameter test for General block Int2Real.

| Test results   |      |      |     |    |
|----------------|------|------|-----|----|
| Time step      | 1    | 2    | ... | 15 |
| CPU cycles     | 59   | 59   | ... | 59 |
| Inputs         |      |      |     |    |
| In (DSP)       | 3277 |      |     |    |
| In             | 0.1  |      |     |    |
| Parameters     |      |      |     |    |
| Scale          | -10  | -5   | ... | 10 |
| Outputs        |      |      |     |    |
| Out            | -1   | -0.5 | ... | 1  |
| Exp. Out       | -1   | -0.5 | ... | 1  |
| Out (DSP)      | -1   | -0.5 | ... | 1  |
| Exp. Out (DSP) | -1   | -0.5 | ... | 1  |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 131072$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 59 |
| Avg CPU cycles  | 59 |

#### Test case: Conversion test

OK

Conversion test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| Time step             | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| Scale                 | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| scale                 | -0  | -0 | ... | 0  |
| Exp. scale            | -0  | -0 | ... | 0  |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| <b>Time step</b>      | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| <b>Scale</b>          | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| <b>scale</b>          | -0  | -0 | ... | 0  |
| <b>Exp. scale</b>     | -0  | -0 | ... | 0  |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 3,0000e-09$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 948  |
| Max CPU cycles  | 1082 |
| Avg CPU cycles  | 1073 |

**Verification: Int2Real FiP16\_Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block Int2Real.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 113   |
| CPU cycles     | 29     | 29     | ... | 29    |
| Inputs         |        |        |     |       |
| In (DSP)       | -32768 | -32183 | ... | 32767 |
| In             | -1     | -0.982 | ... | 1     |
| Parameters     |        |        |     |       |
| Scale          | 7.3    |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -7.3   | -7.17  | ... | 7.3   |
| Exp. Out       | -7.3   | -7.17  | ... | 7.3   |
| Out (DSP)      | -7.3   | -7.17  | ... | 7.3   |
| Exp. Out (DSP) | -7.3   | -7.17  | ... | 7.3   |

| Test settings |                                             |
|---------------|---------------------------------------------|
| Tolerance Out | $\pm 3,0518\text{e-}04$ ( $\pm 655360$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 29 |
| Avg CPU cycles  | 29 |

**Test case: Parameter test****OK**

Parameter test for General block Int2Real.

| Test results   |      |      |     |    |
|----------------|------|------|-----|----|
| Time step      | 1    | 2    | ... | 15 |
| CPU cycles     | 29   | 29   | ... | 29 |
| Inputs         |      |      |     |    |
| In (DSP)       | 3277 |      |     |    |
| In             | 0.1  |      |     |    |
| Parameters     |      |      |     |    |
| Scale          | -10  | -5   | ... | 10 |
| Outputs        |      |      |     |    |
| Out            | -1   | -0.5 | ... | 1  |
| Exp. Out       | -1   | -0.5 | ... | 1  |
| Out (DSP)      | -1   | -0.5 | ... | 1  |
| Exp. Out (DSP) | -1   | -0.5 | ... | 1  |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 131072$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 29 |
| Avg CPU cycles  | 29 |

#### Test case: Conversion test

OK

Conversion test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| <b>Time step</b>      | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| <b>Scale</b>          | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| <b>scale</b>          | -0  | -0 | ... | 0  |
| <b>Exp. scale</b>     | -0  | -0 | ... | 0  |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Int2Real.



| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| <b>Time step</b>      | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| <b>Scale</b>          | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| <b>scale</b>          | -0  | -0 | ... | 0  |
| <b>Exp. scale</b>     | -0  | -0 | ... | 0  |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 3,0000e-09$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 467 |
| Max CPU cycles  | 515 |
| Avg CPU cycles  | 511 |

**Verification: Int2Real FiP16\_Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block Int2Real.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 113   |
| CPU cycles     | 67     | 67     | ... | 67    |
| Inputs         |        |        |     |       |
| In (DSP)       | -32768 | -32183 | ... | 32767 |
| In             | -1     | -0.982 | ... | 1     |
| Parameters     |        |        |     |       |
| Scale          | 7.3    |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -7.3   | -7.17  | ... | 7.3   |
| Exp. Out       | -7.3   | -7.17  | ... | 7.3   |
| Out (DSP)      | -7.3   | -7.17  | ... | 7.3   |
| Exp. Out (DSP) | -7.3   | -7.17  | ... | 7.3   |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 655360$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 67 |
| Max CPU cycles  | 67 |
| Avg CPU cycles  | 67 |

**Test case: Parameter test****OK**

Parameter test for General block Int2Real.

| Test results   |      |      |     |    |
|----------------|------|------|-----|----|
| Time step      | 1    | 2    | ... | 15 |
| CPU cycles     | 67   | 67   | ... | 67 |
| Inputs         |      |      |     |    |
| In (DSP)       | 3277 |      |     |    |
| In             | 0.1  |      |     |    |
| Parameters     |      |      |     |    |
| Scale          | -10  | -5   | ... | 10 |
| Outputs        |      |      |     |    |
| Out            | -1   | -0.5 | ... | 1  |
| Exp. Out       | -1   | -0.5 | ... | 1  |
| Out (DSP)      | -1   | -0.5 | ... | 1  |
| Exp. Out (DSP) | -1   | -0.5 | ... | 1  |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 131072$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 67 |
| Max CPU cycles  | 67 |
| Avg CPU cycles  | 67 |

#### Test case: Conversion test

OK

Conversion test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| Time step             | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| Scale                 | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| scale                 | -0  | -0 | ... | 0  |
| Exp. scale            | -0  | -0 | ... | 0  |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| <b>Time step</b>      | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| <b>Scale</b>          | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| <b>scale</b>          | -0  | -0 | ... | 0  |
| <b>Exp. scale</b>     | -0  | -0 | ... | 0  |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 3,0000e-09$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 538 |
| Max CPU cycles  | 558 |
| Avg CPU cycles  | 556 |

**Verification: Int2Real FiP16\_Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block Int2Real.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 113   |
| CPU cycles     | 310    | 307    | ... | 307   |
| Inputs         |        |        |     |       |
| In (DSP)       | -32768 | -32183 | ... | 32767 |
| In             | -1     | -0.982 | ... | 1     |
| Parameters     |        |        |     |       |
| Scale          | 7.3    |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -7.3   | -7.17  | ... | 7.3   |
| Exp. Out       | -7.3   | -7.17  | ... | 7.3   |
| Out (DSP)      | -7.3   | -7.17  | ... | 7.3   |
| Exp. Out (DSP) | -7.3   | -7.17  | ... | 7.3   |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 655360$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 207 |
| Max CPU cycles  | 311 |
| Avg CPU cycles  | 306 |

**Test case: Parameter test****OK**

Parameter test for General block Int2Real.

| Test results   |      |      |     |     |
|----------------|------|------|-----|-----|
| Time step      | 1    | 2    | ... | 15  |
| CPU cycles     | 307  | 307  | ... | 307 |
| Inputs         |      |      |     |     |
| In (DSP)       | 3277 |      |     |     |
| In             | 0.1  |      |     |     |
| Parameters     |      |      |     |     |
| Scale          | -10  | -5   | ... | 10  |
| Outputs        |      |      |     |     |
| Out            | -1   | -0.5 | ... | 1   |
| Exp. Out       | -1   | -0.5 | ... | 1   |
| Out (DSP)      | -1   | -0.5 | ... | 1   |
| Exp. Out (DSP) | -1   | -0.5 | ... | 1   |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 131072$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 256 |
| Max CPU cycles  | 310 |
| Avg CPU cycles  | 304 |

#### Test case: Conversion test

OK

Conversion test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| <b>Time step</b>      | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| <b>Scale</b>          | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| <b>scale</b>          | -0  | -0 | ... | 0  |
| <b>Exp. scale</b>     | -0  | -0 | ... | 0  |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| <b>Time step</b>      | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| <b>Scale</b>          | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| <b>scale</b>          | -0  | -0 | ... | 0  |
| <b>Exp. scale</b>     | -0  | -0 | ... | 0  |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 3,0000e-09$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 829  |
| Max CPU cycles  | 1075 |
| Avg CPU cycles  | 1052 |

**Verification: Int2Real FiP16\_Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block Int2Real.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 113   |
| CPU cycles     | 115    | 114    | ... | 113   |
| Inputs         |        |        |     |       |
| In (DSP)       | -32768 | -32183 | ... | 32767 |
| In             | -1     | -0.982 | ... | 1     |
| Parameters     |        |        |     |       |
| Scale          | 7.3    |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -7.3   | -7.17  | ... | 7.3   |
| Exp. Out       | -7.3   | -7.17  | ... | 7.3   |
| Out (DSP)      | -7.3   | -7.17  | ... | 7.3   |
| Exp. Out (DSP) | -7.3   | -7.17  | ... | 7.3   |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 655360$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 80  |
| Max CPU cycles  | 116 |
| Avg CPU cycles  | 113 |

**Test case: Parameter test****OK**

Parameter test for General block Int2Real.



| Test results   |      |      |     |     |
|----------------|------|------|-----|-----|
| Time step      | 1    | 2    | ... | 15  |
| CPU cycles     | 112  | 112  | ... | 112 |
| Inputs         |      |      |     |     |
| In (DSP)       | 3277 |      |     |     |
| In             | 0.1  |      |     |     |
| Parameters     |      |      |     |     |
| Scale          | -10  | -5   | ... | 10  |
| Outputs        |      |      |     |     |
| Out            | -1   | -0.5 | ... | 1   |
| Exp. Out       | -1   | -0.5 | ... | 1   |
| Out (DSP)      | -1   | -0.5 | ... | 1   |
| Exp. Out (DSP) | -1   | -0.5 | ... | 1   |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 131072$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 95  |
| Max CPU cycles  | 114 |
| Avg CPU cycles  | 111 |

#### Test case: Conversion test

OK

Conversion test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| <b>Time step</b>      | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| <b>Scale</b>          | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| <b>scale</b>          | -0  | -0 | ... | 0  |
| <b>Exp. scale</b>     | -0  | -0 | ... | 0  |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| <b>Time step</b>      | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| <b>Scale</b>          | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| <b>scale</b>          | -0  | -0 | ... | 0  |
| <b>Exp. scale</b>     | -0  | -0 | ... | 0  |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 3,0000e-09$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 323 |
| Max CPU cycles  | 375 |
| Avg CPU cycles  | 370 |

**Verification: Int2Real FiP16\_Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block Int2Real.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 113   |
| CPU cycles     | 383    | 394    | ... | 389   |
| Inputs         |        |        |     |       |
| In (DSP)       | -32768 | -32183 | ... | 32767 |
| In             | -1     | -0.982 | ... | 1     |
| Parameters     |        |        |     |       |
| Scale          | 7.3    |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -7.3   | -7.17  | ... | 7.3   |
| Exp. Out       | -7.3   | -7.17  | ... | 7.3   |
| Out (DSP)      | -7.3   | -7.17  | ... | 7.3   |
| Exp. Out (DSP) | -7.3   | -7.17  | ... | 7.3   |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 655360$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 201 |
| Max CPU cycles  | 440 |
| Avg CPU cycles  | 396 |

**Test case: Parameter test****OK**

Parameter test for General block Int2Real.

| Test results   |      |      |     |     |
|----------------|------|------|-----|-----|
| Time step      | 1    | 2    | ... | 15  |
| CPU cycles     | 417  | 417  | ... | 417 |
| Inputs         |      |      |     |     |
| In (DSP)       | 3277 |      |     |     |
| In             | 0.1  |      |     |     |
| Parameters     |      |      |     |     |
| Scale          | -10  | -5   | ... | 10  |
| Outputs        |      |      |     |     |
| Out            | -1   | -0.5 | ... | 1   |
| Exp. Out       | -1   | -0.5 | ... | 1   |
| Out (DSP)      | -1   | -0.5 | ... | 1   |
| Exp. Out (DSP) | -1   | -0.5 | ... | 1   |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 131072$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 372 |
| Max CPU cycles  | 419 |
| Avg CPU cycles  | 414 |

#### Test case: Conversion test

OK

Conversion test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| Time step             | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| Scale                 | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| scale                 | -0  | -0 | ... | 0  |
| Exp. scale            | -0  | -0 | ... | 0  |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| <b>Time step</b>      | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| <b>Scale</b>          | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| <b>scale</b>          | -0  | -0 | ... | 0  |
| <b>Exp. scale</b>     | -0  | -0 | ... | 0  |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 3,0000e-09$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 675  |
| Max CPU cycles  | 1285 |
| Avg CPU cycles  | 1241 |

**Verification: Int2Real FiP16\_Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block Int2Real.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 113   |
| CPU cycles     | 59     | 59     | ... | 59    |
| Inputs         |        |        |     |       |
| In (DSP)       | -32768 | -32183 | ... | 32767 |
| In             | -1     | -0.982 | ... | 1     |
| Parameters     |        |        |     |       |
| Scale          | 7.3    |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -7.3   | -7.17  | ... | 7.3   |
| Exp. Out       | -7.3   | -7.17  | ... | 7.3   |
| Out (DSP)      | -7.3   | -7.17  | ... | 7.3   |
| Exp. Out (DSP) | -7.3   | -7.17  | ... | 7.3   |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 655360$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 59 |
| Avg CPU cycles  | 59 |

**Test case: Parameter test****OK**

Parameter test for General block Int2Real.

| Test results   |      |      |     |    |
|----------------|------|------|-----|----|
| Time step      | 1    | 2    | ... | 15 |
| CPU cycles     | 59   | 59   | ... | 59 |
| Inputs         |      |      |     |    |
| In (DSP)       | 3277 |      |     |    |
| In             | 0.1  |      |     |    |
| Parameters     |      |      |     |    |
| Scale          | -10  | -5   | ... | 10 |
| Outputs        |      |      |     |    |
| Out            | -1   | -0.5 | ... | 1  |
| Exp. Out       | -1   | -0.5 | ... | 1  |
| Out (DSP)      | -1   | -0.5 | ... | 1  |
| Exp. Out (DSP) | -1   | -0.5 | ... | 1  |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 131072$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 59 |
| Avg CPU cycles  | 59 |

#### Test case: Conversion test

OK

Conversion test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| Time step             | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| Scale                 | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| scale                 | -0  | -0 | ... | 0  |
| Exp. scale            | -0  | -0 | ... | 0  |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Int2Real.

| Test results                 |     |    |     |    |
|------------------------------|-----|----|-----|----|
| <b>Time step</b>             | 1   | 2  | ... | 15 |
| <i>Mask parameters</i>       |     |    |     |    |
| <b>Scale</b>                 | -10 | -5 | ... | 10 |
| <i>Controller parameters</i> |     |    |     |    |
| <b>scale</b>                 | -0  | -0 | ... | 0  |
| <b>Exp. scale</b>            | -0  | -0 | ... | 0  |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 3,0000e-09$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 450 |
| Max CPU cycles  | 514 |
| Avg CPU cycles  | 467 |



**Verification: Int2Real FiP16\_Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block Int2Real.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 113   |
| CPU cycles     | 40     | 40     | ... | 40    |
| Inputs         |        |        |     |       |
| In (DSP)       | -32768 | -32183 | ... | 32767 |
| In             | -1     | -0.982 | ... | 1     |
| Parameters     |        |        |     |       |
| Scale          | 7.3    |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -7.3   | -7.17  | ... | 7.3   |
| Exp. Out       | -7.3   | -7.17  | ... | 7.3   |
| Out (DSP)      | -7.3   | -7.17  | ... | 7.3   |
| Exp. Out (DSP) | -7.3   | -7.17  | ... | 7.3   |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 655360$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 40 |
| Max CPU cycles  | 40 |
| Avg CPU cycles  | 40 |

**Test case: Parameter test****OK**

Parameter test for General block Int2Real.

| Test results   |      |      |     |    |
|----------------|------|------|-----|----|
| Time step      | 1    | 2    | ... | 15 |
| CPU cycles     | 40   | 40   | ... | 40 |
| Inputs         |      |      |     |    |
| In (DSP)       | 3277 |      |     |    |
| In             | 0.1  |      |     |    |
| Parameters     |      |      |     |    |
| Scale          | -10  | -5   | ... | 10 |
| Outputs        |      |      |     |    |
| Out            | -1   | -0.5 | ... | 1  |
| Exp. Out       | -1   | -0.5 | ... | 1  |
| Out (DSP)      | -1   | -0.5 | ... | 1  |
| Exp. Out (DSP) | -1   | -0.5 | ... | 1  |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 131072$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 40 |
| Max CPU cycles  | 40 |
| Avg CPU cycles  | 40 |

#### Test case: Conversion test

OK

Conversion test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| Time step             | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| Scale                 | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| scale                 | -0  | -0 | ... | 0  |
| Exp. scale            | -0  | -0 | ... | 0  |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Int2Real.

| Test results                 |     |    |     |    |
|------------------------------|-----|----|-----|----|
| <b>Time step</b>             | 1   | 2  | ... | 15 |
| <i>Mask parameters</i>       |     |    |     |    |
| <b>Scale</b>                 | -10 | -5 | ... | 10 |
| <i>Controller parameters</i> |     |    |     |    |
| <b>scale</b>                 | -0  | -0 | ... | 0  |
| <b>Exp. scale</b>            | -0  | -0 | ... | 0  |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 3,0000e-09$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 719 |
| Max CPU cycles  | 811 |
| Avg CPU cycles  | 804 |

**Verification: Int2Real FiP32\_Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block Int2Real.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 113        |
| CPU cycles     | 59          | 59          | ... | 59         |
| Inputs         |             |             |     |            |
| In (DSP)       | -2147483648 | -2109135726 | ... | 2147483647 |
| In             | -1          | -0.982      | ... | 1          |
| Parameters     |             |             |     |            |
| Scale          | 7.3         |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -7.3        | -7.17       | ... | 7.3        |
| Exp. Out       | -7.3        | -7.17       | ... | 7.3        |
| Out (DSP)      | -7.3        | -7.17       | ... | 7.3        |
| Exp. Out (DSP) | -7.3        | -7.17       | ... | 7.3        |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 6,5193e-07$ ( $\pm 1400$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 59 |
| Avg CPU cycles  | 59 |

**Test case: Parameter test****OK**

Parameter test for General block Int2Real.

| Test results   |           |      |     |    |
|----------------|-----------|------|-----|----|
| Time step      | 1         | 2    | ... | 15 |
| CPU cycles     | 59        | 59   | ... | 59 |
| Inputs         |           |      |     |    |
| In (DSP)       | 214748365 |      |     |    |
| In             | 0.1       |      |     |    |
| Parameters     |           |      |     |    |
| Scale          | -10       | -5   | ... | 10 |
| Outputs        |           |      |     |    |
| Out            | -1        | -0.5 | ... | 1  |
| Exp. Out       | -1        | -0.5 | ... | 1  |
| Out (DSP)      | -1        | -0.5 | ... | 1  |
| Exp. Out (DSP) | -1        | -0.5 | ... | 1  |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}08$ ( $\pm 150$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 59 |
| Avg CPU cycles  | 59 |

#### Test case: Conversion test

OK

Conversion test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| Time step             | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| Scale                 | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| scale                 | -0  | -0 | ... | 0  |
| Exp. scale            | -0  | -0 | ... | 0  |

| Test settings   |                         |
|-----------------|-------------------------|
| Tolerance scale | $\pm 0,0000\text{e+}00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| <b>Time step</b>      | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| <b>Scale</b>          | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| <b>scale</b>          | -0  | -0 | ... | 0  |
| <b>Exp. scale</b>     | -0  | -0 | ... | 0  |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 3,0000e-09$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 959  |
| Max CPU cycles  | 1093 |
| Avg CPU cycles  | 1084 |

**Verification: Int2Real FiP32\_Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block Int2Real.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 113        |
| CPU cycles     | 29          | 29          | ... | 29         |
| Inputs         |             |             |     |            |
| In (DSP)       | -2147483648 | -2109135726 | ... | 2147483647 |
| In             | -1          | -0.982      | ... | 1          |
| Parameters     |             |             |     |            |
| Scale          | 7.3         |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -7.3        | -7.17       | ... | 7.3        |
| Exp. Out       | -7.3        | -7.17       | ... | 7.3        |
| Out (DSP)      | -7.3        | -7.17       | ... | 7.3        |
| Exp. Out (DSP) | -7.3        | -7.17       | ... | 7.3        |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 6,5193e-07$ ( $\pm 1400$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 29 |
| Avg CPU cycles  | 29 |

**Test case: Parameter test****OK**

Parameter test for General block Int2Real.

| Test results   |           |      |     |    |
|----------------|-----------|------|-----|----|
| Time step      | 1         | 2    | ... | 15 |
| CPU cycles     | 29        | 29   | ... | 29 |
| Inputs         |           |      |     |    |
| In (DSP)       | 214748365 |      |     |    |
| In             | 0.1       |      |     |    |
| Parameters     |           |      |     |    |
| Scale          | -10       | -5   | ... | 10 |
| Outputs        |           |      |     |    |
| Out            | -1        | -0.5 | ... | 1  |
| Exp. Out       | -1        | -0.5 | ... | 1  |
| Out (DSP)      | -1        | -0.5 | ... | 1  |
| Exp. Out (DSP) | -1        | -0.5 | ... | 1  |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}08$ ( $\pm 150$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 29 |
| Avg CPU cycles  | 29 |

#### Test case: Conversion test

OK

Conversion test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| Time step             | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| Scale                 | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| scale                 | -0  | -0 | ... | 0  |
| Exp. scale            | -0  | -0 | ... | 0  |

| Test settings   |                         |
|-----------------|-------------------------|
| Tolerance scale | $\pm 0,0000\text{e+}00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Int2Real.



| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| <b>Time step</b>      | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| <b>Scale</b>          | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| <b>scale</b>          | -0  | -0 | ... | 0  |
| <b>Exp. scale</b>     | -0  | -0 | ... | 0  |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 3,0000e-09$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 467 |
| Max CPU cycles  | 515 |
| Avg CPU cycles  | 511 |

**Verification: Int2Real FiP32\_Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block Int2Real.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 113        |
| CPU cycles     | 62          | 62          | ... | 62         |
| Inputs         |             |             |     |            |
| In (DSP)       | -2147483648 | -2109135726 | ... | 2147483647 |
| In             | -1          | -0.982      | ... | 1          |
| Parameters     |             |             |     |            |
| Scale          | 7.3         |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -7.3        | -7.17       | ... | 7.3        |
| Exp. Out       | -7.3        | -7.17       | ... | 7.3        |
| Out (DSP)      | -7.3        | -7.17       | ... | 7.3        |
| Exp. Out (DSP) | -7.3        | -7.17       | ... | 7.3        |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 6,5193e-07$ ( $\pm 1400$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 62 |
| Avg CPU cycles  | 62 |

**Test case: Parameter test****OK**

Parameter test for General block Int2Real.

| Test results   |           |      |     |    |
|----------------|-----------|------|-----|----|
| Time step      | 1         | 2    | ... | 15 |
| CPU cycles     | 62        | 62   | ... | 62 |
| Inputs         |           |      |     |    |
| In (DSP)       | 214748365 |      |     |    |
| In             | 0.1       |      |     |    |
| Parameters     |           |      |     |    |
| Scale          | -10       | -5   | ... | 10 |
| Outputs        |           |      |     |    |
| Out            | -1        | -0.5 | ... | 1  |
| Exp. Out       | -1        | -0.5 | ... | 1  |
| Out (DSP)      | -1        | -0.5 | ... | 1  |
| Exp. Out (DSP) | -1        | -0.5 | ... | 1  |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}08$ ( $\pm 150$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 62 |
| Avg CPU cycles  | 62 |

#### Test case: Conversion test

OK

Conversion test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| Time step             | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| Scale                 | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| scale                 | -0  | -0 | ... | 0  |
| Exp. scale            | -0  | -0 | ... | 0  |

| Test settings   |                         |
|-----------------|-------------------------|
| Tolerance scale | $\pm 0,0000\text{e+}00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| <b>Time step</b>      | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| <b>Scale</b>          | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| <b>scale</b>          | -0  | -0 | ... | 0  |
| <b>Exp. scale</b>     | -0  | -0 | ... | 0  |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 3,0000e-09$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 545 |
| Max CPU cycles  | 565 |
| Avg CPU cycles  | 563 |

**Verification: Int2Real FiP32\_Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block Int2Real.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 113        |
| CPU cycles     | 337         | 340         | ... | 343        |
| Inputs         |             |             |     |            |
| In (DSP)       | -2147483648 | -2109135726 | ... | 2147483647 |
| In             | -1          | -0.982      | ... | 1          |
| Parameters     |             |             |     |            |
| Scale          | 7.3         |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -7.3        | -7.17       | ... | 7.3        |
| Exp. Out       | -7.3        | -7.17       | ... | 7.3        |
| Out (DSP)      | -7.3        | -7.17       | ... | 7.3        |
| Exp. Out (DSP) | -7.3        | -7.17       | ... | 7.3        |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 6,5193e-07$ ( $\pm 1400$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 206 |
| Max CPU cycles  | 399 |
| Avg CPU cycles  | 338 |

**Test case: Parameter test****OK**

Parameter test for General block Int2Real.

| Test results   |           |      |     |     |
|----------------|-----------|------|-----|-----|
| Time step      | 1         | 2    | ... | 15  |
| CPU cycles     | 341       | 341  | ... | 341 |
| Inputs         |           |      |     |     |
| In (DSP)       | 214748365 |      |     |     |
| In             | 0.1       |      |     |     |
| Parameters     |           |      |     |     |
| Scale          | -10       | -5   | ... | 10  |
| Outputs        |           |      |     |     |
| Out            | -1        | -0.5 | ... | 1   |
| Exp. Out       | -1        | -0.5 | ... | 1   |
| Out (DSP)      | -1        | -0.5 | ... | 1   |
| Exp. Out (DSP) | -1        | -0.5 | ... | 1   |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}08$ ( $\pm 150$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 290 |
| Max CPU cycles  | 344 |
| Avg CPU cycles  | 338 |

#### Test case: Conversion test

OK

Conversion test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| <b>Time step</b>      | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| <b>Scale</b>          | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| <b>scale</b>          | -0  | -0 | ... | 0  |
| <b>Exp. scale</b>     | -0  | -0 | ... | 0  |

| Test settings   |                         |
|-----------------|-------------------------|
| Tolerance scale | $\pm 0,0000\text{e}+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| <b>Time step</b>      | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| <b>Scale</b>          | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| <b>scale</b>          | -0  | -0 | ... | 0  |
| <b>Exp. scale</b>     | -0  | -0 | ... | 0  |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 3,0000e-09$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 829  |
| Max CPU cycles  | 1125 |
| Avg CPU cycles  | 1056 |

**Verification: Int2Real FiP32\_Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block Int2Real.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 113        |
| CPU cycles     | 115         | 114         | ... | 114        |
| Inputs         |             |             |     |            |
| In (DSP)       | -2147483648 | -2109135726 | ... | 2147483647 |
| In             | -1          | -0.982      | ... | 1          |
| Parameters     |             |             |     |            |
| Scale          | 7.3         |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -7.3        | -7.17       | ... | 7.3        |
| Exp. Out       | -7.3        | -7.17       | ... | 7.3        |
| Out (DSP)      | -7.3        | -7.17       | ... | 7.3        |
| Exp. Out (DSP) | -7.3        | -7.17       | ... | 7.3        |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 6,5193e-07$ ( $\pm 1400$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 80  |
| Max CPU cycles  | 116 |
| Avg CPU cycles  | 113 |

**Test case: Parameter test****OK**

Parameter test for General block Int2Real.



| Test results   |           |      |     |     |
|----------------|-----------|------|-----|-----|
| Time step      | 1         | 2    | ... | 15  |
| CPU cycles     | 112       | 112  | ... | 112 |
| Inputs         |           |      |     |     |
| In (DSP)       | 214748365 |      |     |     |
| In             | 0.1       |      |     |     |
| Parameters     |           |      |     |     |
| Scale          | -10       | -5   | ... | 10  |
| Outputs        |           |      |     |     |
| Out            | -1        | -0.5 | ... | 1   |
| Exp. Out       | -1        | -0.5 | ... | 1   |
| Out (DSP)      | -1        | -0.5 | ... | 1   |
| Exp. Out (DSP) | -1        | -0.5 | ... | 1   |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}08$ ( $\pm 150$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 95  |
| Max CPU cycles  | 114 |
| Avg CPU cycles  | 111 |

#### Test case: Conversion test

OK

Conversion test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| <b>Time step</b>      | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| <b>Scale</b>          | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| <b>scale</b>          | -0  | -0 | ... | 0  |
| <b>Exp. scale</b>     | -0  | -0 | ... | 0  |

| Test settings   |                         |
|-----------------|-------------------------|
| Tolerance scale | $\pm 0,0000\text{e}+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Int2Real.

| Test results                 |     |    |     |    |
|------------------------------|-----|----|-----|----|
| <b>Time step</b>             | 1   | 2  | ... | 15 |
| <i>Mask parameters</i>       |     |    |     |    |
| <b>Scale</b>                 | -10 | -5 | ... | 10 |
| <i>Controller parameters</i> |     |    |     |    |
| <b>scale</b>                 | -0  | -0 | ... | 0  |
| <b>Exp. scale</b>            | -0  | -0 | ... | 0  |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 3,0000e-09$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 323 |
| Max CPU cycles  | 375 |
| Avg CPU cycles  | 370 |

**Verification: Int2Real FiP32\_Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block Int2Real.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 113        |
| CPU cycles     | 397         | 386         | ... | 386        |
| Inputs         |             |             |     |            |
| In (DSP)       | -2147483648 | -2109135726 | ... | 2147483647 |
| In             | -1          | -0.982      | ... | 1          |
| Parameters     |             |             |     |            |
| Scale          | 7.3         |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -7.3        | -7.17       | ... | 7.3        |
| Exp. Out       | -7.3        | -7.17       | ... | 7.3        |
| Out (DSP)      | -7.3        | -7.17       | ... | 7.3        |
| Exp. Out (DSP) | -7.3        | -7.17       | ... | 7.3        |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 6,5193e-07$ ( $\pm 1400$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 201 |
| Max CPU cycles  | 397 |
| Avg CPU cycles  | 371 |

**Test case: Parameter test****OK**

Parameter test for General block Int2Real.

| Test results   |           |      |     |     |
|----------------|-----------|------|-----|-----|
| Time step      | 1         | 2    | ... | 15  |
| CPU cycles     | 345       | 345  | ... | 345 |
| Inputs         |           |      |     |     |
| In (DSP)       | 214748365 |      |     |     |
| In             | 0.1       |      |     |     |
| Parameters     |           |      |     |     |
| Scale          | -10       | -5   | ... | 10  |
| Outputs        |           |      |     |     |
| Out            | -1        | -0.5 | ... | 1   |
| Exp. Out       | -1        | -0.5 | ... | 1   |
| Out (DSP)      | -1        | -0.5 | ... | 1   |
| Exp. Out (DSP) | -1        | -0.5 | ... | 1   |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}08$ ( $\pm 150$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 302 |
| Max CPU cycles  | 349 |
| Avg CPU cycles  | 344 |

#### Test case: Conversion test

OK

Conversion test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| <b>Time step</b>      | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| <b>Scale</b>          | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| <b>scale</b>          | -0  | -0 | ... | 0  |
| <b>Exp. scale</b>     | -0  | -0 | ... | 0  |

| Test settings   |                         |
|-----------------|-------------------------|
| Tolerance scale | $\pm 0,0000\text{e+}00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| <b>Time step</b>      | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| <b>Scale</b>          | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| <b>scale</b>          | -0  | -0 | ... | 0  |
| <b>Exp. scale</b>     | -0  | -0 | ... | 0  |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 3,0000e-09$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 675  |
| Max CPU cycles  | 1285 |
| Avg CPU cycles  | 1241 |

**Verification: Int2Real FiP32\_Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block Int2Real.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 113        |
| CPU cycles     | 58          | 58          | ... | 58         |
| Inputs         |             |             |     |            |
| In (DSP)       | -2147483648 | -2109135726 | ... | 2147483647 |
| In             | -1          | -0.982      | ... | 1          |
| Parameters     |             |             |     |            |
| Scale          | 7.3         |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -7.3        | -7.17       | ... | 7.3        |
| Exp. Out       | -7.3        | -7.17       | ... | 7.3        |
| Out (DSP)      | -7.3        | -7.17       | ... | 7.3        |
| Exp. Out (DSP) | -7.3        | -7.17       | ... | 7.3        |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 6,5193e-07$ ( $\pm 1400$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 58 |
| Max CPU cycles  | 58 |
| Avg CPU cycles  | 58 |

**Test case: Parameter test****OK**

Parameter test for General block Int2Real.

| Test results   |           |      |     |    |
|----------------|-----------|------|-----|----|
| Time step      | 1         | 2    | ... | 15 |
| CPU cycles     | 58        | 58   | ... | 58 |
| Inputs         |           |      |     |    |
| In (DSP)       | 214748365 |      |     |    |
| In             | 0.1       |      |     |    |
| Parameters     |           |      |     |    |
| Scale          | -10       | -5   | ... | 10 |
| Outputs        |           |      |     |    |
| Out            | -1        | -0.5 | ... | 1  |
| Exp. Out       | -1        | -0.5 | ... | 1  |
| Out (DSP)      | -1        | -0.5 | ... | 1  |
| Exp. Out (DSP) | -1        | -0.5 | ... | 1  |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}08$ ( $\pm 150$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 58 |
| Max CPU cycles  | 58 |
| Avg CPU cycles  | 58 |

#### Test case: Conversion test

OK

Conversion test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| Time step             | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| Scale                 | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| scale                 | -0  | -0 | ... | 0  |
| Exp. scale            | -0  | -0 | ... | 0  |

| Test settings   |                         |
|-----------------|-------------------------|
| Tolerance scale | $\pm 0,0000\text{e+}00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| <b>Time step</b>      | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| <b>Scale</b>          | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| <b>scale</b>          | -0  | -0 | ... | 0  |
| <b>Exp. scale</b>     | -0  | -0 | ... | 0  |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 3,0000e-09$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 433 |
| Max CPU cycles  | 496 |
| Avg CPU cycles  | 438 |



**Verification: Int2Real FiP32\_Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block Int2Real.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 113        |
| CPU cycles     | 45          | 45          | ... | 45         |
| Inputs         |             |             |     |            |
| In (DSP)       | -2147483648 | -2109135726 | ... | 2147483647 |
| In             | -1          | -0.982      | ... | 1          |
| Parameters     |             |             |     |            |
| Scale          | 7.3         |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -7.3        | -7.17       | ... | 7.3        |
| Exp. Out       | -7.3        | -7.17       | ... | 7.3        |
| Out (DSP)      | -7.3        | -7.17       | ... | 7.3        |
| Exp. Out (DSP) | -7.3        | -7.17       | ... | 7.3        |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 6,5193e-07$ ( $\pm 1400$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 45 |
| Max CPU cycles  | 45 |
| Avg CPU cycles  | 45 |

**Test case: Parameter test****OK**

Parameter test for General block Int2Real.

| Test results   |           |      |     |    |
|----------------|-----------|------|-----|----|
| Time step      | 1         | 2    | ... | 15 |
| CPU cycles     | 45        | 45   | ... | 45 |
| Inputs         |           |      |     |    |
| In (DSP)       | 214748365 |      |     |    |
| In             | 0.1       |      |     |    |
| Parameters     |           |      |     |    |
| Scale          | -10       | -5   | ... | 10 |
| Outputs        |           |      |     |    |
| Out            | -1        | -0.5 | ... | 1  |
| Exp. Out       | -1        | -0.5 | ... | 1  |
| Out (DSP)      | -1        | -0.5 | ... | 1  |
| Exp. Out (DSP) | -1        | -0.5 | ... | 1  |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}08$ ( $\pm 150$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 45 |
| Max CPU cycles  | 45 |
| Avg CPU cycles  | 45 |

#### Test case: Conversion test

OK

Conversion test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| Time step             | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| Scale                 | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| scale                 | -0  | -0 | ... | 0  |
| Exp. scale            | -0  | -0 | ... | 0  |

| Test settings   |                         |
|-----------------|-------------------------|
| Tolerance scale | $\pm 0,0000\text{e+}00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| <b>Time step</b>      | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| <b>Scale</b>          | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| <b>scale</b>          | -0  | -0 | ... | 0  |
| <b>Exp. scale</b>     | -0  | -0 | ... | 0  |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 3,0000e-09$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 726 |
| Max CPU cycles  | 818 |
| Avg CPU cycles  | 811 |

**Verification: Int2Real Bool\_Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block Int2Real.

| Test results   |      |       |     |     |
|----------------|------|-------|-----|-----|
| Time step      | 1    | 2     | ... | 5   |
| CPU cycles     | 59   | 59    | ... | 59  |
| Inputs         |      |       |     |     |
| In (DSP)       | 0    | 0     | ... | 1   |
| In             | -3.1 | -0.31 | ... | 3.3 |
| Parameters     |      |       |     |     |
| Scale          | 10   |       |     |     |
| Outputs        |      |       |     |     |
| Out            | 0    | 0     | ... | 10  |
| Exp. Out       | 0    | 0     | ... | 10  |
| Out (DSP)      | 0    | 0     | ... | 10  |
| Exp. Out (DSP) | 0    | 0     | ... | 10  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 59 |
| Avg CPU cycles  | 59 |

**Test case: Parameter test****OK**

Parameter test for General block Int2Real.

| Test results   |     |    |     |    |
|----------------|-----|----|-----|----|
| Time step      | 1   | 2  | ... | 15 |
| CPU cycles     | 59  | 59 | ... | 59 |
| Inputs         |     |    |     |    |
| In (DSP)       | 1   |    |     |    |
| In             | 1.1 |    |     |    |
| Parameters     |     |    |     |    |
| Scale          | -10 | -5 | ... | 10 |
| Outputs        |     |    |     |    |
| Out            | -10 | -5 | ... | 10 |
| Exp. Out       | -10 | -5 | ... | 10 |
| Out (DSP)      | -10 | -5 | ... | 10 |
| Exp. Out (DSP) | -10 | -5 | ... | 10 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 4,6566e-09$ ( $\pm 10$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 59 |
| Avg CPU cycles  | 59 |

#### Test case: Conversion test

OK

Conversion test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| Time step             | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| Scale                 | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| scale                 | -10 | -5 | ... | 10 |
| Exp. scale            | -10 | -5 | ... | 10 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Int2Real.

| Test results                 |     |    |     |    |
|------------------------------|-----|----|-----|----|
| <b>Time step</b>             | 1   | 2  | ... | 15 |
| <i>Mask parameters</i>       |     |    |     |    |
| <b>Scale</b>                 | -10 | -5 | ... | 10 |
| <i>Controller parameters</i> |     |    |     |    |
| <b>scale</b>                 | -10 | -5 | ... | 10 |
| <b>Exp. scale</b>            | -10 | -5 | ... | 10 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 3,0000e-09$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 827 |
| Max CPU cycles  | 844 |
| Avg CPU cycles  | 828 |

**Verification: Int2Real Bool\_Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block Int2Real.

| Test results   |      |       |     |     |
|----------------|------|-------|-----|-----|
| Time step      | 1    | 2     | ... | 5   |
| CPU cycles     | 29   | 29    | ... | 29  |
| Inputs         |      |       |     |     |
| In (DSP)       | 0    | 0     | ... | 1   |
| In             | -3.1 | -0.31 | ... | 3.3 |
| Parameters     |      |       |     |     |
| Scale          | 10   |       |     |     |
| Outputs        |      |       |     |     |
| Out            | 0    | 0     | ... | 10  |
| Exp. Out       | 0    | 0     | ... | 10  |
| Out (DSP)      | 0    | 0     | ... | 10  |
| Exp. Out (DSP) | 0    | 0     | ... | 10  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 29 |
| Avg CPU cycles  | 29 |

**Test case: Parameter test****OK**

Parameter test for General block Int2Real.

| Test results   |     |    |     |    |
|----------------|-----|----|-----|----|
| Time step      | 1   | 2  | ... | 15 |
| CPU cycles     | 29  | 29 | ... | 29 |
| Inputs         |     |    |     |    |
| In (DSP)       | 1   |    |     |    |
| In             | 1.1 |    |     |    |
| Parameters     |     |    |     |    |
| Scale          | -10 | -5 | ... | 10 |
| Outputs        |     |    |     |    |
| Out            | -10 | -5 | ... | 10 |
| Exp. Out       | -10 | -5 | ... | 10 |
| Out (DSP)      | -10 | -5 | ... | 10 |
| Exp. Out (DSP) | -10 | -5 | ... | 10 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 4,6566e-09$ ( $\pm 10$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 29 |
| Avg CPU cycles  | 29 |

#### Test case: Conversion test

OK

Conversion test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| Time step             | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| Scale                 | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| scale                 | -10 | -5 | ... | 10 |
| Exp. scale            | -10 | -5 | ... | 10 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Int2Real.



| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| <b>Time step</b>      | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| <b>Scale</b>          | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| <b>scale</b>          | -10 | -5 | ... | 10 |
| <b>Exp. scale</b>     | -10 | -5 | ... | 10 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 3,0000e-09$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 397 |
| Max CPU cycles  | 397 |
| Avg CPU cycles  | 397 |

**Verification: Int2Real Bool\_Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block Int2Real.

| Test results   |      |       |     |     |
|----------------|------|-------|-----|-----|
| Time step      | 1    | 2     | ... | 5   |
| CPU cycles     | 62   | 62    | ... | 62  |
| Inputs         |      |       |     |     |
| In (DSP)       | 0    | 0     | ... | 1   |
| In             | -3.1 | -0.31 | ... | 3.3 |
| Parameters     |      |       |     |     |
| Scale          | 10   |       |     |     |
| Outputs        |      |       |     |     |
| Out            | 0    | 0     | ... | 10  |
| Exp. Out       | 0    | 0     | ... | 10  |
| Out (DSP)      | 0    | 0     | ... | 10  |
| Exp. Out (DSP) | 0    | 0     | ... | 10  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 62 |
| Avg CPU cycles  | 62 |

**Test case: Parameter test****OK**

Parameter test for General block Int2Real.

| Test results   |     |    |     |    |
|----------------|-----|----|-----|----|
| Time step      | 1   | 2  | ... | 15 |
| CPU cycles     | 62  | 62 | ... | 62 |
| Inputs         |     |    |     |    |
| In (DSP)       | 1   |    |     |    |
| In             | 1.1 |    |     |    |
| Parameters     |     |    |     |    |
| Scale          | -10 | -5 | ... | 10 |
| Outputs        |     |    |     |    |
| Out            | -10 | -5 | ... | 10 |
| Exp. Out       | -10 | -5 | ... | 10 |
| Out (DSP)      | -10 | -5 | ... | 10 |
| Exp. Out (DSP) | -10 | -5 | ... | 10 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 4,6566e-09$ ( $\pm 10$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 62 |
| Avg CPU cycles  | 62 |

#### Test case: Conversion test

OK

Conversion test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| Time step             | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| Scale                 | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| scale                 | -10 | -5 | ... | 10 |
| Exp. scale            | -10 | -5 | ... | 10 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| <b>Time step</b>      | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| <b>Scale</b>          | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| <b>scale</b>          | -10 | -5 | ... | 10 |
| <b>Exp. scale</b>     | -10 | -5 | ... | 10 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 3,0000e-09$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 467 |
| Max CPU cycles  | 519 |
| Avg CPU cycles  | 470 |

**Verification: Int2Real Bool\_Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block Int2Real.

| Test results   |      |       |     |     |
|----------------|------|-------|-----|-----|
| Time step      | 1    | 2     | ... | 5   |
| CPU cycles     | 198  | 198   | ... | 298 |
| Inputs         |      |       |     |     |
| In (DSP)       | 0    | 0     | ... | 1   |
| In             | -3.1 | -0.31 | ... | 3.3 |
| Parameters     |      |       |     |     |
| Scale          | 10   |       |     |     |
| Outputs        |      |       |     |     |
| Out            | 0    | 0     | ... | 10  |
| Exp. Out       | 0    | 0     | ... | 10  |
| Out (DSP)      | 0    | 0     | ... | 10  |
| Exp. Out (DSP) | 0    | 0     | ... | 10  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 198 |
| Max CPU cycles  | 298 |
| Avg CPU cycles  | 218 |

**Test case: Parameter test****OK**

Parameter test for General block Int2Real.

| Test results   |     |     |     |     |
|----------------|-----|-----|-----|-----|
| Time step      | 1   | 2   | ... | 15  |
| CPU cycles     | 298 | 298 | ... | 298 |
| Inputs         |     |     |     |     |
| In (DSP)       | 1   |     |     |     |
| In             | 1.1 |     |     |     |
| Parameters     |     |     |     |     |
| Scale          | -10 | -5  | ... | 10  |
| Outputs        |     |     |     |     |
| Out            | -10 | -5  | ... | 10  |
| Exp. Out       | -10 | -5  | ... | 10  |
| Out (DSP)      | -10 | -5  | ... | 10  |
| Exp. Out (DSP) | -10 | -5  | ... | 10  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 4,6566e-09$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 244 |
| Max CPU cycles  | 357 |
| Avg CPU cycles  | 298 |

#### Test case: Conversion test

OK

Conversion test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| <b>Time step</b>      | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| <b>Scale</b>          | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| <b>scale</b>          | -10 | -5 | ... | 10 |
| <b>Exp. scale</b>     | -10 | -5 | ... | 10 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| <b>Time step</b>      | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| <b>Scale</b>          | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| <b>scale</b>          | -10 | -5 | ... | 10 |
| <b>Exp. scale</b>     | -10 | -5 | ... | 10 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 3,0000e-09$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 667 |
| Max CPU cycles  | 747 |
| Avg CPU cycles  | 692 |

**Verification: Int2Real Bool\_Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block Int2Real.

| Test results   |      |       |     |     |
|----------------|------|-------|-----|-----|
| Time step      | 1    | 2     | ... | 5   |
| CPU cycles     | 92   | 92    | ... | 126 |
| Inputs         |      |       |     |     |
| In (DSP)       | 0    | 0     | ... | 1   |
| In             | -3.1 | -0.31 | ... | 3.3 |
| Parameters     |      |       |     |     |
| Scale          | 10   |       |     |     |
| Outputs        |      |       |     |     |
| Out            | 0    | 0     | ... | 10  |
| Exp. Out       | 0    | 0     | ... | 10  |
| Out (DSP)      | 0    | 0     | ... | 10  |
| Exp. Out (DSP) | 0    | 0     | ... | 10  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 92  |
| Max CPU cycles  | 126 |
| Avg CPU cycles  | 98  |

**Test case: Parameter test****OK**

Parameter test for General block Int2Real.



| Test results   |     |     |     |     |
|----------------|-----|-----|-----|-----|
| Time step      | 1   | 2   | ... | 15  |
| CPU cycles     | 126 | 126 | ... | 126 |
| Inputs         |     |     |     |     |
| In (DSP)       | 1   |     |     |     |
| In             | 1.1 |     |     |     |
| Parameters     |     |     |     |     |
| Scale          | -10 | -5  | ... | 10  |
| Outputs        |     |     |     |     |
| Out            | -10 | -5  | ... | 10  |
| Exp. Out       | -10 | -5  | ... | 10  |
| Out (DSP)      | -10 | -5  | ... | 10  |
| Exp. Out (DSP) | -10 | -5  | ... | 10  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 4,6566e-09$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 107 |
| Max CPU cycles  | 126 |
| Avg CPU cycles  | 124 |

#### Test case: Conversion test

OK

Conversion test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| <b>Time step</b>      | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| <b>Scale</b>          | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| <b>scale</b>          | -10 | -5 | ... | 10 |
| <b>Exp. scale</b>     | -10 | -5 | ... | 10 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| <b>Time step</b>      | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| <b>Scale</b>          | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| <b>scale</b>          | -10 | -5 | ... | 10 |
| <b>Exp. scale</b>     | -10 | -5 | ... | 10 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 3,0000e-09$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 277 |
| Max CPU cycles  | 278 |
| Avg CPU cycles  | 277 |

**Verification: Int2Real Bool\_Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block Int2Real.

| Test results   |      |       |     |     |
|----------------|------|-------|-----|-----|
| Time step      | 1    | 2     | ... | 5   |
| CPU cycles     | 180  | 180   | ... | 507 |
| Inputs         |      |       |     |     |
| In (DSP)       | 0    | 0     | ... | 1   |
| In             | -3.1 | -0.31 | ... | 3.3 |
| Parameters     |      |       |     |     |
| Scale          | 10   |       |     |     |
| Outputs        |      |       |     |     |
| Out            | 0    | 0     | ... | 10  |
| Exp. Out       | 0    | 0     | ... | 10  |
| Out (DSP)      | 0    | 0     | ... | 10  |
| Exp. Out (DSP) | 0    | 0     | ... | 10  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 180 |
| Max CPU cycles  | 507 |
| Avg CPU cycles  | 245 |

**Test case: Parameter test****OK**

Parameter test for General block Int2Real.

| Test results   |     |     |     |     |
|----------------|-----|-----|-----|-----|
| Time step      | 1   | 2   | ... | 15  |
| CPU cycles     | 507 | 507 | ... | 507 |
| Inputs         |     |     |     |     |
| In (DSP)       | 1   |     |     |     |
| In             | 1.1 |     |     |     |
| Parameters     |     |     |     |     |
| Scale          | -10 | -5  | ... | 10  |
| Outputs        |     |     |     |     |
| Out            | -10 | -5  | ... | 10  |
| Exp. Out       | -10 | -5  | ... | 10  |
| Out (DSP)      | -10 | -5  | ... | 10  |
| Exp. Out (DSP) | -10 | -5  | ... | 10  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 4,6566e-09$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 461 |
| Max CPU cycles  | 507 |
| Avg CPU cycles  | 503 |

#### Test case: Conversion test

OK

Conversion test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| <b>Time step</b>      | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| <b>Scale</b>          | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| <b>scale</b>          | -10 | -5 | ... | 10 |
| <b>Exp. scale</b>     | -10 | -5 | ... | 10 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Int2Real.

| Test results                 |     |    |     |    |
|------------------------------|-----|----|-----|----|
| <b>Time step</b>             | 1   | 2  | ... | 15 |
| <i>Mask parameters</i>       |     |    |     |    |
| <b>Scale</b>                 | -10 | -5 | ... | 10 |
| <i>Controller parameters</i> |     |    |     |    |
| <b>scale</b>                 | -10 | -5 | ... | 10 |
| <b>Exp. scale</b>            | -10 | -5 | ... | 10 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 3,0000e-09$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 523 |
| Max CPU cycles  | 868 |
| Avg CPU cycles  | 842 |

**Verification: Int2Real Bool\_Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block Int2Real.

| Test results   |      |       |     |     |
|----------------|------|-------|-----|-----|
| Time step      | 1    | 2     | ... | 5   |
| CPU cycles     | 76   | 59    | ... | 59  |
| Inputs         |      |       |     |     |
| In (DSP)       | 0    | 0     | ... | 1   |
| In             | -3.1 | -0.31 | ... | 3.3 |
| Parameters     |      |       |     |     |
| Scale          | 10   |       |     |     |
| Outputs        |      |       |     |     |
| Out            | 0    | 0     | ... | 10  |
| Exp. Out       | 0    | 0     | ... | 10  |
| Out (DSP)      | 0    | 0     | ... | 10  |
| Exp. Out (DSP) | 0    | 0     | ... | 10  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 76 |
| Avg CPU cycles  | 62 |

**Test case: Parameter test****OK**

Parameter test for General block Int2Real.

| Test results   |     |    |     |    |
|----------------|-----|----|-----|----|
| Time step      | 1   | 2  | ... | 15 |
| CPU cycles     | 76  | 76 | ... | 76 |
| Inputs         |     |    |     |    |
| In (DSP)       | 1   |    |     |    |
| In             | 1.1 |    |     |    |
| Parameters     |     |    |     |    |
| Scale          | -10 | -5 | ... | 10 |
| Outputs        |     |    |     |    |
| Out            | -10 | -5 | ... | 10 |
| Exp. Out       | -10 | -5 | ... | 10 |
| Out (DSP)      | -10 | -5 | ... | 10 |
| Exp. Out (DSP) | -10 | -5 | ... | 10 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 4,6566e-09$ ( $\pm 10$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 76 |
| Max CPU cycles  | 76 |
| Avg CPU cycles  | 76 |

### Test case: Conversion test

OK

Conversion test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| <b>Time step</b>      | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| <b>Scale</b>          | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| <b>scale</b>          | -10 | -5 | ... | 10 |
| <b>Exp. scale</b>     | -10 | -5 | ... | 10 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Int2Real.

| Test results                 |     |    |     |    |
|------------------------------|-----|----|-----|----|
| <b>Time step</b>             | 1   | 2  | ... | 15 |
| <i>Mask parameters</i>       |     |    |     |    |
| <b>Scale</b>                 | -10 | -5 | ... | 10 |
| <i>Controller parameters</i> |     |    |     |    |
| <b>scale</b>                 | -10 | -5 | ... | 10 |
| <b>Exp. scale</b>            | -10 | -5 | ... | 10 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 3,0000e-09$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 417 |
| Max CPU cycles  | 442 |
| Avg CPU cycles  | 419 |



**Verification: Int2Real Bool\_Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block Int2Real.

| Test results   |      |       |     |     |
|----------------|------|-------|-----|-----|
| Time step      | 1    | 2     | ... | 5   |
| CPU cycles     | 40   | 40    | ... | 40  |
| Inputs         |      |       |     |     |
| In (DSP)       | 0    | 0     | ... | 1   |
| In             | -3.1 | -0.31 | ... | 3.3 |
| Parameters     |      |       |     |     |
| Scale          | 10   |       |     |     |
| Outputs        |      |       |     |     |
| Out            | 0    | 0     | ... | 10  |
| Exp. Out       | 0    | 0     | ... | 10  |
| Out (DSP)      | 0    | 0     | ... | 10  |
| Exp. Out (DSP) | 0    | 0     | ... | 10  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 40 |
| Max CPU cycles  | 40 |
| Avg CPU cycles  | 40 |

**Test case: Parameter test****OK**

Parameter test for General block Int2Real.

| Test results   |     |    |     |    |
|----------------|-----|----|-----|----|
| Time step      | 1   | 2  | ... | 15 |
| CPU cycles     | 40  | 40 | ... | 40 |
| Inputs         |     |    |     |    |
| In (DSP)       | 1   |    |     |    |
| In             | 1.1 |    |     |    |
| Parameters     |     |    |     |    |
| Scale          | -10 | -5 | ... | 10 |
| Outputs        |     |    |     |    |
| Out            | -10 | -5 | ... | 10 |
| Exp. Out       | -10 | -5 | ... | 10 |
| Out (DSP)      | -10 | -5 | ... | 10 |
| Exp. Out (DSP) | -10 | -5 | ... | 10 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 4,6566e-09$ ( $\pm 10$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 40 |
| Max CPU cycles  | 40 |
| Avg CPU cycles  | 40 |

#### Test case: Conversion test

OK

Conversion test for General block Int2Real.

| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| Time step             | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| Scale                 | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| scale                 | -10 | -5 | ... | 10 |
| Exp. scale            | -10 | -5 | ... | 10 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Int2Real.


| Test results          |     |    |     |    |
|-----------------------|-----|----|-----|----|
| <b>Time step</b>      | 1   | 2  | ... | 15 |
| Mask parameters       |     |    |     |    |
| <b>Scale</b>          | -10 | -5 | ... | 10 |
| Controller parameters |     |    |     |    |
| <b>scale</b>          | -10 | -5 | ... | 10 |
| <b>Exp. scale</b>     | -10 | -5 | ... | 10 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 3,0000e-09$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 637 |
| Max CPU cycles  | 640 |
| Avg CPU cycles  | 637 |

## Block: Limitation

---



Limits the input signal to min and max\_sci.

Caution: For correct computation the upper limit max has to be greater than the lower limit min!

| Inports |              |
|---------|--------------|
| In      | Input signal |
| max     | Upper limit  |
| min     | Lower limit  |

| Outports |                      |
|----------|----------------------|
| Out      | Limited input signal |

### Description:

Calculation:

$$\text{Out} = \begin{cases} \text{max} & \text{In} > \text{max} \\ \text{In} & \\ \text{min} & \text{In} < \text{min} \end{cases}$$

### Implementations:

- FiP16** 16 Bit Fixed Point Implementation
- FiP32** 32 Bit Fixed Point Implementation
- Float32** 32 Bit Floating Point Implementation
- Float64** 64 Bit Floating Point Implementation

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |
| max               | int16 |
| min               | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |
| max               | int32 |
| min               | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |
| max               | float32 |
| min               | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |
| max               | float64 |
| min               | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: Limitation FiP16 CPU TMS320F28335**

Date of Test 2026-06-19  
Target controller TMS320F28335

**Test case: Inport test****OK**

Inport test for General block Limitation.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 159    |
| CPU cycles     | 72     | 72     | 72     | 72     | ... | 72     |
| Inputs         |        |        |        |        |     |        |
| In (DSP)       | -32768 | -31508 | -30247 | -28987 | ... | 19661  |
| max (DSP)      | 9830   | 9830   | 9830   | 9830   | ... | 32767  |
| min (DSP)      | -13107 | -13107 | -13107 | -13107 | ... | -32768 |
| In             | -1     | -0.962 | -0.923 | -0.885 | ... | 0.6    |
| max            | 0.3    | 0.3    | 0.3    | 0.3    | ... | 1      |
| min            | -0.4   | -0.4   | -0.4   | -0.4   | ... | -1     |
| Outputs        |        |        |        |        |     |        |
| Out            | -0.4   | -0.4   | -0.4   | -0.4   | ... | 0.6    |
| Exp. Out       | -0.4   | -0.4   | -0.4   | -0.4   | ... | 0.6    |
| Out (DSP)      | -13107 | -13107 | -13107 | -13107 | ... | 19661  |
| Exp. Out (DSP) | -13107 | -13107 | -13107 | -13107 | ... | 19661  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 67 |
| Max CPU cycles  | 72 |
| Avg CPU cycles  | 69 |

**Verification: Limitation FiP16 CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block Limitation.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 159    |
| CPU cycles     | 35     | 35     | 35     | 35     | ... | 35     |
| Inputs         |        |        |        |        |     |        |
| In (DSP)       | -32768 | -31508 | -30247 | -28987 | ... | 19661  |
| max (DSP)      | 9830   | 9830   | 9830   | 9830   | ... | 32767  |
| min (DSP)      | -13107 | -13107 | -13107 | -13107 | ... | -32768 |
| In             | -1     | -0.962 | -0.923 | -0.885 | ... | 0.6    |
| max            | 0.3    | 0.3    | 0.3    | 0.3    | ... | 1      |
| min            | -0.4   | -0.4   | -0.4   | -0.4   | ... | -1     |
| Outputs        |        |        |        |        |     |        |
| Out            | -0.4   | -0.4   | -0.4   | -0.4   | ... | 0.6    |
| Exp. Out       | -0.4   | -0.4   | -0.4   | -0.4   | ... | 0.6    |
| Out (DSP)      | -13107 | -13107 | -13107 | -13107 | ... | 19661  |
| Exp. Out (DSP) | -13107 | -13107 | -13107 | -13107 | ... | 19661  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 35 |
| Avg CPU cycles  | 32 |

**Verification: Limitation FiP16 CPU STM32G474RE**

Date of Test 2026-06-19  
Target controller STM32G474RE

**Test case: Inport test****OK**

Inport test for General block Limitation.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 159    |
| CPU cycles     | 68     | 68     | 68     | 68     | ... | 68     |
| Inputs         |        |        |        |        |     |        |
| In (DSP)       | -32768 | -31508 | -30247 | -28987 | ... | 19661  |
| max (DSP)      | 9830   | 9830   | 9830   | 9830   | ... | 32767  |
| min (DSP)      | -13107 | -13107 | -13107 | -13107 | ... | -32768 |
| In             | -1     | -0.962 | -0.923 | -0.885 | ... | 0.6    |
| max            | 0.3    | 0.3    | 0.3    | 0.3    | ... | 1      |
| min            | -0.4   | -0.4   | -0.4   | -0.4   | ... | -1     |
| Outputs        |        |        |        |        |     |        |
| Out            | -0.4   | -0.4   | -0.4   | -0.4   | ... | 0.6    |
| Exp. Out       | -0.4   | -0.4   | -0.4   | -0.4   | ... | 0.6    |
| Out (DSP)      | -13107 | -13107 | -13107 | -13107 | ... | 19661  |
| Exp. Out (DSP) | -13107 | -13107 | -13107 | -13107 | ... | 19661  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 68 |
| Max CPU cycles  | 72 |
| Avg CPU cycles  | 70 |



**Verification: Limitation FiP16 CPU STM32F072RB**

Date of Test 2026-06-19  
Target controller STM32F072RB

**Test case: Inport test****OK**

Inport test for General block Limitation.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 159    |
| CPU cycles     | 63     | 63     | 63     | 63     | ... | 63     |
| Inputs         |        |        |        |        |     |        |
| In (DSP)       | -32768 | -31508 | -30247 | -28987 | ... | 19661  |
| max (DSP)      | 9830   | 9830   | 9830   | 9830   | ... | 32767  |
| min (DSP)      | -13107 | -13107 | -13107 | -13107 | ... | -32768 |
| In             | -1     | -0.962 | -0.923 | -0.885 | ... | 0.6    |
| max            | 0.3    | 0.3    | 0.3    | 0.3    | ... | 1      |
| min            | -0.4   | -0.4   | -0.4   | -0.4   | ... | -1     |
| Outputs        |        |        |        |        |     |        |
| Out            | -0.4   | -0.4   | -0.4   | -0.4   | ... | 0.6    |
| Exp. Out       | -0.4   | -0.4   | -0.4   | -0.4   | ... | 0.6    |
| Out (DSP)      | -13107 | -13107 | -13107 | -13107 | ... | 19661  |
| Exp. Out (DSP) | -13107 | -13107 | -13107 | -13107 | ... | 19661  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 59  |
| Max CPU cycles  | 122 |
| Avg CPU cycles  | 60  |

**Verification: Limitation FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block Limitation.

| Test results          |        |        |        |        |     |        |
|-----------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 159    |
| <b>CPU cycles</b>     | 46     | 46     | 46     | 46     | ... | 45     |
| <i>Inputs</i>         |        |        |        |        |     |        |
| <b>In (DSP)</b>       | -32768 | -31508 | -30247 | -28987 | ... | 19661  |
| <b>max (DSP)</b>      | 9830   | 9830   | 9830   | 9830   | ... | 32767  |
| <b>min (DSP)</b>      | -13107 | -13107 | -13107 | -13107 | ... | -32768 |
| <b>In</b>             | -1     | -0.962 | -0.923 | -0.885 | ... | 0.6    |
| <b>max</b>            | 0.3    | 0.3    | 0.3    | 0.3    | ... | 1      |
| <b>min</b>            | -0.4   | -0.4   | -0.4   | -0.4   | ... | -1     |
| <i>Outputs</i>        |        |        |        |        |     |        |
| <b>Out</b>            | -0.4   | -0.4   | -0.4   | -0.4   | ... | 0.6    |
| <b>Exp. Out</b>       | -0.4   | -0.4   | -0.4   | -0.4   | ... | 0.6    |
| <b>Out (DSP)</b>      | -13107 | -13107 | -13107 | -13107 | ... | 19661  |
| <b>Exp. Out (DSP)</b> | -13107 | -13107 | -13107 | -13107 | ... | 19661  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 37 |
| Max CPU cycles  | 46 |
| Avg CPU cycles  | 40 |

**Verification: Limitation FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block Limitation.

| Test results          |        |        |        |        |     |        |
|-----------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 159    |
| <b>CPU cycles</b>     | 52     | 52     | 52     | 52     | ... | 54     |
| <i>Inputs</i>         |        |        |        |        |     |        |
| <b>In (DSP)</b>       | -32768 | -31508 | -30247 | -28987 | ... | 19661  |
| <b>max (DSP)</b>      | 9830   | 9830   | 9830   | 9830   | ... | 32767  |
| <b>min (DSP)</b>      | -13107 | -13107 | -13107 | -13107 | ... | -32768 |
| <b>In</b>             | -1     | -0.962 | -0.923 | -0.885 | ... | 0.6    |
| <b>max</b>            | 0.3    | 0.3    | 0.3    | 0.3    | ... | 1      |
| <b>min</b>            | -0.4   | -0.4   | -0.4   | -0.4   | ... | -1     |
| <i>Outputs</i>        |        |        |        |        |     |        |
| <b>Out</b>            | -0.4   | -0.4   | -0.4   | -0.4   | ... | 0.6    |
| <b>Exp. Out</b>       | -0.4   | -0.4   | -0.4   | -0.4   | ... | 0.6    |
| <b>Out (DSP)</b>      | -13107 | -13107 | -13107 | -13107 | ... | 19661  |
| <b>Exp. Out (DSP)</b> | -13107 | -13107 | -13107 | -13107 | ... | 19661  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 50 |
| Max CPU cycles  | 54 |
| Avg CPU cycles  | 51 |

**Verification: Limitation FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block Limitation.

| Test results          |        |        |        |        |     |        |
|-----------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 159    |
| <b>CPU cycles</b>     | 80     | 69     | 69     | 69     | ... | 69     |
| <i>Inputs</i>         |        |        |        |        |     |        |
| <b>In (DSP)</b>       | -32768 | -31508 | -30247 | -28987 | ... | 19661  |
| <b>max (DSP)</b>      | 9830   | 9830   | 9830   | 9830   | ... | 32767  |
| <b>min (DSP)</b>      | -13107 | -13107 | -13107 | -13107 | ... | -32768 |
| <b>In</b>             | -1     | -0.962 | -0.923 | -0.885 | ... | 0.6    |
| <b>max</b>            | 0.3    | 0.3    | 0.3    | 0.3    | ... | 1      |
| <b>min</b>            | -0.4   | -0.4   | -0.4   | -0.4   | ... | -1     |
| <i>Outputs</i>        |        |        |        |        |     |        |
| <b>Out</b>            | -0.4   | -0.4   | -0.4   | -0.4   | ... | 0.6    |
| <b>Exp. Out</b>       | -0.4   | -0.4   | -0.4   | -0.4   | ... | 0.6    |
| <b>Out (DSP)</b>      | -13107 | -13107 | -13107 | -13107 | ... | 19661  |
| <b>Exp. Out (DSP)</b> | -13107 | -13107 | -13107 | -13107 | ... | 19661  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 61 |
| Max CPU cycles  | 80 |
| Avg CPU cycles  | 64 |

**Verification: Limitation FiP16 CPU TMS320F28379D**

Date of Test 2026-06-22  
Target controller TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block Limitation.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 159    |
| CPU cycles     | 52     | 52     | 52     | 52     | ... | 52     |
| Inputs         |        |        |        |        |     |        |
| In (DSP)       | -32768 | -31508 | -30247 | -28987 | ... | 19661  |
| max (DSP)      | 9830   | 9830   | 9830   | 9830   | ... | 32767  |
| min (DSP)      | -13107 | -13107 | -13107 | -13107 | ... | -32768 |
| In             | -1     | -0.962 | -0.923 | -0.885 | ... | 0.6    |
| max            | 0.3    | 0.3    | 0.3    | 0.3    | ... | 1      |
| min            | -0.4   | -0.4   | -0.4   | -0.4   | ... | -1     |
| Outputs        |        |        |        |        |     |        |
| Out            | -0.4   | -0.4   | -0.4   | -0.4   | ... | 0.6    |
| Exp. Out       | -0.4   | -0.4   | -0.4   | -0.4   | ... | 0.6    |
| Out (DSP)      | -13107 | -13107 | -13107 | -13107 | ... | 19661  |
| Exp. Out (DSP) | -13107 | -13107 | -13107 | -13107 | ... | 19661  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 52 |
| Max CPU cycles  | 56 |
| Avg CPU cycles  | 54 |

**Verification: Limitation FiP32 CPU TMS320F28335**

Date of Test 2026-06-19  
Target controller TMS320F28335

**Test case: Inport test****OK**

Inport test for General block Limitation.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 159         |
| CPU cycles     | 76          | 76          | ... | 76          |
| Inputs         |             |             |     |             |
| In (DSP)       | -2147483648 | -2064888123 | ... | 1288490189  |
| max (DSP)      | 644245094   | 644245094   | ... | 2147483647  |
| min (DSP)      | -858993459  | -858993459  | ... | -2147483648 |
| In             | -1          | -0.962      | ... | 0.6         |
| max            | 0.3         | 0.3         | ... | 1           |
| min            | -0.4        | -0.4        | ... | -1          |
| Outputs        |             |             |     |             |
| Out            | -0.4        | -0.4        | ... | 0.6         |
| Exp. Out       | -0.4        | -0.4        | ... | 0.6         |
| Out (DSP)      | -858993459  | -858993459  | ... | 1288490189  |
| Exp. Out (DSP) | -858993459  | -858993459  | ... | 1288490189  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 70 |
| Max CPU cycles  | 76 |
| Avg CPU cycles  | 72 |

**Verification: Limitation FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block Limitation.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>      | 1           | 2           | ... | 159         |
| <b>CPU cycles</b>     | 35          | 35          | ... | 37          |
| <i>Inputs</i>         |             |             |     |             |
| <b>In (DSP)</b>       | -2147483648 | -2064888123 | ... | 1288490189  |
| <b>max (DSP)</b>      | 644245094   | 644245094   | ... | 2147483647  |
| <b>min (DSP)</b>      | -858993459  | -858993459  | ... | -2147483648 |
| <b>In</b>             | -1          | -0.962      | ... | 0.6         |
| <b>max</b>            | 0.3         | 0.3         | ... | 1           |
| <b>min</b>            | -0.4        | -0.4        | ... | -1          |
| <i>Outputs</i>        |             |             |     |             |
| <b>Out</b>            | -0.4        | -0.4        | ... | 0.6         |
| <b>Exp. Out</b>       | -0.4        | -0.4        | ... | 0.6         |
| <b>Out (DSP)</b>      | -858993459  | -858993459  | ... | 1288490189  |
| <b>Exp. Out (DSP)</b> | -858993459  | -858993459  | ... | 1288490189  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 37 |
| Avg CPU cycles  | 33 |

**Verification: Limitation FiP32 CPU STM32G474RE**

Date of Test 2026-06-19  
Target controller STM32G474RE

**Test case: Inport test****OK**

Inport test for General block Limitation.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 159         |
| CPU cycles     | 67          | 67          | ... | 67          |
| Inputs         |             |             |     |             |
| In (DSP)       | -2147483648 | -2064888123 | ... | 1288490189  |
| max (DSP)      | 644245094   | 644245094   | ... | 2147483647  |
| min (DSP)      | -858993459  | -858993459  | ... | -2147483648 |
| In             | -1          | -0.962      | ... | 0.6         |
| max            | 0.3         | 0.3         | ... | 1           |
| min            | -0.4        | -0.4        | ... | -1          |
| Outputs        |             |             |     |             |
| Out            | -0.4        | -0.4        | ... | 0.6         |
| Exp. Out       | -0.4        | -0.4        | ... | 0.6         |
| Out (DSP)      | -858993459  | -858993459  | ... | 1288490189  |
| Exp. Out (DSP) | -858993459  | -858993459  | ... | 1288490189  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 67  |
| Max CPU cycles  | 118 |
| Avg CPU cycles  | 67  |



**Verification: Limitation FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block Limitation.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>      | 1           | 2           | ... | 159         |
| <b>CPU cycles</b>     | 60          | 60          | ... | 60          |
| <i>Inputs</i>         |             |             |     |             |
| <b>In (DSP)</b>       | -2147483648 | -2064888123 | ... | 1288490189  |
| <b>max (DSP)</b>      | 644245094   | 644245094   | ... | 2147483647  |
| <b>min (DSP)</b>      | -858993459  | -858993459  | ... | -2147483648 |
| <b>In</b>             | -1          | -0.962      | ... | 0.6         |
| <b>max</b>            | 0.3         | 0.3         | ... | 1           |
| <b>min</b>            | -0.4        | -0.4        | ... | -1          |
| <i>Outputs</i>        |             |             |     |             |
| <b>Out</b>            | -0.4        | -0.4        | ... | 0.6         |
| <b>Exp. Out</b>       | -0.4        | -0.4        | ... | 0.6         |
| <b>Out (DSP)</b>      | -858993459  | -858993459  | ... | 1288490189  |
| <b>Exp. Out (DSP)</b> | -858993459  | -858993459  | ... | 1288490189  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 60 |
| Avg CPU cycles  | 58 |

**Verification: Limitation FiP32 CPU PIC32MX170F256**

Date of Test 2026-06-19  
Target controller PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block Limitation.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 159         |
| CPU cycles     | 46          | 46          | ... | 45          |
| Inputs         |             |             |     |             |
| In (DSP)       | -2147483648 | -2064888123 | ... | 1288490189  |
| max (DSP)      | 644245094   | 644245094   | ... | 2147483647  |
| min (DSP)      | -858993459  | -858993459  | ... | -2147483648 |
| In             | -1          | -0.962      | ... | 0.6         |
| max            | 0.3         | 0.3         | ... | 1           |
| min            | -0.4        | -0.4        | ... | -1          |
| Outputs        |             |             |     |             |
| Out            | -0.4        | -0.4        | ... | 0.6         |
| Exp. Out       | -0.4        | -0.4        | ... | 0.6         |
| Out (DSP)      | -858993459  | -858993459  | ... | 1288490189  |
| Exp. Out (DSP) | -858993459  | -858993459  | ... | 1288490189  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 37 |
| Max CPU cycles  | 46 |
| Avg CPU cycles  | 40 |

**Verification: Limitation FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block Limitation.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>      | 1           | 2           | ... | 159         |
| <b>CPU cycles</b>     | 59          | 59          | ... | 60          |
| <i>Inputs</i>         |             |             |     |             |
| <b>In (DSP)</b>       | -2147483648 | -2064888123 | ... | 1288490189  |
| <b>max (DSP)</b>      | 644245094   | 644245094   | ... | 2147483647  |
| <b>min (DSP)</b>      | -858993459  | -858993459  | ... | -2147483648 |
| <b>In</b>             | -1          | -0.962      | ... | 0.6         |
| <b>max</b>            | 0.3         | 0.3         | ... | 1           |
| <b>min</b>            | -0.4        | -0.4        | ... | -1          |
| <i>Outputs</i>        |             |             |     |             |
| <b>Out</b>            | -0.4        | -0.4        | ... | 0.6         |
| <b>Exp. Out</b>       | -0.4        | -0.4        | ... | 0.6         |
| <b>Out (DSP)</b>      | -858993459  | -858993459  | ... | 1288490189  |
| <b>Exp. Out (DSP)</b> | -858993459  | -858993459  | ... | 1288490189  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 55 |
| Max CPU cycles  | 60 |
| Avg CPU cycles  | 56 |

**Verification: Limitation FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block Limitation.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>      | 1           | 2           | ... | 159         |
| <b>CPU cycles</b>     | 66          | 66          | ... | 66          |
| <i>Inputs</i>         |             |             |     |             |
| <b>In (DSP)</b>       | -2147483648 | -2064888123 | ... | 1288490189  |
| <b>max (DSP)</b>      | 644245094   | 644245094   | ... | 2147483647  |
| <b>min (DSP)</b>      | -858993459  | -858993459  | ... | -2147483648 |
| <b>In</b>             | -1          | -0.962      | ... | 0.6         |
| <b>max</b>            | 0.3         | 0.3         | ... | 1           |
| <b>min</b>            | -0.4        | -0.4        | ... | -1          |
| <i>Outputs</i>        |             |             |     |             |
| <b>Out</b>            | -0.4        | -0.4        | ... | 0.6         |
| <b>Exp. Out</b>       | -0.4        | -0.4        | ... | 0.6         |
| <b>Out (DSP)</b>      | -858993459  | -858993459  | ... | 1288490189  |
| <b>Exp. Out (DSP)</b> | -858993459  | -858993459  | ... | 1288490189  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 66 |
| Avg CPU cycles  | 61 |

**Verification: Limitation FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block Limitation.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>      | 1           | 2           | ... | 159         |
| <b>CPU cycles</b>     | 59          | 59          | ... | 63          |
| <i>Inputs</i>         |             |             |     |             |
| <b>In (DSP)</b>       | -2147483648 | -2064888123 | ... | 1288490189  |
| <b>max (DSP)</b>      | 644245094   | 644245094   | ... | 2147483647  |
| <b>min (DSP)</b>      | -858993459  | -858993459  | ... | -2147483648 |
| <b>In</b>             | -1          | -0.962      | ... | 0.6         |
| <b>max</b>            | 0.3         | 0.3         | ... | 1           |
| <b>min</b>            | -0.4        | -0.4        | ... | -1          |
| <i>Outputs</i>        |             |             |     |             |
| <b>Out</b>            | -0.4        | -0.4        | ... | 0.6         |
| <b>Exp. Out</b>       | -0.4        | -0.4        | ... | 0.6         |
| <b>Out (DSP)</b>      | -858993459  | -858993459  | ... | 1288490189  |
| <b>Exp. Out (DSP)</b> | -858993459  | -858993459  | ... | 1288490189  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 58 |
| Max CPU cycles  | 63 |
| Avg CPU cycles  | 59 |

**Verification: Limitation Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block Limitation.

| Test results          |      |        |     |     |
|-----------------------|------|--------|-----|-----|
| <b>Time step</b>      | 1    | 2      | ... | 159 |
| <b>CPU cycles</b>     | 75   | 75     | ... | 75  |
| <i>Inputs</i>         |      |        |     |     |
| <b>In (DSP)</b>       | -1   | -0.962 | ... | 0.6 |
| <b>max (DSP)</b>      | 0.3  | 0.3    | ... | 1   |
| <b>min (DSP)</b>      | -0.4 | -0.4   | ... | -1  |
| <b>In</b>             | -1   | -0.962 | ... | 0.6 |
| <b>max</b>            | 0.3  | 0.3    | ... | 1   |
| <b>min</b>            | -0.4 | -0.4   | ... | -1  |
| <i>Outputs</i>        |      |        |     |     |
| <b>Out</b>            | -0.4 | -0.4   | ... | 0.6 |
| <b>Exp. Out</b>       | -0.4 | -0.4   | ... | 0.6 |
| <b>Out (DSP)</b>      | -0.4 | -0.4   | ... | 0.6 |
| <b>Exp. Out (DSP)</b> | -0.4 | -0.4   | ... | 0.6 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 2,7940e-08$ ( $\pm 60$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 70 |
| Max CPU cycles  | 75 |
| Avg CPU cycles  | 72 |

**Verification: Limitation Float32 CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block Limitation.

| Test results   |      |        |     |     |
|----------------|------|--------|-----|-----|
| Time step      | 1    | 2      | ... | 159 |
| CPU cycles     | 41   | 41     | ... | 41  |
| <i>Inputs</i>  |      |        |     |     |
| In (DSP)       | -1   | -0.962 | ... | 0.6 |
| max (DSP)      | 0.3  | 0.3    | ... | 1   |
| min (DSP)      | -0.4 | -0.4   | ... | -1  |
| In             | -1   | -0.962 | ... | 0.6 |
| max            | 0.3  | 0.3    | ... | 1   |
| min            | -0.4 | -0.4   | ... | -1  |
| <i>Outputs</i> |      |        |     |     |
| Out            | -0.4 | -0.4   | ... | 0.6 |
| Exp. Out       | -0.4 | -0.4   | ... | 0.6 |
| Out (DSP)      | -0.4 | -0.4   | ... | 0.6 |
| Exp. Out (DSP) | -0.4 | -0.4   | ... | 0.6 |

| Test settings |                                         |
|---------------|-----------------------------------------|
| Tolerance Out | $\pm 2,7940\text{e-}08$ ( $\pm 60$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 35 |
| Max CPU cycles  | 41 |
| Avg CPU cycles  | 37 |

**Verification: Limitation Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block Limitation.

| Test results          |      |        |     |     |
|-----------------------|------|--------|-----|-----|
| <b>Time step</b>      | 1    | 2      | ... | 159 |
| <b>CPU cycles</b>     | 77   | 77     | ... | 77  |
| <i>Inputs</i>         |      |        |     |     |
| <b>In (DSP)</b>       | -1   | -0.962 | ... | 0.6 |
| <b>max (DSP)</b>      | 0.3  | 0.3    | ... | 1   |
| <b>min (DSP)</b>      | -0.4 | -0.4   | ... | -1  |
| <b>In</b>             | -1   | -0.962 | ... | 0.6 |
| <b>max</b>            | 0.3  | 0.3    | ... | 1   |
| <b>min</b>            | -0.4 | -0.4   | ... | -1  |
| <i>Outputs</i>        |      |        |     |     |
| <b>Out</b>            | -0.4 | -0.4   | ... | 0.6 |
| <b>Exp. Out</b>       | -0.4 | -0.4   | ... | 0.6 |
| <b>Out (DSP)</b>      | -0.4 | -0.4   | ... | 0.6 |
| <b>Exp. Out (DSP)</b> | -0.4 | -0.4   | ... | 0.6 |

| Test settings |                                         |
|---------------|-----------------------------------------|
| Tolerance Out | $\pm 2,7940\text{e-}08$ ( $\pm 60$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 77 |
| Max CPU cycles  | 77 |
| Avg CPU cycles  | 77 |



**Verification: Limitation Float32 CPU STM32F072RB**

Date of Test 2026-06-19  
Target controller STM32F072RB

**Test case: Inport test****OK**

Inport test for General block Limitation.

| Test results   |      |        |     |     |
|----------------|------|--------|-----|-----|
| Time step      | 1    | 2      | ... | 159 |
| CPU cycles     | 232  | 232    | ... | 234 |
| Inputs         |      |        |     |     |
| In (DSP)       | -1   | -0.962 | ... | 0.6 |
| max (DSP)      | 0.3  | 0.3    | ... | 1   |
| min (DSP)      | -0.4 | -0.4   | ... | -1  |
| In             | -1   | -0.962 | ... | 0.6 |
| max            | 0.3  | 0.3    | ... | 1   |
| min            | -0.4 | -0.4   | ... | -1  |
| Outputs        |      |        |     |     |
| Out            | -0.4 | -0.4   | ... | 0.6 |
| Exp. Out       | -0.4 | -0.4   | ... | 0.6 |
| Out (DSP)      | -0.4 | -0.4   | ... | 0.6 |
| Exp. Out (DSP) | -0.4 | -0.4   | ... | 0.6 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 2,7940e-08$ ( $\pm 60$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 143 |
| Max CPU cycles  | 309 |
| Avg CPU cycles  | 185 |

**Verification: Limitation Float32 CPU PIC32MX170F256**

Date of Test 2026-06-19  
Target controller PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block Limitation.

| Test results   |      |        |     |     |
|----------------|------|--------|-----|-----|
| Time step      | 1    | 2      | ... | 159 |
| CPU cycles     | 126  | 126    | ... | 125 |
| Inputs         |      |        |     |     |
| In (DSP)       | -1   | -0.962 | ... | 0.6 |
| max (DSP)      | 0.3  | 0.3    | ... | 1   |
| min (DSP)      | -0.4 | -0.4   | ... | -1  |
| In             | -1   | -0.962 | ... | 0.6 |
| max            | 0.3  | 0.3    | ... | 1   |
| min            | -0.4 | -0.4   | ... | -1  |
| Outputs        |      |        |     |     |
| Out            | -0.4 | -0.4   | ... | 0.6 |
| Exp. Out       | -0.4 | -0.4   | ... | 0.6 |
| Out (DSP)      | -0.4 | -0.4   | ... | 0.6 |
| Exp. Out (DSP) | -0.4 | -0.4   | ... | 0.6 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 2,7940e-08$ ( $\pm 60$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 89  |
| Max CPU cycles  | 128 |
| Avg CPU cycles  | 104 |

**Verification: Limitation Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block Limitation.

| Test results          |      |        |     |     |
|-----------------------|------|--------|-----|-----|
| <b>Time step</b>      | 1    | 2      | ... | 159 |
| <b>CPU cycles</b>     | 265  | 265    | ... | 264 |
| <i>Inputs</i>         |      |        |     |     |
| <b>In (DSP)</b>       | -1   | -0.962 | ... | 0.6 |
| <b>max (DSP)</b>      | 0.3  | 0.3    | ... | 1   |
| <b>min (DSP)</b>      | -0.4 | -0.4   | ... | -1  |
| <b>In</b>             | -1   | -0.962 | ... | 0.6 |
| <b>max</b>            | 0.3  | 0.3    | ... | 1   |
| <b>min</b>            | -0.4 | -0.4   | ... | -1  |
| <i>Outputs</i>        |      |        |     |     |
| <b>Out</b>            | -0.4 | -0.4   | ... | 0.6 |
| <b>Exp. Out</b>       | -0.4 | -0.4   | ... | 0.6 |
| <b>Out (DSP)</b>      | -0.4 | -0.4   | ... | 0.6 |
| <b>Exp. Out (DSP)</b> | -0.4 | -0.4   | ... | 0.6 |

| Test settings |                                         |
|---------------|-----------------------------------------|
| Tolerance Out | $\pm 2,7940\text{e-}08$ ( $\pm 60$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 162 |
| Max CPU cycles  | 269 |
| Avg CPU cycles  | 204 |

**Verification: Limitation Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block Limitation.

| Test results          |      |        |     |     |
|-----------------------|------|--------|-----|-----|
| <b>Time step</b>      | 1    | 2      | ... | 159 |
| <b>CPU cycles</b>     | 81   | 70     | ... | 70  |
| <i>Inputs</i>         |      |        |     |     |
| <b>In (DSP)</b>       | -1   | -0.962 | ... | 0.6 |
| <b>max (DSP)</b>      | 0.3  | 0.3    | ... | 1   |
| <b>min (DSP)</b>      | -0.4 | -0.4   | ... | -1  |
| <b>In</b>             | -1   | -0.962 | ... | 0.6 |
| <b>max</b>            | 0.3  | 0.3    | ... | 1   |
| <b>min</b>            | -0.4 | -0.4   | ... | -1  |
| <i>Outputs</i>        |      |        |     |     |
| <b>Out</b>            | -0.4 | -0.4   | ... | 0.6 |
| <b>Exp. Out</b>       | -0.4 | -0.4   | ... | 0.6 |
| <b>Out (DSP)</b>      | -0.4 | -0.4   | ... | 0.6 |
| <b>Exp. Out (DSP)</b> | -0.4 | -0.4   | ... | 0.6 |

| Test settings |                                         |
|---------------|-----------------------------------------|
| Tolerance Out | $\pm 2,7940\text{e-}08$ ( $\pm 60$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 63 |
| Max CPU cycles  | 81 |
| Avg CPU cycles  | 65 |

**Verification: Limitation Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block Limitation.


| Test results          |      |        |     |     |
|-----------------------|------|--------|-----|-----|
| <b>Time step</b>      | 1    | 2      | ... | 159 |
| <b>CPU cycles</b>     | 61   | 61     | ... | 61  |
| <i>Inputs</i>         |      |        |     |     |
| <b>In (DSP)</b>       | -1   | -0.962 | ... | 0.6 |
| <b>max (DSP)</b>      | 0.3  | 0.3    | ... | 1   |
| <b>min (DSP)</b>      | -0.4 | -0.4   | ... | -1  |
| <b>In</b>             | -1   | -0.962 | ... | 0.6 |
| <b>max</b>            | 0.3  | 0.3    | ... | 1   |
| <b>min</b>            | -0.4 | -0.4   | ... | -1  |
| <i>Outputs</i>        |      |        |     |     |
| <b>Out</b>            | -0.4 | -0.4   | ... | 0.6 |
| <b>Exp. Out</b>       | -0.4 | -0.4   | ... | 0.6 |
| <b>Out (DSP)</b>      | -0.4 | -0.4   | ... | 0.6 |
| <b>Exp. Out (DSP)</b> | -0.4 | -0.4   | ... | 0.6 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 2,7940e-08$ ( $\pm 60$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 54 |
| Max CPU cycles  | 61 |
| Avg CPU cycles  | 56 |

## Block: LookupTable

---



Look-up Table with 256+1 values.

Note: 257th value is used for preventing index overflow during interpolation.

-> for periodic signals the 257th value should be set equal to 1st value

-> for non-periodic signals the 257th value should be set equal to 256th value

| Inports |             |
|---------|-------------|
| In      | Table index |

| Outputs |              |
|---------|--------------|
| Out     | Table output |

| Mask Parameters |    |               |
|-----------------|----|---------------|
| Name            | ID | Description   |
| Lookup          | 1  | Look-up Table |

### Implementations:

- FiP8**      8 Bit Fixed Point Implementation
- FiP16**    16 Bit Fixed Point Implementation
- FiP32**    32 Bit Fixed Point Implementation

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | int8 |

| Outputs Data Type |      |
|-------------------|------|
| Out               | int8 |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |


### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

# Block: LookupTable1D



One dimensional look-up table with selectable number of data points.  
Table data must be an array of size DimX. If one of the RAM implementations is used, DimX must not exceed 257.  
If input is out of specified range, output will be cut off (no extrapolation).

| Inports |                            |
|---------|----------------------------|
| x       | Table index in x direction |

| Outports |              |
|----------|--------------|
| Out      | Table output |

| Mask Parameters |    |                                                      |
|-----------------|----|------------------------------------------------------|
| Name            | ID | Description                                          |
| TableData       | 1  | Look-up table data                                   |
| DimX            | 2  | Number of data points in x-direction                 |
| x_min           | 3  | Minimum input value of x-dimension for look-up table |
| x_max           | 4  | Maximum input value of x-dimension for look-up table |


## Description:

The table of the LookupTable1D block must contain DimX data points and they have to be arranged as


$$\text{TableData} = [f(x_1), f(x_2), \dots f(x_{n-1}), f(x_n)]$$

with n as the selected DimX value.  
For periodic signals, the last entry must be identical to the first entry, see the example in the following figure.





For non-periodic signals there is no restriction regarding the last data point, see the example in the figure below.



### Implementations:

|                    |                                                                                 |
|--------------------|---------------------------------------------------------------------------------|
| <b>FiP16</b>       | 64 Bit Floating Point Implementation with look-up table located in RAM          |
| <b>FiP32</b>       | 32 Bit Fixed Point Implementation with look-up table located in Flash memory    |
| <b>Float32</b>     | 32 Bit Floating Point Implementation with look-up table located in Flash memory |
| <b>Float64</b>     | 64 Bit Floating Point Implementation with look-up table located in Flash memory |
| <b>FiP16_RAM</b>   | 16 Bit Fixed Point Implementation with look-up table located in RAM             |
| <b>FiP32_RAM</b>   | 32 Bit Fixed Point Implementation with look-up table located in RAM             |
| <b>Float32_RAM</b> | 32 Bit Floating Point Implementation with look-up table located in RAM          |
| <b>Float64_RAM</b> | 64 Bit Floating Point Implementation with look-up table located in RAM          |

### Implementation: FiP16

64 Bit Floating Point Implementation with look-up table located in RAM

| Inports Data Type |       |
|-------------------|-------|
| x                 | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation with look-up table located in Flash memory

| Inports Data Type |       |
|-------------------|-------|
| x                 | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation with look-up table located in Flash memory

| Inports Data Type |         |
|-------------------|---------|
| x                 | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation with look-up table located in Flash memory

| Inports Data Type |         |
|-------------------|---------|
| x                 | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

### Implementation: FiP16\_RAM

16 Bit Fixed Point Implementation with look-up table located in RAM

| Inports Data Type |       |
|-------------------|-------|
| x                 | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32\_RAM

32 Bit Fixed Point Implementation with look-up table located in RAM

| Inports Data Type |       |
|-------------------|-------|
| x                 | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32\_RAM

32 Bit Floating Point Implementation with look-up table located in RAM

| Inports Data Type |         |
|-------------------|---------|
| x                 | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

## Implementation: Float64\_RAM

---

64 Bit Floating Point Implementation with look-up table located in RAM

| Inports Data Type |         |
|-------------------|---------|
| x                 | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: LookupTable1D FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block LookupTable1D.

| Test results   |         |        |        |        |     |        |
|----------------|---------|--------|--------|--------|-----|--------|
| Time step      | 1       | 2      | 3      | 4      | ... | 67     |
| CPU cycles     | 105     | 105    | 105    | 105    | ... | 116    |
| Inputs         |         |        |        |        |     |        |
| x (DSP)        | -32768  | -31775 | -30782 | -29789 | ... | 32767  |
| x              | -1      | -0.97  | -0.939 | -0.909 | ... | 1      |
| Parameters     |         |        |        |        |     |        |
| TableData      | [1x257] |        |        |        |     |        |
| DimX           | 257     |        |        |        |     |        |
| x_min          | -0.8    |        |        |        |     |        |
| x_max          | 0.7     |        |        |        |     |        |
| Outputs        |         |        |        |        |     |        |
| Out            | 0.8     | 0.8    | 0.8    | 0.8    | ... | -0.7   |
| Exp. Out       | 0.8     | 0.8    | 0.8    | 0.8    | ... | -0.7   |
| Out (DSP)      | 26213   | 26213  | 26213  | 26213  | ... | -22938 |
| Exp. Out (DSP) | 26214   | 26214  | 26214  | 26214  | ... | -22938 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 105 |
| Max CPU cycles  | 123 |
| Avg CPU cycles  | 120 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable1D.

| Test results                 |        |        |        |
|------------------------------|--------|--------|--------|
| Time step                    | 1      | 2      | 3      |
| <i>Mask parameters</i>       |        |        |        |
| <b>TableData</b>             | [1x17] | [1x33] | [1x65] |
| <b>DimX</b>                  | 17     | 33     | 65     |
| <b>x_min</b>                 | -0.5   | -0.5   | -0.5   |
| <b>x_max</b>                 | 0.7    | 0.7    | 0.7    |
| <i>Controller parameters</i> |        |        |        |
| <b>gainX</b>                 | 27307  | 27307  | 27307  |
| <b>offsetX</b>               | 3277   | 3277   | 3277   |
| <b>maskX</b>                 | 4095   | 2047   | 1023   |
| <b>Table</b>                 | [1x17] | [1x33] | [1x65] |
| <b>minX</b>                  | -16384 | -16384 | -16384 |
| <b>maxX</b>                  | 22938  | 22938  | 22938  |
| <b>sfrX</b>                  | 12     | 11     | 10     |
| <b>gainXsfr</b>              | 14     | 14     | 14     |
| <b>idxOffsetX</b>            | 8      | 16     | 32     |
| <b>Exp. gainX</b>            | 27307  | 27307  | 27307  |
| <b>Exp. offsetX</b>          | 3277   | 3277   | 3277   |
| <b>Exp. maskX</b>            | 4095   | 2047   | 1023   |
| <b>Exp. Table</b>            | [1x17] | [1x33] | [1x65] |
| <b>Exp. minX</b>             | -16384 | -16384 | -16384 |
| <b>Exp. maxX</b>             | 22938  | 22938  | 22938  |
| <b>Exp. sfrX</b>             | 12     | 11     | 10     |
| <b>Exp. gainXsfr</b>         | 14     | 14     | 14     |
| <b>Exp. idxOffsetX</b>       | 8      | 16     | 32     |

| Test settings        |             |
|----------------------|-------------|
| Tolerance gainX      | ±0,0000e+00 |
| Tolerance offsetX    | ±0,0000e+00 |
| Tolerance maskX      | ±0,0000e+00 |
| Tolerance Table      | ±0,0000e+00 |
| Tolerance minX       | ±0,0000e+00 |
| Tolerance maxX       | ±0,0000e+00 |
| Tolerance sfrX       | ±0,0000e+00 |
| Tolerance gainXsfr   | ±0,0000e+00 |
| Tolerance idxOffsetX | ±0,0000e+00 |

**Verification: LookupTable1D FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block LookupTable1D.

| Test results   |         |        |        |        |     |        |
|----------------|---------|--------|--------|--------|-----|--------|
| Time step      | 1       | 2      | 3      | 4      | ... | 67     |
| CPU cycles     | 63      | 63     | 63     | 63     | ... | 69     |
| Inputs         |         |        |        |        |     |        |
| x (DSP)        | -32768  | -31775 | -30782 | -29789 | ... | 32767  |
| x              | -1      | -0.97  | -0.939 | -0.909 | ... | 1      |
| Parameters     |         |        |        |        |     |        |
| TableData      | [1x257] |        |        |        |     |        |
| DimX           | 257     |        |        |        |     |        |
| x_min          | -0.8    |        |        |        |     |        |
| x_max          | 0.7     |        |        |        |     |        |
| Outputs        |         |        |        |        |     |        |
| Out            | 0.8     | 0.8    | 0.8    | 0.8    | ... | -0.7   |
| Exp. Out       | 0.8     | 0.8    | 0.8    | 0.8    | ... | -0.7   |
| Out (DSP)      | 26213   | 26213  | 26213  | 26213  | ... | -22938 |
| Exp. Out (DSP) | 26214   | 26214  | 26214  | 26214  | ... | -22938 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 63 |
| Max CPU cycles  | 79 |
| Avg CPU cycles  | 75 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable1D.

| Test results                 |        |        |        |
|------------------------------|--------|--------|--------|
| Time step                    | 1      | 2      | 3      |
| <i>Mask parameters</i>       |        |        |        |
| <b>TableData</b>             | [1x17] | [1x33] | [1x65] |
| <b>DimX</b>                  | 17     | 33     | 65     |
| <b>x_min</b>                 | -0.5   | -0.5   | -0.5   |
| <b>x_max</b>                 | 0.7    | 0.7    | 0.7    |
| <i>Controller parameters</i> |        |        |        |
| <b>gainX</b>                 | 27307  | 27307  | 27307  |
| <b>offsetX</b>               | 3277   | 3277   | 3277   |
| <b>maskX</b>                 | 4095   | 2047   | 1023   |
| <b>Table</b>                 | [1x17] | [1x33] | [1x65] |
| <b>minX</b>                  | -16384 | -16384 | -16384 |
| <b>maxX</b>                  | 22938  | 22938  | 22938  |
| <b>sfrX</b>                  | 12     | 11     | 10     |
| <b>gainXsfr</b>              | 14     | 14     | 14     |
| <b>idxOffsetX</b>            | 8      | 16     | 32     |
| <b>Exp. gainX</b>            | 27307  | 27307  | 27307  |
| <b>Exp. offsetX</b>          | 3277   | 3277   | 3277   |
| <b>Exp. maskX</b>            | 4095   | 2047   | 1023   |
| <b>Exp. Table</b>            | [1x17] | [1x33] | [1x65] |
| <b>Exp. minX</b>             | -16384 | -16384 | -16384 |
| <b>Exp. maxX</b>             | 22938  | 22938  | 22938  |
| <b>Exp. sfrX</b>             | 12     | 11     | 10     |
| <b>Exp. gainXsfr</b>         | 14     | 14     | 14     |
| <b>Exp. idxOffsetX</b>       | 8      | 16     | 32     |

| Test settings        |             |
|----------------------|-------------|
| Tolerance gainX      | ±0,0000e+00 |
| Tolerance offsetX    | ±0,0000e+00 |
| Tolerance maskX      | ±0,0000e+00 |
| Tolerance Table      | ±0,0000e+00 |
| Tolerance minX       | ±0,0000e+00 |
| Tolerance maxX       | ±0,0000e+00 |
| Tolerance sfrX       | ±0,0000e+00 |
| Tolerance gainXsfr   | ±0,0000e+00 |
| Tolerance idxOffsetX | ±0,0000e+00 |



**Verification: LookupTable1D FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block LookupTable1D.

| Test results   |         |        |        |        |     |        |
|----------------|---------|--------|--------|--------|-----|--------|
| Time step      | 1       | 2      | 3      | 4      | ... | 67     |
| CPU cycles     | 118     | 118    | 118    | 118    | ... | 118    |
| Inputs         |         |        |        |        |     |        |
| x (DSP)        | -32768  | -31775 | -30782 | -29789 | ... | 32767  |
| x              | -1      | -0.97  | -0.939 | -0.909 | ... | 1      |
| Parameters     |         |        |        |        |     |        |
| TableData      | [1x257] |        |        |        |     |        |
| DimX           | 257     |        |        |        |     |        |
| x_min          | -0.8    |        |        |        |     |        |
| x_max          | 0.7     |        |        |        |     |        |
| Outputs        |         |        |        |        |     |        |
| Out            | 0.8     | 0.8    | 0.8    | 0.8    | ... | -0.7   |
| Exp. Out       | 0.8     | 0.8    | 0.8    | 0.8    | ... | -0.7   |
| Out (DSP)      | 26213   | 26213  | 26213  | 26213  | ... | -22938 |
| Exp. Out (DSP) | 26214   | 26214  | 26214  | 26214  | ... | -22938 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 118 |
| Max CPU cycles  | 146 |
| Avg CPU cycles  | 136 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable1D.

| Test results                 |        |        |        |
|------------------------------|--------|--------|--------|
| Time step                    | 1      | 2      | 3      |
| <i>Mask parameters</i>       |        |        |        |
| <b>TableData</b>             | [1x17] | [1x33] | [1x65] |
| <b>DimX</b>                  | 17     | 33     | 65     |
| <b>x_min</b>                 | -0.5   | -0.5   | -0.5   |
| <b>x_max</b>                 | 0.7    | 0.7    | 0.7    |
| <i>Controller parameters</i> |        |        |        |
| <b>gainX</b>                 | 27307  | 27307  | 27307  |
| <b>offsetX</b>               | 3277   | 3277   | 3277   |
| <b>maskX</b>                 | 4095   | 2047   | 1023   |
| <b>Table</b>                 | [1x17] | [1x33] | [1x65] |
| <b>minX</b>                  | -16384 | -16384 | -16384 |
| <b>maxX</b>                  | 22938  | 22938  | 22938  |
| <b>sfrX</b>                  | 12     | 11     | 10     |
| <b>gainXsfr</b>              | 14     | 14     | 14     |
| <b>idxOffsetX</b>            | 8      | 16     | 32     |
| <b>Exp. gainX</b>            | 27307  | 27307  | 27307  |
| <b>Exp. offsetX</b>          | 3277   | 3277   | 3277   |
| <b>Exp. maskX</b>            | 4095   | 2047   | 1023   |
| <b>Exp. Table</b>            | [1x17] | [1x33] | [1x65] |
| <b>Exp. minX</b>             | -16384 | -16384 | -16384 |
| <b>Exp. maxX</b>             | 22938  | 22938  | 22938  |
| <b>Exp. sfrX</b>             | 12     | 11     | 10     |
| <b>Exp. gainXsfr</b>         | 14     | 14     | 14     |
| <b>Exp. idxOffsetX</b>       | 8      | 16     | 32     |

| Test settings        |             |
|----------------------|-------------|
| Tolerance gainX      | ±0,0000e+00 |
| Tolerance offsetX    | ±0,0000e+00 |
| Tolerance maskX      | ±0,0000e+00 |
| Tolerance Table      | ±0,0000e+00 |
| Tolerance minX       | ±0,0000e+00 |
| Tolerance maxX       | ±0,0000e+00 |
| Tolerance sfrX       | ±0,0000e+00 |
| Tolerance gainXsfr   | ±0,0000e+00 |
| Tolerance idxOffsetX | ±0,0000e+00 |

**Verification: LookupTable1D FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block LookupTable1D.

| Test results   |         |        |        |        |     |        |
|----------------|---------|--------|--------|--------|-----|--------|
| Time step      | 1       | 2      | 3      | 4      | ... | 67     |
| CPU cycles     | 98      | 98     | 98     | 98     | ... | 101    |
| Inputs         |         |        |        |        |     |        |
| x (DSP)        | -32768  | -31775 | -30782 | -29789 | ... | 32767  |
| x              | -1      | -0.97  | -0.939 | -0.909 | ... | 1      |
| Parameters     |         |        |        |        |     |        |
| TableData      | [1x257] |        |        |        |     |        |
| DimX           | 257     |        |        |        |     |        |
| x_min          | -0.8    |        |        |        |     |        |
| x_max          | 0.7     |        |        |        |     |        |
| Outputs        |         |        |        |        |     |        |
| Out            | 0.8     | 0.8    | 0.8    | 0.8    | ... | -0.7   |
| Exp. Out       | 0.8     | 0.8    | 0.8    | 0.8    | ... | -0.7   |
| Out (DSP)      | 26213   | 26213  | 26213  | 26213  | ... | -22938 |
| Exp. Out (DSP) | 26214   | 26214  | 26214  | 26214  | ... | -22938 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 98  |
| Max CPU cycles  | 175 |
| Avg CPU cycles  | 112 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable1D.

| Test results                 |        |        |        |
|------------------------------|--------|--------|--------|
| Time step                    | 1      | 2      | 3      |
| <i>Mask parameters</i>       |        |        |        |
| <b>TableData</b>             | [1x17] | [1x33] | [1x65] |
| <b>DimX</b>                  | 17     | 33     | 65     |
| <b>x_min</b>                 | -0.5   | -0.5   | -0.5   |
| <b>x_max</b>                 | 0.7    | 0.7    | 0.7    |
| <i>Controller parameters</i> |        |        |        |
| <b>gainX</b>                 | 27307  | 27307  | 27307  |
| <b>offsetX</b>               | 3277   | 3277   | 3277   |
| <b>maskX</b>                 | 4095   | 2047   | 1023   |
| <b>Table</b>                 | [1x17] | [1x33] | [1x65] |
| <b>minX</b>                  | -16384 | -16384 | -16384 |
| <b>maxX</b>                  | 22938  | 22938  | 22938  |
| <b>sfrX</b>                  | 12     | 11     | 10     |
| <b>gainXsfr</b>              | 14     | 14     | 14     |
| <b>idxOffsetX</b>            | 8      | 16     | 32     |
| <b>Exp. gainX</b>            | 27307  | 27307  | 27307  |
| <b>Exp. offsetX</b>          | 3277   | 3277   | 3277   |
| <b>Exp. maskX</b>            | 4095   | 2047   | 1023   |
| <b>Exp. Table</b>            | [1x17] | [1x33] | [1x65] |
| <b>Exp. minX</b>             | -16384 | -16384 | -16384 |
| <b>Exp. maxX</b>             | 22938  | 22938  | 22938  |
| <b>Exp. sfrX</b>             | 12     | 11     | 10     |
| <b>Exp. gainXsfr</b>         | 14     | 14     | 14     |
| <b>Exp. idxOffsetX</b>       | 8      | 16     | 32     |

| Test settings        |             |
|----------------------|-------------|
| Tolerance gainX      | ±0,0000e+00 |
| Tolerance offsetX    | ±0,0000e+00 |
| Tolerance maskX      | ±0,0000e+00 |
| Tolerance Table      | ±0,0000e+00 |
| Tolerance minX       | ±0,0000e+00 |
| Tolerance maxX       | ±0,0000e+00 |
| Tolerance sfrX       | ±0,0000e+00 |
| Tolerance gainXsfr   | ±0,0000e+00 |
| Tolerance idxOffsetX | ±0,0000e+00 |

**Verification: LookupTable1D FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block LookupTable1D.

| Test results   |         |        |        |        |     |        |
|----------------|---------|--------|--------|--------|-----|--------|
| Time step      | 1       | 2      | 3      | 4      | ... | 67     |
| CPU cycles     | 57      | 57     | 57     | 57     | ... | 65     |
| Inputs         |         |        |        |        |     |        |
| x (DSP)        | -32768  | -31775 | -30782 | -29789 | ... | 32767  |
| x              | -1      | -0.97  | -0.939 | -0.909 | ... | 1      |
| Parameters     |         |        |        |        |     |        |
| TableData      | [1x257] |        |        |        |     |        |
| DimX           | 257     |        |        |        |     |        |
| x_min          | -0.8    |        |        |        |     |        |
| x_max          | 0.7     |        |        |        |     |        |
| Outputs        |         |        |        |        |     |        |
| Out            | 0.8     | 0.8    | 0.8    | 0.8    | ... | -0.7   |
| Exp. Out       | 0.8     | 0.8    | 0.8    | 0.8    | ... | -0.7   |
| Out (DSP)      | 26213   | 26213  | 26213  | 26213  | ... | -22938 |
| Exp. Out (DSP) | 26214   | 26214  | 26214  | 26214  | ... | -22938 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 75 |
| Avg CPU cycles  | 71 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable1D.

| Test results                 |        |        |        |
|------------------------------|--------|--------|--------|
| Time step                    | 1      | 2      | 3      |
| <i>Mask parameters</i>       |        |        |        |
| <b>TableData</b>             | [1x17] | [1x33] | [1x65] |
| <b>DimX</b>                  | 17     | 33     | 65     |
| <b>x_min</b>                 | -0.5   | -0.5   | -0.5   |
| <b>x_max</b>                 | 0.7    | 0.7    | 0.7    |
| <i>Controller parameters</i> |        |        |        |
| <b>gainX</b>                 | 27307  | 27307  | 27307  |
| <b>offsetX</b>               | 3277   | 3277   | 3277   |
| <b>maskX</b>                 | 4095   | 2047   | 1023   |
| <b>Table</b>                 | [1x17] | [1x33] | [1x65] |
| <b>minX</b>                  | -16384 | -16384 | -16384 |
| <b>maxX</b>                  | 22938  | 22938  | 22938  |
| <b>sfrX</b>                  | 12     | 11     | 10     |
| <b>gainXsfr</b>              | 14     | 14     | 14     |
| <b>idxOffsetX</b>            | 8      | 16     | 32     |
| <b>Exp. gainX</b>            | 27307  | 27307  | 27307  |
| <b>Exp. offsetX</b>          | 3277   | 3277   | 3277   |
| <b>Exp. maskX</b>            | 4095   | 2047   | 1023   |
| <b>Exp. Table</b>            | [1x17] | [1x33] | [1x65] |
| <b>Exp. minX</b>             | -16384 | -16384 | -16384 |
| <b>Exp. maxX</b>             | 22938  | 22938  | 22938  |
| <b>Exp. sfrX</b>             | 12     | 11     | 10     |
| <b>Exp. gainXsfr</b>         | 14     | 14     | 14     |
| <b>Exp. idxOffsetX</b>       | 8      | 16     | 32     |

| Test settings        |             |
|----------------------|-------------|
| Tolerance gainX      | ±0,0000e+00 |
| Tolerance offsetX    | ±0,0000e+00 |
| Tolerance maskX      | ±0,0000e+00 |
| Tolerance Table      | ±0,0000e+00 |
| Tolerance minX       | ±0,0000e+00 |
| Tolerance maxX       | ±0,0000e+00 |
| Tolerance sfrX       | ±0,0000e+00 |
| Tolerance gainXsfr   | ±0,0000e+00 |
| Tolerance idxOffsetX | ±0,0000e+00 |

**Verification: LookupTable1D FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block LookupTable1D.

| Test results   |         |        |        |        |     |        |
|----------------|---------|--------|--------|--------|-----|--------|
| Time step      | 1       | 2      | 3      | 4      | ... | 67     |
| CPU cycles     | 99      | 99     | 99     | 99     | ... | 102    |
| Inputs         |         |        |        |        |     |        |
| x (DSP)        | -32768  | -31775 | -30782 | -29789 | ... | 32767  |
| x              | -1      | -0.97  | -0.939 | -0.909 | ... | 1      |
| Parameters     |         |        |        |        |     |        |
| TableData      | [1x257] |        |        |        |     |        |
| DimX           | 257     |        |        |        |     |        |
| x_min          | -0.8    |        |        |        |     |        |
| x_max          | 0.7     |        |        |        |     |        |
| Outputs        |         |        |        |        |     |        |
| Out            | 0.8     | 0.8    | 0.8    | 0.8    | ... | -0.7   |
| Exp. Out       | 0.8     | 0.8    | 0.8    | 0.8    | ... | -0.7   |
| Out (DSP)      | 26213   | 26213  | 26213  | 26213  | ... | -22938 |
| Exp. Out (DSP) | 26214   | 26214  | 26214  | 26214  | ... | -22938 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 99  |
| Max CPU cycles  | 122 |
| Avg CPU cycles  | 116 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable1D.

| Test results                 |        |        |        |
|------------------------------|--------|--------|--------|
| Time step                    | 1      | 2      | 3      |
| <i>Mask parameters</i>       |        |        |        |
| <b>TableData</b>             | [1x17] | [1x33] | [1x65] |
| <b>DimX</b>                  | 17     | 33     | 65     |
| <b>x_min</b>                 | -0.5   | -0.5   | -0.5   |
| <b>x_max</b>                 | 0.7    | 0.7    | 0.7    |
| <i>Controller parameters</i> |        |        |        |
| <b>gainX</b>                 | 27307  | 27307  | 27307  |
| <b>offsetX</b>               | 3277   | 3277   | 3277   |
| <b>maskX</b>                 | 4095   | 2047   | 1023   |
| <b>Table</b>                 | [1x17] | [1x33] | [1x65] |
| <b>minX</b>                  | -16384 | -16384 | -16384 |
| <b>maxX</b>                  | 22938  | 22938  | 22938  |
| <b>sfrX</b>                  | 12     | 11     | 10     |
| <b>gainXsfr</b>              | 14     | 14     | 14     |
| <b>idxOffsetX</b>            | 8      | 16     | 32     |
| <b>Exp. gainX</b>            | 27307  | 27307  | 27307  |
| <b>Exp. offsetX</b>          | 3277   | 3277   | 3277   |
| <b>Exp. maskX</b>            | 4095   | 2047   | 1023   |
| <b>Exp. Table</b>            | [1x17] | [1x33] | [1x65] |
| <b>Exp. minX</b>             | -16384 | -16384 | -16384 |
| <b>Exp. maxX</b>             | 22938  | 22938  | 22938  |
| <b>Exp. sfrX</b>             | 12     | 11     | 10     |
| <b>Exp. gainXsfr</b>         | 14     | 14     | 14     |
| <b>Exp. idxOffsetX</b>       | 8      | 16     | 32     |

| Test settings        |             |
|----------------------|-------------|
| Tolerance gainX      | ±0,0000e+00 |
| Tolerance offsetX    | ±0,0000e+00 |
| Tolerance maskX      | ±0,0000e+00 |
| Tolerance Table      | ±0,0000e+00 |
| Tolerance minX       | ±0,0000e+00 |
| Tolerance maxX       | ±0,0000e+00 |
| Tolerance sfrX       | ±0,0000e+00 |
| Tolerance gainXsfr   | ±0,0000e+00 |
| Tolerance idxOffsetX | ±0,0000e+00 |



**Verification: LookupTable1D FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block LookupTable1D.

| Test results   |         |        |        |        |     |        |
|----------------|---------|--------|--------|--------|-----|--------|
| Time step      | 1       | 2      | 3      | 4      | ... | 67     |
| CPU cycles     | 126     | 109    | 109    | 109    | ... | 108    |
| Inputs         |         |        |        |        |     |        |
| x (DSP)        | -32768  | -31775 | -30782 | -29789 | ... | 32767  |
| x              | -1      | -0.97  | -0.939 | -0.909 | ... | 1      |
| Parameters     |         |        |        |        |     |        |
| TableData      | [1x257] |        |        |        |     |        |
| DimX           | 257     |        |        |        |     |        |
| x_min          | -0.8    |        |        |        |     |        |
| x_max          | 0.7     |        |        |        |     |        |
| Outputs        |         |        |        |        |     |        |
| Out            | 0.8     | 0.8    | 0.8    | 0.8    | ... | -0.7   |
| Exp. Out       | 0.8     | 0.8    | 0.8    | 0.8    | ... | -0.7   |
| Out (DSP)      | 26213   | 26213  | 26213  | 26213  | ... | -22938 |
| Exp. Out (DSP) | 26214   | 26214  | 26214  | 26214  | ... | -22938 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 108 |
| Max CPU cycles  | 126 |
| Avg CPU cycles  | 110 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable1D.

| Test results                 |        |        |        |
|------------------------------|--------|--------|--------|
| Time step                    | 1      | 2      | 3      |
| <i>Mask parameters</i>       |        |        |        |
| <b>TableData</b>             | [1x17] | [1x33] | [1x65] |
| <b>DimX</b>                  | 17     | 33     | 65     |
| <b>x_min</b>                 | -0.5   | -0.5   | -0.5   |
| <b>x_max</b>                 | 0.7    | 0.7    | 0.7    |
| <i>Controller parameters</i> |        |        |        |
| <b>gainX</b>                 | 27307  | 27307  | 27307  |
| <b>offsetX</b>               | 3277   | 3277   | 3277   |
| <b>maskX</b>                 | 4095   | 2047   | 1023   |
| <b>Table</b>                 | [1x17] | [1x33] | [1x65] |
| <b>minX</b>                  | -16384 | -16384 | -16384 |
| <b>maxX</b>                  | 22938  | 22938  | 22938  |
| <b>sfrX</b>                  | 12     | 11     | 10     |
| <b>gainXsfr</b>              | 14     | 14     | 14     |
| <b>idxOffsetX</b>            | 8      | 16     | 32     |
| <b>Exp. gainX</b>            | 27307  | 27307  | 27307  |
| <b>Exp. offsetX</b>          | 3277   | 3277   | 3277   |
| <b>Exp. maskX</b>            | 4095   | 2047   | 1023   |
| <b>Exp. Table</b>            | [1x17] | [1x33] | [1x65] |
| <b>Exp. minX</b>             | -16384 | -16384 | -16384 |
| <b>Exp. maxX</b>             | 22938  | 22938  | 22938  |
| <b>Exp. sfrX</b>             | 12     | 11     | 10     |
| <b>Exp. gainXsfr</b>         | 14     | 14     | 14     |
| <b>Exp. idxOffsetX</b>       | 8      | 16     | 32     |

| Test settings        |             |
|----------------------|-------------|
| Tolerance gainX      | ±0,0000e+00 |
| Tolerance offsetX    | ±0,0000e+00 |
| Tolerance maskX      | ±0,0000e+00 |
| Tolerance Table      | ±0,0000e+00 |
| Tolerance minX       | ±0,0000e+00 |
| Tolerance maxX       | ±0,0000e+00 |
| Tolerance sfrX       | ±0,0000e+00 |
| Tolerance gainXsfr   | ±0,0000e+00 |
| Tolerance idxOffsetX | ±0,0000e+00 |

**Verification: LookupTable1D FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block LookupTable1D.

| Test results   |         |        |        |        |     |        |
|----------------|---------|--------|--------|--------|-----|--------|
| Time step      | 1       | 2      | 3      | 4      | ... | 67     |
| CPU cycles     | 84      | 84     | 84     | 84     | ... | 101    |
| Inputs         |         |        |        |        |     |        |
| x (DSP)        | -32768  | -31775 | -30782 | -29789 | ... | 32767  |
| x              | -1      | -0.97  | -0.939 | -0.909 | ... | 1      |
| Parameters     |         |        |        |        |     |        |
| TableData      | [1x257] |        |        |        |     |        |
| DimX           | 257     |        |        |        |     |        |
| x_min          | -0.8    |        |        |        |     |        |
| x_max          | 0.7     |        |        |        |     |        |
| Outputs        |         |        |        |        |     |        |
| Out            | 0.8     | 0.8    | 0.8    | 0.8    | ... | -0.7   |
| Exp. Out       | 0.8     | 0.8    | 0.8    | 0.8    | ... | -0.7   |
| Out (DSP)      | 26213   | 26213  | 26213  | 26213  | ... | -22938 |
| Exp. Out (DSP) | 26214   | 26214  | 26214  | 26214  | ... | -22938 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 84  |
| Max CPU cycles  | 105 |
| Avg CPU cycles  | 100 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable1D.

| Test results                 |        |        |        |
|------------------------------|--------|--------|--------|
| Time step                    | 1      | 2      | 3      |
| <i>Mask parameters</i>       |        |        |        |
| <b>TableData</b>             | [1x17] | [1x33] | [1x65] |
| <b>DimX</b>                  | 17     | 33     | 65     |
| <b>x_min</b>                 | -0.5   | -0.5   | -0.5   |
| <b>x_max</b>                 | 0.7    | 0.7    | 0.7    |
| <i>Controller parameters</i> |        |        |        |
| <b>gainX</b>                 | 27307  | 27307  | 27307  |
| <b>offsetX</b>               | 3277   | 3277   | 3277   |
| <b>maskX</b>                 | 4095   | 2047   | 1023   |
| <b>Table</b>                 | [1x17] | [1x33] | [1x65] |
| <b>minX</b>                  | -16384 | -16384 | -16384 |
| <b>maxX</b>                  | 22938  | 22938  | 22938  |
| <b>sfrX</b>                  | 12     | 11     | 10     |
| <b>gainXsfr</b>              | 14     | 14     | 14     |
| <b>idxOffsetX</b>            | 8      | 16     | 32     |
| <b>Exp. gainX</b>            | 27307  | 27307  | 27307  |
| <b>Exp. offsetX</b>          | 3277   | 3277   | 3277   |
| <b>Exp. maskX</b>            | 4095   | 2047   | 1023   |
| <b>Exp. Table</b>            | [1x17] | [1x33] | [1x65] |
| <b>Exp. minX</b>             | -16384 | -16384 | -16384 |
| <b>Exp. maxX</b>             | 22938  | 22938  | 22938  |
| <b>Exp. sfrX</b>             | 12     | 11     | 10     |
| <b>Exp. gainXsfr</b>         | 14     | 14     | 14     |
| <b>Exp. idxOffsetX</b>       | 8      | 16     | 32     |

| Test settings        |             |
|----------------------|-------------|
| Tolerance gainX      | ±0,0000e+00 |
| Tolerance offsetX    | ±0,0000e+00 |
| Tolerance maskX      | ±0,0000e+00 |
| Tolerance Table      | ±0,0000e+00 |
| Tolerance minX       | ±0,0000e+00 |
| Tolerance maxX       | ±0,0000e+00 |
| Tolerance sfrX       | ±0,0000e+00 |
| Tolerance gainXsfr   | ±0,0000e+00 |
| Tolerance idxOffsetX | ±0,0000e+00 |

**Verification: LookupTable1D FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block LookupTable1D.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 67          |
| CPU cycles     | 150         | 150         | ... | 164         |
| Inputs         |             |             |     |             |
| x (DSP)        | -2147483648 | -2082408386 | ... | 2147483647  |
| x              | -1          | -0.97       | ... | 1           |
| Parameters     |             |             |     |             |
| TableData      | [1x257]     |             |     |             |
| DimX           | 257         |             |     |             |
| x_min          | -0.8        |             |     |             |
| x_max          | 0.7         |             |     |             |
| Outputs        |             |             |     |             |
| Out            | 0.8         | 0.8         | ... | -0.7        |
| Exp. Out       | 0.8         | 0.8         | ... | -0.7        |
| Out (DSP)      | 1717986917  | 1717986917  | ... | -1503238554 |
| Exp. Out (DSP) | 1717986918  | 1717986918  | ... | -1503238554 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 150 |
| Max CPU cycles  | 178 |
| Avg CPU cycles  | 172 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable1D.

| Test results                 |             |             |             |
|------------------------------|-------------|-------------|-------------|
| Time step                    | 1           | 2           | 3           |
| <i>Mask parameters</i>       |             |             |             |
| <b>TableData</b>             | [1x17]      | [1x33]      | [1x65]      |
| <b>DimX</b>                  | 17          | 33          | 65          |
| <b>x_min</b>                 | -0.5        | -0.5        | -0.5        |
| <b>x_max</b>                 | 0.7         | 0.7         | 0.7         |
| <i>Controller parameters</i> |             |             |             |
| <b>gainX</b>                 | 1789569707  | 1789569707  | 1789569707  |
| <b>offsetX</b>               | 214748365   | 214748365   | 214748365   |
| <b>maskX</b>                 | 268435455   | 134217727   | 67108863    |
| <b>Table</b>                 | [1x17]      | [1x33]      | [1x65]      |
| <b>minX</b>                  | -1073741824 | -1073741824 | -1073741824 |
| <b>maxX</b>                  | 1503238554  | 1503238554  | 1503238554  |
| <b>sfrX</b>                  | 28          | 27          | 26          |
| <b>gainXsfr</b>              | 30          | 30          | 30          |
| <b>idxOffsetX</b>            | 8           | 16          | 32          |
| <b>Exp. gainX</b>            | 1789569707  | 1789569707  | 1789569707  |
| <b>Exp. offsetX</b>          | 214748365   | 214748365   | 214748365   |
| <b>Exp. maskX</b>            | 268435455   | 134217727   | 67108863    |
| <b>Exp. Table</b>            | [1x17]      | [1x33]      | [1x65]      |
| <b>Exp. minX</b>             | -1073741824 | -1073741824 | -1073741824 |
| <b>Exp. maxX</b>             | 1503238554  | 1503238554  | 1503238554  |
| <b>Exp. sfrX</b>             | 28          | 27          | 26          |
| <b>Exp. gainXsfr</b>         | 30          | 30          | 30          |
| <b>Exp. idxOffsetX</b>       | 8           | 16          | 32          |

| Test settings        |                  |
|----------------------|------------------|
| Tolerance gainX      | $\pm 0,0000e+00$ |
| Tolerance offsetX    | $\pm 0,0000e+00$ |
| Tolerance maskX      | $\pm 0,0000e+00$ |
| Tolerance Table      | $\pm 0,0000e+00$ |
| Tolerance minX       | $\pm 0,0000e+00$ |
| Tolerance maxX       | $\pm 0,0000e+00$ |
| Tolerance sfrX       | $\pm 0,0000e+00$ |
| Tolerance gainXsfr   | $\pm 0,0000e+00$ |
| Tolerance idxOffsetX | $\pm 0,0000e+00$ |

**Verification: LookupTable1D FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block LookupTable1D.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 67          |
| CPU cycles     | 147         | 147         | ... | 155         |
| Inputs         |             |             |     |             |
| x (DSP)        | -2147483648 | -2082408386 | ... | 2147483647  |
| x              | -1          | -0.97       | ... | 1           |
| Parameters     |             |             |     |             |
| TableData      | [1x257]     |             |     |             |
| DimX           | 257         |             |     |             |
| x_min          | -0.8        |             |     |             |
| x_max          | 0.7         |             |     |             |
| Outputs        |             |             |     |             |
| Out            | 0.8         | 0.8         | ... | -0.7        |
| Exp. Out       | 0.8         | 0.8         | ... | -0.7        |
| Out (DSP)      | 1717986917  | 1717986917  | ... | -1503238554 |
| Exp. Out (DSP) | 1717986918  | 1717986918  | ... | -1503238554 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 147 |
| Max CPU cycles  | 209 |
| Avg CPU cycles  | 194 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable1D.

| Test results                 |             |             |             |
|------------------------------|-------------|-------------|-------------|
| Time step                    | 1           | 2           | 3           |
| <i>Mask parameters</i>       |             |             |             |
| <b>TableData</b>             | [1x17]      | [1x33]      | [1x65]      |
| <b>DimX</b>                  | 17          | 33          | 65          |
| <b>x_min</b>                 | -0.5        | -0.5        | -0.5        |
| <b>x_max</b>                 | 0.7         | 0.7         | 0.7         |
| <i>Controller parameters</i> |             |             |             |
| <b>gainX</b>                 | 1789569707  | 1789569707  | 1789569707  |
| <b>offsetX</b>               | 214748365   | 214748365   | 214748365   |
| <b>maskX</b>                 | 268435455   | 134217727   | 67108863    |
| <b>Table</b>                 | [1x17]      | [1x33]      | [1x65]      |
| <b>minX</b>                  | -1073741824 | -1073741824 | -1073741824 |
| <b>maxX</b>                  | 1503238554  | 1503238554  | 1503238554  |
| <b>sfrX</b>                  | 28          | 27          | 26          |
| <b>gainXsfr</b>              | 30          | 30          | 30          |
| <b>idxOffsetX</b>            | 8           | 16          | 32          |
| <b>Exp. gainX</b>            | 1789569707  | 1789569707  | 1789569707  |
| <b>Exp. offsetX</b>          | 214748365   | 214748365   | 214748365   |
| <b>Exp. maskX</b>            | 268435455   | 134217727   | 67108863    |
| <b>Exp. Table</b>            | [1x17]      | [1x33]      | [1x65]      |
| <b>Exp. minX</b>             | -1073741824 | -1073741824 | -1073741824 |
| <b>Exp. maxX</b>             | 1503238554  | 1503238554  | 1503238554  |
| <b>Exp. sfrX</b>             | 28          | 27          | 26          |
| <b>Exp. gainXsfr</b>         | 30          | 30          | 30          |
| <b>Exp. idxOffsetX</b>       | 8           | 16          | 32          |

| Test settings        |                  |
|----------------------|------------------|
| Tolerance gainX      | $\pm 0,0000e+00$ |
| Tolerance offsetX    | $\pm 0,0000e+00$ |
| Tolerance maskX      | $\pm 0,0000e+00$ |
| Tolerance Table      | $\pm 0,0000e+00$ |
| Tolerance minX       | $\pm 0,0000e+00$ |
| Tolerance maxX       | $\pm 0,0000e+00$ |
| Tolerance sfrX       | $\pm 0,0000e+00$ |
| Tolerance gainXsfr   | $\pm 0,0000e+00$ |
| Tolerance idxOffsetX | $\pm 0,0000e+00$ |



**Verification: LookupTable1D FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block LookupTable1D.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 67          |
| CPU cycles     | 160         | 160         | ... | 153         |
| Inputs         |             |             |     |             |
| x (DSP)        | -2147483648 | -2082408386 | ... | 2147483647  |
| x              | -1          | -0.97       | ... | 1           |
| Parameters     |             |             |     |             |
| TableData      | [1x257]     |             |     |             |
| DimX           | 257         |             |     |             |
| x_min          | -0.8        |             |     |             |
| x_max          | 0.7         |             |     |             |
| Outputs        |             |             |     |             |
| Out            | 0.8         | 0.8         | ... | -0.7        |
| Exp. Out       | 0.8         | 0.8         | ... | -0.7        |
| Out (DSP)      | 1717986917  | 1717986917  | ... | -1503238554 |
| Exp. Out (DSP) | 1717986918  | 1717986918  | ... | -1503238554 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 153 |
| Max CPU cycles  | 205 |
| Avg CPU cycles  | 190 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable1D.

| Test results                 |             |             |             |
|------------------------------|-------------|-------------|-------------|
| Time step                    | 1           | 2           | 3           |
| <i>Mask parameters</i>       |             |             |             |
| <b>TableData</b>             | [1x17]      | [1x33]      | [1x65]      |
| <b>DimX</b>                  | 17          | 33          | 65          |
| <b>x_min</b>                 | -0.5        | -0.5        | -0.5        |
| <b>x_max</b>                 | 0.7         | 0.7         | 0.7         |
| <i>Controller parameters</i> |             |             |             |
| <b>gainX</b>                 | 1789569707  | 1789569707  | 1789569707  |
| <b>offsetX</b>               | 214748365   | 214748365   | 214748365   |
| <b>maskX</b>                 | 268435455   | 134217727   | 67108863    |
| <b>Table</b>                 | [1x17]      | [1x33]      | [1x65]      |
| <b>minX</b>                  | -1073741824 | -1073741824 | -1073741824 |
| <b>maxX</b>                  | 1503238554  | 1503238554  | 1503238554  |
| <b>sfrX</b>                  | 28          | 27          | 26          |
| <b>gainXsfr</b>              | 30          | 30          | 30          |
| <b>idxOffsetX</b>            | 8           | 16          | 32          |
| <b>Exp. gainX</b>            | 1789569707  | 1789569707  | 1789569707  |
| <b>Exp. offsetX</b>          | 214748365   | 214748365   | 214748365   |
| <b>Exp. maskX</b>            | 268435455   | 134217727   | 67108863    |
| <b>Exp. Table</b>            | [1x17]      | [1x33]      | [1x65]      |
| <b>Exp. minX</b>             | -1073741824 | -1073741824 | -1073741824 |
| <b>Exp. maxX</b>             | 1503238554  | 1503238554  | 1503238554  |
| <b>Exp. sfrX</b>             | 28          | 27          | 26          |
| <b>Exp. gainXsfr</b>         | 30          | 30          | 30          |
| <b>Exp. idxOffsetX</b>       | 8           | 16          | 32          |

| Test settings        |                  |
|----------------------|------------------|
| Tolerance gainX      | $\pm 0,0000e+00$ |
| Tolerance offsetX    | $\pm 0,0000e+00$ |
| Tolerance maskX      | $\pm 0,0000e+00$ |
| Tolerance Table      | $\pm 0,0000e+00$ |
| Tolerance minX       | $\pm 0,0000e+00$ |
| Tolerance maxX       | $\pm 0,0000e+00$ |
| Tolerance sfrX       | $\pm 0,0000e+00$ |
| Tolerance gainXsfr   | $\pm 0,0000e+00$ |
| Tolerance idxOffsetX | $\pm 0,0000e+00$ |

**Verification: LookupTable1D FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block LookupTable1D.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 67          |
| CPU cycles     | 221         | 221         | ... | 219         |
| Inputs         |             |             |     |             |
| x (DSP)        | -2147483648 | -2082408386 | ... | 2147483647  |
| x              | -1          | -0.97       | ... | 1           |
| Parameters     |             |             |     |             |
| TableData      | [1x257]     |             |     |             |
| DimX           | 257         |             |     |             |
| x_min          | -0.8        |             |     |             |
| x_max          | 0.7         |             |     |             |
| Outputs        |             |             |     |             |
| Out            | 0.8         | 0.8         | ... | -0.7        |
| Exp. Out       | 0.8         | 0.8         | ... | -0.7        |
| Out (DSP)      | 1717986917  | 1717986917  | ... | -1503238554 |
| Exp. Out (DSP) | 1717986918  | 1717986918  | ... | -1503238554 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 219 |
| Max CPU cycles  | 322 |
| Avg CPU cycles  | 296 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable1D.

| Test results                 |             |             |             |
|------------------------------|-------------|-------------|-------------|
| Time step                    | 1           | 2           | 3           |
| <i>Mask parameters</i>       |             |             |             |
| <b>TableData</b>             | [1x17]      | [1x33]      | [1x65]      |
| <b>DimX</b>                  | 17          | 33          | 65          |
| <b>x_min</b>                 | -0.5        | -0.5        | -0.5        |
| <b>x_max</b>                 | 0.7         | 0.7         | 0.7         |
| <i>Controller parameters</i> |             |             |             |
| <b>gainX</b>                 | 1789569707  | 1789569707  | 1789569707  |
| <b>offsetX</b>               | 214748365   | 214748365   | 214748365   |
| <b>maskX</b>                 | 268435455   | 134217727   | 67108863    |
| <b>Table</b>                 | [1x17]      | [1x33]      | [1x65]      |
| <b>minX</b>                  | -1073741824 | -1073741824 | -1073741824 |
| <b>maxX</b>                  | 1503238554  | 1503238554  | 1503238554  |
| <b>sfrX</b>                  | 28          | 27          | 26          |
| <b>gainXsfr</b>              | 30          | 30          | 30          |
| <b>idxOffsetX</b>            | 8           | 16          | 32          |
| <b>Exp. gainX</b>            | 1789569707  | 1789569707  | 1789569707  |
| <b>Exp. offsetX</b>          | 214748365   | 214748365   | 214748365   |
| <b>Exp. maskX</b>            | 268435455   | 134217727   | 67108863    |
| <b>Exp. Table</b>            | [1x17]      | [1x33]      | [1x65]      |
| <b>Exp. minX</b>             | -1073741824 | -1073741824 | -1073741824 |
| <b>Exp. maxX</b>             | 1503238554  | 1503238554  | 1503238554  |
| <b>Exp. sfrX</b>             | 28          | 27          | 26          |
| <b>Exp. gainXsfr</b>         | 30          | 30          | 30          |
| <b>Exp. idxOffsetX</b>       | 8           | 16          | 32          |

| Test settings        |                  |
|----------------------|------------------|
| Tolerance gainX      | $\pm 0,0000e+00$ |
| Tolerance offsetX    | $\pm 0,0000e+00$ |
| Tolerance maskX      | $\pm 0,0000e+00$ |
| Tolerance Table      | $\pm 0,0000e+00$ |
| Tolerance minX       | $\pm 0,0000e+00$ |
| Tolerance maxX       | $\pm 0,0000e+00$ |
| Tolerance sfrX       | $\pm 0,0000e+00$ |
| Tolerance gainXsfr   | $\pm 0,0000e+00$ |
| Tolerance idxOffsetX | $\pm 0,0000e+00$ |

**Verification: LookupTable1D FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block LookupTable1D.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 67          |
| CPU cycles     | 82          | 82          | ... | 92          |
| Inputs         |             |             |     |             |
| x (DSP)        | -2147483648 | -2082408386 | ... | 2147483647  |
| x              | -1          | -0.97       | ... | 1           |
| Parameters     |             |             |     |             |
| TableData      | [1x257]     |             |     |             |
| DimX           | 257         |             |     |             |
| x_min          | -0.8        |             |     |             |
| x_max          | 0.7         |             |     |             |
| Outputs        |             |             |     |             |
| Out            | 0.8         | 0.8         | ... | -0.7        |
| Exp. Out       | 0.8         | 0.8         | ... | -0.7        |
| Out (DSP)      | 1717986917  | 1717986917  | ... | -1503238554 |
| Exp. Out (DSP) | 1717986918  | 1717986918  | ... | -1503238554 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 82  |
| Max CPU cycles  | 122 |
| Avg CPU cycles  | 113 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable1D.

| Test results                 |             |             |             |
|------------------------------|-------------|-------------|-------------|
| Time step                    | 1           | 2           | 3           |
| <i>Mask parameters</i>       |             |             |             |
| <b>TableData</b>             | [1x17]      | [1x33]      | [1x65]      |
| <b>DimX</b>                  | 17          | 33          | 65          |
| <b>x_min</b>                 | -0.5        | -0.5        | -0.5        |
| <b>x_max</b>                 | 0.7         | 0.7         | 0.7         |
| <i>Controller parameters</i> |             |             |             |
| <b>gainX</b>                 | 1789569707  | 1789569707  | 1789569707  |
| <b>offsetX</b>               | 214748365   | 214748365   | 214748365   |
| <b>maskX</b>                 | 268435455   | 134217727   | 67108863    |
| <b>Table</b>                 | [1x17]      | [1x33]      | [1x65]      |
| <b>minX</b>                  | -1073741824 | -1073741824 | -1073741824 |
| <b>maxX</b>                  | 1503238554  | 1503238554  | 1503238554  |
| <b>sfrX</b>                  | 28          | 27          | 26          |
| <b>gainXsfr</b>              | 30          | 30          | 30          |
| <b>idxOffsetX</b>            | 8           | 16          | 32          |
| <b>Exp. gainX</b>            | 1789569707  | 1789569707  | 1789569707  |
| <b>Exp. offsetX</b>          | 214748365   | 214748365   | 214748365   |
| <b>Exp. maskX</b>            | 268435455   | 134217727   | 67108863    |
| <b>Exp. Table</b>            | [1x17]      | [1x33]      | [1x65]      |
| <b>Exp. minX</b>             | -1073741824 | -1073741824 | -1073741824 |
| <b>Exp. maxX</b>             | 1503238554  | 1503238554  | 1503238554  |
| <b>Exp. sfrX</b>             | 28          | 27          | 26          |
| <b>Exp. gainXsfr</b>         | 30          | 30          | 30          |
| <b>Exp. idxOffsetX</b>       | 8           | 16          | 32          |

| Test settings        |                  |
|----------------------|------------------|
| Tolerance gainX      | $\pm 0,0000e+00$ |
| Tolerance offsetX    | $\pm 0,0000e+00$ |
| Tolerance maskX      | $\pm 0,0000e+00$ |
| Tolerance Table      | $\pm 0,0000e+00$ |
| Tolerance minX       | $\pm 0,0000e+00$ |
| Tolerance maxX       | $\pm 0,0000e+00$ |
| Tolerance sfrX       | $\pm 0,0000e+00$ |
| Tolerance gainXsfr   | $\pm 0,0000e+00$ |
| Tolerance idxOffsetX | $\pm 0,0000e+00$ |

**Verification: LookupTable1D FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block LookupTable1D.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 67          |
| CPU cycles     | 737         | 737         | ... | 741         |
| Inputs         |             |             |     |             |
| x (DSP)        | -2147483648 | -2082408386 | ... | 2147483647  |
| x              | -1          | -0.97       | ... | 1           |
| Parameters     |             |             |     |             |
| TableData      | [1x257]     |             |     |             |
| DimX           | 257         |             |     |             |
| x_min          | -0.8        |             |     |             |
| x_max          | 0.7         |             |     |             |
| Outputs        |             |             |     |             |
| Out            | 0.8         | 0.8         | ... | -0.7        |
| Exp. Out       | 0.8         | 0.8         | ... | -0.7        |
| Out (DSP)      | 1717986917  | 1717986917  | ... | -1503238554 |
| Exp. Out (DSP) | 1717986918  | 1717986918  | ... | -1503238554 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 737  |
| Max CPU cycles  | 1155 |
| Avg CPU cycles  | 1046 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable1D.

| Test results                 |             |             |             |
|------------------------------|-------------|-------------|-------------|
| Time step                    | 1           | 2           | 3           |
| <i>Mask parameters</i>       |             |             |             |
| <b>TableData</b>             | [1x17]      | [1x33]      | [1x65]      |
| <b>DimX</b>                  | 17          | 33          | 65          |
| <b>x_min</b>                 | -0.5        | -0.5        | -0.5        |
| <b>x_max</b>                 | 0.7         | 0.7         | 0.7         |
| <i>Controller parameters</i> |             |             |             |
| <b>gainX</b>                 | 1789569707  | 1789569707  | 1789569707  |
| <b>offsetX</b>               | 214748365   | 214748365   | 214748365   |
| <b>maskX</b>                 | 268435455   | 134217727   | 67108863    |
| <b>Table</b>                 | [1x17]      | [1x33]      | [1x65]      |
| <b>minX</b>                  | -1073741824 | -1073741824 | -1073741824 |
| <b>maxX</b>                  | 1503238554  | 1503238554  | 1503238554  |
| <b>sfrX</b>                  | 28          | 27          | 26          |
| <b>gainXsfr</b>              | 30          | 30          | 30          |
| <b>idxOffsetX</b>            | 8           | 16          | 32          |
| <b>Exp. gainX</b>            | 1789569707  | 1789569707  | 1789569707  |
| <b>Exp. offsetX</b>          | 214748365   | 214748365   | 214748365   |
| <b>Exp. maskX</b>            | 268435455   | 134217727   | 67108863    |
| <b>Exp. Table</b>            | [1x17]      | [1x33]      | [1x65]      |
| <b>Exp. minX</b>             | -1073741824 | -1073741824 | -1073741824 |
| <b>Exp. maxX</b>             | 1503238554  | 1503238554  | 1503238554  |
| <b>Exp. sfrX</b>             | 28          | 27          | 26          |
| <b>Exp. gainXsfr</b>         | 30          | 30          | 30          |
| <b>Exp. idxOffsetX</b>       | 8           | 16          | 32          |

| Test settings        |                  |
|----------------------|------------------|
| Tolerance gainX      | $\pm 0,0000e+00$ |
| Tolerance offsetX    | $\pm 0,0000e+00$ |
| Tolerance maskX      | $\pm 0,0000e+00$ |
| Tolerance Table      | $\pm 0,0000e+00$ |
| Tolerance minX       | $\pm 0,0000e+00$ |
| Tolerance maxX       | $\pm 0,0000e+00$ |
| Tolerance sfrX       | $\pm 0,0000e+00$ |
| Tolerance gainXsfr   | $\pm 0,0000e+00$ |
| Tolerance idxOffsetX | $\pm 0,0000e+00$ |



**Verification: LookupTable1D FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block LookupTable1D.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 67          |
| CPU cycles     | 186         | 158         | ... | 156         |
| Inputs         |             |             |     |             |
| x (DSP)        | -2147483648 | -2082408386 | ... | 2147483647  |
| x              | -1          | -0.97       | ... | 1           |
| Parameters     |             |             |     |             |
| TableData      | [1x257]     |             |     |             |
| DimX           | 257         |             |     |             |
| x_min          | -0.8        |             |     |             |
| x_max          | 0.7         |             |     |             |
| Outputs        |             |             |     |             |
| Out            | 0.8         | 0.8         | ... | -0.7        |
| Exp. Out       | 0.8         | 0.8         | ... | -0.7        |
| Out (DSP)      | 1717986917  | 1717986917  | ... | -1503238554 |
| Exp. Out (DSP) | 1717986918  | 1717986918  | ... | -1503238554 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 156 |
| Max CPU cycles  | 186 |
| Avg CPU cycles  | 168 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable1D.

| Test results                 |             |             |             |
|------------------------------|-------------|-------------|-------------|
| Time step                    | 1           | 2           | 3           |
| <i>Mask parameters</i>       |             |             |             |
| <b>TableData</b>             | [1x17]      | [1x33]      | [1x65]      |
| <b>DimX</b>                  | 17          | 33          | 65          |
| <b>x_min</b>                 | -0.5        | -0.5        | -0.5        |
| <b>x_max</b>                 | 0.7         | 0.7         | 0.7         |
| <i>Controller parameters</i> |             |             |             |
| <b>gainX</b>                 | 1789569707  | 1789569707  | 1789569707  |
| <b>offsetX</b>               | 214748365   | 214748365   | 214748365   |
| <b>maskX</b>                 | 268435455   | 134217727   | 67108863    |
| <b>Table</b>                 | [1x17]      | [1x33]      | [1x65]      |
| <b>minX</b>                  | -1073741824 | -1073741824 | -1073741824 |
| <b>maxX</b>                  | 1503238554  | 1503238554  | 1503238554  |
| <b>sfrX</b>                  | 28          | 27          | 26          |
| <b>gainXsfr</b>              | 30          | 30          | 30          |
| <b>idxOffsetX</b>            | 8           | 16          | 32          |
| <b>Exp. gainX</b>            | 1789569707  | 1789569707  | 1789569707  |
| <b>Exp. offsetX</b>          | 214748365   | 214748365   | 214748365   |
| <b>Exp. maskX</b>            | 268435455   | 134217727   | 67108863    |
| <b>Exp. Table</b>            | [1x17]      | [1x33]      | [1x65]      |
| <b>Exp. minX</b>             | -1073741824 | -1073741824 | -1073741824 |
| <b>Exp. maxX</b>             | 1503238554  | 1503238554  | 1503238554  |
| <b>Exp. sfrX</b>             | 28          | 27          | 26          |
| <b>Exp. gainXsfr</b>         | 30          | 30          | 30          |
| <b>Exp. idxOffsetX</b>       | 8           | 16          | 32          |

| Test settings        |                  |
|----------------------|------------------|
| Tolerance gainX      | $\pm 0,0000e+00$ |
| Tolerance offsetX    | $\pm 0,0000e+00$ |
| Tolerance maskX      | $\pm 0,0000e+00$ |
| Tolerance Table      | $\pm 0,0000e+00$ |
| Tolerance minX       | $\pm 0,0000e+00$ |
| Tolerance maxX       | $\pm 0,0000e+00$ |
| Tolerance sfrX       | $\pm 0,0000e+00$ |
| Tolerance gainXsfr   | $\pm 0,0000e+00$ |
| Tolerance idxOffsetX | $\pm 0,0000e+00$ |

**Verification: LookupTable1D FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block LookupTable1D.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 67          |
| CPU cycles     | 126         | 126         | ... | 151         |
| Inputs         |             |             |     |             |
| x (DSP)        | -2147483648 | -2082408386 | ... | 2147483647  |
| x              | -1          | -0.97       | ... | 1           |
| Parameters     |             |             |     |             |
| TableData      | [1x257]     |             |     |             |
| DimX           | 257         |             |     |             |
| x_min          | -0.8        |             |     |             |
| x_max          | 0.7         |             |     |             |
| Outputs        |             |             |     |             |
| Out            | 0.8         | 0.8         | ... | -0.7        |
| Exp. Out       | 0.8         | 0.8         | ... | -0.7        |
| Out (DSP)      | 1717986917  | 1717986917  | ... | -1503238554 |
| Exp. Out (DSP) | 1717986918  | 1717986918  | ... | -1503238554 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 126 |
| Max CPU cycles  | 157 |
| Avg CPU cycles  | 149 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable1D.

| Test results                 |             |             |             |
|------------------------------|-------------|-------------|-------------|
| Time step                    | 1           | 2           | 3           |
| <i>Mask parameters</i>       |             |             |             |
| <b>TableData</b>             | [1x17]      | [1x33]      | [1x65]      |
| <b>DimX</b>                  | 17          | 33          | 65          |
| <b>x_min</b>                 | -0.5        | -0.5        | -0.5        |
| <b>x_max</b>                 | 0.7         | 0.7         | 0.7         |
| <i>Controller parameters</i> |             |             |             |
| <b>gainX</b>                 | 1789569707  | 1789569707  | 1789569707  |
| <b>offsetX</b>               | 214748365   | 214748365   | 214748365   |
| <b>maskX</b>                 | 268435455   | 134217727   | 67108863    |
| <b>Table</b>                 | [1x17]      | [1x33]      | [1x65]      |
| <b>minX</b>                  | -1073741824 | -1073741824 | -1073741824 |
| <b>maxX</b>                  | 1503238554  | 1503238554  | 1503238554  |
| <b>sfrX</b>                  | 28          | 27          | 26          |
| <b>gainXsfr</b>              | 30          | 30          | 30          |
| <b>idxOffsetX</b>            | 8           | 16          | 32          |
| <b>Exp. gainX</b>            | 1789569707  | 1789569707  | 1789569707  |
| <b>Exp. offsetX</b>          | 214748365   | 214748365   | 214748365   |
| <b>Exp. maskX</b>            | 268435455   | 134217727   | 67108863    |
| <b>Exp. Table</b>            | [1x17]      | [1x33]      | [1x65]      |
| <b>Exp. minX</b>             | -1073741824 | -1073741824 | -1073741824 |
| <b>Exp. maxX</b>             | 1503238554  | 1503238554  | 1503238554  |
| <b>Exp. sfrX</b>             | 28          | 27          | 26          |
| <b>Exp. gainXsfr</b>         | 30          | 30          | 30          |
| <b>Exp. idxOffsetX</b>       | 8           | 16          | 32          |

| Test settings        |                  |
|----------------------|------------------|
| Tolerance gainX      | $\pm 0,0000e+00$ |
| Tolerance offsetX    | $\pm 0,0000e+00$ |
| Tolerance maskX      | $\pm 0,0000e+00$ |
| Tolerance Table      | $\pm 0,0000e+00$ |
| Tolerance minX       | $\pm 0,0000e+00$ |
| Tolerance maxX       | $\pm 0,0000e+00$ |
| Tolerance sfrX       | $\pm 0,0000e+00$ |
| Tolerance gainXsfr   | $\pm 0,0000e+00$ |
| Tolerance idxOffsetX | $\pm 0,0000e+00$ |

**Verification: LookupTable1D Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block LookupTable1D.

| Test results   |         |        |     |       |
|----------------|---------|--------|-----|-------|
| Time step      | 1       | 2      | ... | 67    |
| CPU cycles     | 82      | 82     | ... | 99    |
| Inputs         |         |        |     |       |
| x (DSP)        | -1.2    | -1.164 | ... | 1.2   |
| x              | -1.2    | -1.164 | ... | 1.2   |
| Parameters     |         |        |     |       |
| TableData      | [1x257] |        |     |       |
| DimX           | 257     |        |     |       |
| x_min          | -0.8    |        |     |       |
| x_max          | 0.7     |        |     |       |
| Outputs        |         |        |     |       |
| Out            | 1.04    | 1.04   | ... | -0.91 |
| Exp. Out       | 1.04    | 1.04   | ... | -0.91 |
| Out (DSP)      | 1.04    | 1.04   | ... | -0.91 |
| Exp. Out (DSP) | 1.04    | 1.04   | ... | -0.91 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,8626e-07$ ( $\pm 400$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 82  |
| Max CPU cycles  | 122 |
| Avg CPU cycles  | 110 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable1D.

| Test results                 |        |        |        |
|------------------------------|--------|--------|--------|
| Time step                    | 1      | 2      | 3      |
| <i>Mask parameters</i>       |        |        |        |
| <b>TableData</b>             | [1x17] | [1x33] | [1x65] |
| <b>DimX</b>                  | 17     | 33     | 65     |
| <b>x_min</b>                 | -0.8   | -0.8   | -0.8   |
| <b>x_max</b>                 | 0.7    | 0.7    | 0.7    |
| <i>Controller parameters</i> |        |        |        |
| <b>gainX</b>                 | 10.667 | 21.333 | 42.667 |
| <b>offsetX</b>               | -0.8   | -0.8   | -0.8   |
| <b>Table</b>                 | [1x17] | [1x33] | [1x65] |
| <b>dimX</b>                  | 16     | 32     | 64     |
| <b>Exp. gainX</b>            | 10.667 | 21.333 | 42.667 |
| <b>Exp. offsetX</b>          | -0.8   | -0.8   | -0.8   |
| <b>Exp. Table</b>            | [1x17] | [1x33] | [1x65] |
| <b>Exp. dimX</b>             | 16     | 32     | 64     |

| Test settings     |                  |
|-------------------|------------------|
| Tolerance gainX   | $\pm 0,0000e+00$ |
| Tolerance offsetX | $\pm 0,0000e+00$ |
| Tolerance Table   | $\pm 0,0000e+00$ |
| Tolerance dimX    | $\pm 0,0000e+00$ |

**Verification: LookupTable1D Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block LookupTable1D.

| Test results   |         |        |     |       |
|----------------|---------|--------|-----|-------|
| Time step      | 1       | 2      | ... | 67    |
| CPU cycles     | 43      | 43     | ... | 59    |
| Inputs         |         |        |     |       |
| x (DSP)        | -1.2    | -1.164 | ... | 1.2   |
| x              | -1.2    | -1.164 | ... | 1.2   |
| Parameters     |         |        |     |       |
| TableData      | [1x257] |        |     |       |
| DimX           | 257     |        |     |       |
| x_min          | -0.8    |        |     |       |
| x_max          | 0.7     |        |     |       |
| Outputs        |         |        |     |       |
| Out            | 1.04    | 1.04   | ... | -0.91 |
| Exp. Out       | 1.04    | 1.04   | ... | -0.91 |
| Out (DSP)      | 1.04    | 1.04   | ... | -0.91 |
| Exp. Out (DSP) | 1.04    | 1.04   | ... | -0.91 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,8626e-07$ ( $\pm 400$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 43 |
| Max CPU cycles  | 75 |
| Avg CPU cycles  | 66 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable1D.

| Test results                 |        |        |        |
|------------------------------|--------|--------|--------|
| Time step                    | 1      | 2      | 3      |
| <i>Mask parameters</i>       |        |        |        |
| <b>TableData</b>             | [1x17] | [1x33] | [1x65] |
| <b>DimX</b>                  | 17     | 33     | 65     |
| <b>x_min</b>                 | -0.8   | -0.8   | -0.8   |
| <b>x_max</b>                 | 0.7    | 0.7    | 0.7    |
| <i>Controller parameters</i> |        |        |        |
| <b>gainX</b>                 | 10.667 | 21.333 | 42.667 |
| <b>offsetX</b>               | -0.8   | -0.8   | -0.8   |
| <b>Table</b>                 | [1x17] | [1x33] | [1x65] |
| <b>dimX</b>                  | 16     | 32     | 64     |
| <b>Exp. gainX</b>            | 10.667 | 21.333 | 42.667 |
| <b>Exp. offsetX</b>          | -0.8   | -0.8   | -0.8   |
| <b>Exp. Table</b>            | [1x17] | [1x33] | [1x65] |
| <b>Exp. dimX</b>             | 16     | 32     | 64     |

| Test settings     |                  |
|-------------------|------------------|
| Tolerance gainX   | $\pm 0,0000e+00$ |
| Tolerance offsetX | $\pm 0,0000e+00$ |
| Tolerance Table   | $\pm 0,0000e+00$ |
| Tolerance dimX    | $\pm 0,0000e+00$ |



**Verification: LookupTable1D Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block LookupTable1D.

| Test results   |         |        |     |       |
|----------------|---------|--------|-----|-------|
| Time step      | 1       | 2      | ... | 67    |
| CPU cycles     | 92      | 92     | ... | 112   |
| Inputs         |         |        |     |       |
| x (DSP)        | -1.2    | -1.164 | ... | 1.2   |
| x              | -1.2    | -1.164 | ... | 1.2   |
| Parameters     |         |        |     |       |
| TableData      | [1x257] |        |     |       |
| DimX           | 257     |        |     |       |
| x_min          | -0.8    |        |     |       |
| x_max          | 0.7     |        |     |       |
| Outputs        |         |        |     |       |
| Out            | 1.04    | 1.04   | ... | -0.91 |
| Exp. Out       | 1.04    | 1.04   | ... | -0.91 |
| Out (DSP)      | 1.04    | 1.04   | ... | -0.91 |
| Exp. Out (DSP) | 1.04    | 1.04   | ... | -0.91 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,8626e-07$ ( $\pm 400$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 92  |
| Max CPU cycles  | 118 |
| Avg CPU cycles  | 110 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable1D.

| Test results                 |        |        |        |
|------------------------------|--------|--------|--------|
| Time step                    | 1      | 2      | 3      |
| <i>Mask parameters</i>       |        |        |        |
| <b>TableData</b>             | [1x17] | [1x33] | [1x65] |
| <b>DimX</b>                  | 17     | 33     | 65     |
| <b>x_min</b>                 | -0.8   | -0.8   | -0.8   |
| <b>x_max</b>                 | 0.7    | 0.7    | 0.7    |
| <i>Controller parameters</i> |        |        |        |
| <b>gainX</b>                 | 10.667 | 21.333 | 42.667 |
| <b>offsetX</b>               | -0.8   | -0.8   | -0.8   |
| <b>Table</b>                 | [1x17] | [1x33] | [1x65] |
| <b>dimX</b>                  | 16     | 32     | 64     |
| <b>Exp. gainX</b>            | 10.667 | 21.333 | 42.667 |
| <b>Exp. offsetX</b>          | -0.8   | -0.8   | -0.8   |
| <b>Exp. Table</b>            | [1x17] | [1x33] | [1x65] |
| <b>Exp. dimX</b>             | 16     | 32     | 64     |

| Test settings     |                  |
|-------------------|------------------|
| Tolerance gainX   | $\pm 0,0000e+00$ |
| Tolerance offsetX | $\pm 0,0000e+00$ |
| Tolerance Table   | $\pm 0,0000e+00$ |
| Tolerance dimX    | $\pm 0,0000e+00$ |

**Verification: LookupTable1D Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block LookupTable1D.

| Test results   |         |        |     |       |
|----------------|---------|--------|-----|-------|
| Time step      | 1       | 2      | ... | 67    |
| CPU cycles     | 497     | 501    | ... | 625   |
| Inputs         |         |        |     |       |
| x (DSP)        | -1.2    | -1.164 | ... | 1.2   |
| x              | -1.2    | -1.164 | ... | 1.2   |
| Parameters     |         |        |     |       |
| TableData      | [1x257] |        |     |       |
| DimX           | 257     |        |     |       |
| x_min          | -0.8    |        |     |       |
| x_max          | 0.7     |        |     |       |
| Outputs        |         |        |     |       |
| Out            | 1.04    | 1.04   | ... | -0.91 |
| Exp. Out       | 1.04    | 1.04   | ... | -0.91 |
| Out (DSP)      | 1.04    | 1.04   | ... | -0.91 |
| Exp. Out (DSP) | 1.04    | 1.04   | ... | -0.91 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,8626e-07$ ( $\pm 400$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 490  |
| Max CPU cycles  | 1353 |
| Avg CPU cycles  | 1027 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable1D.

| Test results                 |        |        |        |
|------------------------------|--------|--------|--------|
| Time step                    | 1      | 2      | 3      |
| <i>Mask parameters</i>       |        |        |        |
| <b>TableData</b>             | [1x17] | [1x33] | [1x65] |
| <b>DimX</b>                  | 17     | 33     | 65     |
| <b>x_min</b>                 | -0.8   | -0.8   | -0.8   |
| <b>x_max</b>                 | 0.7    | 0.7    | 0.7    |
| <i>Controller parameters</i> |        |        |        |
| <b>gainX</b>                 | 10.667 | 21.333 | 42.667 |
| <b>offsetX</b>               | -0.8   | -0.8   | -0.8   |
| <b>Table</b>                 | [1x17] | [1x33] | [1x65] |
| <b>dimX</b>                  | 16     | 32     | 64     |
| <b>Exp. gainX</b>            | 10.667 | 21.333 | 42.667 |
| <b>Exp. offsetX</b>          | -0.8   | -0.8   | -0.8   |
| <b>Exp. Table</b>            | [1x17] | [1x33] | [1x65] |
| <b>Exp. dimX</b>             | 16     | 32     | 64     |

| Test settings     |                  |
|-------------------|------------------|
| Tolerance gainX   | $\pm 0,0000e+00$ |
| Tolerance offsetX | $\pm 0,0000e+00$ |
| Tolerance Table   | $\pm 0,0000e+00$ |
| Tolerance dimX    | $\pm 0,0000e+00$ |

**Verification: LookupTable1D Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block LookupTable1D.

| Test results   |         |        |     |       |
|----------------|---------|--------|-----|-------|
| Time step      | 1       | 2      | ... | 67    |
| CPU cycles     | 205     | 207    | ... | 240   |
| Inputs         |         |        |     |       |
| x (DSP)        | -1.2    | -1.164 | ... | 1.2   |
| x              | -1.2    | -1.164 | ... | 1.2   |
| Parameters     |         |        |     |       |
| TableData      | [1x257] |        |     |       |
| DimX           | 257     |        |     |       |
| x_min          | -0.8    |        |     |       |
| x_max          | 0.7     |        |     |       |
| Outputs        |         |        |     |       |
| Out            | 1.04    | 1.04   | ... | -0.91 |
| Exp. Out       | 1.04    | 1.04   | ... | -0.91 |
| Out (DSP)      | 1.04    | 1.04   | ... | -0.91 |
| Exp. Out (DSP) | 1.04    | 1.04   | ... | -0.91 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,8626e-07$ ( $\pm 400$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 205 |
| Max CPU cycles  | 515 |
| Avg CPU cycles  | 399 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable1D.

| Test results                 |        |        |        |
|------------------------------|--------|--------|--------|
| Time step                    | 1      | 2      | 3      |
| <i>Mask parameters</i>       |        |        |        |
| <b>TableData</b>             | [1x17] | [1x33] | [1x65] |
| <b>DimX</b>                  | 17     | 33     | 65     |
| <b>x_min</b>                 | -0.8   | -0.8   | -0.8   |
| <b>x_max</b>                 | 0.7    | 0.7    | 0.7    |
| <i>Controller parameters</i> |        |        |        |
| <b>gainX</b>                 | 10.667 | 21.333 | 42.667 |
| <b>offsetX</b>               | -0.8   | -0.8   | -0.8   |
| <b>Table</b>                 | [1x17] | [1x33] | [1x65] |
| <b>dimX</b>                  | 16     | 32     | 64     |
| <b>Exp. gainX</b>            | 10.667 | 21.333 | 42.667 |
| <b>Exp. offsetX</b>          | -0.8   | -0.8   | -0.8   |
| <b>Exp. Table</b>            | [1x17] | [1x33] | [1x65] |
| <b>Exp. dimX</b>             | 16     | 32     | 64     |

| Test settings     |                  |
|-------------------|------------------|
| Tolerance gainX   | $\pm 0,0000e+00$ |
| Tolerance offsetX | $\pm 0,0000e+00$ |
| Tolerance Table   | $\pm 0,0000e+00$ |
| Tolerance dimX    | $\pm 0,0000e+00$ |

**Verification: LookupTable1D Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block LookupTable1D.

| Test results   |         |        |     |       |
|----------------|---------|--------|-----|-------|
| Time step      | 1       | 2      | ... | 67    |
| CPU cycles     | 520     | 521    | ... | 652   |
| Inputs         |         |        |     |       |
| x (DSP)        | -1.2    | -1.164 | ... | 1.2   |
| x              | -1.2    | -1.164 | ... | 1.2   |
| Parameters     |         |        |     |       |
| TableData      | [1x257] |        |     |       |
| DimX           | 257     |        |     |       |
| x_min          | -0.8    |        |     |       |
| x_max          | 0.7     |        |     |       |
| Outputs        |         |        |     |       |
| Out            | 1.04    | 1.04   | ... | -0.91 |
| Exp. Out       | 1.04    | 1.04   | ... | -0.91 |
| Out (DSP)      | 1.04    | 1.04   | ... | -0.91 |
| Exp. Out (DSP) | 1.04    | 1.04   | ... | -0.91 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,8626e-07$ ( $\pm 400$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 507  |
| Max CPU cycles  | 1994 |
| Avg CPU cycles  | 1369 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable1D.

| Test results                 |        |        |        |
|------------------------------|--------|--------|--------|
| Time step                    | 1      | 2      | 3      |
| <i>Mask parameters</i>       |        |        |        |
| <b>TableData</b>             | [1x17] | [1x33] | [1x65] |
| <b>DimX</b>                  | 17     | 33     | 65     |
| <b>x_min</b>                 | -0.8   | -0.8   | -0.8   |
| <b>x_max</b>                 | 0.7    | 0.7    | 0.7    |
| <i>Controller parameters</i> |        |        |        |
| <b>gainX</b>                 | 10.667 | 21.333 | 42.667 |
| <b>offsetX</b>               | -0.8   | -0.8   | -0.8   |
| <b>Table</b>                 | [1x17] | [1x33] | [1x65] |
| <b>dimX</b>                  | 16     | 32     | 64     |
| <b>Exp. gainX</b>            | 10.667 | 21.333 | 42.667 |
| <b>Exp. offsetX</b>          | -0.8   | -0.8   | -0.8   |
| <b>Exp. Table</b>            | [1x17] | [1x33] | [1x65] |
| <b>Exp. dimX</b>             | 16     | 32     | 64     |

| Test settings     |                  |
|-------------------|------------------|
| Tolerance gainX   | $\pm 0,0000e+00$ |
| Tolerance offsetX | $\pm 0,0000e+00$ |
| Tolerance Table   | $\pm 0,0000e+00$ |
| Tolerance dimX    | $\pm 0,0000e+00$ |



**Verification: LookupTable1D Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block LookupTable1D.

| Test results   |         |        |     |       |
|----------------|---------|--------|-----|-------|
| Time step      | 1       | 2      | ... | 67    |
| CPU cycles     | 99      | 77     | ... | 91    |
| Inputs         |         |        |     |       |
| x (DSP)        | -1.2    | -1.164 | ... | 1.2   |
| x              | -1.2    | -1.164 | ... | 1.2   |
| Parameters     |         |        |     |       |
| TableData      | [1x257] |        |     |       |
| DimX           | 257     |        |     |       |
| x_min          | -0.8    |        |     |       |
| x_max          | 0.7     |        |     |       |
| Outputs        |         |        |     |       |
| Out            | 1.04    | 1.04   | ... | -0.91 |
| Exp. Out       | 1.04    | 1.04   | ... | -0.91 |
| Out (DSP)      | 1.04    | 1.04   | ... | -0.91 |
| Exp. Out (DSP) | 1.04    | 1.04   | ... | -0.91 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,8626e-07$ ( $\pm 400$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 77  |
| Max CPU cycles  | 112 |
| Avg CPU cycles  | 98  |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable1D.

| Test results                 |        |        |        |
|------------------------------|--------|--------|--------|
| Time step                    | 1      | 2      | 3      |
| <i>Mask parameters</i>       |        |        |        |
| <b>TableData</b>             | [1x17] | [1x33] | [1x65] |
| <b>DimX</b>                  | 17     | 33     | 65     |
| <b>x_min</b>                 | -0.8   | -0.8   | -0.8   |
| <b>x_max</b>                 | 0.7    | 0.7    | 0.7    |
| <i>Controller parameters</i> |        |        |        |
| <b>gainX</b>                 | 10.667 | 21.333 | 42.667 |
| <b>offsetX</b>               | -0.8   | -0.8   | -0.8   |
| <b>Table</b>                 | [1x17] | [1x33] | [1x65] |
| <b>dimX</b>                  | 16     | 32     | 64     |
| <b>Exp. gainX</b>            | 10.667 | 21.333 | 42.667 |
| <b>Exp. offsetX</b>          | -0.8   | -0.8   | -0.8   |
| <b>Exp. Table</b>            | [1x17] | [1x33] | [1x65] |
| <b>Exp. dimX</b>             | 16     | 32     | 64     |

| Test settings     |                  |
|-------------------|------------------|
| Tolerance gainX   | $\pm 0,0000e+00$ |
| Tolerance offsetX | $\pm 0,0000e+00$ |
| Tolerance Table   | $\pm 0,0000e+00$ |
| Tolerance dimX    | $\pm 0,0000e+00$ |

**Verification: LookupTable1D Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block LookupTable1D.

| Test results   |         |        |     |       |
|----------------|---------|--------|-----|-------|
| Time step      | 1       | 2      | ... | 67    |
| CPU cycles     | 71      | 71     | ... | 96    |
| Inputs         |         |        |     |       |
| x (DSP)        | -1.2    | -1.164 | ... | 1.2   |
| x              | -1.2    | -1.164 | ... | 1.2   |
| Parameters     |         |        |     |       |
| TableData      | [1x257] |        |     |       |
| DimX           | 257     |        |     |       |
| x_min          | -0.8    |        |     |       |
| x_max          | 0.7     |        |     |       |
| Outputs        |         |        |     |       |
| Out            | 1.04    | 1.04   | ... | -0.91 |
| Exp. Out       | 1.04    | 1.04   | ... | -0.91 |
| Out (DSP)      | 1.04    | 1.04   | ... | -0.91 |
| Exp. Out (DSP) | 1.04    | 1.04   | ... | -0.91 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,8626e-07$ ( $\pm 400$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 71  |
| Max CPU cycles  | 108 |
| Avg CPU cycles  | 96  |


**Test case: Conversion test****OK**

Conversion test for General block LookupTable1D.

| Test results                 |        |        |        |
|------------------------------|--------|--------|--------|
| Time step                    | 1      | 2      | 3      |
| <i>Mask parameters</i>       |        |        |        |
| <b>TableData</b>             | [1x17] | [1x33] | [1x65] |
| <b>DimX</b>                  | 17     | 33     | 65     |
| <b>x_min</b>                 | -0.8   | -0.8   | -0.8   |
| <b>x_max</b>                 | 0.7    | 0.7    | 0.7    |
| <i>Controller parameters</i> |        |        |        |
| <b>gainX</b>                 | 10.667 | 21.333 | 42.667 |
| <b>offsetX</b>               | -0.8   | -0.8   | -0.8   |
| <b>Table</b>                 | [1x17] | [1x33] | [1x65] |
| <b>dimX</b>                  | 16     | 32     | 64     |
| <b>Exp. gainX</b>            | 10.667 | 21.333 | 42.667 |
| <b>Exp. offsetX</b>          | -0.8   | -0.8   | -0.8   |
| <b>Exp. Table</b>            | [1x17] | [1x33] | [1x65] |
| <b>Exp. dimX</b>             | 16     | 32     | 64     |

| Test settings     |                  |
|-------------------|------------------|
| Tolerance gainX   | $\pm 0,0000e+00$ |
| Tolerance offsetX | $\pm 0,0000e+00$ |
| Tolerance Table   | $\pm 0,0000e+00$ |
| Tolerance dimX    | $\pm 0,0000e+00$ |

## Block: LookupTable2D



Two dimensional look-up table with selectable number of data points.

Table data must be an array of size DimX\*DimY.

If input is out of specified range, output will be cut off (no extrapolation).

| Inports |                            |
|---------|----------------------------|
| x       | Table index in x direction |
| y       | Table index in y direction |

| Outputs |              |
|---------|--------------|
| Out     | Table output |

| Mask Parameters |    |                                                      |
|-----------------|----|------------------------------------------------------|
| Name            | ID | Description                                          |
| TableData       | 1  | Look-up table data                                   |
| DimX            | 2  | Number of data points in x-direction                 |
| x_min           | 3  | Minimum input value of x-dimension for look-up table |
| x_max           | 4  | Maximum input value of x-dimension for look-up table |
| DimY            | 5  | Number of data points in y-direction                 |
| y_min           | 6  | Minimum input value of y-dimension for look-up table |
| y_max           | 7  | Maximum input value of y-dimension for look-up table |


### Description:

The table of the LookupTable2D block must contain DimX times DimY data points and they have to be arranged as


$$\begin{aligned}
 \text{TableData} = & [f(x_1, y_1), f(x_2, y_1), \dots, f(x_{n-1}, y_1), f(x_n, y_1), \\
 & f(x_1, y_2), f(x_2, y_2), \dots, f(x_{n-1}, y_2), f(x_n, y_2), \\
 & \dots \\
 & f(x_1, y_{m-1}), f(x_2, y_{m-1}), \dots, f(x_{n-1}, y_{m-1}), f(x_n, y_{m-1}), \\
 & f(x_1, y_m), f(x_2, y_m), \dots, f(x_{n-1}, y_m), f(x_n, y_m)]
 \end{aligned}$$

with n as selected DimX and m as selected DimY values.

For periodic signals, the last entries per dimension must be identical to the first entries in this dimension, see the example in the following figure.



For non-periodic signals there is no restriction regarding the last data points, see the example in the figure below.



#### Implementations:

- FiP16** 16 Bit Fixed Point Implementation
- FiP32** 32 Bit Fixed Point Implementation
- Float32** 32 Bit Floating Point Implementation
- Float64** 64 Bit Floating Point Implementation

#### Implementation: FiP16

---

## 16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| x                 | int16 |
| y                 | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

## Implementation: FiP32

### 32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| x                 | int32 |
| y                 | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

## Implementation: Float32

### 32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| x                 | float32 |
| y                 | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

## Implementation: Float64

### 64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| x                 | float64 |
| y                 | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: LookupTable2D FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block LookupTable2D.

| Test results   |         |        |        |        |     |        |
|----------------|---------|--------|--------|--------|-----|--------|
| Time step      | 1       | 2      | 3      | 4      | ... | 67     |
| CPU cycles     | 217     | 217    | 217    | 217    | ... | 210    |
| Inputs         |         |        |        |        |     |        |
| x (DSP)        | -32768  | -31775 | -30782 | -29789 | ... | 32767  |
| y (DSP)        | 26214   | 25370  | 24526  | 23682  | ... | -29491 |
| x              | -1      | -0.97  | -0.939 | -0.909 | ... | 1      |
| y              | 0.8     | 0.774  | 0.748  | 0.723  | ... | -0.9   |
| Parameters     |         |        |        |        |     |        |
| TableData      | [1x561] |        |        |        |     |        |
| DimX           | 17      |        |        |        |     |        |
| x_min          | -0.8    |        |        |        |     |        |
| x_max          | 0.7     |        |        |        |     |        |
| DimY           | 33      |        |        |        |     |        |
| y_min          | -0.6    |        |        |        |     |        |
| y_max          | 0.9     |        |        |        |     |        |
| Outputs        |         |        |        |        |     |        |
| Out            | -0      | -0.013 | -0.026 | -0.039 | ... | 0.05   |
| Exp. Out       | 0       | -0.013 | -0.026 | -0.039 | ... | 0.05   |
| Out (DSP)      | -1      | -423   | -845   | -1267  | ... | 1637   |
| Exp. Out (DSP) | 0       | -422   | -844   | -1266  | ... | 1638   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,1553e-05$ ( $\pm 3$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 210 |
| Max CPU cycles  | 234 |
| Avg CPU cycles  | 228 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable2D.



| Test results                 |             |
|------------------------------|-------------|
| Time step                    | 1           |
| <i>Mask parameters</i>       |             |
| TableData                    | [1x561]     |
| DimX                         | 33          |
| x_min                        | -1          |
| x_max                        | 1           |
| DimY                         | 17          |
| y_min                        | -1          |
| y_max                        | 1           |
| <i>Controller parameters</i> |             |
| gainX                        | 16384       |
| maskY                        | 4095        |
| maskX                        | 2047        |
| Table                        | [1x561]     |
| gainY                        | 16384       |
| maxY                         | 32767       |
| maxX                         | 32767       |
| sfrX                         | 11          |
| sfrY                         | 12          |
| offsetX                      | 0           |
| sizeX                        | 33          |
| offsetY                      | 0           |
| minY                         | -32767      |
| minX                         | -32767      |
| gainXsfr                     | 14          |
| idxOffsetY                   | 8           |
| idxOffsetX                   | 16          |
| gainYsfr                     | 14          |
| Exp. gainX                   | 16384       |
| Exp. maskY                   | 4095        |
| Exp. maskX                   | 2047        |
| Exp. Table                   | [1x561]     |
| Exp. gainY                   | 16384       |
| Exp. maxY                    | 32767       |
| Exp. maxX                    | 32767       |
| Exp. sfrX                    | 11          |
| Exp. sfrY                    | 12          |
| Exp. offsetX                 | 0           |
| Exp. sizeX                   | 33          |
| Exp. offsetY                 | 0           |
| Exp. minY                    | 1796 -32767 |
| Exp. minX                    | -32767      |

| Test settings           |                  |
|-------------------------|------------------|
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |

**Verification: LookupTable2D FiP16 CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block LookupTable2D.

| Test results   |         |        |        |        |     |        |
|----------------|---------|--------|--------|--------|-----|--------|
| Time step      | 1       | 2      | 3      | 4      | ... | 67     |
| CPU cycles     | 133     | 133    | 133    | 133    | ... | 123    |
| Inputs         |         |        |        |        |     |        |
| x (DSP)        | -32768  | -31775 | -30782 | -29789 | ... | 32767  |
| y (DSP)        | 26214   | 25370  | 24526  | 23682  | ... | -29491 |
| x              | -1      | -0.97  | -0.939 | -0.909 | ... | 1      |
| y              | 0.8     | 0.774  | 0.748  | 0.723  | ... | -0.9   |
| Parameters     |         |        |        |        |     |        |
| TableData      | [1x561] |        |        |        |     |        |
| DimX           | 17      |        |        |        |     |        |
| x_min          | -0.8    |        |        |        |     |        |
| x_max          | 0.7     |        |        |        |     |        |
| DimY           | 33      |        |        |        |     |        |
| y_min          | -0.6    |        |        |        |     |        |
| y_max          | 0.9     |        |        |        |     |        |
| Outputs        |         |        |        |        |     |        |
| Out            | -0      | -0.013 | -0.026 | -0.039 | ... | 0.05   |
| Exp. Out       | 0       | -0.013 | -0.026 | -0.039 | ... | 0.05   |
| Out (DSP)      | -1      | -423   | -845   | -1267  | ... | 1637   |
| Exp. Out (DSP) | 0       | -422   | -844   | -1266  | ... | 1638   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,1553e-05$ ( $\pm 3$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 123 |
| Max CPU cycles  | 151 |
| Avg CPU cycles  | 144 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable2D.

| Test results                 |             |
|------------------------------|-------------|
| Time step                    | 1           |
| <i>Mask parameters</i>       |             |
| TableData                    | [1x561]     |
| DimX                         | 33          |
| x_min                        | -1          |
| x_max                        | 1           |
| DimY                         | 17          |
| y_min                        | -1          |
| y_max                        | 1           |
| <i>Controller parameters</i> |             |
| gainX                        | 16384       |
| maskY                        | 4095        |
| maskX                        | 2047        |
| Table                        | [1x561]     |
| gainY                        | 16384       |
| maxY                         | 32767       |
| maxX                         | 32767       |
| sfrX                         | 11          |
| sfrY                         | 12          |
| offsetX                      | 0           |
| sizeX                        | 33          |
| offsetY                      | 0           |
| minY                         | -32767      |
| minX                         | -32767      |
| gainXsfr                     | 14          |
| idxOffsetY                   | 8           |
| idxOffsetX                   | 16          |
| gainYsfr                     | 14          |
| Exp. gainX                   | 16384       |
| Exp. maskY                   | 4095        |
| Exp. maskX                   | 2047        |
| Exp. Table                   | [1x561]     |
| Exp. gainY                   | 16384       |
| Exp. maxY                    | 32767       |
| Exp. maxX                    | 32767       |
| Exp. sfrX                    | 11          |
| Exp. sfrY                    | 12          |
| Exp. offsetX                 | 0           |
| Exp. sizeX                   | 33          |
| Exp. offsetY                 | 0           |
| Exp. minY                    | 1799 -32767 |
| Exp. minX                    | -32767      |

| Test settings           |                  |
|-------------------------|------------------|
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |

**Verification: LookupTable2D FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block LookupTable2D.

| Test results   |         |        |        |        |     |        |
|----------------|---------|--------|--------|--------|-----|--------|
| Time step      | 1       | 2      | 3      | 4      | ... | 67     |
| CPU cycles     | 226     | 226    | 226    | 226    | ... | 185    |
| Inputs         |         |        |        |        |     |        |
| x (DSP)        | -32768  | -31775 | -30782 | -29789 | ... | 32767  |
| y (DSP)        | 26214   | 25370  | 24526  | 23682  | ... | -29491 |
| x              | -1      | -0.97  | -0.939 | -0.909 | ... | 1      |
| y              | 0.8     | 0.774  | 0.748  | 0.723  | ... | -0.9   |
| Parameters     |         |        |        |        |     |        |
| TableData      | [1x561] |        |        |        |     |        |
| DimX           | 17      |        |        |        |     |        |
| x_min          | -0.8    |        |        |        |     |        |
| x_max          | 0.7     |        |        |        |     |        |
| DimY           | 33      |        |        |        |     |        |
| y_min          | -0.6    |        |        |        |     |        |
| y_max          | 0.9     |        |        |        |     |        |
| Outputs        |         |        |        |        |     |        |
| Out            | -0      | -0.013 | -0.026 | -0.039 | ... | 0.05   |
| Exp. Out       | 0       | -0.013 | -0.026 | -0.039 | ... | 0.05   |
| Out (DSP)      | -1      | -423   | -845   | -1267  | ... | 1637   |
| Exp. Out (DSP) | 0       | -422   | -844   | -1266  | ... | 1638   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,1553e-05$ ( $\pm 3$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 185 |
| Max CPU cycles  | 249 |
| Avg CPU cycles  | 234 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable2D.

| Test results                 |             |
|------------------------------|-------------|
| Time step                    | 1           |
| <i>Mask parameters</i>       |             |
| TableData                    | [1x561]     |
| DimX                         | 33          |
| x_min                        | -1          |
| x_max                        | 1           |
| DimY                         | 17          |
| y_min                        | -1          |
| y_max                        | 1           |
| <i>Controller parameters</i> |             |
| gainX                        | 16384       |
| maskY                        | 4095        |
| maskX                        | 2047        |
| Table                        | [1x561]     |
| gainY                        | 16384       |
| maxY                         | 32767       |
| maxX                         | 32767       |
| sfrX                         | 11          |
| sfrY                         | 12          |
| offsetX                      | 0           |
| sizeX                        | 33          |
| offsetY                      | 0           |
| minY                         | -32767      |
| minX                         | -32767      |
| gainXsfr                     | 14          |
| idxOffsetY                   | 8           |
| idxOffsetX                   | 16          |
| gainYsfr                     | 14          |
| Exp. gainX                   | 16384       |
| Exp. maskY                   | 4095        |
| Exp. maskX                   | 2047        |
| Exp. Table                   | [1x561]     |
| Exp. gainY                   | 16384       |
| Exp. maxY                    | 32767       |
| Exp. maxX                    | 32767       |
| Exp. sfrX                    | 11          |
| Exp. sfrY                    | 12          |
| Exp. offsetX                 | 0           |
| Exp. sizeX                   | 33          |
| Exp. offsetY                 | 0           |
| Exp. minY                    | 1802 -32767 |
| Exp. minX                    | -32767      |

| Test settings           |                  |
|-------------------------|------------------|
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |



**Verification: LookupTable2D FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block LookupTable2D.

| Test results   |         |        |        |        |     |        |
|----------------|---------|--------|--------|--------|-----|--------|
| Time step      | 1       | 2      | 3      | 4      | ... | 67     |
| CPU cycles     | 207     | 207    | 207    | 207    | ... | 188    |
| Inputs         |         |        |        |        |     |        |
| x (DSP)        | -32768  | -31775 | -30782 | -29789 | ... | 32767  |
| y (DSP)        | 26214   | 25370  | 24526  | 23682  | ... | -29491 |
| x              | -1      | -0.97  | -0.939 | -0.909 | ... | 1      |
| y              | 0.8     | 0.774  | 0.748  | 0.723  | ... | -0.9   |
| Parameters     |         |        |        |        |     |        |
| TableData      | [1x561] |        |        |        |     |        |
| DimX           | 17      |        |        |        |     |        |
| x_min          | -0.8    |        |        |        |     |        |
| x_max          | 0.7     |        |        |        |     |        |
| DimY           | 33      |        |        |        |     |        |
| y_min          | -0.6    |        |        |        |     |        |
| y_max          | 0.9     |        |        |        |     |        |
| Outputs        |         |        |        |        |     |        |
| Out            | -0      | -0.013 | -0.026 | -0.039 | ... | 0.05   |
| Exp. Out       | 0       | -0.013 | -0.026 | -0.039 | ... | 0.05   |
| Out (DSP)      | -1      | -423   | -845   | -1267  | ... | 1637   |
| Exp. Out (DSP) | 0       | -422   | -844   | -1266  | ... | 1638   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,1553e-05$ ( $\pm 3$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 188 |
| Max CPU cycles  | 287 |
| Avg CPU cycles  | 220 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable2D.

| Test results                 |             |
|------------------------------|-------------|
| Time step                    | 1           |
| <i>Mask parameters</i>       |             |
| TableData                    | [1x561]     |
| DimX                         | 33          |
| x_min                        | -1          |
| x_max                        | 1           |
| DimY                         | 17          |
| y_min                        | -1          |
| y_max                        | 1           |
| <i>Controller parameters</i> |             |
| gainX                        | 16384       |
| maskY                        | 4095        |
| maskX                        | 2047        |
| Table                        | [1x561]     |
| gainY                        | 16384       |
| maxY                         | 32767       |
| maxX                         | 32767       |
| sfrX                         | 11          |
| sfrY                         | 12          |
| offsetX                      | 0           |
| sizeX                        | 33          |
| offsetY                      | 0           |
| minY                         | -32767      |
| minX                         | -32767      |
| gainXsfr                     | 14          |
| idxOffsetY                   | 8           |
| idxOffsetX                   | 16          |
| gainYsfr                     | 14          |
| Exp. gainX                   | 16384       |
| Exp. maskY                   | 4095        |
| Exp. maskX                   | 2047        |
| Exp. Table                   | [1x561]     |
| Exp. gainY                   | 16384       |
| Exp. maxY                    | 32767       |
| Exp. maxX                    | 32767       |
| Exp. sfrX                    | 11          |
| Exp. sfrY                    | 12          |
| Exp. offsetX                 | 0           |
| Exp. sizeX                   | 33          |
| Exp. offsetY                 | 0           |
| Exp. minY                    | 1805 -32767 |
| Exp. minX                    | -32767      |

| Test settings           |                  |
|-------------------------|------------------|
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |

**Verification: LookupTable2D FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block LookupTable2D.

| Test results   |         |        |        |        |     |        |
|----------------|---------|--------|--------|--------|-----|--------|
| Time step      | 1       | 2      | 3      | 4      | ... | 67     |
| CPU cycles     | 124     | 124    | 124    | 124    | ... | 113    |
| Inputs         |         |        |        |        |     |        |
| x (DSP)        | -32768  | -31775 | -30782 | -29789 | ... | 32767  |
| y (DSP)        | 26214   | 25370  | 24526  | 23682  | ... | -29491 |
| x              | -1      | -0.97  | -0.939 | -0.909 | ... | 1      |
| y              | 0.8     | 0.774  | 0.748  | 0.723  | ... | -0.9   |
| Parameters     |         |        |        |        |     |        |
| TableData      | [1x561] |        |        |        |     |        |
| DimX           | 17      |        |        |        |     |        |
| x_min          | -0.8    |        |        |        |     |        |
| x_max          | 0.7     |        |        |        |     |        |
| DimY           | 33      |        |        |        |     |        |
| y_min          | -0.6    |        |        |        |     |        |
| y_max          | 0.9     |        |        |        |     |        |
| Outputs        |         |        |        |        |     |        |
| Out            | -0      | -0.013 | -0.026 | -0.039 | ... | 0.05   |
| Exp. Out       | 0       | -0.013 | -0.026 | -0.039 | ... | 0.05   |
| Out (DSP)      | -1      | -423   | -845   | -1267  | ... | 1637   |
| Exp. Out (DSP) | 0       | -422   | -844   | -1266  | ... | 1638   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,1553e-05$ ( $\pm 3$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 113 |
| Max CPU cycles  | 142 |
| Avg CPU cycles  | 135 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable2D.

| Test results          |             |
|-----------------------|-------------|
| Time step             | 1           |
| Mask parameters       |             |
| TableData             | [1x561]     |
| DimX                  | 33          |
| x_min                 | -1          |
| x_max                 | 1           |
| DimY                  | 17          |
| y_min                 | -1          |
| y_max                 | 1           |
| Controller parameters |             |
| gainX                 | 16384       |
| maskY                 | 4095        |
| maskX                 | 2047        |
| Table                 | [1x561]     |
| gainY                 | 16384       |
| maxY                  | 32767       |
| maxX                  | 32767       |
| sfrX                  | 11          |
| sfrY                  | 12          |
| offsetX               | 0           |
| sizeX                 | 33          |
| offsetY               | 0           |
| minY                  | -32767      |
| minX                  | -32767      |
| gainXsfr              | 14          |
| idxOffsetY            | 8           |
| idxOffsetX            | 16          |
| gainYsfr              | 14          |
| Exp. gainX            | 16384       |
| Exp. maskY            | 4095        |
| Exp. maskX            | 2047        |
| Exp. Table            | [1x561]     |
| Exp. gainY            | 16384       |
| Exp. maxY             | 32767       |
| Exp. maxX             | 32767       |
| Exp. sfrX             | 11          |
| Exp. sfrY             | 12          |
| Exp. offsetX          | 0           |
| Exp. sizeX            | 33          |
| Exp. offsetY          | 0           |
| Exp. minY             | 1808 -32767 |
| Exp. minX             | -32767      |

| Test settings           |                  |
|-------------------------|------------------|
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |

**Verification: LookupTable2D FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block LookupTable2D.

| Test results   |         |        |        |        |     |        |
|----------------|---------|--------|--------|--------|-----|--------|
| Time step      | 1       | 2      | 3      | 4      | ... | 67     |
| CPU cycles     | 249     | 249    | 249    | 249    | ... | 223    |
| Inputs         |         |        |        |        |     |        |
| x (DSP)        | -32768  | -31775 | -30782 | -29789 | ... | 32767  |
| y (DSP)        | 26214   | 25370  | 24526  | 23682  | ... | -29491 |
| x              | -1      | -0.97  | -0.939 | -0.909 | ... | 1      |
| y              | 0.8     | 0.774  | 0.748  | 0.723  | ... | -0.9   |
| Parameters     |         |        |        |        |     |        |
| TableData      | [1x561] |        |        |        |     |        |
| DimX           | 17      |        |        |        |     |        |
| x_min          | -0.8    |        |        |        |     |        |
| x_max          | 0.7     |        |        |        |     |        |
| DimY           | 33      |        |        |        |     |        |
| y_min          | -0.6    |        |        |        |     |        |
| y_max          | 0.9     |        |        |        |     |        |
| Outputs        |         |        |        |        |     |        |
| Out            | -0      | -0.013 | -0.026 | -0.039 | ... | 0.05   |
| Exp. Out       | 0       | -0.013 | -0.026 | -0.039 | ... | 0.05   |
| Out (DSP)      | -1      | -423   | -845   | -1267  | ... | 1637   |
| Exp. Out (DSP) | 0       | -422   | -844   | -1266  | ... | 1638   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,1553e-05$ ( $\pm 3$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 223 |
| Max CPU cycles  | 275 |
| Avg CPU cycles  | 263 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable2D.

| Test results                 |             |
|------------------------------|-------------|
| Time step                    | 1           |
| <i>Mask parameters</i>       |             |
| TableData                    | [1x561]     |
| DimX                         | 33          |
| x_min                        | -1          |
| x_max                        | 1           |
| DimY                         | 17          |
| y_min                        | -1          |
| y_max                        | 1           |
| <i>Controller parameters</i> |             |
| gainX                        | 16384       |
| maskY                        | 4095        |
| maskX                        | 2047        |
| Table                        | [1x561]     |
| gainY                        | 16384       |
| maxY                         | 32767       |
| maxX                         | 32767       |
| sfrX                         | 11          |
| sfrY                         | 12          |
| offsetX                      | 0           |
| sizeX                        | 33          |
| offsetY                      | 0           |
| minY                         | -32767      |
| minX                         | -32767      |
| gainXsfr                     | 14          |
| idxOffsetY                   | 8           |
| idxOffsetX                   | 16          |
| gainYsfr                     | 14          |
| Exp. gainX                   | 16384       |
| Exp. maskY                   | 4095        |
| Exp. maskX                   | 2047        |
| Exp. Table                   | [1x561]     |
| Exp. gainY                   | 16384       |
| Exp. maxY                    | 32767       |
| Exp. maxX                    | 32767       |
| Exp. sfrX                    | 11          |
| Exp. sfrY                    | 12          |
| Exp. offsetX                 | 0           |
| Exp. sizeX                   | 33          |
| Exp. offsetY                 | 0           |
| Exp. minY                    | 1811 -32767 |
| Exp. minX                    | -32767      |



| Test settings           |                  |
|-------------------------|------------------|
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |

**Verification: LookupTable2D FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block LookupTable2D.

| Test results   |         |        |        |        |     |        |
|----------------|---------|--------|--------|--------|-----|--------|
| Time step      | 1       | 2      | 3      | 4      | ... | 67     |
| CPU cycles     | 232     | 178    | 178    | 178    | ... | 169    |
| Inputs         |         |        |        |        |     |        |
| x (DSP)        | -32768  | -31775 | -30782 | -29789 | ... | 32767  |
| y (DSP)        | 26214   | 25370  | 24526  | 23682  | ... | -29491 |
| x              | -1      | -0.97  | -0.939 | -0.909 | ... | 1      |
| y              | 0.8     | 0.774  | 0.748  | 0.723  | ... | -0.9   |
| Parameters     |         |        |        |        |     |        |
| TableData      | [1x561] |        |        |        |     |        |
| DimX           | 17      |        |        |        |     |        |
| x_min          | -0.8    |        |        |        |     |        |
| x_max          | 0.7     |        |        |        |     |        |
| DimY           | 33      |        |        |        |     |        |
| y_min          | -0.6    |        |        |        |     |        |
| y_max          | 0.9     |        |        |        |     |        |
| Outputs        |         |        |        |        |     |        |
| Out            | -0      | -0.013 | -0.026 | -0.039 | ... | 0.05   |
| Exp. Out       | 0       | -0.013 | -0.026 | -0.039 | ... | 0.05   |
| Out (DSP)      | -1      | -423   | -845   | -1267  | ... | 1637   |
| Exp. Out (DSP) | 0       | -422   | -844   | -1266  | ... | 1638   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,1553e-05$ ( $\pm 3$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 169 |
| Max CPU cycles  | 232 |
| Avg CPU cycles  | 183 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable2D.

| Test results                 |             |
|------------------------------|-------------|
| Time step                    | 1           |
| <i>Mask parameters</i>       |             |
| TableData                    | [1x561]     |
| DimX                         | 33          |
| x_min                        | -1          |
| x_max                        | 1           |
| DimY                         | 17          |
| y_min                        | -1          |
| y_max                        | 1           |
| <i>Controller parameters</i> |             |
| gainX                        | 16384       |
| maskY                        | 4095        |
| maskX                        | 2047        |
| Table                        | [1x561]     |
| gainY                        | 16384       |
| maxY                         | 32767       |
| maxX                         | 32767       |
| sfrX                         | 11          |
| sfrY                         | 12          |
| offsetX                      | 0           |
| sizeX                        | 33          |
| offsetY                      | 0           |
| minY                         | -32767      |
| minX                         | -32767      |
| gainXsfr                     | 14          |
| idxOffsetY                   | 8           |
| idxOffsetX                   | 16          |
| gainYsfr                     | 14          |
| Exp. gainX                   | 16384       |
| Exp. maskY                   | 4095        |
| Exp. maskX                   | 2047        |
| Exp. Table                   | [1x561]     |
| Exp. gainY                   | 16384       |
| Exp. maxY                    | 32767       |
| Exp. maxX                    | 32767       |
| Exp. sfrX                    | 11          |
| Exp. sfrY                    | 12          |
| Exp. offsetX                 | 0           |
| Exp. sizeX                   | 33          |
| Exp. offsetY                 | 0           |
| Exp. minY                    | 1814 -32767 |
| Exp. minX                    | -32767      |

| Test settings           |                  |
|-------------------------|------------------|
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |

**Verification: LookupTable2D FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block LookupTable2D.

| Test results   |         |        |        |        |     |        |
|----------------|---------|--------|--------|--------|-----|--------|
| Time step      | 1       | 2      | 3      | 4      | ... | 67     |
| CPU cycles     | 197     | 197    | 197    | 197    | ... | 198    |
| Inputs         |         |        |        |        |     |        |
| x (DSP)        | -32768  | -31775 | -30782 | -29789 | ... | 32767  |
| y (DSP)        | 26214   | 25370  | 24526  | 23682  | ... | -29491 |
| x              | -1      | -0.97  | -0.939 | -0.909 | ... | 1      |
| y              | 0.8     | 0.774  | 0.748  | 0.723  | ... | -0.9   |
| Parameters     |         |        |        |        |     |        |
| TableData      | [1x561] |        |        |        |     |        |
| DimX           | 17      |        |        |        |     |        |
| x_min          | -0.8    |        |        |        |     |        |
| x_max          | 0.7     |        |        |        |     |        |
| DimY           | 33      |        |        |        |     |        |
| y_min          | -0.6    |        |        |        |     |        |
| y_max          | 0.9     |        |        |        |     |        |
| Outputs        |         |        |        |        |     |        |
| Out            | -0      | -0.013 | -0.026 | -0.039 | ... | 0.05   |
| Exp. Out       | 0       | -0.013 | -0.026 | -0.039 | ... | 0.05   |
| Out (DSP)      | -1      | -423   | -845   | -1267  | ... | 1637   |
| Exp. Out (DSP) | 0       | -422   | -844   | -1266  | ... | 1638   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,1553e-05$ ( $\pm 3$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 197 |
| Max CPU cycles  | 217 |
| Avg CPU cycles  | 209 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable2D.

| Test results          |             |
|-----------------------|-------------|
| Time step             | 1           |
| Mask parameters       |             |
| TableData             | [1x561]     |
| DimX                  | 33          |
| x_min                 | -1          |
| x_max                 | 1           |
| DimY                  | 17          |
| y_min                 | -1          |
| y_max                 | 1           |
| Controller parameters |             |
| gainX                 | 16384       |
| maskY                 | 4095        |
| maskX                 | 2047        |
| Table                 | [1x561]     |
| gainY                 | 16384       |
| maxY                  | 32767       |
| maxX                  | 32767       |
| sfrX                  | 11          |
| sfrY                  | 12          |
| offsetX               | 0           |
| sizeX                 | 33          |
| offsetY               | 0           |
| minY                  | -32767      |
| minX                  | -32767      |
| gainXsfr              | 14          |
| idxOffsetY            | 8           |
| idxOffsetX            | 16          |
| gainYsfr              | 14          |
| Exp. gainX            | 16384       |
| Exp. maskY            | 4095        |
| Exp. maskX            | 2047        |
| Exp. Table            | [1x561]     |
| Exp. gainY            | 16384       |
| Exp. maxY             | 32767       |
| Exp. maxX             | 32767       |
| Exp. sfrX             | 11          |
| Exp. sfrY             | 12          |
| Exp. offsetX          | 0           |
| Exp. sizeX            | 33          |
| Exp. offsetY          | 0           |
| Exp. minY             | 1817 -32767 |
| Exp. minX             | -32767      |

| Test settings           |                  |
|-------------------------|------------------|
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |

**Verification: LookupTable2D FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block LookupTable2D.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 67          |
| CPU cycles     | 312         | 312         | ... | 294         |
| Inputs         |             |             |     |             |
| x (DSP)        | -2147483648 | -2082408386 | ... | 2147483647  |
| y (DSP)        | 1717986918  | 1662672946  | ... | -1932735283 |
| x              | -1          | -0.97       | ... | 1           |
| y              | 0.8         | 0.774       | ... | -0.9        |
| Parameters     |             |             |     |             |
| TableData      | [1x561]     |             |     |             |
| DimX           | 17          |             |     |             |
| x_min          | -0.8        |             |     |             |
| x_max          | 0.7         |             |     |             |
| DimY           | 33          |             |     |             |
| y_min          | -0.6        |             |     |             |
| y_max          | 0.9         |             |     |             |
| Outputs        |             |             |     |             |
| Out            | -0          | -0.013      | ... | 0.05        |
| Exp. Out       | 0           | -0.013      | ... | 0.05        |
| Out (DSP)      | -1          | -27656987   | ... | 107374181   |
| Exp. Out (DSP) | 0           | -27656986   | ... | 107374182   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 294 |
| Max CPU cycles  | 342 |
| Avg CPU cycles  | 330 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable2D.



| Test results          |                             |
|-----------------------|-----------------------------|
| Time step             | 1                           |
| Mask parameters       |                             |
| TableData             | [1x561]                     |
| DimX                  | 33                          |
| x_min                 | -0.8                        |
| x_max                 | 0.7                         |
| DimY                  | 17                          |
| y_min                 | -0.6                        |
| y_max                 | 0.9                         |
| Controller parameters |                             |
| gainX                 | 1431655765                  |
| maskY                 | 268435455                   |
| maskX                 | 134217727                   |
| Table                 | [1x561]                     |
| gainY                 | 1431655765                  |
| maxY                  | 1932735283                  |
| maxX                  | 1503238554                  |
| sfrX                  | 27                          |
| sfrY                  | 28                          |
| offsetX               | -107374182                  |
| sizeX                 | 33                          |
| offsetY               | 322122547                   |
| minY                  | -1288490189                 |
| minX                  | -1717986918                 |
| gainXsfr              | 30                          |
| idxOffsetY            | 8                           |
| idxOffsetX            | 16                          |
| gainYsfr              | 30                          |
| Exp. gainX            | 1431655765                  |
| Exp. maskY            | 268435455                   |
| Exp. maskX            | 134217727                   |
| Exp. Table            | [1x561]                     |
| Exp. gainY            | 1431655765                  |
| Exp. maxY             | 1932735283                  |
| Exp. maxX             | 1503238554                  |
| Exp. sfrX             | 27                          |
| Exp. sfrY             | 28                          |
| Exp. offsetX          | -107374182                  |
| Exp. sizeX            | 33                          |
| Exp. offsetY          | 322122547                   |
| Exp. minY             | <sup>1820</sup> -1288490189 |
| Exp. minX             | -1717986918                 |

| Test settings           |                  |
|-------------------------|------------------|
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |

**Verification: LookupTable2D FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block LookupTable2D.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 67          |
| CPU cycles     | 401         | 401         | ... | 345         |
| Inputs         |             |             |     |             |
| x (DSP)        | -2147483648 | -2082408386 | ... | 2147483647  |
| y (DSP)        | 1717986918  | 1662672946  | ... | -1932735283 |
| x              | -1          | -0.97       | ... | 1           |
| y              | 0.8         | 0.774       | ... | -0.9        |
| Parameters     |             |             |     |             |
| TableData      | [1x561]     |             |     |             |
| DimX           | 17          |             |     |             |
| x_min          | -0.8        |             |     |             |
| x_max          | 0.7         |             |     |             |
| DimY           | 33          |             |     |             |
| y_min          | -0.6        |             |     |             |
| y_max          | 0.9         |             |     |             |
| Outputs        |             |             |     |             |
| Out            | -0          | -0.013      | ... | 0.05        |
| Exp. Out       | 0           | -0.013      | ... | 0.05        |
| Out (DSP)      | -1          | -27656987   | ... | 107374181   |
| Exp. Out (DSP) | 0           | -27656986   | ... | 107374182   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 345 |
| Max CPU cycles  | 463 |
| Avg CPU cycles  | 437 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable2D.

| Test results          |                             |
|-----------------------|-----------------------------|
| Time step             | 1                           |
| Mask parameters       |                             |
| TableData             | [1x561]                     |
| DimX                  | 33                          |
| x_min                 | -0.8                        |
| x_max                 | 0.7                         |
| DimY                  | 17                          |
| y_min                 | -0.6                        |
| y_max                 | 0.9                         |
| Controller parameters |                             |
| gainX                 | 1431655765                  |
| maskY                 | 268435455                   |
| maskX                 | 134217727                   |
| Table                 | [1x561]                     |
| gainY                 | 1431655765                  |
| maxY                  | 1932735283                  |
| maxX                  | 1503238554                  |
| sfrX                  | 27                          |
| sfrY                  | 28                          |
| offsetX               | -107374182                  |
| sizeX                 | 33                          |
| offsetY               | 322122547                   |
| minY                  | -1288490189                 |
| minX                  | -1717986918                 |
| gainXsfr              | 30                          |
| idxOffsetY            | 8                           |
| idxOffsetX            | 16                          |
| gainYsfr              | 30                          |
| Exp. gainX            | 1431655765                  |
| Exp. maskY            | 268435455                   |
| Exp. maskX            | 134217727                   |
| Exp. Table            | [1x561]                     |
| Exp. gainY            | 1431655765                  |
| Exp. maxY             | 1932735283                  |
| Exp. maxX             | 1503238554                  |
| Exp. sfrX             | 27                          |
| Exp. sfrY             | 28                          |
| Exp. offsetX          | -107374182                  |
| Exp. sizeX            | 33                          |
| Exp. offsetY          | 322122547                   |
| Exp. minY             | <sup>1823</sup> -1288490189 |
| Exp. minX             | -1717986918                 |

| Test settings           |                  |
|-------------------------|------------------|
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |

**Verification: LookupTable2D FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block LookupTable2D.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 67          |
| CPU cycles     | 374         | 374         | ... | 321         |
| Inputs         |             |             |     |             |
| x (DSP)        | -2147483648 | -2082408386 | ... | 2147483647  |
| y (DSP)        | 1717986918  | 1662672946  | ... | -1932735283 |
| x              | -1          | -0.97       | ... | 1           |
| y              | 0.8         | 0.774       | ... | -0.9        |
| Parameters     |             |             |     |             |
| TableData      | [1x561]     |             |     |             |
| DimX           | 17          |             |     |             |
| x_min          | -0.8        |             |     |             |
| x_max          | 0.7         |             |     |             |
| DimY           | 33          |             |     |             |
| y_min          | -0.6        |             |     |             |
| y_max          | 0.9         |             |     |             |
| Outputs        |             |             |     |             |
| Out            | -0          | -0.013      | ... | 0.05        |
| Exp. Out       | 0           | -0.013      | ... | 0.05        |
| Out (DSP)      | -1          | -27656987   | ... | 107374181   |
| Exp. Out (DSP) | 0           | -27656986   | ... | 107374182   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 321 |
| Max CPU cycles  | 412 |
| Avg CPU cycles  | 393 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable2D.

| Test results          |                             |
|-----------------------|-----------------------------|
| Time step             | 1                           |
| Mask parameters       |                             |
| TableData             | [1x561]                     |
| DimX                  | 33                          |
| x_min                 | -0.8                        |
| x_max                 | 0.7                         |
| DimY                  | 17                          |
| y_min                 | -0.6                        |
| y_max                 | 0.9                         |
| Controller parameters |                             |
| gainX                 | 1431655765                  |
| maskY                 | 268435455                   |
| maskX                 | 134217727                   |
| Table                 | [1x561]                     |
| gainY                 | 1431655765                  |
| maxY                  | 1932735283                  |
| maxX                  | 1503238554                  |
| sfrX                  | 27                          |
| sfrY                  | 28                          |
| offsetX               | -107374182                  |
| sizeX                 | 33                          |
| offsetY               | 322122547                   |
| minY                  | -1288490189                 |
| minX                  | -1717986918                 |
| gainXsfr              | 30                          |
| idxOffsetY            | 8                           |
| idxOffsetX            | 16                          |
| gainYsfr              | 30                          |
| Exp. gainX            | 1431655765                  |
| Exp. maskY            | 268435455                   |
| Exp. maskX            | 134217727                   |
| Exp. Table            | [1x561]                     |
| Exp. gainY            | 1431655765                  |
| Exp. maxY             | 1932735283                  |
| Exp. maxX             | 1503238554                  |
| Exp. sfrX             | 27                          |
| Exp. sfrY             | 28                          |
| Exp. offsetX          | -107374182                  |
| Exp. sizeX            | 33                          |
| Exp. offsetY          | 322122547                   |
| Exp. minY             | <sup>1826</sup> -1288490189 |
| Exp. minX             | -1717986918                 |

| Test settings           |                  |
|-------------------------|------------------|
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |



**Verification: LookupTable2D FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block LookupTable2D.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 67          |
| CPU cycles     | 737         | 737         | ... | 632         |
| Inputs         |             |             |     |             |
| x (DSP)        | -2147483648 | -2082408386 | ... | 2147483647  |
| y (DSP)        | 1717986918  | 1662672946  | ... | -1932735283 |
| x              | -1          | -0.97       | ... | 1           |
| y              | 0.8         | 0.774       | ... | -0.9        |
| Parameters     |             |             |     |             |
| TableData      | [1x561]     |             |     |             |
| DimX           | 17          |             |     |             |
| x_min          | -0.8        |             |     |             |
| x_max          | 0.7         |             |     |             |
| DimY           | 33          |             |     |             |
| y_min          | -0.6        |             |     |             |
| y_max          | 0.9         |             |     |             |
| Outputs        |             |             |     |             |
| Out            | -0          | -0.013      | ... | 0.05        |
| Exp. Out       | 0           | -0.013      | ... | 0.05        |
| Out (DSP)      | -1          | -27656987   | ... | 107374181   |
| Exp. Out (DSP) | 0           | -27656986   | ... | 107374182   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 632 |
| Max CPU cycles  | 899 |
| Avg CPU cycles  | 797 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable2D.

| Test results          |                  |
|-----------------------|------------------|
| Time step             | 1                |
| Mask parameters       |                  |
| TableData             | [1x561]          |
| DimX                  | 33               |
| x_min                 | -0.8             |
| x_max                 | 0.7              |
| DimY                  | 17               |
| y_min                 | -0.6             |
| y_max                 | 0.9              |
| Controller parameters |                  |
| gainX                 | 1431655765       |
| maskY                 | 268435455        |
| maskX                 | 134217727        |
| Table                 | [1x561]          |
| gainY                 | 1431655765       |
| maxY                  | 1932735283       |
| maxX                  | 1503238554       |
| sfrX                  | 27               |
| sfrY                  | 28               |
| offsetX               | -107374182       |
| sizeX                 | 33               |
| offsetY               | 322122547        |
| minY                  | -1288490189      |
| minX                  | -1717986918      |
| gainXsfr              | 30               |
| idxOffsetY            | 8                |
| idxOffsetX            | 16               |
| gainYsfr              | 30               |
| Exp. gainX            | 1431655765       |
| Exp. maskY            | 268435455        |
| Exp. maskX            | 134217727        |
| Exp. Table            | [1x561]          |
| Exp. gainY            | 1431655765       |
| Exp. maxY             | 1932735283       |
| Exp. maxX             | 1503238554       |
| Exp. sfrX             | 27               |
| Exp. sfrY             | 28               |
| Exp. offsetX          | -107374182       |
| Exp. sizeX            | 33               |
| Exp. offsetY          | 322122547        |
| Exp. minY             | 1829 -1288490189 |
| Exp. minX             | -1717986918      |

| Test settings           |                  |
|-------------------------|------------------|
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |

**Verification: LookupTable2D FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block LookupTable2D.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 67          |
| CPU cycles     | 267         | 267         | ... | 234         |
| Inputs         |             |             |     |             |
| x (DSP)        | -2147483648 | -2082408386 | ... | 2147483647  |
| y (DSP)        | 1717986918  | 1662672946  | ... | -1932735283 |
| x              | -1          | -0.97       | ... | 1           |
| y              | 0.8         | 0.774       | ... | -0.9        |
| Parameters     |             |             |     |             |
| TableData      | [1x561]     |             |     |             |
| DimX           | 17          |             |     |             |
| x_min          | -0.8        |             |     |             |
| x_max          | 0.7         |             |     |             |
| DimY           | 33          |             |     |             |
| y_min          | -0.6        |             |     |             |
| y_max          | 0.9         |             |     |             |
| Outputs        |             |             |     |             |
| Out            | -0          | -0.013      | ... | 0.05        |
| Exp. Out       | 0           | -0.013      | ... | 0.05        |
| Out (DSP)      | -1          | -27656987   | ... | 107374181   |
| Exp. Out (DSP) | 0           | -27656986   | ... | 107374182   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 234 |
| Max CPU cycles  | 307 |
| Avg CPU cycles  | 290 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable2D.

| Test results                 |                  |
|------------------------------|------------------|
| Time step                    | 1                |
| <i>Mask parameters</i>       |                  |
| TableData                    | [1x561]          |
| DimX                         | 33               |
| x_min                        | -0.8             |
| x_max                        | 0.7              |
| DimY                         | 17               |
| y_min                        | -0.6             |
| y_max                        | 0.9              |
| <i>Controller parameters</i> |                  |
| gainX                        | 1431655765       |
| maskY                        | 268435455        |
| maskX                        | 134217727        |
| Table                        | [1x561]          |
| gainY                        | 1431655765       |
| maxY                         | 1932735283       |
| maxX                         | 1503238554       |
| sfrX                         | 27               |
| sfrY                         | 28               |
| offsetX                      | -107374182       |
| sizeX                        | 33               |
| offsetY                      | 322122547        |
| minY                         | -1288490189      |
| minX                         | -1717986918      |
| gainXsfr                     | 30               |
| idxOffsetY                   | 8                |
| idxOffsetX                   | 16               |
| gainYsfr                     | 30               |
| Exp. gainX                   | 1431655765       |
| Exp. maskY                   | 268435455        |
| Exp. maskX                   | 134217727        |
| Exp. Table                   | [1x561]          |
| Exp. gainY                   | 1431655765       |
| Exp. maxY                    | 1932735283       |
| Exp. maxX                    | 1503238554       |
| Exp. sfrX                    | 27               |
| Exp. sfrY                    | 28               |
| Exp. offsetX                 | -107374182       |
| Exp. sizeX                   | 33               |
| Exp. offsetY                 | 322122547        |
| Exp. minY                    | 1832 -1288490189 |
| Exp. minX                    | -1717986918      |

| Test settings           |                  |
|-------------------------|------------------|
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |

**Verification: LookupTable2D FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block LookupTable2D.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 67          |
| CPU cycles     | 2269        | 2269        | ... | 1853        |
| Inputs         |             |             |     |             |
| x (DSP)        | -2147483648 | -2082408386 | ... | 2147483647  |
| y (DSP)        | 1717986918  | 1662672946  | ... | -1932735283 |
| x              | -1          | -0.97       | ... | 1           |
| y              | 0.8         | 0.774       | ... | -0.9        |
| Parameters     |             |             |     |             |
| TableData      | [1x561]     |             |     |             |
| DimX           | 17          |             |     |             |
| x_min          | -0.8        |             |     |             |
| x_max          | 0.7         |             |     |             |
| DimY           | 33          |             |     |             |
| y_min          | -0.6        |             |     |             |
| y_max          | 0.9         |             |     |             |
| Outputs        |             |             |     |             |
| Out            | -0          | -0.013      | ... | 0.05        |
| Exp. Out       | 0           | -0.013      | ... | 0.05        |
| Out (DSP)      | -1          | -27656987   | ... | 107374181   |
| Exp. Out (DSP) | 0           | -27656986   | ... | 107374182   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1853 |
| Max CPU cycles  | 2702 |
| Avg CPU cycles  | 2512 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable2D.

| Test results          |                  |
|-----------------------|------------------|
| Time step             | 1                |
| Mask parameters       |                  |
| TableData             | [1x561]          |
| DimX                  | 33               |
| x_min                 | -0.8             |
| x_max                 | 0.7              |
| DimY                  | 17               |
| y_min                 | -0.6             |
| y_max                 | 0.9              |
| Controller parameters |                  |
| gainX                 | 1431655765       |
| maskY                 | 268435455        |
| maskX                 | 134217727        |
| Table                 | [1x561]          |
| gainY                 | 1431655765       |
| maxY                  | 1932735283       |
| maxX                  | 1503238554       |
| sfrX                  | 27               |
| sfrY                  | 28               |
| offsetX               | -107374182       |
| sizeX                 | 33               |
| offsetY               | 322122547        |
| minY                  | -1288490189      |
| minX                  | -1717986918      |
| gainXsfr              | 30               |
| idxOffsetY            | 8                |
| idxOffsetX            | 16               |
| gainYsfr              | 30               |
| Exp. gainX            | 1431655765       |
| Exp. maskY            | 268435455        |
| Exp. maskX            | 134217727        |
| Exp. Table            | [1x561]          |
| Exp. gainY            | 1431655765       |
| Exp. maxY             | 1932735283       |
| Exp. maxX             | 1503238554       |
| Exp. sfrX             | 27               |
| Exp. sfrY             | 28               |
| Exp. offsetX          | -107374182       |
| Exp. sizeX            | 33               |
| Exp. offsetY          | 322122547        |
| Exp. minY             | 1835 -1288490189 |
| Exp. minX             | -1717986918      |



| Test settings           |                  |
|-------------------------|------------------|
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |

**Verification: LookupTable2D FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block LookupTable2D.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 67          |
| CPU cycles     | 396         | 317         | ... | 298         |
| Inputs         |             |             |     |             |
| x (DSP)        | -2147483648 | -2082408386 | ... | 2147483647  |
| y (DSP)        | 1717986918  | 1662672946  | ... | -1932735283 |
| x              | -1          | -0.97       | ... | 1           |
| y              | 0.8         | 0.774       | ... | -0.9        |
| Parameters     |             |             |     |             |
| TableData      | [1x561]     |             |     |             |
| DimX           | 17          |             |     |             |
| x_min          | -0.8        |             |     |             |
| x_max          | 0.7         |             |     |             |
| DimY           | 33          |             |     |             |
| y_min          | -0.6        |             |     |             |
| y_max          | 0.9         |             |     |             |
| Outputs        |             |             |     |             |
| Out            | -0          | -0.013      | ... | 0.05        |
| Exp. Out       | 0           | -0.013      | ... | 0.05        |
| Out (DSP)      | -1          | -27656987   | ... | 107374181   |
| Exp. Out (DSP) | 0           | -27656986   | ... | 107374182   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 298 |
| Max CPU cycles  | 396 |
| Avg CPU cycles  | 330 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable2D.

| Test results          |                  |
|-----------------------|------------------|
| Time step             | 1                |
| Mask parameters       |                  |
| TableData             | [1x561]          |
| DimX                  | 33               |
| x_min                 | -0.8             |
| x_max                 | 0.7              |
| DimY                  | 17               |
| y_min                 | -0.6             |
| y_max                 | 0.9              |
| Controller parameters |                  |
| gainX                 | 1431655765       |
| maskY                 | 268435455        |
| maskX                 | 134217727        |
| Table                 | [1x561]          |
| gainY                 | 1431655765       |
| maxY                  | 1932735283       |
| maxX                  | 1503238554       |
| sfrX                  | 27               |
| sfrY                  | 28               |
| offsetX               | -107374182       |
| sizeX                 | 33               |
| offsetY               | 322122547        |
| minY                  | -1288490189      |
| minX                  | -1717986918      |
| gainXsfr              | 30               |
| idxOffsetY            | 8                |
| idxOffsetX            | 16               |
| gainYsfr              | 30               |
| Exp. gainX            | 1431655765       |
| Exp. maskY            | 268435455        |
| Exp. maskX            | 134217727        |
| Exp. Table            | [1x561]          |
| Exp. gainY            | 1431655765       |
| Exp. maxY             | 1932735283       |
| Exp. maxX             | 1503238554       |
| Exp. sfrX             | 27               |
| Exp. sfrY             | 28               |
| Exp. offsetX          | -107374182       |
| Exp. sizeX            | 33               |
| Exp. offsetY          | 322122547        |
| Exp. minY             | 1838 -1288490189 |
| Exp. minX             | -1717986918      |

| Test settings           |                  |
|-------------------------|------------------|
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |

**Verification: LookupTable2D FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block LookupTable2D.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 67          |
| CPU cycles     | 287         | 287         | ... | 276         |
| Inputs         |             |             |     |             |
| x (DSP)        | -2147483648 | -2082408386 | ... | 2147483647  |
| y (DSP)        | 1717986918  | 1662672946  | ... | -1932735283 |
| x              | -1          | -0.97       | ... | 1           |
| y              | 0.8         | 0.774       | ... | -0.9        |
| Parameters     |             |             |     |             |
| TableData      | [1x561]     |             |     |             |
| DimX           | 17          |             |     |             |
| x_min          | -0.8        |             |     |             |
| x_max          | 0.7         |             |     |             |
| DimY           | 33          |             |     |             |
| y_min          | -0.6        |             |     |             |
| y_max          | 0.9         |             |     |             |
| Outputs        |             |             |     |             |
| Out            | -0          | -0.013      | ... | 0.05        |
| Exp. Out       | 0           | -0.013      | ... | 0.05        |
| Out (DSP)      | -1          | -27656987   | ... | 107374181   |
| Exp. Out (DSP) | 0           | -27656986   | ... | 107374182   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 276 |
| Max CPU cycles  | 324 |
| Avg CPU cycles  | 309 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable2D.

| Test results          |                  |
|-----------------------|------------------|
| Time step             | 1                |
| Mask parameters       |                  |
| TableData             | [1x561]          |
| DimX                  | 33               |
| x_min                 | -0.8             |
| x_max                 | 0.7              |
| DimY                  | 17               |
| y_min                 | -0.6             |
| y_max                 | 0.9              |
| Controller parameters |                  |
| gainX                 | 1431655765       |
| maskY                 | 268435455        |
| maskX                 | 134217727        |
| Table                 | [1x561]          |
| gainY                 | 1431655765       |
| maxY                  | 1932735283       |
| maxX                  | 1503238554       |
| sfrX                  | 27               |
| sfrY                  | 28               |
| offsetX               | -107374182       |
| sizeX                 | 33               |
| offsetY               | 322122547        |
| minY                  | -1288490189      |
| minX                  | -1717986918      |
| gainXsfr              | 30               |
| idxOffsetY            | 8                |
| idxOffsetX            | 16               |
| gainYsfr              | 30               |
| Exp. gainX            | 1431655765       |
| Exp. maskY            | 268435455        |
| Exp. maskX            | 134217727        |
| Exp. Table            | [1x561]          |
| Exp. gainY            | 1431655765       |
| Exp. maxY             | 1932735283       |
| Exp. maxX             | 1503238554       |
| Exp. sfrX             | 27               |
| Exp. sfrY             | 28               |
| Exp. offsetX          | -107374182       |
| Exp. sizeX            | 33               |
| Exp. offsetY          | 322122547        |
| Exp. minY             | 1841 -1288490189 |
| Exp. minX             | -1717986918      |

| Test settings           |                  |
|-------------------------|------------------|
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |

**Verification: LookupTable2D Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block LookupTable2D.

| Test results   |         |        |     |       |
|----------------|---------|--------|-----|-------|
| Time step      | 1       | 2      | ... | 67    |
| CPU cycles     | 185     | 185    | ... | 186   |
| Inputs         |         |        |     |       |
| x (DSP)        | -1.1    | -1.067 | ... | 1.1   |
| y (DSP)        | 1.2     | 1.161  | ... | -1.35 |
| x              | -1.1    | -1.067 | ... | 1.1   |
| y              | 1.2     | 1.161  | ... | -1.35 |
| Parameters     |         |        |     |       |
| TableData      | [1x561] |        |     |       |
| DimX           | 17      |        |     |       |
| x_min          | -0.8    |        |     |       |
| x_max          | 0.7     |        |     |       |
| DimY           | 33      |        |     |       |
| y_min          | -0.6    |        |     |       |
| y_max          | 0.9     |        |     |       |
| Outputs        |         |        |     |       |
| Out            | 0.155   | 0.155  | ... | 0.155 |
| Exp. Out       | 0.155   | 0.155  | ... | 0.155 |
| Out (DSP)      | 0.155   | 0.155  | ... | 0.155 |
| Exp. Out (DSP) | 0.155   | 0.155  | ... | 0.155 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 185 |
| Max CPU cycles  | 186 |
| Avg CPU cycles  | 185 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable2D.



| Test results                 |         |
|------------------------------|---------|
| Time step                    | 1       |
| <i>Mask parameters</i>       |         |
| TableData                    | [1x561] |
| DimX                         | 33      |
| x_min                        | -0.8    |
| x_max                        | 0.7     |
| DimY                         | 17      |
| y_min                        | -0.6    |
| y_max                        | 0.9     |
| <i>Controller parameters</i> |         |
| gainX                        | 21.333  |
| offsetX                      | -0.8    |
| Table                        | [1x561] |
| gainY                        | 10.667  |
| offsetY                      | -0.6    |
| minY                         | -0.6    |
| minX                         | -0.8    |
| maxY                         | 0.9     |
| maxX                         | 0.7     |
| dimY                         | 16      |
| dimX                         | 32      |
| Exp. gainX                   | 21.333  |
| Exp. offsetX                 | -0.8    |
| Exp. Table                   | [1x561] |
| Exp. gainY                   | 10.667  |
| Exp. offsetY                 | -0.6    |
| Exp. minY                    | -0.6    |
| Exp. minX                    | -0.8    |
| Exp. maxY                    | 0.9     |
| Exp. maxX                    | 0.7     |
| Exp. dimY                    | 16      |
| Exp. dimX                    | 32      |

| Test settings     |                  |
|-------------------|------------------|
| Tolerance gainX   | $\pm 0,0000e+00$ |
| Tolerance offsetX | $\pm 0,0000e+00$ |
| Tolerance Table   | $\pm 0,0000e+00$ |
| Tolerance gainY   | $\pm 0,0000e+00$ |
| Tolerance offsetY | $\pm 0,0000e+00$ |
| Tolerance minY    | $\pm 0,0000e+00$ |
| Tolerance minX    | $\pm 0,0000e+00$ |
| Tolerance maxY    | $\pm 0,0000e+00$ |
| Tolerance maxX    | $\pm 0,0000e+00$ |
| Tolerance dimY    | $\pm 0,0000e+00$ |
| Tolerance dimX    | $\pm 0,0000e+00$ |

**Verification: LookupTable2D Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block LookupTable2D.

| Test results   |         |        |     |       |
|----------------|---------|--------|-----|-------|
| Time step      | 1       | 2      | ... | 67    |
| CPU cycles     | 139     | 139    | ... | 143   |
| Inputs         |         |        |     |       |
| x (DSP)        | -1.1    | -1.067 | ... | 1.1   |
| y (DSP)        | 1.2     | 1.161  | ... | -1.35 |
| x              | -1.1    | -1.067 | ... | 1.1   |
| y              | 1.2     | 1.161  | ... | -1.35 |
| Parameters     |         |        |     |       |
| TableData      | [1x561] |        |     |       |
| DimX           | 17      |        |     |       |
| x_min          | -0.8    |        |     |       |
| x_max          | 0.7     |        |     |       |
| DimY           | 33      |        |     |       |
| y_min          | -0.6    |        |     |       |
| y_max          | 0.9     |        |     |       |
| Outputs        |         |        |     |       |
| Out            | 0.155   | 0.155  | ... | 0.155 |
| Exp. Out       | 0.155   | 0.155  | ... | 0.155 |
| Out (DSP)      | 0.155   | 0.155  | ... | 0.155 |
| Exp. Out (DSP) | 0.155   | 0.155  | ... | 0.155 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 139 |
| Max CPU cycles  | 147 |
| Avg CPU cycles  | 144 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable2D.

| Test results                 |         |
|------------------------------|---------|
| Time step                    | 1       |
| <i>Mask parameters</i>       |         |
| TableData                    | [1x561] |
| DimX                         | 33      |
| x_min                        | -0.8    |
| x_max                        | 0.7     |
| DimY                         | 17      |
| y_min                        | -0.6    |
| y_max                        | 0.9     |
| <i>Controller parameters</i> |         |
| gainX                        | 21.333  |
| offsetX                      | -0.8    |
| Table                        | [1x561] |
| gainY                        | 10.667  |
| offsetY                      | -0.6    |
| minY                         | -0.6    |
| minX                         | -0.8    |
| maxY                         | 0.9     |
| maxX                         | 0.7     |
| dimY                         | 16      |
| dimX                         | 32      |
| Exp. gainX                   | 21.333  |
| Exp. offsetX                 | -0.8    |
| Exp. Table                   | [1x561] |
| Exp. gainY                   | 10.667  |
| Exp. offsetY                 | -0.6    |
| Exp. minY                    | -0.6    |
| Exp. minX                    | -0.8    |
| Exp. maxY                    | 0.9     |
| Exp. maxX                    | 0.7     |
| Exp. dimY                    | 16      |
| Exp. dimX                    | 32      |

| Test settings     |                  |
|-------------------|------------------|
| Tolerance gainX   | $\pm 0,0000e+00$ |
| Tolerance offsetX | $\pm 0,0000e+00$ |
| Tolerance Table   | $\pm 0,0000e+00$ |
| Tolerance gainY   | $\pm 0,0000e+00$ |
| Tolerance offsetY | $\pm 0,0000e+00$ |
| Tolerance minY    | $\pm 0,0000e+00$ |
| Tolerance minX    | $\pm 0,0000e+00$ |
| Tolerance maxY    | $\pm 0,0000e+00$ |
| Tolerance maxX    | $\pm 0,0000e+00$ |
| Tolerance dimY    | $\pm 0,0000e+00$ |
| Tolerance dimX    | $\pm 0,0000e+00$ |

**Verification: LookupTable2D Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block LookupTable2D.

| Test results   |         |        |     |       |
|----------------|---------|--------|-----|-------|
| Time step      | 1       | 2      | ... | 67    |
| CPU cycles     | 219     | 219    | ... | 224   |
| Inputs         |         |        |     |       |
| x (DSP)        | -1.1    | -1.067 | ... | 1.1   |
| y (DSP)        | 1.2     | 1.161  | ... | -1.35 |
| x              | -1.1    | -1.067 | ... | 1.1   |
| y              | 1.2     | 1.161  | ... | -1.35 |
| Parameters     |         |        |     |       |
| TableData      | [1x561] |        |     |       |
| DimX           | 17      |        |     |       |
| x_min          | -0.8    |        |     |       |
| x_max          | 0.7     |        |     |       |
| DimY           | 33      |        |     |       |
| y_min          | -0.6    |        |     |       |
| y_max          | 0.9     |        |     |       |
| Outputs        |         |        |     |       |
| Out            | 0.155   | 0.155  | ... | 0.155 |
| Exp. Out       | 0.155   | 0.155  | ... | 0.155 |
| Out (DSP)      | 0.155   | 0.155  | ... | 0.155 |
| Exp. Out (DSP) | 0.155   | 0.155  | ... | 0.155 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 219 |
| Max CPU cycles  | 224 |
| Avg CPU cycles  | 223 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable2D.

| Test results                 |         |
|------------------------------|---------|
| Time step                    | 1       |
| <i>Mask parameters</i>       |         |
| TableData                    | [1x561] |
| DimX                         | 33      |
| x_min                        | -0.8    |
| x_max                        | 0.7     |
| DimY                         | 17      |
| y_min                        | -0.6    |
| y_max                        | 0.9     |
| <i>Controller parameters</i> |         |
| gainX                        | 21.333  |
| offsetX                      | -0.8    |
| Table                        | [1x561] |
| gainY                        | 10.667  |
| offsetY                      | -0.6    |
| minY                         | -0.6    |
| minX                         | -0.8    |
| maxY                         | 0.9     |
| maxX                         | 0.7     |
| dimY                         | 16      |
| dimX                         | 32      |
| Exp. gainX                   | 21.333  |
| Exp. offsetX                 | -0.8    |
| Exp. Table                   | [1x561] |
| Exp. gainY                   | 10.667  |
| Exp. offsetY                 | -0.6    |
| Exp. minY                    | -0.6    |
| Exp. minX                    | -0.8    |
| Exp. maxY                    | 0.9     |
| Exp. maxX                    | 0.7     |
| Exp. dimY                    | 16      |
| Exp. dimX                    | 32      |

| Test settings     |                  |
|-------------------|------------------|
| Tolerance gainX   | $\pm 0,0000e+00$ |
| Tolerance offsetX | $\pm 0,0000e+00$ |
| Tolerance Table   | $\pm 0,0000e+00$ |
| Tolerance gainY   | $\pm 0,0000e+00$ |
| Tolerance offsetY | $\pm 0,0000e+00$ |
| Tolerance minY    | $\pm 0,0000e+00$ |
| Tolerance minX    | $\pm 0,0000e+00$ |
| Tolerance maxY    | $\pm 0,0000e+00$ |
| Tolerance maxX    | $\pm 0,0000e+00$ |
| Tolerance dimY    | $\pm 0,0000e+00$ |
| Tolerance dimX    | $\pm 0,0000e+00$ |



**Verification: LookupTable2D Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block LookupTable2D.

| Test results   |         |        |     |       |
|----------------|---------|--------|-----|-------|
| Time step      | 1       | 2      | ... | 67    |
| CPU cycles     | 2921    | 2921   | ... | 3015  |
| Inputs         |         |        |     |       |
| x (DSP)        | -1.1    | -1.067 | ... | 1.1   |
| y (DSP)        | 1.2     | 1.161  | ... | -1.35 |
| x              | -1.1    | -1.067 | ... | 1.1   |
| y              | 1.2     | 1.161  | ... | -1.35 |
| Parameters     |         |        |     |       |
| TableData      | [1x561] |        |     |       |
| DimX           | 17      |        |     |       |
| x_min          | -0.8    |        |     |       |
| x_max          | 0.7     |        |     |       |
| DimY           | 33      |        |     |       |
| y_min          | -0.6    |        |     |       |
| y_max          | 0.9     |        |     |       |
| Outputs        |         |        |     |       |
| Out            | 0.155   | 0.155  | ... | 0.155 |
| Exp. Out       | 0.155   | 0.155  | ... | 0.155 |
| Out (DSP)      | 0.155   | 0.155  | ... | 0.155 |
| Exp. Out (DSP) | 0.155   | 0.155  | ... | 0.155 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2921 |
| Max CPU cycles  | 3789 |
| Avg CPU cycles  | 3376 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable2D.

| Test results                 |         |
|------------------------------|---------|
| Time step                    | 1       |
| <i>Mask parameters</i>       |         |
| TableData                    | [1x561] |
| DimX                         | 33      |
| x_min                        | -0.8    |
| x_max                        | 0.7     |
| DimY                         | 17      |
| y_min                        | -0.6    |
| y_max                        | 0.9     |
| <i>Controller parameters</i> |         |
| gainX                        | 21.333  |
| offsetX                      | -0.8    |
| Table                        | [1x561] |
| gainY                        | 10.667  |
| offsetY                      | -0.6    |
| minY                         | -0.6    |
| minX                         | -0.8    |
| maxY                         | 0.9     |
| maxX                         | 0.7     |
| dimY                         | 16      |
| dimX                         | 32      |
| Exp. gainX                   | 21.333  |
| Exp. offsetX                 | -0.8    |
| Exp. Table                   | [1x561] |
| Exp. gainY                   | 10.667  |
| Exp. offsetY                 | -0.6    |
| Exp. minY                    | -0.6    |
| Exp. minX                    | -0.8    |
| Exp. maxY                    | 0.9     |
| Exp. maxX                    | 0.7     |
| Exp. dimY                    | 16      |
| Exp. dimX                    | 32      |

| Test settings     |                  |
|-------------------|------------------|
| Tolerance gainX   | $\pm 0,0000e+00$ |
| Tolerance offsetX | $\pm 0,0000e+00$ |
| Tolerance Table   | $\pm 0,0000e+00$ |
| Tolerance gainY   | $\pm 0,0000e+00$ |
| Tolerance offsetY | $\pm 0,0000e+00$ |
| Tolerance minY    | $\pm 0,0000e+00$ |
| Tolerance minX    | $\pm 0,0000e+00$ |
| Tolerance maxY    | $\pm 0,0000e+00$ |
| Tolerance maxX    | $\pm 0,0000e+00$ |
| Tolerance dimY    | $\pm 0,0000e+00$ |
| Tolerance dimX    | $\pm 0,0000e+00$ |

**Verification: LookupTable2D Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block LookupTable2D.

| Test results   |         |        |     |       |
|----------------|---------|--------|-----|-------|
| Time step      | 1       | 2      | ... | 67    |
| CPU cycles     | 1125    | 1125   | ... | 1135  |
| Inputs         |         |        |     |       |
| x (DSP)        | -1.1    | -1.067 | ... | 1.1   |
| y (DSP)        | 1.2     | 1.161  | ... | -1.35 |
| x              | -1.1    | -1.067 | ... | 1.1   |
| y              | 1.2     | 1.161  | ... | -1.35 |
| Parameters     |         |        |     |       |
| TableData      | [1x561] |        |     |       |
| DimX           | 17      |        |     |       |
| x_min          | -0.8    |        |     |       |
| x_max          | 0.7     |        |     |       |
| DimY           | 33      |        |     |       |
| y_min          | -0.6    |        |     |       |
| y_max          | 0.9     |        |     |       |
| Outputs        |         |        |     |       |
| Out            | 0.155   | 0.155  | ... | 0.155 |
| Exp. Out       | 0.155   | 0.155  | ... | 0.155 |
| Out (DSP)      | 0.155   | 0.155  | ... | 0.155 |
| Exp. Out (DSP) | 0.155   | 0.155  | ... | 0.155 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1125 |
| Max CPU cycles  | 1431 |
| Avg CPU cycles  | 1272 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable2D.

| Test results                 |         |
|------------------------------|---------|
| Time step                    | 1       |
| <i>Mask parameters</i>       |         |
| TableData                    | [1x561] |
| DimX                         | 33      |
| x_min                        | -0.8    |
| x_max                        | 0.7     |
| DimY                         | 17      |
| y_min                        | -0.6    |
| y_max                        | 0.9     |
| <i>Controller parameters</i> |         |
| gainX                        | 21.333  |
| offsetX                      | -0.8    |
| Table                        | [1x561] |
| gainY                        | 10.667  |
| offsetY                      | -0.6    |
| minY                         | -0.6    |
| minX                         | -0.8    |
| maxY                         | 0.9     |
| maxX                         | 0.7     |
| dimY                         | 16      |
| dimX                         | 32      |
| Exp. gainX                   | 21.333  |
| Exp. offsetX                 | -0.8    |
| Exp. Table                   | [1x561] |
| Exp. gainY                   | 10.667  |
| Exp. offsetY                 | -0.6    |
| Exp. minY                    | -0.6    |
| Exp. minX                    | -0.8    |
| Exp. maxY                    | 0.9     |
| Exp. maxX                    | 0.7     |
| Exp. dimY                    | 16      |
| Exp. dimX                    | 32      |

| Test settings     |                  |
|-------------------|------------------|
| Tolerance gainX   | $\pm 0,0000e+00$ |
| Tolerance offsetX | $\pm 0,0000e+00$ |
| Tolerance Table   | $\pm 0,0000e+00$ |
| Tolerance gainY   | $\pm 0,0000e+00$ |
| Tolerance offsetY | $\pm 0,0000e+00$ |
| Tolerance minY    | $\pm 0,0000e+00$ |
| Tolerance minX    | $\pm 0,0000e+00$ |
| Tolerance maxY    | $\pm 0,0000e+00$ |
| Tolerance maxX    | $\pm 0,0000e+00$ |
| Tolerance dimY    | $\pm 0,0000e+00$ |
| Tolerance dimX    | $\pm 0,0000e+00$ |

**Verification: LookupTable2D Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block LookupTable2D.

| Test results   |         |        |     |       |
|----------------|---------|--------|-----|-------|
| Time step      | 1       | 2      | ... | 67    |
| CPU cycles     | 3485    | 3485   | ... | 4028  |
| Inputs         |         |        |     |       |
| x (DSP)        | -1.1    | -1.067 | ... | 1.1   |
| y (DSP)        | 1.2     | 1.161  | ... | -1.35 |
| x              | -1.1    | -1.067 | ... | 1.1   |
| y              | 1.2     | 1.161  | ... | -1.35 |
| Parameters     |         |        |     |       |
| TableData      | [1x561] |        |     |       |
| DimX           | 17      |        |     |       |
| x_min          | -0.8    |        |     |       |
| x_max          | 0.7     |        |     |       |
| DimY           | 33      |        |     |       |
| y_min          | -0.6    |        |     |       |
| y_max          | 0.9     |        |     |       |
| Outputs        |         |        |     |       |
| Out            | 0.155   | 0.155  | ... | 0.155 |
| Exp. Out       | 0.155   | 0.155  | ... | 0.155 |
| Out (DSP)      | 0.155   | 0.155  | ... | 0.155 |
| Exp. Out (DSP) | 0.155   | 0.155  | ... | 0.155 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3485 |
| Max CPU cycles  | 5208 |
| Avg CPU cycles  | 4323 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable2D.

| Test results                 |         |
|------------------------------|---------|
| Time step                    | 1       |
| <i>Mask parameters</i>       |         |
| TableData                    | [1x561] |
| DimX                         | 33      |
| x_min                        | -0.8    |
| x_max                        | 0.7     |
| DimY                         | 17      |
| y_min                        | -0.6    |
| y_max                        | 0.9     |
| <i>Controller parameters</i> |         |
| gainX                        | 21.333  |
| offsetX                      | -0.8    |
| Table                        | [1x561] |
| gainY                        | 10.667  |
| offsetY                      | -0.6    |
| minY                         | -0.6    |
| minX                         | -0.8    |
| maxY                         | 0.9     |
| maxX                         | 0.7     |
| dimY                         | 16      |
| dimX                         | 32      |
| Exp. gainX                   | 21.333  |
| Exp. offsetX                 | -0.8    |
| Exp. Table                   | [1x561] |
| Exp. gainY                   | 10.667  |
| Exp. offsetY                 | -0.6    |
| Exp. minY                    | -0.6    |
| Exp. minX                    | -0.8    |
| Exp. maxY                    | 0.9     |
| Exp. maxX                    | 0.7     |
| Exp. dimY                    | 16      |
| Exp. dimX                    | 32      |



| Test settings     |                  |
|-------------------|------------------|
| Tolerance gainX   | $\pm 0,0000e+00$ |
| Tolerance offsetX | $\pm 0,0000e+00$ |
| Tolerance Table   | $\pm 0,0000e+00$ |
| Tolerance gainY   | $\pm 0,0000e+00$ |
| Tolerance offsetY | $\pm 0,0000e+00$ |
| Tolerance minY    | $\pm 0,0000e+00$ |
| Tolerance minX    | $\pm 0,0000e+00$ |
| Tolerance maxY    | $\pm 0,0000e+00$ |
| Tolerance maxX    | $\pm 0,0000e+00$ |
| Tolerance dimY    | $\pm 0,0000e+00$ |
| Tolerance dimX    | $\pm 0,0000e+00$ |

**Verification: LookupTable2D Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block LookupTable2D.

| Test results   |         |        |     |       |
|----------------|---------|--------|-----|-------|
| Time step      | 1       | 2      | ... | 67    |
| CPU cycles     | 218     | 171    | ... | 171   |
| Inputs         |         |        |     |       |
| x (DSP)        | -1.1    | -1.067 | ... | 1.1   |
| y (DSP)        | 1.2     | 1.161  | ... | -1.35 |
| x              | -1.1    | -1.067 | ... | 1.1   |
| y              | 1.2     | 1.161  | ... | -1.35 |
| Parameters     |         |        |     |       |
| TableData      | [1x561] |        |     |       |
| DimX           | 17      |        |     |       |
| x_min          | -0.8    |        |     |       |
| x_max          | 0.7     |        |     |       |
| DimY           | 33      |        |     |       |
| y_min          | -0.6    |        |     |       |
| y_max          | 0.9     |        |     |       |
| Outputs        |         |        |     |       |
| Out            | 0.155   | 0.155  | ... | 0.155 |
| Exp. Out       | 0.155   | 0.155  | ... | 0.155 |
| Out (DSP)      | 0.155   | 0.155  | ... | 0.155 |
| Exp. Out (DSP) | 0.155   | 0.155  | ... | 0.155 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 169 |
| Max CPU cycles  | 218 |
| Avg CPU cycles  | 174 |

**Test case: Conversion test****OK**

Conversion test for General block LookupTable2D.

| Test results                 |         |
|------------------------------|---------|
| Time step                    | 1       |
| <i>Mask parameters</i>       |         |
| TableData                    | [1x561] |
| DimX                         | 33      |
| x_min                        | -0.8    |
| x_max                        | 0.7     |
| DimY                         | 17      |
| y_min                        | -0.6    |
| y_max                        | 0.9     |
| <i>Controller parameters</i> |         |
| gainX                        | 21.333  |
| offsetX                      | -0.8    |
| Table                        | [1x561] |
| gainY                        | 10.667  |
| offsetY                      | -0.6    |
| minY                         | -0.6    |
| minX                         | -0.8    |
| maxY                         | 0.9     |
| maxX                         | 0.7     |
| dimY                         | 16      |
| dimX                         | 32      |
| Exp. gainX                   | 21.333  |
| Exp. offsetX                 | -0.8    |
| Exp. Table                   | [1x561] |
| Exp. gainY                   | 10.667  |
| Exp. offsetY                 | -0.6    |
| Exp. minY                    | -0.6    |
| Exp. minX                    | -0.8    |
| Exp. maxY                    | 0.9     |
| Exp. maxX                    | 0.7     |
| Exp. dimY                    | 16      |
| Exp. dimX                    | 32      |

| Test settings     |                  |
|-------------------|------------------|
| Tolerance gainX   | $\pm 0,0000e+00$ |
| Tolerance offsetX | $\pm 0,0000e+00$ |
| Tolerance Table   | $\pm 0,0000e+00$ |
| Tolerance gainY   | $\pm 0,0000e+00$ |
| Tolerance offsetY | $\pm 0,0000e+00$ |
| Tolerance minY    | $\pm 0,0000e+00$ |
| Tolerance minX    | $\pm 0,0000e+00$ |
| Tolerance maxY    | $\pm 0,0000e+00$ |
| Tolerance maxX    | $\pm 0,0000e+00$ |
| Tolerance dimY    | $\pm 0,0000e+00$ |
| Tolerance dimX    | $\pm 0,0000e+00$ |

**Verification: LookupTable2D Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block LookupTable2D.

| Test results   |         |        |     |       |
|----------------|---------|--------|-----|-------|
| Time step      | 1       | 2      | ... | 67    |
| CPU cycles     | 165     | 165    | ... | 168   |
| Inputs         |         |        |     |       |
| x (DSP)        | -1.1    | -1.067 | ... | 1.1   |
| y (DSP)        | 1.2     | 1.161  | ... | -1.35 |
| x              | -1.1    | -1.067 | ... | 1.1   |
| y              | 1.2     | 1.161  | ... | -1.35 |
| Parameters     |         |        |     |       |
| TableData      | [1x561] |        |     |       |
| DimX           | 17      |        |     |       |
| x_min          | -0.8    |        |     |       |
| x_max          | 0.7     |        |     |       |
| DimY           | 33      |        |     |       |
| y_min          | -0.6    |        |     |       |
| y_max          | 0.9     |        |     |       |
| Outputs        |         |        |     |       |
| Out            | 0.155   | 0.155  | ... | 0.155 |
| Exp. Out       | 0.155   | 0.155  | ... | 0.155 |
| Out (DSP)      | 0.155   | 0.155  | ... | 0.155 |
| Exp. Out (DSP) | 0.155   | 0.155  | ... | 0.155 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 162 |
| Max CPU cycles  | 174 |
| Avg CPU cycles  | 165 |


**Test case: Conversion test****OK**

Conversion test for General block LookupTable2D.

| Test results                 |         |
|------------------------------|---------|
| Time step                    | 1       |
| <i>Mask parameters</i>       |         |
| TableData                    | [1x561] |
| DimX                         | 33      |
| x_min                        | -0.8    |
| x_max                        | 0.7     |
| DimY                         | 17      |
| y_min                        | -0.6    |
| y_max                        | 0.9     |
| <i>Controller parameters</i> |         |
| gainX                        | 21.333  |
| offsetX                      | -0.8    |
| Table                        | [1x561] |
| gainY                        | 10.667  |
| offsetY                      | -0.6    |
| minY                         | -0.6    |
| minX                         | -0.8    |
| maxY                         | 0.9     |
| maxX                         | 0.7     |
| dimY                         | 16      |
| dimX                         | 32      |
| Exp. gainX                   | 21.333  |
| Exp. offsetX                 | -0.8    |
| Exp. Table                   | [1x561] |
| Exp. gainY                   | 10.667  |
| Exp. offsetY                 | -0.6    |
| Exp. minY                    | -0.6    |
| Exp. minX                    | -0.8    |
| Exp. maxY                    | 0.9     |
| Exp. maxX                    | 0.7     |
| Exp. dimY                    | 16      |
| Exp. dimX                    | 32      |

| Test settings     |                  |
|-------------------|------------------|
| Tolerance gainX   | $\pm 0,0000e+00$ |
| Tolerance offsetX | $\pm 0,0000e+00$ |
| Tolerance Table   | $\pm 0,0000e+00$ |
| Tolerance gainY   | $\pm 0,0000e+00$ |
| Tolerance offsetY | $\pm 0,0000e+00$ |
| Tolerance minY    | $\pm 0,0000e+00$ |
| Tolerance minX    | $\pm 0,0000e+00$ |
| Tolerance maxY    | $\pm 0,0000e+00$ |
| Tolerance maxX    | $\pm 0,0000e+00$ |
| Tolerance dimY    | $\pm 0,0000e+00$ |
| Tolerance dimX    | $\pm 0,0000e+00$ |

## Block: LookupTable3D



Three dimensional look-up table with selectable number of data points.

Table data must be an array of size DimX\*DimY\*DimZ.

If input is out of specified range, output will be cut off (no extrapolation).

| Inports |                            |
|---------|----------------------------|
| x       | Table index in x direction |
| y       | Table index in y direction |
| z       | Table index in z direction |

| Outputs |              |
|---------|--------------|
| Out     | Table output |

| Mask Parameters |    |                                                      |
|-----------------|----|------------------------------------------------------|
| Name            | ID | Description                                          |
| TableData       | 1  | Look-up table data                                   |
| DimX            | 2  | Number of data points in x-direction                 |
| x_min           | 3  | Minimum input value of x-dimension for look-up table |
| x_max           | 4  | Maximum input value of x-dimension for look-up table |
| DimY            | 5  | Number of data points in y-direction                 |
| y_max           | 6  | Maximum input value of y-dimension for look-up table |
| y_min           | 7  | Minimum input value of y-dimension for look-up table |
| DimZ            | 8  | Number of data points in z-direction                 |
| z_min           | 9  | Minimum input value of z-dimension for look-up table |
| z_max           | 10 | Maximum input value of z-dimension for look-up table |

### Description:

The table of the LookupTable3D block must contain DimX times DimY times DimZ data points and they have to be arranged as



$$\begin{aligned} \text{TableData} = & [f(x_1, y_1, z_1), f(x_2, y_1, z_1), \dots, f(x_{n-1}, y_1, z_1), f(x_n, y_1, z_1), \\ & f(x_1, y_2, z_1), f(x_2, y_2, z_1), \dots, f(x_{n-1}, y_2, z_1), f(x_n, y_2, z_1), \\ & \dots \\ & f(x_1, y_{m-1}, z_1), f(x_2, y_{m-1}, z_1), \dots, f(x_{n-1}, y_{m-1}, z_1), f(x_n, y_{m-1}, z_1), \\ & f(x_1, y_m, z_1), f(x_2, y_m, z_1), \dots, f(x_{n-1}, y_m, z_1), f(x_n, y_m, z_1) \\ & f(x_1, y_1, z_2), f(x_2, y_1, z_2), \dots, f(x_{n-1}, y_1, z_2), f(x_n, y_1, z_2), \\ & f(x_1, y_2, z_2), f(x_2, y_2, z_2), \dots, f(x_{n-1}, y_2, z_2), f(x_n, y_2, z_2), \\ & \dots \\ & f(x_1, y_{m-1}, z_k), f(x_2, y_{m-1}, z_k), \dots, f(x_{n-1}, y_{m-1}, z_k), f(x_n, y_{m-1}, z_k), \\ & f(x_1, y_m, z_k), f(x_2, y_m, z_k), \dots, f(x_{n-1}, y_m, z_k), f(x_n, y_m, z_k)] \end{aligned}$$

with n as selected DimX, m as selected DimY and k as selected DimZ values.

For interpolation of the data, the trilinear interpolation method is used. The interpolation is implemented as

$$f(x, y, z) = c_0 + c_1\Delta x + c_2\Delta y + c_3\Delta z + c_4\Delta x\Delta y + c_5\Delta y\Delta z + c_6\Delta z\Delta x + c_7\Delta x\Delta y\Delta z$$

with  $\Delta x$ ,  $\Delta y$ ,  $\Delta z$  as relative distances to the starting point  $f_{000}$  and with the coefficients

$$\begin{aligned} c_0 &= f_{000} \\ c_1 &= f_{100} - f_{000} \\ c_2 &= f_{010} - f_{000} \\ c_3 &= f_{001} - f_{000} \\ c_4 &= f_{110} - f_{010} - f_{100} + f_{000} \\ c_5 &= f_{011} - f_{001} - f_{010} + f_{000} \\ c_6 &= f_{101} - f_{001} - f_{100} + f_{000} \\ c_7 &= f_{111} - f_{011} - f_{101} - f_{110} + f_{100} + f_{001} + f_{010} - f_{000} \end{aligned}$$

derived from the lattice points relative to the starting point.

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP16

16 Bit Fixed Point Implementation

| Imports Data Type |       |
|-------------------|-------|
| x                 | int16 |
| y                 | int16 |
| z                 | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| x                 | int32 |
| y                 | int32 |
| z                 | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| x                 | float32 |
| y                 | float32 |
| z                 | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| x                 | float64 |
| y                 | float64 |
| z                 | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: LookupTable3D FiP16 CPU TMS320F28335**

Date of Test 2026-06-19  
Target controller TMS320F28335

**Test case: Inport test****OK**

Inport test for General block LookupTable3D.

| Test results   |         |        |        |        |     |       |
|----------------|---------|--------|--------|--------|-----|-------|
| Time step      | 1       | 2      | 3      | 4      | ... | 19    |
| CPU cycles     | 424     | 424    | 443    | 443    | ... | 452   |
| Inputs         |         |        |        |        |     |       |
| x (DSP)        | -32768  | -29127 | -25486 | -21845 | ... | 32767 |
| y (DSP)        | -29491  | -26396 | -23302 | -20207 | ... | 26214 |
| z (DSP)        | -26214  | -23484 | -20753 | -18022 | ... | 22938 |
| x              | -1      | -0.889 | -0.778 | -0.667 | ... | 1     |
| y              | -0.9    | -0.806 | -0.711 | -0.617 | ... | 0.8   |
| z              | -0.8    | -0.717 | -0.633 | -0.55  | ... | 0.7   |
| Parameters     |         |        |        |        |     |       |
| TableData      | [1x765] |        |        |        |     |       |
| DimX           | 9       |        |        |        |     |       |
| x_min          | -0.8    |        |        |        |     |       |
| x_max          | 0.7     |        |        |        |     |       |
| DimY           | 17      |        |        |        |     |       |
| y_max          | 0.9     |        |        |        |     |       |
| y_min          | -0.6    |        |        |        |     |       |
| DimZ           | 5       |        |        |        |     |       |
| z_min          | -0.9    |        |        |        |     |       |
| z_max          | 0.95    |        |        |        |     |       |
| Outputs        |         |        |        |        |     |       |
| Out            | 0.56    | 0.502  | 0.436  | 0.348  | ... | 0.525 |
| Exp. Out       | 0.56    | 0.502  | 0.436  | 0.348  | ... | 0.525 |
| Out (DSP)      | 18346   | 16435  | 14292  | 11410  | ... | 17198 |
| Exp. Out (DSP) | 18350   | 16439  | 14297  | 11414  | ... | 17203 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 424 |
| Max CPU cycles  | 460 |
| Avg CPU cycles  | 453 |

**Test case: Conversion test**

OK

Conversion test for General block LookupTable3D.

| Test results          |         |
|-----------------------|---------|
| Time step             | 1       |
| Mask parameters       |         |
| TableData             | [1x135] |
| DimX                  | 5       |
| x_min                 | -0.8    |
| x_max                 | 0.7     |
| DimY                  | 9       |
| y_max                 | 0.9     |
| y_min                 | -0.6    |
| DimZ                  | 3       |
| z_min                 | -0.9    |
| z_max                 | 0.95    |
| Controller parameters |         |
| maskY                 | 8191    |
| maskX                 | 16383   |
| maskZ                 | 32767   |
| maxZ                  | 31130   |
| maxY                  | 29491   |
| maxX                  | 22938   |
| sfrX                  | 14      |
| sfrZ                  | 15      |
| sfrY                  | 13      |
| offsetX               | -1638   |
| offsetZ               | 819     |
| offsetY               | 4915    |
| gainXsfr              | 14      |
| gainZsfr              | 14      |
| gainX                 | 21845   |
| gainZ                 | 17712   |
| Table                 | [1x135] |
| gainY                 | 21845   |
| sizeX                 | 5       |
| minY                  | -19661  |
| minX                  | -26214  |
| minZ                  | -29491  |
| idxOffsetY            | 4       |
| idxOffsetX            | 2       |
| sizeY                 | 9       |
| idxOffsetZ            | 1       |
| sizeXY                | 45      |
| gainYsfr              | 1872 14 |
| Exp. maskY            | 8191    |

| Test settings           |                  |
|-------------------------|------------------|
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance maskZ         | $\pm 0,0000e+00$ |
| Tolerance maxZ          | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrZ          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance offsetZ       | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance gainZsfr      | $\pm 0,0000e+00$ |
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance gainZ         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance minZ          | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance sizeY         | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetZ | $\pm 0,0000e+00$ |
| Tolerance sizeXY        | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |

**Verification: LookupTable3D FiP16 CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block LookupTable3D.

| Test results   |         |        |        |        |     |       |
|----------------|---------|--------|--------|--------|-----|-------|
| Time step      | 1       | 2      | 3      | 4      | ... | 19    |
| CPU cycles     | 247     | 247    | 265    | 265    | ... | 273   |
| Inputs         |         |        |        |        |     |       |
| x (DSP)        | -32768  | -29127 | -25486 | -21845 | ... | 32767 |
| y (DSP)        | -29491  | -26396 | -23302 | -20207 | ... | 26214 |
| z (DSP)        | -26214  | -23484 | -20753 | -18022 | ... | 22938 |
| x              | -1      | -0.889 | -0.778 | -0.667 | ... | 1     |
| y              | -0.9    | -0.806 | -0.711 | -0.617 | ... | 0.8   |
| z              | -0.8    | -0.717 | -0.633 | -0.55  | ... | 0.7   |
| Parameters     |         |        |        |        |     |       |
| TableData      | [1x765] |        |        |        |     |       |
| DimX           | 9       |        |        |        |     |       |
| x_min          | -0.8    |        |        |        |     |       |
| x_max          | 0.7     |        |        |        |     |       |
| DimY           | 17      |        |        |        |     |       |
| y_max          | 0.9     |        |        |        |     |       |
| y_min          | -0.6    |        |        |        |     |       |
| DimZ           | 5       |        |        |        |     |       |
| z_min          | -0.9    |        |        |        |     |       |
| z_max          | 0.95    |        |        |        |     |       |
| Outputs        |         |        |        |        |     |       |
| Out            | 0.56    | 0.502  | 0.436  | 0.348  | ... | 0.525 |
| Exp. Out       | 0.56    | 0.502  | 0.436  | 0.348  | ... | 0.525 |
| Out (DSP)      | 18346   | 16435  | 14292  | 11410  | ... | 17198 |
| Exp. Out (DSP) | 18350   | 16439  | 14297  | 11414  | ... | 17203 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 247 |
| Max CPU cycles  | 283 |
| Avg CPU cycles  | 275 |

**Test case: Conversion test**

OK

Conversion test for General block LookupTable3D.



| Test results          |         |
|-----------------------|---------|
| Time step             | 1       |
| Mask parameters       |         |
| TableData             | [1x135] |
| DimX                  | 5       |
| x_min                 | -0.8    |
| x_max                 | 0.7     |
| DimY                  | 9       |
| y_max                 | 0.9     |
| y_min                 | -0.6    |
| DimZ                  | 3       |
| z_min                 | -0.9    |
| z_max                 | 0.95    |
| Controller parameters |         |
| maskY                 | 8191    |
| maskX                 | 16383   |
| maskZ                 | 32767   |
| maxZ                  | 31130   |
| maxY                  | 29491   |
| maxX                  | 22938   |
| sfrX                  | 14      |
| sfrZ                  | 15      |
| sfrY                  | 13      |
| offsetX               | -1638   |
| offsetZ               | 819     |
| offsetY               | 4915    |
| gainXsfr              | 14      |
| gainZsfr              | 14      |
| gainX                 | 21845   |
| gainZ                 | 17712   |
| Table                 | [1x135] |
| gainY                 | 21845   |
| sizeX                 | 5       |
| minY                  | -19661  |
| minX                  | -26214  |
| minZ                  | -29491  |
| idxOffsetY            | 4       |
| idxOffsetX            | 2       |
| sizeY                 | 9       |
| idxOffsetZ            | 1       |
| sizeXY                | 45      |
| gainYsfr              | 1876 14 |
| Exp. maskY            | 8191    |

| Test settings           |                  |
|-------------------------|------------------|
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance maskZ         | $\pm 0,0000e+00$ |
| Tolerance maxZ          | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrZ          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance offsetZ       | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance gainZsfr      | $\pm 0,0000e+00$ |
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance gainZ         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance minZ          | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance sizeY         | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetZ | $\pm 0,0000e+00$ |
| Tolerance sizeXY        | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |

**Verification: LookupTable3D FiP16 CPU STM32G474RE**

Date of Test 2026-06-19  
Target controller STM32G474RE

**Test case: Inport test****OK**

Inport test for General block LookupTable3D.

| Test results   |         |        |        |        |     |       |
|----------------|---------|--------|--------|--------|-----|-------|
| Time step      | 1       | 2      | 3      | 4      | ... | 19    |
| CPU cycles     | 368     | 368    | 395    | 395    | ... | 394   |
| Inputs         |         |        |        |        |     |       |
| x (DSP)        | -32768  | -29127 | -25486 | -21845 | ... | 32767 |
| y (DSP)        | -29491  | -26396 | -23302 | -20207 | ... | 26214 |
| z (DSP)        | -26214  | -23484 | -20753 | -18022 | ... | 22938 |
| x              | -1      | -0.889 | -0.778 | -0.667 | ... | 1     |
| y              | -0.9    | -0.806 | -0.711 | -0.617 | ... | 0.8   |
| z              | -0.8    | -0.717 | -0.633 | -0.55  | ... | 0.7   |
| Parameters     |         |        |        |        |     |       |
| TableData      | [1x765] |        |        |        |     |       |
| DimX           | 9       |        |        |        |     |       |
| x_min          | -0.8    |        |        |        |     |       |
| x_max          | 0.7     |        |        |        |     |       |
| DimY           | 17      |        |        |        |     |       |
| y_max          | 0.9     |        |        |        |     |       |
| y_min          | -0.6    |        |        |        |     |       |
| DimZ           | 5       |        |        |        |     |       |
| z_min          | -0.9    |        |        |        |     |       |
| z_max          | 0.95    |        |        |        |     |       |
| Outputs        |         |        |        |        |     |       |
| Out            | 0.56    | 0.502  | 0.436  | 0.348  | ... | 0.525 |
| Exp. Out       | 0.56    | 0.502  | 0.436  | 0.348  | ... | 0.525 |
| Out (DSP)      | 18346   | 16435  | 14292  | 11410  | ... | 17198 |
| Exp. Out (DSP) | 18350   | 16439  | 14297  | 11414  | ... | 17203 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 368 |
| Max CPU cycles  | 430 |
| Avg CPU cycles  | 411 |

**Test case: Conversion test**

OK

Conversion test for General block LookupTable3D.

| Test results          |         |
|-----------------------|---------|
| Time step             | 1       |
| Mask parameters       |         |
| TableData             | [1x135] |
| DimX                  | 5       |
| x_min                 | -0.8    |
| x_max                 | 0.7     |
| DimY                  | 9       |
| y_max                 | 0.9     |
| y_min                 | -0.6    |
| DimZ                  | 3       |
| z_min                 | -0.9    |
| z_max                 | 0.95    |
| Controller parameters |         |
| maskY                 | 8191    |
| maskX                 | 16383   |
| maskZ                 | 32767   |
| maxZ                  | 31130   |
| maxY                  | 29491   |
| maxX                  | 22938   |
| sfrX                  | 14      |
| sfrZ                  | 15      |
| sfrY                  | 13      |
| offsetX               | -1638   |
| offsetZ               | 819     |
| offsetY               | 4915    |
| gainXsfr              | 14      |
| gainZsfr              | 14      |
| gainX                 | 21845   |
| gainZ                 | 17712   |
| Table                 | [1x135] |
| gainY                 | 21845   |
| sizeX                 | 5       |
| minY                  | -19661  |
| minX                  | -26214  |
| minZ                  | -29491  |
| idxOffsetY            | 4       |
| idxOffsetX            | 2       |
| sizeY                 | 9       |
| idxOffsetZ            | 1       |
| sizeXY                | 45      |
| gainYsfr              | 1880 14 |
| Exp. maskY            | 8191    |

| Test settings           |                  |
|-------------------------|------------------|
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance maskZ         | $\pm 0,0000e+00$ |
| Tolerance maxZ          | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrZ          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance offsetZ       | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance gainZsfr      | $\pm 0,0000e+00$ |
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance gainZ         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance minZ          | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance sizeY         | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetZ | $\pm 0,0000e+00$ |
| Tolerance sizeXY        | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |

**Verification: LookupTable3D FiP16 CPU STM32F072RB**

Date of Test 2026-06-19  
Target controller STM32F072RB

**Test case: Inport test****OK**

Inport test for General block LookupTable3D.

| Test results   |         |        |        |        |     |       |
|----------------|---------|--------|--------|--------|-----|-------|
| Time step      | 1       | 2      | 3      | 4      | ... | 19    |
| CPU cycles     | 369     | 369    | 390    | 390    | ... | 395   |
| Inputs         |         |        |        |        |     |       |
| x (DSP)        | -32768  | -29127 | -25486 | -21845 | ... | 32767 |
| y (DSP)        | -29491  | -26396 | -23302 | -20207 | ... | 26214 |
| z (DSP)        | -26214  | -23484 | -20753 | -18022 | ... | 22938 |
| x              | -1      | -0.889 | -0.778 | -0.667 | ... | 1     |
| y              | -0.9    | -0.806 | -0.711 | -0.617 | ... | 0.8   |
| z              | -0.8    | -0.717 | -0.633 | -0.55  | ... | 0.7   |
| Parameters     |         |        |        |        |     |       |
| TableData      | [1x765] |        |        |        |     |       |
| DimX           | 9       |        |        |        |     |       |
| x_min          | -0.8    |        |        |        |     |       |
| x_max          | 0.7     |        |        |        |     |       |
| DimY           | 17      |        |        |        |     |       |
| y_max          | 0.9     |        |        |        |     |       |
| y_min          | -0.6    |        |        |        |     |       |
| DimZ           | 5       |        |        |        |     |       |
| z_min          | -0.9    |        |        |        |     |       |
| z_max          | 0.95    |        |        |        |     |       |
| Outputs        |         |        |        |        |     |       |
| Out            | 0.56    | 0.502  | 0.436  | 0.348  | ... | 0.525 |
| Exp. Out       | 0.56    | 0.502  | 0.436  | 0.348  | ... | 0.525 |
| Out (DSP)      | 18346   | 16435  | 14292  | 11410  | ... | 17198 |
| Exp. Out (DSP) | 18350   | 16439  | 14297  | 11414  | ... | 17203 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 369 |
| Max CPU cycles  | 411 |
| Avg CPU cycles  | 401 |

**Test case: Conversion test**

OK

Conversion test for General block LookupTable3D.



| Test results          |         |
|-----------------------|---------|
| Time step             | 1       |
| Mask parameters       |         |
| TableData             | [1x135] |
| DimX                  | 5       |
| x_min                 | -0.8    |
| x_max                 | 0.7     |
| DimY                  | 9       |
| y_max                 | 0.9     |
| y_min                 | -0.6    |
| DimZ                  | 3       |
| z_min                 | -0.9    |
| z_max                 | 0.95    |
| Controller parameters |         |
| maskY                 | 8191    |
| maskX                 | 16383   |
| maskZ                 | 32767   |
| maxZ                  | 31130   |
| maxY                  | 29491   |
| maxX                  | 22938   |
| sfrX                  | 14      |
| sfrZ                  | 15      |
| sfrY                  | 13      |
| offsetX               | -1638   |
| offsetZ               | 819     |
| offsetY               | 4915    |
| gainXsfr              | 14      |
| gainZsfr              | 14      |
| gainX                 | 21845   |
| gainZ                 | 17712   |
| Table                 | [1x135] |
| gainY                 | 21845   |
| sizeX                 | 5       |
| minY                  | -19661  |
| minX                  | -26214  |
| minZ                  | -29491  |
| idxOffsetY            | 4       |
| idxOffsetX            | 2       |
| sizeY                 | 9       |
| idxOffsetZ            | 1       |
| sizeXY                | 45      |
| gainYsfr              | 1884 14 |
| Exp. maskY            | 8191    |

| Test settings           |                  |
|-------------------------|------------------|
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance maskZ         | $\pm 0,0000e+00$ |
| Tolerance maxZ          | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrZ          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance offsetZ       | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance gainZsfr      | $\pm 0,0000e+00$ |
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance gainZ         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance minZ          | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance sizeY         | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetZ | $\pm 0,0000e+00$ |
| Tolerance sizeXY        | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |

**Verification: LookupTable3D FiP16 CPU PIC32MX170F256**

Date of Test 2026-06-19  
Target controller PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block LookupTable3D.

| Test results   |         |        |        |        |     |       |
|----------------|---------|--------|--------|--------|-----|-------|
| Time step      | 1       | 2      | 3      | 4      | ... | 19    |
| CPU cycles     | 222     | 222    | 239    | 239    | ... | 245   |
| Inputs         |         |        |        |        |     |       |
| x (DSP)        | -32768  | -29127 | -25486 | -21845 | ... | 32767 |
| y (DSP)        | -29491  | -26396 | -23302 | -20207 | ... | 26214 |
| z (DSP)        | -26214  | -23484 | -20753 | -18022 | ... | 22938 |
| x              | -1      | -0.889 | -0.778 | -0.667 | ... | 1     |
| y              | -0.9    | -0.806 | -0.711 | -0.617 | ... | 0.8   |
| z              | -0.8    | -0.717 | -0.633 | -0.55  | ... | 0.7   |
| Parameters     |         |        |        |        |     |       |
| TableData      | [1x765] |        |        |        |     |       |
| DimX           | 9       |        |        |        |     |       |
| x_min          | -0.8    |        |        |        |     |       |
| x_max          | 0.7     |        |        |        |     |       |
| DimY           | 17      |        |        |        |     |       |
| y_max          | 0.9     |        |        |        |     |       |
| y_min          | -0.6    |        |        |        |     |       |
| DimZ           | 5       |        |        |        |     |       |
| z_min          | -0.9    |        |        |        |     |       |
| z_max          | 0.95    |        |        |        |     |       |
| Outputs        |         |        |        |        |     |       |
| Out            | 0.56    | 0.502  | 0.436  | 0.348  | ... | 0.525 |
| Exp. Out       | 0.56    | 0.502  | 0.436  | 0.348  | ... | 0.525 |
| Out (DSP)      | 18346   | 16435  | 14292  | 11410  | ... | 17198 |
| Exp. Out (DSP) | 18350   | 16439  | 14297  | 11414  | ... | 17203 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 222 |
| Max CPU cycles  | 257 |
| Avg CPU cycles  | 249 |

**Test case: Conversion test**

OK

Conversion test for General block LookupTable3D.

| Test results          |         |
|-----------------------|---------|
| Time step             | 1       |
| Mask parameters       |         |
| TableData             | [1x135] |
| DimX                  | 5       |
| x_min                 | -0.8    |
| x_max                 | 0.7     |
| DimY                  | 9       |
| y_max                 | 0.9     |
| y_min                 | -0.6    |
| DimZ                  | 3       |
| z_min                 | -0.9    |
| z_max                 | 0.95    |
| Controller parameters |         |
| maskY                 | 8191    |
| maskX                 | 16383   |
| maskZ                 | 32767   |
| maxZ                  | 31130   |
| maxY                  | 29491   |
| maxX                  | 22938   |
| sfrX                  | 14      |
| sfrZ                  | 15      |
| sfrY                  | 13      |
| offsetX               | -1638   |
| offsetZ               | 819     |
| offsetY               | 4915    |
| gainXsfr              | 14      |
| gainZsfr              | 14      |
| gainX                 | 21845   |
| gainZ                 | 17712   |
| Table                 | [1x135] |
| gainY                 | 21845   |
| sizeX                 | 5       |
| minY                  | -19661  |
| minX                  | -26214  |
| minZ                  | -29491  |
| idxOffsetY            | 4       |
| idxOffsetX            | 2       |
| sizeY                 | 9       |
| idxOffsetZ            | 1       |
| sizeXY                | 45      |
| gainYsfr              | 1888 14 |
| Exp. maskY            | 8191    |

| Test settings           |                  |
|-------------------------|------------------|
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance maskZ         | $\pm 0,0000e+00$ |
| Tolerance maxZ          | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrZ          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance offsetZ       | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance gainZsfr      | $\pm 0,0000e+00$ |
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance gainZ         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance minZ          | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance sizeY         | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetZ | $\pm 0,0000e+00$ |
| Tolerance sizeXY        | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |

**Verification: LookupTable3D FiP16 CPU dsPIC33EP256MC502**

Date of Test 2026-06-19  
Target controller dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block LookupTable3D.

| Test results   |         |        |        |        |     |       |
|----------------|---------|--------|--------|--------|-----|-------|
| Time step      | 1       | 2      | 3      | 4      | ... | 19    |
| CPU cycles     | 598     | 598    | 630    | 630    | ... | 628   |
| Inputs         |         |        |        |        |     |       |
| x (DSP)        | -32768  | -29127 | -25486 | -21845 | ... | 32767 |
| y (DSP)        | -29491  | -26396 | -23302 | -20207 | ... | 26214 |
| z (DSP)        | -26214  | -23484 | -20753 | -18022 | ... | 22938 |
| x              | -1      | -0.889 | -0.778 | -0.667 | ... | 1     |
| y              | -0.9    | -0.806 | -0.711 | -0.617 | ... | 0.8   |
| z              | -0.8    | -0.717 | -0.633 | -0.55  | ... | 0.7   |
| Parameters     |         |        |        |        |     |       |
| TableData      | [1x765] |        |        |        |     |       |
| DimX           | 9       |        |        |        |     |       |
| x_min          | -0.8    |        |        |        |     |       |
| x_max          | 0.7     |        |        |        |     |       |
| DimY           | 17      |        |        |        |     |       |
| y_max          | 0.9     |        |        |        |     |       |
| y_min          | -0.6    |        |        |        |     |       |
| DimZ           | 5       |        |        |        |     |       |
| z_min          | -0.9    |        |        |        |     |       |
| z_max          | 0.95    |        |        |        |     |       |
| Outputs        |         |        |        |        |     |       |
| Out            | 0.56    | 0.502  | 0.436  | 0.348  | ... | 0.525 |
| Exp. Out       | 0.56    | 0.502  | 0.436  | 0.348  | ... | 0.525 |
| Out (DSP)      | 18346   | 16435  | 14292  | 11410  | ... | 17198 |
| Exp. Out (DSP) | 18350   | 16439  | 14297  | 11414  | ... | 17203 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 598 |
| Max CPU cycles  | 657 |
| Avg CPU cycles  | 643 |

#### Test case: Conversion test

OK

Conversion test for General block LookupTable3D.



| Test results          |         |
|-----------------------|---------|
| Time step             | 1       |
| Mask parameters       |         |
| TableData             | [1x135] |
| DimX                  | 5       |
| x_min                 | -0.8    |
| x_max                 | 0.7     |
| DimY                  | 9       |
| y_max                 | 0.9     |
| y_min                 | -0.6    |
| DimZ                  | 3       |
| z_min                 | -0.9    |
| z_max                 | 0.95    |
| Controller parameters |         |
| maskY                 | 8191    |
| maskX                 | 16383   |
| maskZ                 | 32767   |
| maxZ                  | 31130   |
| maxY                  | 29491   |
| maxX                  | 22938   |
| sfrX                  | 14      |
| sfrZ                  | 15      |
| sfrY                  | 13      |
| offsetX               | -1638   |
| offsetZ               | 819     |
| offsetY               | 4915    |
| gainXsfr              | 14      |
| gainZsfr              | 14      |
| gainX                 | 21845   |
| gainZ                 | 17712   |
| Table                 | [1x135] |
| gainY                 | 21845   |
| sizeX                 | 5       |
| minY                  | -19661  |
| minX                  | -26214  |
| minZ                  | -29491  |
| idxOffsetY            | 4       |
| idxOffsetX            | 2       |
| sizeY                 | 9       |
| idxOffsetZ            | 1       |
| sizeXY                | 45      |
| gainYsfr              | 1892 14 |
| Exp. maskY            | 8191    |

| Test settings           |                  |
|-------------------------|------------------|
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance maskZ         | $\pm 0,0000e+00$ |
| Tolerance maxZ          | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrZ          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance offsetZ       | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance gainZsfr      | $\pm 0,0000e+00$ |
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance gainZ         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance minZ          | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance sizeY         | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetZ | $\pm 0,0000e+00$ |
| Tolerance sizeXY        | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |

**Verification: LookupTable3D FiP16 CPU XMC4800-F144K2048**

Date of Test 2026-06-19  
Target controller XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block LookupTable3D.

| Test results   |         |        |        |        |     |       |
|----------------|---------|--------|--------|--------|-----|-------|
| Time step      | 1       | 2      | 3      | 4      | ... | 19    |
| CPU cycles     | 411     | 323    | 343    | 333    | ... | 338   |
| Inputs         |         |        |        |        |     |       |
| x (DSP)        | -32768  | -29127 | -25486 | -21845 | ... | 32767 |
| y (DSP)        | -29491  | -26396 | -23302 | -20207 | ... | 26214 |
| z (DSP)        | -26214  | -23484 | -20753 | -18022 | ... | 22938 |
| x              | -1      | -0.889 | -0.778 | -0.667 | ... | 1     |
| y              | -0.9    | -0.806 | -0.711 | -0.617 | ... | 0.8   |
| z              | -0.8    | -0.717 | -0.633 | -0.55  | ... | 0.7   |
| Parameters     |         |        |        |        |     |       |
| TableData      | [1x765] |        |        |        |     |       |
| DimX           | 9       |        |        |        |     |       |
| x_min          | -0.8    |        |        |        |     |       |
| x_max          | 0.7     |        |        |        |     |       |
| DimY           | 17      |        |        |        |     |       |
| y_max          | 0.9     |        |        |        |     |       |
| y_min          | -0.6    |        |        |        |     |       |
| DimZ           | 5       |        |        |        |     |       |
| z_min          | -0.9    |        |        |        |     |       |
| z_max          | 0.95    |        |        |        |     |       |
| Outputs        |         |        |        |        |     |       |
| Out            | 0.56    | 0.502  | 0.436  | 0.348  | ... | 0.525 |
| Exp. Out       | 0.56    | 0.502  | 0.436  | 0.348  | ... | 0.525 |
| Out (DSP)      | 18346   | 16435  | 14292  | 11410  | ... | 17198 |
| Exp. Out (DSP) | 18350   | 16439  | 14297  | 11414  | ... | 17203 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 323 |
| Max CPU cycles  | 411 |
| Avg CPU cycles  | 346 |

**Test case: Conversion test**

OK

Conversion test for General block LookupTable3D.

| Test results          |         |
|-----------------------|---------|
| Time step             | 1       |
| Mask parameters       |         |
| TableData             | [1x135] |
| DimX                  | 5       |
| x_min                 | -0.8    |
| x_max                 | 0.7     |
| DimY                  | 9       |
| y_max                 | 0.9     |
| y_min                 | -0.6    |
| DimZ                  | 3       |
| z_min                 | -0.9    |
| z_max                 | 0.95    |
| Controller parameters |         |
| maskY                 | 8191    |
| maskX                 | 16383   |
| maskZ                 | 32767   |
| maxZ                  | 31130   |
| maxY                  | 29491   |
| maxX                  | 22938   |
| sfrX                  | 14      |
| sfrZ                  | 15      |
| sfrY                  | 13      |
| offsetX               | -1638   |
| offsetZ               | 819     |
| offsetY               | 4915    |
| gainXsfr              | 14      |
| gainZsfr              | 14      |
| gainX                 | 21845   |
| gainZ                 | 17712   |
| Table                 | [1x135] |
| gainY                 | 21845   |
| sizeX                 | 5       |
| minY                  | -19661  |
| minX                  | -26214  |
| minZ                  | -29491  |
| idxOffsetY            | 4       |
| idxOffsetX            | 2       |
| sizeY                 | 9       |
| idxOffsetZ            | 1       |
| sizeXY                | 45      |
| gainYsfr              | 1896 14 |
| Exp. maskY            | 8191    |

| Test settings           |                  |
|-------------------------|------------------|
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance maskZ         | $\pm 0,0000e+00$ |
| Tolerance maxZ          | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrZ          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance offsetZ       | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance gainZsfr      | $\pm 0,0000e+00$ |
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance gainZ         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance minZ          | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance sizeY         | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetZ | $\pm 0,0000e+00$ |
| Tolerance sizeXY        | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |

**Verification: LookupTable3D FiP16 CPU TMS320F28379D**

Date of Test 2026-06-22  
Target controller TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block LookupTable3D.

| Test results   |         |        |        |        |     |       |
|----------------|---------|--------|--------|--------|-----|-------|
| Time step      | 1       | 2      | 3      | 4      | ... | 19    |
| CPU cycles     | 389     | 389    | 410    | 410    | ... | 421   |
| Inputs         |         |        |        |        |     |       |
| x (DSP)        | -32768  | -29127 | -25486 | -21845 | ... | 32767 |
| y (DSP)        | -29491  | -26396 | -23302 | -20207 | ... | 26214 |
| z (DSP)        | -26214  | -23484 | -20753 | -18022 | ... | 22938 |
| x              | -1      | -0.889 | -0.778 | -0.667 | ... | 1     |
| y              | -0.9    | -0.806 | -0.711 | -0.617 | ... | 0.8   |
| z              | -0.8    | -0.717 | -0.633 | -0.55  | ... | 0.7   |
| Parameters     |         |        |        |        |     |       |
| TableData      | [1x765] |        |        |        |     |       |
| DimX           | 9       |        |        |        |     |       |
| x_min          | -0.8    |        |        |        |     |       |
| x_max          | 0.7     |        |        |        |     |       |
| DimY           | 17      |        |        |        |     |       |
| y_max          | 0.9     |        |        |        |     |       |
| y_min          | -0.6    |        |        |        |     |       |
| DimZ           | 5       |        |        |        |     |       |
| z_min          | -0.9    |        |        |        |     |       |
| z_max          | 0.95    |        |        |        |     |       |
| Outputs        |         |        |        |        |     |       |
| Out            | 0.56    | 0.502  | 0.436  | 0.348  | ... | 0.525 |
| Exp. Out       | 0.56    | 0.502  | 0.436  | 0.348  | ... | 0.525 |
| Out (DSP)      | 18346   | 16435  | 14292  | 11410  | ... | 17198 |
| Exp. Out (DSP) | 18350   | 16439  | 14297  | 11414  | ... | 17203 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,0518e-04$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 389 |
| Max CPU cycles  | 431 |
| Avg CPU cycles  | 421 |

**Test case: Conversion test**

OK

Conversion test for General block LookupTable3D.



| Test results          |         |
|-----------------------|---------|
| Time step             | 1       |
| Mask parameters       |         |
| TableData             | [1x135] |
| DimX                  | 5       |
| x_min                 | -0.8    |
| x_max                 | 0.7     |
| DimY                  | 9       |
| y_max                 | 0.9     |
| y_min                 | -0.6    |
| DimZ                  | 3       |
| z_min                 | -0.9    |
| z_max                 | 0.95    |
| Controller parameters |         |
| maskY                 | 8191    |
| maskX                 | 16383   |
| maskZ                 | 32767   |
| maxZ                  | 31130   |
| maxY                  | 29491   |
| maxX                  | 22938   |
| sfrX                  | 14      |
| sfrZ                  | 15      |
| sfrY                  | 13      |
| offsetX               | -1638   |
| offsetZ               | 819     |
| offsetY               | 4915    |
| gainXsfr              | 14      |
| gainZsfr              | 14      |
| gainX                 | 21845   |
| gainZ                 | 17712   |
| Table                 | [1x135] |
| gainY                 | 21845   |
| sizeX                 | 5       |
| minY                  | -19661  |
| minX                  | -26214  |
| minZ                  | -29491  |
| idxOffsetY            | 4       |
| idxOffsetX            | 2       |
| sizeY                 | 9       |
| idxOffsetZ            | 1       |
| sizeXY                | 45      |
| gainYsfr              | 1900 14 |
| Exp. maskY            | 8191    |

| Test settings           |                  |
|-------------------------|------------------|
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance maskZ         | $\pm 0,0000e+00$ |
| Tolerance maxZ          | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrZ          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance offsetZ       | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance gainZsfr      | $\pm 0,0000e+00$ |
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance gainZ         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance minZ          | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance sizeY         | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetZ | $\pm 0,0000e+00$ |
| Tolerance sizeXY        | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |

**Verification: LookupTable3D FiP32 CPU TMS320F28335**

Date of Test 2026-06-19  
Target controller TMS320F28335

**Test case: Inport test****OK**

Inport test for General block LookupTable3D.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 19         |
| CPU cycles     | 652         | 652         | ... | 694        |
| Inputs         |             |             |     |            |
| x (DSP)        | -2147483648 | -1908874354 | ... | 2147483647 |
| y (DSP)        | -1932735283 | -1729917383 | ... | 1717986918 |
| z (DSP)        | -1717986918 | -1539029948 | ... | 1503238554 |
| x              | -1          | -0.889      | ... | 1          |
| y              | -0.9        | -0.806      | ... | 0.8        |
| z              | -0.8        | -0.717      | ... | 0.7        |
| Parameters     |             |             |     |            |
| TableData      | [1x765]     |             |     |            |
| DimX           | 9           |             |     |            |
| x_min          | -0.8        |             |     |            |
| x_max          | 0.7         |             |     |            |
| DimY           | 17          |             |     |            |
| y_max          | 0.9         |             |     |            |
| y_min          | -0.6        |             |     |            |
| DimZ           | 5           |             |     |            |
| z_min          | -0.9        |             |     |            |
| z_max          | 0.95        |             |     |            |
| Outputs        |             |             |     |            |
| Out            | 0.56        | 0.502       | ... | 0.525      |
| Exp. Out       | 0.56        | 0.502       | ... | 0.525      |
| Out (DSP)      | 1202590840  | 1077320961  | ... | 1127428909 |
| Exp. Out (DSP) | 1202590843  | 1077320963  | ... | 1127428915 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 4,6566e-09$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 652 |
| Max CPU cycles  | 711 |
| Avg CPU cycles  | 698 |

**Test case: Conversion test**

OK

Conversion test for General block LookupTable3D.

| Test results          |             |
|-----------------------|-------------|
| Time step             | 1           |
| Mask parameters       |             |
| TableData             | [1x135]     |
| DimX                  | 5           |
| x_min                 | -0.8        |
| x_max                 | 0.7         |
| DimY                  | 9           |
| y_max                 | 0.9         |
| y_min                 | -0.6        |
| DimZ                  | 3           |
| z_min                 | -0.9        |
| z_max                 | 0.95        |
| Controller parameters |             |
| maskY                 | 536870911   |
| maskX                 | 1073741823  |
| maskZ                 | 2147483647  |
| maxZ                  | 2040109466  |
| maxY                  | 1932735283  |
| maxX                  | 1503238554  |
| sfrX                  | 30          |
| sfrZ                  | 31          |
| sfrY                  | 29          |
| offsetX               | -107374182  |
| offsetZ               | 53687091    |
| offsetY               | 322122547   |
| gainXsfr              | 30          |
| gainZsfr              | 30          |
| gainX                 | 1431655765  |
| gainZ                 | 1160801972  |
| Table                 | [1x135]     |
| gainY                 | 1431655765  |
| sizeX                 | 5           |
| minY                  | -1288490189 |
| minX                  | -1717986918 |
| minZ                  | -1932735283 |
| idxOffsetY            | 4           |
| idxOffsetX            | 2           |
| sizeY                 | 9           |
| idxOffsetZ            | 1           |
| sizeXY                | 45          |
| gainYsfr              | 1904 30     |
| Exp. maskY            | 536870911   |

| Test settings           |                  |
|-------------------------|------------------|
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance maskZ         | $\pm 0,0000e+00$ |
| Tolerance maxZ          | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrZ          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance offsetZ       | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance gainZsfr      | $\pm 0,0000e+00$ |
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance gainZ         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance minZ          | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance sizeY         | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetZ | $\pm 0,0000e+00$ |
| Tolerance sizeXY        | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |

**Verification: LookupTable3D FiP32 CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block LookupTable3D.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 19         |
| CPU cycles     | 1015        | 1015        | ... | 1087       |
| Inputs         |             |             |     |            |
| x (DSP)        | -2147483648 | -1908874354 | ... | 2147483647 |
| y (DSP)        | -1932735283 | -1729917383 | ... | 1717986918 |
| z (DSP)        | -1717986918 | -1539029948 | ... | 1503238554 |
| x              | -1          | -0.889      | ... | 1          |
| y              | -0.9        | -0.806      | ... | 0.8        |
| z              | -0.8        | -0.717      | ... | 0.7        |
| Parameters     |             |             |     |            |
| TableData      | [1x765]     |             |     |            |
| DimX           | 9           |             |     |            |
| x_min          | -0.8        |             |     |            |
| x_max          | 0.7         |             |     |            |
| DimY           | 17          |             |     |            |
| y_max          | 0.9         |             |     |            |
| y_min          | -0.6        |             |     |            |
| DimZ           | 5           |             |     |            |
| z_min          | -0.9        |             |     |            |
| z_max          | 0.95        |             |     |            |
| Outputs        |             |             |     |            |
| Out            | 0.56        | 0.502       | ... | 0.525      |
| Exp. Out       | 0.56        | 0.502       | ... | 0.525      |
| Out (DSP)      | 1202590840  | 1077320961  | ... | 1127428909 |
| Exp. Out (DSP) | 1202590843  | 1077320963  | ... | 1127428915 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 4,6566e-09$ ( $\pm 10$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1015 |
| Max CPU cycles  | 1143 |
| Avg CPU cycles  | 1113 |

**Test case: Conversion test**

OK

Conversion test for General block LookupTable3D.



| Test results          |             |
|-----------------------|-------------|
| Time step             | 1           |
| Mask parameters       |             |
| TableData             | [1x135]     |
| DimX                  | 5           |
| x_min                 | -0.8        |
| x_max                 | 0.7         |
| DimY                  | 9           |
| y_max                 | 0.9         |
| y_min                 | -0.6        |
| DimZ                  | 3           |
| z_min                 | -0.9        |
| z_max                 | 0.95        |
| Controller parameters |             |
| maskY                 | 536870911   |
| maskX                 | 1073741823  |
| maskZ                 | 2147483647  |
| maxZ                  | 2040109466  |
| maxY                  | 1932735283  |
| maxX                  | 1503238554  |
| sfrX                  | 30          |
| sfrZ                  | 31          |
| sfrY                  | 29          |
| offsetX               | -107374182  |
| offsetZ               | 53687091    |
| offsetY               | 322122547   |
| gainXsfr              | 30          |
| gainZsfr              | 30          |
| gainX                 | 1431655765  |
| gainZ                 | 1160801972  |
| Table                 | [1x135]     |
| gainY                 | 1431655765  |
| sizeX                 | 5           |
| minY                  | -1288490189 |
| minX                  | -1717986918 |
| minZ                  | -1932735283 |
| idxOffsetY            | 4           |
| idxOffsetX            | 2           |
| sizeY                 | 9           |
| idxOffsetZ            | 1           |
| sizeXY                | 45          |
| gainYsfr              | 1908 30     |
| Exp. maskY            | 536870911   |

| Test settings           |                  |
|-------------------------|------------------|
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance maskZ         | $\pm 0,0000e+00$ |
| Tolerance maxZ          | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrZ          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance offsetZ       | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance gainZsfr      | $\pm 0,0000e+00$ |
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance gainZ         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance minZ          | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance sizeY         | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetZ | $\pm 0,0000e+00$ |
| Tolerance sizeXY        | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |

**Verification: LookupTable3D FiP32 CPU STM32G474RE**

Date of Test 2026-06-19  
Target controller STM32G474RE

**Test case: Inport test****OK**

Inport test for General block LookupTable3D.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 19         |
| CPU cycles     | 830         | 830         | ... | 863        |
| Inputs         |             |             |     |            |
| x (DSP)        | -2147483648 | -1908874354 | ... | 2147483647 |
| y (DSP)        | -1932735283 | -1729917383 | ... | 1717986918 |
| z (DSP)        | -1717986918 | -1539029948 | ... | 1503238554 |
| x              | -1          | -0.889      | ... | 1          |
| y              | -0.9        | -0.806      | ... | 0.8        |
| z              | -0.8        | -0.717      | ... | 0.7        |
| Parameters     |             |             |     |            |
| TableData      | [1x765]     |             |     |            |
| DimX           | 9           |             |     |            |
| x_min          | -0.8        |             |     |            |
| x_max          | 0.7         |             |     |            |
| DimY           | 17          |             |     |            |
| y_max          | 0.9         |             |     |            |
| y_min          | -0.6        |             |     |            |
| DimZ           | 5           |             |     |            |
| z_min          | -0.9        |             |     |            |
| z_max          | 0.95        |             |     |            |
| Outputs        |             |             |     |            |
| Out            | 0.56        | 0.502       | ... | 0.525      |
| Exp. Out       | 0.56        | 0.502       | ... | 0.525      |
| Out (DSP)      | 1202590840  | 1077320961  | ... | 1127428909 |
| Exp. Out (DSP) | 1202590843  | 1077320963  | ... | 1127428915 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 4,6566e-09$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 830 |
| Max CPU cycles  | 900 |
| Avg CPU cycles  | 882 |

**Test case: Conversion test**

OK

Conversion test for General block LookupTable3D.

| Test results          |             |
|-----------------------|-------------|
| Time step             | 1           |
| Mask parameters       |             |
| TableData             | [1x135]     |
| DimX                  | 5           |
| x_min                 | -0.8        |
| x_max                 | 0.7         |
| DimY                  | 9           |
| y_max                 | 0.9         |
| y_min                 | -0.6        |
| DimZ                  | 3           |
| z_min                 | -0.9        |
| z_max                 | 0.95        |
| Controller parameters |             |
| maskY                 | 536870911   |
| maskX                 | 1073741823  |
| maskZ                 | 2147483647  |
| maxZ                  | 2040109466  |
| maxY                  | 1932735283  |
| maxX                  | 1503238554  |
| sfrX                  | 30          |
| sfrZ                  | 31          |
| sfrY                  | 29          |
| offsetX               | -107374182  |
| offsetZ               | 53687091    |
| offsetY               | 322122547   |
| gainXsfr              | 30          |
| gainZsfr              | 30          |
| gainX                 | 1431655765  |
| gainZ                 | 1160801972  |
| Table                 | [1x135]     |
| gainY                 | 1431655765  |
| sizeX                 | 5           |
| minY                  | -1288490189 |
| minX                  | -1717986918 |
| minZ                  | -1932735283 |
| idxOffsetY            | 4           |
| idxOffsetX            | 2           |
| sizeY                 | 9           |
| idxOffsetZ            | 1           |
| sizeXY                | 45          |
| gainYsfr              | 1912 30     |
| Exp. maskY            | 536870911   |

| Test settings           |                  |
|-------------------------|------------------|
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance maskZ         | $\pm 0,0000e+00$ |
| Tolerance maxZ          | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrZ          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance offsetZ       | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance gainZsfr      | $\pm 0,0000e+00$ |
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance gainZ         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance minZ          | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance sizeY         | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetZ | $\pm 0,0000e+00$ |
| Tolerance sizeXY        | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |

**Verification: LookupTable3D FiP32 CPU STM32F072RB**

Date of Test 2026-06-19  
Target controller STM32F072RB

**Test case: Inport test****OK**

Inport test for General block LookupTable3D.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 19         |
| CPU cycles     | 1713        | 1713        | ... | 1824       |
| Inputs         |             |             |     |            |
| x (DSP)        | -2147483648 | -1908874354 | ... | 2147483647 |
| y (DSP)        | -1932735283 | -1729917383 | ... | 1717986918 |
| z (DSP)        | -1717986918 | -1539029948 | ... | 1503238554 |
| x              | -1          | -0.889      | ... | 1          |
| y              | -0.9        | -0.806      | ... | 0.8        |
| z              | -0.8        | -0.717      | ... | 0.7        |
| Parameters     |             |             |     |            |
| TableData      | [1x765]     |             |     |            |
| DimX           | 9           |             |     |            |
| x_min          | -0.8        |             |     |            |
| x_max          | 0.7         |             |     |            |
| DimY           | 17          |             |     |            |
| y_max          | 0.9         |             |     |            |
| y_min          | -0.6        |             |     |            |
| DimZ           | 5           |             |     |            |
| z_min          | -0.9        |             |     |            |
| z_max          | 0.95        |             |     |            |
| Outputs        |             |             |     |            |
| Out            | 0.56        | 0.502       | ... | 0.525      |
| Exp. Out       | 0.56        | 0.502       | ... | 0.525      |
| Out (DSP)      | 1202590840  | 1077320961  | ... | 1127428909 |
| Exp. Out (DSP) | 1202590843  | 1077320963  | ... | 1127428915 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 4,6566e-09$ ( $\pm 10$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1713 |
| Max CPU cycles  | 1919 |
| Avg CPU cycles  | 1870 |

**Test case: Conversion test**

OK

Conversion test for General block LookupTable3D.



| Test results          |             |
|-----------------------|-------------|
| Time step             | 1           |
| Mask parameters       |             |
| TableData             | [1x135]     |
| DimX                  | 5           |
| x_min                 | -0.8        |
| x_max                 | 0.7         |
| DimY                  | 9           |
| y_max                 | 0.9         |
| y_min                 | -0.6        |
| DimZ                  | 3           |
| z_min                 | -0.9        |
| z_max                 | 0.95        |
| Controller parameters |             |
| maskY                 | 536870911   |
| maskX                 | 1073741823  |
| maskZ                 | 2147483647  |
| maxZ                  | 2040109466  |
| maxY                  | 1932735283  |
| maxX                  | 1503238554  |
| sfrX                  | 30          |
| sfrZ                  | 31          |
| sfrY                  | 29          |
| offsetX               | -107374182  |
| offsetZ               | 53687091    |
| offsetY               | 322122547   |
| gainXsfr              | 30          |
| gainZsfr              | 30          |
| gainX                 | 1431655765  |
| gainZ                 | 1160801972  |
| Table                 | [1x135]     |
| gainY                 | 1431655765  |
| sizeX                 | 5           |
| minY                  | -1288490189 |
| minX                  | -1717986918 |
| minZ                  | -1932735283 |
| idxOffsetY            | 4           |
| idxOffsetX            | 2           |
| sizeY                 | 9           |
| idxOffsetZ            | 1           |
| sizeXY                | 45          |
| gainYsfr              | 1916 30     |
| Exp. maskY            | 536870911   |

| Test settings           |                  |
|-------------------------|------------------|
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance maskZ         | $\pm 0,0000e+00$ |
| Tolerance maxZ          | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrZ          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance offsetZ       | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance gainZsfr      | $\pm 0,0000e+00$ |
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance gainZ         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance minZ          | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance sizeY         | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetZ | $\pm 0,0000e+00$ |
| Tolerance sizeXY        | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |

**Verification: LookupTable3D FiP32 CPU PIC32MX170F256**

Date of Test 2026-06-19  
Target controller PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block LookupTable3D.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 19         |
| CPU cycles     | 672         | 672         | ... | 724        |
| Inputs         |             |             |     |            |
| x (DSP)        | -2147483648 | -1908874354 | ... | 2147483647 |
| y (DSP)        | -1932735283 | -1729917383 | ... | 1717986918 |
| z (DSP)        | -1717986918 | -1539029948 | ... | 1503238554 |
| x              | -1          | -0.889      | ... | 1          |
| y              | -0.9        | -0.806      | ... | 0.8        |
| z              | -0.8        | -0.717      | ... | 0.7        |
| Parameters     |             |             |     |            |
| TableData      | [1x765]     |             |     |            |
| DimX           | 9           |             |     |            |
| x_min          | -0.8        |             |     |            |
| x_max          | 0.7         |             |     |            |
| DimY           | 17          |             |     |            |
| y_max          | 0.9         |             |     |            |
| y_min          | -0.6        |             |     |            |
| DimZ           | 5           |             |     |            |
| z_min          | -0.9        |             |     |            |
| z_max          | 0.95        |             |     |            |
| Outputs        |             |             |     |            |
| Out            | 0.56        | 0.502       | ... | 0.525      |
| Exp. Out       | 0.56        | 0.502       | ... | 0.525      |
| Out (DSP)      | 1202590840  | 1077320961  | ... | 1127428909 |
| Exp. Out (DSP) | 1202590843  | 1077320963  | ... | 1127428915 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 4,6566e-09$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 672 |
| Max CPU cycles  | 758 |
| Avg CPU cycles  | 739 |

**Test case: Conversion test**

OK

Conversion test for General block LookupTable3D.

| Test results          |             |
|-----------------------|-------------|
| Time step             | 1           |
| Mask parameters       |             |
| TableData             | [1x135]     |
| DimX                  | 5           |
| x_min                 | -0.8        |
| x_max                 | 0.7         |
| DimY                  | 9           |
| y_max                 | 0.9         |
| y_min                 | -0.6        |
| DimZ                  | 3           |
| z_min                 | -0.9        |
| z_max                 | 0.95        |
| Controller parameters |             |
| maskY                 | 536870911   |
| maskX                 | 1073741823  |
| maskZ                 | 2147483647  |
| maxZ                  | 2040109466  |
| maxY                  | 1932735283  |
| maxX                  | 1503238554  |
| sfrX                  | 30          |
| sfrZ                  | 31          |
| sfrY                  | 29          |
| offsetX               | -107374182  |
| offsetZ               | 53687091    |
| offsetY               | 322122547   |
| gainXsfr              | 30          |
| gainZsfr              | 30          |
| gainX                 | 1431655765  |
| gainZ                 | 1160801972  |
| Table                 | [1x135]     |
| gainY                 | 1431655765  |
| sizeX                 | 5           |
| minY                  | -1288490189 |
| minX                  | -1717986918 |
| minZ                  | -1932735283 |
| idxOffsetY            | 4           |
| idxOffsetX            | 2           |
| sizeY                 | 9           |
| idxOffsetZ            | 1           |
| sizeXY                | 45          |
| gainYsfr              | 1920 30     |
| Exp. maskY            | 536870911   |

| Test settings           |                  |
|-------------------------|------------------|
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance maskZ         | $\pm 0,0000e+00$ |
| Tolerance maxZ          | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrZ          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance offsetZ       | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance gainZsfr      | $\pm 0,0000e+00$ |
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance gainZ         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance minZ          | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance sizeY         | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetZ | $\pm 0,0000e+00$ |
| Tolerance sizeXY        | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |

**Verification: LookupTable3D FiP32 CPU dsPIC33EP256MC502**

Date of Test 2026-06-19  
Target controller dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block LookupTable3D.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 19         |
| CPU cycles     | 5802        | 5802        | ... | 6219       |
| Inputs         |             |             |     |            |
| x (DSP)        | -2147483648 | -1908874354 | ... | 2147483647 |
| y (DSP)        | -1932735283 | -1729917383 | ... | 1717986918 |
| z (DSP)        | -1717986918 | -1539029948 | ... | 1503238554 |
| x              | -1          | -0.889      | ... | 1          |
| y              | -0.9        | -0.806      | ... | 0.8        |
| z              | -0.8        | -0.717      | ... | 0.7        |
| Parameters     |             |             |     |            |
| TableData      | [1x765]     |             |     |            |
| DimX           | 9           |             |     |            |
| x_min          | -0.8        |             |     |            |
| x_max          | 0.7         |             |     |            |
| DimY           | 17          |             |     |            |
| y_max          | 0.9         |             |     |            |
| y_min          | -0.6        |             |     |            |
| DimZ           | 5           |             |     |            |
| z_min          | -0.9        |             |     |            |
| z_max          | 0.95        |             |     |            |
| Outputs        |             |             |     |            |
| Out            | 0.56        | 0.502       | ... | 0.525      |
| Exp. Out       | 0.56        | 0.502       | ... | 0.525      |
| Out (DSP)      | 1202590840  | 1077320961  | ... | 1127428909 |
| Exp. Out (DSP) | 1202590843  | 1077320963  | ... | 1127428915 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 4,6566e-09$ ( $\pm 10$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 5802 |
| Max CPU cycles  | 6679 |
| Avg CPU cycles  | 6445 |

# Test case: Conversion test

OK

Conversion test for General block LookupTable3D.



| Test results          |             |
|-----------------------|-------------|
| Time step             | 1           |
| Mask parameters       |             |
| TableData             | [1x135]     |
| DimX                  | 5           |
| x_min                 | -0.8        |
| x_max                 | 0.7         |
| DimY                  | 9           |
| y_max                 | 0.9         |
| y_min                 | -0.6        |
| DimZ                  | 3           |
| z_min                 | -0.9        |
| z_max                 | 0.95        |
| Controller parameters |             |
| maskY                 | 536870911   |
| maskX                 | 1073741823  |
| maskZ                 | 2147483647  |
| maxZ                  | 2040109466  |
| maxY                  | 1932735283  |
| maxX                  | 1503238554  |
| sfrX                  | 30          |
| sfrZ                  | 31          |
| sfrY                  | 29          |
| offsetX               | -107374182  |
| offsetZ               | 53687091    |
| offsetY               | 322122547   |
| gainXsfr              | 30          |
| gainZsfr              | 30          |
| gainX                 | 1431655765  |
| gainZ                 | 1160801972  |
| Table                 | [1x135]     |
| gainY                 | 1431655765  |
| sizeX                 | 5           |
| minY                  | -1288490189 |
| minX                  | -1717986918 |
| minZ                  | -1932735283 |
| idxOffsetY            | 4           |
| idxOffsetX            | 2           |
| sizeY                 | 9           |
| idxOffsetZ            | 1           |
| sizeXY                | 45          |
| gainYsfr              | 1924 30     |
| Exp. maskY            | 536870911   |

| Test settings           |                  |
|-------------------------|------------------|
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance maskZ         | $\pm 0,0000e+00$ |
| Tolerance maxZ          | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrZ          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance offsetZ       | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance gainZsfr      | $\pm 0,0000e+00$ |
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance gainZ         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance minZ          | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance sizeY         | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetZ | $\pm 0,0000e+00$ |
| Tolerance sizeXY        | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |

**Verification: LookupTable3D FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block LookupTable3D.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 19         |
| CPU cycles     | 1005        | 849         | ... | 877        |
| Inputs         |             |             |     |            |
| x (DSP)        | -2147483648 | -1908874354 | ... | 2147483647 |
| y (DSP)        | -1932735283 | -1729917383 | ... | 1717986918 |
| z (DSP)        | -1717986918 | -1539029948 | ... | 1503238554 |
| x              | -1          | -0.889      | ... | 1          |
| y              | -0.9        | -0.806      | ... | 0.8        |
| z              | -0.8        | -0.717      | ... | 0.7        |
| Parameters     |             |             |     |            |
| TableData      | [1x765]     |             |     |            |
| DimX           | 9           |             |     |            |
| x_min          | -0.8        |             |     |            |
| x_max          | 0.7         |             |     |            |
| DimY           | 17          |             |     |            |
| y_max          | 0.9         |             |     |            |
| y_min          | -0.6        |             |     |            |
| DimZ           | 5           |             |     |            |
| z_min          | -0.9        |             |     |            |
| z_max          | 0.95        |             |     |            |
| Outputs        |             |             |     |            |
| Out            | 0.56        | 0.502       | ... | 0.525      |
| Exp. Out       | 0.56        | 0.502       | ... | 0.525      |
| Out (DSP)      | 1202590840  | 1077320961  | ... | 1127428909 |
| Exp. Out (DSP) | 1202590843  | 1077320963  | ... | 1127428915 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 4,6566e-09$ ( $\pm 10$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 849  |
| Max CPU cycles  | 1005 |
| Avg CPU cycles  | 896  |

**Test case: Conversion test**

OK

Conversion test for General block LookupTable3D.

| Test results          |             |
|-----------------------|-------------|
| Time step             | 1           |
| Mask parameters       |             |
| TableData             | [1x135]     |
| DimX                  | 5           |
| x_min                 | -0.8        |
| x_max                 | 0.7         |
| DimY                  | 9           |
| y_max                 | 0.9         |
| y_min                 | -0.6        |
| DimZ                  | 3           |
| z_min                 | -0.9        |
| z_max                 | 0.95        |
| Controller parameters |             |
| maskY                 | 536870911   |
| maskX                 | 1073741823  |
| maskZ                 | 2147483647  |
| maxZ                  | 2040109466  |
| maxY                  | 1932735283  |
| maxX                  | 1503238554  |
| sfrX                  | 30          |
| sfrZ                  | 31          |
| sfrY                  | 29          |
| offsetX               | -107374182  |
| offsetZ               | 53687091    |
| offsetY               | 322122547   |
| gainXsfr              | 30          |
| gainZsfr              | 30          |
| gainX                 | 1431655765  |
| gainZ                 | 1160801972  |
| Table                 | [1x135]     |
| gainY                 | 1431655765  |
| sizeX                 | 5           |
| minY                  | -1288490189 |
| minX                  | -1717986918 |
| minZ                  | -1932735283 |
| idxOffsetY            | 4           |
| idxOffsetX            | 2           |
| sizeY                 | 9           |
| idxOffsetZ            | 1           |
| sizeXY                | 45          |
| gainYsfr              | 1928 30     |
| Exp. maskY            | 536870911   |

| Test settings           |                  |
|-------------------------|------------------|
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance maskZ         | $\pm 0,0000e+00$ |
| Tolerance maxZ          | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrZ          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance offsetZ       | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance gainZsfr      | $\pm 0,0000e+00$ |
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance gainZ         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance minZ          | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance sizeY         | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetZ | $\pm 0,0000e+00$ |
| Tolerance sizeXY        | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |

**Verification: LookupTable3D FiP32 CPU TMS320F28379D**

Date of Test 2026-06-22  
Target controller TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block LookupTable3D.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 19         |
| CPU cycles     | 586         | 586         | ... | 635        |
| Inputs         |             |             |     |            |
| x (DSP)        | -2147483648 | -1908874354 | ... | 2147483647 |
| y (DSP)        | -1932735283 | -1729917383 | ... | 1717986918 |
| z (DSP)        | -1717986918 | -1539029948 | ... | 1503238554 |
| x              | -1          | -0.889      | ... | 1          |
| y              | -0.9        | -0.806      | ... | 0.8        |
| z              | -0.8        | -0.717      | ... | 0.7        |
| Parameters     |             |             |     |            |
| TableData      | [1x765]     |             |     |            |
| DimX           | 9           |             |     |            |
| x_min          | -0.8        |             |     |            |
| x_max          | 0.7         |             |     |            |
| DimY           | 17          |             |     |            |
| y_max          | 0.9         |             |     |            |
| y_min          | -0.6        |             |     |            |
| DimZ           | 5           |             |     |            |
| z_min          | -0.9        |             |     |            |
| z_max          | 0.95        |             |     |            |
| Outputs        |             |             |     |            |
| Out            | 0.56        | 0.502       | ... | 0.525      |
| Exp. Out       | 0.56        | 0.502       | ... | 0.525      |
| Out (DSP)      | 1202590840  | 1077320961  | ... | 1127428909 |
| Exp. Out (DSP) | 1202590843  | 1077320963  | ... | 1127428915 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 4,6566e-09$ ( $\pm 10$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 586 |
| Max CPU cycles  | 650 |
| Avg CPU cycles  | 636 |

**Test case: Conversion test**

OK

Conversion test for General block LookupTable3D.



| Test results          |             |
|-----------------------|-------------|
| Time step             | 1           |
| Mask parameters       |             |
| TableData             | [1x135]     |
| DimX                  | 5           |
| x_min                 | -0.8        |
| x_max                 | 0.7         |
| DimY                  | 9           |
| y_max                 | 0.9         |
| y_min                 | -0.6        |
| DimZ                  | 3           |
| z_min                 | -0.9        |
| z_max                 | 0.95        |
| Controller parameters |             |
| maskY                 | 536870911   |
| maskX                 | 1073741823  |
| maskZ                 | 2147483647  |
| maxZ                  | 2040109466  |
| maxY                  | 1932735283  |
| maxX                  | 1503238554  |
| sfrX                  | 30          |
| sfrZ                  | 31          |
| sfrY                  | 29          |
| offsetX               | -107374182  |
| offsetZ               | 53687091    |
| offsetY               | 322122547   |
| gainXsfr              | 30          |
| gainZsfr              | 30          |
| gainX                 | 1431655765  |
| gainZ                 | 1160801972  |
| Table                 | [1x135]     |
| gainY                 | 1431655765  |
| sizeX                 | 5           |
| minY                  | -1288490189 |
| minX                  | -1717986918 |
| minZ                  | -1932735283 |
| idxOffsetY            | 4           |
| idxOffsetX            | 2           |
| sizeY                 | 9           |
| idxOffsetZ            | 1           |
| sizeXY                | 45          |
| gainYsfr              | 1932 30     |
| Exp. maskY            | 536870911   |

| Test settings           |                  |
|-------------------------|------------------|
| Tolerance maskY         | $\pm 0,0000e+00$ |
| Tolerance maskX         | $\pm 0,0000e+00$ |
| Tolerance maskZ         | $\pm 0,0000e+00$ |
| Tolerance maxZ          | $\pm 0,0000e+00$ |
| Tolerance maxY          | $\pm 0,0000e+00$ |
| Tolerance maxX          | $\pm 0,0000e+00$ |
| Tolerance sfrX          | $\pm 0,0000e+00$ |
| Tolerance sfrZ          | $\pm 0,0000e+00$ |
| Tolerance sfrY          | $\pm 0,0000e+00$ |
| Tolerance offsetX       | $\pm 0,0000e+00$ |
| Tolerance offsetZ       | $\pm 0,0000e+00$ |
| Tolerance offsetY       | $\pm 0,0000e+00$ |
| Tolerance gainXsfr      | $\pm 0,0000e+00$ |
| Tolerance gainZsfr      | $\pm 0,0000e+00$ |
| Tolerance gainX         | $\pm 0,0000e+00$ |
| Tolerance gainZ         | $\pm 0,0000e+00$ |
| Tolerance Table         | $\pm 0,0000e+00$ |
| Tolerance gainY         | $\pm 0,0000e+00$ |
| Tolerance sizeX         | $\pm 0,0000e+00$ |
| Tolerance minY          | $\pm 0,0000e+00$ |
| Tolerance minX          | $\pm 0,0000e+00$ |
| Tolerance minZ          | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetY | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetX | $\pm 0,0000e+00$ |
| Tolerance sizeY         | $\pm 0,0000e+00$ |
| Tolerance<br>idxOffsetZ | $\pm 0,0000e+00$ |
| Tolerance sizeXY        | $\pm 0,0000e+00$ |
| Tolerance gainYsfr      | $\pm 0,0000e+00$ |

**Verification: LookupTable3D Float32 CPU TMS320F28335**

Date of Test 2026-06-19  
Target controller TMS320F28335

**Test case: Inport test****OK**

Inport test for General block LookupTable3D.

| Test results   |         |        |     |       |
|----------------|---------|--------|-----|-------|
| Time step      | 1       | 2      | ... | 19    |
| CPU cycles     | 346     | 346    | ... | 349   |
| Inputs         |         |        |     |       |
| x (DSP)        | -1.1    | -0.978 | ... | 1.1   |
| y (DSP)        | -1.35   | -1.208 | ... | 1.2   |
| z (DSP)        | -2.16   | -1.935 | ... | 1.89  |
| x              | -1.1    | -0.978 | ... | 1.1   |
| y              | -1.35   | -1.208 | ... | 1.2   |
| z              | -2.16   | -1.935 | ... | 1.89  |
| Parameters     |         |        |     |       |
| TableData      | [1x765] |        |     |       |
| DimX           | 9       |        |     |       |
| x_min          | -0.8    |        |     |       |
| x_max          | 0.7     |        |     |       |
| DimY           | 17      |        |     |       |
| y_max          | 0.9     |        |     |       |
| y_min          | -0.6    |        |     |       |
| DimZ           | 5       |        |     |       |
| z_min          | -0.9    |        |     |       |
| z_max          | 0.95    |        |     |       |
| Outputs        |         |        |     |       |
| Out            | 1.953   | 1.953  | ... | 2.356 |
| Exp. Out       | 1.953   | 1.953  | ... | 2.356 |
| Out (DSP)      | 1.953   | 1.953  | ... | 2.356 |
| Exp. Out (DSP) | 1.953   | 1.953  | ... | 2.356 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 346 |
| Max CPU cycles  | 349 |
| Avg CPU cycles  | 348 |

**Test case: Conversion test**

OK

Conversion test for General block LookupTable3D.

| Test results                 |         |
|------------------------------|---------|
| Time step                    | 1       |
| <i>Mask parameters</i>       |         |
| TableData                    | [1x135] |
| DimX                         | 5       |
| x_min                        | -0.8    |
| x_max                        | 0.7     |
| DimY                         | 9       |
| y_max                        | 0.9     |
| y_min                        | -0.6    |
| DimZ                         | 3       |
| z_min                        | -0.9    |
| z_max                        | 0.95    |
| <i>Controller parameters</i> |         |
| gainX                        | 2.667   |
| gainZ                        | 1.081   |
| Table                        | [1x135] |
| gainY                        | 5.333   |
| maxZ                         | 0.95    |
| maxY                         | 0.9     |
| maxX                         | 0.7     |
| offsetX                      | -0.8    |
| sizeX                        | 5       |
| offsetZ                      | -0.9    |
| offsetY                      | -0.6    |
| minY                         | -0.6    |
| minX                         | -0.8    |
| minZ                         | -0.9    |
| dimZ                         | 2       |
| dimY                         | 8       |
| sizeY                        | 9       |
| dimX                         | 4       |
| sizeXY                       | 45      |
| Exp. gainX                   | 2.667   |
| Exp. gainZ                   | 1.081   |
| Exp. Table                   | [1x135] |
| Exp. gainY                   | 5.333   |
| Exp. maxZ                    | 0.95    |
| Exp. maxY                    | 0.9     |
| Exp. maxX                    | 0.7     |
| Exp. offsetX                 | -0.8    |
| Exp. sizeX                   | 1936 5  |
| Exp. offsetZ                 | -0.9    |

| Test settings     |                  |
|-------------------|------------------|
| Tolerance gainX   | $\pm 0,0000e+00$ |
| Tolerance gainZ   | $\pm 0,0000e+00$ |
| Tolerance Table   | $\pm 0,0000e+00$ |
| Tolerance gainY   | $\pm 0,0000e+00$ |
| Tolerance maxZ    | $\pm 0,0000e+00$ |
| Tolerance maxY    | $\pm 0,0000e+00$ |
| Tolerance maxX    | $\pm 0,0000e+00$ |
| Tolerance offsetX | $\pm 0,0000e+00$ |
| Tolerance sizeX   | $\pm 0,0000e+00$ |
| Tolerance offsetZ | $\pm 0,0000e+00$ |
| Tolerance offsetY | $\pm 0,0000e+00$ |
| Tolerance minY    | $\pm 0,0000e+00$ |
| Tolerance minX    | $\pm 0,0000e+00$ |
| Tolerance minZ    | $\pm 0,0000e+00$ |
| Tolerance dimZ    | $\pm 0,0000e+00$ |
| Tolerance dimY    | $\pm 0,0000e+00$ |
| Tolerance sizeY   | $\pm 0,0000e+00$ |
| Tolerance dimX    | $\pm 0,0000e+00$ |
| Tolerance sizeXY  | $\pm 0,0000e+00$ |

**Verification: LookupTable3D Float32 CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block LookupTable3D.

| Test results   |         |        |     |       |
|----------------|---------|--------|-----|-------|
| Time step      | 1       | 2      | ... | 19    |
| CPU cycles     | 249     | 249    | ... | 277   |
| Inputs         |         |        |     |       |
| x (DSP)        | -1.1    | -0.978 | ... | 1.1   |
| y (DSP)        | -1.35   | -1.208 | ... | 1.2   |
| z (DSP)        | -2.16   | -1.935 | ... | 1.89  |
| x              | -1.1    | -0.978 | ... | 1.1   |
| y              | -1.35   | -1.208 | ... | 1.2   |
| z              | -2.16   | -1.935 | ... | 1.89  |
| Parameters     |         |        |     |       |
| TableData      | [1x765] |        |     |       |
| DimX           | 9       |        |     |       |
| x_min          | -0.8    |        |     |       |
| x_max          | 0.7     |        |     |       |
| DimY           | 17      |        |     |       |
| y_max          | 0.9     |        |     |       |
| y_min          | -0.6    |        |     |       |
| DimZ           | 5       |        |     |       |
| z_min          | -0.9    |        |     |       |
| z_max          | 0.95    |        |     |       |
| Outputs        |         |        |     |       |
| Out            | 1.953   | 1.953  | ... | 2.356 |
| Exp. Out       | 1.953   | 1.953  | ... | 2.356 |
| Out (DSP)      | 1.953   | 1.953  | ... | 2.356 |
| Exp. Out (DSP) | 1.953   | 1.953  | ... | 2.356 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 249 |
| Max CPU cycles  | 277 |
| Avg CPU cycles  | 266 |

**Test case: Conversion test**

OK

Conversion test for General block LookupTable3D.



| Test results          |         |
|-----------------------|---------|
| Time step             | 1       |
| Mask parameters       |         |
| TableData             | [1x135] |
| DimX                  | 5       |
| x_min                 | -0.8    |
| x_max                 | 0.7     |
| DimY                  | 9       |
| y_max                 | 0.9     |
| y_min                 | -0.6    |
| DimZ                  | 3       |
| z_min                 | -0.9    |
| z_max                 | 0.95    |
| Controller parameters |         |
| gainX                 | 2.667   |
| gainZ                 | 1.081   |
| Table                 | [1x135] |
| gainY                 | 5.333   |
| maxZ                  | 0.95    |
| maxY                  | 0.9     |
| maxX                  | 0.7     |
| offsetX               | -0.8    |
| sizeX                 | 5       |
| offsetZ               | -0.9    |
| offsetY               | -0.6    |
| minY                  | -0.6    |
| minX                  | -0.8    |
| minZ                  | -0.9    |
| dimZ                  | 2       |
| dimY                  | 8       |
| sizeY                 | 9       |
| dimX                  | 4       |
| sizeXY                | 45      |
| Exp. gainX            | 2.667   |
| Exp. gainZ            | 1.081   |
| Exp. Table            | [1x135] |
| Exp. gainY            | 5.333   |
| Exp. maxZ             | 0.95    |
| Exp. maxY             | 0.9     |
| Exp. maxX             | 0.7     |
| Exp. offsetX          | -0.8    |
| Exp. sizeX            | 1940 5  |
| Exp. offsetZ          | -0.9    |

| Test settings     |                  |
|-------------------|------------------|
| Tolerance gainX   | $\pm 0,0000e+00$ |
| Tolerance gainZ   | $\pm 0,0000e+00$ |
| Tolerance Table   | $\pm 0,0000e+00$ |
| Tolerance gainY   | $\pm 0,0000e+00$ |
| Tolerance maxZ    | $\pm 0,0000e+00$ |
| Tolerance maxY    | $\pm 0,0000e+00$ |
| Tolerance maxX    | $\pm 0,0000e+00$ |
| Tolerance offsetX | $\pm 0,0000e+00$ |
| Tolerance sizeX   | $\pm 0,0000e+00$ |
| Tolerance offsetZ | $\pm 0,0000e+00$ |
| Tolerance offsetY | $\pm 0,0000e+00$ |
| Tolerance minY    | $\pm 0,0000e+00$ |
| Tolerance minX    | $\pm 0,0000e+00$ |
| Tolerance minZ    | $\pm 0,0000e+00$ |
| Tolerance dimZ    | $\pm 0,0000e+00$ |
| Tolerance dimY    | $\pm 0,0000e+00$ |
| Tolerance sizeY   | $\pm 0,0000e+00$ |
| Tolerance dimX    | $\pm 0,0000e+00$ |
| Tolerance sizeXY  | $\pm 0,0000e+00$ |

**Verification: LookupTable3D Float32 CPU STM32G474RE**

Date of Test 2026-06-19  
Target controller STM32G474RE

**Test case: Inport test****OK**

Inport test for General block LookupTable3D.

| Test results   |         |        |     |       |
|----------------|---------|--------|-----|-------|
| Time step      | 1       | 2      | ... | 19    |
| CPU cycles     | 371     | 371    | ... | 376   |
| Inputs         |         |        |     |       |
| x (DSP)        | -1.1    | -0.978 | ... | 1.1   |
| y (DSP)        | -1.35   | -1.208 | ... | 1.2   |
| z (DSP)        | -2.16   | -1.935 | ... | 1.89  |
| x              | -1.1    | -0.978 | ... | 1.1   |
| y              | -1.35   | -1.208 | ... | 1.2   |
| z              | -2.16   | -1.935 | ... | 1.89  |
| Parameters     |         |        |     |       |
| TableData      | [1x765] |        |     |       |
| DimX           | 9       |        |     |       |
| x_min          | -0.8    |        |     |       |
| x_max          | 0.7     |        |     |       |
| DimY           | 17      |        |     |       |
| y_max          | 0.9     |        |     |       |
| y_min          | -0.6    |        |     |       |
| DimZ           | 5       |        |     |       |
| z_min          | -0.9    |        |     |       |
| z_max          | 0.95    |        |     |       |
| Outputs        |         |        |     |       |
| Out            | 1.953   | 1.953  | ... | 2.356 |
| Exp. Out       | 1.953   | 1.953  | ... | 2.356 |
| Out (DSP)      | 1.953   | 1.953  | ... | 2.356 |
| Exp. Out (DSP) | 1.953   | 1.953  | ... | 2.356 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 371 |
| Max CPU cycles  | 376 |
| Avg CPU cycles  | 375 |

**Test case: Conversion test**

OK

Conversion test for General block LookupTable3D.

| Test results          |         |
|-----------------------|---------|
| Time step             | 1       |
| Mask parameters       |         |
| TableData             | [1x135] |
| DimX                  | 5       |
| x_min                 | -0.8    |
| x_max                 | 0.7     |
| DimY                  | 9       |
| y_max                 | 0.9     |
| y_min                 | -0.6    |
| DimZ                  | 3       |
| z_min                 | -0.9    |
| z_max                 | 0.95    |
| Controller parameters |         |
| gainX                 | 2.667   |
| gainZ                 | 1.081   |
| Table                 | [1x135] |
| gainY                 | 5.333   |
| maxZ                  | 0.95    |
| maxY                  | 0.9     |
| maxX                  | 0.7     |
| offsetX               | -0.8    |
| sizeX                 | 5       |
| offsetZ               | -0.9    |
| offsetY               | -0.6    |
| minY                  | -0.6    |
| minX                  | -0.8    |
| minZ                  | -0.9    |
| dimZ                  | 2       |
| dimY                  | 8       |
| sizeY                 | 9       |
| dimX                  | 4       |
| sizeXY                | 45      |
| Exp. gainX            | 2.667   |
| Exp. gainZ            | 1.081   |
| Exp. Table            | [1x135] |
| Exp. gainY            | 5.333   |
| Exp. maxZ             | 0.95    |
| Exp. maxY             | 0.9     |
| Exp. maxX             | 0.7     |
| Exp. offsetX          | -0.8    |
| Exp. sizeX            | 1944 5  |
| Exp. offsetZ          | -0.9    |

| Test settings     |                  |
|-------------------|------------------|
| Tolerance gainX   | $\pm 0,0000e+00$ |
| Tolerance gainZ   | $\pm 0,0000e+00$ |
| Tolerance Table   | $\pm 0,0000e+00$ |
| Tolerance gainY   | $\pm 0,0000e+00$ |
| Tolerance maxZ    | $\pm 0,0000e+00$ |
| Tolerance maxY    | $\pm 0,0000e+00$ |
| Tolerance maxX    | $\pm 0,0000e+00$ |
| Tolerance offsetX | $\pm 0,0000e+00$ |
| Tolerance sizeX   | $\pm 0,0000e+00$ |
| Tolerance offsetZ | $\pm 0,0000e+00$ |
| Tolerance offsetY | $\pm 0,0000e+00$ |
| Tolerance minY    | $\pm 0,0000e+00$ |
| Tolerance minX    | $\pm 0,0000e+00$ |
| Tolerance minZ    | $\pm 0,0000e+00$ |
| Tolerance dimZ    | $\pm 0,0000e+00$ |
| Tolerance dimY    | $\pm 0,0000e+00$ |
| Tolerance sizeY   | $\pm 0,0000e+00$ |
| Tolerance dimX    | $\pm 0,0000e+00$ |
| Tolerance sizeXY  | $\pm 0,0000e+00$ |

**Verification: LookupTable3D Float32 CPU STM32F072RB**

Date of Test 2026-06-19  
Target controller STM32F072RB

**Test case: Inport test****OK**

Inport test for General block LookupTable3D.

| Test results   |         |        |     |       |
|----------------|---------|--------|-----|-------|
| Time step      | 1       | 2      | ... | 19    |
| CPU cycles     | 6805    | 6748   | ... | 7046  |
| Inputs         |         |        |     |       |
| x (DSP)        | -1.1    | -0.978 | ... | 1.1   |
| y (DSP)        | -1.35   | -1.208 | ... | 1.2   |
| z (DSP)        | -2.16   | -1.935 | ... | 1.89  |
| x              | -1.1    | -0.978 | ... | 1.1   |
| y              | -1.35   | -1.208 | ... | 1.2   |
| z              | -2.16   | -1.935 | ... | 1.89  |
| Parameters     |         |        |     |       |
| TableData      | [1x765] |        |     |       |
| DimX           | 9       |        |     |       |
| x_min          | -0.8    |        |     |       |
| x_max          | 0.7     |        |     |       |
| DimY           | 17      |        |     |       |
| y_max          | 0.9     |        |     |       |
| y_min          | -0.6    |        |     |       |
| DimZ           | 5       |        |     |       |
| z_min          | -0.9    |        |     |       |
| z_max          | 0.95    |        |     |       |
| Outputs        |         |        |     |       |
| Out            | 1.953   | 1.953  | ... | 2.356 |
| Exp. Out       | 1.953   | 1.953  | ... | 2.356 |
| Out (DSP)      | 1.953   | 1.953  | ... | 2.356 |
| Exp. Out (DSP) | 1.953   | 1.953  | ... | 2.356 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 6748 |
| Max CPU cycles  | 8744 |
| Avg CPU cycles  | 7726 |

**Test case: Conversion test**

OK

Conversion test for General block LookupTable3D.



| Test results                 |         |
|------------------------------|---------|
| Time step                    | 1       |
| <i>Mask parameters</i>       |         |
| TableData                    | [1x135] |
| DimX                         | 5       |
| x_min                        | -0.8    |
| x_max                        | 0.7     |
| DimY                         | 9       |
| y_max                        | 0.9     |
| y_min                        | -0.6    |
| DimZ                         | 3       |
| z_min                        | -0.9    |
| z_max                        | 0.95    |
| <i>Controller parameters</i> |         |
| gainX                        | 2.667   |
| gainZ                        | 1.081   |
| Table                        | [1x135] |
| gainY                        | 5.333   |
| maxZ                         | 0.95    |
| maxY                         | 0.9     |
| maxX                         | 0.7     |
| offsetX                      | -0.8    |
| sizeX                        | 5       |
| offsetZ                      | -0.9    |
| offsetY                      | -0.6    |
| minY                         | -0.6    |
| minX                         | -0.8    |
| minZ                         | -0.9    |
| dimZ                         | 2       |
| dimY                         | 8       |
| sizeY                        | 9       |
| dimX                         | 4       |
| sizeXY                       | 45      |
| Exp. gainX                   | 2.667   |
| Exp. gainZ                   | 1.081   |
| Exp. Table                   | [1x135] |
| Exp. gainY                   | 5.333   |
| Exp. maxZ                    | 0.95    |
| Exp. maxY                    | 0.9     |
| Exp. maxX                    | 0.7     |
| Exp. offsetX                 | -0.8    |
| Exp. sizeX                   | 1948 5  |
| Exp. offsetZ                 | -0.9    |

| Test settings     |                  |
|-------------------|------------------|
| Tolerance gainX   | $\pm 0,0000e+00$ |
| Tolerance gainZ   | $\pm 0,0000e+00$ |
| Tolerance Table   | $\pm 0,0000e+00$ |
| Tolerance gainY   | $\pm 0,0000e+00$ |
| Tolerance maxZ    | $\pm 0,0000e+00$ |
| Tolerance maxY    | $\pm 0,0000e+00$ |
| Tolerance maxX    | $\pm 0,0000e+00$ |
| Tolerance offsetX | $\pm 0,0000e+00$ |
| Tolerance sizeX   | $\pm 0,0000e+00$ |
| Tolerance offsetZ | $\pm 0,0000e+00$ |
| Tolerance offsetY | $\pm 0,0000e+00$ |
| Tolerance minY    | $\pm 0,0000e+00$ |
| Tolerance minX    | $\pm 0,0000e+00$ |
| Tolerance minZ    | $\pm 0,0000e+00$ |
| Tolerance dimZ    | $\pm 0,0000e+00$ |
| Tolerance dimY    | $\pm 0,0000e+00$ |
| Tolerance sizeY   | $\pm 0,0000e+00$ |
| Tolerance dimX    | $\pm 0,0000e+00$ |
| Tolerance sizeXY  | $\pm 0,0000e+00$ |

**Verification: LookupTable3D Float32 CPU PIC32MX170F256**

Date of Test 2026-06-19  
Target controller PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block LookupTable3D.

| Test results   |         |        |     |       |
|----------------|---------|--------|-----|-------|
| Time step      | 1       | 2      | ... | 19    |
| CPU cycles     | 2531    | 2531   | ... | 2839  |
| Inputs         |         |        |     |       |
| x (DSP)        | -1.1    | -0.978 | ... | 1.1   |
| y (DSP)        | -1.35   | -1.208 | ... | 1.2   |
| z (DSP)        | -2.16   | -1.935 | ... | 1.89  |
| x              | -1.1    | -0.978 | ... | 1.1   |
| y              | -1.35   | -1.208 | ... | 1.2   |
| z              | -2.16   | -1.935 | ... | 1.89  |
| Parameters     |         |        |     |       |
| TableData      | [1x765] |        |     |       |
| DimX           | 9       |        |     |       |
| x_min          | -0.8    |        |     |       |
| x_max          | 0.7     |        |     |       |
| DimY           | 17      |        |     |       |
| y_max          | 0.9     |        |     |       |
| y_min          | -0.6    |        |     |       |
| DimZ           | 5       |        |     |       |
| z_min          | -0.9    |        |     |       |
| z_max          | 0.95    |        |     |       |
| Outputs        |         |        |     |       |
| Out            | 1.953   | 1.953  | ... | 2.356 |
| Exp. Out       | 1.953   | 1.953  | ... | 2.356 |
| Out (DSP)      | 1.953   | 1.953  | ... | 2.356 |
| Exp. Out (DSP) | 1.953   | 1.953  | ... | 2.356 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2531 |
| Max CPU cycles  | 3299 |
| Avg CPU cycles  | 2957 |

**Test case: Conversion test**

OK

Conversion test for General block LookupTable3D.

| Test results                 |         |
|------------------------------|---------|
| Time step                    | 1       |
| <i>Mask parameters</i>       |         |
| TableData                    | [1x135] |
| DimX                         | 5       |
| x_min                        | -0.8    |
| x_max                        | 0.7     |
| DimY                         | 9       |
| y_max                        | 0.9     |
| y_min                        | -0.6    |
| DimZ                         | 3       |
| z_min                        | -0.9    |
| z_max                        | 0.95    |
| <i>Controller parameters</i> |         |
| gainX                        | 2.667   |
| gainZ                        | 1.081   |
| Table                        | [1x135] |
| gainY                        | 5.333   |
| maxZ                         | 0.95    |
| maxY                         | 0.9     |
| maxX                         | 0.7     |
| offsetX                      | -0.8    |
| sizeX                        | 5       |
| offsetZ                      | -0.9    |
| offsetY                      | -0.6    |
| minY                         | -0.6    |
| minX                         | -0.8    |
| minZ                         | -0.9    |
| dimZ                         | 2       |
| dimY                         | 8       |
| sizeY                        | 9       |
| dimX                         | 4       |
| sizeXY                       | 45      |
| Exp. gainX                   | 2.667   |
| Exp. gainZ                   | 1.081   |
| Exp. Table                   | [1x135] |
| Exp. gainY                   | 5.333   |
| Exp. maxZ                    | 0.95    |
| Exp. maxY                    | 0.9     |
| Exp. maxX                    | 0.7     |
| Exp. offsetX                 | -0.8    |
| Exp. sizeX                   | 1952 5  |
| Exp. offsetZ                 | -0.9    |

| Test settings     |                  |
|-------------------|------------------|
| Tolerance gainX   | $\pm 0,0000e+00$ |
| Tolerance gainZ   | $\pm 0,0000e+00$ |
| Tolerance Table   | $\pm 0,0000e+00$ |
| Tolerance gainY   | $\pm 0,0000e+00$ |
| Tolerance maxZ    | $\pm 0,0000e+00$ |
| Tolerance maxY    | $\pm 0,0000e+00$ |
| Tolerance maxX    | $\pm 0,0000e+00$ |
| Tolerance offsetX | $\pm 0,0000e+00$ |
| Tolerance sizeX   | $\pm 0,0000e+00$ |
| Tolerance offsetZ | $\pm 0,0000e+00$ |
| Tolerance offsetY | $\pm 0,0000e+00$ |
| Tolerance minY    | $\pm 0,0000e+00$ |
| Tolerance minX    | $\pm 0,0000e+00$ |
| Tolerance minZ    | $\pm 0,0000e+00$ |
| Tolerance dimZ    | $\pm 0,0000e+00$ |
| Tolerance dimY    | $\pm 0,0000e+00$ |
| Tolerance sizeY   | $\pm 0,0000e+00$ |
| Tolerance dimX    | $\pm 0,0000e+00$ |
| Tolerance sizeXY  | $\pm 0,0000e+00$ |

**Verification: LookupTable3D Float32 CPU dsPIC33EP256MC502**

Date of Test 2026-06-19  
Target controller dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block LookupTable3D.

| Test results   |         |        |     |       |
|----------------|---------|--------|-----|-------|
| Time step      | 1       | 2      | ... | 19    |
| CPU cycles     | 8253    | 8253   | ... | 10165 |
| Inputs         |         |        |     |       |
| x (DSP)        | -1.1    | -0.978 | ... | 1.1   |
| y (DSP)        | -1.35   | -1.208 | ... | 1.2   |
| z (DSP)        | -2.16   | -1.935 | ... | 1.89  |
| x              | -1.1    | -0.978 | ... | 1.1   |
| y              | -1.35   | -1.208 | ... | 1.2   |
| z              | -2.16   | -1.935 | ... | 1.89  |
| Parameters     |         |        |     |       |
| TableData      | [1x765] |        |     |       |
| DimX           | 9       |        |     |       |
| x_min          | -0.8    |        |     |       |
| x_max          | 0.7     |        |     |       |
| DimY           | 17      |        |     |       |
| y_max          | 0.9     |        |     |       |
| y_min          | -0.6    |        |     |       |
| DimZ           | 5       |        |     |       |
| z_min          | -0.9    |        |     |       |
| z_max          | 0.95    |        |     |       |
| Outputs        |         |        |     |       |
| Out            | 1.953   | 1.953  | ... | 2.356 |
| Exp. Out       | 1.953   | 1.953  | ... | 2.356 |
| Out (DSP)      | 1.953   | 1.953  | ... | 2.356 |
| Exp. Out (DSP) | 1.953   | 1.953  | ... | 2.356 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 8253  |
| Max CPU cycles  | 11431 |
| Avg CPU cycles  | 9995  |

**Test case: Conversion test**

OK

Conversion test for General block LookupTable3D.



| Test results          |         |
|-----------------------|---------|
| Time step             | 1       |
| Mask parameters       |         |
| TableData             | [1x135] |
| DimX                  | 5       |
| x_min                 | -0.8    |
| x_max                 | 0.7     |
| DimY                  | 9       |
| y_max                 | 0.9     |
| y_min                 | -0.6    |
| DimZ                  | 3       |
| z_min                 | -0.9    |
| z_max                 | 0.95    |
| Controller parameters |         |
| gainX                 | 2.667   |
| gainZ                 | 1.081   |
| Table                 | [1x135] |
| gainY                 | 5.333   |
| maxZ                  | 0.95    |
| maxY                  | 0.9     |
| maxX                  | 0.7     |
| offsetX               | -0.8    |
| sizeX                 | 5       |
| offsetZ               | -0.9    |
| offsetY               | -0.6    |
| minY                  | -0.6    |
| minX                  | -0.8    |
| minZ                  | -0.9    |
| dimZ                  | 2       |
| dimY                  | 8       |
| sizeY                 | 9       |
| dimX                  | 4       |
| sizeXY                | 45      |
| Exp. gainX            | 2.667   |
| Exp. gainZ            | 1.081   |
| Exp. Table            | [1x135] |
| Exp. gainY            | 5.333   |
| Exp. maxZ             | 0.95    |
| Exp. maxY             | 0.9     |
| Exp. maxX             | 0.7     |
| Exp. offsetX          | -0.8    |
| Exp. sizeX            | 1956 5  |
| Exp. offsetZ          | -0.9    |

| Test settings     |                  |
|-------------------|------------------|
| Tolerance gainX   | $\pm 0,0000e+00$ |
| Tolerance gainZ   | $\pm 0,0000e+00$ |
| Tolerance Table   | $\pm 0,0000e+00$ |
| Tolerance gainY   | $\pm 0,0000e+00$ |
| Tolerance maxZ    | $\pm 0,0000e+00$ |
| Tolerance maxY    | $\pm 0,0000e+00$ |
| Tolerance maxX    | $\pm 0,0000e+00$ |
| Tolerance offsetX | $\pm 0,0000e+00$ |
| Tolerance sizeX   | $\pm 0,0000e+00$ |
| Tolerance offsetZ | $\pm 0,0000e+00$ |
| Tolerance offsetY | $\pm 0,0000e+00$ |
| Tolerance minY    | $\pm 0,0000e+00$ |
| Tolerance minX    | $\pm 0,0000e+00$ |
| Tolerance minZ    | $\pm 0,0000e+00$ |
| Tolerance dimZ    | $\pm 0,0000e+00$ |
| Tolerance dimY    | $\pm 0,0000e+00$ |
| Tolerance sizeY   | $\pm 0,0000e+00$ |
| Tolerance dimX    | $\pm 0,0000e+00$ |
| Tolerance sizeXY  | $\pm 0,0000e+00$ |

**Verification: LookupTable3D Float32 CPU XMC4800-F144K2048**

Date of Test 2026-06-19  
Target controller XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block LookupTable3D.

| Test results   |         |        |     |       |
|----------------|---------|--------|-----|-------|
| Time step      | 1       | 2      | ... | 19    |
| CPU cycles     | 362     | 273    | ... | 291   |
| Inputs         |         |        |     |       |
| x (DSP)        | -1.1    | -0.978 | ... | 1.1   |
| y (DSP)        | -1.35   | -1.208 | ... | 1.2   |
| z (DSP)        | -2.16   | -1.935 | ... | 1.89  |
| x              | -1.1    | -0.978 | ... | 1.1   |
| y              | -1.35   | -1.208 | ... | 1.2   |
| z              | -2.16   | -1.935 | ... | 1.89  |
| Parameters     |         |        |     |       |
| TableData      | [1x765] |        |     |       |
| DimX           | 9       |        |     |       |
| x_min          | -0.8    |        |     |       |
| x_max          | 0.7     |        |     |       |
| DimY           | 17      |        |     |       |
| y_max          | 0.9     |        |     |       |
| y_min          | -0.6    |        |     |       |
| DimZ           | 5       |        |     |       |
| z_min          | -0.9    |        |     |       |
| z_max          | 0.95    |        |     |       |
| Outputs        |         |        |     |       |
| Out            | 1.953   | 1.953  | ... | 2.356 |
| Exp. Out       | 1.953   | 1.953  | ... | 2.356 |
| Out (DSP)      | 1.953   | 1.953  | ... | 2.356 |
| Exp. Out (DSP) | 1.953   | 1.953  | ... | 2.356 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 273 |
| Max CPU cycles  | 362 |
| Avg CPU cycles  | 291 |

**Test case: Conversion test**

OK

Conversion test for General block LookupTable3D.

| Test results                 |         |
|------------------------------|---------|
| Time step                    | 1       |
| <i>Mask parameters</i>       |         |
| TableData                    | [1x135] |
| DimX                         | 5       |
| x_min                        | -0.8    |
| x_max                        | 0.7     |
| DimY                         | 9       |
| y_max                        | 0.9     |
| y_min                        | -0.6    |
| DimZ                         | 3       |
| z_min                        | -0.9    |
| z_max                        | 0.95    |
| <i>Controller parameters</i> |         |
| gainX                        | 2.667   |
| gainZ                        | 1.081   |
| Table                        | [1x135] |
| gainY                        | 5.333   |
| maxZ                         | 0.95    |
| maxY                         | 0.9     |
| maxX                         | 0.7     |
| offsetX                      | -0.8    |
| sizeX                        | 5       |
| offsetZ                      | -0.9    |
| offsetY                      | -0.6    |
| minY                         | -0.6    |
| minX                         | -0.8    |
| minZ                         | -0.9    |
| dimZ                         | 2       |
| dimY                         | 8       |
| sizeY                        | 9       |
| dimX                         | 4       |
| sizeXY                       | 45      |
| Exp. gainX                   | 2.667   |
| Exp. gainZ                   | 1.081   |
| Exp. Table                   | [1x135] |
| Exp. gainY                   | 5.333   |
| Exp. maxZ                    | 0.95    |
| Exp. maxY                    | 0.9     |
| Exp. maxX                    | 0.7     |
| Exp. offsetX                 | -0.8    |
| Exp. sizeX                   | 1960 5  |
| Exp. offsetZ                 | -0.9    |

| Test settings     |                  |
|-------------------|------------------|
| Tolerance gainX   | $\pm 0,0000e+00$ |
| Tolerance gainZ   | $\pm 0,0000e+00$ |
| Tolerance Table   | $\pm 0,0000e+00$ |
| Tolerance gainY   | $\pm 0,0000e+00$ |
| Tolerance maxZ    | $\pm 0,0000e+00$ |
| Tolerance maxY    | $\pm 0,0000e+00$ |
| Tolerance maxX    | $\pm 0,0000e+00$ |
| Tolerance offsetX | $\pm 0,0000e+00$ |
| Tolerance sizeX   | $\pm 0,0000e+00$ |
| Tolerance offsetZ | $\pm 0,0000e+00$ |
| Tolerance offsetY | $\pm 0,0000e+00$ |
| Tolerance minY    | $\pm 0,0000e+00$ |
| Tolerance minX    | $\pm 0,0000e+00$ |
| Tolerance minZ    | $\pm 0,0000e+00$ |
| Tolerance dimZ    | $\pm 0,0000e+00$ |
| Tolerance dimY    | $\pm 0,0000e+00$ |
| Tolerance sizeY   | $\pm 0,0000e+00$ |
| Tolerance dimX    | $\pm 0,0000e+00$ |
| Tolerance sizeXY  | $\pm 0,0000e+00$ |

**Verification: LookupTable3D Float32 CPU TMS320F28379D**

Date of Test 2026-06-22  
Target controller TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block LookupTable3D.

| Test results   |         |        |     |       |
|----------------|---------|--------|-----|-------|
| Time step      | 1       | 2      | ... | 19    |
| CPU cycles     | 303     | 303    | ... | 296   |
| Inputs         |         |        |     |       |
| x (DSP)        | -1.1    | -0.978 | ... | 1.1   |
| y (DSP)        | -1.35   | -1.208 | ... | 1.2   |
| z (DSP)        | -2.16   | -1.935 | ... | 1.89  |
| x              | -1.1    | -0.978 | ... | 1.1   |
| y              | -1.35   | -1.208 | ... | 1.2   |
| z              | -2.16   | -1.935 | ... | 1.89  |
| Parameters     |         |        |     |       |
| TableData      | [1x765] |        |     |       |
| DimX           | 9       |        |     |       |
| x_min          | -0.8    |        |     |       |
| x_max          | 0.7     |        |     |       |
| DimY           | 17      |        |     |       |
| y_max          | 0.9     |        |     |       |
| y_min          | -0.6    |        |     |       |
| DimZ           | 5       |        |     |       |
| z_min          | -0.9    |        |     |       |
| z_max          | 0.95    |        |     |       |
| Outputs        |         |        |     |       |
| Out            | 1.953   | 1.953  | ... | 2.356 |
| Exp. Out       | 1.953   | 1.953  | ... | 2.356 |
| Out (DSP)      | 1.953   | 1.953  | ... | 2.356 |
| Exp. Out (DSP) | 1.953   | 1.953  | ... | 2.356 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 9,3132e-07$ ( $\pm 2000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 291 |
| Max CPU cycles  | 303 |
| Avg CPU cycles  | 296 |

**Test case: Conversion test**

OK

Conversion test for General block LookupTable3D.



| Test results                 |         |
|------------------------------|---------|
| Time step                    | 1       |
| <i>Mask parameters</i>       |         |
| TableData                    | [1x135] |
| DimX                         | 5       |
| x_min                        | -0.8    |
| x_max                        | 0.7     |
| DimY                         | 9       |
| y_max                        | 0.9     |
| y_min                        | -0.6    |
| DimZ                         | 3       |
| z_min                        | -0.9    |
| z_max                        | 0.95    |
| <i>Controller parameters</i> |         |
| gainX                        | 2.667   |
| gainZ                        | 1.081   |
| Table                        | [1x135] |
| gainY                        | 5.333   |
| maxZ                         | 0.95    |
| maxY                         | 0.9     |
| maxX                         | 0.7     |
| offsetX                      | -0.8    |
| sizeX                        | 5       |
| offsetZ                      | -0.9    |
| offsetY                      | -0.6    |
| minY                         | -0.6    |
| minX                         | -0.8    |
| minZ                         | -0.9    |
| dimZ                         | 2       |
| dimY                         | 8       |
| sizeY                        | 9       |
| dimX                         | 4       |
| sizeXY                       | 45      |
| Exp. gainX                   | 2.667   |
| Exp. gainZ                   | 1.081   |
| Exp. Table                   | [1x135] |
| Exp. gainY                   | 5.333   |
| Exp. maxZ                    | 0.95    |
| Exp. maxY                    | 0.9     |
| Exp. maxX                    | 0.7     |
| Exp. offsetX                 | -0.8    |
| Exp. sizeX                   | 1964 5  |
| Exp. offsetZ                 | -0.9    |

| Test settings     |                  |
|-------------------|------------------|
| Tolerance gainX   | $\pm 0,0000e+00$ |
| Tolerance gainZ   | $\pm 0,0000e+00$ |
| Tolerance Table   | $\pm 0,0000e+00$ |
| Tolerance gainY   | $\pm 0,0000e+00$ |
| Tolerance maxZ    | $\pm 0,0000e+00$ |
| Tolerance maxY    | $\pm 0,0000e+00$ |
| Tolerance maxX    | $\pm 0,0000e+00$ |
| Tolerance offsetX | $\pm 0,0000e+00$ |
| Tolerance sizeX   | $\pm 0,0000e+00$ |
| Tolerance offsetZ | $\pm 0,0000e+00$ |
| Tolerance offsetY | $\pm 0,0000e+00$ |
| Tolerance minY    | $\pm 0,0000e+00$ |
| Tolerance minX    | $\pm 0,0000e+00$ |
| Tolerance minZ    | $\pm 0,0000e+00$ |
| Tolerance dimZ    | $\pm 0,0000e+00$ |
| Tolerance dimY    | $\pm 0,0000e+00$ |
| Tolerance sizeY   | $\pm 0,0000e+00$ |
| Tolerance dimX    | $\pm 0,0000e+00$ |
| Tolerance sizeXY  | $\pm 0,0000e+00$ |

## Block: LoopBreaker

---



Block to break algebraic loops.

| Inports |             |
|---------|-------------|
| In      | Input In(k) |

| Outports |                       |
|----------|-----------------------|
| Out      | Output Out(k)=In(k-1) |

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>Bool</b>    | Boolean Integration                  |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: Bool

---

Boolean Integration

| Inports Data Type |      |
|-------------------|------|
| In                | bool |

| Outports Data Type |      |
|--------------------|------|
| Out                | bool |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

---

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

---

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

---

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: LoopBreaker FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block LoopBreaker.

| Test results          |    |       |       |       |     |    |
|-----------------------|----|-------|-------|-------|-----|----|
| <b>Time step</b>      | 1  | 2     | 3     | 4     | ... | 18 |
| <b>CPU cycles</b>     | 56 | 56    | 56    | 56    | ... | 56 |
| <i>Inputs</i>         |    |       |       |       |     |    |
| <b>In (DSP)</b>       | 0  | 32767 | 32767 | 32767 | ... | 0  |
| <b>In</b>             | 0  | 1     | 1     | 1.1   | ... | 0  |
| <i>Outputs</i>        |    |       |       |       |     |    |
| <b>Out</b>            | 0  | 1     | 1     | 1     | ... | 0  |
| <b>Exp. Out</b>       | 0  | 1     | 1     | 1     | ... | 0  |
| <b>Out (DSP)</b>      | 0  | 32767 | 32767 | 32767 | ... | 0  |
| <b>Exp. Out (DSP)</b> | 0  | 32767 | 32767 | 32767 | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 56 |
| Avg CPU cycles  | 56 |

**Verification: LoopBreaker FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block LoopBreaker.

| Test results          |    |       |       |       |     |    |
|-----------------------|----|-------|-------|-------|-----|----|
| <b>Time step</b>      | 1  | 2     | 3     | 4     | ... | 18 |
| <b>CPU cycles</b>     | 23 | 23    | 23    | 23    | ... | 23 |
| <i>Inputs</i>         |    |       |       |       |     |    |
| <b>In (DSP)</b>       | 0  | 32767 | 32767 | 32767 | ... | 0  |
| <b>In</b>             | 0  | 1     | 1     | 1.1   | ... | 0  |
| <i>Outputs</i>        |    |       |       |       |     |    |
| <b>Out</b>            | 0  | 1     | 1     | 1     | ... | 0  |
| <b>Exp. Out</b>       | 0  | 1     | 1     | 1     | ... | 0  |
| <b>Out (DSP)</b>      | 0  | 32767 | 32767 | 32767 | ... | 0  |
| <b>Exp. Out (DSP)</b> | 0  | 32767 | 32767 | 32767 | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 23 |
| Max CPU cycles  | 23 |
| Avg CPU cycles  | 23 |

## Verification: LoopBreaker FiP16 CPU STM32G474RE

Date of Test 2026-06-19  
Target controller STM32G474RE

### Test case: Inport test

OK

Inport test for General block LoopBreaker.

| Test results   |    |       |       |       |     |    |
|----------------|----|-------|-------|-------|-----|----|
| Time step      | 1  | 2     | 3     | 4     | ... | 18 |
| CPU cycles     | 57 | 57    | 57    | 57    | ... | 57 |
| Inputs         |    |       |       |       |     |    |
| In (DSP)       | 0  | 32767 | 32767 | 32767 | ... | 0  |
| In             | 0  | 1     | 1     | 1.1   | ... | 0  |
| Outputs        |    |       |       |       |     |    |
| Out            | 0  | 1     | 1     | 1     | ... | 0  |
| Exp. Out       | 0  | 1     | 1     | 1     | ... | 0  |
| Out (DSP)      | 0  | 32767 | 32767 | 32767 | ... | 0  |
| Exp. Out (DSP) | 0  | 32767 | 32767 | 32767 | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 57 |

**Verification: LoopBreaker FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block LoopBreaker.

| Test results          |    |       |       |       |     |    |
|-----------------------|----|-------|-------|-------|-----|----|
| <b>Time step</b>      | 1  | 2     | 3     | 4     | ... | 18 |
| <b>CPU cycles</b>     | 46 | 46    | 46    | 46    | ... | 46 |
| <i>Inputs</i>         |    |       |       |       |     |    |
| <b>In (DSP)</b>       | 0  | 32767 | 32767 | 32767 | ... | 0  |
| <b>In</b>             | 0  | 1     | 1     | 1.1   | ... | 0  |
| <i>Outputs</i>        |    |       |       |       |     |    |
| <b>Out</b>            | 0  | 1     | 1     | 1     | ... | 0  |
| <b>Exp. Out</b>       | 0  | 1     | 1     | 1     | ... | 0  |
| <b>Out (DSP)</b>      | 0  | 32767 | 32767 | 32767 | ... | 0  |
| <b>Exp. Out (DSP)</b> | 0  | 32767 | 32767 | 32767 | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 46 |
| Max CPU cycles  | 46 |
| Avg CPU cycles  | 46 |



**Verification: LoopBreaker FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block LoopBreaker.

| Test results          |    |       |       |       |     |    |
|-----------------------|----|-------|-------|-------|-----|----|
| <b>Time step</b>      | 1  | 2     | 3     | 4     | ... | 18 |
| <b>CPU cycles</b>     | 27 | 27    | 27    | 27    | ... | 27 |
| <i>Inputs</i>         |    |       |       |       |     |    |
| <b>In (DSP)</b>       | 0  | 32767 | 32767 | 32767 | ... | 0  |
| <b>In</b>             | 0  | 1     | 1     | 1.1   | ... | 0  |
| <i>Outputs</i>        |    |       |       |       |     |    |
| <b>Out</b>            | 0  | 1     | 1     | 1     | ... | 0  |
| <b>Exp. Out</b>       | 0  | 1     | 1     | 1     | ... | 0  |
| <b>Out (DSP)</b>      | 0  | 32767 | 32767 | 32767 | ... | 0  |
| <b>Exp. Out (DSP)</b> | 0  | 32767 | 32767 | 32767 | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 27 |
| Max CPU cycles  | 27 |
| Avg CPU cycles  | 27 |

**Verification: LoopBreaker FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block LoopBreaker.

| Test results          |    |       |       |       |     |    |
|-----------------------|----|-------|-------|-------|-----|----|
| <b>Time step</b>      | 1  | 2     | 3     | 4     | ... | 18 |
| <b>CPU cycles</b>     | 41 | 41    | 41    | 41    | ... | 41 |
| <i>Inputs</i>         |    |       |       |       |     |    |
| <b>In (DSP)</b>       | 0  | 32767 | 32767 | 32767 | ... | 0  |
| <b>In</b>             | 0  | 1     | 1     | 1.1   | ... | 0  |
| <i>Outputs</i>        |    |       |       |       |     |    |
| <b>Out</b>            | 0  | 1     | 1     | 1     | ... | 0  |
| <b>Exp. Out</b>       | 0  | 1     | 1     | 1     | ... | 0  |
| <b>Out (DSP)</b>      | 0  | 32767 | 32767 | 32767 | ... | 0  |
| <b>Exp. Out (DSP)</b> | 0  | 32767 | 32767 | 32767 | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 41 |
| Max CPU cycles  | 41 |
| Avg CPU cycles  | 41 |

**Verification: LoopBreaker FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block LoopBreaker.

| Test results          |    |       |       |       |     |    |
|-----------------------|----|-------|-------|-------|-----|----|
| <b>Time step</b>      | 1  | 2     | 3     | 4     | ... | 18 |
| <b>CPU cycles</b>     | 63 | 53    | 53    | 53    | ... | 53 |
| <i>Inputs</i>         |    |       |       |       |     |    |
| <b>In (DSP)</b>       | 0  | 32767 | 32767 | 32767 | ... | 0  |
| <b>In</b>             | 0  | 1     | 1     | 1.1   | ... | 0  |
| <i>Outputs</i>        |    |       |       |       |     |    |
| <b>Out</b>            | 0  | 1     | 1     | 1     | ... | 0  |
| <b>Exp. Out</b>       | 0  | 1     | 1     | 1     | ... | 0  |
| <b>Out (DSP)</b>      | 0  | 32767 | 32767 | 32767 | ... | 0  |
| <b>Exp. Out (DSP)</b> | 0  | 32767 | 32767 | 32767 | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 53 |
| Max CPU cycles  | 63 |
| Avg CPU cycles  | 53 |

**Verification: LoopBreaker FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block LoopBreaker.

| Test results          |    |       |       |       |     |    |
|-----------------------|----|-------|-------|-------|-----|----|
| <b>Time step</b>      | 1  | 2     | 3     | 4     | ... | 18 |
| <b>CPU cycles</b>     | 38 | 38    | 38    | 38    | ... | 38 |
| <i>Inputs</i>         |    |       |       |       |     |    |
| <b>In (DSP)</b>       | 0  | 32767 | 32767 | 32767 | ... | 0  |
| <b>In</b>             | 0  | 1     | 1     | 1.1   | ... | 0  |
| <i>Outputs</i>        |    |       |       |       |     |    |
| <b>Out</b>            | 0  | 1     | 1     | 1     | ... | 0  |
| <b>Exp. Out</b>       | 0  | 1     | 1     | 1     | ... | 0  |
| <b>Out (DSP)</b>      | 0  | 32767 | 32767 | 32767 | ... | 0  |
| <b>Exp. Out (DSP)</b> | 0  | 32767 | 32767 | 32767 | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 38 |
| Max CPU cycles  | 38 |
| Avg CPU cycles  | 38 |

**Verification: LoopBreaker FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block LoopBreaker.

| Test results          |    |            |     |    |
|-----------------------|----|------------|-----|----|
| <b>Time step</b>      | 1  | 2          | ... | 18 |
| <b>CPU cycles</b>     | 56 | 56         | ... | 56 |
| <i>Inputs</i>         |    |            |     |    |
| <b>In (DSP)</b>       | 0  | 2147483647 | ... | 0  |
| <b>In</b>             | 0  | 1          | ... | 0  |
| <i>Outputs</i>        |    |            |     |    |
| <b>Out</b>            | 0  | 1          | ... | 0  |
| <b>Exp. Out</b>       | 0  | 1          | ... | 0  |
| <b>Out (DSP)</b>      | 0  | 2147483647 | ... | 0  |
| <b>Exp. Out (DSP)</b> | 0  | 2147483647 | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 56 |
| Avg CPU cycles  | 56 |

## Verification: LoopBreaker FiP32 CPU TM4C123GH6

Date of Test 2026-06-19  
Target controller TM4C123GH6

### Test case: Inport test

OK

Inport test for General block LoopBreaker.

| Test results   |    |            |     |    |
|----------------|----|------------|-----|----|
| Time step      | 1  | 2          | ... | 18 |
| CPU cycles     | 23 | 23         | ... | 23 |
| Inputs         |    |            |     |    |
| In (DSP)       | 0  | 2147483647 | ... | 0  |
| In             | 0  | 1          | ... | 0  |
| Outputs        |    |            |     |    |
| Out            | 0  | 1          | ... | 0  |
| Exp. Out       | 0  | 1          | ... | 0  |
| Out (DSP)      | 0  | 2147483647 | ... | 0  |
| Exp. Out (DSP) | 0  | 2147483647 | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 23 |
| Max CPU cycles  | 23 |
| Avg CPU cycles  | 23 |

**Verification: LoopBreaker FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block LoopBreaker.

| Test results          |    |            |     |    |
|-----------------------|----|------------|-----|----|
| <b>Time step</b>      | 1  | 2          | ... | 18 |
| <b>CPU cycles</b>     | 52 | 52         | ... | 52 |
| <i>Inputs</i>         |    |            |     |    |
| <b>In (DSP)</b>       | 0  | 2147483647 | ... | 0  |
| <b>In</b>             | 0  | 1          | ... | 0  |
| <i>Outputs</i>        |    |            |     |    |
| <b>Out</b>            | 0  | 1          | ... | 0  |
| <b>Exp. Out</b>       | 0  | 1          | ... | 0  |
| <b>Out (DSP)</b>      | 0  | 2147483647 | ... | 0  |
| <b>Exp. Out (DSP)</b> | 0  | 2147483647 | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 52 |
| Max CPU cycles  | 52 |
| Avg CPU cycles  | 52 |

**Verification: LoopBreaker FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block LoopBreaker.

| Test results          |    |            |     |    |
|-----------------------|----|------------|-----|----|
| <b>Time step</b>      | 1  | 2          | ... | 18 |
| <b>CPU cycles</b>     | 45 | 45         | ... | 45 |
| <i>Inputs</i>         |    |            |     |    |
| <b>In (DSP)</b>       | 0  | 2147483647 | ... | 0  |
| <b>In</b>             | 0  | 1          | ... | 0  |
| <i>Outputs</i>        |    |            |     |    |
| <b>Out</b>            | 0  | 1          | ... | 0  |
| <b>Exp. Out</b>       | 0  | 1          | ... | 0  |
| <b>Out (DSP)</b>      | 0  | 2147483647 | ... | 0  |
| <b>Exp. Out (DSP)</b> | 0  | 2147483647 | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 45 |
| Max CPU cycles  | 45 |
| Avg CPU cycles  | 45 |



**Verification: LoopBreaker FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block LoopBreaker.

| Test results          |    |            |     |    |
|-----------------------|----|------------|-----|----|
| <b>Time step</b>      | 1  | 2          | ... | 18 |
| <b>CPU cycles</b>     | 27 | 27         | ... | 27 |
| <i>Inputs</i>         |    |            |     |    |
| <b>In (DSP)</b>       | 0  | 2147483647 | ... | 0  |
| <b>In</b>             | 0  | 1          | ... | 0  |
| <i>Outputs</i>        |    |            |     |    |
| <b>Out</b>            | 0  | 1          | ... | 0  |
| <b>Exp. Out</b>       | 0  | 1          | ... | 0  |
| <b>Out (DSP)</b>      | 0  | 2147483647 | ... | 0  |
| <b>Exp. Out (DSP)</b> | 0  | 2147483647 | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 27 |
| Max CPU cycles  | 27 |
| Avg CPU cycles  | 27 |

**Verification: LoopBreaker FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block LoopBreaker.

| Test results          |    |            |     |    |
|-----------------------|----|------------|-----|----|
| <b>Time step</b>      | 1  | 2          | ... | 18 |
| <b>CPU cycles</b>     | 43 | 43         | ... | 43 |
| <i>Inputs</i>         |    |            |     |    |
| <b>In (DSP)</b>       | 0  | 2147483647 | ... | 0  |
| <b>In</b>             | 0  | 1          | ... | 0  |
| <i>Outputs</i>        |    |            |     |    |
| <b>Out</b>            | 0  | 1          | ... | 0  |
| <b>Exp. Out</b>       | 0  | 1          | ... | 0  |
| <b>Out (DSP)</b>      | 0  | 2147483647 | ... | 0  |
| <b>Exp. Out (DSP)</b> | 0  | 2147483647 | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 43 |
| Max CPU cycles  | 43 |
| Avg CPU cycles  | 43 |

**Verification: LoopBreaker FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block LoopBreaker.

| Test results          |    |            |     |    |
|-----------------------|----|------------|-----|----|
| <b>Time step</b>      | 1  | 2          | ... | 18 |
| <b>CPU cycles</b>     | 53 | 53         | ... | 53 |
| <i>Inputs</i>         |    |            |     |    |
| <b>In (DSP)</b>       | 0  | 2147483647 | ... | 0  |
| <b>In</b>             | 0  | 1          | ... | 0  |
| <i>Outputs</i>        |    |            |     |    |
| <b>Out</b>            | 0  | 1          | ... | 0  |
| <b>Exp. Out</b>       | 0  | 1          | ... | 0  |
| <b>Out (DSP)</b>      | 0  | 2147483647 | ... | 0  |
| <b>Exp. Out (DSP)</b> | 0  | 2147483647 | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 53 |
| Max CPU cycles  | 53 |
| Avg CPU cycles  | 53 |

**Verification: LoopBreaker FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block LoopBreaker.

| Test results          |    |            |     |    |
|-----------------------|----|------------|-----|----|
| <b>Time step</b>      | 1  | 2          | ... | 18 |
| <b>CPU cycles</b>     | 36 | 36         | ... | 36 |
| <i>Inputs</i>         |    |            |     |    |
| <b>In (DSP)</b>       | 0  | 2147483647 | ... | 0  |
| <b>In</b>             | 0  | 1          | ... | 0  |
| <i>Outputs</i>        |    |            |     |    |
| <b>Out</b>            | 0  | 1          | ... | 0  |
| <b>Exp. Out</b>       | 0  | 1          | ... | 0  |
| <b>Out (DSP)</b>      | 0  | 2147483647 | ... | 0  |
| <b>Exp. Out (DSP)</b> | 0  | 2147483647 | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 36 |
| Max CPU cycles  | 36 |
| Avg CPU cycles  | 36 |

**Verification: LoopBreaker Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block LoopBreaker.

| Test results          |    |    |     |    |
|-----------------------|----|----|-----|----|
| <b>Time step</b>      | 1  | 2  | ... | 18 |
| <b>CPU cycles</b>     | 56 | 56 | ... | 56 |
| <i>Inputs</i>         |    |    |     |    |
| <b>In (DSP)</b>       | 0  | 1  | ... | 0  |
| <b>In</b>             | 0  | 1  | ... | 0  |
| <i>Outputs</i>        |    |    |     |    |
| <b>Out</b>            | 0  | 1  | ... | 0  |
| <b>Exp. Out</b>       | 0  | 1  | ... | 0  |
| <b>Out (DSP)</b>      | 0  | 1  | ... | 0  |
| <b>Exp. Out (DSP)</b> | 0  | 1  | ... | 0  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 56 |
| Avg CPU cycles  | 56 |

## Verification: LoopBreaker Float32 CPU TM4C123GH6

Date of Test 2026-06-19  
Target controller TM4C123GH6

### Test case: Inport test

OK

Inport test for General block LoopBreaker.

| Test results   |    |    |     |    |
|----------------|----|----|-----|----|
| Time step      | 1  | 2  | ... | 18 |
| CPU cycles     | 23 | 23 | ... | 23 |
| Inputs         |    |    |     |    |
| In (DSP)       | 0  | 1  | ... | 0  |
| In             | 0  | 1  | ... | 0  |
| Outputs        |    |    |     |    |
| Out            | 0  | 1  | ... | 0  |
| Exp. Out       | 0  | 1  | ... | 0  |
| Out (DSP)      | 0  | 1  | ... | 0  |
| Exp. Out (DSP) | 0  | 1  | ... | 0  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 23 |
| Max CPU cycles  | 23 |
| Avg CPU cycles  | 23 |

## Verification: LoopBreaker Float32 CPU STM32G474RE

Date of Test 2026-06-19  
Target controller STM32G474RE

### Test case: Inport test

OK

Inport test for General block LoopBreaker.

| Test results   |    |    |     |    |
|----------------|----|----|-----|----|
| Time step      | 1  | 2  | ... | 18 |
| CPU cycles     | 52 | 52 | ... | 52 |
| Inputs         |    |    |     |    |
| In (DSP)       | 0  | 1  | ... | 0  |
| In             | 0  | 1  | ... | 0  |
| Outputs        |    |    |     |    |
| Out            | 0  | 1  | ... | 0  |
| Exp. Out       | 0  | 1  | ... | 0  |
| Out (DSP)      | 0  | 1  | ... | 0  |
| Exp. Out (DSP) | 0  | 1  | ... | 0  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 52 |
| Max CPU cycles  | 52 |
| Avg CPU cycles  | 52 |

**Verification: LoopBreaker Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block LoopBreaker.

| Test results          |    |    |     |    |
|-----------------------|----|----|-----|----|
| <b>Time step</b>      | 1  | 2  | ... | 18 |
| <b>CPU cycles</b>     | 45 | 45 | ... | 45 |
| <i>Inputs</i>         |    |    |     |    |
| <b>In (DSP)</b>       | 0  | 1  | ... | 0  |
| <b>In</b>             | 0  | 1  | ... | 0  |
| <i>Outputs</i>        |    |    |     |    |
| <b>Out</b>            | 0  | 1  | ... | 0  |
| <b>Exp. Out</b>       | 0  | 1  | ... | 0  |
| <b>Out (DSP)</b>      | 0  | 1  | ... | 0  |
| <b>Exp. Out (DSP)</b> | 0  | 1  | ... | 0  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 45 |
| Max CPU cycles  | 45 |
| Avg CPU cycles  | 45 |



**Verification: LoopBreaker Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block LoopBreaker.

| Test results   |    |    |     |    |
|----------------|----|----|-----|----|
| Time step      | 1  | 2  | ... | 18 |
| CPU cycles     | 27 | 27 | ... | 27 |
| Inputs         |    |    |     |    |
| In (DSP)       | 0  | 1  | ... | 0  |
| In             | 0  | 1  | ... | 0  |
| Outputs        |    |    |     |    |
| Out            | 0  | 1  | ... | 0  |
| Exp. Out       | 0  | 1  | ... | 0  |
| Out (DSP)      | 0  | 1  | ... | 0  |
| Exp. Out (DSP) | 0  | 1  | ... | 0  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 27 |
| Max CPU cycles  | 27 |
| Avg CPU cycles  | 27 |

**Verification: LoopBreaker Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block LoopBreaker.

| Test results          |    |    |     |    |
|-----------------------|----|----|-----|----|
| <b>Time step</b>      | 1  | 2  | ... | 18 |
| <b>CPU cycles</b>     | 43 | 43 | ... | 43 |
| <i>Inputs</i>         |    |    |     |    |
| <b>In (DSP)</b>       | 0  | 1  | ... | 0  |
| <b>In</b>             | 0  | 1  | ... | 0  |
| <i>Outputs</i>        |    |    |     |    |
| <b>Out</b>            | 0  | 1  | ... | 0  |
| <b>Exp. Out</b>       | 0  | 1  | ... | 0  |
| <b>Out (DSP)</b>      | 0  | 1  | ... | 0  |
| <b>Exp. Out (DSP)</b> | 0  | 1  | ... | 0  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 43 |
| Max CPU cycles  | 43 |
| Avg CPU cycles  | 43 |

**Verification: LoopBreaker Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block LoopBreaker.

| Test results          |    |    |     |    |
|-----------------------|----|----|-----|----|
| <b>Time step</b>      | 1  | 2  | ... | 18 |
| <b>CPU cycles</b>     | 53 | 53 | ... | 53 |
| <i>Inputs</i>         |    |    |     |    |
| <b>In (DSP)</b>       | 0  | 1  | ... | 0  |
| <b>In</b>             | 0  | 1  | ... | 0  |
| <i>Outputs</i>        |    |    |     |    |
| <b>Out</b>            | 0  | 1  | ... | 0  |
| <b>Exp. Out</b>       | 0  | 1  | ... | 0  |
| <b>Out (DSP)</b>      | 0  | 1  | ... | 0  |
| <b>Exp. Out (DSP)</b> | 0  | 1  | ... | 0  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 53 |
| Max CPU cycles  | 53 |
| Avg CPU cycles  | 53 |

**Verification: LoopBreaker Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block LoopBreaker.

| Test results   |    |    |     |    |
|----------------|----|----|-----|----|
| Time step      | 1  | 2  | ... | 18 |
| CPU cycles     | 38 | 38 | ... | 38 |
| Inputs         |    |    |     |    |
| In (DSP)       | 0  | 1  | ... | 0  |
| In             | 0  | 1  | ... | 0  |
| Outputs        |    |    |     |    |
| Out            | 0  | 1  | ... | 0  |
| Exp. Out       | 0  | 1  | ... | 0  |
| Out (DSP)      | 0  | 1  | ... | 0  |
| Exp. Out (DSP) | 0  | 1  | ... | 0  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 38 |
| Max CPU cycles  | 38 |
| Avg CPU cycles  | 38 |

## Block: ManualSwitch

---



Toggling between inputs by double-clicking on block.

| Inports |          |
|---------|----------|
| In1     | Input #1 |
| In2     | Input #2 |

| Outputs |  |
|---------|--|
| Out     |  |

| Mask Parameters |    |             |
|-----------------|----|-------------|
| Name            | ID | Description |
| Toggle          | 1  | Toggle      |

### Description:

Doubleclicking of the *ManualSwitch* block changes the routing of the input signals and doesn't open the *Function Block Parameters* dialog. So if changing the implementation is required, one has to open the dialog via *Mask Parameters* command of the context menu.

**Developer note:** To get the double-click feature the callback function of *OpenFnc* in *Block Properties* is manually altered to

```
if get_param(gcb, 'Toggle') == '0'
    set_param(gcb, 'Toggle', '1');
else
    set_param(gcb, 'Toggle', '0');
end
setBlockData(gcs, gcb);
initSFunction(gcb);
```

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>Bool</b>    | Boolean Implementation               |
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: Bool

Boolean Implementation

| Inports Data Type |      |
|-------------------|------|
| In1               | bool |
| In2               | bool |

| Outports Data Type |      |
|--------------------|------|
| Out                | bool |

### Implementation: FiP8

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In1               | int8 |
| In2               | int8 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In1               | int16 |
| In2               | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In1               | int32 |
| In2               | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In1               | float32 |
| In2               | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In1               | float64 |
| In2               | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: ManualSwitch Bool CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |     |     |     |     |     |     |
|----------------|-----|-----|-----|-----|-----|-----|
| Time step      | 1   | 2   | 3   | 4   | ... | 7   |
| CPU cycles     | 56  | 56  | 56  | 56  | ... | 56  |
| Inputs         |     |     |     |     |     |     |
| In1 (DSP)      | 0   | 0   | 0   | 0   | ... | 1   |
| In2 (DSP)      | 0   | 0   | 0   | 0   | ... | 1   |
| In1            | 0   | 0.1 | 0.2 | 0.3 | ... | 1.1 |
| In2            | 0.1 | 0.2 | 0.3 | 0.4 | ... | 1.2 |
| Parameters     |     |     |     |     |     |     |
| Toggle         | 0   |     |     |     |     |     |
| Outputs        |     |     |     |     |     |     |
| Out            | 0   | 0   | 0   | 0   | ... | 1   |
| Exp. Out       | 0   | 0   | 0   | 0   | ... | 1   |
| Out (DSP)      | 0   | 0   | 0   | 0   | ... | 1   |
| Exp. Out (DSP) | 0   | 0   | 0   | 0   | ... | 1   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 56 |
| Avg CPU cycles  | 56 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.



| Test results   |    |     |    |    |     |  |    |
|----------------|----|-----|----|----|-----|--|----|
| Time step      | 1  | 2   | 3  | 4  | ... |  | 10 |
| CPU cycles     | 56 | 56  | 56 | 56 | ... |  | 56 |
| Inputs         |    |     |    |    |     |  |    |
| In1 (DSP)      | 1  |     |    |    |     |  |    |
| In2 (DSP)      | 0  |     |    |    |     |  |    |
| In1            | 1  |     |    |    |     |  |    |
| In2            | 0  |     |    |    |     |  |    |
| Parameters     |    |     |    |    |     |  |    |
| Toggle         | 0  | 0.1 | 1  | 2  | ... |  | -3 |
| Outputs        |    |     |    |    |     |  |    |
| Out            | 1  | 0   | 0  | 0  | ... |  | 0  |
| Exp. Out       | 1  | 0   | 0  | 0  | ... |  | 0  |
| Out (DSP)      | 1  | 0   | 0  | 0  | ... |  | 0  |
| Exp. Out (DSP) | 1  | 0   | 0  | 0  | ... |  | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 56 |
| Avg CPU cycles  | 56 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results          |   |     |   |   |     |  |    |
|-----------------------|---|-----|---|---|-----|--|----|
| Time step             | 1 | 2   | 3 | 4 | ... |  | 10 |
| Mask parameters       |   |     |   |   |     |  |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... |  | -3 |
| Controller parameters |   |     |   |   |     |  |    |
| Toggle                | 0 | 1   | 1 | 1 | ... |  | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... |  | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 793 |
| Max CPU cycles  | 834 |
| Avg CPU cycles  | 825 |

**Verification: ManualSwitch Bool CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |     |     |     |     |     |     |
|----------------|-----|-----|-----|-----|-----|-----|
| Time step      | 1   | 2   | 3   | 4   | ... | 7   |
| CPU cycles     | 23  | 23  | 23  | 23  | ... | 23  |
| Inputs         |     |     |     |     |     |     |
| In1 (DSP)      | 0   | 0   | 0   | 0   | ... | 1   |
| In2 (DSP)      | 0   | 0   | 0   | 0   | ... | 1   |
| In1            | 0   | 0.1 | 0.2 | 0.3 | ... | 1.1 |
| In2            | 0.1 | 0.2 | 0.3 | 0.4 | ... | 1.2 |
| Parameters     |     |     |     |     |     |     |
| Toggle         | 0   |     |     |     |     |     |
| Outputs        |     |     |     |     |     |     |
| Out            | 0   | 0   | 0   | 0   | ... | 1   |
| Exp. Out       | 0   | 0   | 0   | 0   | ... | 1   |
| Out (DSP)      | 0   | 0   | 0   | 0   | ... | 1   |
| Exp. Out (DSP) | 0   | 0   | 0   | 0   | ... | 1   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 23 |
| Max CPU cycles  | 23 |
| Avg CPU cycles  | 23 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.

| Test results   |    |     |    |    |     |  |    |
|----------------|----|-----|----|----|-----|--|----|
| Time step      | 1  | 2   | 3  | 4  | ... |  | 10 |
| CPU cycles     | 23 | 23  | 23 | 23 | ... |  | 23 |
| Inputs         |    |     |    |    |     |  |    |
| In1 (DSP)      | 1  |     |    |    |     |  |    |
| In2 (DSP)      | 0  |     |    |    |     |  |    |
| In1            | 1  |     |    |    |     |  |    |
| In2            | 0  |     |    |    |     |  |    |
| Parameters     |    |     |    |    |     |  |    |
| Toggle         | 0  | 0.1 | 1  | 2  | ... |  | -3 |
| Outputs        |    |     |    |    |     |  |    |
| Out            | 1  | 0   | 0  | 0  | ... |  | 0  |
| Exp. Out       | 1  | 0   | 0  | 0  | ... |  | 0  |
| Out (DSP)      | 1  | 0   | 0  | 0  | ... |  | 0  |
| Exp. Out (DSP) | 1  | 0   | 0  | 0  | ... |  | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 23 |
| Max CPU cycles  | 23 |
| Avg CPU cycles  | 23 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results          |   |     |   |   |     |  |    |
|-----------------------|---|-----|---|---|-----|--|----|
| <b>Time step</b>      | 1 | 2   | 3 | 4 | ... |  | 10 |
| Mask parameters       |   |     |   |   |     |  |    |
| <b>Toggle</b>         | 0 | 0.1 | 1 | 2 | ... |  | -3 |
| Controller parameters |   |     |   |   |     |  |    |
| <b>Toggle</b>         | 0 | 1   | 1 | 1 | ... |  | 1  |
| <b>Exp. Toggle</b>    | 0 | 1   | 1 | 1 | ... |  | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 375 |
| Max CPU cycles  | 399 |
| Avg CPU cycles  | 393 |

**Verification: ManualSwitch Bool CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |     |     |     |     |     |     |
|----------------|-----|-----|-----|-----|-----|-----|
| Time step      | 1   | 2   | 3   | 4   | ... | 7   |
| CPU cycles     | 52  | 52  | 52  | 52  | ... | 52  |
| Inputs         |     |     |     |     |     |     |
| In1 (DSP)      | 0   | 0   | 0   | 0   | ... | 1   |
| In2 (DSP)      | 0   | 0   | 0   | 0   | ... | 1   |
| In1            | 0   | 0.1 | 0.2 | 0.3 | ... | 1.1 |
| In2            | 0.1 | 0.2 | 0.3 | 0.4 | ... | 1.2 |
| Parameters     |     |     |     |     |     |     |
| Toggle         | 0   |     |     |     |     |     |
| Outputs        |     |     |     |     |     |     |
| Out            | 0   | 0   | 0   | 0   | ... | 1   |
| Exp. Out       | 0   | 0   | 0   | 0   | ... | 1   |
| Out (DSP)      | 0   | 0   | 0   | 0   | ... | 1   |
| Exp. Out (DSP) | 0   | 0   | 0   | 0   | ... | 1   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 52 |
| Max CPU cycles  | 52 |
| Avg CPU cycles  | 52 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.

| Test results   |    |     |    |    |     |  |     |
|----------------|----|-----|----|----|-----|--|-----|
| Time step      | 1  | 2   | 3  | 4  | ... |  | 10  |
| CPU cycles     | 52 | 52  | 52 | 52 | ... |  | 111 |
| Inputs         |    |     |    |    |     |  |     |
| In1 (DSP)      | 1  |     |    |    |     |  |     |
| In2 (DSP)      | 0  |     |    |    |     |  |     |
| In1            | 1  |     |    |    |     |  |     |
| In2            | 0  |     |    |    |     |  |     |
| Parameters     |    |     |    |    |     |  |     |
| Toggle         | 0  | 0.1 | 1  | 2  | ... |  | -3  |
| Outputs        |    |     |    |    |     |  |     |
| Out            | 1  | 0   | 0  | 0  | ... |  | 0   |
| Exp. Out       | 1  | 0   | 0  | 0  | ... |  | 0   |
| Out (DSP)      | 1  | 0   | 0  | 0  | ... |  | 0   |
| Exp. Out (DSP) | 1  | 0   | 0  | 0  | ... |  | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 0$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 52  |
| Max CPU cycles  | 111 |
| Avg CPU cycles  | 57  |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results          |   |     |   |   |     |  |    |
|-----------------------|---|-----|---|---|-----|--|----|
| <b>Time step</b>      | 1 | 2   | 3 | 4 | ... |  | 10 |
| Mask parameters       |   |     |   |   |     |  |    |
| <b>Toggle</b>         | 0 | 0.1 | 1 | 2 | ... |  | -3 |
| Controller parameters |   |     |   |   |     |  |    |
| <b>Toggle</b>         | 0 | 1   | 1 | 1 | ... |  | 1  |
| <b>Exp. Toggle</b>    | 0 | 1   | 1 | 1 | ... |  | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 516 |
| Max CPU cycles  | 541 |
| Avg CPU cycles  | 536 |



**Verification: ManualSwitch Bool CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |     |     |     |     |     |     |
|----------------|-----|-----|-----|-----|-----|-----|
| Time step      | 1   | 2   | 3   | 4   | ... | 7   |
| CPU cycles     | 45  | 45  | 45  | 45  | ... | 45  |
| Inputs         |     |     |     |     |     |     |
| In1 (DSP)      | 0   | 0   | 0   | 0   | ... | 1   |
| In2 (DSP)      | 0   | 0   | 0   | 0   | ... | 1   |
| In1            | 0   | 0.1 | 0.2 | 0.3 | ... | 1.1 |
| In2            | 0.1 | 0.2 | 0.3 | 0.4 | ... | 1.2 |
| Parameters     |     |     |     |     |     |     |
| Toggle         | 0   |     |     |     |     |     |
| Outputs        |     |     |     |     |     |     |
| Out            | 0   | 0   | 0   | 0   | ... | 1   |
| Exp. Out       | 0   | 0   | 0   | 0   | ... | 1   |
| Out (DSP)      | 0   | 0   | 0   | 0   | ... | 1   |
| Exp. Out (DSP) | 0   | 0   | 0   | 0   | ... | 1   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 45 |
| Max CPU cycles  | 45 |
| Avg CPU cycles  | 45 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.

| Test results   |    |     |    |    |     |  |    |
|----------------|----|-----|----|----|-----|--|----|
| Time step      | 1  | 2   | 3  | 4  | ... |  | 10 |
| CPU cycles     | 45 | 45  | 45 | 45 | ... |  | 45 |
| Inputs         |    |     |    |    |     |  |    |
| In1 (DSP)      | 1  |     |    |    |     |  |    |
| In2 (DSP)      | 0  |     |    |    |     |  |    |
| In1            | 1  |     |    |    |     |  |    |
| In2            | 0  |     |    |    |     |  |    |
| Parameters     |    |     |    |    |     |  |    |
| Toggle         | 0  | 0.1 | 1  | 2  | ... |  | -3 |
| Outputs        |    |     |    |    |     |  |    |
| Out            | 1  | 0   | 0  | 0  | ... |  | 0  |
| Exp. Out       | 1  | 0   | 0  | 0  | ... |  | 0  |
| Out (DSP)      | 1  | 0   | 0  | 0  | ... |  | 0  |
| Exp. Out (DSP) | 1  | 0   | 0  | 0  | ... |  | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 45 |
| Max CPU cycles  | 45 |
| Avg CPU cycles  | 45 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results          |   |     |   |   |     |  |    |
|-----------------------|---|-----|---|---|-----|--|----|
| <b>Time step</b>      | 1 | 2   | 3 | 4 | ... |  | 10 |
| Mask parameters       |   |     |   |   |     |  |    |
| <b>Toggle</b>         | 0 | 0.1 | 1 | 2 | ... |  | -3 |
| Controller parameters |   |     |   |   |     |  |    |
| <b>Toggle</b>         | 0 | 1   | 1 | 1 | ... |  | 1  |
| <b>Exp. Toggle</b>    | 0 | 1   | 1 | 1 | ... |  | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 602 |
| Max CPU cycles  | 612 |
| Avg CPU cycles  | 604 |

**Verification: ManualSwitch Bool CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |     |     |     |     |     |     |
|----------------|-----|-----|-----|-----|-----|-----|
| Time step      | 1   | 2   | 3   | 4   | ... | 7   |
| CPU cycles     | 27  | 27  | 27  | 27  | ... | 27  |
| Inputs         |     |     |     |     |     |     |
| In1 (DSP)      | 0   | 0   | 0   | 0   | ... | 1   |
| In2 (DSP)      | 0   | 0   | 0   | 0   | ... | 1   |
| In1            | 0   | 0.1 | 0.2 | 0.3 | ... | 1.1 |
| In2            | 0.1 | 0.2 | 0.3 | 0.4 | ... | 1.2 |
| Parameters     |     |     |     |     |     |     |
| Toggle         | 0   |     |     |     |     |     |
| Outputs        |     |     |     |     |     |     |
| Out            | 0   | 0   | 0   | 0   | ... | 1   |
| Exp. Out       | 0   | 0   | 0   | 0   | ... | 1   |
| Out (DSP)      | 0   | 0   | 0   | 0   | ... | 1   |
| Exp. Out (DSP) | 0   | 0   | 0   | 0   | ... | 1   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 27 |
| Max CPU cycles  | 27 |
| Avg CPU cycles  | 27 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.

| Test results   |    |     |    |    |     |  |    |
|----------------|----|-----|----|----|-----|--|----|
| Time step      | 1  | 2   | 3  | 4  | ... |  | 10 |
| CPU cycles     | 27 | 27  | 27 | 27 | ... |  | 27 |
| Inputs         |    |     |    |    |     |  |    |
| In1 (DSP)      | 1  |     |    |    |     |  |    |
| In2 (DSP)      | 0  |     |    |    |     |  |    |
| In1            | 1  |     |    |    |     |  |    |
| In2            | 0  |     |    |    |     |  |    |
| Parameters     |    |     |    |    |     |  |    |
| Toggle         | 0  | 0.1 | 1  | 2  | ... |  | -3 |
| Outputs        |    |     |    |    |     |  |    |
| Out            | 1  | 0   | 0  | 0  | ... |  | 0  |
| Exp. Out       | 1  | 0   | 0  | 0  | ... |  | 0  |
| Out (DSP)      | 1  | 0   | 0  | 0  | ... |  | 0  |
| Exp. Out (DSP) | 1  | 0   | 0  | 0  | ... |  | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 27 |
| Max CPU cycles  | 27 |
| Avg CPU cycles  | 27 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results          |   |     |   |   |     |  |    |
|-----------------------|---|-----|---|---|-----|--|----|
| <b>Time step</b>      | 1 | 2   | 3 | 4 | ... |  | 10 |
| Mask parameters       |   |     |   |   |     |  |    |
| <b>Toggle</b>         | 0 | 0.1 | 1 | 2 | ... |  | -3 |
| Controller parameters |   |     |   |   |     |  |    |
| <b>Toggle</b>         | 0 | 1   | 1 | 1 | ... |  | 1  |
| <b>Exp. Toggle</b>    | 0 | 1   | 1 | 1 | ... |  | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 245 |
| Max CPU cycles  | 279 |
| Avg CPU cycles  | 266 |

**Verification: ManualSwitch Bool CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |     |     |     |     |     |     |
|----------------|-----|-----|-----|-----|-----|-----|
| Time step      | 1   | 2   | 3   | 4   | ... | 7   |
| CPU cycles     | 41  | 41  | 41  | 41  | ... | 41  |
| Inputs         |     |     |     |     |     |     |
| In1 (DSP)      | 0   | 0   | 0   | 0   | ... | 1   |
| In2 (DSP)      | 0   | 0   | 0   | 0   | ... | 1   |
| In1            | 0   | 0.1 | 0.2 | 0.3 | ... | 1.1 |
| In2            | 0.1 | 0.2 | 0.3 | 0.4 | ... | 1.2 |
| Parameters     |     |     |     |     |     |     |
| Toggle         | 0   |     |     |     |     |     |
| Outputs        |     |     |     |     |     |     |
| Out            | 0   | 0   | 0   | 0   | ... | 1   |
| Exp. Out       | 0   | 0   | 0   | 0   | ... | 1   |
| Out (DSP)      | 0   | 0   | 0   | 0   | ... | 1   |
| Exp. Out (DSP) | 0   | 0   | 0   | 0   | ... | 1   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 41 |
| Max CPU cycles  | 41 |
| Avg CPU cycles  | 41 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.

| Test results   |    |     |    |    |     |  |    |
|----------------|----|-----|----|----|-----|--|----|
| Time step      | 1  | 2   | 3  | 4  | ... |  | 10 |
| CPU cycles     | 41 | 41  | 41 | 41 | ... |  | 41 |
| Inputs         |    |     |    |    |     |  |    |
| In1 (DSP)      | 1  |     |    |    |     |  |    |
| In2 (DSP)      | 0  |     |    |    |     |  |    |
| In1            | 1  |     |    |    |     |  |    |
| In2            | 0  |     |    |    |     |  |    |
| Parameters     |    |     |    |    |     |  |    |
| Toggle         | 0  | 0.1 | 1  | 2  | ... |  | -3 |
| Outputs        |    |     |    |    |     |  |    |
| Out            | 1  | 0   | 0  | 0  | ... |  | 0  |
| Exp. Out       | 1  | 0   | 0  | 0  | ... |  | 0  |
| Out (DSP)      | 1  | 0   | 0  | 0  | ... |  | 0  |
| Exp. Out (DSP) | 1  | 0   | 0  | 0  | ... |  | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 41 |
| Max CPU cycles  | 41 |
| Avg CPU cycles  | 41 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results          |   |     |   |   |     |  |    |
|-----------------------|---|-----|---|---|-----|--|----|
| <b>Time step</b>      | 1 | 2   | 3 | 4 | ... |  | 10 |
| Mask parameters       |   |     |   |   |     |  |    |
| <b>Toggle</b>         | 0 | 0.1 | 1 | 2 | ... |  | -3 |
| Controller parameters |   |     |   |   |     |  |    |
| <b>Toggle</b>         | 0 | 1   | 1 | 1 | ... |  | 1  |
| <b>Exp. Toggle</b>    | 0 | 1   | 1 | 1 | ... |  | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |



**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 520 |
| Max CPU cycles  | 546 |
| Avg CPU cycles  | 527 |

**Verification: ManualSwitch Bool CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |     |     |     |     |     |     |
|----------------|-----|-----|-----|-----|-----|-----|
| Time step      | 1   | 2   | 3   | 4   | ... | 7   |
| CPU cycles     | 53  | 53  | 53  | 53  | ... | 53  |
| Inputs         |     |     |     |     |     |     |
| In1 (DSP)      | 0   | 0   | 0   | 0   | ... | 1   |
| In2 (DSP)      | 0   | 0   | 0   | 0   | ... | 1   |
| In1            | 0   | 0.1 | 0.2 | 0.3 | ... | 1.1 |
| In2            | 0.1 | 0.2 | 0.3 | 0.4 | ... | 1.2 |
| Parameters     |     |     |     |     |     |     |
| Toggle         | 0   |     |     |     |     |     |
| Outputs        |     |     |     |     |     |     |
| Out            | 0   | 0   | 0   | 0   | ... | 1   |
| Exp. Out       | 0   | 0   | 0   | 0   | ... | 1   |
| Out (DSP)      | 0   | 0   | 0   | 0   | ... | 1   |
| Exp. Out (DSP) | 0   | 0   | 0   | 0   | ... | 1   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 53 |
| Max CPU cycles  | 53 |
| Avg CPU cycles  | 53 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.

| Test results   |    |     |    |    |     |  |    |
|----------------|----|-----|----|----|-----|--|----|
| Time step      | 1  | 2   | 3  | 4  | ... |  | 10 |
| CPU cycles     | 53 | 53  | 53 | 53 | ... |  | 53 |
| Inputs         |    |     |    |    |     |  |    |
| In1 (DSP)      | 1  |     |    |    |     |  |    |
| In2 (DSP)      | 0  |     |    |    |     |  |    |
| In1            | 1  |     |    |    |     |  |    |
| In2            | 0  |     |    |    |     |  |    |
| Parameters     |    |     |    |    |     |  |    |
| Toggle         | 0  | 0.1 | 1  | 2  | ... |  | -3 |
| Outputs        |    |     |    |    |     |  |    |
| Out            | 1  | 0   | 0  | 0  | ... |  | 0  |
| Exp. Out       | 1  | 0   | 0  | 0  | ... |  | 0  |
| Out (DSP)      | 1  | 0   | 0  | 0  | ... |  | 0  |
| Exp. Out (DSP) | 1  | 0   | 0  | 0  | ... |  | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 53 |
| Max CPU cycles  | 53 |
| Avg CPU cycles  | 53 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results          |   |     |   |   |     |  |    |
|-----------------------|---|-----|---|---|-----|--|----|
| Time step             | 1 | 2   | 3 | 4 | ... |  | 10 |
| Mask parameters       |   |     |   |   |     |  |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... |  | -3 |
| Controller parameters |   |     |   |   |     |  |    |
| Toggle                | 0 | 1   | 1 | 1 | ... |  | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... |  | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 476 |
| Max CPU cycles  | 516 |
| Avg CPU cycles  | 484 |

**Verification: ManualSwitch Bool CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |     |     |     |     |     |     |
|----------------|-----|-----|-----|-----|-----|-----|
| Time step      | 1   | 2   | 3   | 4   | ... | 7   |
| CPU cycles     | 36  | 36  | 36  | 36  | ... | 36  |
| Inputs         |     |     |     |     |     |     |
| In1 (DSP)      | 0   | 0   | 0   | 0   | ... | 1   |
| In2 (DSP)      | 0   | 0   | 0   | 0   | ... | 1   |
| In1            | 0   | 0.1 | 0.2 | 0.3 | ... | 1.1 |
| In2            | 0.1 | 0.2 | 0.3 | 0.4 | ... | 1.2 |
| Parameters     |     |     |     |     |     |     |
| Toggle         | 0   |     |     |     |     |     |
| Outputs        |     |     |     |     |     |     |
| Out            | 0   | 0   | 0   | 0   | ... | 1   |
| Exp. Out       | 0   | 0   | 0   | 0   | ... | 1   |
| Out (DSP)      | 0   | 0   | 0   | 0   | ... | 1   |
| Exp. Out (DSP) | 0   | 0   | 0   | 0   | ... | 1   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 36 |
| Max CPU cycles  | 36 |
| Avg CPU cycles  | 36 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.

| Test results   |    |     |    |    |     |  |    |
|----------------|----|-----|----|----|-----|--|----|
| Time step      | 1  | 2   | 3  | 4  | ... |  | 10 |
| CPU cycles     | 36 | 36  | 36 | 36 | ... |  | 36 |
| Inputs         |    |     |    |    |     |  |    |
| In1 (DSP)      | 1  |     |    |    |     |  |    |
| In2 (DSP)      | 0  |     |    |    |     |  |    |
| In1            | 1  |     |    |    |     |  |    |
| In2            | 0  |     |    |    |     |  |    |
| Parameters     |    |     |    |    |     |  |    |
| Toggle         | 0  | 0.1 | 1  | 2  | ... |  | -3 |
| Outputs        |    |     |    |    |     |  |    |
| Out            | 1  | 0   | 0  | 0  | ... |  | 0  |
| Exp. Out       | 1  | 0   | 0  | 0  | ... |  | 0  |
| Out (DSP)      | 1  | 0   | 0  | 0  | ... |  | 0  |
| Exp. Out (DSP) | 1  | 0   | 0  | 0  | ... |  | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 36 |
| Max CPU cycles  | 36 |
| Avg CPU cycles  | 36 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results          |   |     |   |   |     |  |    |
|-----------------------|---|-----|---|---|-----|--|----|
| <b>Time step</b>      | 1 | 2   | 3 | 4 | ... |  | 10 |
| Mask parameters       |   |     |   |   |     |  |    |
| <b>Toggle</b>         | 0 | 0.1 | 1 | 2 | ... |  | -3 |
| Controller parameters |   |     |   |   |     |  |    |
| <b>Toggle</b>         | 0 | 1   | 1 | 1 | ... |  | 1  |
| <b>Exp. Toggle</b>    | 0 | 1   | 1 | 1 | ... |  | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |  |    |
|-----------------------|---|-----|---|---|-----|--|----|
| Time step             | 1 | 2   | 3 | 4 | ... |  | 10 |
| Mask parameters       |   |     |   |   |     |  |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... |  | -3 |
| Controller parameters |   |     |   |   |     |  |    |
| Toggle                | 0 | 1   | 1 | 1 | ... |  | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... |  | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 614 |
| Max CPU cycles  | 648 |
| Avg CPU cycles  | 641 |

**Verification: ManualSwitch FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |      |      |      |       |       |
|----------------|------|------|------|-------|-------|
| Time step      | 1    | 2    | 3    | 4     | 5     |
| CPU cycles     | 56   | 56   | 56   | 56    | 56    |
| Inputs         |      |      |      |       |       |
| In1 (DSP)      | 0    | 3277 | 6554 | 9830  | 13107 |
| In2 (DSP)      | 3277 | 6554 | 9830 | 13107 | 16384 |
| In1            | 0    | 0.1  | 0.2  | 0.3   | 0.4   |
| In2            | 0.1  | 0.2  | 0.3  | 0.4   | 0.5   |
| Parameters     |      |      |      |       |       |
| Toggle         |      |      |      |       |       |
| Outputs        |      |      |      |       |       |
| Out            | 0    | 0.1  | 0.2  | 0.3   | 0.4   |
| Exp. Out       | 0    | 0.1  | 0.2  | 0.3   | 0.4   |
| Out (DSP)      | 0    | 3277 | 6554 | 9830  | 13107 |
| Exp. Out (DSP) | 0    | 3277 | 6554 | 9830  | 13107 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 56 |
| Avg CPU cycles  | 56 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.



| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 10    |
| CPU cycles     | 56    | 56    | 56    | 56    | ... | 56    |
| Inputs         |       |       |       |       |     |       |
| In1 (DSP)      | 9830  |       |       |       |     |       |
| In2 (DSP)      | 19661 |       |       |       |     |       |
| In1            | 0.3   |       |       |       |     |       |
| In2            | 0.6   |       |       |       |     |       |
| Parameters     |       |       |       |       |     |       |
| Toggle         | 0     | 0.1   | 1     | 2     | ... | -3    |
| Outputs        |       |       |       |       |     |       |
| Out            | 0.3   | 0.6   | 0.6   | 0.6   | ... | 0.6   |
| Exp. Out       | 0.3   | 0.6   | 0.6   | 0.6   | ... | 0.6   |
| Out (DSP)      | 9830  | 19661 | 19661 | 19661 | ... | 19661 |
| Exp. Out (DSP) | 9830  | 19661 | 19661 | 19661 | ... | 19661 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 56 |
| Avg CPU cycles  | 56 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results                 |   |     |   |   |     |    |
|------------------------------|---|-----|---|---|-----|----|
| <b>Time step</b>             | 1 | 2   | 3 | 4 | ... | 10 |
| <i>Mask parameters</i>       |   |     |   |   |     |    |
| <b>Toggle</b>                | 0 | 0.1 | 1 | 2 | ... | -3 |
| <i>Controller parameters</i> |   |     |   |   |     |    |
| <b>Toggle</b>                | 0 | 1   | 1 | 1 | ... | 1  |
| <b>Exp. Toggle</b>           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 778 |
| Max CPU cycles  | 815 |
| Avg CPU cycles  | 807 |

**Verification: ManualSwitch FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |      |      |      |       |       |
|----------------|------|------|------|-------|-------|
| Time step      | 1    | 2    | 3    | 4     | 5     |
| CPU cycles     | 23   | 23   | 23   | 23    | 23    |
| Inputs         |      |      |      |       |       |
| In1 (DSP)      | 0    | 3277 | 6554 | 9830  | 13107 |
| In2 (DSP)      | 3277 | 6554 | 9830 | 13107 | 16384 |
| In1            | 0    | 0.1  | 0.2  | 0.3   | 0.4   |
| In2            | 0.1  | 0.2  | 0.3  | 0.4   | 0.5   |
| Parameters     |      |      |      |       |       |
| Toggle         |      |      |      |       |       |
| Outputs        |      |      |      |       |       |
| Out            | 0    | 0.1  | 0.2  | 0.3   | 0.4   |
| Exp. Out       | 0    | 0.1  | 0.2  | 0.3   | 0.4   |
| Out (DSP)      | 0    | 3277 | 6554 | 9830  | 13107 |
| Exp. Out (DSP) | 0    | 3277 | 6554 | 9830  | 13107 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 23 |
| Max CPU cycles  | 23 |
| Avg CPU cycles  | 23 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 10    |
| CPU cycles     | 23    | 23    | 23    | 23    | ... | 23    |
| Inputs         |       |       |       |       |     |       |
| In1 (DSP)      | 9830  |       |       |       |     |       |
| In2 (DSP)      | 19661 |       |       |       |     |       |
| In1            | 0.3   |       |       |       |     |       |
| In2            | 0.6   |       |       |       |     |       |
| Parameters     |       |       |       |       |     |       |
| Toggle         | 0     | 0.1   | 1     | 2     | ... | -3    |
| Outputs        |       |       |       |       |     |       |
| Out            | 0.3   | 0.6   | 0.6   | 0.6   | ... | 0.6   |
| Exp. Out       | 0.3   | 0.6   | 0.6   | 0.6   | ... | 0.6   |
| Out (DSP)      | 9830  | 19661 | 19661 | 19661 | ... | 19661 |
| Exp. Out (DSP) | 9830  | 19661 | 19661 | 19661 | ... | 19661 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 23 |
| Max CPU cycles  | 23 |
| Avg CPU cycles  | 23 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 375 |
| Max CPU cycles  | 399 |
| Avg CPU cycles  | 393 |

**Verification: ManualSwitch FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |      |      |      |       |       |
|----------------|------|------|------|-------|-------|
| Time step      | 1    | 2    | 3    | 4     | 5     |
| CPU cycles     | 57   | 57   | 57   | 57    | 57    |
| Inputs         |      |      |      |       |       |
| In1 (DSP)      | 0    | 3277 | 6554 | 9830  | 13107 |
| In2 (DSP)      | 3277 | 6554 | 9830 | 13107 | 16384 |
| In1            | 0    | 0.1  | 0.2  | 0.3   | 0.4   |
| In2            | 0.1  | 0.2  | 0.3  | 0.4   | 0.5   |
| Parameters     |      |      |      |       |       |
| Toggle         |      |      |      |       |       |
| Outputs        |      |      |      |       |       |
| Out            | 0    | 0.1  | 0.2  | 0.3   | 0.4   |
| Exp. Out       | 0    | 0.1  | 0.2  | 0.3   | 0.4   |
| Out (DSP)      | 0    | 3277 | 6554 | 9830  | 13107 |
| Exp. Out (DSP) | 0    | 3277 | 6554 | 9830  | 13107 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 57 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 10    |
| CPU cycles     | 57    | 57    | 57    | 57    | ... | 57    |
| Inputs         |       |       |       |       |     |       |
| In1 (DSP)      | 9830  |       |       |       |     |       |
| In2 (DSP)      | 19661 |       |       |       |     |       |
| In1            | 0.3   |       |       |       |     |       |
| In2            | 0.6   |       |       |       |     |       |
| Parameters     |       |       |       |       |     |       |
| Toggle         | 0     | 0.1   | 1     | 2     | ... | -3    |
| Outputs        |       |       |       |       |     |       |
| Out            | 0.3   | 0.6   | 0.6   | 0.6   | ... | 0.6   |
| Exp. Out       | 0.3   | 0.6   | 0.6   | 0.6   | ... | 0.6   |
| Out (DSP)      | 9830  | 19661 | 19661 | 19661 | ... | 19661 |
| Exp. Out (DSP) | 9830  | 19661 | 19661 | 19661 | ... | 19661 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 57 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results                 |   |     |   |   |     |    |
|------------------------------|---|-----|---|---|-----|----|
| <b>Time step</b>             | 1 | 2   | 3 | 4 | ... | 10 |
| <i>Mask parameters</i>       |   |     |   |   |     |    |
| <b>Toggle</b>                | 0 | 0.1 | 1 | 2 | ... | -3 |
| <i>Controller parameters</i> |   |     |   |   |     |    |
| <b>Toggle</b>                | 0 | 1   | 1 | 1 | ... | 1  |
| <b>Exp. Toggle</b>           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 518 |
| Max CPU cycles  | 543 |
| Avg CPU cycles  | 538 |



**Verification: ManualSwitch FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |      |      |      |       |       |
|----------------|------|------|------|-------|-------|
| Time step      | 1    | 2    | 3    | 4     | 5     |
| CPU cycles     | 46   | 46   | 46   | 46    | 46    |
| Inputs         |      |      |      |       |       |
| In1 (DSP)      | 0    | 3277 | 6554 | 9830  | 13107 |
| In2 (DSP)      | 3277 | 6554 | 9830 | 13107 | 16384 |
| In1            | 0    | 0.1  | 0.2  | 0.3   | 0.4   |
| In2            | 0.1  | 0.2  | 0.3  | 0.4   | 0.5   |
| Parameters     |      |      |      |       |       |
| Toggle         |      |      |      |       |       |
| Outputs        |      |      |      |       |       |
| Out            | 0    | 0.1  | 0.2  | 0.3   | 0.4   |
| Exp. Out       | 0    | 0.1  | 0.2  | 0.3   | 0.4   |
| Out (DSP)      | 0    | 3277 | 6554 | 9830  | 13107 |
| Exp. Out (DSP) | 0    | 3277 | 6554 | 9830  | 13107 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 46 |
| Max CPU cycles  | 46 |
| Avg CPU cycles  | 46 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 10    |
| CPU cycles     | 46    | 46    | 46    | 46    | ... | 46    |
| Inputs         |       |       |       |       |     |       |
| In1 (DSP)      | 9830  |       |       |       |     |       |
| In2 (DSP)      | 19661 |       |       |       |     |       |
| In1            | 0.3   |       |       |       |     |       |
| In2            | 0.6   |       |       |       |     |       |
| Parameters     |       |       |       |       |     |       |
| Toggle         | 0     | 0.1   | 1     | 2     | ... | -3    |
| Outputs        |       |       |       |       |     |       |
| Out            | 0.3   | 0.6   | 0.6   | 0.6   | ... | 0.6   |
| Exp. Out       | 0.3   | 0.6   | 0.6   | 0.6   | ... | 0.6   |
| Out (DSP)      | 9830  | 19661 | 19661 | 19661 | ... | 19661 |
| Exp. Out (DSP) | 9830  | 19661 | 19661 | 19661 | ... | 19661 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 46 |
| Max CPU cycles  | 46 |
| Avg CPU cycles  | 46 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results                 |   |     |   |   |     |    |
|------------------------------|---|-----|---|---|-----|----|
| <b>Time step</b>             | 1 | 2   | 3 | 4 | ... | 10 |
| <i>Mask parameters</i>       |   |     |   |   |     |    |
| <b>Toggle</b>                | 0 | 0.1 | 1 | 2 | ... | -3 |
| <i>Controller parameters</i> |   |     |   |   |     |    |
| <b>Toggle</b>                | 0 | 1   | 1 | 1 | ... | 1  |
| <b>Exp. Toggle</b>           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 602 |
| Max CPU cycles  | 612 |
| Avg CPU cycles  | 604 |

**Verification: ManualSwitch FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |      |      |      |       |       |
|----------------|------|------|------|-------|-------|
| Time step      | 1    | 2    | 3    | 4     | 5     |
| CPU cycles     | 27   | 27   | 27   | 27    | 27    |
| Inputs         |      |      |      |       |       |
| In1 (DSP)      | 0    | 3277 | 6554 | 9830  | 13107 |
| In2 (DSP)      | 3277 | 6554 | 9830 | 13107 | 16384 |
| In1            | 0    | 0.1  | 0.2  | 0.3   | 0.4   |
| In2            | 0.1  | 0.2  | 0.3  | 0.4   | 0.5   |
| Parameters     |      |      |      |       |       |
| Toggle         |      |      |      |       |       |
| Outputs        |      |      |      |       |       |
| Out            | 0    | 0.1  | 0.2  | 0.3   | 0.4   |
| Exp. Out       | 0    | 0.1  | 0.2  | 0.3   | 0.4   |
| Out (DSP)      | 0    | 3277 | 6554 | 9830  | 13107 |
| Exp. Out (DSP) | 0    | 3277 | 6554 | 9830  | 13107 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 27 |
| Max CPU cycles  | 27 |
| Avg CPU cycles  | 27 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 10    |
| CPU cycles     | 27    | 27    | 27    | 27    | ... | 27    |
| Inputs         |       |       |       |       |     |       |
| In1 (DSP)      | 9830  |       |       |       |     |       |
| In2 (DSP)      | 19661 |       |       |       |     |       |
| In1            | 0.3   |       |       |       |     |       |
| In2            | 0.6   |       |       |       |     |       |
| Parameters     |       |       |       |       |     |       |
| Toggle         | 0     | 0.1   | 1     | 2     | ... | -3    |
| Outputs        |       |       |       |       |     |       |
| Out            | 0.3   | 0.6   | 0.6   | 0.6   | ... | 0.6   |
| Exp. Out       | 0.3   | 0.6   | 0.6   | 0.6   | ... | 0.6   |
| Out (DSP)      | 9830  | 19661 | 19661 | 19661 | ... | 19661 |
| Exp. Out (DSP) | 9830  | 19661 | 19661 | 19661 | ... | 19661 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 27 |
| Max CPU cycles  | 27 |
| Avg CPU cycles  | 27 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| <b>Time step</b>      | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| <b>Toggle</b>         | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| <b>Toggle</b>         | 0 | 1   | 1 | 1 | ... | 1  |
| <b>Exp. Toggle</b>    | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 245 |
| Max CPU cycles  | 279 |
| Avg CPU cycles  | 266 |

**Verification: ManualSwitch FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |      |      |      |       |       |
|----------------|------|------|------|-------|-------|
| Time step      | 1    | 2    | 3    | 4     | 5     |
| CPU cycles     | 41   | 41   | 41   | 41    | 41    |
| Inputs         |      |      |      |       |       |
| In1 (DSP)      | 0    | 3277 | 6554 | 9830  | 13107 |
| In2 (DSP)      | 3277 | 6554 | 9830 | 13107 | 16384 |
| In1            | 0    | 0.1  | 0.2  | 0.3   | 0.4   |
| In2            | 0.1  | 0.2  | 0.3  | 0.4   | 0.5   |
| Parameters     |      |      |      |       |       |
| Toggle         |      |      |      |       |       |
| Outputs        |      |      |      |       |       |
| Out            | 0    | 0.1  | 0.2  | 0.3   | 0.4   |
| Exp. Out       | 0    | 0.1  | 0.2  | 0.3   | 0.4   |
| Out (DSP)      | 0    | 3277 | 6554 | 9830  | 13107 |
| Exp. Out (DSP) | 0    | 3277 | 6554 | 9830  | 13107 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 41 |
| Max CPU cycles  | 41 |
| Avg CPU cycles  | 41 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 10    |
| CPU cycles     | 41    | 41    | 41    | 41    | ... | 41    |
| Inputs         |       |       |       |       |     |       |
| In1 (DSP)      | 9830  |       |       |       |     |       |
| In2 (DSP)      | 19661 |       |       |       |     |       |
| In1            | 0.3   |       |       |       |     |       |
| In2            | 0.6   |       |       |       |     |       |
| Parameters     |       |       |       |       |     |       |
| Toggle         | 0     | 0.1   | 1     | 2     | ... | -3    |
| Outputs        |       |       |       |       |     |       |
| Out            | 0.3   | 0.6   | 0.6   | 0.6   | ... | 0.6   |
| Exp. Out       | 0.3   | 0.6   | 0.6   | 0.6   | ... | 0.6   |
| Out (DSP)      | 9830  | 19661 | 19661 | 19661 | ... | 19661 |
| Exp. Out (DSP) | 9830  | 19661 | 19661 | 19661 | ... | 19661 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 41 |
| Max CPU cycles  | 41 |
| Avg CPU cycles  | 41 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| <b>Time step</b>      | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| <b>Toggle</b>         | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| <b>Toggle</b>         | 0 | 1   | 1 | 1 | ... | 1  |
| <b>Exp. Toggle</b>    | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |



**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 520 |
| Max CPU cycles  | 546 |
| Avg CPU cycles  | 527 |

**Verification: ManualSwitch FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |      |      |      |       |       |
|----------------|------|------|------|-------|-------|
| Time step      | 1    | 2    | 3    | 4     | 5     |
| CPU cycles     | 53   | 53   | 53   | 53    | 53    |
| Inputs         |      |      |      |       |       |
| In1 (DSP)      | 0    | 3277 | 6554 | 9830  | 13107 |
| In2 (DSP)      | 3277 | 6554 | 9830 | 13107 | 16384 |
| In1            | 0    | 0.1  | 0.2  | 0.3   | 0.4   |
| In2            | 0.1  | 0.2  | 0.3  | 0.4   | 0.5   |
| Parameters     |      |      |      |       |       |
| Toggle         |      |      |      |       |       |
| Outputs        |      |      |      |       |       |
| Out            | 0    | 0.1  | 0.2  | 0.3   | 0.4   |
| Exp. Out       | 0    | 0.1  | 0.2  | 0.3   | 0.4   |
| Out (DSP)      | 0    | 3277 | 6554 | 9830  | 13107 |
| Exp. Out (DSP) | 0    | 3277 | 6554 | 9830  | 13107 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 53 |
| Max CPU cycles  | 53 |
| Avg CPU cycles  | 53 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 10    |
| CPU cycles     | 53    | 53    | 53    | 53    | ... | 53    |
| Inputs         |       |       |       |       |     |       |
| In1 (DSP)      | 9830  |       |       |       |     |       |
| In2 (DSP)      | 19661 |       |       |       |     |       |
| In1            | 0.3   |       |       |       |     |       |
| In2            | 0.6   |       |       |       |     |       |
| Parameters     |       |       |       |       |     |       |
| Toggle         | 0     | 0.1   | 1     | 2     | ... | -3    |
| Outputs        |       |       |       |       |     |       |
| Out            | 0.3   | 0.6   | 0.6   | 0.6   | ... | 0.6   |
| Exp. Out       | 0.3   | 0.6   | 0.6   | 0.6   | ... | 0.6   |
| Out (DSP)      | 9830  | 19661 | 19661 | 19661 | ... | 19661 |
| Exp. Out (DSP) | 9830  | 19661 | 19661 | 19661 | ... | 19661 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 53 |
| Max CPU cycles  | 53 |
| Avg CPU cycles  | 53 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results                 |   |     |   |   |     |    |
|------------------------------|---|-----|---|---|-----|----|
| <b>Time step</b>             | 1 | 2   | 3 | 4 | ... | 10 |
| <i>Mask parameters</i>       |   |     |   |   |     |    |
| <b>Toggle</b>                | 0 | 0.1 | 1 | 2 | ... | -3 |
| <i>Controller parameters</i> |   |     |   |   |     |    |
| <b>Toggle</b>                | 0 | 1   | 1 | 1 | ... | 1  |
| <b>Exp. Toggle</b>           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 451 |
| Max CPU cycles  | 506 |
| Avg CPU cycles  | 461 |

**Verification: ManualSwitch FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |      |      |      |       |       |
|----------------|------|------|------|-------|-------|
| Time step      | 1    | 2    | 3    | 4     | 5     |
| CPU cycles     | 38   | 38   | 38   | 38    | 38    |
| Inputs         |      |      |      |       |       |
| In1 (DSP)      | 0    | 3277 | 6554 | 9830  | 13107 |
| In2 (DSP)      | 3277 | 6554 | 9830 | 13107 | 16384 |
| In1            | 0    | 0.1  | 0.2  | 0.3   | 0.4   |
| In2            | 0.1  | 0.2  | 0.3  | 0.4   | 0.5   |
| Parameters     |      |      |      |       |       |
| Toggle         |      |      |      |       |       |
| Outputs        |      |      |      |       |       |
| Out            | 0    | 0.1  | 0.2  | 0.3   | 0.4   |
| Exp. Out       | 0    | 0.1  | 0.2  | 0.3   | 0.4   |
| Out (DSP)      | 0    | 3277 | 6554 | 9830  | 13107 |
| Exp. Out (DSP) | 0    | 3277 | 6554 | 9830  | 13107 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 38 |
| Max CPU cycles  | 38 |
| Avg CPU cycles  | 38 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.

| Test results   |       |       |       |       |     |       |
|----------------|-------|-------|-------|-------|-----|-------|
| Time step      | 1     | 2     | 3     | 4     | ... | 10    |
| CPU cycles     | 38    | 38    | 38    | 38    | ... | 38    |
| Inputs         |       |       |       |       |     |       |
| In1 (DSP)      | 9830  |       |       |       |     |       |
| In2 (DSP)      | 19661 |       |       |       |     |       |
| In1            | 0.3   |       |       |       |     |       |
| In2            | 0.6   |       |       |       |     |       |
| Parameters     |       |       |       |       |     |       |
| Toggle         | 0     | 0.1   | 1     | 2     | ... | -3    |
| Outputs        |       |       |       |       |     |       |
| Out            | 0.3   | 0.6   | 0.6   | 0.6   | ... | 0.6   |
| Exp. Out       | 0.3   | 0.6   | 0.6   | 0.6   | ... | 0.6   |
| Out (DSP)      | 9830  | 19661 | 19661 | 19661 | ... | 19661 |
| Exp. Out (DSP) | 9830  | 19661 | 19661 | 19661 | ... | 19661 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 38 |
| Max CPU cycles  | 38 |
| Avg CPU cycles  | 38 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results                 |   |     |   |   |     |    |
|------------------------------|---|-----|---|---|-----|----|
| <b>Time step</b>             | 1 | 2   | 3 | 4 | ... | 10 |
| <i>Mask parameters</i>       |   |     |   |   |     |    |
| <b>Toggle</b>                | 0 | 0.1 | 1 | 2 | ... | -3 |
| <i>Controller parameters</i> |   |     |   |   |     |    |
| <b>Toggle</b>                | 0 | 1   | 1 | 1 | ... | 1  |
| <b>Exp. Toggle</b>           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 611 |
| Max CPU cycles  | 646 |
| Avg CPU cycles  | 639 |

**Verification: ManualSwitch FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |           |           |     |            |
|----------------|-----------|-----------|-----|------------|
| Time step      | 1         | 2         | ... | 5          |
| CPU cycles     | 56        | 56        | ... | 56         |
| Inputs         |           |           |     |            |
| In1 (DSP)      | 0         | 214748365 | ... | 858993459  |
| In2 (DSP)      | 214748365 | 429496730 | ... | 1073741824 |
| In1            | 0         | 0.1       | ... | 0.4        |
| In2            | 0.1       | 0.2       | ... | 0.5        |
| Parameters     |           |           |     |            |
| Toggle         | 0         |           |     |            |
| Outputs        |           |           |     |            |
| Out            | 0         | 0.1       | ... | 0.4        |
| Exp. Out       | 0         | 0.1       | ... | 0.4        |
| Out (DSP)      | 0         | 214748365 | ... | 858993459  |
| Exp. Out (DSP) | 0         | 214748365 | ... | 858993459  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 56 |
| Avg CPU cycles  | 56 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.



| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 10         |
| CPU cycles     | 56         | 56         | ... | 56         |
| Inputs         |            |            |     |            |
| In1 (DSP)      | 644245094  |            |     |            |
| In2 (DSP)      | 1288490189 |            |     |            |
| In1            | 0.3        |            |     |            |
| In2            | 0.6        |            |     |            |
| Parameters     |            |            |     |            |
| Toggle         | 0          | 0.1        | ... | -3         |
| Outputs        |            |            |     |            |
| Out            | 0.3        | 0.6        | ... | 0.6        |
| Exp. Out       | 0.3        | 0.6        | ... | 0.6        |
| Out (DSP)      | 644245094  | 1288490189 | ... | 1288490189 |
| Exp. Out (DSP) | 644245094  | 1288490189 | ... | 1288490189 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 56 |
| Avg CPU cycles  | 56 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results                 |   |     |   |   |     |  |    |
|------------------------------|---|-----|---|---|-----|--|----|
| Time step                    | 1 | 2   | 3 | 4 | ... |  | 10 |
| <i>Mask parameters</i>       |   |     |   |   |     |  |    |
| Toggle                       | 0 | 0.1 | 1 | 2 | ... |  | -3 |
| <i>Controller parameters</i> |   |     |   |   |     |  |    |
| Toggle                       | 0 | 1   | 1 | 1 | ... |  | 1  |
| Exp. Toggle                  | 0 | 1   | 1 | 1 | ... |  | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |  |    |
|-----------------------|---|-----|---|---|-----|--|----|
| Time step             | 1 | 2   | 3 | 4 | ... |  | 10 |
| Mask parameters       |   |     |   |   |     |  |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... |  | -3 |
| Controller parameters |   |     |   |   |     |  |    |
| Toggle                | 0 | 1   | 1 | 1 | ... |  | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... |  | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 788 |
| Max CPU cycles  | 829 |
| Avg CPU cycles  | 820 |

**Verification: ManualSwitch FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |           |           |     |            |
|----------------|-----------|-----------|-----|------------|
| Time step      | 1         | 2         | ... | 5          |
| CPU cycles     | 23        | 23        | ... | 23         |
| Inputs         |           |           |     |            |
| In1 (DSP)      | 0         | 214748365 | ... | 858993459  |
| In2 (DSP)      | 214748365 | 429496730 | ... | 1073741824 |
| In1            | 0         | 0.1       | ... | 0.4        |
| In2            | 0.1       | 0.2       | ... | 0.5        |
| Parameters     |           |           |     |            |
| Toggle         | 0         |           |     |            |
| Outputs        |           |           |     |            |
| Out            | 0         | 0.1       | ... | 0.4        |
| Exp. Out       | 0         | 0.1       | ... | 0.4        |
| Out (DSP)      | 0         | 214748365 | ... | 858993459  |
| Exp. Out (DSP) | 0         | 214748365 | ... | 858993459  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 23 |
| Max CPU cycles  | 23 |
| Avg CPU cycles  | 23 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 10         |
| CPU cycles     | 23         | 23         | ... | 23         |
| Inputs         |            |            |     |            |
| In1 (DSP)      | 644245094  |            |     |            |
| In2 (DSP)      | 1288490189 |            |     |            |
| In1            | 0.3        |            |     |            |
| In2            | 0.6        |            |     |            |
| Parameters     |            |            |     |            |
| Toggle         | 0          | 0.1        | ... | -3         |
| Outputs        |            |            |     |            |
| Out            | 0.3        | 0.6        | ... | 0.6        |
| Exp. Out       | 0.3        | 0.6        | ... | 0.6        |
| Out (DSP)      | 644245094  | 1288490189 | ... | 1288490189 |
| Exp. Out (DSP) | 644245094  | 1288490189 | ... | 1288490189 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 23 |
| Max CPU cycles  | 23 |
| Avg CPU cycles  | 23 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results                 |   |     |   |   |     |  |    |
|------------------------------|---|-----|---|---|-----|--|----|
| Time step                    | 1 | 2   | 3 | 4 | ... |  | 10 |
| <i>Mask parameters</i>       |   |     |   |   |     |  |    |
| Toggle                       | 0 | 0.1 | 1 | 2 | ... |  | -3 |
| <i>Controller parameters</i> |   |     |   |   |     |  |    |
| Toggle                       | 0 | 1   | 1 | 1 | ... |  | 1  |
| Exp. Toggle                  | 0 | 1   | 1 | 1 | ... |  | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 375 |
| Max CPU cycles  | 399 |
| Avg CPU cycles  | 393 |

**Verification: ManualSwitch FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |           |           |     |            |
|----------------|-----------|-----------|-----|------------|
| Time step      | 1         | 2         | ... | 5          |
| CPU cycles     | 57        | 57        | ... | 57         |
| Inputs         |           |           |     |            |
| In1 (DSP)      | 0         | 214748365 | ... | 858993459  |
| In2 (DSP)      | 214748365 | 429496730 | ... | 1073741824 |
| In1            | 0         | 0.1       | ... | 0.4        |
| In2            | 0.1       | 0.2       | ... | 0.5        |
| Parameters     |           |           |     |            |
| Toggle         | 0         |           |     |            |
| Outputs        |           |           |     |            |
| Out            | 0         | 0.1       | ... | 0.4        |
| Exp. Out       | 0         | 0.1       | ... | 0.4        |
| Out (DSP)      | 0         | 214748365 | ... | 858993459  |
| Exp. Out (DSP) | 0         | 214748365 | ... | 858993459  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 57 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 10         |
| CPU cycles     | 57         | 57         | ... | 57         |
| Inputs         |            |            |     |            |
| In1 (DSP)      | 644245094  |            |     |            |
| In2 (DSP)      | 1288490189 |            |     |            |
| In1            | 0.3        |            |     |            |
| In2            | 0.6        |            |     |            |
| Parameters     |            |            |     |            |
| Toggle         | 0          | 0.1        | ... | -3         |
| Outputs        |            |            |     |            |
| Out            | 0.3        | 0.6        | ... | 0.6        |
| Exp. Out       | 0.3        | 0.6        | ... | 0.6        |
| Out (DSP)      | 644245094  | 1288490189 | ... | 1288490189 |
| Exp. Out (DSP) | 644245094  | 1288490189 | ... | 1288490189 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 57 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results                 |   |     |   |   |     |  |    |
|------------------------------|---|-----|---|---|-----|--|----|
| Time step                    | 1 | 2   | 3 | 4 | ... |  | 10 |
| <i>Mask parameters</i>       |   |     |   |   |     |  |    |
| Toggle                       | 0 | 0.1 | 1 | 2 | ... |  | -3 |
| <i>Controller parameters</i> |   |     |   |   |     |  |    |
| Toggle                       | 0 | 1   | 1 | 1 | ... |  | 1  |
| Exp. Toggle                  | 0 | 1   | 1 | 1 | ... |  | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |  |    |
|-----------------------|---|-----|---|---|-----|--|----|
| Time step             | 1 | 2   | 3 | 4 | ... |  | 10 |
| Mask parameters       |   |     |   |   |     |  |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... |  | -3 |
| Controller parameters |   |     |   |   |     |  |    |
| Toggle                | 0 | 1   | 1 | 1 | ... |  | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... |  | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 511 |
| Max CPU cycles  | 539 |
| Avg CPU cycles  | 533 |



**Verification: ManualSwitch FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |           |           |     |            |
|----------------|-----------|-----------|-----|------------|
| Time step      | 1         | 2         | ... | 5          |
| CPU cycles     | 45        | 45        | ... | 45         |
| Inputs         |           |           |     |            |
| In1 (DSP)      | 0         | 214748365 | ... | 858993459  |
| In2 (DSP)      | 214748365 | 429496730 | ... | 1073741824 |
| In1            | 0         | 0.1       | ... | 0.4        |
| In2            | 0.1       | 0.2       | ... | 0.5        |
| Parameters     |           |           |     |            |
| Toggle         | 0         |           |     |            |
| Outputs        |           |           |     |            |
| Out            | 0         | 0.1       | ... | 0.4        |
| Exp. Out       | 0         | 0.1       | ... | 0.4        |
| Out (DSP)      | 0         | 214748365 | ... | 858993459  |
| Exp. Out (DSP) | 0         | 214748365 | ... | 858993459  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 45 |
| Max CPU cycles  | 45 |
| Avg CPU cycles  | 45 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 10         |
| CPU cycles     | 45         | 45         | ... | 45         |
| Inputs         |            |            |     |            |
| In1 (DSP)      | 644245094  |            |     |            |
| In2 (DSP)      | 1288490189 |            |     |            |
| In1            | 0.3        |            |     |            |
| In2            | 0.6        |            |     |            |
| Parameters     |            |            |     |            |
| Toggle         | 0          | 0.1        | ... | -3         |
| Outputs        |            |            |     |            |
| Out            | 0.3        | 0.6        | ... | 0.6        |
| Exp. Out       | 0.3        | 0.6        | ... | 0.6        |
| Out (DSP)      | 644245094  | 1288490189 | ... | 1288490189 |
| Exp. Out (DSP) | 644245094  | 1288490189 | ... | 1288490189 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 45 |
| Max CPU cycles  | 45 |
| Avg CPU cycles  | 45 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results                 |   |     |   |   |     |  |    |
|------------------------------|---|-----|---|---|-----|--|----|
| Time step                    | 1 | 2   | 3 | 4 | ... |  | 10 |
| <i>Mask parameters</i>       |   |     |   |   |     |  |    |
| Toggle                       | 0 | 0.1 | 1 | 2 | ... |  | -3 |
| <i>Controller parameters</i> |   |     |   |   |     |  |    |
| Toggle                       | 0 | 1   | 1 | 1 | ... |  | 1  |
| Exp. Toggle                  | 0 | 1   | 1 | 1 | ... |  | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 602 |
| Max CPU cycles  | 612 |
| Avg CPU cycles  | 604 |

**Verification: ManualSwitch FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |           |           |     |            |
|----------------|-----------|-----------|-----|------------|
| Time step      | 1         | 2         | ... | 5          |
| CPU cycles     | 27        | 27        | ... | 27         |
| Inputs         |           |           |     |            |
| In1 (DSP)      | 0         | 214748365 | ... | 858993459  |
| In2 (DSP)      | 214748365 | 429496730 | ... | 1073741824 |
| In1            | 0         | 0.1       | ... | 0.4        |
| In2            | 0.1       | 0.2       | ... | 0.5        |
| Parameters     |           |           |     |            |
| Toggle         | 0         |           |     |            |
| Outputs        |           |           |     |            |
| Out            | 0         | 0.1       | ... | 0.4        |
| Exp. Out       | 0         | 0.1       | ... | 0.4        |
| Out (DSP)      | 0         | 214748365 | ... | 858993459  |
| Exp. Out (DSP) | 0         | 214748365 | ... | 858993459  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 27 |
| Max CPU cycles  | 27 |
| Avg CPU cycles  | 27 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 10         |
| CPU cycles     | 27         | 27         | ... | 27         |
| Inputs         |            |            |     |            |
| In1 (DSP)      | 644245094  |            |     |            |
| In2 (DSP)      | 1288490189 |            |     |            |
| In1            | 0.3        |            |     |            |
| In2            | 0.6        |            |     |            |
| Parameters     |            |            |     |            |
| Toggle         | 0          | 0.1        | ... | -3         |
| Outputs        |            |            |     |            |
| Out            | 0.3        | 0.6        | ... | 0.6        |
| Exp. Out       | 0.3        | 0.6        | ... | 0.6        |
| Out (DSP)      | 644245094  | 1288490189 | ... | 1288490189 |
| Exp. Out (DSP) | 644245094  | 1288490189 | ... | 1288490189 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 27 |
| Max CPU cycles  | 27 |
| Avg CPU cycles  | 27 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results                 |   |     |   |   |     |  |    |
|------------------------------|---|-----|---|---|-----|--|----|
| Time step                    | 1 | 2   | 3 | 4 | ... |  | 10 |
| <i>Mask parameters</i>       |   |     |   |   |     |  |    |
| Toggle                       | 0 | 0.1 | 1 | 2 | ... |  | -3 |
| <i>Controller parameters</i> |   |     |   |   |     |  |    |
| Toggle                       | 0 | 1   | 1 | 1 | ... |  | 1  |
| Exp. Toggle                  | 0 | 1   | 1 | 1 | ... |  | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |  |    |
|-----------------------|---|-----|---|---|-----|--|----|
| Time step             | 1 | 2   | 3 | 4 | ... |  | 10 |
| Mask parameters       |   |     |   |   |     |  |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... |  | -3 |
| Controller parameters |   |     |   |   |     |  |    |
| Toggle                | 0 | 1   | 1 | 1 | ... |  | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... |  | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 245 |
| Max CPU cycles  | 279 |
| Avg CPU cycles  | 266 |

**Verification: ManualSwitch FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |           |           |     |            |
|----------------|-----------|-----------|-----|------------|
| Time step      | 1         | 2         | ... | 5          |
| CPU cycles     | 43        | 43        | ... | 43         |
| Inputs         |           |           |     |            |
| In1 (DSP)      | 0         | 214748365 | ... | 858993459  |
| In2 (DSP)      | 214748365 | 429496730 | ... | 1073741824 |
| In1            | 0         | 0.1       | ... | 0.4        |
| In2            | 0.1       | 0.2       | ... | 0.5        |
| Parameters     |           |           |     |            |
| Toggle         | 0         |           |     |            |
| Outputs        |           |           |     |            |
| Out            | 0         | 0.1       | ... | 0.4        |
| Exp. Out       | 0         | 0.1       | ... | 0.4        |
| Out (DSP)      | 0         | 214748365 | ... | 858993459  |
| Exp. Out (DSP) | 0         | 214748365 | ... | 858993459  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 43 |
| Max CPU cycles  | 43 |
| Avg CPU cycles  | 43 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 10         |
| CPU cycles     | 43         | 43         | ... | 43         |
| Inputs         |            |            |     |            |
| In1 (DSP)      | 644245094  |            |     |            |
| In2 (DSP)      | 1288490189 |            |     |            |
| In1            | 0.3        |            |     |            |
| In2            | 0.6        |            |     |            |
| Parameters     |            |            |     |            |
| Toggle         | 0          | 0.1        | ... | -3         |
| Outputs        |            |            |     |            |
| Out            | 0.3        | 0.6        | ... | 0.6        |
| Exp. Out       | 0.3        | 0.6        | ... | 0.6        |
| Out (DSP)      | 644245094  | 1288490189 | ... | 1288490189 |
| Exp. Out (DSP) | 644245094  | 1288490189 | ... | 1288490189 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 43 |
| Max CPU cycles  | 43 |
| Avg CPU cycles  | 43 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results                 |   |     |   |   |     |  |    |
|------------------------------|---|-----|---|---|-----|--|----|
| Time step                    | 1 | 2   | 3 | 4 | ... |  | 10 |
| <i>Mask parameters</i>       |   |     |   |   |     |  |    |
| Toggle                       | 0 | 0.1 | 1 | 2 | ... |  | -3 |
| <i>Controller parameters</i> |   |     |   |   |     |  |    |
| Toggle                       | 0 | 1   | 1 | 1 | ... |  | 1  |
| Exp. Toggle                  | 0 | 1   | 1 | 1 | ... |  | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |



**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |  |    |
|-----------------------|---|-----|---|---|-----|--|----|
| Time step             | 1 | 2   | 3 | 4 | ... |  | 10 |
| Mask parameters       |   |     |   |   |     |  |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... |  | -3 |
| Controller parameters |   |     |   |   |     |  |    |
| Toggle                | 0 | 1   | 1 | 1 | ... |  | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... |  | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 520 |
| Max CPU cycles  | 546 |
| Avg CPU cycles  | 527 |

**Verification: ManualSwitch FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |           |           |     |            |
|----------------|-----------|-----------|-----|------------|
| Time step      | 1         | 2         | ... | 5          |
| CPU cycles     | 53        | 53        | ... | 53         |
| Inputs         |           |           |     |            |
| In1 (DSP)      | 0         | 214748365 | ... | 858993459  |
| In2 (DSP)      | 214748365 | 429496730 | ... | 1073741824 |
| In1            | 0         | 0.1       | ... | 0.4        |
| In2            | 0.1       | 0.2       | ... | 0.5        |
| Parameters     |           |           |     |            |
| Toggle         | 0         |           |     |            |
| Outputs        |           |           |     |            |
| Out            | 0         | 0.1       | ... | 0.4        |
| Exp. Out       | 0         | 0.1       | ... | 0.4        |
| Out (DSP)      | 0         | 214748365 | ... | 858993459  |
| Exp. Out (DSP) | 0         | 214748365 | ... | 858993459  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 53 |
| Max CPU cycles  | 53 |
| Avg CPU cycles  | 53 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 10         |
| CPU cycles     | 68         | 68         | ... | 68         |
| Inputs         |            |            |     |            |
| In1 (DSP)      | 644245094  |            |     |            |
| In2 (DSP)      | 1288490189 |            |     |            |
| In1            | 0.3        |            |     |            |
| In2            | 0.6        |            |     |            |
| Parameters     |            |            |     |            |
| Toggle         | 0          | 0.1        | ... | -3         |
| Outputs        |            |            |     |            |
| Out            | 0.3        | 0.6        | ... | 0.6        |
| Exp. Out       | 0.3        | 0.6        | ... | 0.6        |
| Out (DSP)      | 644245094  | 1288490189 | ... | 1288490189 |
| Exp. Out (DSP) | 644245094  | 1288490189 | ... | 1288490189 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 68 |
| Max CPU cycles  | 68 |
| Avg CPU cycles  | 68 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results                 |   |     |   |   |     |  |    |
|------------------------------|---|-----|---|---|-----|--|----|
| Time step                    | 1 | 2   | 3 | 4 | ... |  | 10 |
| <i>Mask parameters</i>       |   |     |   |   |     |  |    |
| Toggle                       | 0 | 0.1 | 1 | 2 | ... |  | -3 |
| <i>Controller parameters</i> |   |     |   |   |     |  |    |
| Toggle                       | 0 | 1   | 1 | 1 | ... |  | 1  |
| Exp. Toggle                  | 0 | 1   | 1 | 1 | ... |  | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 453 |
| Max CPU cycles  | 512 |
| Avg CPU cycles  | 463 |

**Verification: ManualSwitch FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |           |           |     |            |
|----------------|-----------|-----------|-----|------------|
| Time step      | 1         | 2         | ... | 5          |
| CPU cycles     | 36        | 36        | ... | 36         |
| Inputs         |           |           |     |            |
| In1 (DSP)      | 0         | 214748365 | ... | 858993459  |
| In2 (DSP)      | 214748365 | 429496730 | ... | 1073741824 |
| In1            | 0         | 0.1       | ... | 0.4        |
| In2            | 0.1       | 0.2       | ... | 0.5        |
| Parameters     |           |           |     |            |
| Toggle         | 0         |           |     |            |
| Outputs        |           |           |     |            |
| Out            | 0         | 0.1       | ... | 0.4        |
| Exp. Out       | 0         | 0.1       | ... | 0.4        |
| Out (DSP)      | 0         | 214748365 | ... | 858993459  |
| Exp. Out (DSP) | 0         | 214748365 | ... | 858993459  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 36 |
| Max CPU cycles  | 36 |
| Avg CPU cycles  | 36 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.

| Test results   |            |            |     |            |
|----------------|------------|------------|-----|------------|
| Time step      | 1          | 2          | ... | 10         |
| CPU cycles     | 36         | 36         | ... | 36         |
| Inputs         |            |            |     |            |
| In1 (DSP)      | 644245094  |            |     |            |
| In2 (DSP)      | 1288490189 |            |     |            |
| In1            | 0.3        |            |     |            |
| In2            | 0.6        |            |     |            |
| Parameters     |            |            |     |            |
| Toggle         | 0          | 0.1        | ... | -3         |
| Outputs        |            |            |     |            |
| Out            | 0.3        | 0.6        | ... | 0.6        |
| Exp. Out       | 0.3        | 0.6        | ... | 0.6        |
| Out (DSP)      | 644245094  | 1288490189 | ... | 1288490189 |
| Exp. Out (DSP) | 644245094  | 1288490189 | ... | 1288490189 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 36 |
| Max CPU cycles  | 36 |
| Avg CPU cycles  | 36 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results                 |   |     |   |   |     |  |    |
|------------------------------|---|-----|---|---|-----|--|----|
| Time step                    | 1 | 2   | 3 | 4 | ... |  | 10 |
| <i>Mask parameters</i>       |   |     |   |   |     |  |    |
| Toggle                       | 0 | 0.1 | 1 | 2 | ... |  | -3 |
| <i>Controller parameters</i> |   |     |   |   |     |  |    |
| Toggle                       | 0 | 1   | 1 | 1 | ... |  | 1  |
| Exp. Toggle                  | 0 | 1   | 1 | 1 | ... |  | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 606 |
| Max CPU cycles  | 633 |
| Avg CPU cycles  | 627 |

**Verification: ManualSwitch Float32 CPU TMS320F28335**

Date of Test 2026-06-19  
Target controller TMS320F28335

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |     |     |     |     |
|----------------|-----|-----|-----|-----|
| Time step      | 1   | 2   | ... | 5   |
| CPU cycles     | 56  | 56  | ... | 56  |
| Inputs         |     |     |     |     |
| In1 (DSP)      | 0   | 0.1 | ... | 0.4 |
| In2 (DSP)      | 0.1 | 0.2 | ... | 0.5 |
| In1            | 0   | 0.1 | ... | 0.4 |
| In2            | 0.1 | 0.2 | ... | 0.5 |
| Parameters     |     |     |     |     |
| Toggle         | 0   |     |     |     |
| Outputs        |     |     |     |     |
| Out            | 0   | 0.1 | ... | 0.4 |
| Exp. Out       | 0   | 0.1 | ... | 0.4 |
| Out (DSP)      | 0   | 0.1 | ... | 0.4 |
| Exp. Out (DSP) | 0   | 0.1 | ... | 0.4 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 1,5259e-05$ ( $\pm 32768$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 56 |
| Avg CPU cycles  | 56 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.



| Test results   |     |     |     |     |
|----------------|-----|-----|-----|-----|
| Time step      | 1   | 2   | ... | 10  |
| CPU cycles     | 56  | 56  | ... | 56  |
| Inputs         |     |     |     |     |
| In1 (DSP)      | 0.3 |     |     |     |
| In2 (DSP)      | 0.6 |     |     |     |
| In1            | 0.3 |     |     |     |
| In2            | 0.6 |     |     |     |
| Parameters     |     |     |     |     |
| Toggle         | 0   | 0.1 | ... | -3  |
| Outputs        |     |     |     |     |
| Out            | 0.3 | 0.6 | ... | 0.6 |
| Exp. Out       | 0.3 | 0.6 | ... | 0.6 |
| Out (DSP)      | 0.3 | 0.6 | ... | 0.6 |
| Exp. Out (DSP) | 0.3 | 0.6 | ... | 0.6 |

| Test settings |                                            |
|---------------|--------------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}05$ ( $\pm 32768$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 56 |
| Avg CPU cycles  | 56 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                         |
|------------------|-------------------------|
| Tolerance Toggle | $\pm 0,0000\text{e+}00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 778 |
| Max CPU cycles  | 825 |
| Avg CPU cycles  | 815 |

**Verification: ManualSwitch Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |     |     |     |     |
|----------------|-----|-----|-----|-----|
| Time step      | 1   | 2   | ... | 5   |
| CPU cycles     | 23  | 23  | ... | 23  |
| Inputs         |     |     |     |     |
| In1 (DSP)      | 0   | 0.1 | ... | 0.4 |
| In2 (DSP)      | 0.1 | 0.2 | ... | 0.5 |
| In1            | 0   | 0.1 | ... | 0.4 |
| In2            | 0.1 | 0.2 | ... | 0.5 |
| Parameters     |     |     |     |     |
| Toggle         | 0   |     |     |     |
| Outputs        |     |     |     |     |
| Out            | 0   | 0.1 | ... | 0.4 |
| Exp. Out       | 0   | 0.1 | ... | 0.4 |
| Out (DSP)      | 0   | 0.1 | ... | 0.4 |
| Exp. Out (DSP) | 0   | 0.1 | ... | 0.4 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 1,5259e-05$ ( $\pm 32768$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 23 |
| Max CPU cycles  | 23 |
| Avg CPU cycles  | 23 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.

| Test results   |     |     |     |     |
|----------------|-----|-----|-----|-----|
| Time step      | 1   | 2   | ... | 10  |
| CPU cycles     | 23  | 23  | ... | 23  |
| Inputs         |     |     |     |     |
| In1 (DSP)      | 0.3 |     |     |     |
| In2 (DSP)      | 0.6 |     |     |     |
| In1            | 0.3 |     |     |     |
| In2            | 0.6 |     |     |     |
| Parameters     |     |     |     |     |
| Toggle         | 0   | 0.1 | ... | -3  |
| Outputs        |     |     |     |     |
| Out            | 0.3 | 0.6 | ... | 0.6 |
| Exp. Out       | 0.3 | 0.6 | ... | 0.6 |
| Out (DSP)      | 0.3 | 0.6 | ... | 0.6 |
| Exp. Out (DSP) | 0.3 | 0.6 | ... | 0.6 |

| Test settings |                                            |
|---------------|--------------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}05$ ( $\pm 32768$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 23 |
| Max CPU cycles  | 23 |
| Avg CPU cycles  | 23 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                         |
|------------------|-------------------------|
| Tolerance Toggle | $\pm 0,0000\text{e}+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 375 |
| Max CPU cycles  | 399 |
| Avg CPU cycles  | 393 |

**Verification: ManualSwitch Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |     |     |     |     |
|----------------|-----|-----|-----|-----|
| Time step      | 1   | 2   | ... | 5   |
| CPU cycles     | 52  | 52  | ... | 52  |
| Inputs         |     |     |     |     |
| In1 (DSP)      | 0   | 0.1 | ... | 0.4 |
| In2 (DSP)      | 0.1 | 0.2 | ... | 0.5 |
| In1            | 0   | 0.1 | ... | 0.4 |
| In2            | 0.1 | 0.2 | ... | 0.5 |
| Parameters     |     |     |     |     |
| Toggle         | 0   |     |     |     |
| Outputs        |     |     |     |     |
| Out            | 0   | 0.1 | ... | 0.4 |
| Exp. Out       | 0   | 0.1 | ... | 0.4 |
| Out (DSP)      | 0   | 0.1 | ... | 0.4 |
| Exp. Out (DSP) | 0   | 0.1 | ... | 0.4 |

| Test settings |                                            |
|---------------|--------------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}05$ ( $\pm 32768$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 52 |
| Max CPU cycles  | 52 |
| Avg CPU cycles  | 52 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.

| Test results   |     |     |     |     |
|----------------|-----|-----|-----|-----|
| Time step      | 1   | 2   | ... | 10  |
| CPU cycles     | 52  | 52  | ... | 52  |
| Inputs         |     |     |     |     |
| In1 (DSP)      | 0.3 |     |     |     |
| In2 (DSP)      | 0.6 |     |     |     |
| In1            | 0.3 |     |     |     |
| In2            | 0.6 |     |     |     |
| Parameters     |     |     |     |     |
| Toggle         | 0   | 0.1 | ... | -3  |
| Outputs        |     |     |     |     |
| Out            | 0.3 | 0.6 | ... | 0.6 |
| Exp. Out       | 0.3 | 0.6 | ... | 0.6 |
| Out (DSP)      | 0.3 | 0.6 | ... | 0.6 |
| Exp. Out (DSP) | 0.3 | 0.6 | ... | 0.6 |

| Test settings |                                            |
|---------------|--------------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}05$ ( $\pm 32768$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 52 |
| Max CPU cycles  | 52 |
| Avg CPU cycles  | 52 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                         |
|------------------|-------------------------|
| Tolerance Toggle | $\pm 0,0000\text{e}+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |  |    |
|-----------------------|---|-----|---|---|-----|--|----|
| Time step             | 1 | 2   | 3 | 4 | ... |  | 10 |
| Mask parameters       |   |     |   |   |     |  |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... |  | -3 |
| Controller parameters |   |     |   |   |     |  |    |
| Toggle                | 0 | 1   | 1 | 1 | ... |  | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... |  | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 513 |
| Max CPU cycles  | 539 |
| Avg CPU cycles  | 533 |



**Verification: ManualSwitch Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |     |     |     |     |
|----------------|-----|-----|-----|-----|
| Time step      | 1   | 2   | ... | 5   |
| CPU cycles     | 45  | 45  | ... | 45  |
| Inputs         |     |     |     |     |
| In1 (DSP)      | 0   | 0.1 | ... | 0.4 |
| In2 (DSP)      | 0.1 | 0.2 | ... | 0.5 |
| In1            | 0   | 0.1 | ... | 0.4 |
| In2            | 0.1 | 0.2 | ... | 0.5 |
| Parameters     |     |     |     |     |
| Toggle         | 0   |     |     |     |
| Outputs        |     |     |     |     |
| Out            | 0   | 0.1 | ... | 0.4 |
| Exp. Out       | 0   | 0.1 | ... | 0.4 |
| Out (DSP)      | 0   | 0.1 | ... | 0.4 |
| Exp. Out (DSP) | 0   | 0.1 | ... | 0.4 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 1,5259e-05$ ( $\pm 32768$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 45 |
| Max CPU cycles  | 45 |
| Avg CPU cycles  | 45 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.

| Test results   |     |     |     |     |
|----------------|-----|-----|-----|-----|
| Time step      | 1   | 2   | ... | 10  |
| CPU cycles     | 45  | 45  | ... | 45  |
| Inputs         |     |     |     |     |
| In1 (DSP)      | 0.3 |     |     |     |
| In2 (DSP)      | 0.6 |     |     |     |
| In1            | 0.3 |     |     |     |
| In2            | 0.6 |     |     |     |
| Parameters     |     |     |     |     |
| Toggle         | 0   | 0.1 | ... | -3  |
| Outputs        |     |     |     |     |
| Out            | 0.3 | 0.6 | ... | 0.6 |
| Exp. Out       | 0.3 | 0.6 | ... | 0.6 |
| Out (DSP)      | 0.3 | 0.6 | ... | 0.6 |
| Exp. Out (DSP) | 0.3 | 0.6 | ... | 0.6 |

| Test settings |                                            |
|---------------|--------------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}05$ ( $\pm 32768$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 45 |
| Max CPU cycles  | 45 |
| Avg CPU cycles  | 45 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                         |
|------------------|-------------------------|
| Tolerance Toggle | $\pm 0,0000\text{e+}00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 602 |
| Max CPU cycles  | 612 |
| Avg CPU cycles  | 604 |

**Verification: ManualSwitch Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |     |     |     |     |
|----------------|-----|-----|-----|-----|
| Time step      | 1   | 2   | ... | 5   |
| CPU cycles     | 27  | 27  | ... | 27  |
| Inputs         |     |     |     |     |
| In1 (DSP)      | 0   | 0.1 | ... | 0.4 |
| In2 (DSP)      | 0.1 | 0.2 | ... | 0.5 |
| In1            | 0   | 0.1 | ... | 0.4 |
| In2            | 0.1 | 0.2 | ... | 0.5 |
| Parameters     |     |     |     |     |
| Toggle         | 0   |     |     |     |
| Outputs        |     |     |     |     |
| Out            | 0   | 0.1 | ... | 0.4 |
| Exp. Out       | 0   | 0.1 | ... | 0.4 |
| Out (DSP)      | 0   | 0.1 | ... | 0.4 |
| Exp. Out (DSP) | 0   | 0.1 | ... | 0.4 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 1,5259e-05$ ( $\pm 32768$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 27 |
| Max CPU cycles  | 27 |
| Avg CPU cycles  | 27 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.

| Test results   |     |     |     |     |
|----------------|-----|-----|-----|-----|
| Time step      | 1   | 2   | ... | 10  |
| CPU cycles     | 27  | 27  | ... | 27  |
| Inputs         |     |     |     |     |
| In1 (DSP)      | 0.3 |     |     |     |
| In2 (DSP)      | 0.6 |     |     |     |
| In1            | 0.3 |     |     |     |
| In2            | 0.6 |     |     |     |
| Parameters     |     |     |     |     |
| Toggle         | 0   | 0.1 | ... | -3  |
| Outputs        |     |     |     |     |
| Out            | 0.3 | 0.6 | ... | 0.6 |
| Exp. Out       | 0.3 | 0.6 | ... | 0.6 |
| Out (DSP)      | 0.3 | 0.6 | ... | 0.6 |
| Exp. Out (DSP) | 0.3 | 0.6 | ... | 0.6 |

| Test settings |                                            |
|---------------|--------------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}05$ ( $\pm 32768$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 27 |
| Max CPU cycles  | 27 |
| Avg CPU cycles  | 27 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                         |
|------------------|-------------------------|
| Tolerance Toggle | $\pm 0,0000\text{e+}00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 245 |
| Max CPU cycles  | 279 |
| Avg CPU cycles  | 266 |

**Verification: ManualSwitch Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |     |     |     |     |
|----------------|-----|-----|-----|-----|
| Time step      | 1   | 2   | ... | 5   |
| CPU cycles     | 43  | 43  | ... | 43  |
| Inputs         |     |     |     |     |
| In1 (DSP)      | 0   | 0.1 | ... | 0.4 |
| In2 (DSP)      | 0.1 | 0.2 | ... | 0.5 |
| In1            | 0   | 0.1 | ... | 0.4 |
| In2            | 0.1 | 0.2 | ... | 0.5 |
| Parameters     |     |     |     |     |
| Toggle         | 0   |     |     |     |
| Outputs        |     |     |     |     |
| Out            | 0   | 0.1 | ... | 0.4 |
| Exp. Out       | 0   | 0.1 | ... | 0.4 |
| Out (DSP)      | 0   | 0.1 | ... | 0.4 |
| Exp. Out (DSP) | 0   | 0.1 | ... | 0.4 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 1,5259e-05$ ( $\pm 32768$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 43 |
| Max CPU cycles  | 43 |
| Avg CPU cycles  | 43 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.

| Test results   |     |     |     |     |
|----------------|-----|-----|-----|-----|
| Time step      | 1   | 2   | ... | 10  |
| CPU cycles     | 43  | 43  | ... | 43  |
| Inputs         |     |     |     |     |
| In1 (DSP)      | 0.3 |     |     |     |
| In2 (DSP)      | 0.6 |     |     |     |
| In1            | 0.3 |     |     |     |
| In2            | 0.6 |     |     |     |
| Parameters     |     |     |     |     |
| Toggle         | 0   | 0.1 | ... | -3  |
| Outputs        |     |     |     |     |
| Out            | 0.3 | 0.6 | ... | 0.6 |
| Exp. Out       | 0.3 | 0.6 | ... | 0.6 |
| Out (DSP)      | 0.3 | 0.6 | ... | 0.6 |
| Exp. Out (DSP) | 0.3 | 0.6 | ... | 0.6 |

| Test settings |                                            |
|---------------|--------------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}05$ ( $\pm 32768$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 43 |
| Max CPU cycles  | 43 |
| Avg CPU cycles  | 43 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                         |
|------------------|-------------------------|
| Tolerance Toggle | $\pm 0,0000\text{e+}00$ |



**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 520 |
| Max CPU cycles  | 546 |
| Avg CPU cycles  | 527 |

**Verification: ManualSwitch Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |     |     |     |     |
|----------------|-----|-----|-----|-----|
| Time step      | 1   | 2   | ... | 5   |
| CPU cycles     | 53  | 53  | ... | 53  |
| Inputs         |     |     |     |     |
| In1 (DSP)      | 0   | 0.1 | ... | 0.4 |
| In2 (DSP)      | 0.1 | 0.2 | ... | 0.5 |
| In1            | 0   | 0.1 | ... | 0.4 |
| In2            | 0.1 | 0.2 | ... | 0.5 |
| Parameters     |     |     |     |     |
| Toggle         | 0   |     |     |     |
| Outputs        |     |     |     |     |
| Out            | 0   | 0.1 | ... | 0.4 |
| Exp. Out       | 0   | 0.1 | ... | 0.4 |
| Out (DSP)      | 0   | 0.1 | ... | 0.4 |
| Exp. Out (DSP) | 0   | 0.1 | ... | 0.4 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 1,5259e-05$ ( $\pm 32768$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 53 |
| Max CPU cycles  | 53 |
| Avg CPU cycles  | 53 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.

| Test results   |     |     |     |     |
|----------------|-----|-----|-----|-----|
| Time step      | 1   | 2   | ... | 10  |
| CPU cycles     | 53  | 53  | ... | 53  |
| Inputs         |     |     |     |     |
| In1 (DSP)      | 0.3 |     |     |     |
| In2 (DSP)      | 0.6 |     |     |     |
| In1            | 0.3 |     |     |     |
| In2            | 0.6 |     |     |     |
| Parameters     |     |     |     |     |
| Toggle         | 0   | 0.1 | ... | -3  |
| Outputs        |     |     |     |     |
| Out            | 0.3 | 0.6 | ... | 0.6 |
| Exp. Out       | 0.3 | 0.6 | ... | 0.6 |
| Out (DSP)      | 0.3 | 0.6 | ... | 0.6 |
| Exp. Out (DSP) | 0.3 | 0.6 | ... | 0.6 |

| Test settings |                                            |
|---------------|--------------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}05$ ( $\pm 32768$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 53 |
| Max CPU cycles  | 53 |
| Avg CPU cycles  | 53 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                         |
|------------------|-------------------------|
| Tolerance Toggle | $\pm 0,0000\text{e+}00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 418 |
| Max CPU cycles  | 467 |
| Avg CPU cycles  | 427 |

**Verification: ManualSwitch Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block ManualSwitch.

| Test results   |     |     |     |     |
|----------------|-----|-----|-----|-----|
| Time step      | 1   | 2   | ... | 5   |
| CPU cycles     | 38  | 38  | ... | 38  |
| Inputs         |     |     |     |     |
| In1 (DSP)      | 0   | 0.1 | ... | 0.4 |
| In2 (DSP)      | 0.1 | 0.2 | ... | 0.5 |
| In1            | 0   | 0.1 | ... | 0.4 |
| In2            | 0.1 | 0.2 | ... | 0.5 |
| Parameters     |     |     |     |     |
| Toggle         | 0   |     |     |     |
| Outputs        |     |     |     |     |
| Out            | 0   | 0.1 | ... | 0.4 |
| Exp. Out       | 0   | 0.1 | ... | 0.4 |
| Out (DSP)      | 0   | 0.1 | ... | 0.4 |
| Exp. Out (DSP) | 0   | 0.1 | ... | 0.4 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 1,5259e-05$ ( $\pm 32768$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 38 |
| Max CPU cycles  | 38 |
| Avg CPU cycles  | 38 |

**Test case: Parameter test****OK**

Parameter test for General block ManualSwitch.

| Test results   |     |     |     |     |
|----------------|-----|-----|-----|-----|
| Time step      | 1   | 2   | ... | 10  |
| CPU cycles     | 38  | 38  | ... | 38  |
| Inputs         |     |     |     |     |
| In1 (DSP)      | 0.3 |     |     |     |
| In2 (DSP)      | 0.6 |     |     |     |
| In1            | 0.3 |     |     |     |
| In2            | 0.6 |     |     |     |
| Parameters     |     |     |     |     |
| Toggle         | 0   | 0.1 | ... | -3  |
| Outputs        |     |     |     |     |
| Out            | 0.3 | 0.6 | ... | 0.6 |
| Exp. Out       | 0.3 | 0.6 | ... | 0.6 |
| Out (DSP)      | 0.3 | 0.6 | ... | 0.6 |
| Exp. Out (DSP) | 0.3 | 0.6 | ... | 0.6 |

| Test settings |                                            |
|---------------|--------------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}05$ ( $\pm 32768$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 38 |
| Max CPU cycles  | 38 |
| Avg CPU cycles  | 38 |

### Test case: Conversion test

OK

Conversion test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                         |
|------------------|-------------------------|
| Tolerance Toggle | $\pm 0,0000\text{e+}00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block ManualSwitch.

| Test results          |   |     |   |   |     |    |
|-----------------------|---|-----|---|---|-----|----|
| Time step             | 1 | 2   | 3 | 4 | ... | 10 |
| Mask parameters       |   |     |   |   |     |    |
| Toggle                | 0 | 0.1 | 1 | 2 | ... | -3 |
| Controller parameters |   |     |   |   |     |    |
| Toggle                | 0 | 1   | 1 | 1 | ... | 1  |
| Exp. Toggle           | 0 | 1   | 1 | 1 | ... | 1  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance Toggle | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 620 |
| Max CPU cycles  | 652 |
| Avg CPU cycles  | 645 |

## Block: Maximum

---



Outputs the greater value of the two input signals.

| Inports |          |
|---------|----------|
| In1     | Input #1 |
| In2     | Input #2 |

| Outports |                                  |
|----------|----------------------------------|
| Out      | Maximum of Input #1 and Input #2 |

### Description:

Calculation:

$$\text{Out} = \max(\text{In}_1, \text{In}_2)$$

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In1               | int16 |
| In2               | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

---

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In1               | int32 |
| In2               | int32 |



| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In1               | float32 |
| In2               | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In1               | float64 |
| In2               | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: Maximum FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block Maximum.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 64     | 64     | 64     | 64     | ... | 63    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In1 (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>In2 (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>In1</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>In2</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <b>Exp. Out</b>       | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <b>Out (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 32767  | 32150  | 31531  | 30913  | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 63 |
| Max CPU cycles  | 64 |
| Avg CPU cycles  | 63 |

**Verification: Maximum FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block Maximum.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 27     | 27     | 27     | 27     | ... | 27    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In1 (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>In2 (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>In1</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>In2</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <b>Exp. Out</b>       | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <b>Out (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 32767  | 32150  | 31531  | 30913  | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 27 |
| Max CPU cycles  | 27 |
| Avg CPU cycles  | 27 |

**Verification: Maximum FiP16 CPU STM32G474RE**

Date of Test 2026-06-19  
Target controller STM32G474RE

**Test case: Inport test****OK**

Inport test for General block Maximum.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 214   |
| CPU cycles     | 62     | 62     | 62     | 62     | ... | 62    |
| Inputs         |        |        |        |        |     |       |
| In1 (DSP)      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| In2 (DSP)      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| In1            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| In2            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| Outputs        |        |        |        |        |     |       |
| Out            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| Exp. Out       | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| Out (DSP)      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| Exp. Out (DSP) | 32767  | 32150  | 31531  | 30913  | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 62 |
| Avg CPU cycles  | 62 |

**Verification: Maximum FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block Maximum.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 66     | 66     | 66     | 66     | ... | 67    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In1 (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>In2 (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>In1</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>In2</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <b>Exp. Out</b>       | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <b>Out (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 32767  | 32150  | 31531  | 30913  | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 66 |
| Max CPU cycles  | 67 |
| Avg CPU cycles  | 66 |

**Verification: Maximum FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block Maximum.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 35     | 35     | 35     | 35     | ... | 35    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In1 (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>In2 (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>In1</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>In2</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <b>Exp. Out</b>       | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <b>Out (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 32767  | 32150  | 31531  | 30913  | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 35 |
| Max CPU cycles  | 35 |
| Avg CPU cycles  | 35 |

**Verification: Maximum FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block Maximum.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 46     | 46     | 46     | 46     | ... | 49    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In1 (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>In2 (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>In1</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>In2</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <b>Exp. Out</b>       | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <b>Out (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 32767  | 32150  | 31531  | 30913  | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 46 |
| Max CPU cycles  | 49 |
| Avg CPU cycles  | 48 |

**Verification: Maximum FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block Maximum.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 75     | 64     | 64     | 64     | ... | 64    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In1 (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>In2 (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>In1</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>In2</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <b>Exp. Out</b>       | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <b>Out (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 32767  | 32150  | 31531  | 30913  | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 64 |
| Max CPU cycles  | 75 |
| Avg CPU cycles  | 64 |



**Verification: Maximum FiP16 CPU TMS320F28379D**

Date of Test 2026-06-22  
Target controller TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block Maximum.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 214   |
| CPU cycles     | 49     | 49     | 49     | 49     | ... | 44    |
| Inputs         |        |        |        |        |     |       |
| In1 (DSP)      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| In2 (DSP)      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| In1            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| In2            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| Outputs        |        |        |        |        |     |       |
| Out            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| Exp. Out       | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| Out (DSP)      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| Exp. Out (DSP) | 32767  | 32150  | 31531  | 30913  | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 44 |
| Max CPU cycles  | 49 |
| Avg CPU cycles  | 45 |

**Verification: Maximum FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block Maximum.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 66          | 66          | ... | 65         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 0.981       | ... | 1          |
| <b>Exp. Out</b>       | 1           | 0.981       | ... | 1          |
| <b>Out (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2106965089  | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 65 |
| Max CPU cycles  | 66 |
| Avg CPU cycles  | 65 |

**Verification: Maximum FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block Maximum.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 27          | 27          | ... | 27         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 0.981       | ... | 1          |
| <b>Exp. Out</b>       | 1           | 0.981       | ... | 1          |
| <b>Out (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2106965089  | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 27 |
| Max CPU cycles  | 27 |
| Avg CPU cycles  | 27 |

**Verification: Maximum FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block Maximum.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 57          | 57          | ... | 57         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 0.981       | ... | 1          |
| <b>Exp. Out</b>       | 1           | 0.981       | ... | 1          |
| <b>Out (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2106965089  | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 65 |
| Avg CPU cycles  | 57 |

**Verification: Maximum FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block Maximum.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 53          | 53          | ... | 54         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 0.981       | ... | 1          |
| <b>Exp. Out</b>       | 1           | 0.981       | ... | 1          |
| <b>Out (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2106965089  | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 53 |
| Max CPU cycles  | 54 |
| Avg CPU cycles  | 53 |

**Verification: Maximum FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block Maximum.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 33          | 33          | ... | 33         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 0.981       | ... | 1          |
| <b>Exp. Out</b>       | 1           | 0.981       | ... | 1          |
| <b>Out (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2106965089  | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 33 |
| Max CPU cycles  | 33 |
| Avg CPU cycles  | 33 |

**Verification: Maximum FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block Maximum.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 50          | 50          | ... | 53         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 0.981       | ... | 1          |
| <b>Exp. Out</b>       | 1           | 0.981       | ... | 1          |
| <b>Out (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2106965089  | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 50 |
| Max CPU cycles  | 53 |
| Avg CPU cycles  | 52 |

**Verification: Maximum FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block Maximum.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 57          | 57          | ... | 57         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 0.981       | ... | 1          |
| <b>Exp. Out</b>       | 1           | 0.981       | ... | 1          |
| <b>Out (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2106965089  | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 57 |



**Verification: Maximum FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block Maximum.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 49          | 49          | ... | 51         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 0.981       | ... | 1          |
| <b>Exp. Out</b>       | 1           | 0.981       | ... | 1          |
| <b>Out (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2106965089  | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 49 |
| Max CPU cycles  | 51 |
| Avg CPU cycles  | 50 |

**Verification: Maximum Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block Maximum.

| Test results          |    |        |     |     |
|-----------------------|----|--------|-----|-----|
| <b>Time step</b>      | 1  | 2      | ... | 214 |
| <b>CPU cycles</b>     | 58 | 58     | ... | 58  |
| <i>Inputs</i>         |    |        |     |     |
| <b>In1 (DSP)</b>      | -1 | -0.981 | ... | 1   |
| <b>In2 (DSP)</b>      | 1  | 0.981  | ... | 1   |
| <b>In1</b>            | -1 | -0.981 | ... | 1   |
| <b>In2</b>            | 1  | 0.981  | ... | 1   |
| <i>Outputs</i>        |    |        |     |     |
| <b>Out</b>            | 1  | 0.981  | ... | 1   |
| <b>Exp. Out</b>       | 1  | 0.981  | ... | 1   |
| <b>Out (DSP)</b>      | 1  | 0.981  | ... | 1   |
| <b>Exp. Out (DSP)</b> | 1  | 0.981  | ... | 1   |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 58 |
| Max CPU cycles  | 58 |
| Avg CPU cycles  | 58 |

**Verification: Maximum Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block Maximum.

| Test results          |    |        |     |     |
|-----------------------|----|--------|-----|-----|
| <b>Time step</b>      | 1  | 2      | ... | 214 |
| <b>CPU cycles</b>     | 31 | 31     | ... | 33  |
| <i>Inputs</i>         |    |        |     |     |
| <b>In1 (DSP)</b>      | -1 | -0.981 | ... | 1   |
| <b>In2 (DSP)</b>      | 1  | 0.981  | ... | 1   |
| <b>In1</b>            | -1 | -0.981 | ... | 1   |
| <b>In2</b>            | 1  | 0.981  | ... | 1   |
| <i>Outputs</i>        |    |        |     |     |
| <b>Out</b>            | 1  | 0.981  | ... | 1   |
| <b>Exp. Out</b>       | 1  | 0.981  | ... | 1   |
| <b>Out (DSP)</b>      | 1  | 0.981  | ... | 1   |
| <b>Exp. Out (DSP)</b> | 1  | 0.981  | ... | 1   |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 33 |
| Avg CPU cycles  | 32 |

**Verification: Maximum Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block Maximum.

| Test results          |    |        |     |     |
|-----------------------|----|--------|-----|-----|
| <b>Time step</b>      | 1  | 2      | ... | 214 |
| <b>CPU cycles</b>     | 72 | 72     | ... | 72  |
| <i>Inputs</i>         |    |        |     |     |
| <b>In1 (DSP)</b>      | -1 | -0.981 | ... | 1   |
| <b>In2 (DSP)</b>      | 1  | 0.981  | ... | 1   |
| <b>In1</b>            | -1 | -0.981 | ... | 1   |
| <b>In2</b>            | 1  | 0.981  | ... | 1   |
| <i>Outputs</i>        |    |        |     |     |
| <b>Out</b>            | 1  | 0.981  | ... | 1   |
| <b>Exp. Out</b>       | 1  | 0.981  | ... | 1   |
| <b>Out (DSP)</b>      | 1  | 0.981  | ... | 1   |
| <b>Exp. Out (DSP)</b> | 1  | 0.981  | ... | 1   |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 72 |
| Max CPU cycles  | 72 |
| Avg CPU cycles  | 72 |

**Verification: Maximum Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block Maximum.

| Test results          |     |        |     |     |
|-----------------------|-----|--------|-----|-----|
| <b>Time step</b>      | 1   | 2      | ... | 214 |
| <b>CPU cycles</b>     | 136 | 136    | ... | 150 |
| <i>Inputs</i>         |     |        |     |     |
| <b>In1 (DSP)</b>      | -1  | -0.981 | ... | 1   |
| <b>In2 (DSP)</b>      | 1   | 0.981  | ... | 1   |
| <b>In1</b>            | -1  | -0.981 | ... | 1   |
| <b>In2</b>            | 1   | 0.981  | ... | 1   |
| <i>Outputs</i>        |     |        |     |     |
| <b>Out</b>            | 1   | 0.981  | ... | 1   |
| <b>Exp. Out</b>       | 1   | 0.981  | ... | 1   |
| <b>Out (DSP)</b>      | 1   | 0.981  | ... | 1   |
| <b>Exp. Out (DSP)</b> | 1   | 0.981  | ... | 1   |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 136 |
| Max CPU cycles  | 202 |
| Avg CPU cycles  | 143 |

**Verification: Maximum Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block Maximum.

| Test results          |    |        |     |     |
|-----------------------|----|--------|-----|-----|
| <b>Time step</b>      | 1  | 2      | ... | 214 |
| <b>CPU cycles</b>     | 85 | 85     | ... | 85  |
| <i>Inputs</i>         |    |        |     |     |
| <b>In1 (DSP)</b>      | -1 | -0.981 | ... | 1   |
| <b>In2 (DSP)</b>      | 1  | 0.981  | ... | 1   |
| <b>In1</b>            | -1 | -0.981 | ... | 1   |
| <b>In2</b>            | 1  | 0.981  | ... | 1   |
| <i>Outputs</i>        |    |        |     |     |
| <b>Out</b>            | 1  | 0.981  | ... | 1   |
| <b>Exp. Out</b>       | 1  | 0.981  | ... | 1   |
| <b>Out (DSP)</b>      | 1  | 0.981  | ... | 1   |
| <b>Exp. Out (DSP)</b> | 1  | 0.981  | ... | 1   |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 63 |
| Max CPU cycles  | 88 |
| Avg CPU cycles  | 86 |

**Verification: Maximum Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block Maximum.

| Test results          |     |        |     |     |
|-----------------------|-----|--------|-----|-----|
| <b>Time step</b>      | 1   | 2      | ... | 214 |
| <b>CPU cycles</b>     | 157 | 157    | ... | 162 |
| <i>Inputs</i>         |     |        |     |     |
| <b>In1 (DSP)</b>      | -1  | -0.981 | ... | 1   |
| <b>In2 (DSP)</b>      | 1   | 0.981  | ... | 1   |
| <b>In1</b>            | -1  | -0.981 | ... | 1   |
| <b>In2</b>            | 1   | 0.981  | ... | 1   |
| <i>Outputs</i>        |     |        |     |     |
| <b>Out</b>            | 1   | 0.981  | ... | 1   |
| <b>Exp. Out</b>       | 1   | 0.981  | ... | 1   |
| <b>Out (DSP)</b>      | 1   | 0.981  | ... | 1   |
| <b>Exp. Out (DSP)</b> | 1   | 0.981  | ... | 1   |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 157 |
| Max CPU cycles  | 166 |
| Avg CPU cycles  | 160 |

**Verification: Maximum Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block Maximum.

| Test results          |    |        |     |     |
|-----------------------|----|--------|-----|-----|
| <b>Time step</b>      | 1  | 2      | ... | 214 |
| <b>CPU cycles</b>     | 70 | 59     | ... | 59  |
| <i>Inputs</i>         |    |        |     |     |
| <b>In1 (DSP)</b>      | -1 | -0.981 | ... | 1   |
| <b>In2 (DSP)</b>      | 1  | 0.981  | ... | 1   |
| <b>In1</b>            | -1 | -0.981 | ... | 1   |
| <b>In2</b>            | 1  | 0.981  | ... | 1   |
| <i>Outputs</i>        |    |        |     |     |
| <b>Out</b>            | 1  | 0.981  | ... | 1   |
| <b>Exp. Out</b>       | 1  | 0.981  | ... | 1   |
| <b>Out (DSP)</b>      | 1  | 0.981  | ... | 1   |
| <b>Exp. Out (DSP)</b> | 1  | 0.981  | ... | 1   |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 70 |
| Avg CPU cycles  | 59 |



**Verification: Maximum Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block Maximum.

| Test results          |    |        |     |     |
|-----------------------|----|--------|-----|-----|
| <b>Time step</b>      | 1  | 2      | ... | 214 |
| <b>CPU cycles</b>     | 42 | 42     | ... | 42  |
| <i>Inputs</i>         |    |        |     |     |
| <b>In1 (DSP)</b>      | -1 | -0.981 | ... | 1   |
| <b>In2 (DSP)</b>      | 1  | 0.981  | ... | 1   |
| <b>In1</b>            | -1 | -0.981 | ... | 1   |
| <b>In2</b>            | 1  | 0.981  | ... | 1   |
| <i>Outputs</i>        |    |        |     |     |
| <b>Out</b>            | 1  | 0.981  | ... | 1   |
| <b>Exp. Out</b>       | 1  | 0.981  | ... | 1   |
| <b>Out (DSP)</b>      | 1  | 0.981  | ... | 1   |
| <b>Exp. Out (DSP)</b> | 1  | 0.981  | ... | 1   |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 42 |
| Max CPU cycles  | 42 |
| Avg CPU cycles  | 42 |

## Block: Minimum

---



Outputs the lesser value of the two input signals.

| Inports |          |
|---------|----------|
| In1     | Input #1 |
| In2     | Input #2 |

| Outports |                                  |
|----------|----------------------------------|
| Out      | Minimum of Input #1 and Input #2 |

### Description:

Calculation:

$$\text{Out} = \min(\text{In}_1, \text{In}_2)$$

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In1               | int16 |
| In2               | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

---

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In1               | int32 |
| In2               | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In1               | float32 |
| In2               | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In1               | float64 |
| In2               | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: Minimum FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block Minimum.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 63     | 63     | 63     | 63     | ... | 63    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In1 (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>In2 (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>In1</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>In2</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Exp. Out</b>       | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Out (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>Exp. Out (DSP)</b> | -32768 | -32150 | -31531 | -30913 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 63 |
| Max CPU cycles  | 64 |
| Avg CPU cycles  | 63 |

**Verification: Minimum FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block Minimum.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 27     | 27     | 27     | 27     | ... | 27    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In1 (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>In2 (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>In1</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>In2</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Exp. Out</b>       | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Out (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>Exp. Out (DSP)</b> | -32768 | -32150 | -31531 | -30913 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 27 |
| Max CPU cycles  | 27 |
| Avg CPU cycles  | 27 |

**Verification: Minimum FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block Minimum.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 62     | 62     | 62     | 62     | ... | 62    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In1 (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>In2 (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>In1</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>In2</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Exp. Out</b>       | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Out (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>Exp. Out (DSP)</b> | -32768 | -32150 | -31531 | -30913 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 62  |
| Max CPU cycles  | 115 |
| Avg CPU cycles  | 62  |

**Verification: Minimum FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block Minimum.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 67     | 67     | 67     | 67     | ... | 67    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In1 (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>In2 (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>In1</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>In2</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Exp. Out</b>       | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Out (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>Exp. Out (DSP)</b> | -32768 | -32150 | -31531 | -30913 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 66  |
| Max CPU cycles  | 127 |
| Avg CPU cycles  | 67  |

**Verification: Minimum FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block Minimum.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 35     | 35     | 35     | 35     | ... | 35    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In1 (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>In2 (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>In1</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>In2</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Exp. Out</b>       | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Out (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>Exp. Out (DSP)</b> | -32768 | -32150 | -31531 | -30913 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 35 |
| Max CPU cycles  | 35 |
| Avg CPU cycles  | 35 |



**Verification: Minimum FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block Minimum.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 49     | 49     | 49     | 49     | ... | 49    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In1 (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>In2 (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>In1</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>In2</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Exp. Out</b>       | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Out (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>Exp. Out (DSP)</b> | -32768 | -32150 | -31531 | -30913 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 46 |
| Max CPU cycles  | 49 |
| Avg CPU cycles  | 48 |

**Verification: Minimum FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block Minimum.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 75     | 64     | 64     | 64     | ... | 64    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In1 (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>In2 (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>In1</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>In2</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Exp. Out</b>       | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Out (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>Exp. Out (DSP)</b> | -32768 | -32150 | -31531 | -30913 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 64 |
| Max CPU cycles  | 75 |
| Avg CPU cycles  | 64 |

**Verification: Minimum FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block Minimum.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 43     | 43     | 43     | 43     | ... | 43    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In1 (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>In2 (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>In1</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>In2</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Exp. Out</b>       | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Out (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>Exp. Out (DSP)</b> | -32768 | -32150 | -31531 | -30913 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 43 |
| Max CPU cycles  | 48 |
| Avg CPU cycles  | 44 |

**Verification: Minimum FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block Minimum.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 65          | 65          | ... | 65         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -1          | -0.981      | ... | 1          |
| <b>Exp. Out</b>       | -1          | -0.981      | ... | 1          |
| <b>Out (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2106965089 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 65 |
| Max CPU cycles  | 66 |
| Avg CPU cycles  | 65 |

**Verification: Minimum FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block Minimum.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 27          | 27          | ... | 27         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -1          | -0.981      | ... | 1          |
| <b>Exp. Out</b>       | -1          | -0.981      | ... | 1          |
| <b>Out (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2106965089 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 27 |
| Max CPU cycles  | 27 |
| Avg CPU cycles  | 27 |

**Verification: Minimum FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block Minimum.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 62          | 62          | ... | 62         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -1          | -0.981      | ... | 1          |
| <b>Exp. Out</b>       | -1          | -0.981      | ... | 1          |
| <b>Out (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2106965089 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 65 |
| Avg CPU cycles  | 62 |

**Verification: Minimum FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block Minimum.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 54          | 54          | ... | 54         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -1          | -0.981      | ... | 1          |
| <b>Exp. Out</b>       | -1          | -0.981      | ... | 1          |
| <b>Out (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2106965089 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 53 |
| Max CPU cycles  | 54 |
| Avg CPU cycles  | 53 |

**Verification: Minimum FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block Minimum.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 33          | 33          | ... | 33         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -1          | -0.981      | ... | 1          |
| <b>Exp. Out</b>       | -1          | -0.981      | ... | 1          |
| <b>Out (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2106965089 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 33 |
| Max CPU cycles  | 33 |
| Avg CPU cycles  | 33 |



**Verification: Minimum FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block Minimum.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 53          | 53          | ... | 53         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -1          | -0.981      | ... | 1          |
| <b>Exp. Out</b>       | -1          | -0.981      | ... | 1          |
| <b>Out (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2106965089 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 50 |
| Max CPU cycles  | 53 |
| Avg CPU cycles  | 52 |

**Verification: Minimum FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block Minimum.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 68          | 57          | ... | 57         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -1          | -0.981      | ... | 1          |
| <b>Exp. Out</b>       | -1          | -0.981      | ... | 1          |
| <b>Out (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2106965089 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 68 |
| Avg CPU cycles  | 57 |

**Verification: Minimum FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block Minimum.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 51          | 51          | ... | 51         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -1          | -0.981      | ... | 1          |
| <b>Exp. Out</b>       | -1          | -0.981      | ... | 1          |
| <b>Out (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2106965089 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 49 |
| Max CPU cycles  | 51 |
| Avg CPU cycles  | 50 |

**Verification: Minimum Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block Minimum.

| Test results          |    |        |     |     |
|-----------------------|----|--------|-----|-----|
| <b>Time step</b>      | 1  | 2      | ... | 214 |
| <b>CPU cycles</b>     | 58 | 58     | ... | 58  |
| <i>Inputs</i>         |    |        |     |     |
| <b>In1 (DSP)</b>      | -1 | -0.981 | ... | 1   |
| <b>In2 (DSP)</b>      | 1  | 0.981  | ... | 1   |
| <b>In1</b>            | -1 | -0.981 | ... | 1   |
| <b>In2</b>            | 1  | 0.981  | ... | 1   |
| <i>Outputs</i>        |    |        |     |     |
| <b>Out</b>            | -1 | -0.981 | ... | 1   |
| <b>Exp. Out</b>       | -1 | -0.981 | ... | 1   |
| <b>Out (DSP)</b>      | -1 | -0.981 | ... | 1   |
| <b>Exp. Out (DSP)</b> | -1 | -0.981 | ... | 1   |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 58 |
| Max CPU cycles  | 58 |
| Avg CPU cycles  | 58 |

**Verification: Minimum Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block Minimum.

| Test results          |    |        |     |     |
|-----------------------|----|--------|-----|-----|
| <b>Time step</b>      | 1  | 2      | ... | 214 |
| <b>CPU cycles</b>     | 33 | 33     | ... | 33  |
| <i>Inputs</i>         |    |        |     |     |
| <b>In1 (DSP)</b>      | -1 | -0.981 | ... | 1   |
| <b>In2 (DSP)</b>      | 1  | 0.981  | ... | 1   |
| <b>In1</b>            | -1 | -0.981 | ... | 1   |
| <b>In2</b>            | 1  | 0.981  | ... | 1   |
| <i>Outputs</i>        |    |        |     |     |
| <b>Out</b>            | -1 | -0.981 | ... | 1   |
| <b>Exp. Out</b>       | -1 | -0.981 | ... | 1   |
| <b>Out (DSP)</b>      | -1 | -0.981 | ... | 1   |
| <b>Exp. Out (DSP)</b> | -1 | -0.981 | ... | 1   |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 33 |
| Avg CPU cycles  | 32 |

**Verification: Minimum Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block Minimum.

| Test results          |    |        |     |     |
|-----------------------|----|--------|-----|-----|
| <b>Time step</b>      | 1  | 2      | ... | 214 |
| <b>CPU cycles</b>     | 67 | 67     | ... | 67  |
| <i>Inputs</i>         |    |        |     |     |
| <b>In1 (DSP)</b>      | -1 | -0.981 | ... | 1   |
| <b>In2 (DSP)</b>      | 1  | 0.981  | ... | 1   |
| <b>In1</b>            | -1 | -0.981 | ... | 1   |
| <b>In2</b>            | 1  | 0.981  | ... | 1   |
| <i>Outputs</i>        |    |        |     |     |
| <b>Out</b>            | -1 | -0.981 | ... | 1   |
| <b>Exp. Out</b>       | -1 | -0.981 | ... | 1   |
| <b>Out (DSP)</b>      | -1 | -0.981 | ... | 1   |
| <b>Exp. Out (DSP)</b> | -1 | -0.981 | ... | 1   |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 67 |
| Max CPU cycles  | 67 |
| Avg CPU cycles  | 67 |

**Verification: Minimum Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block Minimum.

| Test results          |     |        |     |     |
|-----------------------|-----|--------|-----|-----|
| <b>Time step</b>      | 1   | 2      | ... | 214 |
| <b>CPU cycles</b>     | 142 | 142    | ... | 150 |
| <i>Inputs</i>         |     |        |     |     |
| <b>In1 (DSP)</b>      | -1  | -0.981 | ... | 1   |
| <b>In2 (DSP)</b>      | 1   | 0.981  | ... | 1   |
| <b>In1</b>            | -1  | -0.981 | ... | 1   |
| <b>In2</b>            | 1   | 0.981  | ... | 1   |
| <i>Outputs</i>        |     |        |     |     |
| <b>Out</b>            | -1  | -0.981 | ... | 1   |
| <b>Exp. Out</b>       | -1  | -0.981 | ... | 1   |
| <b>Out (DSP)</b>      | -1  | -0.981 | ... | 1   |
| <b>Exp. Out (DSP)</b> | -1  | -0.981 | ... | 1   |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 134 |
| Max CPU cycles  | 150 |
| Avg CPU cycles  | 145 |

**Verification: Minimum Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block Minimum.

| Test results          |    |        |     |     |
|-----------------------|----|--------|-----|-----|
| <b>Time step</b>      | 1  | 2      | ... | 214 |
| <b>CPU cycles</b>     | 85 | 85     | ... | 85  |
| <i>Inputs</i>         |    |        |     |     |
| <b>In1 (DSP)</b>      | -1 | -0.981 | ... | 1   |
| <b>In2 (DSP)</b>      | 1  | 0.981  | ... | 1   |
| <b>In1</b>            | -1 | -0.981 | ... | 1   |
| <b>In2</b>            | 1  | 0.981  | ... | 1   |
| <i>Outputs</i>        |    |        |     |     |
| <b>Out</b>            | -1 | -0.981 | ... | 1   |
| <b>Exp. Out</b>       | -1 | -0.981 | ... | 1   |
| <b>Out (DSP)</b>      | -1 | -0.981 | ... | 1   |
| <b>Exp. Out (DSP)</b> | -1 | -0.981 | ... | 1   |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 63 |
| Max CPU cycles  | 88 |
| Avg CPU cycles  | 86 |



**Verification: Minimum Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block Minimum.

| Test results          |     |        |     |     |
|-----------------------|-----|--------|-----|-----|
| <b>Time step</b>      | 1   | 2      | ... | 214 |
| <b>CPU cycles</b>     | 160 | 160    | ... | 162 |
| <i>Inputs</i>         |     |        |     |     |
| <b>In1 (DSP)</b>      | -1  | -0.981 | ... | 1   |
| <b>In2 (DSP)</b>      | 1   | 0.981  | ... | 1   |
| <b>In1</b>            | -1  | -0.981 | ... | 1   |
| <b>In2</b>            | 1   | 0.981  | ... | 1   |
| <i>Outputs</i>        |     |        |     |     |
| <b>Out</b>            | -1  | -0.981 | ... | 1   |
| <b>Exp. Out</b>       | -1  | -0.981 | ... | 1   |
| <b>Out (DSP)</b>      | -1  | -0.981 | ... | 1   |
| <b>Exp. Out (DSP)</b> | -1  | -0.981 | ... | 1   |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 157 |
| Max CPU cycles  | 166 |
| Avg CPU cycles  | 160 |

**Verification: Minimum Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block Minimum.

| Test results          |    |        |     |     |
|-----------------------|----|--------|-----|-----|
| <b>Time step</b>      | 1  | 2      | ... | 214 |
| <b>CPU cycles</b>     | 70 | 59     | ... | 59  |
| <i>Inputs</i>         |    |        |     |     |
| <b>In1 (DSP)</b>      | -1 | -0.981 | ... | 1   |
| <b>In2 (DSP)</b>      | 1  | 0.981  | ... | 1   |
| <b>In1</b>            | -1 | -0.981 | ... | 1   |
| <b>In2</b>            | 1  | 0.981  | ... | 1   |
| <i>Outputs</i>        |    |        |     |     |
| <b>Out</b>            | -1 | -0.981 | ... | 1   |
| <b>Exp. Out</b>       | -1 | -0.981 | ... | 1   |
| <b>Out (DSP)</b>      | -1 | -0.981 | ... | 1   |
| <b>Exp. Out (DSP)</b> | -1 | -0.981 | ... | 1   |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 70 |
| Avg CPU cycles  | 59 |

**Verification: Minimum Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block Minimum.

| Test results          |    |        |     |     |
|-----------------------|----|--------|-----|-----|
| <b>Time step</b>      | 1  | 2      | ... | 214 |
| <b>CPU cycles</b>     | 40 | 40     | ... | 40  |
| <i>Inputs</i>         |    |        |     |     |
| <b>In1 (DSP)</b>      | -1 | -0.981 | ... | 1   |
| <b>In2 (DSP)</b>      | 1  | 0.981  | ... | 1   |
| <b>In1</b>            | -1 | -0.981 | ... | 1   |
| <b>In2</b>            | 1  | 0.981  | ... | 1   |
| <i>Outputs</i>        |    |        |     |     |
| <b>Out</b>            | -1 | -0.981 | ... | 1   |
| <b>Exp. Out</b>       | -1 | -0.981 | ... | 1   |
| <b>Out (DSP)</b>      | -1 | -0.981 | ... | 1   |
| <b>Exp. Out (DSP)</b> | -1 | -0.981 | ... | 1   |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 40 |
| Max CPU cycles  | 40 |
| Avg CPU cycles  | 40 |

## Block: Not

---



Logical inverter block.

| Inports |  |
|---------|--|
| In      |  |

| Outports |  |
|----------|--|
| Out      |  |

### Implementations:

**Bool**    Boolean Implementation

### Implementation: Bool

---

Boolean Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | bool |

| Outports Data Type |      |
|--------------------|------|
| Out                | bool |

**Verification: Not Bool CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block Not.

| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 9  |
| <b>CPU cycles</b>     | 58 | 58 | 58   | 58   | ... | 58 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In (DSP)</b>       | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In</b>             | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 1  | 1  | 1    | 1    | ... | 0  |
| <b>Exp. Out</b>       | 1  | 1  | 1    | 1    | ... | 0  |
| <b>Out (DSP)</b>      | 1  | 1  | 1    | 1    | ... | 0  |
| <b>Exp. Out (DSP)</b> | 1  | 1  | 1    | 1    | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 58 |
| Max CPU cycles  | 58 |
| Avg CPU cycles  | 58 |

**Verification: Not Bool CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block Not.

| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 9  |
| <b>CPU cycles</b>     | 29 | 29 | 29   | 29   | ... | 29 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In (DSP)</b>       | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In</b>             | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 1  | 1  | 1    | 1    | ... | 0  |
| <b>Exp. Out</b>       | 1  | 1  | 1    | 1    | ... | 0  |
| <b>Out (DSP)</b>      | 1  | 1  | 1    | 1    | ... | 0  |
| <b>Exp. Out (DSP)</b> | 1  | 1  | 1    | 1    | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 29 |
| Avg CPU cycles  | 29 |

**Verification: Not Bool CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block Not.

| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 9  |
| <b>CPU cycles</b>     | 57 | 57 | 57   | 57   | ... | 57 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In (DSP)</b>       | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In</b>             | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 1  | 1  | 1    | 1    | ... | 0  |
| <b>Exp. Out</b>       | 1  | 1  | 1    | 1    | ... | 0  |
| <b>Out (DSP)</b>      | 1  | 1  | 1    | 1    | ... | 0  |
| <b>Exp. Out (DSP)</b> | 1  | 1  | 1    | 1    | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 57 |

**Verification: Not Bool CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block Not.

| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 9  |
| <b>CPU cycles</b>     | 48 | 48 | 48   | 48   | ... | 48 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In (DSP)</b>       | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In</b>             | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 1  | 1  | 1    | 1    | ... | 0  |
| <b>Exp. Out</b>       | 1  | 1  | 1    | 1    | ... | 0  |
| <b>Out (DSP)</b>      | 1  | 1  | 1    | 1    | ... | 0  |
| <b>Exp. Out (DSP)</b> | 1  | 1  | 1    | 1    | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 48 |
| Max CPU cycles  | 48 |
| Avg CPU cycles  | 48 |



**Verification: Not Bool CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block Not.

| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 9  |
| <b>CPU cycles</b>     | 29 | 29 | 29   | 29   | ... | 29 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In (DSP)</b>       | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In</b>             | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 1  | 1  | 1    | 1    | ... | 0  |
| <b>Exp. Out</b>       | 1  | 1  | 1    | 1    | ... | 0  |
| <b>Out (DSP)</b>      | 1  | 1  | 1    | 1    | ... | 0  |
| <b>Exp. Out (DSP)</b> | 1  | 1  | 1    | 1    | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 29 |
| Avg CPU cycles  | 29 |

**Verification: Not Bool CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block Not.

| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 9  |
| <b>CPU cycles</b>     | 42 | 42 | 42   | 42   | ... | 42 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In (DSP)</b>       | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In</b>             | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 1  | 1  | 1    | 1    | ... | 0  |
| <b>Exp. Out</b>       | 1  | 1  | 1    | 1    | ... | 0  |
| <b>Out (DSP)</b>      | 1  | 1  | 1    | 1    | ... | 0  |
| <b>Exp. Out (DSP)</b> | 1  | 1  | 1    | 1    | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 42 |
| Max CPU cycles  | 42 |
| Avg CPU cycles  | 42 |

**Verification: Not Bool CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block Not.

| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 9  |
| <b>CPU cycles</b>     | 64 | 56 | 56   | 56   | ... | 56 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In (DSP)</b>       | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In</b>             | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 1  | 1  | 1    | 1    | ... | 0  |
| <b>Exp. Out</b>       | 1  | 1  | 1    | 1    | ... | 0  |
| <b>Out (DSP)</b>      | 1  | 1  | 1    | 1    | ... | 0  |
| <b>Exp. Out (DSP)</b> | 1  | 1  | 1    | 1    | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 64 |
| Avg CPU cycles  | 56 |

**Verification: Not Bool CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block Not.


| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 9  |
| <b>CPU cycles</b>     | 40 | 40 | 40   | 40   | ... | 40 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In (DSP)</b>       | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In</b>             | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 1  | 1  | 1    | 1    | ... | 0  |
| <b>Exp. Out</b>       | 1  | 1  | 1    | 1    | ... | 0  |
| <b>Out (DSP)</b>      | 1  | 1  | 1    | 1    | ... | 0  |
| <b>Exp. Out (DSP)</b> | 1  | 1  | 1    | 1    | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 40 |
| Max CPU cycles  | 40 |
| Avg CPU cycles  | 40 |

## Block: Or

---



Logical OR block.

| Inports |  |
|---------|--|
| In1     |  |
| In2     |  |

| Outports |  |
|----------|--|
| Out      |  |

### Implementations:

**Bool**     Boolean Implementation

### Implementation: Bool

---

Boolean Implementation

| Inports Data Type |      |
|-------------------|------|
| In1               | bool |
| In2               | bool |

| Outports Data Type |      |
|--------------------|------|
| Out                | bool |

**Verification: Or Bool CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block Or.

| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 25 |
| <b>CPU cycles</b>     | 67 | 67 | 67   | 67   | ... | 64 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In1 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In2 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In1</b>            | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <b>In2</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Exp. Out</b>       | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Out (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Exp. Out (DSP)</b> | 0  | 0  | 0    | 0    | ... | 1  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 64 |
| Max CPU cycles  | 67 |
| Avg CPU cycles  | 66 |

**Verification: Or Bool CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block Or.

| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 25 |
| <b>CPU cycles</b>     | 33 | 33 | 33   | 33   | ... | 31 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In1 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In2 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In1</b>            | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <b>In2</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Exp. Out</b>       | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Out (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Exp. Out (DSP)</b> | 0  | 0  | 0    | 0    | ... | 1  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 33 |
| Avg CPU cycles  | 32 |

**Verification: Or Bool CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block Or.

| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 25 |
| <b>CPU cycles</b>     | 57 | 57 | 57   | 57   | ... | 60 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In1 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In2 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In1</b>            | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <b>In2</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Exp. Out</b>       | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Out (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Exp. Out (DSP)</b> | 0  | 0  | 0    | 0    | ... | 1  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 60 |
| Avg CPU cycles  | 57 |



**Verification: Or Bool CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block Or.

| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 25 |
| <b>CPU cycles</b>     | 52 | 52 | 52   | 52   | ... | 50 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In1 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In2 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In1</b>            | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <b>In2</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Exp. Out</b>       | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Out (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Exp. Out (DSP)</b> | 0  | 0  | 0    | 0    | ... | 1  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 50 |
| Max CPU cycles  | 52 |
| Avg CPU cycles  | 51 |

**Verification: Or Bool CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block Or.

| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 25 |
| <b>CPU cycles</b>     | 35 | 35 | 35   | 35   | ... | 30 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In1 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In2 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In1</b>            | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <b>In2</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Exp. Out</b>       | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Out (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Exp. Out (DSP)</b> | 0  | 0  | 0    | 0    | ... | 1  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 30 |
| Max CPU cycles  | 35 |
| Avg CPU cycles  | 34 |

**Verification: Or Bool CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block Or.

| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 25 |
| <b>CPU cycles</b>     | 45 | 45 | 45   | 45   | ... | 45 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In1 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In2 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In1</b>            | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <b>In2</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Exp. Out</b>       | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Out (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Exp. Out (DSP)</b> | 0  | 0  | 0    | 0    | ... | 1  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 45 |
| Max CPU cycles  | 45 |
| Avg CPU cycles  | 45 |

**Verification: Or Bool CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block Or.

| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 25 |
| <b>CPU cycles</b>     | 60 | 60 | 60   | 60   | ... | 58 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In1 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In2 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In1</b>            | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <b>In2</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Exp. Out</b>       | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Out (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Exp. Out (DSP)</b> | 0  | 0  | 0    | 0    | ... | 1  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 58 |
| Max CPU cycles  | 60 |
| Avg CPU cycles  | 59 |

**Verification: Or Bool CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block Or.

| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 25 |
| <b>CPU cycles</b>     | 47 | 47 | 47   | 47   | ... | 47 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In1 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In2 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In1</b>            | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <b>In2</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Exp. Out</b>       | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Out (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>Exp. Out (DSP)</b> | 0  | 0  | 0    | 0    | ... | 1  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 47 |
| Max CPU cycles  | 47 |
| Avg CPU cycles  | 47 |

## Block: Output



### Outputs

|     |                         |
|-----|-------------------------|
| OUT | Signal to frame program |
|-----|-------------------------|


### Mask Parameters

|         |                                                                 |
|---------|-----------------------------------------------------------------|
| ts_fact | Multiplication factor of base sampling time (in integer format) |
| Gain    | Gain value used in simulation                                   |
| Offset  | Offset value used in simulation                                 |

### Description:

Serves as interface to the frame program. The output of this block is intended for simulation purposes and can be left unconnected if not used. Also the parameters *Gain*, and *Offset* are only used during simulation. The schematic for simulation can be seen in the figure below. The Unit Delay block is only used during simulation and should reflect the time delay caused by a discrete controller.

**Note:** Currently, *Gain* and *Offset* parameters are only available in Matlab/Simulink.




### Data Types:

|                |                       |
|----------------|-----------------------|
| <b>bool</b>    | Boolean               |
| <b>int8</b>    | 8 Bit Fixed Point     |
| <b>int16</b>   | 16 Bit Fixed Point    |
| <b>int32</b>   | 32 Bit Fixed Point    |
| <b>float32</b> | 32 Bit Floating Point |
| <b>float64</b> | 64 Bit Floating Point |

## Block: RateLimiter

---



Limitation of rising and falling rate.

Function of Enable:

0: rate limiting disabled, signal is passed through

1: rate limiting enabled, signal is rate limited

0->1: preload of output with value from init input

| Inports |                                                                                                                                                                                         |
|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| In      |                                                                                                                                                                                         |
| Init    | Value which is loaded at rising flanke of enable signal                                                                                                                                 |
| Enable  | Enable == 0: Deactivation of block; Out is set to In.<br>Enable != 0: Activation of block; Out is rate limited.<br>Enable 0->1: Preloading of output; Out is set to value of Init input |

| Outports |  |
|----------|--|
| Out      |  |

| Mask Parameters |    |                                                                 |
|-----------------|----|-----------------------------------------------------------------|
| Name            | ID | Description                                                     |
| Tr              | 1  | Rising time in seconds. Slew rate will be $1/Tr$                |
| Tf              | 2  | Falling time in seconds. Slew rate will be $1/Tf$               |
| ts_fact         | 3  | Multiplication factor of base sampling time (in integer format) |

### Description:

Rising and falling time refer to a step from 0 to 1. Entries for *Tr*: *Rising time* and *Tf*: *Falling time* smaller than the actual sample time will be limited to the sample time internally.

The 16- and 32-Bit fixed point implementations are based on an internal 32-Bit wide slew-rate variable while the 8-Bit fixed point implementation uses a 16-Bit wide slew-rate variable.

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |
| Init              | int16 |
| Enable            | bool  |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |
| Init              | int32 |
| Enable            | bool  |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |
| Init              | float32 |
| Enable            | bool    |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |
| Init              | float64 |
| Enable            | bool    |



| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: RateLimiter FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block RateLimiter.

| Test results   |      |        |        |        |     |       |
|----------------|------|--------|--------|--------|-----|-------|
| Time step      | 1    | 2      | 3      | 4      | ... | 266   |
| CPU cycles     | 81   | 81     | 81     | 81     | ... | 125   |
| Inputs         |      |        |        |        |     |       |
| In (DSP)       | 0    | -32768 | -31508 | -30247 | ... | -6554 |
| Init (DSP)     | 0    | 9830   | 9830   | 9830   | ... | 9830  |
| Enable (DSP)   | 0    | 0      | 0      | 0      | ... | 1     |
| In             | 0    | -1     | -0.962 | -0.923 | ... | -0.2  |
| Init           | 0    | 0.3    | 0.3    | 0.3    | ... | 0.3   |
| Enable         | 0    | 0      | 0      | 0      | ... | 1     |
| Parameters     |      |        |        |        |     |       |
| Tr             | 0.01 |        |        |        |     |       |
| Tf             | 0.03 |        |        |        |     |       |
| ts_fact        | 1    |        |        |        |     |       |
| Outputs        |      |        |        |        |     |       |
| Out            | 0    | -1     | -0.962 | -0.923 | ... | 0.423 |
| Exp. Out       | 0    | -1     | -0.962 | -0.923 | ... | 0.423 |
| Out (DSP)      | 0    | -32768 | -31508 | -30247 | ... | 13871 |
| Exp. Out (DSP) | 0    | -32768 | -31508 | -30247 | ... | 13872 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 81  |
| Max CPU cycles  | 125 |
| Avg CPU cycles  | 106 |

**Test case: Conversion test****OK**

Conversion test for General block RateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block RateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 1,0000e+00$ |
| Tolerance RateDown | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2851 |
| Max CPU cycles  | 2961 |
| Avg CPU cycles  | 2905 |

**Verification: RateLimiter FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block RateLimiter.

| Test results   |      |        |        |        |     |       |
|----------------|------|--------|--------|--------|-----|-------|
| Time step      | 1    | 2      | 3      | 4      | ... | 266   |
| CPU cycles     | 51   | 51     | 51     | 51     | ... | 79    |
| Inputs         |      |        |        |        |     |       |
| In (DSP)       | 0    | -32768 | -31508 | -30247 | ... | -6554 |
| Init (DSP)     | 0    | 9830   | 9830   | 9830   | ... | 9830  |
| Enable (DSP)   | 0    | 0      | 0      | 0      | ... | 1     |
| In             | 0    | -1     | -0.962 | -0.923 | ... | -0.2  |
| Init           | 0    | 0.3    | 0.3    | 0.3    | ... | 0.3   |
| Enable         | 0    | 0      | 0      | 0      | ... | 1     |
| Parameters     |      |        |        |        |     |       |
| Tr             | 0.01 |        |        |        |     |       |
| Tf             | 0.03 |        |        |        |     |       |
| ts_fact        | 1    |        |        |        |     |       |
| Outputs        |      |        |        |        |     |       |
| Out            | 0    | -1     | -0.962 | -0.923 | ... | 0.423 |
| Exp. Out       | 0    | -1     | -0.962 | -0.923 | ... | 0.423 |
| Out (DSP)      | 0    | -32768 | -31508 | -30247 | ... | 13871 |
| Exp. Out (DSP) | 0    | -32768 | -31508 | -30247 | ... | 13872 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 51 |
| Max CPU cycles  | 79 |
| Avg CPU cycles  | 69 |

**Test case: Conversion test****OK**

Conversion test for General block RateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block RateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 1,0000e+00$ |
| Tolerance RateDown | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1087 |
| Max CPU cycles  | 1097 |
| Avg CPU cycles  | 1091 |

**Verification: RateLimiter FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block RateLimiter.

| Test results   |      |        |        |        |     |       |
|----------------|------|--------|--------|--------|-----|-------|
| Time step      | 1    | 2      | 3      | 4      | ... | 266   |
| CPU cycles     | 67   | 67     | 67     | 67     | ... | 131   |
| Inputs         |      |        |        |        |     |       |
| In (DSP)       | 0    | -32768 | -31508 | -30247 | ... | -6554 |
| Init (DSP)     | 0    | 9830   | 9830   | 9830   | ... | 9830  |
| Enable (DSP)   | 0    | 0      | 0      | 0      | ... | 1     |
| In             | 0    | -1     | -0.962 | -0.923 | ... | -0.2  |
| Init           | 0    | 0.3    | 0.3    | 0.3    | ... | 0.3   |
| Enable         | 0    | 0      | 0      | 0      | ... | 1     |
| Parameters     |      |        |        |        |     |       |
| Tr             | 0.01 |        |        |        |     |       |
| Tf             | 0.03 |        |        |        |     |       |
| ts_fact        | 1    |        |        |        |     |       |
| Outputs        |      |        |        |        |     |       |
| Out            | 0    | -1     | -0.962 | -0.923 | ... | 0.423 |
| Exp. Out       | 0    | -1     | -0.962 | -0.923 | ... | 0.423 |
| Out (DSP)      | 0    | -32768 | -31508 | -30247 | ... | 13871 |
| Exp. Out (DSP) | 0    | -32768 | -31508 | -30247 | ... | 13872 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 67  |
| Max CPU cycles  | 131 |
| Avg CPU cycles  | 105 |

**Test case: Conversion test****OK**

Conversion test for General block RateLimiter.



| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block RateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 1,0000e+00$ |
| Tolerance RateDown | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1654 |
| Max CPU cycles  | 1701 |
| Avg CPU cycles  | 1655 |

**Verification: RateLimiter FiP16 CPU STM32F072RB**

Date of Test 2026-06-19  
Target controller STM32F072RB

**Test case: Inport test****OK**

Inport test for General block RateLimiter.

| Test results   |      |        |        |        |     |       |
|----------------|------|--------|--------|--------|-----|-------|
| Time step      | 1    | 2      | 3      | 4      | ... | 266   |
| CPU cycles     | 67   | 67     | 67     | 67     | ... | 105   |
| Inputs         |      |        |        |        |     |       |
| In (DSP)       | 0    | -32768 | -31508 | -30247 | ... | -6554 |
| Init (DSP)     | 0    | 9830   | 9830   | 9830   | ... | 9830  |
| Enable (DSP)   | 0    | 0      | 0      | 0      | ... | 1     |
| In             | 0    | -1     | -0.962 | -0.923 | ... | -0.2  |
| Init           | 0    | 0.3    | 0.3    | 0.3    | ... | 0.3   |
| Enable         | 0    | 0      | 0      | 0      | ... | 1     |
| Parameters     |      |        |        |        |     |       |
| Tr             | 0.01 |        |        |        |     |       |
| Tf             | 0.03 |        |        |        |     |       |
| ts_fact        | 1    |        |        |        |     |       |
| Outputs        |      |        |        |        |     |       |
| Out            | 0    | -1     | -0.962 | -0.923 | ... | 0.423 |
| Exp. Out       | 0    | -1     | -0.962 | -0.923 | ... | 0.423 |
| Out (DSP)      | 0    | -32768 | -31508 | -30247 | ... | 13871 |
| Exp. Out (DSP) | 0    | -32768 | -31508 | -30247 | ... | 13872 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 67  |
| Max CPU cycles  | 166 |
| Avg CPU cycles  | 91  |

**Test case: Conversion test****OK**

Conversion test for General block RateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block RateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 1,0000e+00$ |
| Tolerance RateDown | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 6095 |
| Max CPU cycles  | 6408 |
| Avg CPU cycles  | 6238 |

**Verification: RateLimiter FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block RateLimiter.

| Test results   |      |        |        |        |     |       |
|----------------|------|--------|--------|--------|-----|-------|
| Time step      | 1    | 2      | 3      | 4      | ... | 266   |
| CPU cycles     | 41   | 41     | 41     | 41     | ... | 62    |
| Inputs         |      |        |        |        |     |       |
| In (DSP)       | 0    | -32768 | -31508 | -30247 | ... | -6554 |
| Init (DSP)     | 0    | 9830   | 9830   | 9830   | ... | 9830  |
| Enable (DSP)   | 0    | 0      | 0      | 0      | ... | 1     |
| In             | 0    | -1     | -0.962 | -0.923 | ... | -0.2  |
| Init           | 0    | 0.3    | 0.3    | 0.3    | ... | 0.3   |
| Enable         | 0    | 0      | 0      | 0      | ... | 1     |
| Parameters     |      |        |        |        |     |       |
| Tr             | 0.01 |        |        |        |     |       |
| Tf             | 0.03 |        |        |        |     |       |
| ts_fact        | 1    |        |        |        |     |       |
| Outputs        |      |        |        |        |     |       |
| Out            | 0    | -1     | -0.962 | -0.923 | ... | 0.423 |
| Exp. Out       | 0    | -1     | -0.962 | -0.923 | ... | 0.423 |
| Out (DSP)      | 0    | -32768 | -31508 | -30247 | ... | 13871 |
| Exp. Out (DSP) | 0    | -32768 | -31508 | -30247 | ... | 13872 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 41 |
| Max CPU cycles  | 62 |
| Avg CPU cycles  | 53 |

**Test case: Conversion test****OK**

Conversion test for General block RateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block RateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 1,0000e+00$ |
| Tolerance RateDown | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2067 |
| Max CPU cycles  | 2100 |
| Avg CPU cycles  | 2082 |



**Verification: RateLimiter FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block RateLimiter.

| Test results   |      |        |        |        |     |       |
|----------------|------|--------|--------|--------|-----|-------|
| Time step      | 1    | 2      | 3      | 4      | ... | 266   |
| CPU cycles     | 61   | 61     | 61     | 61     | ... | 82    |
| Inputs         |      |        |        |        |     |       |
| In (DSP)       | 0    | -32768 | -31508 | -30247 | ... | -6554 |
| Init (DSP)     | 0    | 9830   | 9830   | 9830   | ... | 9830  |
| Enable (DSP)   | 0    | 0      | 0      | 0      | ... | 1     |
| In             | 0    | -1     | -0.962 | -0.923 | ... | -0.2  |
| Init           | 0    | 0.3    | 0.3    | 0.3    | ... | 0.3   |
| Enable         | 0    | 0      | 0      | 0      | ... | 1     |
| Parameters     |      |        |        |        |     |       |
| Tr             | 0.01 |        |        |        |     |       |
| Tf             | 0.03 |        |        |        |     |       |
| ts_fact        | 1    |        |        |        |     |       |
| Outputs        |      |        |        |        |     |       |
| Out            | 0    | -1     | -0.962 | -0.923 | ... | 0.423 |
| Exp. Out       | 0    | -1     | -0.962 | -0.923 | ... | 0.423 |
| Out (DSP)      | 0    | -32768 | -31508 | -30247 | ... | 13871 |
| Exp. Out (DSP) | 0    | -32768 | -31508 | -30247 | ... | 13872 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 60 |
| Max CPU cycles  | 82 |
| Avg CPU cycles  | 73 |

**Test case: Conversion test****OK**

Conversion test for General block RateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block RateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 1,0000e+00$ |
| Tolerance RateDown | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 4978 |
| Max CPU cycles  | 5687 |
| Avg CPU cycles  | 5633 |

**Verification: RateLimiter FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block RateLimiter.

| Test results   |      |        |        |        |     |       |
|----------------|------|--------|--------|--------|-----|-------|
| Time step      | 1    | 2      | 3      | 4      | ... | 266   |
| CPU cycles     | 85   | 66     | 66     | 66     | ... | 96    |
| Inputs         |      |        |        |        |     |       |
| In (DSP)       | 0    | -32768 | -31508 | -30247 | ... | -6554 |
| Init (DSP)     | 0    | 9830   | 9830   | 9830   | ... | 9830  |
| Enable (DSP)   | 0    | 0      | 0      | 0      | ... | 1     |
| In             | 0    | -1     | -0.962 | -0.923 | ... | -0.2  |
| Init           | 0    | 0.3    | 0.3    | 0.3    | ... | 0.3   |
| Enable         | 0    | 0      | 0      | 0      | ... | 1     |
| Parameters     |      |        |        |        |     |       |
| Tr             | 0.01 |        |        |        |     |       |
| Tf             | 0.03 |        |        |        |     |       |
| ts_fact        | 1    |        |        |        |     |       |
| Outputs        |      |        |        |        |     |       |
| Out            | 0    | -1     | -0.962 | -0.923 | ... | 0.423 |
| Exp. Out       | 0    | -1     | -0.962 | -0.923 | ... | 0.423 |
| Out (DSP)      | 0    | -32768 | -31508 | -30247 | ... | 13871 |
| Exp. Out (DSP) | 0    | -32768 | -31508 | -30247 | ... | 13872 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 66 |
| Max CPU cycles  | 96 |
| Avg CPU cycles  | 84 |

**Test case: Conversion test****OK**

Conversion test for General block RateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block RateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 1,0000e+00$ |
| Tolerance RateDown | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1354 |
| Max CPU cycles  | 1641 |
| Avg CPU cycles  | 1361 |

**Verification: RateLimiter FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block RateLimiter.

| Test results   |      |        |        |        |     |       |
|----------------|------|--------|--------|--------|-----|-------|
| Time step      | 1    | 2      | 3      | 4      | ... | 266   |
| CPU cycles     | 66   | 66     | 66     | 66     | ... | 124   |
| Inputs         |      |        |        |        |     |       |
| In (DSP)       | 0    | -32768 | -31508 | -30247 | ... | -6554 |
| Init (DSP)     | 0    | 9830   | 9830   | 9830   | ... | 9830  |
| Enable (DSP)   | 0    | 0      | 0      | 0      | ... | 1     |
| In             | 0    | -1     | -0.962 | -0.923 | ... | -0.2  |
| Init           | 0    | 0.3    | 0.3    | 0.3    | ... | 0.3   |
| Enable         | 0    | 0      | 0      | 0      | ... | 1     |
| Parameters     |      |        |        |        |     |       |
| Tr             | 0.01 |        |        |        |     |       |
| Tf             | 0.03 |        |        |        |     |       |
| ts_fact        | 1    |        |        |        |     |       |
| Outputs        |      |        |        |        |     |       |
| Out            | 0    | -1     | -0.962 | -0.923 | ... | 0.423 |
| Exp. Out       | 0    | -1     | -0.962 | -0.923 | ... | 0.423 |
| Out (DSP)      | 0    | -32768 | -31508 | -30247 | ... | 13871 |
| Exp. Out (DSP) | 0    | -32768 | -31508 | -30247 | ... | 13872 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 66  |
| Max CPU cycles  | 124 |
| Avg CPU cycles  | 100 |

**Test case: Conversion test****OK**

Conversion test for General block RateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block RateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 1,0000e+00$ |
| Tolerance RateDown | $\pm 1,0000e+00$ |



| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2164 |
| Max CPU cycles  | 2242 |
| Avg CPU cycles  | 2202 |

**Verification: RateLimiter FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block RateLimiter.

| Test results   |      |             |     |            |
|----------------|------|-------------|-----|------------|
| Time step      | 1    | 2           | ... | 266        |
| CPU cycles     | 82   | 82          | ... | 168        |
| Inputs         |      |             |     |            |
| In (DSP)       | 0    | -2147483648 | ... | -429496730 |
| Init (DSP)     | 0    | 644245094   | ... | 644245094  |
| Enable (DSP)   | 0    | 0           | ... | 1          |
| In             | 0    | -1          | ... | -0.2       |
| Init           | 0    | 0.3         | ... | 0.3        |
| Enable         | 0    | 0           | ... | 1          |
| Parameters     |      |             |     |            |
| Tr             | 0.01 |             |     |            |
| Tf             | 0.03 |             |     |            |
| ts_fact        | 1    |             |     |            |
| Outputs        |      |             |     |            |
| Out            | 0    | -1          | ... | 0.423      |
| Exp. Out       | 0    | -1          | ... | 0.423      |
| Out (DSP)      | 0    | -2147483648 | ... | 909101402  |
| Exp. Out (DSP) | 0    | -2147483648 | ... | 909101411  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 1,8626e-08$ ( $\pm 40$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 82  |
| Max CPU cycles  | 168 |
| Avg CPU cycles  | 136 |

**Test case: Conversion test****OK**

Conversion test for General block RateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block RateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 3,0000e+00$ |
| Tolerance RateDown | $\pm 3,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2851 |
| Max CPU cycles  | 2961 |
| Avg CPU cycles  | 2905 |

**Verification: RateLimiter FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block RateLimiter.

| Test results   |      |             |     |            |
|----------------|------|-------------|-----|------------|
| Time step      | 1    | 2           | ... | 266        |
| CPU cycles     | 49   | 49          | ... | 81         |
| Inputs         |      |             |     |            |
| In (DSP)       | 0    | -2147483648 | ... | -429496730 |
| Init (DSP)     | 0    | 644245094   | ... | 644245094  |
| Enable (DSP)   | 0    | 0           | ... | 1          |
| In             | 0    | -1          | ... | -0.2       |
| Init           | 0    | 0.3         | ... | 0.3        |
| Enable         | 0    | 0           | ... | 1          |
| Parameters     |      |             |     |            |
| Tr             | 0.01 |             |     |            |
| Tf             | 0.03 |             |     |            |
| ts_fact        | 1    |             |     |            |
| Outputs        |      |             |     |            |
| Out            | 0    | -1          | ... | 0.423      |
| Exp. Out       | 0    | -1          | ... | 0.423      |
| Out (DSP)      | 0    | -2147483648 | ... | 909101402  |
| Exp. Out (DSP) | 0    | -2147483648 | ... | 909101411  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 1,8626e-08$ ( $\pm 40$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 49 |
| Max CPU cycles  | 81 |
| Avg CPU cycles  | 70 |

**Test case: Conversion test****OK**

Conversion test for General block RateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block RateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 3,0000e+00$ |
| Tolerance RateDown | $\pm 3,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1087 |
| Max CPU cycles  | 1097 |
| Avg CPU cycles  | 1091 |

**Verification: RateLimiter FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block RateLimiter.

| Test results   |      |             |     |            |
|----------------|------|-------------|-----|------------|
| Time step      | 1    | 2           | ... | 266        |
| CPU cycles     | 57   | 57          | ... | 124        |
| Inputs         |      |             |     |            |
| In (DSP)       | 0    | -2147483648 | ... | -429496730 |
| Init (DSP)     | 0    | 644245094   | ... | 644245094  |
| Enable (DSP)   | 0    | 0           | ... | 1          |
| In             | 0    | -1          | ... | -0.2       |
| Init           | 0    | 0.3         | ... | 0.3        |
| Enable         | 0    | 0           | ... | 1          |
| Parameters     |      |             |     |            |
| Tr             | 0.01 |             |     |            |
| Tf             | 0.03 |             |     |            |
| ts_fact        | 1    |             |     |            |
| Outputs        |      |             |     |            |
| Out            | 0    | -1          | ... | 0.423      |
| Exp. Out       | 0    | -1          | ... | 0.423      |
| Out (DSP)      | 0    | -2147483648 | ... | 909101402  |
| Exp. Out (DSP) | 0    | -2147483648 | ... | 909101411  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 1,8626e-08$ ( $\pm 40$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 57  |
| Max CPU cycles  | 124 |
| Avg CPU cycles  | 101 |

**Test case: Conversion test****OK**

Conversion test for General block RateLimiter.



| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block RateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 3,0000e+00$ |
| Tolerance RateDown | $\pm 3,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1654 |
| Max CPU cycles  | 1659 |
| Avg CPU cycles  | 1654 |

**Verification: RateLimiter FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block RateLimiter.

| Test results   |      |             |     |            |
|----------------|------|-------------|-----|------------|
| Time step      | 1    | 2           | ... | 266        |
| CPU cycles     | 72   | 72          | ... | 121        |
| Inputs         |      |             |     |            |
| In (DSP)       | 0    | -2147483648 | ... | -429496730 |
| Init (DSP)     | 0    | 644245094   | ... | 644245094  |
| Enable (DSP)   | 0    | 0           | ... | 1          |
| In             | 0    | -1          | ... | -0.2       |
| Init           | 0    | 0.3         | ... | 0.3        |
| Enable         | 0    | 0           | ... | 1          |
| Parameters     |      |             |     |            |
| Tr             | 0.01 |             |     |            |
| Tf             | 0.03 |             |     |            |
| ts_fact        | 1    |             |     |            |
| Outputs        |      |             |     |            |
| Out            | 0    | -1          | ... | 0.423      |
| Exp. Out       | 0    | -1          | ... | 0.423      |
| Out (DSP)      | 0    | -2147483648 | ... | 909101402  |
| Exp. Out (DSP) | 0    | -2147483648 | ... | 909101411  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 1,8626e-08$ ( $\pm 40$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 72  |
| Max CPU cycles  | 183 |
| Avg CPU cycles  | 106 |

**Test case: Conversion test****OK**

Conversion test for General block RateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block RateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 3,0000e+00$ |
| Tolerance RateDown | $\pm 3,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 6095 |
| Max CPU cycles  | 6411 |
| Avg CPU cycles  | 6235 |

**Verification: RateLimiter FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block RateLimiter.

| Test results   |      |             |     |            |
|----------------|------|-------------|-----|------------|
| Time step      | 1    | 2           | ... | 266        |
| CPU cycles     | 38   | 38          | ... | 69         |
| Inputs         |      |             |     |            |
| In (DSP)       | 0    | -2147483648 | ... | -429496730 |
| Init (DSP)     | 0    | 644245094   | ... | 644245094  |
| Enable (DSP)   | 0    | 0           | ... | 1          |
| In             | 0    | -1          | ... | -0.2       |
| Init           | 0    | 0.3         | ... | 0.3        |
| Enable         | 0    | 0           | ... | 1          |
| Parameters     |      |             |     |            |
| Tr             | 0.01 |             |     |            |
| Tf             | 0.03 |             |     |            |
| ts_fact        | 1    |             |     |            |
| Outputs        |      |             |     |            |
| Out            | 0    | -1          | ... | 0.423      |
| Exp. Out       | 0    | -1          | ... | 0.423      |
| Out (DSP)      | 0    | -2147483648 | ... | 909101402  |
| Exp. Out (DSP) | 0    | -2147483648 | ... | 909101411  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 1,8626e-08$ ( $\pm 40$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 38 |
| Max CPU cycles  | 69 |
| Avg CPU cycles  | 57 |

**Test case: Conversion test****OK**

Conversion test for General block RateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block RateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 3,0000e+00$ |
| Tolerance RateDown | $\pm 3,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2067 |
| Max CPU cycles  | 2100 |
| Avg CPU cycles  | 2082 |



**Verification: RateLimiter FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block RateLimiter.

| Test results   |      |             |     |            |
|----------------|------|-------------|-----|------------|
| Time step      | 1    | 2           | ... | 266        |
| CPU cycles     | 66   | 66          | ... | 141        |
| Inputs         |      |             |     |            |
| In (DSP)       | 0    | -2147483648 | ... | -429496730 |
| Init (DSP)     | 0    | 644245094   | ... | 644245094  |
| Enable (DSP)   | 0    | 0           | ... | 1          |
| In             | 0    | -1          | ... | -0.2       |
| Init           | 0    | 0.3         | ... | 0.3        |
| Enable         | 0    | 0           | ... | 1          |
| Parameters     |      |             |     |            |
| Tr             | 0.01 |             |     |            |
| Tf             | 0.03 |             |     |            |
| ts_fact        | 1    |             |     |            |
| Outputs        |      |             |     |            |
| Out            | 0    | -1          | ... | 0.423      |
| Exp. Out       | 0    | -1          | ... | 0.423      |
| Out (DSP)      | 0    | -2147483648 | ... | 909101402  |
| Exp. Out (DSP) | 0    | -2147483648 | ... | 909101411  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 1,8626e-08$ ( $\pm 40$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 66  |
| Max CPU cycles  | 141 |
| Avg CPU cycles  | 111 |

**Test case: Conversion test****OK**

Conversion test for General block RateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block RateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 3,0000e+00$ |
| Tolerance RateDown | $\pm 3,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 4978 |
| Max CPU cycles  | 5687 |
| Avg CPU cycles  | 5633 |

**Verification: RateLimiter FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block RateLimiter.

| Test results   |      |             |     |            |
|----------------|------|-------------|-----|------------|
| Time step      | 1    | 2           | ... | 266        |
| CPU cycles     | 76   | 64          | ... | 105        |
| Inputs         |      |             |     |            |
| In (DSP)       | 0    | -2147483648 | ... | -429496730 |
| Init (DSP)     | 0    | 644245094   | ... | 644245094  |
| Enable (DSP)   | 0    | 0           | ... | 1          |
| In             | 0    | -1          | ... | -0.2       |
| Init           | 0    | 0.3         | ... | 0.3        |
| Enable         | 0    | 0           | ... | 1          |
| Parameters     |      |             |     |            |
| Tr             | 0.01 |             |     |            |
| Tf             | 0.03 |             |     |            |
| ts_fact        | 1    |             |     |            |
| Outputs        |      |             |     |            |
| Out            | 0    | -1          | ... | 0.423      |
| Exp. Out       | 0    | -1          | ... | 0.423      |
| Out (DSP)      | 0    | -2147483648 | ... | 909101402  |
| Exp. Out (DSP) | 0    | -2147483648 | ... | 909101411  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 1,8626e-08$ ( $\pm 40$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 64  |
| Max CPU cycles  | 105 |
| Avg CPU cycles  | 91  |

**Test case: Conversion test****OK**

Conversion test for General block RateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block RateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 3,0000e+00$ |
| Tolerance RateDown | $\pm 3,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1391 |
| Max CPU cycles  | 1646 |
| Avg CPU cycles  | 1398 |

**Verification: RateLimiter FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block RateLimiter.

| Test results   |      |             |     |            |
|----------------|------|-------------|-----|------------|
| Time step      | 1    | 2           | ... | 266        |
| CPU cycles     | 61   | 61          | ... | 142        |
| Inputs         |      |             |     |            |
| In (DSP)       | 0    | -2147483648 | ... | -429496730 |
| Init (DSP)     | 0    | 644245094   | ... | 644245094  |
| Enable (DSP)   | 0    | 0           | ... | 1          |
| In             | 0    | -1          | ... | -0.2       |
| Init           | 0    | 0.3         | ... | 0.3        |
| Enable         | 0    | 0           | ... | 1          |
| Parameters     |      |             |     |            |
| Tr             | 0.01 |             |     |            |
| Tf             | 0.03 |             |     |            |
| ts_fact        | 1    |             |     |            |
| Outputs        |      |             |     |            |
| Out            | 0    | -1          | ... | 0.423      |
| Exp. Out       | 0    | -1          | ... | 0.423      |
| Out (DSP)      | 0    | -2147483648 | ... | 909101402  |
| Exp. Out (DSP) | 0    | -2147483648 | ... | 909101411  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 1,8626e-08$ ( $\pm 40$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 61  |
| Max CPU cycles  | 154 |
| Avg CPU cycles  | 115 |

**Test case: Conversion test****OK**

Conversion test for General block RateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block RateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 3,0000e+00$ |
| Tolerance RateDown | $\pm 3,0000e+00$ |



| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2162 |
| Max CPU cycles  | 2240 |
| Avg CPU cycles  | 2200 |

**Verification: RateLimiter Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block RateLimiter.

| Test results   |      |     |     |       |
|----------------|------|-----|-----|-------|
| Time step      | 1    | 2   | ... | 213   |
| CPU cycles     | 72   | 72  | ... | 111   |
| Inputs         |      |     |     |       |
| In (DSP)       | 0    | -1  | ... | -0.8  |
| Init (DSP)     | 0    | 0.3 | ... | 0.3   |
| Enable (DSP)   | 0    | 0   | ... | 1     |
| In             | 0    | -1  | ... | -0.8  |
| Init           | 0    | 0.3 | ... | 0.3   |
| Enable         | 0    | 0   | ... | 1     |
| Parameters     |      |     |     |       |
| Tr             | 0.01 |     |     |       |
| Tf             | 0.03 |     |     |       |
| ts_fact        | 1    |     |     |       |
| Outputs        |      |     |     |       |
| Out            | 0    | -1  | ... | 0.423 |
| Exp. Out       | 0    | -1  | ... | 0.423 |
| Out (DSP)      | 0    | -1  | ... | 0.423 |
| Exp. Out (DSP) | 0    | -1  | ... | 0.423 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,9558e-07$ ( $\pm 420$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 72  |
| Max CPU cycles  | 111 |
| Avg CPU cycles  | 95  |

**Test case: Conversion test****OK**

Conversion test for General block RateLimiter.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Tr</b>                    | -10 | -9.444 | ... | 10 |
| <b>Tf</b>                    | -9  | -8.5   | ... | 9  |
| <b>ts_fact</b>               | 3   | 3      | ... | 3  |
| <i>Controller parameters</i> |     |        |     |    |
| <b>RateUp</b>                | 1   | 1      | ... | 0  |
| <b>RateDown</b>              | 1   | 1      | ... | 0  |
| <b>Exp. RateUp</b>           | 1   | 1      | ... | 0  |
| <b>Exp. RateDown</b>         | 1   | 1      | ... | 0  |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block RateLimiter.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Tr</b>                    | -10 | -9.444 | ... | 10 |
| <b>Tf</b>                    | -9  | -8.5   | ... | 9  |
| <b>ts_fact</b>               | 3   | 3      | ... | 3  |
| <i>Controller parameters</i> |     |        |     |    |
| <b>RateUp</b>                | 1   | 1      | ... | 0  |
| <b>RateDown</b>              | 1   | 1      | ... | 0  |
| <b>Exp. RateUp</b>           | 1   | 1      | ... | 0  |
| <b>Exp. RateDown</b>         | 1   | 1      | ... | 0  |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 3,0000e-09$ |
| Tolerance RateDown | $\pm 3,0000e-09$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2418 |
| Max CPU cycles  | 2452 |
| Avg CPU cycles  | 2418 |

**Verification: RateLimiter Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block RateLimiter.

| Test results   |      |     |     |       |
|----------------|------|-----|-----|-------|
| Time step      | 1    | 2   | ... | 213   |
| CPU cycles     | 41   | 41  | ... | 81    |
| Inputs         |      |     |     |       |
| In (DSP)       | 0    | -1  | ... | -0.8  |
| Init (DSP)     | 0    | 0.3 | ... | 0.3   |
| Enable (DSP)   | 0    | 0   | ... | 1     |
| In             | 0    | -1  | ... | -0.8  |
| Init           | 0    | 0.3 | ... | 0.3   |
| Enable         | 0    | 0   | ... | 1     |
| Parameters     |      |     |     |       |
| Tr             | 0.01 |     |     |       |
| Tf             | 0.03 |     |     |       |
| ts_fact        | 1    |     |     |       |
| Outputs        |      |     |     |       |
| Out            | 0    | -1  | ... | 0.423 |
| Exp. Out       | 0    | -1  | ... | 0.423 |
| Out (DSP)      | 0    | -1  | ... | 0.423 |
| Exp. Out (DSP) | 0    | -1  | ... | 0.423 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,9558e-07$ ( $\pm 420$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 41 |
| Max CPU cycles  | 81 |
| Avg CPU cycles  | 67 |

**Test case: Conversion test****OK**

Conversion test for General block RateLimiter.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Tr</b>                    | -10 | -9.444 | ... | 10 |
| <b>Tf</b>                    | -9  | -8.5   | ... | 9  |
| <b>ts_fact</b>               | 3   | 3      | ... | 3  |
| <i>Controller parameters</i> |     |        |     |    |
| <b>RateUp</b>                | 1   | 1      | ... | 0  |
| <b>RateDown</b>              | 1   | 1      | ... | 0  |
| <b>Exp. RateUp</b>           | 1   | 1      | ... | 0  |
| <b>Exp. RateDown</b>         | 1   | 1      | ... | 0  |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block RateLimiter.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Tr</b>                    | -10 | -9.444 | ... | 10 |
| <b>Tf</b>                    | -9  | -8.5   | ... | 9  |
| <b>ts_fact</b>               | 3   | 3      | ... | 3  |
| <i>Controller parameters</i> |     |        |     |    |
| <b>RateUp</b>                | 1   | 1      | ... | 0  |
| <b>RateDown</b>              | 1   | 1      | ... | 0  |
| <b>Exp. RateUp</b>           | 1   | 1      | ... | 0  |
| <b>Exp. RateDown</b>         | 1   | 1      | ... | 0  |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 3,0000e-09$ |
| Tolerance RateDown | $\pm 3,0000e-09$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 927 |
| Max CPU cycles  | 927 |
| Avg CPU cycles  | 927 |

**Verification: RateLimiter Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block RateLimiter.

| Test results   |      |     |     |       |
|----------------|------|-----|-----|-------|
| Time step      | 1    | 2   | ... | 213   |
| CPU cycles     | 57   | 57  | ... | 115   |
| Inputs         |      |     |     |       |
| In (DSP)       | 0    | -1  | ... | -0.8  |
| Init (DSP)     | 0    | 0.3 | ... | 0.3   |
| Enable (DSP)   | 0    | 0   | ... | 1     |
| In             | 0    | -1  | ... | -0.8  |
| Init           | 0    | 0.3 | ... | 0.3   |
| Enable         | 0    | 0   | ... | 1     |
| Parameters     |      |     |     |       |
| Tr             | 0.01 |     |     |       |
| Tf             | 0.03 |     |     |       |
| ts_fact        | 1    |     |     |       |
| Outputs        |      |     |     |       |
| Out            | 0    | -1  | ... | 0.423 |
| Exp. Out       | 0    | -1  | ... | 0.423 |
| Out (DSP)      | 0    | -1  | ... | 0.423 |
| Exp. Out (DSP) | 0    | -1  | ... | 0.423 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,9558e-07$ ( $\pm 420$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 57  |
| Max CPU cycles  | 175 |
| Avg CPU cycles  | 94  |

**Test case: Conversion test****OK**

Conversion test for General block RateLimiter.



| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Tr</b>                    | -10 | -9.444 | ... | 10 |
| <b>Tf</b>                    | -9  | -8.5   | ... | 9  |
| <b>ts_fact</b>               | 3   | 3      | ... | 3  |
| <i>Controller parameters</i> |     |        |     |    |
| <b>RateUp</b>                | 1   | 1      | ... | 0  |
| <b>RateDown</b>              | 1   | 1      | ... | 0  |
| <b>Exp. RateUp</b>           | 1   | 1      | ... | 0  |
| <b>Exp. RateDown</b>         | 1   | 1      | ... | 0  |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block RateLimiter.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Tr</b>                    | -10 | -9.444 | ... | 10 |
| <b>Tf</b>                    | -9  | -8.5   | ... | 9  |
| <b>ts_fact</b>               | 3   | 3      | ... | 3  |
| <i>Controller parameters</i> |     |        |     |    |
| <b>RateUp</b>                | 1   | 1      | ... | 0  |
| <b>RateDown</b>              | 1   | 1      | ... | 0  |
| <b>Exp. RateUp</b>           | 1   | 1      | ... | 0  |
| <b>Exp. RateDown</b>         | 1   | 1      | ... | 0  |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 3,0000e-09$ |
| Tolerance RateDown | $\pm 3,0000e-09$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 957 |
| Max CPU cycles  | 962 |
| Avg CPU cycles  | 957 |

**Verification: RateLimiter Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block RateLimiter.

| Test results   |      |     |     |       |
|----------------|------|-----|-----|-------|
| Time step      | 1    | 2   | ... | 213   |
| CPU cycles     | 79   | 79  | ... | 618   |
| Inputs         |      |     |     |       |
| In (DSP)       | 0    | -1  | ... | -0.8  |
| Init (DSP)     | 0    | 0.3 | ... | 0.3   |
| Enable (DSP)   | 0    | 0   | ... | 1     |
| In             | 0    | -1  | ... | -0.8  |
| Init           | 0    | 0.3 | ... | 0.3   |
| Enable         | 0    | 0   | ... | 1     |
| Parameters     |      |     |     |       |
| Tr             | 0.01 |     |     |       |
| Tf             | 0.03 |     |     |       |
| ts_fact        | 1    |     |     |       |
| Outputs        |      |     |     |       |
| Out            | 0    | -1  | ... | 0.423 |
| Exp. Out       | 0    | -1  | ... | 0.423 |
| Out (DSP)      | 0    | -1  | ... | 0.423 |
| Exp. Out (DSP) | 0    | -1  | ... | 0.423 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,9558e-07$ ( $\pm 420$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 79  |
| Max CPU cycles  | 676 |
| Avg CPU cycles  | 418 |

**Test case: Conversion test****OK**

Conversion test for General block RateLimiter.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Tr</b>                    | -10 | -9.444 | ... | 10 |
| <b>Tf</b>                    | -9  | -8.5   | ... | 9  |
| <b>ts_fact</b>               | 3   | 3      | ... | 3  |
| <i>Controller parameters</i> |     |        |     |    |
| <b>RateUp</b>                | 1   | 1      | ... | 0  |
| <b>RateDown</b>              | 1   | 1      | ... | 0  |
| <b>Exp. RateUp</b>           | 1   | 1      | ... | 0  |
| <b>Exp. RateDown</b>         | 1   | 1      | ... | 0  |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block RateLimiter.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Tr</b>                    | -10 | -9.444 | ... | 10 |
| <b>Tf</b>                    | -9  | -8.5   | ... | 9  |
| <b>ts_fact</b>               | 3   | 3      | ... | 3  |
| <i>Controller parameters</i> |     |        |     |    |
| <b>RateUp</b>                | 1   | 1      | ... | 0  |
| <b>RateDown</b>              | 1   | 1      | ... | 0  |
| <b>Exp. RateUp</b>           | 1   | 1      | ... | 0  |
| <b>Exp. RateDown</b>         | 1   | 1      | ... | 0  |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 3,0000e-09$ |
| Tolerance RateDown | $\pm 3,0000e-09$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3110 |
| Max CPU cycles  | 3216 |
| Avg CPU cycles  | 3175 |

**Verification: RateLimiter Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block RateLimiter.

| Test results   |      |     |     |       |
|----------------|------|-----|-----|-------|
| Time step      | 1    | 2   | ... | 213   |
| CPU cycles     | 66   | 66  | ... | 311   |
| Inputs         |      |     |     |       |
| In (DSP)       | 0    | -1  | ... | -0.8  |
| Init (DSP)     | 0    | 0.3 | ... | 0.3   |
| Enable (DSP)   | 0    | 0   | ... | 1     |
| In             | 0    | -1  | ... | -0.8  |
| Init           | 0    | 0.3 | ... | 0.3   |
| Enable         | 0    | 0   | ... | 1     |
| Parameters     |      |     |     |       |
| Tr             | 0.01 |     |     |       |
| Tf             | 0.03 |     |     |       |
| ts_fact        | 1    |     |     |       |
| Outputs        |      |     |     |       |
| Out            | 0    | -1  | ... | 0.423 |
| Exp. Out       | 0    | -1  | ... | 0.423 |
| Out (DSP)      | 0    | -1  | ... | 0.423 |
| Exp. Out (DSP) | 0    | -1  | ... | 0.423 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,9558e-07$ ( $\pm 420$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 66  |
| Max CPU cycles  | 313 |
| Avg CPU cycles  | 211 |

**Test case: Conversion test****OK**

Conversion test for General block RateLimiter.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Tr</b>                    | -10 | -9.444 | ... | 10 |
| <b>Tf</b>                    | -9  | -8.5   | ... | 9  |
| <b>ts_fact</b>               | 3   | 3      | ... | 3  |
| <i>Controller parameters</i> |     |        |     |    |
| <b>RateUp</b>                | 1   | 1      | ... | 0  |
| <b>RateDown</b>              | 1   | 1      | ... | 0  |
| <b>Exp. RateUp</b>           | 1   | 1      | ... | 0  |
| <b>Exp. RateDown</b>         | 1   | 1      | ... | 0  |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block RateLimiter.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Tr</b>                    | -10 | -9.444 | ... | 10 |
| <b>Tf</b>                    | -9  | -8.5   | ... | 9  |
| <b>ts_fact</b>               | 3   | 3      | ... | 3  |
| <i>Controller parameters</i> |     |        |     |    |
| <b>RateUp</b>                | 1   | 1      | ... | 0  |
| <b>RateDown</b>              | 1   | 1      | ... | 0  |
| <b>Exp. RateUp</b>           | 1   | 1      | ... | 0  |
| <b>Exp. RateDown</b>         | 1   | 1      | ... | 0  |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 3,0000e-09$ |
| Tolerance RateDown | $\pm 3,0000e-09$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 972  |
| Max CPU cycles  | 1013 |
| Avg CPU cycles  | 991  |



**Verification: RateLimiter Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block RateLimiter.

| Test results   |      |     |     |       |
|----------------|------|-----|-----|-------|
| Time step      | 1    | 2   | ... | 213   |
| CPU cycles     | 71   | 71  | ... | 809   |
| Inputs         |      |     |     |       |
| In (DSP)       | 0    | -1  | ... | -0.8  |
| Init (DSP)     | 0    | 0.3 | ... | 0.3   |
| Enable (DSP)   | 0    | 0   | ... | 1     |
| In             | 0    | -1  | ... | -0.8  |
| Init           | 0    | 0.3 | ... | 0.3   |
| Enable         | 0    | 0   | ... | 1     |
| Parameters     |      |     |     |       |
| Tr             | 0.01 |     |     |       |
| Tf             | 0.03 |     |     |       |
| ts_fact        | 1    |     |     |       |
| Outputs        |      |     |     |       |
| Out            | 0    | -1  | ... | 0.423 |
| Exp. Out       | 0    | -1  | ... | 0.423 |
| Out (DSP)      | 0    | -1  | ... | 0.423 |
| Exp. Out (DSP) | 0    | -1  | ... | 0.423 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,9558e-07$ ( $\pm 420$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 71  |
| Max CPU cycles  | 849 |
| Avg CPU cycles  | 545 |

**Test case: Conversion test****OK**

Conversion test for General block RateLimiter.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Tr</b>                    | -10 | -9.444 | ... | 10 |
| <b>Tf</b>                    | -9  | -8.5   | ... | 9  |
| <b>ts_fact</b>               | 3   | 3      | ... | 3  |
| <i>Controller parameters</i> |     |        |     |    |
| <b>RateUp</b>                | 1   | 1      | ... | 0  |
| <b>RateDown</b>              | 1   | 1      | ... | 0  |
| <b>Exp. RateUp</b>           | 1   | 1      | ... | 0  |
| <b>Exp. RateDown</b>         | 1   | 1      | ... | 0  |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block RateLimiter.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Tr</b>                    | -10 | -9.444 | ... | 10 |
| <b>Tf</b>                    | -9  | -8.5   | ... | 9  |
| <b>ts_fact</b>               | 3   | 3      | ... | 3  |
| <i>Controller parameters</i> |     |        |     |    |
| <b>RateUp</b>                | 1   | 1      | ... | 0  |
| <b>RateDown</b>              | 1   | 1      | ... | 0  |
| <b>Exp. RateUp</b>           | 1   | 1      | ... | 0  |
| <b>Exp. RateDown</b>         | 1   | 1      | ... | 0  |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 3,0000e-09$ |
| Tolerance RateDown | $\pm 3,0000e-09$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3463 |
| Max CPU cycles  | 4224 |
| Avg CPU cycles  | 4149 |

**Verification: RateLimiter Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block RateLimiter.

| Test results   |      |     |     |       |
|----------------|------|-----|-----|-------|
| Time step      | 1    | 2   | ... | 213   |
| CPU cycles     | 92   | 66  | ... | 84    |
| Inputs         |      |     |     |       |
| In (DSP)       | 0    | -1  | ... | -0.8  |
| Init (DSP)     | 0    | 0.3 | ... | 0.3   |
| Enable (DSP)   | 0    | 0   | ... | 1     |
| In             | 0    | -1  | ... | -0.8  |
| Init           | 0    | 0.3 | ... | 0.3   |
| Enable         | 0    | 0   | ... | 1     |
| Parameters     |      |     |     |       |
| Tr             | 0.01 |     |     |       |
| Tf             | 0.03 |     |     |       |
| ts_fact        | 1    |     |     |       |
| Outputs        |      |     |     |       |
| Out            | 0    | -1  | ... | 0.423 |
| Exp. Out       | 0    | -1  | ... | 0.423 |
| Out (DSP)      | 0    | -1  | ... | 0.423 |
| Exp. Out (DSP) | 0    | -1  | ... | 0.423 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,9558e-07$ ( $\pm 420$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 66 |
| Max CPU cycles  | 92 |
| Avg CPU cycles  | 76 |

**Test case: Conversion test****OK**

Conversion test for General block RateLimiter.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Tr</b>                    | -10 | -9.444 | ... | 10 |
| <b>Tf</b>                    | -9  | -8.5   | ... | 9  |
| <b>ts_fact</b>               | 3   | 3      | ... | 3  |
| <i>Controller parameters</i> |     |        |     |    |
| <b>RateUp</b>                | 1   | 1      | ... | 0  |
| <b>RateDown</b>              | 1   | 1      | ... | 0  |
| <b>Exp. RateUp</b>           | 1   | 1      | ... | 0  |
| <b>Exp. RateDown</b>         | 1   | 1      | ... | 0  |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block RateLimiter.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Tr</b>                    | -10 | -9.444 | ... | 10 |
| <b>Tf</b>                    | -9  | -8.5   | ... | 9  |
| <b>ts_fact</b>               | 3   | 3      | ... | 3  |
| <i>Controller parameters</i> |     |        |     |    |
| <b>RateUp</b>                | 1   | 1      | ... | 0  |
| <b>RateDown</b>              | 1   | 1      | ... | 0  |
| <b>Exp. RateUp</b>           | 1   | 1      | ... | 0  |
| <b>Exp. RateDown</b>         | 1   | 1      | ... | 0  |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 3,0000e-09$ |
| Tolerance RateDown | $\pm 3,0000e-09$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 787 |
| Max CPU cycles  | 938 |
| Avg CPU cycles  | 791 |

**Verification: RateLimiter Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block RateLimiter.

| Test results   |      |     |     |       |
|----------------|------|-----|-----|-------|
| Time step      | 1    | 2   | ... | 213   |
| CPU cycles     | 57   | 57  | ... | 109   |
| Inputs         |      |     |     |       |
| In (DSP)       | 0    | -1  | ... | -0.8  |
| Init (DSP)     | 0    | 0.3 | ... | 0.3   |
| Enable (DSP)   | 0    | 0   | ... | 1     |
| In             | 0    | -1  | ... | -0.8  |
| Init           | 0    | 0.3 | ... | 0.3   |
| Enable         | 0    | 0   | ... | 1     |
| Parameters     |      |     |     |       |
| Tr             | 0.01 |     |     |       |
| Tf             | 0.03 |     |     |       |
| ts_fact        | 1    |     |     |       |
| Outputs        |      |     |     |       |
| Out            | 0    | -1  | ... | 0.423 |
| Exp. Out       | 0    | -1  | ... | 0.423 |
| Out (DSP)      | 0    | -1  | ... | 0.423 |
| Exp. Out (DSP) | 0    | -1  | ... | 0.423 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,9558e-07$ ( $\pm 420$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 57  |
| Max CPU cycles  | 109 |
| Avg CPU cycles  | 88  |

**Test case: Conversion test****OK**

Conversion test for General block RateLimiter.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Tr</b>                    | -10 | -9.444 | ... | 10 |
| <b>Tf</b>                    | -9  | -8.5   | ... | 9  |
| <b>ts_fact</b>               | 3   | 3      | ... | 3  |
| <i>Controller parameters</i> |     |        |     |    |
| <b>RateUp</b>                | 1   | 1      | ... | 0  |
| <b>RateDown</b>              | 1   | 1      | ... | 0  |
| <b>Exp. RateUp</b>           | 1   | 1      | ... | 0  |
| <b>Exp. RateDown</b>         | 1   | 1      | ... | 0  |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block RateLimiter.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Tr</b>                    | -10 | -9.444 | ... | 10 |
| <b>Tf</b>                    | -9  | -8.5   | ... | 9  |
| <b>ts_fact</b>               | 3   | 3      | ... | 3  |
| <i>Controller parameters</i> |     |        |     |    |
| <b>RateUp</b>                | 1   | 1      | ... | 0  |
| <b>RateDown</b>              | 1   | 1      | ... | 0  |
| <b>Exp. RateUp</b>           | 1   | 1      | ... | 0  |
| <b>Exp. RateDown</b>         | 1   | 1      | ... | 0  |


| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 3,0000e-09$ |
| Tolerance RateDown | $\pm 3,0000e-09$ |



| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1858 |
| Max CPU cycles  | 1864 |
| Avg CPU cycles  | 1858 |

## Block: Real2Int

---



Conversion block from real (floating point) datatypes to integer (fixed point) datatypes.

$\text{Out} = \text{In} / \text{Scale}$

| Inports |            |
|---------|------------|
| In      | Real input |

| Outports |                |
|----------|----------------|
| Out      | Integer output |

| Mask Parameters |    |                                     |
|-----------------|----|-------------------------------------|
| Name            | ID | Description                         |
| Scale           | 1  | Scaling factor from real to integer |

### Implementations:

|                      |                                                        |
|----------------------|--------------------------------------------------------|
| <b>Float32_FiP8</b>  | 32 Floating Point to 8 Bit Fixed Point Implementation  |
| <b>Float32_FiP16</b> | 32 Floating Point to 16 Bit Fixed Point Implementation |
| <b>Float32_FiP32</b> | 32 Floating Point to 32 Bit Fixed Point Implementation |
| <b>Float64_FiP8</b>  | 64 Floating Point to 8 Bit Fixed Point Implementation  |
| <b>Float64_FiP16</b> | 64 Floating Point to 16 Bit Fixed Point Implementation |
| <b>Float64_FiP32</b> | 64 Floating Point to 32 Bit Fixed Point Implementation |
| <b>Float32_Bool</b>  | 32 Floating Point to Boolean Implementation            |
| <b>Float64_Bool</b>  | 64 Floating Point to Boolean Implementation            |

### Implementation: Float32\_FiP8

---

32 Floating Point to 8 Bit Fixed Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: Float32\_FiP16

---

32 Floating Point to 16 Bit Fixed Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: Float32\_FiP32

32 Floating Point to 32 Bit Fixed Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float64\_FiP8

64 Floating Point to 8 Bit Fixed Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: Float64\_FiP16

64 Floating Point to 16 Bit Fixed Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: Float64\_FiP32

64 Floating Point to 32 Bit Fixed Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32\_Bool

32 Floating Point to Boolean Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

| Outports Data Type |      |
|--------------------|------|
| Out                | bool |

### Implementation: Float64\_Bool

64 Floating Point to Boolean Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |      |
|--------------------|------|
| Out                | bool |

**Verification: Real2Int Float32\_FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block Real2Int.

| Test results   |        |         |     |       |
|----------------|--------|---------|-----|-------|
| Time step      | 1      | 2       | ... | 113   |
| CPU cycles     | 82     | 82      | ... | 82    |
| Inputs         |        |         |     |       |
| In (DSP)       | -31    | -30.446 | ... | 31    |
| In             | -31    | -30.446 | ... | 31    |
| Parameters     |        |         |     |       |
| Scale          | 73.5   |         |     |       |
| Outputs        |        |         |     |       |
| Out            | -0.422 | -0.414  | ... | 0.422 |
| Exp. Out       | -0.422 | -0.414  | ... | 0.422 |
| Out (DSP)      | -13820 | -13573  | ... | 13820 |
| Exp. Out (DSP) | -13821 | -13574  | ... | 13821 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 82 |
| Max CPU cycles  | 82 |
| Avg CPU cycles  | 82 |

**Test case: Parameter test****OK**

Parameter test for General block Real2Int.

| Test results   |       |       |     |      |
|----------------|-------|-------|-----|------|
| Time step      | 1     | 2     | ... | 14   |
| CPU cycles     | 82    | 82    | ... | 82   |
| Inputs         |       |       |     |      |
| In (DSP)       | 0.1   |       |     |      |
| In             | 0.1   |       |     |      |
| Parameters     |       |       |     |      |
| Scale          | -10   | -5    | ... | 10   |
| Outputs        |       |       |     |      |
| Out            | -0.01 | -0.02 | ... | 0.01 |
| Exp. Out       | -0.01 | -0.02 | ... | 0.01 |
| Out (DSP)      | -327  | -655  | ... | 327  |
| Exp. Out (DSP) | -328  | -655  | ... | 328  |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 3,0518\text{e-}05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 78 |
| Max CPU cycles  | 82 |
| Avg CPU cycles  | 81 |

#### Test case: Conversion test

OK

Conversion test for General block Real2Int.

| Test results                 |         |         |     |        |
|------------------------------|---------|---------|-----|--------|
| <b>Time step</b>             | 1       | 2       | ... | 14     |
| <i>Mask parameters</i>       |         |         |     |        |
| <b>Scale</b>                 | -10     | -5      | ... | 10     |
| <i>Controller parameters</i> |         |         |     |        |
| <b>scale</b>                 | -3276.8 | -6553.6 | ... | 3276.8 |
| <b>Exp. scale</b>            | -3276.8 | -6553.6 | ... | 3276.8 |

| Test settings   |                         |
|-----------------|-------------------------|
| Tolerance scale | $\pm 0,0000\text{e+}00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Real2Int.

| Test results          |         |         |     |        |
|-----------------------|---------|---------|-----|--------|
| <b>Time step</b>      | 1       | 2       | ... | 14     |
| Mask parameters       |         |         |     |        |
| <b>Scale</b>          | -10     | -5      | ... | 10     |
| Controller parameters |         |         |     |        |
| <b>scale</b>          | -3276.8 | -6553.6 | ... | 3276.8 |
| <b>Exp. scale</b>     | -3276.8 | -6553.6 | ... | 3276.8 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 5,0000e-04$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1095 |
| Max CPU cycles  | 1095 |
| Avg CPU cycles  | 1095 |

**Verification: Real2Int Float32\_FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block Real2Int.

| Test results   |        |         |     |       |
|----------------|--------|---------|-----|-------|
| Time step      | 1      | 2       | ... | 113   |
| CPU cycles     | 41     | 41      | ... | 41    |
| Inputs         |        |         |     |       |
| In (DSP)       | -31    | -30.446 | ... | 31    |
| In             | -31    | -30.446 | ... | 31    |
| Parameters     |        |         |     |       |
| Scale          | 73.5   |         |     |       |
| Outputs        |        |         |     |       |
| Out            | -0.422 | -0.414  | ... | 0.422 |
| Exp. Out       | -0.422 | -0.414  | ... | 0.422 |
| Out (DSP)      | -13820 | -13573  | ... | 13820 |
| Exp. Out (DSP) | -13821 | -13574  | ... | 13821 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 41 |
| Max CPU cycles  | 41 |
| Avg CPU cycles  | 41 |

**Test case: Parameter test****OK**

Parameter test for General block Real2Int.



| Test results   |       |       |     |      |
|----------------|-------|-------|-----|------|
| Time step      | 1     | 2     | ... | 14   |
| CPU cycles     | 41    | 41    | ... | 41   |
| Inputs         |       |       |     |      |
| In (DSP)       | 0.1   |       |     |      |
| In             | 0.1   |       |     |      |
| Parameters     |       |       |     |      |
| Scale          | -10   | -5    | ... | 10   |
| Outputs        |       |       |     |      |
| Out            | -0.01 | -0.02 | ... | 0.01 |
| Exp. Out       | -0.01 | -0.02 | ... | 0.01 |
| Out (DSP)      | -327  | -655  | ... | 327  |
| Exp. Out (DSP) | -328  | -655  | ... | 328  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 37 |
| Max CPU cycles  | 43 |
| Avg CPU cycles  | 40 |

### Test case: Conversion test

OK

Conversion test for General block Real2Int.

| Test results          |         |         |     |        |
|-----------------------|---------|---------|-----|--------|
| <b>Time step</b>      | 1       | 2       | ... | 14     |
| Mask parameters       |         |         |     |        |
| <b>Scale</b>          | -10     | -5      | ... | 10     |
| Controller parameters |         |         |     |        |
| <b>scale</b>          | -3276.8 | -6553.6 | ... | 3276.8 |
| <b>Exp. scale</b>     | -3276.8 | -6553.6 | ... | 3276.8 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Real2Int.

| Test results                 |         |         |     |        |
|------------------------------|---------|---------|-----|--------|
| <b>Time step</b>             | 1       | 2       | ... | 14     |
| <i>Mask parameters</i>       |         |         |     |        |
| <b>Scale</b>                 | -10     | -5      | ... | 10     |
| <i>Controller parameters</i> |         |         |     |        |
| <b>scale</b>                 | -3276.8 | -6553.6 | ... | 3276.8 |
| <b>Exp. scale</b>            | -3276.8 | -6553.6 | ... | 3276.8 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 5,0000e-04$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 415 |
| Max CPU cycles  | 415 |
| Avg CPU cycles  | 415 |

**Verification: Real2Int Float32\_FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block Real2Int.

| Test results   |        |         |     |       |
|----------------|--------|---------|-----|-------|
| Time step      | 1      | 2       | ... | 113   |
| CPU cycles     | 82     | 82      | ... | 82    |
| Inputs         |        |         |     |       |
| In (DSP)       | -31    | -30.446 | ... | 31    |
| In             | -31    | -30.446 | ... | 31    |
| Parameters     |        |         |     |       |
| Scale          | 73.5   |         |     |       |
| Outputs        |        |         |     |       |
| Out            | -0.422 | -0.414  | ... | 0.422 |
| Exp. Out       | -0.422 | -0.414  | ... | 0.422 |
| Out (DSP)      | -13820 | -13573  | ... | 13820 |
| Exp. Out (DSP) | -13821 | -13574  | ... | 13821 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 82 |
| Max CPU cycles  | 82 |
| Avg CPU cycles  | 82 |

**Test case: Parameter test****OK**

Parameter test for General block Real2Int.

| Test results   |       |       |     |      |
|----------------|-------|-------|-----|------|
| Time step      | 1     | 2     | ... | 14   |
| CPU cycles     | 82    | 82    | ... | 82   |
| Inputs         |       |       |     |      |
| In (DSP)       | 0.1   |       |     |      |
| In             | 0.1   |       |     |      |
| Parameters     |       |       |     |      |
| Scale          | -10   | -5    | ... | 10   |
| Outputs        |       |       |     |      |
| Out            | -0.01 | -0.02 | ... | 0.01 |
| Exp. Out       | -0.01 | -0.02 | ... | 0.01 |
| Out (DSP)      | -327  | -655  | ... | 327  |
| Exp. Out (DSP) | -328  | -655  | ... | 328  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 82 |
| Max CPU cycles  | 82 |
| Avg CPU cycles  | 82 |

#### Test case: Conversion test

OK

Conversion test for General block Real2Int.

| Test results                 |         |         |     |        |
|------------------------------|---------|---------|-----|--------|
| <b>Time step</b>             | 1       | 2       | ... | 14     |
| <i>Mask parameters</i>       |         |         |     |        |
| <b>Scale</b>                 | -10     | -5      | ... | 10     |
| <i>Controller parameters</i> |         |         |     |        |
| <b>scale</b>                 | -3276.8 | -6553.6 | ... | 3276.8 |
| <b>Exp. scale</b>            | -3276.8 | -6553.6 | ... | 3276.8 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Real2Int.

| Test results          |         |         |     |        |
|-----------------------|---------|---------|-----|--------|
| <b>Time step</b>      | 1       | 2       | ... | 14     |
| Mask parameters       |         |         |     |        |
| <b>Scale</b>          | -10     | -5      | ... | 10     |
| Controller parameters |         |         |     |        |
| <b>scale</b>          | -3276.8 | -6553.6 | ... | 3276.8 |
| <b>Exp. scale</b>     | -3276.8 | -6553.6 | ... | 3276.8 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 5,0000e-04$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 492 |
| Max CPU cycles  | 492 |
| Avg CPU cycles  | 492 |

**Verification: Real2Int Float32\_FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block Real2Int.

| Test results   |        |         |     |       |
|----------------|--------|---------|-----|-------|
| Time step      | 1      | 2       | ... | 113   |
| CPU cycles     | 276    | 276     | ... | 278   |
| Inputs         |        |         |     |       |
| In (DSP)       | -31    | -30.446 | ... | 31    |
| In             | -31    | -30.446 | ... | 31    |
| Parameters     |        |         |     |       |
| Scale          | 73.5   |         |     |       |
| Outputs        |        |         |     |       |
| Out            | -0.422 | -0.414  | ... | 0.422 |
| Exp. Out       | -0.422 | -0.414  | ... | 0.422 |
| Out (DSP)      | -13820 | -13573  | ... | 13820 |
| Exp. Out (DSP) | -13821 | -13574  | ... | 13821 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 205 |
| Max CPU cycles  | 282 |
| Avg CPU cycles  | 277 |

**Test case: Parameter test****OK**

Parameter test for General block Real2Int.

| Test results   |       |       |     |      |
|----------------|-------|-------|-----|------|
| Time step      | 1     | 2     | ... | 14   |
| CPU cycles     | 276   | 276   | ... | 278  |
| Inputs         |       |       |     |      |
| In (DSP)       | 0.1   |       |     |      |
| In             | 0.1   |       |     |      |
| Parameters     |       |       |     |      |
| Scale          | -10   | -5    | ... | 10   |
| Outputs        |       |       |     |      |
| Out            | -0.01 | -0.02 | ... | 0.01 |
| Exp. Out       | -0.01 | -0.02 | ... | 0.01 |
| Out (DSP)      | -327  | -655  | ... | 327  |
| Exp. Out (DSP) | -328  | -655  | ... | 328  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 275 |
| Max CPU cycles  | 281 |
| Avg CPU cycles  | 278 |

### Test case: Conversion test

OK

Conversion test for General block Real2Int.

| Test results                 |         |         |     |        |
|------------------------------|---------|---------|-----|--------|
| <b>Time step</b>             | 1       | 2       | ... | 14     |
| <i>Mask parameters</i>       |         |         |     |        |
| <b>Scale</b>                 | -10     | -5      | ... | 10     |
| <i>Controller parameters</i> |         |         |     |        |
| <b>scale</b>                 | -3276.8 | -6553.6 | ... | 3276.8 |
| <b>Exp. scale</b>            | -3276.8 | -6553.6 | ... | 3276.8 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Real2Int.

| Test results          |         |         |     |        |
|-----------------------|---------|---------|-----|--------|
| <b>Time step</b>      | 1       | 2       | ... | 14     |
| Mask parameters       |         |         |     |        |
| <b>Scale</b>          | -10     | -5      | ... | 10     |
| Controller parameters |         |         |     |        |
| <b>scale</b>          | -3276.8 | -6553.6 | ... | 3276.8 |
| <b>Exp. scale</b>     | -3276.8 | -6553.6 | ... | 3276.8 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 5,0000e-04$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1254 |
| Max CPU cycles  | 1272 |
| Avg CPU cycles  | 1261 |



**Verification: Real2Int Float32\_FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block Real2Int.

| Test results   |        |         |     |       |
|----------------|--------|---------|-----|-------|
| Time step      | 1      | 2       | ... | 113   |
| CPU cycles     | 115    | 116     | ... | 114   |
| Inputs         |        |         |     |       |
| In (DSP)       | -31    | -30.446 | ... | 31    |
| In             | -31    | -30.446 | ... | 31    |
| Parameters     |        |         |     |       |
| Scale          | 73.5   |         |     |       |
| Outputs        |        |         |     |       |
| Out            | -0.422 | -0.414  | ... | 0.422 |
| Exp. Out       | -0.422 | -0.414  | ... | 0.422 |
| Out (DSP)      | -13820 | -13573  | ... | 13820 |
| Exp. Out (DSP) | -13821 | -13574  | ... | 13821 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 97  |
| Max CPU cycles  | 118 |
| Avg CPU cycles  | 115 |

**Test case: Parameter test****OK**

Parameter test for General block Real2Int.

| Test results   |       |       |     |      |
|----------------|-------|-------|-----|------|
| Time step      | 1     | 2     | ... | 14   |
| CPU cycles     | 116   | 116   | ... | 115  |
| Inputs         |       |       |     |      |
| In (DSP)       | 0.1   |       |     |      |
| In             | 0.1   |       |     |      |
| Parameters     |       |       |     |      |
| Scale          | -10   | -5    | ... | 10   |
| Outputs        |       |       |     |      |
| Out            | -0.01 | -0.02 | ... | 0.01 |
| Exp. Out       | -0.01 | -0.02 | ... | 0.01 |
| Out (DSP)      | -327  | -655  | ... | 327  |
| Exp. Out (DSP) | -328  | -655  | ... | 328  |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 3,0518\text{e-}05$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 114 |
| Max CPU cycles  | 117 |
| Avg CPU cycles  | 115 |

#### Test case: Conversion test

OK

Conversion test for General block Real2Int.

| Test results                 |         |         |     |        |
|------------------------------|---------|---------|-----|--------|
| <b>Time step</b>             | 1       | 2       | ... | 14     |
| <i>Mask parameters</i>       |         |         |     |        |
| <b>Scale</b>                 | -10     | -5      | ... | 10     |
| <i>Controller parameters</i> |         |         |     |        |
| <b>scale</b>                 | -3276.8 | -6553.6 | ... | 3276.8 |
| <b>Exp. scale</b>            | -3276.8 | -6553.6 | ... | 3276.8 |

| Test settings   |                         |
|-----------------|-------------------------|
| Tolerance scale | $\pm 0,0000\text{e+}00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Real2Int.

| Test results                 |         |         |     |        |
|------------------------------|---------|---------|-----|--------|
| <b>Time step</b>             | 1       | 2       | ... | 14     |
| <i>Mask parameters</i>       |         |         |     |        |
| <b>Scale</b>                 | -10     | -5      | ... | 10     |
| <i>Controller parameters</i> |         |         |     |        |
| <b>scale</b>                 | -3276.8 | -6553.6 | ... | 3276.8 |
| <b>Exp. scale</b>            | -3276.8 | -6553.6 | ... | 3276.8 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 5,0000e-04$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 396 |
| Max CPU cycles  | 422 |
| Avg CPU cycles  | 409 |

**Verification: Real2Int Float32\_FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block Real2Int.

| Test results   |        |         |     |       |
|----------------|--------|---------|-----|-------|
| Time step      | 1      | 2       | ... | 113   |
| CPU cycles     | 323    | 327     | ... | 324   |
| Inputs         |        |         |     |       |
| In (DSP)       | -31    | -30.446 | ... | 31    |
| In             | -31    | -30.446 | ... | 31    |
| Parameters     |        |         |     |       |
| Scale          | 73.5   |         |     |       |
| Outputs        |        |         |     |       |
| Out            | -0.422 | -0.414  | ... | 0.422 |
| Exp. Out       | -0.422 | -0.414  | ... | 0.422 |
| Out (DSP)      | -13820 | -13573  | ... | 13820 |
| Exp. Out (DSP) | -13821 | -13574  | ... | 13821 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 209 |
| Max CPU cycles  | 371 |
| Avg CPU cycles  | 333 |

**Test case: Parameter test****OK**

Parameter test for General block Real2Int.

| Test results   |       |       |     |      |
|----------------|-------|-------|-----|------|
| Time step      | 1     | 2     | ... | 14   |
| CPU cycles     | 362   | 355   | ... | 363  |
| Inputs         |       |       |     |      |
| In (DSP)       | 0.1   |       |     |      |
| In             | 0.1   |       |     |      |
| Parameters     |       |       |     |      |
| Scale          | -10   | -5    | ... | 10   |
| Outputs        |       |       |     |      |
| Out            | -0.01 | -0.02 | ... | 0.01 |
| Exp. Out       | -0.01 | -0.02 | ... | 0.01 |
| Out (DSP)      | -327  | -655  | ... | 327  |
| Exp. Out (DSP) | -328  | -655  | ... | 328  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 308 |
| Max CPU cycles  | 363 |
| Avg CPU cycles  | 337 |

### Test case: Conversion test

OK

Conversion test for General block Real2Int.

| Test results                 |         |         |     |        |
|------------------------------|---------|---------|-----|--------|
| <b>Time step</b>             | 1       | 2       | ... | 14     |
| <i>Mask parameters</i>       |         |         |     |        |
| <b>Scale</b>                 | -10     | -5      | ... | 10     |
| <i>Controller parameters</i> |         |         |     |        |
| <b>scale</b>                 | -3276.8 | -6553.6 | ... | 3276.8 |
| <b>Exp. scale</b>            | -3276.8 | -6553.6 | ... | 3276.8 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Real2Int.

| Test results          |         |         |     |        |
|-----------------------|---------|---------|-----|--------|
| <b>Time step</b>      | 1       | 2       | ... | 14     |
| Mask parameters       |         |         |     |        |
| <b>Scale</b>          | -10     | -5      | ... | 10     |
| Controller parameters |         |         |     |        |
| <b>scale</b>          | -3276.8 | -6553.6 | ... | 3276.8 |
| <b>Exp. scale</b>     | -3276.8 | -6553.6 | ... | 3276.8 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 5,0000e-04$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1305 |
| Max CPU cycles  | 1369 |
| Avg CPU cycles  | 1331 |

**Verification: Real2Int Float32\_FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block Real2Int.

| Test results   |        |         |     |       |
|----------------|--------|---------|-----|-------|
| Time step      | 1      | 2       | ... | 113   |
| CPU cycles     | 91     | 80      | ... | 80    |
| Inputs         |        |         |     |       |
| In (DSP)       | -31    | -30.446 | ... | 31    |
| In             | -31    | -30.446 | ... | 31    |
| Parameters     |        |         |     |       |
| Scale          | 73.5   |         |     |       |
| Outputs        |        |         |     |       |
| Out            | -0.422 | -0.414  | ... | 0.422 |
| Exp. Out       | -0.422 | -0.414  | ... | 0.422 |
| Out (DSP)      | -13820 | -13573  | ... | 13820 |
| Exp. Out (DSP) | -13821 | -13574  | ... | 13821 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 80 |
| Max CPU cycles  | 91 |
| Avg CPU cycles  | 80 |

**Test case: Parameter test****OK**

Parameter test for General block Real2Int.

| Test results   |       |       |     |      |
|----------------|-------|-------|-----|------|
| Time step      | 1     | 2     | ... | 14   |
| CPU cycles     | 91    | 91    | ... | 91   |
| Inputs         |       |       |     |      |
| In (DSP)       | 0.1   |       |     |      |
| In             | 0.1   |       |     |      |
| Parameters     |       |       |     |      |
| Scale          | -10   | -5    | ... | 10   |
| Outputs        |       |       |     |      |
| Out            | -0.01 | -0.02 | ... | 0.01 |
| Exp. Out       | -0.01 | -0.02 | ... | 0.01 |
| Out (DSP)      | -327  | -655  | ... | 327  |
| Exp. Out (DSP) | -328  | -655  | ... | 328  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 91 |
| Max CPU cycles  | 91 |
| Avg CPU cycles  | 91 |

#### Test case: Conversion test

OK

Conversion test for General block Real2Int.

| Test results                 |         |         |     |        |
|------------------------------|---------|---------|-----|--------|
| <b>Time step</b>             | 1       | 2       | ... | 14     |
| <i>Mask parameters</i>       |         |         |     |        |
| <b>Scale</b>                 | -10     | -5      | ... | 10     |
| <i>Controller parameters</i> |         |         |     |        |
| <b>scale</b>                 | -3276.8 | -6553.6 | ... | 3276.8 |
| <b>Exp. scale</b>            | -3276.8 | -6553.6 | ... | 3276.8 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Real2Int.



| Test results          |         |         |     |        |
|-----------------------|---------|---------|-----|--------|
| <b>Time step</b>      | 1       | 2       | ... | 14     |
| Mask parameters       |         |         |     |        |
| <b>Scale</b>          | -10     | -5      | ... | 10     |
| Controller parameters |         |         |     |        |
| <b>scale</b>          | -3276.8 | -6553.6 | ... | 3276.8 |
| <b>Exp. scale</b>     | -3276.8 | -6553.6 | ... | 3276.8 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 5,0000e-04$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 398 |
| Max CPU cycles  | 464 |
| Avg CPU cycles  | 402 |

**Verification: Real2Int Float32\_FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block Real2Int.

| Test results   |        |         |     |       |
|----------------|--------|---------|-----|-------|
| Time step      | 1      | 2       | ... | 113   |
| CPU cycles     | 65     | 65      | ... | 65    |
| Inputs         |        |         |     |       |
| In (DSP)       | -31    | -30.446 | ... | 31    |
| In             | -31    | -30.446 | ... | 31    |
| Parameters     |        |         |     |       |
| Scale          | 73.5   |         |     |       |
| Outputs        |        |         |     |       |
| Out            | -0.422 | -0.414  | ... | 0.422 |
| Exp. Out       | -0.422 | -0.414  | ... | 0.422 |
| Out (DSP)      | -13820 | -13573  | ... | 13820 |
| Exp. Out (DSP) | -13821 | -13574  | ... | 13821 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 65 |
| Max CPU cycles  | 65 |
| Avg CPU cycles  | 65 |

**Test case: Parameter test****OK**

Parameter test for General block Real2Int.

| Test results   |       |       |     |      |
|----------------|-------|-------|-----|------|
| Time step      | 1     | 2     | ... | 14   |
| CPU cycles     | 65    | 65    | ... | 65   |
| Inputs         |       |       |     |      |
| In (DSP)       | 0.1   |       |     |      |
| In             | 0.1   |       |     |      |
| Parameters     |       |       |     |      |
| Scale          | -10   | -5    | ... | 10   |
| Outputs        |       |       |     |      |
| Out            | -0.01 | -0.02 | ... | 0.01 |
| Exp. Out       | -0.01 | -0.02 | ... | 0.01 |
| Out (DSP)      | -327  | -655  | ... | 327  |
| Exp. Out (DSP) | -328  | -655  | ... | 328  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 64 |
| Max CPU cycles  | 65 |
| Avg CPU cycles  | 64 |

#### Test case: Conversion test

OK

Conversion test for General block Real2Int.

| Test results                 |         |         |     |        |
|------------------------------|---------|---------|-----|--------|
| <b>Time step</b>             | 1       | 2       | ... | 14     |
| <i>Mask parameters</i>       |         |         |     |        |
| <b>Scale</b>                 | -10     | -5      | ... | 10     |
| <i>Controller parameters</i> |         |         |     |        |
| <b>scale</b>                 | -3276.8 | -6553.6 | ... | 3276.8 |
| <b>Exp. scale</b>            | -3276.8 | -6553.6 | ... | 3276.8 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Real2Int.

| Test results                 |         |         |     |        |
|------------------------------|---------|---------|-----|--------|
| <b>Time step</b>             | 1       | 2       | ... | 14     |
| <i>Mask parameters</i>       |         |         |     |        |
| <b>Scale</b>                 | -10     | -5      | ... | 10     |
| <i>Controller parameters</i> |         |         |     |        |
| <b>scale</b>                 | -3276.8 | -6553.6 | ... | 3276.8 |
| <b>Exp. scale</b>            | -3276.8 | -6553.6 | ... | 3276.8 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 5,0000e-04$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 884 |
| Max CPU cycles  | 884 |
| Avg CPU cycles  | 884 |

**Verification: Real2Int Float32\_FIP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block Real2Int.

| Test results   |            |            |     |           |
|----------------|------------|------------|-----|-----------|
| Time step      | 1          | 2          | ... | 113       |
| CPU cycles     | 244        | 244        | ... | 251       |
| Inputs         |            |            |     |           |
| In (DSP)       | -31        | -30.446    | ... | 31        |
| In             | -31        | -30.446    | ... | 31        |
| Parameters     |            |            |     |           |
| Scale          | 73.5       |            |     |           |
| Outputs        |            |            |     |           |
| Out            | -0.422     | -0.414     | ... | 0.422     |
| Exp. Out       | -0.422     | -0.414     | ... | 0.422     |
| Out (DSP)      | -905741376 | -889567424 | ... | 905741376 |
| Exp. Out (DSP) | -905741403 | -889567449 | ... | 905741403 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 4,6566e-08$ ( $\pm 100$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 202 |
| Max CPU cycles  | 251 |
| Avg CPU cycles  | 247 |

**Test case: Parameter test****OK**

Parameter test for General block Real2Int.

| Test results   |           |           |     |          |
|----------------|-----------|-----------|-----|----------|
| Time step      | 1         | 2         | ... | 14       |
| CPU cycles     | 244       | 244       | ... | 251      |
| Inputs         |           |           |     |          |
| In (DSP)       | 0.1       |           |     |          |
| In             | 0.1       |           |     |          |
| Parameters     |           |           |     |          |
| Scale          | -10       | -5        | ... | 10       |
| Outputs        |           |           |     |          |
| Out            | -0.01     | -0.02     | ... | 0.01     |
| Exp. Out       | -0.01     | -0.02     | ... | 0.01     |
| Out (DSP)      | -21474838 | -42949676 | ... | 21474838 |
| Exp. Out (DSP) | -21474836 | -42949673 | ... | 21474836 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,7253e-09$ ( $\pm 8$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 204 |
| Max CPU cycles  | 251 |
| Avg CPU cycles  | 244 |

### Test case: Conversion test

OK

Conversion test for General block Real2Int.

| Test results                 |              |              |     |             |
|------------------------------|--------------|--------------|-----|-------------|
| <b>Time step</b>             | 1            | 2            | ... | 14          |
| <i>Mask parameters</i>       |              |              |     |             |
| <b>Scale</b>                 | -10          | -5           | ... | 10          |
| <i>Controller parameters</i> |              |              |     |             |
| <b>scale</b>                 | -214748364.8 | -429496729.6 | ... | 214748364.8 |
| <b>Exp. scale</b>            | -214748364.8 | -429496729.6 | ... | 214748364.8 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Real2Int.

| Test results                 |              |              |     |             |
|------------------------------|--------------|--------------|-----|-------------|
| <b>Time step</b>             | 1            | 2            | ... | 14          |
| <i>Mask parameters</i>       |              |              |     |             |
| <b>Scale</b>                 | -10          | -5           | ... | 10          |
| <i>Controller parameters</i> |              |              |     |             |
| <b>scale</b>                 | -214748352   | -429496704   | ... | 214748352   |
| <b>Exp. scale</b>            | -214748364.8 | -429496729.6 | ... | 214748364.8 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 5,0000e+01$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1083 |
| Max CPU cycles  | 1083 |
| Avg CPU cycles  | 1083 |

**Verification: Real2Int Float32\_FIP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block Real2Int.

| Test results   |            |            |     |           |
|----------------|------------|------------|-----|-----------|
| Time step      | 1          | 2          | ... | 113       |
| CPU cycles     | 111        | 111        | ... | 109       |
| Inputs         |            |            |     |           |
| In (DSP)       | -31        | -30.446    | ... | 31        |
| In             | -31        | -30.446    | ... | 31        |
| Parameters     |            |            |     |           |
| Scale          | 73.5       |            |     |           |
| Outputs        |            |            |     |           |
| Out            | -0.422     | -0.414     | ... | 0.422     |
| Exp. Out       | -0.422     | -0.414     | ... | 0.422     |
| Out (DSP)      | -905741376 | -889567424 | ... | 905741376 |
| Exp. Out (DSP) | -905741403 | -889567449 | ... | 905741403 |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 4,6566\text{e-}08$ ( $\pm 100$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 83  |
| Max CPU cycles  | 111 |
| Avg CPU cycles  | 109 |

**Test case: Parameter test****OK**

Parameter test for General block Real2Int.



| Test results   |           |           |     |          |
|----------------|-----------|-----------|-----|----------|
| Time step      | 1         | 2         | ... | 14       |
| CPU cycles     | 111       | 111       | ... | 109      |
| Inputs         |           |           |     |          |
| In (DSP)       | 0.1       |           |     |          |
| In             | 0.1       |           |     |          |
| Parameters     |           |           |     |          |
| Scale          | -10       | -5        | ... | 10       |
| Outputs        |           |           |     |          |
| Out            | -0.01     | -0.02     | ... | 0.01     |
| Exp. Out       | -0.01     | -0.02     | ... | 0.01     |
| Out (DSP)      | -21474838 | -42949676 | ... | 21474838 |
| Exp. Out (DSP) | -21474836 | -42949673 | ... | 21474836 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,7253e-09$ ( $\pm 8$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 103 |
| Max CPU cycles  | 115 |
| Avg CPU cycles  | 109 |

### Test case: Conversion test

OK

Conversion test for General block Real2Int.

| Test results                 |              |              |     |             |
|------------------------------|--------------|--------------|-----|-------------|
| <b>Time step</b>             | 1            | 2            | ... | 14          |
| <i>Mask parameters</i>       |              |              |     |             |
| <b>Scale</b>                 | -10          | -5           | ... | 10          |
| <i>Controller parameters</i> |              |              |     |             |
| <b>scale</b>                 | -214748364.8 | -429496729.6 | ... | 214748364.8 |
| <b>Exp. scale</b>            | -214748364.8 | -429496729.6 | ... | 214748364.8 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Real2Int.

| Test results                 |              |              |     |             |
|------------------------------|--------------|--------------|-----|-------------|
| <b>Time step</b>             | 1            | 2            | ... | 14          |
| <i>Mask parameters</i>       |              |              |     |             |
| <b>Scale</b>                 | -10          | -5           | ... | 10          |
| <i>Controller parameters</i> |              |              |     |             |
| <b>scale</b>                 | -214748368   | -429496736   | ... | 214748368   |
| <b>Exp. scale</b>            | -214748364.8 | -429496729.6 | ... | 214748364.8 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 5,0000e+01$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 415 |
| Max CPU cycles  | 415 |
| Avg CPU cycles  | 415 |

**Verification: Real2Int Float32\_FIP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block Real2Int.

| Test results   |            |            |     |           |
|----------------|------------|------------|-----|-----------|
| Time step      | 1          | 2          | ... | 113       |
| CPU cycles     | 530        | 530        | ... | 516       |
| Inputs         |            |            |     |           |
| In (DSP)       | -31        | -30.446    | ... | 31        |
| In             | -31        | -30.446    | ... | 31        |
| Parameters     |            |            |     |           |
| Scale          | 73.5       |            |     |           |
| Outputs        |            |            |     |           |
| Out            | -0.422     | -0.414     | ... | 0.422     |
| Exp. Out       | -0.422     | -0.414     | ... | 0.422     |
| Out (DSP)      | -905741376 | -889567424 | ... | 905741376 |
| Exp. Out (DSP) | -905741403 | -889567449 | ... | 905741403 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 4,6566e-08$ ( $\pm 100$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 471 |
| Max CPU cycles  | 569 |
| Avg CPU cycles  | 523 |

**Test case: Parameter test****OK**

Parameter test for General block Real2Int.

| Test results   |           |           |     |          |
|----------------|-----------|-----------|-----|----------|
| Time step      | 1         | 2         | ... | 14       |
| CPU cycles     | 530       | 530       | ... | 516      |
| Inputs         |           |           |     |          |
| In (DSP)       | 0.1       |           |     |          |
| In             | 0.1       |           |     |          |
| Parameters     |           |           |     |          |
| Scale          | -10       | -5        | ... | 10       |
| Outputs        |           |           |     |          |
| Out            | -0.01     | -0.02     | ... | 0.01     |
| Exp. Out       | -0.01     | -0.02     | ... | 0.01     |
| Out (DSP)      | -21474838 | -42949676 | ... | 21474838 |
| Exp. Out (DSP) | -21474836 | -42949673 | ... | 21474836 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,7253e-09$ ( $\pm 8$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 516 |
| Max CPU cycles  | 530 |
| Avg CPU cycles  | 523 |

### Test case: Conversion test

OK

Conversion test for General block Real2Int.

| Test results                 |              |              |     |             |
|------------------------------|--------------|--------------|-----|-------------|
| <b>Time step</b>             | 1            | 2            | ... | 14          |
| <i>Mask parameters</i>       |              |              |     |             |
| <b>Scale</b>                 | -10          | -5           | ... | 10          |
| <i>Controller parameters</i> |              |              |     |             |
| <b>scale</b>                 | -214748364.8 | -429496729.6 | ... | 214748364.8 |
| <b>Exp. scale</b>            | -214748364.8 | -429496729.6 | ... | 214748364.8 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Real2Int.

| Test results                 |              |              |     |             |
|------------------------------|--------------|--------------|-----|-------------|
| <b>Time step</b>             | 1            | 2            | ... | 14          |
| <i>Mask parameters</i>       |              |              |     |             |
| <b>Scale</b>                 | -10          | -5           | ... | 10          |
| <i>Controller parameters</i> |              |              |     |             |
| <b>scale</b>                 | -214748368   | -429496736   | ... | 214748368   |
| <b>Exp. scale</b>            | -214748364.8 | -429496729.6 | ... | 214748364.8 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 5,0000e+01$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 484 |
| Max CPU cycles  | 484 |
| Avg CPU cycles  | 484 |

**Verification: Real2Int Float32\_FIP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block Real2Int.

| Test results   |            |            |     |           |
|----------------|------------|------------|-----|-----------|
| Time step      | 1          | 2          | ... | 113       |
| CPU cycles     | 1496       | 1496       | ... | 1487      |
| Inputs         |            |            |     |           |
| In (DSP)       | -31        | -30.446    | ... | 31        |
| In             | -31        | -30.446    | ... | 31        |
| Parameters     |            |            |     |           |
| Scale          | 73.5       |            |     |           |
| Outputs        |            |            |     |           |
| Out            | -0.422     | -0.414     | ... | 0.422     |
| Exp. Out       | -0.422     | -0.414     | ... | 0.422     |
| Out (DSP)      | -905741376 | -889567424 | ... | 905741376 |
| Exp. Out (DSP) | -905741403 | -889567449 | ... | 905741403 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 4,6566e-08$ ( $\pm 100$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1174 |
| Max CPU cycles  | 1556 |
| Avg CPU cycles  | 1492 |

**Test case: Parameter test****OK**

Parameter test for General block Real2Int.

| Test results   |           |           |     |          |
|----------------|-----------|-----------|-----|----------|
| Time step      | 1         | 2         | ... | 14       |
| CPU cycles     | 1555      | 1496      | ... | 1487     |
| Inputs         |           |           |     |          |
| In (DSP)       | 0.1       |           |     |          |
| In             | 0.1       |           |     |          |
| Parameters     |           |           |     |          |
| Scale          | -10       | -5        | ... | 10       |
| Outputs        |           |           |     |          |
| Out            | -0.01     | -0.02     | ... | 0.01     |
| Exp. Out       | -0.01     | -0.02     | ... | 0.01     |
| Out (DSP)      | -21474838 | -42949676 | ... | 21474838 |
| Exp. Out (DSP) | -21474836 | -42949673 | ... | 21474836 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,7253e-09$ ( $\pm 8$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1487 |
| Max CPU cycles  | 1624 |
| Avg CPU cycles  | 1515 |

### Test case: Conversion test

OK

Conversion test for General block Real2Int.

| Test results                 |              |              |     |             |
|------------------------------|--------------|--------------|-----|-------------|
| <b>Time step</b>             | 1            | 2            | ... | 14          |
| <i>Mask parameters</i>       |              |              |     |             |
| <b>Scale</b>                 | -10          | -5           | ... | 10          |
| <i>Controller parameters</i> |              |              |     |             |
| <b>scale</b>                 | -214748364.8 | -429496729.6 | ... | 214748364.8 |
| <b>Exp. scale</b>            | -214748364.8 | -429496729.6 | ... | 214748364.8 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Real2Int.

| Test results                 |              |              |     |             |
|------------------------------|--------------|--------------|-----|-------------|
| <b>Time step</b>             | 1            | 2            | ... | 14          |
| <i>Mask parameters</i>       |              |              |     |             |
| <b>Scale</b>                 | -10          | -5           | ... | 10          |
| <i>Controller parameters</i> |              |              |     |             |
| <b>scale</b>                 | -214748368   | -429496736   | ... | 214748368   |
| <b>Exp. scale</b>            | -214748364.8 | -429496729.6 | ... | 214748364.8 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 5,0000e+01$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1254 |
| Max CPU cycles  | 1314 |
| Avg CPU cycles  | 1266 |



**Verification: Real2Int Float32\_FIP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block Real2Int.

| Test results   |            |            |     |           |
|----------------|------------|------------|-----|-----------|
| Time step      | 1          | 2          | ... | 113       |
| CPU cycles     | 471        | 472        | ... | 466       |
| Inputs         |            |            |     |           |
| In (DSP)       | -31        | -30.446    | ... | 31        |
| In             | -31        | -30.446    | ... | 31        |
| Parameters     |            |            |     |           |
| Scale          | 73.5       |            |     |           |
| Outputs        |            |            |     |           |
| Out            | -0.422     | -0.414     | ... | 0.422     |
| Exp. Out       | -0.422     | -0.414     | ... | 0.422     |
| Out (DSP)      | -905741376 | -889567424 | ... | 905741376 |
| Exp. Out (DSP) | -905741403 | -889567449 | ... | 905741403 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 4,6566e-08$ ( $\pm 100$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 379 |
| Max CPU cycles  | 474 |
| Avg CPU cycles  | 468 |

**Test case: Parameter test****OK**

Parameter test for General block Real2Int.

| Test results   |           |           |     |          |
|----------------|-----------|-----------|-----|----------|
| Time step      | 1         | 2         | ... | 14       |
| CPU cycles     | 472       | 472       | ... | 467      |
| Inputs         |           |           |     |          |
| In (DSP)       | 0.1       |           |     |          |
| In             | 0.1       |           |     |          |
| Parameters     |           |           |     |          |
| Scale          | -10       | -5        | ... | 10       |
| Outputs        |           |           |     |          |
| Out            | -0.01     | -0.02     | ... | 0.01     |
| Exp. Out       | -0.01     | -0.02     | ... | 0.01     |
| Out (DSP)      | -21474838 | -42949676 | ... | 21474838 |
| Exp. Out (DSP) | -21474836 | -42949673 | ... | 21474836 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,7253e-09$ ( $\pm 8$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 466 |
| Max CPU cycles  | 473 |
| Avg CPU cycles  | 469 |

### Test case: Conversion test

OK

Conversion test for General block Real2Int.

| Test results                 |              |              |     |             |
|------------------------------|--------------|--------------|-----|-------------|
| <b>Time step</b>             | 1            | 2            | ... | 14          |
| <i>Mask parameters</i>       |              |              |     |             |
| <b>Scale</b>                 | -10          | -5           | ... | 10          |
| <i>Controller parameters</i> |              |              |     |             |
| <b>scale</b>                 | -214748364.8 | -429496729.6 | ... | 214748364.8 |
| <b>Exp. scale</b>            | -214748364.8 | -429496729.6 | ... | 214748364.8 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Real2Int.

| Test results                 |              |              |     |             |
|------------------------------|--------------|--------------|-----|-------------|
| <b>Time step</b>             | 1            | 2            | ... | 14          |
| <i>Mask parameters</i>       |              |              |     |             |
| <b>Scale</b>                 | -10          | -5           | ... | 10          |
| <i>Controller parameters</i> |              |              |     |             |
| <b>scale</b>                 | -214748368   | -429496736   | ... | 214748368   |
| <b>Exp. scale</b>            | -214748364.8 | -429496729.6 | ... | 214748364.8 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 5,0000e+01$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 396 |
| Max CPU cycles  | 422 |
| Avg CPU cycles  | 409 |

**Verification: Real2Int Float32\_FIP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block Real2Int.

| Test results   |            |            |     |           |
|----------------|------------|------------|-----|-----------|
| Time step      | 1          | 2          | ... | 113       |
| CPU cycles     | 325        | 329        | ... | 324       |
| Inputs         |            |            |     |           |
| In (DSP)       | -31        | -30.446    | ... | 31        |
| In             | -31        | -30.446    | ... | 31        |
| Parameters     |            |            |     |           |
| Scale          | 73.5       |            |     |           |
| Outputs        |            |            |     |           |
| Out            | -0.422     | -0.414     | ... | 0.422     |
| Exp. Out       | -0.422     | -0.414     | ... | 0.422     |
| Out (DSP)      | -905741376 | -889567424 | ... | 905741376 |
| Exp. Out (DSP) | -905741403 | -889567449 | ... | 905741403 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 4,6566e-08$ ( $\pm 100$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 223 |
| Max CPU cycles  | 329 |
| Avg CPU cycles  | 316 |

**Test case: Parameter test****OK**

Parameter test for General block Real2Int.

| Test results   |           |           |     |          |
|----------------|-----------|-----------|-----|----------|
| Time step      | 1         | 2         | ... | 14       |
| CPU cycles     | 284       | 293       | ... | 283      |
| Inputs         |           |           |     |          |
| In (DSP)       | 0.1       |           |     |          |
| In             | 0.1       |           |     |          |
| Parameters     |           |           |     |          |
| Scale          | -10       | -5        | ... | 10       |
| Outputs        |           |           |     |          |
| Out            | -0.01     | -0.02     | ... | 0.01     |
| Exp. Out       | -0.01     | -0.02     | ... | 0.01     |
| Out (DSP)      | -21474838 | -42949676 | ... | 21474838 |
| Exp. Out (DSP) | -21474836 | -42949673 | ... | 21474836 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,7253e-09$ ( $\pm 8$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 283 |
| Max CPU cycles  | 344 |
| Avg CPU cycles  | 311 |

### Test case: Conversion test

OK

Conversion test for General block Real2Int.

| Test results                 |              |              |     |             |
|------------------------------|--------------|--------------|-----|-------------|
| <b>Time step</b>             | 1            | 2            | ... | 14          |
| <i>Mask parameters</i>       |              |              |     |             |
| <b>Scale</b>                 | -10          | -5           | ... | 10          |
| <i>Controller parameters</i> |              |              |     |             |
| <b>scale</b>                 | -214748364.8 | -429496729.6 | ... | 214748364.8 |
| <b>Exp. scale</b>            | -214748364.8 | -429496729.6 | ... | 214748364.8 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Real2Int.

| Test results                 |              |              |     |             |
|------------------------------|--------------|--------------|-----|-------------|
| Time step                    | 1            | 2            | ... | 14          |
| <i>Mask parameters</i>       |              |              |     |             |
| Scale                        | -10          | -5           | ... | 10          |
| <i>Controller parameters</i> |              |              |     |             |
| scale                        | -214748368   | -429496736   | ... | 214748368   |
| Exp. scale                   | -214748364.8 | -429496729.6 | ... | 214748364.8 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 5,0000e+01$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1305 |
| Max CPU cycles  | 1369 |
| Avg CPU cycles  | 1331 |

**Verification: Real2Int Float32\_FIP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block Real2Int.

| Test results   |            |            |     |           |
|----------------|------------|------------|-----|-----------|
| Time step      | 1          | 2          | ... | 113       |
| CPU cycles     | 455        | 341        | ... | 326       |
| Inputs         |            |            |     |           |
| In (DSP)       | -31        | -30.446    | ... | 31        |
| In             | -31        | -30.446    | ... | 31        |
| Parameters     |            |            |     |           |
| Scale          | 73.5       |            |     |           |
| Outputs        |            |            |     |           |
| Out            | -0.422     | -0.414     | ... | 0.422     |
| Exp. Out       | -0.422     | -0.414     | ... | 0.422     |
| Out (DSP)      | -905741376 | -889567424 | ... | 905741376 |
| Exp. Out (DSP) | -905741403 | -889567449 | ... | 905741403 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 4,6566e-08$ ( $\pm 100$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 319 |
| Max CPU cycles  | 455 |
| Avg CPU cycles  | 334 |

**Test case: Parameter test****OK**

Parameter test for General block Real2Int.

| Test results   |           |           |     |          |
|----------------|-----------|-----------|-----|----------|
| Time step      | 1         | 2         | ... | 14       |
| CPU cycles     | 356       | 356       | ... | 341      |
| Inputs         |           |           |     |          |
| In (DSP)       | 0.1       |           |     |          |
| In             | 0.1       |           |     |          |
| Parameters     |           |           |     |          |
| Scale          | -10       | -5        | ... | 10       |
| Outputs        |           |           |     |          |
| Out            | -0.01     | -0.02     | ... | 0.01     |
| Exp. Out       | -0.01     | -0.02     | ... | 0.01     |
| Out (DSP)      | -21474838 | -42949676 | ... | 21474838 |
| Exp. Out (DSP) | -21474836 | -42949673 | ... | 21474836 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,7253e-09$ ( $\pm 8$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 341 |
| Max CPU cycles  | 356 |
| Avg CPU cycles  | 348 |

### Test case: Conversion test

OK

Conversion test for General block Real2Int.

| Test results                 |              |              |     |             |
|------------------------------|--------------|--------------|-----|-------------|
| <b>Time step</b>             | 1            | 2            | ... | 14          |
| <i>Mask parameters</i>       |              |              |     |             |
| <b>Scale</b>                 | -10          | -5           | ... | 10          |
| <i>Controller parameters</i> |              |              |     |             |
| <b>scale</b>                 | -214748364.8 | -429496729.6 | ... | 214748364.8 |
| <b>Exp. scale</b>            | -214748364.8 | -429496729.6 | ... | 214748364.8 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Real2Int.



| Test results                 |              |              |     |             |
|------------------------------|--------------|--------------|-----|-------------|
| Time step                    | 1            | 2            | ... | 14          |
| <i>Mask parameters</i>       |              |              |     |             |
| Scale                        | -10          | -5           | ... | 10          |
| <i>Controller parameters</i> |              |              |     |             |
| scale                        | -214748368   | -429496736   | ... | 214748368   |
| Exp. scale                   | -214748364.8 | -429496729.6 | ... | 214748364.8 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 5,0000e+01$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 403 |
| Max CPU cycles  | 448 |
| Avg CPU cycles  | 406 |

**Verification: Real2Int Float32\_FIP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block Real2Int.

| Test results   |            |            |     |           |
|----------------|------------|------------|-----|-----------|
| Time step      | 1          | 2          | ... | 113       |
| CPU cycles     | 204        | 204        | ... | 212       |
| Inputs         |            |            |     |           |
| In (DSP)       | -31        | -30.446    | ... | 31        |
| In             | -31        | -30.446    | ... | 31        |
| Parameters     |            |            |     |           |
| Scale          | 73.5       |            |     |           |
| Outputs        |            |            |     |           |
| Out            | -0.422     | -0.414     | ... | 0.422     |
| Exp. Out       | -0.422     | -0.414     | ... | 0.422     |
| Out (DSP)      | -905741376 | -889567424 | ... | 905741376 |
| Exp. Out (DSP) | -905741403 | -889567449 | ... | 905741403 |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 4,6566\text{e-}08$ ( $\pm 100$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 172 |
| Max CPU cycles  | 212 |
| Avg CPU cycles  | 207 |

**Test case: Parameter test****OK**

Parameter test for General block Real2Int.

| Test results   |           |           |     |          |
|----------------|-----------|-----------|-----|----------|
| Time step      | 1         | 2         | ... | 14       |
| CPU cycles     | 204       | 204       | ... | 212      |
| Inputs         |           |           |     |          |
| In (DSP)       | 0.1       |           |     |          |
| In             | 0.1       |           |     |          |
| Parameters     |           |           |     |          |
| Scale          | -10       | -5        | ... | 10       |
| Outputs        |           |           |     |          |
| Out            | -0.01     | -0.02     | ... | 0.01     |
| Exp. Out       | -0.01     | -0.02     | ... | 0.01     |
| Out (DSP)      | -21474838 | -42949676 | ... | 21474838 |
| Exp. Out (DSP) | -21474836 | -42949673 | ... | 21474836 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,7253e-09$ ( $\pm 8$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 174 |
| Max CPU cycles  | 212 |
| Avg CPU cycles  | 205 |

### Test case: Conversion test

OK

Conversion test for General block Real2Int.

| Test results                 |              |              |     |             |
|------------------------------|--------------|--------------|-----|-------------|
| <b>Time step</b>             | 1            | 2            | ... | 14          |
| <i>Mask parameters</i>       |              |              |     |             |
| <b>Scale</b>                 | -10          | -5           | ... | 10          |
| <i>Controller parameters</i> |              |              |     |             |
| <b>scale</b>                 | -214748364.8 | -429496729.6 | ... | 214748364.8 |
| <b>Exp. scale</b>            | -214748364.8 | -429496729.6 | ... | 214748364.8 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block Real2Int.

| Test results                 |              |              |     |             |
|------------------------------|--------------|--------------|-----|-------------|
| <b>Time step</b>             | 1            | 2            | ... | 14          |
| <i>Mask parameters</i>       |              |              |     |             |
| <b>Scale</b>                 | -10          | -5           | ... | 10          |
| <i>Controller parameters</i> |              |              |     |             |
| <b>scale</b>                 | -214748352   | -429496704   | ... | 214748352   |
| <b>Exp. scale</b>            | -214748364.8 | -429496729.6 | ... | 214748364.8 |

| Test settings   |                  |
|-----------------|------------------|
| Tolerance scale | $\pm 5,0000e+01$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 879 |
| Max CPU cycles  | 879 |
| Avg CPU cycles  | 879 |

**Verification: Real2Int Float32\_Bool CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block Real2Int.

| Test results   |      |      |     |     |
|----------------|------|------|-----|-----|
| Time step      | 1    | 2    | ... | 5   |
| CPU cycles     | 61   | 61   | ... | 61  |
| Inputs         |      |      |     |     |
| In (DSP)       | 3.1  | 0.31 | ... | 3.3 |
| In             | 3.1  | 0.31 | ... | 3.3 |
| Parameters     |      |      |     |     |
| Scale          | 7.35 |      |     |     |
| Outputs        |      |      |     |     |
| Out            | 1    | 1    | ... | 1   |
| Exp. Out       | 1    | 1    | ... | 1   |
| Out (DSP)      | 1    | 1    | ... | 1   |
| Exp. Out (DSP) | 1    | 1    | ... | 1   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 61 |
| Max CPU cycles  | 61 |
| Avg CPU cycles  | 61 |

**Test case: Parameter test****OK**

Parameter test for General block Real2Int.

| Test results   |     |    |     |    |
|----------------|-----|----|-----|----|
| Time step      | 1   | 2  | ... | 14 |
| CPU cycles     | 61  | 61 | ... | 61 |
| Inputs         |     |    |     |    |
| In (DSP)       | 0.1 |    |     |    |
| In             | 0.1 |    |     |    |
| Parameters     |     |    |     |    |
| Scale          | -10 | -5 | ... | 10 |
| Outputs        |     |    |     |    |
| Out            | 1   | 1  | ... | 1  |
| Exp. Out       | 1   | 1  | ... | 1  |
| Out (DSP)      | 1   | 1  | ... | 1  |
| Exp. Out (DSP) | 1   | 1  | ... | 1  |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 4,6566\text{e-}10$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 61 |
| Max CPU cycles  | 61 |
| Avg CPU cycles  | 61 |

**Verification: Real2Int Float32\_Bool CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block Real2Int.

| Test results   |      |      |     |     |
|----------------|------|------|-----|-----|
| Time step      | 1    | 2    | ... | 5   |
| CPU cycles     | 29   | 29   | ... | 29  |
| Inputs         |      |      |     |     |
| In (DSP)       | 3.1  | 0.31 | ... | 3.3 |
| In             | 3.1  | 0.31 | ... | 3.3 |
| Parameters     |      |      |     |     |
| Scale          | 7.35 |      |     |     |
| Outputs        |      |      |     |     |
| Out            | 1    | 1    | ... | 1   |
| Exp. Out       | 1    | 1    | ... | 1   |
| Out (DSP)      | 1    | 1    | ... | 1   |
| Exp. Out (DSP) | 1    | 1    | ... | 1   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 29 |
| Avg CPU cycles  | 29 |

**Test case: Parameter test****OK**

Parameter test for General block Real2Int.

| Test results   |     |    |     |    |
|----------------|-----|----|-----|----|
| Time step      | 1   | 2  | ... | 14 |
| CPU cycles     | 29  | 29 | ... | 29 |
| Inputs         |     |    |     |    |
| In (DSP)       | 0.1 |    |     |    |
| In             | 0.1 |    |     |    |
| Parameters     |     |    |     |    |
| Scale          | -10 | -5 | ... | 10 |
| Outputs        |     |    |     |    |
| Out            | 1   | 1  | ... | 1  |
| Exp. Out       | 1   | 1  | ... | 1  |
| Out (DSP)      | 1   | 1  | ... | 1  |
| Exp. Out (DSP) | 1   | 1  | ... | 1  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 29 |
| Avg CPU cycles  | 29 |



**Verification: Real2Int Float32\_Bool CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block Real2Int.

| Test results   |      |      |     |     |
|----------------|------|------|-----|-----|
| Time step      | 1    | 2    | ... | 5   |
| CPU cycles     | 67   | 67   | ... | 67  |
| Inputs         |      |      |     |     |
| In (DSP)       | 3.1  | 0.31 | ... | 3.3 |
| In             | 3.1  | 0.31 | ... | 3.3 |
| Parameters     |      |      |     |     |
| Scale          | 7.35 |      |     |     |
| Outputs        |      |      |     |     |
| Out            | 1    | 1    | ... | 1   |
| Exp. Out       | 1    | 1    | ... | 1   |
| Out (DSP)      | 1    | 1    | ... | 1   |
| Exp. Out (DSP) | 1    | 1    | ... | 1   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 67 |
| Max CPU cycles  | 67 |
| Avg CPU cycles  | 67 |

**Test case: Parameter test****OK**

Parameter test for General block Real2Int.

| Test results   |     |    |     |    |
|----------------|-----|----|-----|----|
| Time step      | 1   | 2  | ... | 14 |
| CPU cycles     | 67  | 67 | ... | 67 |
| Inputs         |     |    |     |    |
| In (DSP)       | 0.1 |    |     |    |
| In             | 0.1 |    |     |    |
| Parameters     |     |    |     |    |
| Scale          | -10 | -5 | ... | 10 |
| Outputs        |     |    |     |    |
| Out            | 1   | 1  | ... | 1  |
| Exp. Out       | 1   | 1  | ... | 1  |
| Out (DSP)      | 1   | 1  | ... | 1  |
| Exp. Out (DSP) | 1   | 1  | ... | 1  |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 4,6566\text{e-}10$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 67 |
| Max CPU cycles  | 67 |
| Avg CPU cycles  | 67 |

**Verification: Real2Int Float32\_Bool CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block Real2Int.

| Test results   |      |      |     |     |
|----------------|------|------|-----|-----|
| Time step      | 1    | 2    | ... | 5   |
| CPU cycles     | 132  | 132  | ... | 132 |
| Inputs         |      |      |     |     |
| In (DSP)       | 3.1  | 0.31 | ... | 3.3 |
| In             | 3.1  | 0.31 | ... | 3.3 |
| Parameters     |      |      |     |     |
| Scale          | 7.35 |      |     |     |
| Outputs        |      |      |     |     |
| Out            | 1    | 1    | ... | 1   |
| Exp. Out       | 1    | 1    | ... | 1   |
| Out (DSP)      | 1    | 1    | ... | 1   |
| Exp. Out (DSP) | 1    | 1    | ... | 1   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 0$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 127 |
| Max CPU cycles  | 132 |
| Avg CPU cycles  | 131 |

**Test case: Parameter test****OK**

Parameter test for General block Real2Int.

| Test results   |     |     |     |     |
|----------------|-----|-----|-----|-----|
| Time step      | 1   | 2   | ... | 14  |
| CPU cycles     | 132 | 132 | ... | 132 |
| Inputs         |     |     |     |     |
| In (DSP)       | 0.1 |     |     |     |
| In             | 0.1 |     |     |     |
| Parameters     |     |     |     |     |
| Scale          | -10 | -5  | ... | 10  |
| Outputs        |     |     |     |     |
| Out            | 1   | 1   | ... | 1   |
| Exp. Out       | 1   | 1   | ... | 1   |
| Out (DSP)      | 1   | 1   | ... | 1   |
| Exp. Out (DSP) | 1   | 1   | ... | 1   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 0$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 132 |
| Max CPU cycles  | 132 |
| Avg CPU cycles  | 132 |

**Verification: Real2Int Float32\_Bool CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block Real2Int.

| Test results   |      |      |     |     |
|----------------|------|------|-----|-----|
| Time step      | 1    | 2    | ... | 5   |
| CPU cycles     | 74   | 74   | ... | 74  |
| Inputs         |      |      |     |     |
| In (DSP)       | 3.1  | 0.31 | ... | 3.3 |
| In             | 3.1  | 0.31 | ... | 3.3 |
| Parameters     |      |      |     |     |
| Scale          | 7.35 |      |     |     |
| Outputs        |      |      |     |     |
| Out            | 1    | 1    | ... | 1   |
| Exp. Out       | 1    | 1    | ... | 1   |
| Out (DSP)      | 1    | 1    | ... | 1   |
| Exp. Out (DSP) | 1    | 1    | ... | 1   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 50 |
| Max CPU cycles  | 74 |
| Avg CPU cycles  | 69 |

**Test case: Parameter test****OK**

Parameter test for General block Real2Int.

| Test results   |     |    |     |    |
|----------------|-----|----|-----|----|
| Time step      | 1   | 2  | ... | 14 |
| CPU cycles     | 74  | 74 | ... | 74 |
| Inputs         |     |    |     |    |
| In (DSP)       | 0.1 |    |     |    |
| In             | 0.1 |    |     |    |
| Parameters     |     |    |     |    |
| Scale          | -10 | -5 | ... | 10 |
| Outputs        |     |    |     |    |
| Out            | 1   | 1  | ... | 1  |
| Exp. Out       | 1   | 1  | ... | 1  |
| Out (DSP)      | 1   | 1  | ... | 1  |
| Exp. Out (DSP) | 1   | 1  | ... | 1  |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 4,6566\text{e-}10$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 74 |
| Max CPU cycles  | 74 |
| Avg CPU cycles  | 74 |

**Verification: Real2Int Float32\_Bool CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block Real2Int.

| Test results   |      |      |     |     |
|----------------|------|------|-----|-----|
| Time step      | 1    | 2    | ... | 5   |
| CPU cycles     | 151  | 151  | ... | 151 |
| Inputs         |      |      |     |     |
| In (DSP)       | 3.1  | 0.31 | ... | 3.3 |
| In             | 3.1  | 0.31 | ... | 3.3 |
| Parameters     |      |      |     |     |
| Scale          | 7.35 |      |     |     |
| Outputs        |      |      |     |     |
| Out            | 1    | 1    | ... | 1   |
| Exp. Out       | 1    | 1    | ... | 1   |
| Out (DSP)      | 1    | 1    | ... | 1   |
| Exp. Out (DSP) | 1    | 1    | ... | 1   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 0$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 151 |
| Max CPU cycles  | 155 |
| Avg CPU cycles  | 151 |

**Test case: Parameter test****OK**

Parameter test for General block Real2Int.

| Test results   |     |     |     |     |
|----------------|-----|-----|-----|-----|
| Time step      | 1   | 2   | ... | 14  |
| CPU cycles     | 151 | 151 | ... | 151 |
| Inputs         |     |     |     |     |
| In (DSP)       | 0.1 |     |     |     |
| In             | 0.1 |     |     |     |
| Parameters     |     |     |     |     |
| Scale          | -10 | -5  | ... | 10  |
| Outputs        |     |     |     |     |
| Out            | 1   | 1   | ... | 1   |
| Exp. Out       | 1   | 1   | ... | 1   |
| Out (DSP)      | 1   | 1   | ... | 1   |
| Exp. Out (DSP) | 1   | 1   | ... | 1   |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 4,6566\text{e-}10$ ( $\pm 0$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 151 |
| Max CPU cycles  | 151 |
| Avg CPU cycles  | 151 |



**Verification: Real2Int Float32\_Bool CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block Real2Int.

| Test results   |      |      |     |     |
|----------------|------|------|-----|-----|
| Time step      | 1    | 2    | ... | 5   |
| CPU cycles     | 70   | 70   | ... | 70  |
| Inputs         |      |      |     |     |
| In (DSP)       | 3.1  | 0.31 | ... | 3.3 |
| In             | 3.1  | 0.31 | ... | 3.3 |
| Parameters     |      |      |     |     |
| Scale          | 7.35 |      |     |     |
| Outputs        |      |      |     |     |
| Out            | 1    | 1    | ... | 1   |
| Exp. Out       | 1    | 1    | ... | 1   |
| Out (DSP)      | 1    | 1    | ... | 1   |
| Exp. Out (DSP) | 1    | 1    | ... | 1   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 70 |
| Max CPU cycles  | 70 |
| Avg CPU cycles  | 70 |

**Test case: Parameter test****OK**

Parameter test for General block Real2Int.

| Test results   |     |    |     |    |
|----------------|-----|----|-----|----|
| Time step      | 1   | 2  | ... | 14 |
| CPU cycles     | 70  | 70 | ... | 70 |
| Inputs         |     |    |     |    |
| In (DSP)       | 0.1 |    |     |    |
| In             | 0.1 |    |     |    |
| Parameters     |     |    |     |    |
| Scale          | -10 | -5 | ... | 10 |
| Outputs        |     |    |     |    |
| Out            | 1   | 1  | ... | 1  |
| Exp. Out       | 1   | 1  | ... | 1  |
| Out (DSP)      | 1   | 1  | ... | 1  |
| Exp. Out (DSP) | 1   | 1  | ... | 1  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 70 |
| Max CPU cycles  | 70 |
| Avg CPU cycles  | 70 |

**Verification: Real2Int Float32\_Bool CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block Real2Int.

| Test results   |      |      |     |     |
|----------------|------|------|-----|-----|
| Time step      | 1    | 2    | ... | 5   |
| CPU cycles     | 43   | 43   | ... | 43  |
| Inputs         |      |      |     |     |
| In (DSP)       | 3.1  | 0.31 | ... | 3.3 |
| In             | 3.1  | 0.31 | ... | 3.3 |
| Parameters     |      |      |     |     |
| Scale          | 7.35 |      |     |     |
| Outputs        |      |      |     |     |
| Out            | 1    | 1    | ... | 1   |
| Exp. Out       | 1    | 1    | ... | 1   |
| Out (DSP)      | 1    | 1    | ... | 1   |
| Exp. Out (DSP) | 1    | 1    | ... | 1   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 43 |
| Max CPU cycles  | 43 |
| Avg CPU cycles  | 43 |

**Test case: Parameter test****OK**

Parameter test for General block Real2Int.

| Test results   |     |    |     |    |
|----------------|-----|----|-----|----|
| Time step      | 1   | 2  | ... | 14 |
| CPU cycles     | 43  | 43 | ... | 43 |
| Inputs         |     |    |     |    |
| In (DSP)       | 0.1 |    |     |    |
| In             | 0.1 |    |     |    |
| Parameters     |     |    |     |    |
| Scale          | -10 | -5 | ... | 10 |
| Outputs        |     |    |     |    |
| Out            | 1   | 1  | ... | 1  |
| Exp. Out       | 1   | 1  | ... | 1  |
| Out (DSP)      | 1   | 1  | ... | 1  |
| Exp. Out (DSP) | 1   | 1  | ... | 1  |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 4,6566\text{e-}10$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 43 |
| Max CPU cycles  | 43 |
| Avg CPU cycles  | 43 |

## Block: Saturation

---



Saturation of output to adjustable upper and lower limit.

| Inports |       |
|---------|-------|
| In      | Input |

| Outports |                |
|----------|----------------|
| Out      | Limited output |

| Mask Parameters |    |             |
|-----------------|----|-------------|
| Name            | ID | Description |
| max             | 1  | Upper Limit |
| min             | 2  | Lower Limit |

### Description:

If the entry for *Upper Limit* is lower than the entry for *Lower Limit* then the limits will be swapped internally.

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

---

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: Saturation FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block Saturation.

| Test results   |      |        |        |        |     |     |
|----------------|------|--------|--------|--------|-----|-----|
| Time step      | 1    | 2      | 3      | 4      | ... | 137 |
| CPU cycles     | 64   | 64     | 64     | 64     | ... | 64  |
| Inputs         |      |        |        |        |     |     |
| In (DSP)       | 0    | -1513  | -3023  | -4527  | ... | 0   |
| In             | -0   | -0.046 | -0.092 | -0.138 | ... | 0   |
| Parameters     |      |        |        |        |     |     |
| max            | 0.8  |        |        |        |     |     |
| min            | -0.3 |        |        |        |     |     |
| Outputs        |      |        |        |        |     |     |
| Out            | 0    | -0.046 | -0.092 | -0.138 | ... | 0   |
| Exp. Out       | -0   | -0.046 | -0.092 | -0.138 | ... | 0   |
| Out (DSP)      | 0    | -1513  | -3023  | -4527  | ... | 0   |
| Exp. Out (DSP) | 0    | -1513  | -3023  | -4527  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 64 |
| Max CPU cycles  | 64 |
| Avg CPU cycles  | 64 |

**Verification: Saturation FiP16 CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block Saturation.

| Test results   |      |        |        |        |     |     |
|----------------|------|--------|--------|--------|-----|-----|
| Time step      | 1    | 2      | 3      | 4      | ... | 137 |
| CPU cycles     | 33   | 33     | 33     | 33     | ... | 33  |
| Inputs         |      |        |        |        |     |     |
| In (DSP)       | 0    | -1513  | -3023  | -4527  | ... | 0   |
| In             | -0   | -0.046 | -0.092 | -0.138 | ... | 0   |
| Parameters     |      |        |        |        |     |     |
| max            | 0.8  |        |        |        |     |     |
| min            | -0.3 |        |        |        |     |     |
| Outputs        |      |        |        |        |     |     |
| Out            | 0    | -0.046 | -0.092 | -0.138 | ... | 0   |
| Exp. Out       | -0   | -0.046 | -0.092 | -0.138 | ... | 0   |
| Out (DSP)      | 0    | -1513  | -3023  | -4527  | ... | 0   |
| Exp. Out (DSP) | 0    | -1513  | -3023  | -4527  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 33 |
| Avg CPU cycles  | 32 |



**Verification: Saturation FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block Saturation.

| Test results   |      |        |        |        |     |     |
|----------------|------|--------|--------|--------|-----|-----|
| Time step      | 1    | 2      | 3      | 4      | ... | 137 |
| CPU cycles     | 63   | 63     | 63     | 63     | ... | 63  |
| Inputs         |      |        |        |        |     |     |
| In (DSP)       | 0    | -1513  | -3023  | -4527  | ... | 0   |
| In             | -0   | -0.046 | -0.092 | -0.138 | ... | 0   |
| Parameters     |      |        |        |        |     |     |
| max            | 0.8  |        |        |        |     |     |
| min            | -0.3 |        |        |        |     |     |
| Outputs        |      |        |        |        |     |     |
| Out            | 0    | -0.046 | -0.092 | -0.138 | ... | 0   |
| Exp. Out       | -0   | -0.046 | -0.092 | -0.138 | ... | 0   |
| Out (DSP)      | 0    | -1513  | -3023  | -4527  | ... | 0   |
| Exp. Out (DSP) | 0    | -1513  | -3023  | -4527  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 63 |
| Max CPU cycles  | 70 |
| Avg CPU cycles  | 65 |

**Verification: Saturation FiP16 CPU STM32F072RB**

Date of Test 2026-06-19  
Target controller STM32F072RB

**Test case: Inport test****OK**

Inport test for General block Saturation.

| Test results   |      |        |        |        |     |     |
|----------------|------|--------|--------|--------|-----|-----|
| Time step      | 1    | 2      | 3      | 4      | ... | 137 |
| CPU cycles     | 59   | 59     | 59     | 59     | ... | 59  |
| Inputs         |      |        |        |        |     |     |
| In (DSP)       | 0    | -1513  | -3023  | -4527  | ... | 0   |
| In             | -0   | -0.046 | -0.092 | -0.138 | ... | 0   |
| Parameters     |      |        |        |        |     |     |
| max            | 0.8  |        |        |        |     |     |
| min            | -0.3 |        |        |        |     |     |
| Outputs        |      |        |        |        |     |     |
| Out            | 0    | -0.046 | -0.092 | -0.138 | ... | 0   |
| Exp. Out       | -0   | -0.046 | -0.092 | -0.138 | ... | 0   |
| Out (DSP)      | 0    | -1513  | -3023  | -4527  | ... | 0   |
| Exp. Out (DSP) | 0    | -1513  | -3023  | -4527  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 59 |
| Avg CPU cycles  | 58 |

**Verification: Saturation FiP16 CPU PIC32MX170F256**

Date of Test 2026-06-19  
Target controller PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block Saturation.

| Test results   |      |        |        |        |     |     |
|----------------|------|--------|--------|--------|-----|-----|
| Time step      | 1    | 2      | 3      | 4      | ... | 137 |
| CPU cycles     | 38   | 38     | 38     | 38     | ... | 38  |
| Inputs         |      |        |        |        |     |     |
| In (DSP)       | 0    | -1513  | -3023  | -4527  | ... | 0   |
| In             | -0   | -0.046 | -0.092 | -0.138 | ... | 0   |
| Parameters     |      |        |        |        |     |     |
| max            | 0.8  |        |        |        |     |     |
| min            | -0.3 |        |        |        |     |     |
| Outputs        |      |        |        |        |     |     |
| Out            | 0    | -0.046 | -0.092 | -0.138 | ... | 0   |
| Exp. Out       | -0   | -0.046 | -0.092 | -0.138 | ... | 0   |
| Out (DSP)      | 0    | -1513  | -3023  | -4527  | ... | 0   |
| Exp. Out (DSP) | 0    | -1513  | -3023  | -4527  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 34 |
| Max CPU cycles  | 40 |
| Avg CPU cycles  | 38 |

**Verification: Saturation FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block Saturation.

| Test results   |      |        |        |        |     |     |
|----------------|------|--------|--------|--------|-----|-----|
| Time step      | 1    | 2      | 3      | 4      | ... | 137 |
| CPU cycles     | 50   | 50     | 50     | 50     | ... | 50  |
| Inputs         |      |        |        |        |     |     |
| In (DSP)       | 0    | -1513  | -3023  | -4527  | ... | 0   |
| In             | -0   | -0.046 | -0.092 | -0.138 | ... | 0   |
| Parameters     |      |        |        |        |     |     |
| max            | 0.8  |        |        |        |     |     |
| min            | -0.3 |        |        |        |     |     |
| Outputs        |      |        |        |        |     |     |
| Out            | 0    | -0.046 | -0.092 | -0.138 | ... | 0   |
| Exp. Out       | -0   | -0.046 | -0.092 | -0.138 | ... | 0   |
| Out (DSP)      | 0    | -1513  | -3023  | -4527  | ... | 0   |
| Exp. Out (DSP) | 0    | -1513  | -3023  | -4527  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 48 |
| Max CPU cycles  | 50 |
| Avg CPU cycles  | 48 |

**Verification: Saturation FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block Saturation.

| Test results   |      |        |        |        |     |     |
|----------------|------|--------|--------|--------|-----|-----|
| Time step      | 1    | 2      | 3      | 4      | ... | 137 |
| CPU cycles     | 75   | 64     | 64     | 64     | ... | 64  |
| Inputs         |      |        |        |        |     |     |
| In (DSP)       | 0    | -1513  | -3023  | -4527  | ... | 0   |
| In             | -0   | -0.046 | -0.092 | -0.138 | ... | 0   |
| Parameters     |      |        |        |        |     |     |
| max            | 0.8  |        |        |        |     |     |
| min            | -0.3 |        |        |        |     |     |
| Outputs        |      |        |        |        |     |     |
| Out            | 0    | -0.046 | -0.092 | -0.138 | ... | 0   |
| Exp. Out       | -0   | -0.046 | -0.092 | -0.138 | ... | 0   |
| Out (DSP)      | 0    | -1513  | -3023  | -4527  | ... | 0   |
| Exp. Out (DSP) | 0    | -1513  | -3023  | -4527  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 75 |
| Avg CPU cycles  | 63 |

**Verification: Saturation FiP16 CPU TMS320F28379D**

Date of Test 2026-06-22  
Target controller TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block Saturation.

| Test results   |      |        |        |        |     |     |
|----------------|------|--------|--------|--------|-----|-----|
| Time step      | 1    | 2      | 3      | 4      | ... | 137 |
| CPU cycles     | 44   | 44     | 44     | 44     | ... | 44  |
| Inputs         |      |        |        |        |     |     |
| In (DSP)       | 0    | -1513  | -3023  | -4527  | ... | 0   |
| In             | -0   | -0.046 | -0.092 | -0.138 | ... | 0   |
| Parameters     |      |        |        |        |     |     |
| max            | 0.8  |        |        |        |     |     |
| min            | -0.3 |        |        |        |     |     |
| Outputs        |      |        |        |        |     |     |
| Out            | 0    | -0.046 | -0.092 | -0.138 | ... | 0   |
| Exp. Out       | -0   | -0.046 | -0.092 | -0.138 | ... | 0   |
| Out (DSP)      | 0    | -1513  | -3023  | -4527  | ... | 0   |
| Exp. Out (DSP) | 0    | -1513  | -3023  | -4527  | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 44 |
| Max CPU cycles  | 52 |
| Avg CPU cycles  | 45 |

**Verification: Saturation FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block Saturation.

| Test results   |      |           |     |     |
|----------------|------|-----------|-----|-----|
| Time step      | 1    | 2         | ... | 137 |
| CPU cycles     | 68   | 68        | ... | 68  |
| Inputs         |      |           |     |     |
| In (DSP)       | 0    | -99178222 | ... | 0   |
| In             | -0   | -0.046    | ... | 0   |
| Parameters     |      |           |     |     |
| max            | 0.8  |           |     |     |
| min            | -0.3 |           |     |     |
| Outputs        |      |           |     |     |
| Out            | 0    | -0.046    | ... | 0   |
| Exp. Out       | -0   | -0.046    | ... | 0   |
| Out (DSP)      | 0    | -99178222 | ... | 0   |
| Exp. Out (DSP) | 0    | -99178222 | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 63 |
| Max CPU cycles  | 70 |
| Avg CPU cycles  | 67 |

**Verification: Saturation FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block Saturation.

| Test results   |      |           |     |     |
|----------------|------|-----------|-----|-----|
| Time step      | 1    | 2         | ... | 137 |
| CPU cycles     | 31   | 31        | ... | 31  |
| Inputs         |      |           |     |     |
| In (DSP)       | 0    | -99178222 | ... | 0   |
| In             | -0   | -0.046    | ... | 0   |
| Parameters     |      |           |     |     |
| max            | 0.8  |           |     |     |
| min            | -0.3 |           |     |     |
| Outputs        |      |           |     |     |
| Out            | 0    | -0.046    | ... | 0   |
| Exp. Out       | -0   | -0.046    | ... | 0   |
| Out (DSP)      | 0    | -99178222 | ... | 0   |
| Exp. Out (DSP) | 0    | -99178222 | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 27 |
| Max CPU cycles  | 31 |
| Avg CPU cycles  | 30 |



**Verification: Saturation FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block Saturation.

| Test results   |      |           |     |     |
|----------------|------|-----------|-----|-----|
| Time step      | 1    | 2         | ... | 137 |
| CPU cycles     | 62   | 62        | ... | 62  |
| Inputs         |      |           |     |     |
| In (DSP)       | 0    | -99178222 | ... | 0   |
| In             | -0   | -0.046    | ... | 0   |
| Parameters     |      |           |     |     |
| max            | 0.8  |           |     |     |
| min            | -0.3 |           |     |     |
| Outputs        |      |           |     |     |
| Out            | 0    | -0.046    | ... | 0   |
| Exp. Out       | -0   | -0.046    | ... | 0   |
| Out (DSP)      | 0    | -99178222 | ... | 0   |
| Exp. Out (DSP) | 0    | -99178222 | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 62 |
| Avg CPU cycles  | 62 |

**Verification: Saturation FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block Saturation.

| Test results   |      |           |     |     |
|----------------|------|-----------|-----|-----|
| Time step      | 1    | 2         | ... | 137 |
| CPU cycles     | 56   | 56        | ... | 56  |
| Inputs         |      |           |     |     |
| In (DSP)       | 0    | -99178222 | ... | 0   |
| In             | -0   | -0.046    | ... | 0   |
| Parameters     |      |           |     |     |
| max            | 0.8  |           |     |     |
| min            | -0.3 |           |     |     |
| Outputs        |      |           |     |     |
| Out            | 0    | -0.046    | ... | 0   |
| Exp. Out       | -0   | -0.046    | ... | 0   |
| Out (DSP)      | 0    | -99178222 | ... | 0   |
| Exp. Out (DSP) | 0    | -99178222 | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 54 |
| Max CPU cycles  | 56 |
| Avg CPU cycles  | 55 |

**Verification: Saturation FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block Saturation.

| Test results   |      |           |     |     |
|----------------|------|-----------|-----|-----|
| Time step      | 1    | 2         | ... | 137 |
| CPU cycles     | 38   | 38        | ... | 38  |
| Inputs         |      |           |     |     |
| In (DSP)       | 0    | -99178222 | ... | 0   |
| In             | -0   | -0.046    | ... | 0   |
| Parameters     |      |           |     |     |
| max            | 0.8  |           |     |     |
| min            | -0.3 |           |     |     |
| Outputs        |      |           |     |     |
| Out            | 0    | -0.046    | ... | 0   |
| Exp. Out       | -0   | -0.046    | ... | 0   |
| Out (DSP)      | 0    | -99178222 | ... | 0   |
| Exp. Out (DSP) | 0    | -99178222 | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 34 |
| Max CPU cycles  | 40 |
| Avg CPU cycles  | 38 |

**Verification: Saturation FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block Saturation.

| Test results   |      |           |     |     |
|----------------|------|-----------|-----|-----|
| Time step      | 1    | 2         | ... | 137 |
| CPU cycles     | 56   | 56        | ... | 56  |
| Inputs         |      |           |     |     |
| In (DSP)       | 0    | -99178222 | ... | 0   |
| In             | -0   | -0.046    | ... | 0   |
| Parameters     |      |           |     |     |
| max            | 0.8  |           |     |     |
| min            | -0.3 |           |     |     |
| Outputs        |      |           |     |     |
| Out            | 0    | -0.046    | ... | 0   |
| Exp. Out       | -0   | -0.046    | ... | 0   |
| Out (DSP)      | 0    | -99178222 | ... | 0   |
| Exp. Out (DSP) | 0    | -99178222 | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 53 |
| Max CPU cycles  | 56 |
| Avg CPU cycles  | 55 |

**Verification: Saturation FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block Saturation.

| Test results   |      |           |     |     |
|----------------|------|-----------|-----|-----|
| Time step      | 1    | 2         | ... | 137 |
| CPU cycles     | 61   | 61        | ... | 61  |
| Inputs         |      |           |     |     |
| In (DSP)       | 0    | -99178222 | ... | 0   |
| In             | -0   | -0.046    | ... | 0   |
| Parameters     |      |           |     |     |
| max            | 0.8  |           |     |     |
| min            | -0.3 |           |     |     |
| Outputs        |      |           |     |     |
| Out            | 0    | -0.046    | ... | 0   |
| Exp. Out       | -0   | -0.046    | ... | 0   |
| Out (DSP)      | 0    | -99178222 | ... | 0   |
| Exp. Out (DSP) | 0    | -99178222 | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 61 |
| Avg CPU cycles  | 60 |

**Verification: Saturation FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block Saturation.

| Test results   |      |           |     |     |
|----------------|------|-----------|-----|-----|
| Time step      | 1    | 2         | ... | 137 |
| CPU cycles     | 48   | 48        | ... | 48  |
| Inputs         |      |           |     |     |
| In (DSP)       | 0    | -99178222 | ... | 0   |
| In             | -0   | -0.046    | ... | 0   |
| Parameters     |      |           |     |     |
| max            | 0.8  |           |     |     |
| min            | -0.3 |           |     |     |
| Outputs        |      |           |     |     |
| Out            | 0    | -0.046    | ... | 0   |
| Exp. Out       | -0   | -0.046    | ... | 0   |
| Out (DSP)      | 0    | -99178222 | ... | 0   |
| Exp. Out (DSP) | 0    | -99178222 | ... | 0   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 46 |
| Max CPU cycles  | 53 |
| Avg CPU cycles  | 49 |

**Verification: Saturation Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block Saturation.

| Test results   |      |        |     |     |
|----------------|------|--------|-----|-----|
| Time step      | 1    | 2      | ... | 137 |
| CPU cycles     | 70   | 70     | ... | 70  |
| Inputs         |      |        |     |     |
| In (DSP)       | -0   | -0.046 | ... | 0   |
| In             | -0   | -0.046 | ... | 0   |
| Parameters     |      |        |     |     |
| max            | 0.8  |        |     |     |
| min            | -0.3 |        |     |     |
| Outputs        |      |        |     |     |
| Out            | -0   | -0.046 | ... | 0   |
| Exp. Out       | -0   | -0.046 | ... | 0   |
| Out (DSP)      | -0   | -0.046 | ... | 0   |
| Exp. Out (DSP) | -0   | -0.046 | ... | 0   |

| Test settings |                                         |
|---------------|-----------------------------------------|
| Tolerance Out | $\pm 2,7940\text{e-}08$ ( $\pm 60$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 66 |
| Max CPU cycles  | 70 |
| Avg CPU cycles  | 69 |

**Verification: Saturation Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block Saturation.

| Test results   |      |        |     |     |
|----------------|------|--------|-----|-----|
| Time step      | 1    | 2      | ... | 137 |
| CPU cycles     | 39   | 39     | ... | 39  |
| Inputs         |      |        |     |     |
| In (DSP)       | -0   | -0.046 | ... | 0   |
| In             | -0   | -0.046 | ... | 0   |
| Parameters     |      |        |     |     |
| max            | 0.8  |        |     |     |
| min            | -0.3 |        |     |     |
| Outputs        |      |        |     |     |
| Out            | -0   | -0.046 | ... | 0   |
| Exp. Out       | -0   | -0.046 | ... | 0   |
| Out (DSP)      | -0   | -0.046 | ... | 0   |
| Exp. Out (DSP) | -0   | -0.046 | ... | 0   |

| Test settings |                                         |
|---------------|-----------------------------------------|
| Tolerance Out | $\pm 2,7940\text{e-}08$ ( $\pm 60$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 33 |
| Max CPU cycles  | 39 |
| Avg CPU cycles  | 37 |



**Verification: Saturation Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block Saturation.

| Test results   |      |        |     |     |
|----------------|------|--------|-----|-----|
| Time step      | 1    | 2      | ... | 137 |
| CPU cycles     | 73   | 73     | ... | 73  |
| Inputs         |      |        |     |     |
| In (DSP)       | -0   | -0.046 | ... | 0   |
| In             | -0   | -0.046 | ... | 0   |
| Parameters     |      |        |     |     |
| max            | 0.8  |        |     |     |
| min            | -0.3 |        |     |     |
| Outputs        |      |        |     |     |
| Out            | -0   | -0.046 | ... | 0   |
| Exp. Out       | -0   | -0.046 | ... | 0   |
| Out (DSP)      | -0   | -0.046 | ... | 0   |
| Exp. Out (DSP) | -0   | -0.046 | ... | 0   |

| Test settings |                                         |
|---------------|-----------------------------------------|
| Tolerance Out | $\pm 2,7940\text{e-}08$ ( $\pm 60$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 73 |
| Max CPU cycles  | 77 |
| Avg CPU cycles  | 75 |

**Verification: Saturation Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block Saturation.

| Test results   |      |        |     |     |
|----------------|------|--------|-----|-----|
| Time step      | 1    | 2      | ... | 137 |
| CPU cycles     | 223  | 223    | ... | 229 |
| Inputs         |      |        |     |     |
| In (DSP)       | -0   | -0.046 | ... | 0   |
| In             | -0   | -0.046 | ... | 0   |
| Parameters     |      |        |     |     |
| max            | 0.8  |        |     |     |
| min            | -0.3 |        |     |     |
| Outputs        |      |        |     |     |
| Out            | -0   | -0.046 | ... | 0   |
| Exp. Out       | -0   | -0.046 | ... | 0   |
| Out (DSP)      | -0   | -0.046 | ... | 0   |
| Exp. Out (DSP) | -0   | -0.046 | ... | 0   |

| Test settings |                                         |
|---------------|-----------------------------------------|
| Tolerance Out | $\pm 2,7940\text{e-}08$ ( $\pm 60$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 154 |
| Max CPU cycles  | 290 |
| Avg CPU cycles  | 214 |

**Verification: Saturation Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block Saturation.

| Test results   |      |        |     |     |
|----------------|------|--------|-----|-----|
| Time step      | 1    | 2      | ... | 137 |
| CPU cycles     | 124  | 124    | ... | 122 |
| Inputs         |      |        |     |     |
| In (DSP)       | -0   | -0.046 | ... | 0   |
| In             | -0   | -0.046 | ... | 0   |
| Parameters     |      |        |     |     |
| max            | 0.8  |        |     |     |
| min            | -0.3 |        |     |     |
| Outputs        |      |        |     |     |
| Out            | -0   | -0.046 | ... | 0   |
| Exp. Out       | -0   | -0.046 | ... | 0   |
| Out (DSP)      | -0   | -0.046 | ... | 0   |
| Exp. Out (DSP) | -0   | -0.046 | ... | 0   |

| Test settings |                                         |
|---------------|-----------------------------------------|
| Tolerance Out | $\pm 2,7940\text{e-}08$ ( $\pm 60$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 86  |
| Max CPU cycles  | 125 |
| Avg CPU cycles  | 116 |

**Verification: Saturation Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block Saturation.

| Test results   |      |        |     |     |
|----------------|------|--------|-----|-----|
| Time step      | 1    | 2      | ... | 137 |
| CPU cycles     | 260  | 260    | ... | 260 |
| Inputs         |      |        |     |     |
| In (DSP)       | -0   | -0.046 | ... | 0   |
| In             | -0   | -0.046 | ... | 0   |
| Parameters     |      |        |     |     |
| max            | 0.8  |        |     |     |
| min            | -0.3 |        |     |     |
| Outputs        |      |        |     |     |
| Out            | -0   | -0.046 | ... | 0   |
| Exp. Out       | -0   | -0.046 | ... | 0   |
| Out (DSP)      | -0   | -0.046 | ... | 0   |
| Exp. Out (DSP) | -0   | -0.046 | ... | 0   |

| Test settings |                                         |
|---------------|-----------------------------------------|
| Tolerance Out | $\pm 2,7940\text{e-}08$ ( $\pm 60$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 164 |
| Max CPU cycles  | 264 |
| Avg CPU cycles  | 241 |

**Verification: Saturation Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block Saturation.

| Test results   |      |        |     |     |
|----------------|------|--------|-----|-----|
| Time step      | 1    | 2      | ... | 137 |
| CPU cycles     | 76   | 64     | ... | 64  |
| Inputs         |      |        |     |     |
| In (DSP)       | -0   | -0.046 | ... | 0   |
| In             | -0   | -0.046 | ... | 0   |
| Parameters     |      |        |     |     |
| max            | 0.8  |        |     |     |
| min            | -0.3 |        |     |     |
| Outputs        |      |        |     |     |
| Out            | -0   | -0.046 | ... | 0   |
| Exp. Out       | -0   | -0.046 | ... | 0   |
| Out (DSP)      | -0   | -0.046 | ... | 0   |
| Exp. Out (DSP) | -0   | -0.046 | ... | 0   |

| Test settings |                                         |
|---------------|-----------------------------------------|
| Tolerance Out | $\pm 2,7940\text{e-}08$ ( $\pm 60$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 61 |
| Max CPU cycles  | 76 |
| Avg CPU cycles  | 63 |

**Verification: Saturation Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block Saturation.

| Test results   |      |        |     |     |
|----------------|------|--------|-----|-----|
| Time step      | 1    | 2      | ... | 137 |
| CPU cycles     | 55   | 55     | ... | 55  |
| Inputs         |      |        |     |     |
| In (DSP)       | -0   | -0.046 | ... | 0   |
| In             | -0   | -0.046 | ... | 0   |
| Parameters     |      |        |     |     |
| max            | 0.8  |        |     |     |
| min            | -0.3 |        |     |     |
| Outputs        |      |        |     |     |
| Out            | -0   | -0.046 | ... | 0   |
| Exp. Out       | -0   | -0.046 | ... | 0   |
| Out (DSP)      | -0   | -0.046 | ... | 0   |
| Exp. Out (DSP) | -0   | -0.046 | ... | 0   |

| Test settings |                                         |
|---------------|-----------------------------------------|
| Tolerance Out | $\pm 2,7940\text{e-}08$ ( $\pm 60$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 53 |
| Max CPU cycles  | 55 |
| Avg CPU cycles  | 54 |

## Block: SaveSignal

---



Makes the incoming signal accessible for reading with parameter numbers.

| Inports |                          |
|---------|--------------------------|
| In      | Input signal to be saved |

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>Bool</b>    | Boolean Implementation               |
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: Bool

---

Boolean Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | bool |

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | int8 |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |

### Implementation: FiP32

---

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

### Implementation: Float32

---

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

### Implementation: Float64

---


64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |



## Block: Selector

---



Passing through of input signal selected by the select inport:

Select = 0 (DSP): Out = In0

Select = 1 (DSP): Out = In1

...

Select = 7 (DSP): Out = In7

| Inports |              |
|---------|--------------|
| In0     | Input #0     |
| In1     | Input #1     |
| In2     | Input #2     |
| In3     | Input #3     |
| In4     | Input #4     |
| In5     | Input #5     |
| In6     | Input #6     |
| In7     | Input #7     |
| Select  | Input select |

| Outports |                       |
|----------|-----------------------|
| Out      | Selected input signal |

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In0               | int8 |
| In1               | int8 |
| In2               | int8 |
| In3               | int8 |
| In4               | int8 |
| In5               | int8 |
| In6               | int8 |
| In7               | int8 |
| Select            | int8 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In0               | int16 |
| In1               | int16 |
| In2               | int16 |
| In3               | int16 |
| In4               | int16 |
| In5               | int16 |
| In6               | int16 |
| In7               | int16 |
| Select            | int8  |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In0               | int32 |
| In1               | int32 |
| In2               | int32 |
| In3               | int32 |
| In4               | int32 |
| In5               | int32 |
| In6               | int32 |
| In7               | int32 |
| Select            | int8  |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In0               | float32 |
| In1               | float32 |
| In2               | float32 |
| In3               | float32 |
| In4               | float32 |
| In5               | float32 |
| In6               | float32 |
| In7               | float32 |
| Select            | int8    |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In0               | float64 |
| In1               | float64 |
| In2               | float64 |
| In3               | float64 |
| In4               | float64 |
| In5               | float64 |
| In6               | float64 |
| In7               | float64 |
| Select            | int8    |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: Selector FiP16 CPU TMS320F28335**

Date of Test 2026-06-19  
Target controller TMS320F28335

**Test case: Inport test****OK**

Inport test for General block Selector.

| Test results   |       |        |       |        |     |        |
|----------------|-------|--------|-------|--------|-----|--------|
| Time step      | 1     | 2      | 3     | 4      | ... | 16     |
| CPU cycles     | 68    | 68     | 68    | 68     | ... | 68     |
| Inputs         |       |        |       |        |     |        |
| In0 (DSP)      | 3277  | -3277  | 3277  | -3277  | ... | -3277  |
| In1 (DSP)      | 6554  | -6554  | 6554  | -6554  | ... | -6554  |
| In2 (DSP)      | 9830  | -9830  | 9830  | -9830  | ... | -9830  |
| In3 (DSP)      | 13107 | -13107 | 13107 | -13107 | ... | -13107 |
| In4 (DSP)      | 16384 | -16384 | 16384 | -16384 | ... | -16384 |
| In5 (DSP)      | 19661 | -19661 | 19661 | -19661 | ... | -19661 |
| In6 (DSP)      | 22938 | -22938 | 22938 | -22938 | ... | -22938 |
| In7 (DSP)      | 26214 | -26214 | 26214 | -26214 | ... | -26214 |
| Select (DSP)   | 0     | 0      | 1     | 1      | ... | 7      |
| In0            | 0.1   | -0.1   | 0.1   | -0.1   | ... | -0.1   |
| In1            | 0.2   | -0.2   | 0.2   | -0.2   | ... | -0.2   |
| In2            | 0.3   | -0.3   | 0.3   | -0.3   | ... | -0.3   |
| In3            | 0.4   | -0.4   | 0.4   | -0.4   | ... | -0.4   |
| In4            | 0.5   | -0.5   | 0.5   | -0.5   | ... | -0.5   |
| In5            | 0.6   | -0.6   | 0.6   | -0.6   | ... | -0.6   |
| In6            | 0.7   | -0.7   | 0.7   | -0.7   | ... | -0.7   |
| In7            | 0.8   | -0.8   | 0.8   | -0.8   | ... | -0.8   |
| Select         | 0     | 0      | 0.008 | 0.008  | ... | 0.055  |
| Outputs        |       |        |       |        |     |        |
| Out            | 0.1   | -0.1   | 0.2   | -0.2   | ... | -0.8   |
| Exp. Out       | 0.1   | -0.1   | 0.2   | -0.2   | ... | -0.8   |
| Out (DSP)      | 3277  | -3277  | 6554  | -6554  | ... | -26214 |
| Exp. Out (DSP) | 3277  | -3277  | 6554  | -6554  | ... | -26214 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 68 |
| Max CPU cycles  | 68 |
| Avg CPU cycles  | 68 |

**Verification: Selector FiP16 CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block Selector.

| Test results   |       |        |       |        |     |        |
|----------------|-------|--------|-------|--------|-----|--------|
| Time step      | 1     | 2      | 3     | 4      | ... | 16     |
| CPU cycles     | 29    | 29     | 29    | 29     | ... | 29     |
| Inputs         |       |        |       |        |     |        |
| In0 (DSP)      | 3277  | -3277  | 3277  | -3277  | ... | -3277  |
| In1 (DSP)      | 6554  | -6554  | 6554  | -6554  | ... | -6554  |
| In2 (DSP)      | 9830  | -9830  | 9830  | -9830  | ... | -9830  |
| In3 (DSP)      | 13107 | -13107 | 13107 | -13107 | ... | -13107 |
| In4 (DSP)      | 16384 | -16384 | 16384 | -16384 | ... | -16384 |
| In5 (DSP)      | 19661 | -19661 | 19661 | -19661 | ... | -19661 |
| In6 (DSP)      | 22938 | -22938 | 22938 | -22938 | ... | -22938 |
| In7 (DSP)      | 26214 | -26214 | 26214 | -26214 | ... | -26214 |
| Select (DSP)   | 0     | 0      | 1     | 1      | ... | 7      |
| In0            | 0.1   | -0.1   | 0.1   | -0.1   | ... | -0.1   |
| In1            | 0.2   | -0.2   | 0.2   | -0.2   | ... | -0.2   |
| In2            | 0.3   | -0.3   | 0.3   | -0.3   | ... | -0.3   |
| In3            | 0.4   | -0.4   | 0.4   | -0.4   | ... | -0.4   |
| In4            | 0.5   | -0.5   | 0.5   | -0.5   | ... | -0.5   |
| In5            | 0.6   | -0.6   | 0.6   | -0.6   | ... | -0.6   |
| In6            | 0.7   | -0.7   | 0.7   | -0.7   | ... | -0.7   |
| In7            | 0.8   | -0.8   | 0.8   | -0.8   | ... | -0.8   |
| Select         | 0     | 0      | 0.008 | 0.008  | ... | 0.055  |
| Outputs        |       |        |       |        |     |        |
| Out            | 0.1   | -0.1   | 0.2   | -0.2   | ... | -0.8   |
| Exp. Out       | 0.1   | -0.1   | 0.2   | -0.2   | ... | -0.8   |
| Out (DSP)      | 3277  | -3277  | 6554  | -6554  | ... | -26214 |
| Exp. Out (DSP) | 3277  | -3277  | 6554  | -6554  | ... | -26214 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 29 |
| Avg CPU cycles  | 29 |



**Verification: Selector FiP16 CPU STM32G474RE**

Date of Test 2026-06-19  
Target controller STM32G474RE

**Test case: Inport test****OK**

Inport test for General block Selector.

| Test results   |       |        |       |        |     |        |
|----------------|-------|--------|-------|--------|-----|--------|
| Time step      | 1     | 2      | 3     | 4      | ... | 16     |
| CPU cycles     | 62    | 62     | 62    | 62     | ... | 62     |
| Inputs         |       |        |       |        |     |        |
| In0 (DSP)      | 3277  | -3277  | 3277  | -3277  | ... | -3277  |
| In1 (DSP)      | 6554  | -6554  | 6554  | -6554  | ... | -6554  |
| In2 (DSP)      | 9830  | -9830  | 9830  | -9830  | ... | -9830  |
| In3 (DSP)      | 13107 | -13107 | 13107 | -13107 | ... | -13107 |
| In4 (DSP)      | 16384 | -16384 | 16384 | -16384 | ... | -16384 |
| In5 (DSP)      | 19661 | -19661 | 19661 | -19661 | ... | -19661 |
| In6 (DSP)      | 22938 | -22938 | 22938 | -22938 | ... | -22938 |
| In7 (DSP)      | 26214 | -26214 | 26214 | -26214 | ... | -26214 |
| Select (DSP)   | 0     | 0      | 1     | 1      | ... | 7      |
| In0            | 0.1   | -0.1   | 0.1   | -0.1   | ... | -0.1   |
| In1            | 0.2   | -0.2   | 0.2   | -0.2   | ... | -0.2   |
| In2            | 0.3   | -0.3   | 0.3   | -0.3   | ... | -0.3   |
| In3            | 0.4   | -0.4   | 0.4   | -0.4   | ... | -0.4   |
| In4            | 0.5   | -0.5   | 0.5   | -0.5   | ... | -0.5   |
| In5            | 0.6   | -0.6   | 0.6   | -0.6   | ... | -0.6   |
| In6            | 0.7   | -0.7   | 0.7   | -0.7   | ... | -0.7   |
| In7            | 0.8   | -0.8   | 0.8   | -0.8   | ... | -0.8   |
| Select         | 0     | 0      | 0.008 | 0.008  | ... | 0.055  |
| Outputs        |       |        |       |        |     |        |
| Out            | 0.1   | -0.1   | 0.2   | -0.2   | ... | -0.8   |
| Exp. Out       | 0.1   | -0.1   | 0.2   | -0.2   | ... | -0.8   |
| Out (DSP)      | 3277  | -3277  | 6554  | -6554  | ... | -26214 |
| Exp. Out (DSP) | 3277  | -3277  | 6554  | -6554  | ... | -26214 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 62 |
| Avg CPU cycles  | 62 |

**Verification: Selector FiP16 CPU STM32F072RB**

Date of Test 2026-06-19  
Target controller STM32F072RB

**Test case: Inport test****OK**

Inport test for General block Selector.

| Test results   |       |        |       |        |     |        |
|----------------|-------|--------|-------|--------|-----|--------|
| Time step      | 1     | 2      | 3     | 4      | ... | 16     |
| CPU cycles     | 55    | 55     | 55    | 55     | ... | 55     |
| Inputs         |       |        |       |        |     |        |
| In0 (DSP)      | 3277  | -3277  | 3277  | -3277  | ... | -3277  |
| In1 (DSP)      | 6554  | -6554  | 6554  | -6554  | ... | -6554  |
| In2 (DSP)      | 9830  | -9830  | 9830  | -9830  | ... | -9830  |
| In3 (DSP)      | 13107 | -13107 | 13107 | -13107 | ... | -13107 |
| In4 (DSP)      | 16384 | -16384 | 16384 | -16384 | ... | -16384 |
| In5 (DSP)      | 19661 | -19661 | 19661 | -19661 | ... | -19661 |
| In6 (DSP)      | 22938 | -22938 | 22938 | -22938 | ... | -22938 |
| In7 (DSP)      | 26214 | -26214 | 26214 | -26214 | ... | -26214 |
| Select (DSP)   | 0     | 0      | 1     | 1      | ... | 7      |
| In0            | 0.1   | -0.1   | 0.1   | -0.1   | ... | -0.1   |
| In1            | 0.2   | -0.2   | 0.2   | -0.2   | ... | -0.2   |
| In2            | 0.3   | -0.3   | 0.3   | -0.3   | ... | -0.3   |
| In3            | 0.4   | -0.4   | 0.4   | -0.4   | ... | -0.4   |
| In4            | 0.5   | -0.5   | 0.5   | -0.5   | ... | -0.5   |
| In5            | 0.6   | -0.6   | 0.6   | -0.6   | ... | -0.6   |
| In6            | 0.7   | -0.7   | 0.7   | -0.7   | ... | -0.7   |
| In7            | 0.8   | -0.8   | 0.8   | -0.8   | ... | -0.8   |
| Select         | 0     | 0      | 0.008 | 0.008  | ... | 0.055  |
| Outputs        |       |        |       |        |     |        |
| Out            | 0.1   | -0.1   | 0.2   | -0.2   | ... | -0.8   |
| Exp. Out       | 0.1   | -0.1   | 0.2   | -0.2   | ... | -0.8   |
| Out (DSP)      | 3277  | -3277  | 6554  | -6554  | ... | -26214 |
| Exp. Out (DSP) | 3277  | -3277  | 6554  | -6554  | ... | -26214 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 55 |
| Max CPU cycles  | 55 |
| Avg CPU cycles  | 55 |

**Verification: Selector FiP16 CPU PIC32MX170F256**

Date of Test 2026-06-19  
Target controller PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block Selector.

| Test results   |       |        |       |        |     |        |
|----------------|-------|--------|-------|--------|-----|--------|
| Time step      | 1     | 2      | 3     | 4      | ... | 16     |
| CPU cycles     | 36    | 36     | 36    | 36     | ... | 36     |
| Inputs         |       |        |       |        |     |        |
| In0 (DSP)      | 3277  | -3277  | 3277  | -3277  | ... | -3277  |
| In1 (DSP)      | 6554  | -6554  | 6554  | -6554  | ... | -6554  |
| In2 (DSP)      | 9830  | -9830  | 9830  | -9830  | ... | -9830  |
| In3 (DSP)      | 13107 | -13107 | 13107 | -13107 | ... | -13107 |
| In4 (DSP)      | 16384 | -16384 | 16384 | -16384 | ... | -16384 |
| In5 (DSP)      | 19661 | -19661 | 19661 | -19661 | ... | -19661 |
| In6 (DSP)      | 22938 | -22938 | 22938 | -22938 | ... | -22938 |
| In7 (DSP)      | 26214 | -26214 | 26214 | -26214 | ... | -26214 |
| Select (DSP)   | 0     | 0      | 1     | 1      | ... | 7      |
| In0            | 0.1   | -0.1   | 0.1   | -0.1   | ... | -0.1   |
| In1            | 0.2   | -0.2   | 0.2   | -0.2   | ... | -0.2   |
| In2            | 0.3   | -0.3   | 0.3   | -0.3   | ... | -0.3   |
| In3            | 0.4   | -0.4   | 0.4   | -0.4   | ... | -0.4   |
| In4            | 0.5   | -0.5   | 0.5   | -0.5   | ... | -0.5   |
| In5            | 0.6   | -0.6   | 0.6   | -0.6   | ... | -0.6   |
| In6            | 0.7   | -0.7   | 0.7   | -0.7   | ... | -0.7   |
| In7            | 0.8   | -0.8   | 0.8   | -0.8   | ... | -0.8   |
| Select         | 0     | 0      | 0.008 | 0.008  | ... | 0.055  |
| Outputs        |       |        |       |        |     |        |
| Out            | 0.1   | -0.1   | 0.2   | -0.2   | ... | -0.8   |
| Exp. Out       | 0.1   | -0.1   | 0.2   | -0.2   | ... | -0.8   |
| Out (DSP)      | 3277  | -3277  | 6554  | -6554  | ... | -26214 |
| Exp. Out (DSP) | 3277  | -3277  | 6554  | -6554  | ... | -26214 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 36 |
| Max CPU cycles  | 36 |
| Avg CPU cycles  | 36 |

**Verification: Selector FiP16 CPU dsPIC33EP256MC502**

Date of Test 2026-06-19  
Target controller dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block Selector.

| Test results   |       |        |       |        |     |        |
|----------------|-------|--------|-------|--------|-----|--------|
| Time step      | 1     | 2      | 3     | 4      | ... | 16     |
| CPU cycles     | 48    | 48     | 48    | 48     | ... | 48     |
| Inputs         |       |        |       |        |     |        |
| In0 (DSP)      | 3277  | -3277  | 3277  | -3277  | ... | -3277  |
| In1 (DSP)      | 6554  | -6554  | 6554  | -6554  | ... | -6554  |
| In2 (DSP)      | 9830  | -9830  | 9830  | -9830  | ... | -9830  |
| In3 (DSP)      | 13107 | -13107 | 13107 | -13107 | ... | -13107 |
| In4 (DSP)      | 16384 | -16384 | 16384 | -16384 | ... | -16384 |
| In5 (DSP)      | 19661 | -19661 | 19661 | -19661 | ... | -19661 |
| In6 (DSP)      | 22938 | -22938 | 22938 | -22938 | ... | -22938 |
| In7 (DSP)      | 26214 | -26214 | 26214 | -26214 | ... | -26214 |
| Select (DSP)   | 0     | 0      | 1     | 1      | ... | 7      |
| In0            | 0.1   | -0.1   | 0.1   | -0.1   | ... | -0.1   |
| In1            | 0.2   | -0.2   | 0.2   | -0.2   | ... | -0.2   |
| In2            | 0.3   | -0.3   | 0.3   | -0.3   | ... | -0.3   |
| In3            | 0.4   | -0.4   | 0.4   | -0.4   | ... | -0.4   |
| In4            | 0.5   | -0.5   | 0.5   | -0.5   | ... | -0.5   |
| In5            | 0.6   | -0.6   | 0.6   | -0.6   | ... | -0.6   |
| In6            | 0.7   | -0.7   | 0.7   | -0.7   | ... | -0.7   |
| In7            | 0.8   | -0.8   | 0.8   | -0.8   | ... | -0.8   |
| Select         | 0     | 0      | 0.008 | 0.008  | ... | 0.055  |
| Outputs        |       |        |       |        |     |        |
| Out            | 0.1   | -0.1   | 0.2   | -0.2   | ... | -0.8   |
| Exp. Out       | 0.1   | -0.1   | 0.2   | -0.2   | ... | -0.8   |
| Out (DSP)      | 3277  | -3277  | 6554  | -6554  | ... | -26214 |
| Exp. Out (DSP) | 3277  | -3277  | 6554  | -6554  | ... | -26214 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 3,0518\text{e-}05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 48 |
| Max CPU cycles  | 48 |
| Avg CPU cycles  | 48 |



**Verification: Selector FiP16 CPU XMC4800-F144K2048**

Date of Test 2026-06-19  
Target controller XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block Selector.

| Test results   |       |        |       |        |     |        |
|----------------|-------|--------|-------|--------|-----|--------|
| Time step      | 1     | 2      | 3     | 4      | ... | 16     |
| CPU cycles     | 70    | 62     | 62    | 62     | ... | 62     |
| Inputs         |       |        |       |        |     |        |
| In0 (DSP)      | 3277  | -3277  | 3277  | -3277  | ... | -3277  |
| In1 (DSP)      | 6554  | -6554  | 6554  | -6554  | ... | -6554  |
| In2 (DSP)      | 9830  | -9830  | 9830  | -9830  | ... | -9830  |
| In3 (DSP)      | 13107 | -13107 | 13107 | -13107 | ... | -13107 |
| In4 (DSP)      | 16384 | -16384 | 16384 | -16384 | ... | -16384 |
| In5 (DSP)      | 19661 | -19661 | 19661 | -19661 | ... | -19661 |
| In6 (DSP)      | 22938 | -22938 | 22938 | -22938 | ... | -22938 |
| In7 (DSP)      | 26214 | -26214 | 26214 | -26214 | ... | -26214 |
| Select (DSP)   | 0     | 0      | 1     | 1      | ... | 7      |
| In0            | 0.1   | -0.1   | 0.1   | -0.1   | ... | -0.1   |
| In1            | 0.2   | -0.2   | 0.2   | -0.2   | ... | -0.2   |
| In2            | 0.3   | -0.3   | 0.3   | -0.3   | ... | -0.3   |
| In3            | 0.4   | -0.4   | 0.4   | -0.4   | ... | -0.4   |
| In4            | 0.5   | -0.5   | 0.5   | -0.5   | ... | -0.5   |
| In5            | 0.6   | -0.6   | 0.6   | -0.6   | ... | -0.6   |
| In6            | 0.7   | -0.7   | 0.7   | -0.7   | ... | -0.7   |
| In7            | 0.8   | -0.8   | 0.8   | -0.8   | ... | -0.8   |
| Select         | 0     | 0      | 0.008 | 0.008  | ... | 0.055  |
| Outputs        |       |        |       |        |     |        |
| Out            | 0.1   | -0.1   | 0.2   | -0.2   | ... | -0.8   |
| Exp. Out       | 0.1   | -0.1   | 0.2   | -0.2   | ... | -0.8   |
| Out (DSP)      | 3277  | -3277  | 6554  | -6554  | ... | -26214 |
| Exp. Out (DSP) | 3277  | -3277  | 6554  | -6554  | ... | -26214 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 70 |
| Avg CPU cycles  | 62 |

**Verification: Selector FiP16 CPU TMS320F28379D**

Date of Test 2026-06-22  
Target controller TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block Selector.

| Test results   |       |        |       |        |     |        |
|----------------|-------|--------|-------|--------|-----|--------|
| Time step      | 1     | 2      | 3     | 4      | ... | 16     |
| CPU cycles     | 51    | 51     | 51    | 51     | ... | 51     |
| Inputs         |       |        |       |        |     |        |
| In0 (DSP)      | 3277  | -3277  | 3277  | -3277  | ... | -3277  |
| In1 (DSP)      | 6554  | -6554  | 6554  | -6554  | ... | -6554  |
| In2 (DSP)      | 9830  | -9830  | 9830  | -9830  | ... | -9830  |
| In3 (DSP)      | 13107 | -13107 | 13107 | -13107 | ... | -13107 |
| In4 (DSP)      | 16384 | -16384 | 16384 | -16384 | ... | -16384 |
| In5 (DSP)      | 19661 | -19661 | 19661 | -19661 | ... | -19661 |
| In6 (DSP)      | 22938 | -22938 | 22938 | -22938 | ... | -22938 |
| In7 (DSP)      | 26214 | -26214 | 26214 | -26214 | ... | -26214 |
| Select (DSP)   | 0     | 0      | 1     | 1      | ... | 7      |
| In0            | 0.1   | -0.1   | 0.1   | -0.1   | ... | -0.1   |
| In1            | 0.2   | -0.2   | 0.2   | -0.2   | ... | -0.2   |
| In2            | 0.3   | -0.3   | 0.3   | -0.3   | ... | -0.3   |
| In3            | 0.4   | -0.4   | 0.4   | -0.4   | ... | -0.4   |
| In4            | 0.5   | -0.5   | 0.5   | -0.5   | ... | -0.5   |
| In5            | 0.6   | -0.6   | 0.6   | -0.6   | ... | -0.6   |
| In6            | 0.7   | -0.7   | 0.7   | -0.7   | ... | -0.7   |
| In7            | 0.8   | -0.8   | 0.8   | -0.8   | ... | -0.8   |
| Select         | 0     | 0      | 0.008 | 0.008  | ... | 0.055  |
| Outputs        |       |        |       |        |     |        |
| Out            | 0.1   | -0.1   | 0.2   | -0.2   | ... | -0.8   |
| Exp. Out       | 0.1   | -0.1   | 0.2   | -0.2   | ... | -0.8   |
| Out (DSP)      | 3277  | -3277  | 6554  | -6554  | ... | -26214 |
| Exp. Out (DSP) | 3277  | -3277  | 6554  | -6554  | ... | -26214 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 3,0518\text{e-}05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 51 |
| Max CPU cycles  | 51 |
| Avg CPU cycles  | 51 |

**Verification: Selector FiP32 CPU TMS320F28335**

Date of Test 2026-06-19  
Target controller TMS320F28335

**Test case: Inport test****OK**

Inport test for General block Selector.

| Test results   |            |             |     |             |
|----------------|------------|-------------|-----|-------------|
| Time step      | 1          | 2           | ... | 16          |
| CPU cycles     | 68         | 68          | ... | 68          |
| Inputs         |            |             |     |             |
| In0 (DSP)      | 214748365  | -214748365  | ... | -214748365  |
| In1 (DSP)      | 429496730  | -429496730  | ... | -429496730  |
| In2 (DSP)      | 644245094  | -644245094  | ... | -644245094  |
| In3 (DSP)      | 858993459  | -858993459  | ... | -858993459  |
| In4 (DSP)      | 1073741824 | -1073741824 | ... | -1073741824 |
| In5 (DSP)      | 1288490189 | -1288490189 | ... | -1288490189 |
| In6 (DSP)      | 1503238554 | -1503238554 | ... | -1503238554 |
| In7 (DSP)      | 1717986918 | -1717986918 | ... | -1717986918 |
| Select (DSP)   | 0          | 0           | ... | 7           |
| In0            | 0.1        | -0.1        | ... | -0.1        |
| In1            | 0.2        | -0.2        | ... | -0.2        |
| In2            | 0.3        | -0.3        | ... | -0.3        |
| In3            | 0.4        | -0.4        | ... | -0.4        |
| In4            | 0.5        | -0.5        | ... | -0.5        |
| In5            | 0.6        | -0.6        | ... | -0.6        |
| In6            | 0.7        | -0.7        | ... | -0.7        |
| In7            | 0.8        | -0.8        | ... | -0.8        |
| Select         | 0          | 0           | ... | 0.055       |
| Outputs        |            |             |     |             |
| Out            | 0.1        | -0.1        | ... | -0.8        |
| Exp. Out       | 0.1        | -0.1        | ... | -0.8        |
| Out (DSP)      | 214748365  | -214748365  | ... | -1717986918 |
| Exp. Out (DSP) | 214748365  | -214748365  | ... | -1717986918 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 68 |
| Max CPU cycles  | 68 |
| Avg CPU cycles  | 68 |

**Verification: Selector FiP32 CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block Selector.

| Test results   |            |             |     |             |
|----------------|------------|-------------|-----|-------------|
| Time step      | 1          | 2           | ... | 16          |
| CPU cycles     | 29         | 29          | ... | 29          |
| Inputs         |            |             |     |             |
| In0 (DSP)      | 214748365  | -214748365  | ... | -214748365  |
| In1 (DSP)      | 429496730  | -429496730  | ... | -429496730  |
| In2 (DSP)      | 644245094  | -644245094  | ... | -644245094  |
| In3 (DSP)      | 858993459  | -858993459  | ... | -858993459  |
| In4 (DSP)      | 1073741824 | -1073741824 | ... | -1073741824 |
| In5 (DSP)      | 1288490189 | -1288490189 | ... | -1288490189 |
| In6 (DSP)      | 1503238554 | -1503238554 | ... | -1503238554 |
| In7 (DSP)      | 1717986918 | -1717986918 | ... | -1717986918 |
| Select (DSP)   | 0          | 0           | ... | 7           |
| In0            | 0.1        | -0.1        | ... | -0.1        |
| In1            | 0.2        | -0.2        | ... | -0.2        |
| In2            | 0.3        | -0.3        | ... | -0.3        |
| In3            | 0.4        | -0.4        | ... | -0.4        |
| In4            | 0.5        | -0.5        | ... | -0.5        |
| In5            | 0.6        | -0.6        | ... | -0.6        |
| In6            | 0.7        | -0.7        | ... | -0.7        |
| In7            | 0.8        | -0.8        | ... | -0.8        |
| Select         | 0          | 0           | ... | 0.055       |
| Outputs        |            |             |     |             |
| Out            | 0.1        | -0.1        | ... | -0.8        |
| Exp. Out       | 0.1        | -0.1        | ... | -0.8        |
| Out (DSP)      | 214748365  | -214748365  | ... | -1717986918 |
| Exp. Out (DSP) | 214748365  | -214748365  | ... | -1717986918 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 29 |
| Avg CPU cycles  | 29 |



**Verification: Selector FiP32 CPU STM32G474RE**

Date of Test 2026-06-19  
Target controller STM32G474RE

**Test case: Inport test****OK**

Inport test for General block Selector.

| Test results   |            |             |     |             |
|----------------|------------|-------------|-----|-------------|
| Time step      | 1          | 2           | ... | 16          |
| CPU cycles     | 62         | 62          | ... | 62          |
| <i>Inputs</i>  |            |             |     |             |
| In0 (DSP)      | 214748365  | -214748365  | ... | -214748365  |
| In1 (DSP)      | 429496730  | -429496730  | ... | -429496730  |
| In2 (DSP)      | 644245094  | -644245094  | ... | -644245094  |
| In3 (DSP)      | 858993459  | -858993459  | ... | -858993459  |
| In4 (DSP)      | 1073741824 | -1073741824 | ... | -1073741824 |
| In5 (DSP)      | 1288490189 | -1288490189 | ... | -1288490189 |
| In6 (DSP)      | 1503238554 | -1503238554 | ... | -1503238554 |
| In7 (DSP)      | 1717986918 | -1717986918 | ... | -1717986918 |
| Select (DSP)   | 0          | 0           | ... | 7           |
| In0            | 0.1        | -0.1        | ... | -0.1        |
| In1            | 0.2        | -0.2        | ... | -0.2        |
| In2            | 0.3        | -0.3        | ... | -0.3        |
| In3            | 0.4        | -0.4        | ... | -0.4        |
| In4            | 0.5        | -0.5        | ... | -0.5        |
| In5            | 0.6        | -0.6        | ... | -0.6        |
| In6            | 0.7        | -0.7        | ... | -0.7        |
| In7            | 0.8        | -0.8        | ... | -0.8        |
| Select         | 0          | 0           | ... | 0.055       |
| <i>Outputs</i> |            |             |     |             |
| Out            | 0.1        | -0.1        | ... | -0.8        |
| Exp. Out       | 0.1        | -0.1        | ... | -0.8        |
| Out (DSP)      | 214748365  | -214748365  | ... | -1717986918 |
| Exp. Out (DSP) | 214748365  | -214748365  | ... | -1717986918 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 62 |
| Avg CPU cycles  | 62 |

**Verification: Selector FiP32 CPU STM32F072RB**

Date of Test 2026-06-19  
Target controller STM32F072RB

**Test case: Inport test****OK**

Inport test for General block Selector.

| Test results   |            |             |     |             |
|----------------|------------|-------------|-----|-------------|
| Time step      | 1          | 2           | ... | 16          |
| CPU cycles     | 54         | 54          | ... | 54          |
| Inputs         |            |             |     |             |
| In0 (DSP)      | 214748365  | -214748365  | ... | -214748365  |
| In1 (DSP)      | 429496730  | -429496730  | ... | -429496730  |
| In2 (DSP)      | 644245094  | -644245094  | ... | -644245094  |
| In3 (DSP)      | 858993459  | -858993459  | ... | -858993459  |
| In4 (DSP)      | 1073741824 | -1073741824 | ... | -1073741824 |
| In5 (DSP)      | 1288490189 | -1288490189 | ... | -1288490189 |
| In6 (DSP)      | 1503238554 | -1503238554 | ... | -1503238554 |
| In7 (DSP)      | 1717986918 | -1717986918 | ... | -1717986918 |
| Select (DSP)   | 0          | 0           | ... | 7           |
| In0            | 0.1        | -0.1        | ... | -0.1        |
| In1            | 0.2        | -0.2        | ... | -0.2        |
| In2            | 0.3        | -0.3        | ... | -0.3        |
| In3            | 0.4        | -0.4        | ... | -0.4        |
| In4            | 0.5        | -0.5        | ... | -0.5        |
| In5            | 0.6        | -0.6        | ... | -0.6        |
| In6            | 0.7        | -0.7        | ... | -0.7        |
| In7            | 0.8        | -0.8        | ... | -0.8        |
| Select         | 0          | 0           | ... | 0.055       |
| Outputs        |            |             |     |             |
| Out            | 0.1        | -0.1        | ... | -0.8        |
| Exp. Out       | 0.1        | -0.1        | ... | -0.8        |
| Out (DSP)      | 214748365  | -214748365  | ... | -1717986918 |
| Exp. Out (DSP) | 214748365  | -214748365  | ... | -1717986918 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 54 |
| Max CPU cycles  | 54 |
| Avg CPU cycles  | 54 |

**Verification: Selector FiP32 CPU PIC32MX170F256**

Date of Test 2026-06-19  
Target controller PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block Selector.

| Test results   |            |             |     |             |
|----------------|------------|-------------|-----|-------------|
| Time step      | 1          | 2           | ... | 16          |
| CPU cycles     | 36         | 36          | ... | 36          |
| Inputs         |            |             |     |             |
| In0 (DSP)      | 214748365  | -214748365  | ... | -214748365  |
| In1 (DSP)      | 429496730  | -429496730  | ... | -429496730  |
| In2 (DSP)      | 644245094  | -644245094  | ... | -644245094  |
| In3 (DSP)      | 858993459  | -858993459  | ... | -858993459  |
| In4 (DSP)      | 1073741824 | -1073741824 | ... | -1073741824 |
| In5 (DSP)      | 1288490189 | -1288490189 | ... | -1288490189 |
| In6 (DSP)      | 1503238554 | -1503238554 | ... | -1503238554 |
| In7 (DSP)      | 1717986918 | -1717986918 | ... | -1717986918 |
| Select (DSP)   | 0          | 0           | ... | 7           |
| In0            | 0.1        | -0.1        | ... | -0.1        |
| In1            | 0.2        | -0.2        | ... | -0.2        |
| In2            | 0.3        | -0.3        | ... | -0.3        |
| In3            | 0.4        | -0.4        | ... | -0.4        |
| In4            | 0.5        | -0.5        | ... | -0.5        |
| In5            | 0.6        | -0.6        | ... | -0.6        |
| In6            | 0.7        | -0.7        | ... | -0.7        |
| In7            | 0.8        | -0.8        | ... | -0.8        |
| Select         | 0          | 0           | ... | 0.055       |
| Outputs        |            |             |     |             |
| Out            | 0.1        | -0.1        | ... | -0.8        |
| Exp. Out       | 0.1        | -0.1        | ... | -0.8        |
| Out (DSP)      | 214748365  | -214748365  | ... | -1717986918 |
| Exp. Out (DSP) | 214748365  | -214748365  | ... | -1717986918 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 36 |
| Max CPU cycles  | 36 |
| Avg CPU cycles  | 36 |

**Verification: Selector FiP32 CPU dsPIC33EP256MC502**

Date of Test 2026-06-19  
Target controller dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block Selector.

| Test results   |            |             |     |             |
|----------------|------------|-------------|-----|-------------|
| Time step      | 1          | 2           | ... | 16          |
| CPU cycles     | 50         | 50          | ... | 50          |
| Inputs         |            |             |     |             |
| In0 (DSP)      | 214748365  | -214748365  | ... | -214748365  |
| In1 (DSP)      | 429496730  | -429496730  | ... | -429496730  |
| In2 (DSP)      | 644245094  | -644245094  | ... | -644245094  |
| In3 (DSP)      | 858993459  | -858993459  | ... | -858993459  |
| In4 (DSP)      | 1073741824 | -1073741824 | ... | -1073741824 |
| In5 (DSP)      | 1288490189 | -1288490189 | ... | -1288490189 |
| In6 (DSP)      | 1503238554 | -1503238554 | ... | -1503238554 |
| In7 (DSP)      | 1717986918 | -1717986918 | ... | -1717986918 |
| Select (DSP)   | 0          | 0           | ... | 7           |
| In0            | 0.1        | -0.1        | ... | -0.1        |
| In1            | 0.2        | -0.2        | ... | -0.2        |
| In2            | 0.3        | -0.3        | ... | -0.3        |
| In3            | 0.4        | -0.4        | ... | -0.4        |
| In4            | 0.5        | -0.5        | ... | -0.5        |
| In5            | 0.6        | -0.6        | ... | -0.6        |
| In6            | 0.7        | -0.7        | ... | -0.7        |
| In7            | 0.8        | -0.8        | ... | -0.8        |
| Select         | 0          | 0           | ... | 0.055       |
| Outputs        |            |             |     |             |
| Out            | 0.1        | -0.1        | ... | -0.8        |
| Exp. Out       | 0.1        | -0.1        | ... | -0.8        |
| Out (DSP)      | 214748365  | -214748365  | ... | -1717986918 |
| Exp. Out (DSP) | 214748365  | -214748365  | ... | -1717986918 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 50 |
| Max CPU cycles  | 50 |
| Avg CPU cycles  | 50 |



**Verification: Selector FiP32 CPU XMC4800-F144K2048**

Date of Test 2026-06-19  
Target controller XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block Selector.

| Test results   |            |             |     |             |
|----------------|------------|-------------|-----|-------------|
| Time step      | 1          | 2           | ... | 16          |
| CPU cycles     | 70         | 62          | ... | 62          |
| Inputs         |            |             |     |             |
| In0 (DSP)      | 214748365  | -214748365  | ... | -214748365  |
| In1 (DSP)      | 429496730  | -429496730  | ... | -429496730  |
| In2 (DSP)      | 644245094  | -644245094  | ... | -644245094  |
| In3 (DSP)      | 858993459  | -858993459  | ... | -858993459  |
| In4 (DSP)      | 1073741824 | -1073741824 | ... | -1073741824 |
| In5 (DSP)      | 1288490189 | -1288490189 | ... | -1288490189 |
| In6 (DSP)      | 1503238554 | -1503238554 | ... | -1503238554 |
| In7 (DSP)      | 1717986918 | -1717986918 | ... | -1717986918 |
| Select (DSP)   | 0          | 0           | ... | 7           |
| In0            | 0.1        | -0.1        | ... | -0.1        |
| In1            | 0.2        | -0.2        | ... | -0.2        |
| In2            | 0.3        | -0.3        | ... | -0.3        |
| In3            | 0.4        | -0.4        | ... | -0.4        |
| In4            | 0.5        | -0.5        | ... | -0.5        |
| In5            | 0.6        | -0.6        | ... | -0.6        |
| In6            | 0.7        | -0.7        | ... | -0.7        |
| In7            | 0.8        | -0.8        | ... | -0.8        |
| Select         | 0          | 0           | ... | 0.055       |
| Outputs        |            |             |     |             |
| Out            | 0.1        | -0.1        | ... | -0.8        |
| Exp. Out       | 0.1        | -0.1        | ... | -0.8        |
| Out (DSP)      | 214748365  | -214748365  | ... | -1717986918 |
| Exp. Out (DSP) | 214748365  | -214748365  | ... | -1717986918 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 70 |
| Avg CPU cycles  | 62 |

**Verification: Selector FiP32 CPU TMS320F28379D**

Date of Test 2026-06-22  
Target controller TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block Selector.

| Test results   |            |             |     |             |
|----------------|------------|-------------|-----|-------------|
| Time step      | 1          | 2           | ... | 16          |
| CPU cycles     | 49         | 49          | ... | 49          |
| <i>Inputs</i>  |            |             |     |             |
| In0 (DSP)      | 214748365  | -214748365  | ... | -214748365  |
| In1 (DSP)      | 429496730  | -429496730  | ... | -429496730  |
| In2 (DSP)      | 644245094  | -644245094  | ... | -644245094  |
| In3 (DSP)      | 858993459  | -858993459  | ... | -858993459  |
| In4 (DSP)      | 1073741824 | -1073741824 | ... | -1073741824 |
| In5 (DSP)      | 1288490189 | -1288490189 | ... | -1288490189 |
| In6 (DSP)      | 1503238554 | -1503238554 | ... | -1503238554 |
| In7 (DSP)      | 1717986918 | -1717986918 | ... | -1717986918 |
| Select (DSP)   | 0          | 0           | ... | 7           |
| In0            | 0.1        | -0.1        | ... | -0.1        |
| In1            | 0.2        | -0.2        | ... | -0.2        |
| In2            | 0.3        | -0.3        | ... | -0.3        |
| In3            | 0.4        | -0.4        | ... | -0.4        |
| In4            | 0.5        | -0.5        | ... | -0.5        |
| In5            | 0.6        | -0.6        | ... | -0.6        |
| In6            | 0.7        | -0.7        | ... | -0.7        |
| In7            | 0.8        | -0.8        | ... | -0.8        |
| Select         | 0          | 0           | ... | 0.055       |
| <i>Outputs</i> |            |             |     |             |
| Out            | 0.1        | -0.1        | ... | -0.8        |
| Exp. Out       | 0.1        | -0.1        | ... | -0.8        |
| Out (DSP)      | 214748365  | -214748365  | ... | -1717986918 |
| Exp. Out (DSP) | 214748365  | -214748365  | ... | -1717986918 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 49 |
| Max CPU cycles  | 49 |
| Avg CPU cycles  | 49 |

**Verification: Selector Float32 CPU TMS320F28335**

Date of Test 2026-06-19  
Target controller TMS320F28335

**Test case: Inport test****OK**

Inport test for General block Selector.

| Test results   |     |      |     |       |
|----------------|-----|------|-----|-------|
| Time step      | 1   | 2    | ... | 16    |
| CPU cycles     | 68  | 68   | ... | 68    |
| <i>Inputs</i>  |     |      |     |       |
| In0 (DSP)      | 0.1 | -0.1 | ... | -0.1  |
| In1 (DSP)      | 0.2 | -0.2 | ... | -0.2  |
| In2 (DSP)      | 0.3 | -0.3 | ... | -0.3  |
| In3 (DSP)      | 0.4 | -0.4 | ... | -0.4  |
| In4 (DSP)      | 0.5 | -0.5 | ... | -0.5  |
| In5 (DSP)      | 0.6 | -0.6 | ... | -0.6  |
| In6 (DSP)      | 0.7 | -0.7 | ... | -0.7  |
| In7 (DSP)      | 0.8 | -0.8 | ... | -0.8  |
| Select (DSP)   | 0   | 0    | ... | 7     |
| In0            | 0.1 | -0.1 | ... | -0.1  |
| In1            | 0.2 | -0.2 | ... | -0.2  |
| In2            | 0.3 | -0.3 | ... | -0.3  |
| In3            | 0.4 | -0.4 | ... | -0.4  |
| In4            | 0.5 | -0.5 | ... | -0.5  |
| In5            | 0.6 | -0.6 | ... | -0.6  |
| In6            | 0.7 | -0.7 | ... | -0.7  |
| In7            | 0.8 | -0.8 | ... | -0.8  |
| Select         | 0   | 0    | ... | 0.055 |
| <i>Outputs</i> |     |      |     |       |
| Out            | 0.1 | -0.1 | ... | -0.8  |
| Exp. Out       | 0.1 | -0.1 | ... | -0.8  |
| Out (DSP)      | 0.1 | -0.1 | ... | -0.8  |
| Exp. Out (DSP) | 0.1 | -0.1 | ... | -0.8  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 68 |
| Max CPU cycles  | 68 |
| Avg CPU cycles  | 68 |

**Verification: Selector Float32 CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block Selector.

| Test results   |     |      |     |       |
|----------------|-----|------|-----|-------|
| Time step      | 1   | 2    | ... | 16    |
| CPU cycles     | 29  | 29   | ... | 29    |
| Inputs         |     |      |     |       |
| In0 (DSP)      | 0.1 | -0.1 | ... | -0.1  |
| In1 (DSP)      | 0.2 | -0.2 | ... | -0.2  |
| In2 (DSP)      | 0.3 | -0.3 | ... | -0.3  |
| In3 (DSP)      | 0.4 | -0.4 | ... | -0.4  |
| In4 (DSP)      | 0.5 | -0.5 | ... | -0.5  |
| In5 (DSP)      | 0.6 | -0.6 | ... | -0.6  |
| In6 (DSP)      | 0.7 | -0.7 | ... | -0.7  |
| In7 (DSP)      | 0.8 | -0.8 | ... | -0.8  |
| Select (DSP)   | 0   | 0    | ... | 7     |
| In0            | 0.1 | -0.1 | ... | -0.1  |
| In1            | 0.2 | -0.2 | ... | -0.2  |
| In2            | 0.3 | -0.3 | ... | -0.3  |
| In3            | 0.4 | -0.4 | ... | -0.4  |
| In4            | 0.5 | -0.5 | ... | -0.5  |
| In5            | 0.6 | -0.6 | ... | -0.6  |
| In6            | 0.7 | -0.7 | ... | -0.7  |
| In7            | 0.8 | -0.8 | ... | -0.8  |
| Select         | 0   | 0    | ... | 0.055 |
| Outputs        |     |      |     |       |
| Out            | 0.1 | -0.1 | ... | -0.8  |
| Exp. Out       | 0.1 | -0.1 | ... | -0.8  |
| Out (DSP)      | 0.1 | -0.1 | ... | -0.8  |
| Exp. Out (DSP) | 0.1 | -0.1 | ... | -0.8  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 29 |
| Avg CPU cycles  | 29 |



**Verification: Selector Float32 CPU STM32G474RE**

Date of Test 2026-06-19  
Target controller STM32G474RE

**Test case: Inport test****OK**

Inport test for General block Selector.

| Test results   |     |      |     |       |
|----------------|-----|------|-----|-------|
| Time step      | 1   | 2    | ... | 16    |
| CPU cycles     | 62  | 62   | ... | 62    |
| Inputs         |     |      |     |       |
| In0 (DSP)      | 0.1 | -0.1 | ... | -0.1  |
| In1 (DSP)      | 0.2 | -0.2 | ... | -0.2  |
| In2 (DSP)      | 0.3 | -0.3 | ... | -0.3  |
| In3 (DSP)      | 0.4 | -0.4 | ... | -0.4  |
| In4 (DSP)      | 0.5 | -0.5 | ... | -0.5  |
| In5 (DSP)      | 0.6 | -0.6 | ... | -0.6  |
| In6 (DSP)      | 0.7 | -0.7 | ... | -0.7  |
| In7 (DSP)      | 0.8 | -0.8 | ... | -0.8  |
| Select (DSP)   | 0   | 0    | ... | 7     |
| In0            | 0.1 | -0.1 | ... | -0.1  |
| In1            | 0.2 | -0.2 | ... | -0.2  |
| In2            | 0.3 | -0.3 | ... | -0.3  |
| In3            | 0.4 | -0.4 | ... | -0.4  |
| In4            | 0.5 | -0.5 | ... | -0.5  |
| In5            | 0.6 | -0.6 | ... | -0.6  |
| In6            | 0.7 | -0.7 | ... | -0.7  |
| In7            | 0.8 | -0.8 | ... | -0.8  |
| Select         | 0   | 0    | ... | 0.055 |
| Outputs        |     |      |     |       |
| Out            | 0.1 | -0.1 | ... | -0.8  |
| Exp. Out       | 0.1 | -0.1 | ... | -0.8  |
| Out (DSP)      | 0.1 | -0.1 | ... | -0.8  |
| Exp. Out (DSP) | 0.1 | -0.1 | ... | -0.8  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 62 |
| Avg CPU cycles  | 62 |

**Verification: Selector Float32 CPU STM32F072RB**

Date of Test 2026-06-19  
Target controller STM32F072RB

**Test case: Inport test****OK**

Inport test for General block Selector.

| Test results   |     |      |     |       |
|----------------|-----|------|-----|-------|
| Time step      | 1   | 2    | ... | 16    |
| CPU cycles     | 54  | 54   | ... | 54    |
| <i>Inputs</i>  |     |      |     |       |
| In0 (DSP)      | 0.1 | -0.1 | ... | -0.1  |
| In1 (DSP)      | 0.2 | -0.2 | ... | -0.2  |
| In2 (DSP)      | 0.3 | -0.3 | ... | -0.3  |
| In3 (DSP)      | 0.4 | -0.4 | ... | -0.4  |
| In4 (DSP)      | 0.5 | -0.5 | ... | -0.5  |
| In5 (DSP)      | 0.6 | -0.6 | ... | -0.6  |
| In6 (DSP)      | 0.7 | -0.7 | ... | -0.7  |
| In7 (DSP)      | 0.8 | -0.8 | ... | -0.8  |
| Select (DSP)   | 0   | 0    | ... | 7     |
| In0            | 0.1 | -0.1 | ... | -0.1  |
| In1            | 0.2 | -0.2 | ... | -0.2  |
| In2            | 0.3 | -0.3 | ... | -0.3  |
| In3            | 0.4 | -0.4 | ... | -0.4  |
| In4            | 0.5 | -0.5 | ... | -0.5  |
| In5            | 0.6 | -0.6 | ... | -0.6  |
| In6            | 0.7 | -0.7 | ... | -0.7  |
| In7            | 0.8 | -0.8 | ... | -0.8  |
| Select         | 0   | 0    | ... | 0.055 |
| <i>Outputs</i> |     |      |     |       |
| Out            | 0.1 | -0.1 | ... | -0.8  |
| Exp. Out       | 0.1 | -0.1 | ... | -0.8  |
| Out (DSP)      | 0.1 | -0.1 | ... | -0.8  |
| Exp. Out (DSP) | 0.1 | -0.1 | ... | -0.8  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 54 |
| Max CPU cycles  | 54 |
| Avg CPU cycles  | 54 |

**Verification: Selector Float32 CPU PIC32MX170F256**

Date of Test 2026-06-19  
Target controller PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block Selector.

| Test results   |     |      |     |       |
|----------------|-----|------|-----|-------|
| Time step      | 1   | 2    | ... | 16    |
| CPU cycles     | 36  | 36   | ... | 36    |
| Inputs         |     |      |     |       |
| In0 (DSP)      | 0.1 | -0.1 | ... | -0.1  |
| In1 (DSP)      | 0.2 | -0.2 | ... | -0.2  |
| In2 (DSP)      | 0.3 | -0.3 | ... | -0.3  |
| In3 (DSP)      | 0.4 | -0.4 | ... | -0.4  |
| In4 (DSP)      | 0.5 | -0.5 | ... | -0.5  |
| In5 (DSP)      | 0.6 | -0.6 | ... | -0.6  |
| In6 (DSP)      | 0.7 | -0.7 | ... | -0.7  |
| In7 (DSP)      | 0.8 | -0.8 | ... | -0.8  |
| Select (DSP)   | 0   | 0    | ... | 7     |
| In0            | 0.1 | -0.1 | ... | -0.1  |
| In1            | 0.2 | -0.2 | ... | -0.2  |
| In2            | 0.3 | -0.3 | ... | -0.3  |
| In3            | 0.4 | -0.4 | ... | -0.4  |
| In4            | 0.5 | -0.5 | ... | -0.5  |
| In5            | 0.6 | -0.6 | ... | -0.6  |
| In6            | 0.7 | -0.7 | ... | -0.7  |
| In7            | 0.8 | -0.8 | ... | -0.8  |
| Select         | 0   | 0    | ... | 0.055 |
| Outputs        |     |      |     |       |
| Out            | 0.1 | -0.1 | ... | -0.8  |
| Exp. Out       | 0.1 | -0.1 | ... | -0.8  |
| Out (DSP)      | 0.1 | -0.1 | ... | -0.8  |
| Exp. Out (DSP) | 0.1 | -0.1 | ... | -0.8  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 36 |
| Max CPU cycles  | 36 |
| Avg CPU cycles  | 36 |

**Verification: Selector Float32 CPU dsPIC33EP256MC502**

Date of Test 2026-06-19  
Target controller dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block Selector.

| Test results   |     |      |     |       |
|----------------|-----|------|-----|-------|
| Time step      | 1   | 2    | ... | 16    |
| CPU cycles     | 50  | 50   | ... | 50    |
| <i>Inputs</i>  |     |      |     |       |
| In0 (DSP)      | 0.1 | -0.1 | ... | -0.1  |
| In1 (DSP)      | 0.2 | -0.2 | ... | -0.2  |
| In2 (DSP)      | 0.3 | -0.3 | ... | -0.3  |
| In3 (DSP)      | 0.4 | -0.4 | ... | -0.4  |
| In4 (DSP)      | 0.5 | -0.5 | ... | -0.5  |
| In5 (DSP)      | 0.6 | -0.6 | ... | -0.6  |
| In6 (DSP)      | 0.7 | -0.7 | ... | -0.7  |
| In7 (DSP)      | 0.8 | -0.8 | ... | -0.8  |
| Select (DSP)   | 0   | 0    | ... | 7     |
| In0            | 0.1 | -0.1 | ... | -0.1  |
| In1            | 0.2 | -0.2 | ... | -0.2  |
| In2            | 0.3 | -0.3 | ... | -0.3  |
| In3            | 0.4 | -0.4 | ... | -0.4  |
| In4            | 0.5 | -0.5 | ... | -0.5  |
| In5            | 0.6 | -0.6 | ... | -0.6  |
| In6            | 0.7 | -0.7 | ... | -0.7  |
| In7            | 0.8 | -0.8 | ... | -0.8  |
| Select         | 0   | 0    | ... | 0.055 |
| <i>Outputs</i> |     |      |     |       |
| Out            | 0.1 | -0.1 | ... | -0.8  |
| Exp. Out       | 0.1 | -0.1 | ... | -0.8  |
| Out (DSP)      | 0.1 | -0.1 | ... | -0.8  |
| Exp. Out (DSP) | 0.1 | -0.1 | ... | -0.8  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 50 |
| Max CPU cycles  | 50 |
| Avg CPU cycles  | 50 |



**Verification: Selector Float32 CPU XMC4800-F144K2048**

Date of Test 2026-06-19  
Target controller XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block Selector.

| Test results   |     |      |     |       |
|----------------|-----|------|-----|-------|
| Time step      | 1   | 2    | ... | 16    |
| CPU cycles     | 62  | 62   | ... | 62    |
| Inputs         |     |      |     |       |
| In0 (DSP)      | 0.1 | -0.1 | ... | -0.1  |
| In1 (DSP)      | 0.2 | -0.2 | ... | -0.2  |
| In2 (DSP)      | 0.3 | -0.3 | ... | -0.3  |
| In3 (DSP)      | 0.4 | -0.4 | ... | -0.4  |
| In4 (DSP)      | 0.5 | -0.5 | ... | -0.5  |
| In5 (DSP)      | 0.6 | -0.6 | ... | -0.6  |
| In6 (DSP)      | 0.7 | -0.7 | ... | -0.7  |
| In7 (DSP)      | 0.8 | -0.8 | ... | -0.8  |
| Select (DSP)   | 0   | 0    | ... | 7     |
| In0            | 0.1 | -0.1 | ... | -0.1  |
| In1            | 0.2 | -0.2 | ... | -0.2  |
| In2            | 0.3 | -0.3 | ... | -0.3  |
| In3            | 0.4 | -0.4 | ... | -0.4  |
| In4            | 0.5 | -0.5 | ... | -0.5  |
| In5            | 0.6 | -0.6 | ... | -0.6  |
| In6            | 0.7 | -0.7 | ... | -0.7  |
| In7            | 0.8 | -0.8 | ... | -0.8  |
| Select         | 0   | 0    | ... | 0.055 |
| Outputs        |     |      |     |       |
| Out            | 0.1 | -0.1 | ... | -0.8  |
| Exp. Out       | 0.1 | -0.1 | ... | -0.8  |
| Out (DSP)      | 0.1 | -0.1 | ... | -0.8  |
| Exp. Out (DSP) | 0.1 | -0.1 | ... | -0.8  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 62 |
| Avg CPU cycles  | 62 |

**Verification: Selector Float32 CPU TMS320F28379D**

Date of Test 2026-06-22  
Target controller TMS320F28379D

**Test case: Inport test****OK**


Inport test for General block Selector.

| Test results   |     |      |     |       |
|----------------|-----|------|-----|-------|
| Time step      | 1   | 2    | ... | 16    |
| CPU cycles     | 48  | 48   | ... | 48    |
| <i>Inputs</i>  |     |      |     |       |
| In0 (DSP)      | 0.1 | -0.1 | ... | -0.1  |
| In1 (DSP)      | 0.2 | -0.2 | ... | -0.2  |
| In2 (DSP)      | 0.3 | -0.3 | ... | -0.3  |
| In3 (DSP)      | 0.4 | -0.4 | ... | -0.4  |
| In4 (DSP)      | 0.5 | -0.5 | ... | -0.5  |
| In5 (DSP)      | 0.6 | -0.6 | ... | -0.6  |
| In6 (DSP)      | 0.7 | -0.7 | ... | -0.7  |
| In7 (DSP)      | 0.8 | -0.8 | ... | -0.8  |
| Select (DSP)   | 0   | 0    | ... | 7     |
| In0            | 0.1 | -0.1 | ... | -0.1  |
| In1            | 0.2 | -0.2 | ... | -0.2  |
| In2            | 0.3 | -0.3 | ... | -0.3  |
| In3            | 0.4 | -0.4 | ... | -0.4  |
| In4            | 0.5 | -0.5 | ... | -0.5  |
| In5            | 0.6 | -0.6 | ... | -0.6  |
| In6            | 0.7 | -0.7 | ... | -0.7  |
| In7            | 0.8 | -0.8 | ... | -0.8  |
| Select         | 0   | 0    | ... | 0.055 |
| <i>Outputs</i> |     |      |     |       |
| Out            | 0.1 | -0.1 | ... | -0.8  |
| Exp. Out       | 0.1 | -0.1 | ... | -0.8  |
| Out (DSP)      | 0.1 | -0.1 | ... | -0.8  |
| Exp. Out (DSP) | 0.1 | -0.1 | ... | -0.8  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,2596e-08$ ( $\pm 70$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 48 |
| Max CPU cycles  | 48 |
| Avg CPU cycles  | 48 |

## Block: Sequencer



Generation of time delayed (enable) sequence.

| Inports |                                              |
|---------|----------------------------------------------|
| Start   | Start signal. Rising flank triggers sequence |

| Outports |           |
|----------|-----------|
| Out1     | Output #1 |
| Out2     | Output #2 |
| Out3     | Output #3 |
| Out4     | Output #4 |

| Mask Parameters |    |                                                                 |
|-----------------|----|-----------------------------------------------------------------|
| Name            | ID | Description                                                     |
| Delay1          | 1  | Time delay for output 1                                         |
| Delay2          | 2  | Time delay for output 2                                         |
| Delay3          | 3  | Time delay for output 3                                         |
| Delay4          | 4  | Time delay for output 4                                         |
| ts_fact         | 5  | Multiplication factor of base sampling time (in integer format) |

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>Bool</b>    | Boolean Implementation               |
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: Bool

Boolean Implementation

| Inports Data Type |      |
|-------------------|------|
| Start             | bool |

| Outports Data Type |      |
|--------------------|------|
| Out1               | bool |
| Out2               | bool |
| Out3               | bool |
| Out4               | bool |

### Implementation: FiP8

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| Start             | int8 |

| Outports Data Type |      |
|--------------------|------|
| Out1               | int8 |
| Out2               | int8 |
| Out3               | int8 |
| Out4               | int8 |

### Implementation: FiP16

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| Start             | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out1               | int16 |
| Out2               | int16 |
| Out3               | int16 |
| Out4               | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| Start             | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out1               | int32 |
| Out2               | int32 |
| Out3               | int32 |
| Out4               | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| Start             | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out1               | float32 |
| Out2               | float32 |
| Out3               | float32 |
| Out4               | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| Start             | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out1               | float64 |
| Out2               | float64 |
| Out3               | float64 |
| Out4               | float64 |

**Verification: Sequencer Bool CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block Sequencer.

| Test results    |       |     |     |     |     |    |
|-----------------|-------|-----|-----|-----|-----|----|
| Time step       | 1     | 2   | 3   | 4   | ... | 16 |
| CPU cycles      | 72    | 115 | 113 | 111 | ... | 72 |
| Inputs          |       |     |     |     |     |    |
| Start (DSP)     | 0     | 1   | 1   | 1   | ... | 0  |
| Start           | 0     | 1   | 1   | 1   | ... | 0  |
| Parameters      |       |     |     |     |     |    |
| Delay1          | 0     |     |     |     |     |    |
| Delay2          | 0     |     |     |     |     |    |
| Delay3          | 0.001 |     |     |     |     |    |
| Delay4          | 0     |     |     |     |     |    |
| ts_fact         | 1     |     |     |     |     |    |
| Outputs         |       |     |     |     |     |    |
| Out1            | 0     | 0   | 1   | 1   | ... | 0  |
| Out2            | 0     | 0   | 0   | 1   | ... | 0  |
| Out3            | 0     | 0   | 0   | 0   | ... | 0  |
| Out4            | 0     | 1   | 1   | 1   | ... | 0  |
| Exp. Out1       | 0     | 0   | 1   | 1   | ... | 0  |
| Exp. Out2       | 0     | 0   | 0   | 1   | ... | 0  |
| Exp. Out3       | 0     | 0   | 0   | 0   | ... | 0  |
| Exp. Out4       | 0     | 1   | 1   | 1   | ... | 0  |
| Out1 (DSP)      | 0     | 0   | 1   | 1   | ... | 0  |
| Out2 (DSP)      | 0     | 0   | 0   | 1   | ... | 0  |
| Out3 (DSP)      | 0     | 0   | 0   | 0   | ... | 0  |
| Out4 (DSP)      | 0     | 1   | 1   | 1   | ... | 0  |
| Exp. Out1 (DSP) | 0     | 0   | 1   | 1   | ... | 0  |
| Exp. Out2 (DSP) | 0     | 0   | 0   | 1   | ... | 0  |
| Exp. Out3 (DSP) | 0     | 0   | 0   | 0   | ... | 0  |
| Exp. Out4 (DSP) | 0     | 1   | 1   | 1   | ... | 0  |



| Test settings  |                                 |
|----------------|---------------------------------|
| Tolerance Out1 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |
| Tolerance Out2 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |
| Tolerance Out3 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |
| Tolerance Out4 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 72  |
| Max CPU cycles  | 115 |
| Avg CPU cycles  | 106 |

### Test case: Conversion test

OK

Conversion test for General block Sequencer.

| Test results                 |       |      |      |
|------------------------------|-------|------|------|
| Time step                    | 1     | 2    | 3    |
| <i>Mask parameters</i>       |       |      |      |
| <b>Delay1</b>                | 0.1   | 0.1  | 0.1  |
| <b>Delay2</b>                | 0.2   | 0.2  | 0.2  |
| <b>Delay3</b>                | 1     | 1    | 1    |
| <b>Delay4</b>                | 1.7   | 1.7  | 1.7  |
| <b>ts_fact</b>               | 1     | 2    | 10   |
| <i>Controller parameters</i> |       |      |      |
| <b>delay3</b>                | 10000 | 5000 | 1000 |
| <b>delay4</b>                | 17000 | 8500 | 1700 |
| <b>delay1</b>                | 1000  | 500  | 100  |
| <b>delay2</b>                | 2000  | 1000 | 200  |
| <b>Exp. delay3</b>           | 10000 | 5000 | 1000 |
| <b>Exp. delay4</b>           | 17000 | 8500 | 1700 |
| <b>Exp. delay1</b>           | 1000  | 500  | 100  |
| <b>Exp. delay2</b>           | 2000  | 1000 | 200  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance delay3 | $\pm 0,0000e+00$ |
| Tolerance delay4 | $\pm 0,0000e+00$ |
| Tolerance delay1 | $\pm 0,0000e+00$ |
| Tolerance delay2 | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block Sequencer.

| Test results          |       |      |      |
|-----------------------|-------|------|------|
| Time step             | 1     | 2    | 3    |
| Mask parameters       |       |      |      |
| Delay1                | 0.1   | 0.1  | 0.1  |
| Delay2                | 0.2   | 0.2  | 0.2  |
| Delay3                | 1     | 1    | 1    |
| Delay4                | 1.7   | 1.7  | 1.7  |
| ts_fact               | 1     | 2    | 10   |
| Controller parameters |       |      |      |
| delay3                | 10000 | 5000 | 1000 |
| delay4                | 17000 | 8500 | 1700 |
| delay1                | 1000  | 500  | 100  |
| delay2                | 2000  | 1000 | 200  |
| Exp. delay3           | 10000 | 5000 | 1000 |
| Exp. delay4           | 17000 | 8500 | 1700 |
| Exp. delay1           | 1000  | 500  | 100  |
| Exp. delay2           | 2000  | 1000 | 200  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance delay3 | $\pm 0,0000e+00$ |
| Tolerance delay4 | $\pm 0,0000e+00$ |
| Tolerance delay1 | $\pm 0,0000e+00$ |
| Tolerance delay2 | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3591 |
| Max CPU cycles  | 3598 |
| Avg CPU cycles  | 3595 |

**Verification: Sequencer Bool CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block Sequencer.

| Test results    |       |    |    |    |     |    |
|-----------------|-------|----|----|----|-----|----|
| Time step       | 1     | 2  | 3  | 4  | ... | 16 |
| CPU cycles      | 53    | 77 | 77 | 77 | ... | 53 |
| Inputs          |       |    |    |    |     |    |
| Start (DSP)     | 0     | 1  | 1  | 1  | ... | 0  |
| Start           | 0     | 1  | 1  | 1  | ... | 0  |
| Parameters      |       |    |    |    |     |    |
| Delay1          | 0     |    |    |    |     |    |
| Delay2          | 0     |    |    |    |     |    |
| Delay3          | 0.001 |    |    |    |     |    |
| Delay4          | 0     |    |    |    |     |    |
| ts_fact         | 1     |    |    |    |     |    |
| Outputs         |       |    |    |    |     |    |
| Out1            | 0     | 0  | 1  | 1  | ... | 0  |
| Out2            | 0     | 0  | 0  | 1  | ... | 0  |
| Out3            | 0     | 0  | 0  | 0  | ... | 0  |
| Out4            | 0     | 1  | 1  | 1  | ... | 0  |
| Exp. Out1       | 0     | 0  | 1  | 1  | ... | 0  |
| Exp. Out2       | 0     | 0  | 0  | 1  | ... | 0  |
| Exp. Out3       | 0     | 0  | 0  | 0  | ... | 0  |
| Exp. Out4       | 0     | 1  | 1  | 1  | ... | 0  |
| Out1 (DSP)      | 0     | 0  | 1  | 1  | ... | 0  |
| Out2 (DSP)      | 0     | 0  | 0  | 1  | ... | 0  |
| Out3 (DSP)      | 0     | 0  | 0  | 0  | ... | 0  |
| Out4 (DSP)      | 0     | 1  | 1  | 1  | ... | 0  |
| Exp. Out1 (DSP) | 0     | 0  | 1  | 1  | ... | 0  |
| Exp. Out2 (DSP) | 0     | 0  | 0  | 1  | ... | 0  |
| Exp. Out3 (DSP) | 0     | 0  | 0  | 0  | ... | 0  |
| Exp. Out4 (DSP) | 0     | 1  | 1  | 1  | ... | 0  |

| Test settings  |                                 |
|----------------|---------------------------------|
| Tolerance Out1 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |
| Tolerance Out2 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |
| Tolerance Out3 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |
| Tolerance Out4 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 53 |
| Max CPU cycles  | 77 |
| Avg CPU cycles  | 74 |

### Test case: Conversion test

OK

Conversion test for General block Sequencer.

| Test results                 |       |      |      |
|------------------------------|-------|------|------|
| Time step                    | 1     | 2    | 3    |
| <i>Mask parameters</i>       |       |      |      |
| <b>Delay1</b>                | 0.1   | 0.1  | 0.1  |
| <b>Delay2</b>                | 0.2   | 0.2  | 0.2  |
| <b>Delay3</b>                | 1     | 1    | 1    |
| <b>Delay4</b>                | 1.7   | 1.7  | 1.7  |
| <b>ts_fact</b>               | 1     | 2    | 10   |
| <i>Controller parameters</i> |       |      |      |
| <b>delay3</b>                | 10000 | 5000 | 1000 |
| <b>delay4</b>                | 17000 | 8500 | 1700 |
| <b>delay1</b>                | 1000  | 500  | 100  |
| <b>delay2</b>                | 2000  | 1000 | 200  |
| <b>Exp. delay3</b>           | 10000 | 5000 | 1000 |
| <b>Exp. delay4</b>           | 17000 | 8500 | 1700 |
| <b>Exp. delay1</b>           | 1000  | 500  | 100  |
| <b>Exp. delay2</b>           | 2000  | 1000 | 200  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance delay3 | $\pm 0,0000e+00$ |
| Tolerance delay4 | $\pm 0,0000e+00$ |
| Tolerance delay1 | $\pm 0,0000e+00$ |
| Tolerance delay2 | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block Sequencer.

| Test results          |       |      |      |
|-----------------------|-------|------|------|
| Time step             | 1     | 2    | 3    |
| Mask parameters       |       |      |      |
| Delay1                | 0.1   | 0.1  | 0.1  |
| Delay2                | 0.2   | 0.2  | 0.2  |
| Delay3                | 1     | 1    | 1    |
| Delay4                | 1.7   | 1.7  | 1.7  |
| ts_fact               | 1     | 2    | 10   |
| Controller parameters |       |      |      |
| delay3                | 10000 | 5000 | 1000 |
| delay4                | 17000 | 8500 | 1700 |
| delay1                | 1000  | 500  | 100  |
| delay2                | 2000  | 1000 | 200  |
| Exp. delay3           | 10000 | 5000 | 1000 |
| Exp. delay4           | 17000 | 8500 | 1700 |
| Exp. delay1           | 1000  | 500  | 100  |
| Exp. delay2           | 2000  | 1000 | 200  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance delay3 | $\pm 0,0000e+00$ |
| Tolerance delay4 | $\pm 0,0000e+00$ |
| Tolerance delay1 | $\pm 0,0000e+00$ |
| Tolerance delay2 | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1209 |
| Max CPU cycles  | 1209 |
| Avg CPU cycles  | 1209 |

**Verification: Sequencer Bool CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block Sequencer.

| Test results    |       |     |     |     |     |    |
|-----------------|-------|-----|-----|-----|-----|----|
| Time step       | 1     | 2   | 3   | 4   | ... | 16 |
| CPU cycles      | 86    | 106 | 145 | 145 | ... | 86 |
| Inputs          |       |     |     |     |     |    |
| Start (DSP)     | 0     | 1   | 1   | 1   | ... | 0  |
| Start           | 0     | 1   | 1   | 1   | ... | 0  |
| Parameters      |       |     |     |     |     |    |
| Delay1          | 0     |     |     |     |     |    |
| Delay2          | 0     |     |     |     |     |    |
| Delay3          | 0.001 |     |     |     |     |    |
| Delay4          | 0     |     |     |     |     |    |
| ts_fact         | 1     |     |     |     |     |    |
| Outputs         |       |     |     |     |     |    |
| Out1            | 0     | 0   | 1   | 1   | ... | 0  |
| Out2            | 0     | 0   | 0   | 1   | ... | 0  |
| Out3            | 0     | 0   | 0   | 0   | ... | 0  |
| Out4            | 0     | 1   | 1   | 1   | ... | 0  |
| Exp. Out1       | 0     | 0   | 1   | 1   | ... | 0  |
| Exp. Out2       | 0     | 0   | 0   | 1   | ... | 0  |
| Exp. Out3       | 0     | 0   | 0   | 0   | ... | 0  |
| Exp. Out4       | 0     | 1   | 1   | 1   | ... | 0  |
| Out1 (DSP)      | 0     | 0   | 1   | 1   | ... | 0  |
| Out2 (DSP)      | 0     | 0   | 0   | 1   | ... | 0  |
| Out3 (DSP)      | 0     | 0   | 0   | 0   | ... | 0  |
| Out4 (DSP)      | 0     | 1   | 1   | 1   | ... | 0  |
| Exp. Out1 (DSP) | 0     | 0   | 1   | 1   | ... | 0  |
| Exp. Out2 (DSP) | 0     | 0   | 0   | 1   | ... | 0  |
| Exp. Out3 (DSP) | 0     | 0   | 0   | 0   | ... | 0  |
| Exp. Out4 (DSP) | 0     | 1   | 1   | 1   | ... | 0  |

| Test settings  |                                 |
|----------------|---------------------------------|
| Tolerance Out1 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |
| Tolerance Out2 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |
| Tolerance Out3 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |
| Tolerance Out4 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 86  |
| Max CPU cycles  | 145 |
| Avg CPU cycles  | 135 |

### Test case: Conversion test

OK

Conversion test for General block Sequencer.

| Test results                 |       |      |      |
|------------------------------|-------|------|------|
| Time step                    | 1     | 2    | 3    |
| <i>Mask parameters</i>       |       |      |      |
| <b>Delay1</b>                | 0.1   | 0.1  | 0.1  |
| <b>Delay2</b>                | 0.2   | 0.2  | 0.2  |
| <b>Delay3</b>                | 1     | 1    | 1    |
| <b>Delay4</b>                | 1.7   | 1.7  | 1.7  |
| <b>ts_fact</b>               | 1     | 2    | 10   |
| <i>Controller parameters</i> |       |      |      |
| <b>delay3</b>                | 10000 | 5000 | 1000 |
| <b>delay4</b>                | 17000 | 8500 | 1700 |
| <b>delay1</b>                | 1000  | 500  | 100  |
| <b>delay2</b>                | 2000  | 1000 | 200  |
| <b>Exp. delay3</b>           | 10000 | 5000 | 1000 |
| <b>Exp. delay4</b>           | 17000 | 8500 | 1700 |
| <b>Exp. delay1</b>           | 1000  | 500  | 100  |
| <b>Exp. delay2</b>           | 2000  | 1000 | 200  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance delay3 | $\pm 0,0000e+00$ |
| Tolerance delay4 | $\pm 0,0000e+00$ |
| Tolerance delay1 | $\pm 0,0000e+00$ |
| Tolerance delay2 | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block Sequencer.

| Test results          |       |      |      |
|-----------------------|-------|------|------|
| Time step             | 1     | 2    | 3    |
| Mask parameters       |       |      |      |
| Delay1                | 0.1   | 0.1  | 0.1  |
| Delay2                | 0.2   | 0.2  | 0.2  |
| Delay3                | 1     | 1    | 1    |
| Delay4                | 1.7   | 1.7  | 1.7  |
| ts_fact               | 1     | 2    | 10   |
| Controller parameters |       |      |      |
| delay3                | 10000 | 5000 | 1000 |
| delay4                | 17000 | 8500 | 1700 |
| delay1                | 1000  | 500  | 100  |
| delay2                | 2000  | 1000 | 200  |
| Exp. delay3           | 10000 | 5000 | 1000 |
| Exp. delay4           | 17000 | 8500 | 1700 |
| Exp. delay1           | 1000  | 500  | 100  |
| Exp. delay2           | 2000  | 1000 | 200  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance delay3 | $\pm 0,0000e+00$ |
| Tolerance delay4 | $\pm 0,0000e+00$ |
| Tolerance delay1 | $\pm 0,0000e+00$ |
| Tolerance delay2 | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1272 |
| Max CPU cycles  | 1315 |
| Avg CPU cycles  | 1286 |



**Verification: Sequencer Bool CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block Sequencer.

| Test results    |       |     |     |     |     |    |
|-----------------|-------|-----|-----|-----|-----|----|
| Time step       | 1     | 2   | 3   | 4   | ... | 16 |
| CPU cycles      | 77    | 100 | 120 | 120 | ... | 77 |
| Inputs          |       |     |     |     |     |    |
| Start (DSP)     | 0     | 1   | 1   | 1   | ... | 0  |
| Start           | 0     | 1   | 1   | 1   | ... | 0  |
| Parameters      |       |     |     |     |     |    |
| Delay1          | 0     |     |     |     |     |    |
| Delay2          | 0     |     |     |     |     |    |
| Delay3          | 0.001 |     |     |     |     |    |
| Delay4          | 0     |     |     |     |     |    |
| ts_fact         | 1     |     |     |     |     |    |
| Outputs         |       |     |     |     |     |    |
| Out1            | 0     | 0   | 1   | 1   | ... | 0  |
| Out2            | 0     | 0   | 0   | 1   | ... | 0  |
| Out3            | 0     | 0   | 0   | 0   | ... | 0  |
| Out4            | 0     | 1   | 1   | 1   | ... | 0  |
| Exp. Out1       | 0     | 0   | 1   | 1   | ... | 0  |
| Exp. Out2       | 0     | 0   | 0   | 1   | ... | 0  |
| Exp. Out3       | 0     | 0   | 0   | 0   | ... | 0  |
| Exp. Out4       | 0     | 1   | 1   | 1   | ... | 0  |
| Out1 (DSP)      | 0     | 0   | 1   | 1   | ... | 0  |
| Out2 (DSP)      | 0     | 0   | 0   | 1   | ... | 0  |
| Out3 (DSP)      | 0     | 0   | 0   | 0   | ... | 0  |
| Out4 (DSP)      | 0     | 1   | 1   | 1   | ... | 0  |
| Exp. Out1 (DSP) | 0     | 0   | 1   | 1   | ... | 0  |
| Exp. Out2 (DSP) | 0     | 0   | 0   | 1   | ... | 0  |
| Exp. Out3 (DSP) | 0     | 0   | 0   | 0   | ... | 0  |
| Exp. Out4 (DSP) | 0     | 1   | 1   | 1   | ... | 0  |

| Test settings  |                                 |
|----------------|---------------------------------|
| Tolerance Out1 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |
| Tolerance Out2 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |
| Tolerance Out3 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |
| Tolerance Out4 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 77  |
| Max CPU cycles  | 120 |
| Avg CPU cycles  | 113 |

### Test case: Conversion test

OK

Conversion test for General block Sequencer.

| Test results                 |       |      |      |
|------------------------------|-------|------|------|
| Time step                    | 1     | 2    | 3    |
| <i>Mask parameters</i>       |       |      |      |
| Delay1                       | 0.1   | 0.1  | 0.1  |
| Delay2                       | 0.2   | 0.2  | 0.2  |
| Delay3                       | 1     | 1    | 1    |
| Delay4                       | 1.7   | 1.7  | 1.7  |
| ts_fact                      | 1     | 2    | 10   |
| <i>Controller parameters</i> |       |      |      |
| delay3                       | 10000 | 5000 | 1000 |
| delay4                       | 17000 | 8500 | 1700 |
| delay1                       | 1000  | 500  | 100  |
| delay2                       | 2000  | 1000 | 200  |
| Exp. delay3                  | 10000 | 5000 | 1000 |
| Exp. delay4                  | 17000 | 8500 | 1700 |
| Exp. delay1                  | 1000  | 500  | 100  |
| Exp. delay2                  | 2000  | 1000 | 200  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance delay3 | $\pm 0,0000e+00$ |
| Tolerance delay4 | $\pm 0,0000e+00$ |
| Tolerance delay1 | $\pm 0,0000e+00$ |
| Tolerance delay2 | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block Sequencer.

| Test results          |       |      |      |
|-----------------------|-------|------|------|
| Time step             | 1     | 2    | 3    |
| Mask parameters       |       |      |      |
| Delay1                | 0.1   | 0.1  | 0.1  |
| Delay2                | 0.2   | 0.2  | 0.2  |
| Delay3                | 1     | 1    | 1    |
| Delay4                | 1.7   | 1.7  | 1.7  |
| ts_fact               | 1     | 2    | 10   |
| Controller parameters |       |      |      |
| delay3                | 10000 | 5000 | 1000 |
| delay4                | 17000 | 8500 | 1700 |
| delay1                | 1000  | 500  | 100  |
| delay2                | 2000  | 1000 | 200  |
| Exp. delay3           | 10000 | 5000 | 1000 |
| Exp. delay4           | 17000 | 8500 | 1700 |
| Exp. delay1           | 1000  | 500  | 100  |
| Exp. delay2           | 2000  | 1000 | 200  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance delay3 | $\pm 0,0000e+00$ |
| Tolerance delay4 | $\pm 0,0000e+00$ |
| Tolerance delay1 | $\pm 0,0000e+00$ |
| Tolerance delay2 | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 5808 |
| Max CPU cycles  | 5817 |
| Avg CPU cycles  | 5814 |

**Verification: Sequencer Bool CPU PIC32MX170F256**

Date of Test 2026-06-19  
Target controller PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block Sequencer.

| Test results    |       |    |    |    |     |    |  |
|-----------------|-------|----|----|----|-----|----|--|
| Time step       | 1     | 2  | 3  | 4  | ... | 16 |  |
| CPU cycles      | 42    | 58 | 68 | 68 | ... | 42 |  |
| Inputs          |       |    |    |    |     |    |  |
| Start (DSP)     | 0     | 1  | 1  | 1  | ... | 0  |  |
| Start           | 0     | 1  | 1  | 1  | ... | 0  |  |
| Parameters      |       |    |    |    |     |    |  |
| Delay1          | 0     |    |    |    |     |    |  |
| Delay2          | 0     |    |    |    |     |    |  |
| Delay3          | 0.001 |    |    |    |     |    |  |
| Delay4          | 0     |    |    |    |     |    |  |
| ts_fact         | 1     |    |    |    |     |    |  |
| Outputs         |       |    |    |    |     |    |  |
| Out1            | 0     | 0  | 1  | 1  | ... | 0  |  |
| Out2            | 0     | 0  | 0  | 1  | ... | 0  |  |
| Out3            | 0     | 0  | 0  | 0  | ... | 0  |  |
| Out4            | 0     | 1  | 1  | 1  | ... | 0  |  |
| Exp. Out1       | 0     | 0  | 1  | 1  | ... | 0  |  |
| Exp. Out2       | 0     | 0  | 0  | 1  | ... | 0  |  |
| Exp. Out3       | 0     | 0  | 0  | 0  | ... | 0  |  |
| Exp. Out4       | 0     | 1  | 1  | 1  | ... | 0  |  |
| Out1 (DSP)      | 0     | 0  | 1  | 1  | ... | 0  |  |
| Out2 (DSP)      | 0     | 0  | 0  | 1  | ... | 0  |  |
| Out3 (DSP)      | 0     | 0  | 0  | 0  | ... | 0  |  |
| Out4 (DSP)      | 0     | 1  | 1  | 1  | ... | 0  |  |
| Exp. Out1 (DSP) | 0     | 0  | 1  | 1  | ... | 0  |  |
| Exp. Out2 (DSP) | 0     | 0  | 0  | 1  | ... | 0  |  |
| Exp. Out3 (DSP) | 0     | 0  | 0  | 0  | ... | 0  |  |
| Exp. Out4 (DSP) | 0     | 1  | 1  | 1  | ... | 0  |  |

| Test settings  |                                 |
|----------------|---------------------------------|
| Tolerance Out1 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |
| Tolerance Out2 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |
| Tolerance Out3 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |
| Tolerance Out4 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 42 |
| Max CPU cycles  | 68 |
| Avg CPU cycles  | 64 |

### Test case: Conversion test

OK

Conversion test for General block Sequencer.

| Test results                 |       |      |      |
|------------------------------|-------|------|------|
| Time step                    | 1     | 2    | 3    |
| <i>Mask parameters</i>       |       |      |      |
| Delay1                       | 0.1   | 0.1  | 0.1  |
| Delay2                       | 0.2   | 0.2  | 0.2  |
| Delay3                       | 1     | 1    | 1    |
| Delay4                       | 1.7   | 1.7  | 1.7  |
| ts_fact                      | 1     | 2    | 10   |
| <i>Controller parameters</i> |       |      |      |
| delay3                       | 10000 | 5000 | 1000 |
| delay4                       | 17000 | 8500 | 1700 |
| delay1                       | 1000  | 500  | 100  |
| delay2                       | 2000  | 1000 | 200  |
| Exp. delay3                  | 10000 | 5000 | 1000 |
| Exp. delay4                  | 17000 | 8500 | 1700 |
| Exp. delay1                  | 1000  | 500  | 100  |
| Exp. delay2                  | 2000  | 1000 | 200  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance delay3 | $\pm 0,0000e+00$ |
| Tolerance delay4 | $\pm 0,0000e+00$ |
| Tolerance delay1 | $\pm 0,0000e+00$ |
| Tolerance delay2 | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block Sequencer.

| Test results          |       |      |      |
|-----------------------|-------|------|------|
| Time step             | 1     | 2    | 3    |
| Mask parameters       |       |      |      |
| Delay1                | 0.1   | 0.1  | 0.1  |
| Delay2                | 0.2   | 0.2  | 0.2  |
| Delay3                | 1     | 1    | 1    |
| Delay4                | 1.7   | 1.7  | 1.7  |
| ts_fact               | 1     | 2    | 10   |
| Controller parameters |       |      |      |
| delay3                | 10000 | 5000 | 1000 |
| delay4                | 17000 | 8500 | 1700 |
| delay1                | 1000  | 500  | 100  |
| delay2                | 2000  | 1000 | 200  |
| Exp. delay3           | 10000 | 5000 | 1000 |
| Exp. delay4           | 17000 | 8500 | 1700 |
| Exp. delay1           | 1000  | 500  | 100  |
| Exp. delay2           | 2000  | 1000 | 200  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance delay3 | $\pm 0,0000e+00$ |
| Tolerance delay4 | $\pm 0,0000e+00$ |
| Tolerance delay1 | $\pm 0,0000e+00$ |
| Tolerance delay2 | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1852 |
| Max CPU cycles  | 1853 |
| Avg CPU cycles  | 1852 |

**Verification: Sequencer Bool CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block Sequencer.

| Test results    |       |    |    |    |     |    |  |
|-----------------|-------|----|----|----|-----|----|--|
| Time step       | 1     | 2  | 3  | 4  | ... | 16 |  |
| CPU cycles      | 54    | 72 | 90 | 85 | ... | 54 |  |
| Inputs          |       |    |    |    |     |    |  |
| Start (DSP)     | 0     | 1  | 1  | 1  | ... | 0  |  |
| Start           | 0     | 1  | 1  | 1  | ... | 0  |  |
| Parameters      |       |    |    |    |     |    |  |
| Delay1          | 0     |    |    |    |     |    |  |
| Delay2          | 0     |    |    |    |     |    |  |
| Delay3          | 0.001 |    |    |    |     |    |  |
| Delay4          | 0     |    |    |    |     |    |  |
| ts_fact         | 1     |    |    |    |     |    |  |
| Outputs         |       |    |    |    |     |    |  |
| Out1            | 0     | 0  | 1  | 1  | ... | 0  |  |
| Out2            | 0     | 0  | 0  | 1  | ... | 0  |  |
| Out3            | 0     | 0  | 0  | 0  | ... | 0  |  |
| Out4            | 0     | 1  | 1  | 1  | ... | 0  |  |
| Exp. Out1       | 0     | 0  | 1  | 1  | ... | 0  |  |
| Exp. Out2       | 0     | 0  | 0  | 1  | ... | 0  |  |
| Exp. Out3       | 0     | 0  | 0  | 0  | ... | 0  |  |
| Exp. Out4       | 0     | 1  | 1  | 1  | ... | 0  |  |
| Out1 (DSP)      | 0     | 0  | 1  | 1  | ... | 0  |  |
| Out2 (DSP)      | 0     | 0  | 0  | 1  | ... | 0  |  |
| Out3 (DSP)      | 0     | 0  | 0  | 0  | ... | 0  |  |
| Out4 (DSP)      | 0     | 1  | 1  | 1  | ... | 0  |  |
| Exp. Out1 (DSP) | 0     | 0  | 1  | 1  | ... | 0  |  |
| Exp. Out2 (DSP) | 0     | 0  | 0  | 1  | ... | 0  |  |
| Exp. Out3 (DSP) | 0     | 0  | 0  | 0  | ... | 0  |  |
| Exp. Out4 (DSP) | 0     | 1  | 1  | 1  | ... | 0  |  |

| Test settings  |                                 |
|----------------|---------------------------------|
| Tolerance Out1 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |
| Tolerance Out2 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |
| Tolerance Out3 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |
| Tolerance Out4 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 54 |
| Max CPU cycles  | 90 |
| Avg CPU cycles  | 77 |

### Test case: Conversion test

OK

Conversion test for General block Sequencer.

| Test results                 |       |      |      |
|------------------------------|-------|------|------|
| Time step                    | 1     | 2    | 3    |
| <i>Mask parameters</i>       |       |      |      |
| <b>Delay1</b>                | 0.1   | 0.1  | 0.1  |
| <b>Delay2</b>                | 0.2   | 0.2  | 0.2  |
| <b>Delay3</b>                | 1     | 1    | 1    |
| <b>Delay4</b>                | 1.7   | 1.7  | 1.7  |
| <b>ts_fact</b>               | 1     | 2    | 10   |
| <i>Controller parameters</i> |       |      |      |
| <b>delay3</b>                | 10000 | 5000 | 1000 |
| <b>delay4</b>                | 17000 | 8500 | 1700 |
| <b>delay1</b>                | 1000  | 500  | 100  |
| <b>delay2</b>                | 2000  | 1000 | 200  |
| <b>Exp. delay3</b>           | 10000 | 5000 | 1000 |
| <b>Exp. delay4</b>           | 17000 | 8500 | 1700 |
| <b>Exp. delay1</b>           | 1000  | 500  | 100  |
| <b>Exp. delay2</b>           | 2000  | 1000 | 200  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance delay3 | $\pm 0,0000e+00$ |
| Tolerance delay4 | $\pm 0,0000e+00$ |
| Tolerance delay1 | $\pm 0,0000e+00$ |
| Tolerance delay2 | $\pm 0,0000e+00$ |



**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block Sequencer.

| Test results          |       |      |      |
|-----------------------|-------|------|------|
| Time step             | 1     | 2    | 3    |
| Mask parameters       |       |      |      |
| Delay1                | 0.1   | 0.1  | 0.1  |
| Delay2                | 0.2   | 0.2  | 0.2  |
| Delay3                | 1     | 1    | 1    |
| Delay4                | 1.7   | 1.7  | 1.7  |
| ts_fact               | 1     | 2    | 10   |
| Controller parameters |       |      |      |
| delay3                | 10000 | 5000 | 1000 |
| delay4                | 17000 | 8500 | 1700 |
| delay1                | 1000  | 500  | 100  |
| delay2                | 2000  | 1000 | 200  |
| Exp. delay3           | 10000 | 5000 | 1000 |
| Exp. delay4           | 17000 | 8500 | 1700 |
| Exp. delay1           | 1000  | 500  | 100  |
| Exp. delay2           | 2000  | 1000 | 200  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance delay3 | $\pm 0,0000e+00$ |
| Tolerance delay4 | $\pm 0,0000e+00$ |
| Tolerance delay1 | $\pm 0,0000e+00$ |
| Tolerance delay2 | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 7397 |
| Max CPU cycles  | 7489 |
| Avg CPU cycles  | 7437 |

**Verification: Sequencer Bool CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block Sequencer.

| Test results    |       |    |     |     |     |    |
|-----------------|-------|----|-----|-----|-----|----|
| Time step       | 1     | 2  | 3   | 4   | ... | 16 |
| CPU cycles      | 107   | 99 | 109 | 102 | ... | 79 |
| Inputs          |       |    |     |     |     |    |
| Start (DSP)     | 0     | 1  | 1   | 1   | ... | 0  |
| Start           | 0     | 1  | 1   | 1   | ... | 0  |
| Parameters      |       |    |     |     |     |    |
| Delay1          | 0     |    |     |     |     |    |
| Delay2          | 0     |    |     |     |     |    |
| Delay3          | 0.001 |    |     |     |     |    |
| Delay4          | 0     |    |     |     |     |    |
| ts_fact         | 1     |    |     |     |     |    |
| Outputs         |       |    |     |     |     |    |
| Out1            | 0     | 0  | 1   | 1   | ... | 0  |
| Out2            | 0     | 0  | 0   | 1   | ... | 0  |
| Out3            | 0     | 0  | 0   | 0   | ... | 0  |
| Out4            | 0     | 1  | 1   | 1   | ... | 0  |
| Exp. Out1       | 0     | 0  | 1   | 1   | ... | 0  |
| Exp. Out2       | 0     | 0  | 0   | 1   | ... | 0  |
| Exp. Out3       | 0     | 0  | 0   | 0   | ... | 0  |
| Exp. Out4       | 0     | 1  | 1   | 1   | ... | 0  |
| Out1 (DSP)      | 0     | 0  | 1   | 1   | ... | 0  |
| Out2 (DSP)      | 0     | 0  | 0   | 1   | ... | 0  |
| Out3 (DSP)      | 0     | 0  | 0   | 0   | ... | 0  |
| Out4 (DSP)      | 0     | 1  | 1   | 1   | ... | 0  |
| Exp. Out1 (DSP) | 0     | 0  | 1   | 1   | ... | 0  |
| Exp. Out2 (DSP) | 0     | 0  | 0   | 1   | ... | 0  |
| Exp. Out3 (DSP) | 0     | 0  | 0   | 0   | ... | 0  |
| Exp. Out4 (DSP) | 0     | 1  | 1   | 1   | ... | 0  |

| Test settings  |                                 |
|----------------|---------------------------------|
| Tolerance Out1 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |
| Tolerance Out2 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |
| Tolerance Out3 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |
| Tolerance Out4 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 79  |
| Max CPU cycles  | 109 |
| Avg CPU cycles  | 101 |

### Test case: Conversion test

OK

Conversion test for General block Sequencer.

| Test results                 |       |      |      |
|------------------------------|-------|------|------|
| Time step                    | 1     | 2    | 3    |
| <i>Mask parameters</i>       |       |      |      |
| <b>Delay1</b>                | 0.1   | 0.1  | 0.1  |
| <b>Delay2</b>                | 0.2   | 0.2  | 0.2  |
| <b>Delay3</b>                | 1     | 1    | 1    |
| <b>Delay4</b>                | 1.7   | 1.7  | 1.7  |
| <b>ts_fact</b>               | 1     | 2    | 10   |
| <i>Controller parameters</i> |       |      |      |
| <b>delay3</b>                | 10000 | 5000 | 1000 |
| <b>delay4</b>                | 17000 | 8500 | 1700 |
| <b>delay1</b>                | 1000  | 500  | 100  |
| <b>delay2</b>                | 2000  | 1000 | 200  |
| <b>Exp. delay3</b>           | 10000 | 5000 | 1000 |
| <b>Exp. delay4</b>           | 17000 | 8500 | 1700 |
| <b>Exp. delay1</b>           | 1000  | 500  | 100  |
| <b>Exp. delay2</b>           | 2000  | 1000 | 200  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance delay3 | $\pm 0,0000e+00$ |
| Tolerance delay4 | $\pm 0,0000e+00$ |
| Tolerance delay1 | $\pm 0,0000e+00$ |
| Tolerance delay2 | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block Sequencer.

| Test results          |       |      |      |
|-----------------------|-------|------|------|
| Time step             | 1     | 2    | 3    |
| Mask parameters       |       |      |      |
| Delay1                | 0.1   | 0.1  | 0.1  |
| Delay2                | 0.2   | 0.2  | 0.2  |
| Delay3                | 1     | 1    | 1    |
| Delay4                | 1.7   | 1.7  | 1.7  |
| ts_fact               | 1     | 2    | 10   |
| Controller parameters |       |      |      |
| delay3                | 10000 | 5000 | 1000 |
| delay4                | 17000 | 8500 | 1700 |
| delay1                | 1000  | 500  | 100  |
| delay2                | 2000  | 1000 | 200  |
| Exp. delay3           | 10000 | 5000 | 1000 |
| Exp. delay4           | 17000 | 8500 | 1700 |
| Exp. delay1           | 1000  | 500  | 100  |
| Exp. delay2           | 2000  | 1000 | 200  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance delay3 | $\pm 0,0000e+00$ |
| Tolerance delay4 | $\pm 0,0000e+00$ |
| Tolerance delay1 | $\pm 0,0000e+00$ |
| Tolerance delay2 | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1037 |
| Max CPU cycles  | 1300 |
| Avg CPU cycles  | 1136 |

**Verification: Sequencer Bool CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block Sequencer.

| Test results    |       |     |     |    |     |    |
|-----------------|-------|-----|-----|----|-----|----|
| Time step       | 1     | 2   | 3   | 4  | ... | 16 |
| CPU cycles      | 55    | 111 | 107 | 99 | ... | 55 |
| Inputs          |       |     |     |    |     |    |
| Start (DSP)     | 0     | 1   | 1   | 1  | ... | 0  |
| Start           | 0     | 1   | 1   | 1  | ... | 0  |
| Parameters      |       |     |     |    |     |    |
| Delay1          | 0     |     |     |    |     |    |
| Delay2          | 0     |     |     |    |     |    |
| Delay3          | 0.001 |     |     |    |     |    |
| Delay4          | 0     |     |     |    |     |    |
| ts_fact         | 1     |     |     |    |     |    |
| Outputs         |       |     |     |    |     |    |
| Out1            | 0     | 0   | 1   | 1  | ... | 0  |
| Out2            | 0     | 0   | 0   | 1  | ... | 0  |
| Out3            | 0     | 0   | 0   | 0  | ... | 0  |
| Out4            | 0     | 1   | 1   | 1  | ... | 0  |
| Exp. Out1       | 0     | 0   | 1   | 1  | ... | 0  |
| Exp. Out2       | 0     | 0   | 0   | 1  | ... | 0  |
| Exp. Out3       | 0     | 0   | 0   | 0  | ... | 0  |
| Exp. Out4       | 0     | 1   | 1   | 1  | ... | 0  |
| Out1 (DSP)      | 0     | 0   | 1   | 1  | ... | 0  |
| Out2 (DSP)      | 0     | 0   | 0   | 1  | ... | 0  |
| Out3 (DSP)      | 0     | 0   | 0   | 0  | ... | 0  |
| Out4 (DSP)      | 0     | 1   | 1   | 1  | ... | 0  |
| Exp. Out1 (DSP) | 0     | 0   | 1   | 1  | ... | 0  |
| Exp. Out2 (DSP) | 0     | 0   | 0   | 1  | ... | 0  |
| Exp. Out3 (DSP) | 0     | 0   | 0   | 0  | ... | 0  |
| Exp. Out4 (DSP) | 0     | 1   | 1   | 1  | ... | 0  |

| Test settings  |                                 |
|----------------|---------------------------------|
| Tolerance Out1 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |
| Tolerance Out2 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |
| Tolerance Out3 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |
| Tolerance Out4 | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 55  |
| Max CPU cycles  | 111 |
| Avg CPU cycles  | 94  |

### Test case: Conversion test

OK

Conversion test for General block Sequencer.

| Test results                 |       |      |      |
|------------------------------|-------|------|------|
| Time step                    | 1     | 2    | 3    |
| <i>Mask parameters</i>       |       |      |      |
| <b>Delay1</b>                | 0.1   | 0.1  | 0.1  |
| <b>Delay2</b>                | 0.2   | 0.2  | 0.2  |
| <b>Delay3</b>                | 1     | 1    | 1    |
| <b>Delay4</b>                | 1.7   | 1.7  | 1.7  |
| <b>ts_fact</b>               | 1     | 2    | 10   |
| <i>Controller parameters</i> |       |      |      |
| <b>delay3</b>                | 10000 | 5000 | 1000 |
| <b>delay4</b>                | 17000 | 8500 | 1700 |
| <b>delay1</b>                | 1000  | 500  | 100  |
| <b>delay2</b>                | 2000  | 1000 | 200  |
| <b>Exp. delay3</b>           | 10000 | 5000 | 1000 |
| <b>Exp. delay4</b>           | 17000 | 8500 | 1700 |
| <b>Exp. delay1</b>           | 1000  | 500  | 100  |
| <b>Exp. delay2</b>           | 2000  | 1000 | 200  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance delay3 | $\pm 0,0000e+00$ |
| Tolerance delay4 | $\pm 0,0000e+00$ |
| Tolerance delay1 | $\pm 0,0000e+00$ |
| Tolerance delay2 | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block Sequencer.


| Test results          |       |      |      |
|-----------------------|-------|------|------|
| Time step             | 1     | 2    | 3    |
| Mask parameters       |       |      |      |
| Delay1                | 0.1   | 0.1  | 0.1  |
| Delay2                | 0.2   | 0.2  | 0.2  |
| Delay3                | 1     | 1    | 1    |
| Delay4                | 1.7   | 1.7  | 1.7  |
| ts_fact               | 1     | 2    | 10   |
| Controller parameters |       |      |      |
| delay3                | 10000 | 5000 | 1000 |
| delay4                | 17000 | 8500 | 1700 |
| delay1                | 1000  | 500  | 100  |
| delay2                | 2000  | 1000 | 200  |
| Exp. delay3           | 10000 | 5000 | 1000 |
| Exp. delay4           | 17000 | 8500 | 1700 |
| Exp. delay1           | 1000  | 500  | 100  |
| Exp. delay2           | 2000  | 1000 | 200  |

| Test settings    |                  |
|------------------|------------------|
| Tolerance delay3 | $\pm 0,0000e+00$ |
| Tolerance delay4 | $\pm 0,0000e+00$ |
| Tolerance delay1 | $\pm 0,0000e+00$ |
| Tolerance delay2 | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2737 |
| Max CPU cycles  | 2742 |
| Avg CPU cycles  | 2740 |

## Block: Sin2Limiter

---



Limitation of rising and falling rate with  $\sin^2$  characteristic.

Note: A running limitation process can not be interrupted!

Function of Enable:

0: rate limiting disabled, signal is set to zero

1: rate limiting enabled, signal is rate limited

0->1: preload of output with value from init input

| Inports |                                                                                                                                                                                           |
|---------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| In      |                                                                                                                                                                                           |
| Init    | Value which is loaded at rising flanke of enable signal                                                                                                                                   |
| Enable  | Enable == 0: Deactivation of block; Out is set to zero.<br>Enable != 0: Activation of block; Out is rate limited.<br>Enable 0->1: Preloading of output; Out is set to value of Init input |

| Outports |  |
|----------|--|
| Out      |  |

| Mask Parameters |    |                                                                 |
|-----------------|----|-----------------------------------------------------------------|
| Name            | ID | Description                                                     |
| Tr              | 1  | Rising time in seconds. Slew rate will be $1/Tr$                |
| Tf              | 2  | Falling time in seconds. Slew rate will be $1/Tf$               |
| ts_fact         | 3  | Multiplication factor of base sampling time (in integer format) |

### Description:

Rising and falling time refer to a step from 0 to 1. Entries for *Tr*: *Rising time* and *Tf*: *Falling time* smaller than the actual sample time will be limited to the sample time internally.

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation



| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |
| Init              | int16 |
| Enable            | bool  |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |
| Init              | int32 |
| Enable            | bool  |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |
| Init              | float32 |
| Enable            | bool    |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |


### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |
| Init              | float64 |
| Enable            | bool    |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

## Block: Sin3Gen



Generation of a 3 sine waves with amplitude (A) and frequency (f).

| Inports |           |
|---------|-----------|
| A       | Amplitude |
| f       | Frequency |

| Outputs |                          |
|---------|--------------------------|
| u       | Sine wave output phase u |
| v       | Sine wave output phase v |
| w       | Sine wave output phase w |

| Mask Parameters |    |                                                                 |
|-----------------|----|-----------------------------------------------------------------|
| Name            | ID | Description                                                     |
| fmax            | 1  | Maximum Frequency in Hz                                         |
| Offset          | 2  | Offset                                                          |
| ts_fact         | 3  | Multiplication factor of base sampling time (in integer format) |

### Description:

Calculation fixed point implementation:

$$\begin{aligned}
 u_k &= A_k \sin(2f_k f_{\max} kT_s) + A_{\text{offset}} \\
 v_k &= A_k \sin\left(2f_k f_{\max} kT_s - \frac{2\pi}{3}\right) + A_{\text{offset}} \\
 w_k &= A_k \sin\left(2f_k f_{\max} kT_s + \frac{2\pi}{3}\right) + A_{\text{offset}}
 \end{aligned}$$

For sine calculation a lookup table with 256 entries is used. This results in a short computation time but with the downside of reduced accuracy for the FiP32 implementation.

Calculation floating point implementation (parameter  $f_{\max}$  is ignored):

$$\begin{aligned}
 u_k &= A_k \sin(2\pi f_k kT_s) + A_{\text{offset}} \\
 v_k &= A_k \sin\left(2\pi f_k kT_s - \frac{2\pi}{3}\right) + A_{\text{offset}} \\
 w_k &= A_k \sin\left(2\pi f_k kT_s + \frac{2\pi}{3}\right) + A_{\text{offset}}
 \end{aligned}$$

**Implementations:**

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

**Implementation: FiP16**

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| A                 | int16 |
| f                 | int16 |

| Outports Data Type |       |
|--------------------|-------|
| u                  | int16 |
| v                  | int16 |
| w                  | int16 |

**Implementation: FiP32**

---

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| A                 | int32 |
| f                 | int32 |

| Outports Data Type |       |
|--------------------|-------|
| u                  | int32 |
| v                  | int32 |
| w                  | int32 |

**Implementation: Float32**

---

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| A                 | float32 |
| f                 | float32 |

| Outports Data Type |         |
|--------------------|---------|
| u                  | float32 |
| v                  | float32 |
| w                  | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| A                 | float64 |
| f                 | float64 |

| Outports Data Type |         |
|--------------------|---------|
| u                  | float64 |
| v                  | float64 |
| w                  | float64 |

**Verification: Sin3Gen FiP16 CPU TMS320F28335**

Date of Test 2026-06-19  
Target controller TMS320F28335

**Test case: Inport test****OK**

Inport test for General block Sin3Gen.

| Test results |       |       |       |       |     |        |
|--------------|-------|-------|-------|-------|-----|--------|
| Time step    | 1     | 2     | 3     | 4     | ... | 200    |
| CPU cycles   | 230   | 230   | 230   | 230   | ... | 230    |
| Inputs       |       |       |       |       |     |        |
| A (DSP)      | 164   | 328   | 492   | 655   | ... | 32767  |
| f (DSP)      | 32767 | 32767 | 32767 | 32767 | ... | 32767  |
| A            | 0.005 | 0.01  | 0.015 | 0.02  | ... | 1      |
| f            | 1     | 1     | 1     | 1     | ... | 1      |
| Parameters   |       |       |       |       |     |        |
| fmax         | 200   |       |       |       |     |        |
| Offset       | 0.13  |       |       |       |     |        |
| ts_fact      | 1     |       |       |       |     |        |
| Outputs      |       |       |       |       |     |        |
| u            | 0.131 | 0.133 | 0.136 | 0.14  | ... | 0.135  |
| v            | 0.125 | 0.12  | 0.115 | 0.11  | ... | -0.739 |
| w            | 0.134 | 0.137 | 0.139 | 0.14  | ... | 0.993  |
| Exp. u       | 0.131 | 0.132 | 0.136 | 0.14  | ... | 0.13   |
| Exp. v       | 0.125 | 0.12  | 0.115 | 0.11  | ... | -0.736 |
| Exp. w       | 0.134 | 0.137 | 0.139 | 0.14  | ... | 0.996  |
| u (DSP)      | 4281  | 4342  | 4441  | 4576  | ... | 4435   |
| v (DSP)      | 4109  | 3944  | 3773  | 3605  | ... | -24204 |
| w (DSP)      | 4391  | 4494  | 4566  | 4599  | ... | 32545  |
| Exp. u (DSP) | 4280  | 4341  | 4441  | 4576  | ... | 4260   |
| Exp. v (DSP) | 4109  | 3944  | 3774  | 3605  | ... | -24118 |
| Exp. w (DSP) | 4390  | 4494  | 4565  | 4599  | ... | 32638  |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance u   | $\pm 5,3711\text{e-}03$ ( $\pm 176$ LSB) |
| Tolerance v   | $\pm 5,3711\text{e-}03$ ( $\pm 176$ LSB) |
| Tolerance w   | $\pm 5,3711\text{e-}03$ ( $\pm 176$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 227 |
| Max CPU cycles  | 230 |
| Avg CPU cycles  | 229 |

**Verification: Sin3Gen FiP16 CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block Sin3Gen.

| Test results |       |       |       |       |     |        |
|--------------|-------|-------|-------|-------|-----|--------|
| Time step    | 1     | 2     | 3     | 4     | ... | 200    |
| CPU cycles   | 181   | 181   | 181   | 181   | ... | 181    |
| Inputs       |       |       |       |       |     |        |
| A (DSP)      | 164   | 328   | 492   | 655   | ... | 32767  |
| f (DSP)      | 32767 | 32767 | 32767 | 32767 | ... | 32767  |
| A            | 0.005 | 0.01  | 0.015 | 0.02  | ... | 1      |
| f            | 1     | 1     | 1     | 1     | ... | 1      |
| Parameters   |       |       |       |       |     |        |
| fmax         | 200   |       |       |       |     |        |
| Offset       | 0.13  |       |       |       |     |        |
| ts_fact      | 1     |       |       |       |     |        |
| Outputs      |       |       |       |       |     |        |
| u            | 0.131 | 0.133 | 0.136 | 0.14  | ... | 0.135  |
| v            | 0.125 | 0.12  | 0.115 | 0.11  | ... | -0.739 |
| w            | 0.134 | 0.137 | 0.139 | 0.14  | ... | 0.993  |
| Exp. u       | 0.131 | 0.132 | 0.136 | 0.14  | ... | 0.13   |
| Exp. v       | 0.125 | 0.12  | 0.115 | 0.11  | ... | -0.736 |
| Exp. w       | 0.134 | 0.137 | 0.139 | 0.14  | ... | 0.996  |
| u (DSP)      | 4281  | 4342  | 4441  | 4576  | ... | 4435   |
| v (DSP)      | 4109  | 3944  | 3773  | 3605  | ... | -24204 |
| w (DSP)      | 4391  | 4494  | 4566  | 4599  | ... | 32545  |
| Exp. u (DSP) | 4280  | 4341  | 4441  | 4576  | ... | 4260   |
| Exp. v (DSP) | 4109  | 3944  | 3774  | 3605  | ... | -24118 |
| Exp. w (DSP) | 4390  | 4494  | 4565  | 4599  | ... | 32638  |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance u   | $\pm 5,3711\text{e-}03$ ( $\pm 176$ LSB) |
| Tolerance v   | $\pm 5,3711\text{e-}03$ ( $\pm 176$ LSB) |
| Tolerance w   | $\pm 5,3711\text{e-}03$ ( $\pm 176$ LSB) |



| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 175 |
| Max CPU cycles  | 181 |
| Avg CPU cycles  | 180 |

**Verification: Sin3Gen FiP16 CPU STM32G474RE**

Date of Test 2026-06-19  
Target controller STM32G474RE

**Test case: Inport test****OK**

Inport test for General block Sin3Gen.

| Test results |       |       |       |       |     |        |
|--------------|-------|-------|-------|-------|-----|--------|
| Time step    | 1     | 2     | 3     | 4     | ... | 200    |
| CPU cycles   | 215   | 211   | 211   | 216   | ... | 216    |
| Inputs       |       |       |       |       |     |        |
| A (DSP)      | 164   | 328   | 492   | 655   | ... | 32767  |
| f (DSP)      | 32767 | 32767 | 32767 | 32767 | ... | 32767  |
| A            | 0.005 | 0.01  | 0.015 | 0.02  | ... | 1      |
| f            | 1     | 1     | 1     | 1     | ... | 1      |
| Parameters   |       |       |       |       |     |        |
| fmax         | 200   |       |       |       |     |        |
| Offset       | 0.13  |       |       |       |     |        |
| ts_fact      | 1     |       |       |       |     |        |
| Outputs      |       |       |       |       |     |        |
| u            | 0.131 | 0.133 | 0.136 | 0.14  | ... | 0.135  |
| v            | 0.125 | 0.12  | 0.115 | 0.11  | ... | -0.739 |
| w            | 0.134 | 0.137 | 0.139 | 0.14  | ... | 0.993  |
| Exp. u       | 0.131 | 0.132 | 0.136 | 0.14  | ... | 0.13   |
| Exp. v       | 0.125 | 0.12  | 0.115 | 0.11  | ... | -0.736 |
| Exp. w       | 0.134 | 0.137 | 0.139 | 0.14  | ... | 0.996  |
| u (DSP)      | 4281  | 4342  | 4441  | 4576  | ... | 4435   |
| v (DSP)      | 4109  | 3944  | 3773  | 3605  | ... | -24204 |
| w (DSP)      | 4391  | 4494  | 4566  | 4599  | ... | 32545  |
| Exp. u (DSP) | 4280  | 4341  | 4441  | 4576  | ... | 4260   |
| Exp. v (DSP) | 4109  | 3944  | 3774  | 3605  | ... | -24118 |
| Exp. w (DSP) | 4390  | 4494  | 4565  | 4599  | ... | 32638  |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance u   | $\pm 5,3711\text{e-}03$ ( $\pm 176$ LSB) |
| Tolerance v   | $\pm 5,3711\text{e-}03$ ( $\pm 176$ LSB) |
| Tolerance w   | $\pm 5,3711\text{e-}03$ ( $\pm 176$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 211 |
| Max CPU cycles  | 216 |
| Avg CPU cycles  | 214 |

**Verification: Sin3Gen FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block Sin3Gen.

| Test results |       |       |       |       |     |        |
|--------------|-------|-------|-------|-------|-----|--------|
| Time step    | 1     | 2     | 3     | 4     | ... | 200    |
| CPU cycles   | 249   | 249   | 249   | 249   | ... | 249    |
| Inputs       |       |       |       |       |     |        |
| A (DSP)      | 164   | 328   | 492   | 655   | ... | 32767  |
| f (DSP)      | 32767 | 32767 | 32767 | 32767 | ... | 32767  |
| A            | 0.005 | 0.01  | 0.015 | 0.02  | ... | 1      |
| f            | 1     | 1     | 1     | 1     | ... | 1      |
| Parameters   |       |       |       |       |     |        |
| fmax         | 200   |       |       |       |     |        |
| Offset       | 0.13  |       |       |       |     |        |
| ts_fact      | 1     |       |       |       |     |        |
| Outputs      |       |       |       |       |     |        |
| u            | 0.131 | 0.133 | 0.136 | 0.14  | ... | 0.135  |
| v            | 0.125 | 0.12  | 0.115 | 0.11  | ... | -0.739 |
| w            | 0.134 | 0.137 | 0.139 | 0.14  | ... | 0.993  |
| Exp. u       | 0.131 | 0.132 | 0.136 | 0.14  | ... | 0.13   |
| Exp. v       | 0.125 | 0.12  | 0.115 | 0.11  | ... | -0.736 |
| Exp. w       | 0.134 | 0.137 | 0.139 | 0.14  | ... | 0.996  |
| u (DSP)      | 4281  | 4342  | 4441  | 4576  | ... | 4435   |
| v (DSP)      | 4109  | 3944  | 3773  | 3605  | ... | -24204 |
| w (DSP)      | 4391  | 4494  | 4566  | 4599  | ... | 32545  |
| Exp. u (DSP) | 4280  | 4341  | 4441  | 4576  | ... | 4260   |
| Exp. v (DSP) | 4109  | 3944  | 3774  | 3605  | ... | -24118 |
| Exp. w (DSP) | 4390  | 4494  | 4565  | 4599  | ... | 32638  |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance u   | $\pm 5,3711\text{e-}03$ ( $\pm 176$ LSB) |
| Tolerance v   | $\pm 5,3711\text{e-}03$ ( $\pm 176$ LSB) |
| Tolerance w   | $\pm 5,3711\text{e-}03$ ( $\pm 176$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 249 |
| Max CPU cycles  | 308 |
| Avg CPU cycles  | 249 |

**Verification: Sin3Gen FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block Sin3Gen.

| Test results |       |       |       |       |     |        |
|--------------|-------|-------|-------|-------|-----|--------|
| Time step    | 1     | 2     | 3     | 4     | ... | 200    |
| CPU cycles   | 139   | 139   | 139   | 139   | ... | 139    |
| Inputs       |       |       |       |       |     |        |
| A (DSP)      | 164   | 328   | 492   | 655   | ... | 32767  |
| f (DSP)      | 32767 | 32767 | 32767 | 32767 | ... | 32767  |
| A            | 0.005 | 0.01  | 0.015 | 0.02  | ... | 1      |
| f            | 1     | 1     | 1     | 1     | ... | 1      |
| Parameters   |       |       |       |       |     |        |
| fmax         | 200   |       |       |       |     |        |
| Offset       | 0.13  |       |       |       |     |        |
| ts_fact      | 1     |       |       |       |     |        |
| Outputs      |       |       |       |       |     |        |
| u            | 0.131 | 0.133 | 0.136 | 0.14  | ... | 0.135  |
| v            | 0.125 | 0.12  | 0.115 | 0.11  | ... | -0.739 |
| w            | 0.134 | 0.137 | 0.139 | 0.14  | ... | 0.993  |
| Exp. u       | 0.131 | 0.132 | 0.136 | 0.14  | ... | 0.13   |
| Exp. v       | 0.125 | 0.12  | 0.115 | 0.11  | ... | -0.736 |
| Exp. w       | 0.134 | 0.137 | 0.139 | 0.14  | ... | 0.996  |
| u (DSP)      | 4281  | 4342  | 4441  | 4576  | ... | 4435   |
| v (DSP)      | 4109  | 3944  | 3773  | 3605  | ... | -24204 |
| w (DSP)      | 4391  | 4494  | 4566  | 4599  | ... | 32545  |
| Exp. u (DSP) | 4280  | 4341  | 4441  | 4576  | ... | 4260   |
| Exp. v (DSP) | 4109  | 3944  | 3774  | 3605  | ... | -24118 |
| Exp. w (DSP) | 4390  | 4494  | 4565  | 4599  | ... | 32638  |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance u   | $\pm 5,3711e-03$ ( $\pm 176$ LSB) |
| Tolerance v   | $\pm 5,3711e-03$ ( $\pm 176$ LSB) |
| Tolerance w   | $\pm 5,3711e-03$ ( $\pm 176$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 139 |
| Max CPU cycles  | 139 |
| Avg CPU cycles  | 139 |

**Verification: Sin3Gen FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block Sin3Gen.

| Test results |       |       |       |       |     |        |
|--------------|-------|-------|-------|-------|-----|--------|
| Time step    | 1     | 2     | 3     | 4     | ... | 200    |
| CPU cycles   | 228   | 228   | 228   | 228   | ... | 228    |
| Inputs       |       |       |       |       |     |        |
| A (DSP)      | 164   | 328   | 492   | 655   | ... | 32767  |
| f (DSP)      | 32767 | 32767 | 32767 | 32767 | ... | 32767  |
| A            | 0.005 | 0.01  | 0.015 | 0.02  | ... | 1      |
| f            | 1     | 1     | 1     | 1     | ... | 1      |
| Parameters   |       |       |       |       |     |        |
| fmax         | 200   |       |       |       |     |        |
| Offset       | 0.13  |       |       |       |     |        |
| ts_fact      | 1     |       |       |       |     |        |
| Outputs      |       |       |       |       |     |        |
| u            | 0.131 | 0.133 | 0.136 | 0.14  | ... | 0.135  |
| v            | 0.125 | 0.12  | 0.115 | 0.11  | ... | -0.739 |
| w            | 0.134 | 0.137 | 0.139 | 0.14  | ... | 0.993  |
| Exp. u       | 0.131 | 0.132 | 0.136 | 0.14  | ... | 0.13   |
| Exp. v       | 0.125 | 0.12  | 0.115 | 0.11  | ... | -0.736 |
| Exp. w       | 0.134 | 0.137 | 0.139 | 0.14  | ... | 0.996  |
| u (DSP)      | 4281  | 4342  | 4441  | 4576  | ... | 4435   |
| v (DSP)      | 4109  | 3944  | 3773  | 3605  | ... | -24204 |
| w (DSP)      | 4391  | 4494  | 4566  | 4599  | ... | 32545  |
| Exp. u (DSP) | 4280  | 4341  | 4441  | 4576  | ... | 4260   |
| Exp. v (DSP) | 4109  | 3944  | 3774  | 3605  | ... | -24118 |
| Exp. w (DSP) | 4390  | 4494  | 4565  | 4599  | ... | 32638  |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance u   | $\pm 5,3711e-03$ ( $\pm 176$ LSB) |
| Tolerance v   | $\pm 5,3711e-03$ ( $\pm 176$ LSB) |
| Tolerance w   | $\pm 5,3711e-03$ ( $\pm 176$ LSB) |



| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 227 |
| Max CPU cycles  | 228 |
| Avg CPU cycles  | 227 |

**Verification: Sin3Gen FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block Sin3Gen.

| Test results |       |       |       |       |     |        |
|--------------|-------|-------|-------|-------|-----|--------|
| Time step    | 1     | 2     | 3     | 4     | ... | 200    |
| CPU cycles   | 257   | 211   | 211   | 211   | ... | 211    |
| Inputs       |       |       |       |       |     |        |
| A (DSP)      | 164   | 328   | 492   | 655   | ... | 32767  |
| f (DSP)      | 32767 | 32767 | 32767 | 32767 | ... | 32767  |
| A            | 0.005 | 0.01  | 0.015 | 0.02  | ... | 1      |
| f            | 1     | 1     | 1     | 1     | ... | 1      |
| Parameters   |       |       |       |       |     |        |
| fmax         | 200   |       |       |       |     |        |
| Offset       | 0.13  |       |       |       |     |        |
| ts_fact      | 1     |       |       |       |     |        |
| Outputs      |       |       |       |       |     |        |
| u            | 0.131 | 0.133 | 0.136 | 0.14  | ... | 0.135  |
| v            | 0.125 | 0.12  | 0.115 | 0.11  | ... | -0.739 |
| w            | 0.134 | 0.137 | 0.139 | 0.14  | ... | 0.993  |
| Exp. u       | 0.131 | 0.132 | 0.136 | 0.14  | ... | 0.13   |
| Exp. v       | 0.125 | 0.12  | 0.115 | 0.11  | ... | -0.736 |
| Exp. w       | 0.134 | 0.137 | 0.139 | 0.14  | ... | 0.996  |
| u (DSP)      | 4281  | 4342  | 4441  | 4576  | ... | 4435   |
| v (DSP)      | 4109  | 3944  | 3773  | 3605  | ... | -24204 |
| w (DSP)      | 4391  | 4494  | 4566  | 4599  | ... | 32545  |
| Exp. u (DSP) | 4280  | 4341  | 4441  | 4576  | ... | 4260   |
| Exp. v (DSP) | 4109  | 3944  | 3774  | 3605  | ... | -24118 |
| Exp. w (DSP) | 4390  | 4494  | 4565  | 4599  | ... | 32638  |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance u   | $\pm 5,3711\text{e-}03$ ( $\pm 176$ LSB) |
| Tolerance v   | $\pm 5,3711\text{e-}03$ ( $\pm 176$ LSB) |
| Tolerance w   | $\pm 5,3711\text{e-}03$ ( $\pm 176$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 211 |
| Max CPU cycles  | 257 |
| Avg CPU cycles  | 211 |

**Verification: Sin3Gen FiP16 CPU TMS320F28379D**

Date of Test 2026-06-22  
Target controller TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block Sin3Gen.

| Test results |       |       |       |       |     |        |
|--------------|-------|-------|-------|-------|-----|--------|
| Time step    | 1     | 2     | 3     | 4     | ... | 200    |
| CPU cycles   | 202   | 202   | 202   | 205   | ... | 202    |
| Inputs       |       |       |       |       |     |        |
| A (DSP)      | 164   | 328   | 492   | 655   | ... | 32767  |
| f (DSP)      | 32767 | 32767 | 32767 | 32767 | ... | 32767  |
| A            | 0.005 | 0.01  | 0.015 | 0.02  | ... | 1      |
| f            | 1     | 1     | 1     | 1     | ... | 1      |
| Parameters   |       |       |       |       |     |        |
| fmax         | 200   |       |       |       |     |        |
| Offset       | 0.13  |       |       |       |     |        |
| ts_fact      | 1     |       |       |       |     |        |
| Outputs      |       |       |       |       |     |        |
| u            | 0.131 | 0.133 | 0.136 | 0.14  | ... | 0.135  |
| v            | 0.125 | 0.12  | 0.115 | 0.11  | ... | -0.739 |
| w            | 0.134 | 0.137 | 0.139 | 0.14  | ... | 0.993  |
| Exp. u       | 0.131 | 0.132 | 0.136 | 0.14  | ... | 0.13   |
| Exp. v       | 0.125 | 0.12  | 0.115 | 0.11  | ... | -0.736 |
| Exp. w       | 0.134 | 0.137 | 0.139 | 0.14  | ... | 0.996  |
| u (DSP)      | 4281  | 4342  | 4441  | 4576  | ... | 4435   |
| v (DSP)      | 4109  | 3944  | 3773  | 3605  | ... | -24204 |
| w (DSP)      | 4391  | 4494  | 4566  | 4599  | ... | 32545  |
| Exp. u (DSP) | 4280  | 4341  | 4441  | 4576  | ... | 4260   |
| Exp. v (DSP) | 4109  | 3944  | 3774  | 3605  | ... | -24118 |
| Exp. w (DSP) | 4390  | 4494  | 4565  | 4599  | ... | 32638  |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance u   | $\pm 5,3711\text{e-}03$ ( $\pm 176$ LSB) |
| Tolerance v   | $\pm 5,3711\text{e-}03$ ( $\pm 176$ LSB) |
| Tolerance w   | $\pm 5,3711\text{e-}03$ ( $\pm 176$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 196 |
| Max CPU cycles  | 208 |
| Avg CPU cycles  | 203 |

**Verification: Sin3Gen FiP32 CPU TMS320F28335**

Date of Test 2026-06-19  
Target controller TMS320F28335

**Test case: Inport test****OK**

Inport test for General block Sin3Gen.

| Test results |            |            |     |             |
|--------------|------------|------------|-----|-------------|
| Time step    | 1          | 2          | ... | 200         |
| CPU cycles   | 627        | 627        | ... | 627         |
| Inputs       |            |            |     |             |
| A (DSP)      | 10737418   | 21474836   | ... | 2147483647  |
| f (DSP)      | 2147483647 | 2147483647 | ... | 2147483647  |
| A            | 0.005      | 0.01       | ... | 1           |
| f            | 1          | 1          | ... | 1           |
| Parameters   |            |            |     |             |
| fmax         | 200        |            |     |             |
| Offset       | 0.13       |            |     |             |
| ts_fact      | 1          |            |     |             |
| Outputs      |            |            |     |             |
| u            | 0.131      | 0.132      | ... | 0.13        |
| v            | 0.125      | 0.12       | ... | -0.736      |
| w            | 0.134      | 0.137      | ... | 0.996       |
| Exp. u       | 0.131      | 0.132      | ... | 0.13        |
| Exp. v       | 0.125      | 0.12       | ... | -0.736      |
| Exp. w       | 0.134      | 0.137      | ... | 0.996       |
| u (DSP)      | 280518584  | 284513150  | ... | 279172924   |
| v (DSP)      | 269274943  | 258489642  | ... | -1580478263 |
| w (DSP)      | 287724911  | 294514926  | ... | 2138823959  |
| Exp. u (DSP) | 280518630  | 284513449  | ... | 279172874   |
| Exp. v (DSP) | 269274444  | 258489116  | ... | -1580602519 |
| Exp. w (DSP) | 287725549  | 294516058  | ... | 2138948268  |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance u   | $\pm 6,9849e-05$ ( $\pm 150000$ LSB) |
| Tolerance v   | $\pm 6,9849e-05$ ( $\pm 150000$ LSB) |
| Tolerance w   | $\pm 6,9849e-05$ ( $\pm 150000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 575 |
| Max CPU cycles  | 627 |
| Avg CPU cycles  | 624 |

**Verification: Sin3Gen FiP32 CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block Sin3Gen.

| Test results |            |            |     |             |
|--------------|------------|------------|-----|-------------|
| Time step    | 1          | 2          | ... | 200         |
| CPU cycles   | 189        | 189        | ... | 189         |
| Inputs       |            |            |     |             |
| A (DSP)      | 10737418   | 21474836   | ... | 2147483647  |
| f (DSP)      | 2147483647 | 2147483647 | ... | 2147483647  |
| A            | 0.005      | 0.01       | ... | 1           |
| f            | 1          | 1          | ... | 1           |
| Parameters   |            |            |     |             |
| fmax         | 200        |            |     |             |
| Offset       | 0.13       |            |     |             |
| ts_fact      | 1          |            |     |             |
| Outputs      |            |            |     |             |
| u            | 0.131      | 0.132      | ... | 0.13        |
| v            | 0.125      | 0.12       | ... | -0.736      |
| w            | 0.134      | 0.137      | ... | 0.996       |
| Exp. u       | 0.131      | 0.132      | ... | 0.13        |
| Exp. v       | 0.125      | 0.12       | ... | -0.736      |
| Exp. w       | 0.134      | 0.137      | ... | 0.996       |
| u (DSP)      | 280518584  | 284513150  | ... | 279172924   |
| v (DSP)      | 269274943  | 258489642  | ... | -1580478263 |
| w (DSP)      | 287724911  | 294514926  | ... | 2138823959  |
| Exp. u (DSP) | 280518630  | 284513449  | ... | 279172874   |
| Exp. v (DSP) | 269274444  | 258489116  | ... | -1580602519 |
| Exp. w (DSP) | 287725549  | 294516058  | ... | 2138948268  |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance u   | $\pm 6,9849e-05$ ( $\pm 150000$ LSB) |
| Tolerance v   | $\pm 6,9849e-05$ ( $\pm 150000$ LSB) |
| Tolerance w   | $\pm 6,9849e-05$ ( $\pm 150000$ LSB) |



| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 183 |
| Max CPU cycles  | 189 |
| Avg CPU cycles  | 188 |

**Verification: Sin3Gen FiP32 CPU STM32G474RE**

Date of Test 2026-06-19  
Target controller STM32G474RE

**Test case: Inport test****OK**

Inport test for General block Sin3Gen.

| Test results |            |            |     |             |
|--------------|------------|------------|-----|-------------|
| Time step    | 1          | 2          | ... | 200         |
| CPU cycles   | 288        | 283        | ... | 283         |
| Inputs       |            |            |     |             |
| A (DSP)      | 10737418   | 21474836   | ... | 2147483647  |
| f (DSP)      | 2147483647 | 2147483647 | ... | 2147483647  |
| A            | 0.005      | 0.01       | ... | 1           |
| f            | 1          | 1          | ... | 1           |
| Parameters   |            |            |     |             |
| fmax         | 200        |            |     |             |
| Offset       | 0.13       |            |     |             |
| ts_fact      | 1          |            |     |             |
| Outputs      |            |            |     |             |
| u            | 0.131      | 0.132      | ... | 0.13        |
| v            | 0.125      | 0.12       | ... | -0.736      |
| w            | 0.134      | 0.137      | ... | 0.996       |
| Exp. u       | 0.131      | 0.132      | ... | 0.13        |
| Exp. v       | 0.125      | 0.12       | ... | -0.736      |
| Exp. w       | 0.134      | 0.137      | ... | 0.996       |
| u (DSP)      | 280518584  | 284513150  | ... | 279172924   |
| v (DSP)      | 269274943  | 258489642  | ... | -1580478263 |
| w (DSP)      | 287724911  | 294514926  | ... | 2138823959  |
| Exp. u (DSP) | 280518630  | 284513449  | ... | 279172874   |
| Exp. v (DSP) | 269274444  | 258489116  | ... | -1580602519 |
| Exp. w (DSP) | 287725549  | 294516058  | ... | 2138948268  |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance u   | $\pm 6,9849e-05$ ( $\pm 150000$ LSB) |
| Tolerance v   | $\pm 6,9849e-05$ ( $\pm 150000$ LSB) |
| Tolerance w   | $\pm 6,9849e-05$ ( $\pm 150000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 283 |
| Max CPU cycles  | 288 |
| Avg CPU cycles  | 285 |

**Verification: Sin3Gen FiP32 CPU STM32F072RB**

Date of Test 2026-06-19  
Target controller STM32F072RB

**Test case: Inport test****OK**

Inport test for General block Sin3Gen.

| Test results |            |            |     |             |
|--------------|------------|------------|-----|-------------|
| Time step    | 1          | 2          | ... | 200         |
| CPU cycles   | 789        | 789        | ... | 795         |
| Inputs       |            |            |     |             |
| A (DSP)      | 10737418   | 21474836   | ... | 2147483647  |
| f (DSP)      | 2147483647 | 2147483647 | ... | 2147483647  |
| A            | 0.005      | 0.01       | ... | 1           |
| f            | 1          | 1          | ... | 1           |
| Parameters   |            |            |     |             |
| fmax         | 200        |            |     |             |
| Offset       | 0.13       |            |     |             |
| ts_fact      | 1          |            |     |             |
| Outputs      |            |            |     |             |
| u            | 0.131      | 0.132      | ... | 0.13        |
| v            | 0.125      | 0.12       | ... | -0.736      |
| w            | 0.134      | 0.137      | ... | 0.996       |
| Exp. u       | 0.131      | 0.132      | ... | 0.13        |
| Exp. v       | 0.125      | 0.12       | ... | -0.736      |
| Exp. w       | 0.134      | 0.137      | ... | 0.996       |
| u (DSP)      | 280518584  | 284513150  | ... | 279172924   |
| v (DSP)      | 269274943  | 258489642  | ... | -1580478263 |
| w (DSP)      | 287724911  | 294514926  | ... | 2138823959  |
| Exp. u (DSP) | 280518630  | 284513449  | ... | 279172874   |
| Exp. v (DSP) | 269274444  | 258489116  | ... | -1580602519 |
| Exp. w (DSP) | 287725549  | 294516058  | ... | 2138948268  |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance u   | $\pm 6,9849e-05$ ( $\pm 150000$ LSB) |
| Tolerance v   | $\pm 6,9849e-05$ ( $\pm 150000$ LSB) |
| Tolerance w   | $\pm 6,9849e-05$ ( $\pm 150000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 789 |
| Max CPU cycles  | 862 |
| Avg CPU cycles  | 795 |

**Verification: Sin3Gen FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block Sin3Gen.

| Test results |            |            |     |             |
|--------------|------------|------------|-----|-------------|
| Time step    | 1          | 2          | ... | 200         |
| CPU cycles   | 215        | 215        | ... | 213         |
| Inputs       |            |            |     |             |
| A (DSP)      | 10737418   | 21474836   | ... | 2147483647  |
| f (DSP)      | 2147483647 | 2147483647 | ... | 2147483647  |
| A            | 0.005      | 0.01       | ... | 1           |
| f            | 1          | 1          | ... | 1           |
| Parameters   |            |            |     |             |
| fmax         | 200        |            |     |             |
| Offset       | 0.13       |            |     |             |
| ts_fact      | 1          |            |     |             |
| Outputs      |            |            |     |             |
| u            | 0.131      | 0.132      | ... | 0.13        |
| v            | 0.125      | 0.12       | ... | -0.736      |
| w            | 0.134      | 0.137      | ... | 0.996       |
| Exp. u       | 0.131      | 0.132      | ... | 0.13        |
| Exp. v       | 0.125      | 0.12       | ... | -0.736      |
| Exp. w       | 0.134      | 0.137      | ... | 0.996       |
| u (DSP)      | 280518584  | 284513150  | ... | 279172924   |
| v (DSP)      | 269274943  | 258489642  | ... | -1580478263 |
| w (DSP)      | 287724911  | 294514926  | ... | 2138823959  |
| Exp. u (DSP) | 280518630  | 284513449  | ... | 279172874   |
| Exp. v (DSP) | 269274444  | 258489116  | ... | -1580602519 |
| Exp. w (DSP) | 287725549  | 294516058  | ... | 2138948268  |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance u   | $\pm 6,9849e-05$ ( $\pm 150000$ LSB) |
| Tolerance v   | $\pm 6,9849e-05$ ( $\pm 150000$ LSB) |
| Tolerance w   | $\pm 6,9849e-05$ ( $\pm 150000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 213 |
| Max CPU cycles  | 218 |
| Avg CPU cycles  | 214 |

**Verification: Sin3Gen FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block Sin3Gen.

| Test results |            |            |     |             |
|--------------|------------|------------|-----|-------------|
| Time step    | 1          | 2          | ... | 200         |
| CPU cycles   | 1164       | 1164       | ... | 1164        |
| Inputs       |            |            |     |             |
| A (DSP)      | 10737418   | 21474836   | ... | 2147483647  |
| f (DSP)      | 2147483647 | 2147483647 | ... | 2147483647  |
| A            | 0.005      | 0.01       | ... | 1           |
| f            | 1          | 1          | ... | 1           |
| Parameters   |            |            |     |             |
| fmax         | 200        |            |     |             |
| Offset       | 0.13       |            |     |             |
| ts_fact      | 1          |            |     |             |
| Outputs      |            |            |     |             |
| u            | 0.131      | 0.132      | ... | 0.13        |
| v            | 0.125      | 0.12       | ... | -0.736      |
| w            | 0.134      | 0.137      | ... | 0.996       |
| Exp. u       | 0.131      | 0.132      | ... | 0.13        |
| Exp. v       | 0.125      | 0.12       | ... | -0.736      |
| Exp. w       | 0.134      | 0.137      | ... | 0.996       |
| u (DSP)      | 280518584  | 284513150  | ... | 279172924   |
| v (DSP)      | 269274943  | 258489642  | ... | -1580478263 |
| w (DSP)      | 287724911  | 294514926  | ... | 2138823959  |
| Exp. u (DSP) | 280518630  | 284513449  | ... | 279172874   |
| Exp. v (DSP) | 269274444  | 258489116  | ... | -1580602519 |
| Exp. w (DSP) | 287725549  | 294516058  | ... | 2138948268  |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance u   | $\pm 6,9849e-05$ ( $\pm 150000$ LSB) |
| Tolerance v   | $\pm 6,9849e-05$ ( $\pm 150000$ LSB) |
| Tolerance w   | $\pm 6,9849e-05$ ( $\pm 150000$ LSB) |



| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1157 |
| Max CPU cycles  | 1172 |
| Avg CPU cycles  | 1164 |

**Verification: Sin3Gen FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block Sin3Gen.

| Test results |            |            |     |             |
|--------------|------------|------------|-----|-------------|
| Time step    | 1          | 2          | ... | 200         |
| CPU cycles   | 379        | 297        | ... | 299         |
| Inputs       |            |            |     |             |
| A (DSP)      | 10737418   | 21474836   | ... | 2147483647  |
| f (DSP)      | 2147483647 | 2147483647 | ... | 2147483647  |
| A            | 0.005      | 0.01       | ... | 1           |
| f            | 1          | 1          | ... | 1           |
| Parameters   |            |            |     |             |
| fmax         | 200        |            |     |             |
| Offset       | 0.13       |            |     |             |
| ts_fact      | 1          |            |     |             |
| Outputs      |            |            |     |             |
| u            | 0.131      | 0.132      | ... | 0.13        |
| v            | 0.125      | 0.12       | ... | -0.736      |
| w            | 0.134      | 0.137      | ... | 0.996       |
| Exp. u       | 0.131      | 0.132      | ... | 0.13        |
| Exp. v       | 0.125      | 0.12       | ... | -0.736      |
| Exp. w       | 0.134      | 0.137      | ... | 0.996       |
| u (DSP)      | 280518584  | 284513150  | ... | 279172924   |
| v (DSP)      | 269274943  | 258489642  | ... | -1580478263 |
| w (DSP)      | 287724911  | 294514926  | ... | 2138823959  |
| Exp. u (DSP) | 280518630  | 284513449  | ... | 279172874   |
| Exp. v (DSP) | 269274444  | 258489116  | ... | -1580602519 |
| Exp. w (DSP) | 287725549  | 294516058  | ... | 2138948268  |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance u   | $\pm 6,9849e-05$ ( $\pm 150000$ LSB) |
| Tolerance v   | $\pm 6,9849e-05$ ( $\pm 150000$ LSB) |
| Tolerance w   | $\pm 6,9849e-05$ ( $\pm 150000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 297 |
| Max CPU cycles  | 379 |
| Avg CPU cycles  | 298 |

**Verification: Sin3Gen FiP32 CPU TMS320F28379D**

Date of Test 2026-06-22  
Target controller TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block Sin3Gen.


| Test results |            |            |     |             |
|--------------|------------|------------|-----|-------------|
| Time step    | 1          | 2          | ... | 200         |
| CPU cycles   | 551        | 542        | ... | 547         |
| Inputs       |            |            |     |             |
| A (DSP)      | 10737418   | 21474836   | ... | 2147483647  |
| f (DSP)      | 2147483647 | 2147483647 | ... | 2147483647  |
| A            | 0.005      | 0.01       | ... | 1           |
| f            | 1          | 1          | ... | 1           |
| Parameters   |            |            |     |             |
| fmax         | 200        |            |     |             |
| Offset       | 0.13       |            |     |             |
| ts_fact      | 1          |            |     |             |
| Outputs      |            |            |     |             |
| u            | 0.131      | 0.132      | ... | 0.13        |
| v            | 0.125      | 0.12       | ... | -0.736      |
| w            | 0.134      | 0.137      | ... | 0.996       |
| Exp. u       | 0.131      | 0.132      | ... | 0.13        |
| Exp. v       | 0.125      | 0.12       | ... | -0.736      |
| Exp. w       | 0.134      | 0.137      | ... | 0.996       |
| u (DSP)      | 280518584  | 284513150  | ... | 279172924   |
| v (DSP)      | 269274943  | 258489642  | ... | -1580478263 |
| w (DSP)      | 287724911  | 294514926  | ... | 2138823959  |
| Exp. u (DSP) | 280518630  | 284513449  | ... | 279172874   |
| Exp. v (DSP) | 269274444  | 258489116  | ... | -1580602519 |
| Exp. w (DSP) | 287725549  | 294516058  | ... | 2138948268  |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance u   | $\pm 6,9849e-05$ ( $\pm 150000$ LSB) |
| Tolerance v   | $\pm 6,9849e-05$ ( $\pm 150000$ LSB) |
| Tolerance w   | $\pm 6,9849e-05$ ( $\pm 150000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 496 |
| Max CPU cycles  | 551 |
| Avg CPU cycles  | 543 |

## Block: SinGen

---



Generation of a sine wave with amplitude (A) and frequency (f).

| Inports |           |
|---------|-----------|
| A       | Amplitude |
| f       | Frequency |

| Outputs |                  |
|---------|------------------|
| u       | Sine wave output |

| Mask Parameters |    |                                                                 |
|-----------------|----|-----------------------------------------------------------------|
| Name            | ID | Description                                                     |
| fmax            | 1  | Maximum Frequency in Hz                                         |
| Offset          | 2  | Offset                                                          |
| Phase           | 3  | Phase [-Pi..Pi]                                                 |
| ts_fact         | 4  | Multiplication factor of base sampling time (in integer format) |

### Description:

Calculation fixed point implementation:

$$u_k = A_k \sin(2f_k f_{\max} kT_s + \phi_{\text{phase}}) + A_{\text{offset}}$$

For sine calculation a lookup table with 256 entries is used. This results in a short computation time but with the downside of reduced accuracy for the FiP32 implementation.

Calculation floating point implementation (parameter  $f_{\max}$  is ignored):

$$u_k = A_k \sin(2\pi f_k kT_s + \phi_{\text{phase}}) + A_{\text{offset}}$$

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| A                 | int16 |
| f                 | int16 |

| Outports Data Type |       |
|--------------------|-------|
| u                  | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| A                 | int32 |
| f                 | int32 |

| Outports Data Type |       |
|--------------------|-------|
| u                  | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| A                 | float32 |
| f                 | float32 |

| Outports Data Type |         |
|--------------------|---------|
| u                  | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| A                 | float64 |
| f                 | float64 |

| Outports Data Type |         |
|--------------------|---------|
| u                  | float64 |

**Verification: SinGen FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block SinGen.

| Test results |       |       |       |       |     |       |
|--------------|-------|-------|-------|-------|-----|-------|
| Time step    | 1     | 2     | 3     | 4     | ... | 200   |
| CPU cycles   | 117   | 117   | 117   | 117   | ... | 117   |
| Inputs       |       |       |       |       |     |       |
| A (DSP)      | 164   | 328   | 492   | 655   | ... | 32767 |
| f (DSP)      | 32767 | 32767 | 32767 | 32767 | ... | 32767 |
| A            | 0.005 | 0.01  | 0.015 | 0.02  | ... | 1     |
| f            | 1     | 1     | 1     | 1     | ... | 1     |
| Parameters   |       |       |       |       |     |       |
| fmax         | 200   |       |       |       |     |       |
| Offset       | 0.13  |       |       |       |     |       |
| Phase        | 0     |       |       |       |     |       |
| ts_fact      | 1     |       |       |       |     |       |
| Outputs      |       |       |       |       |     |       |
| u            | 0.131 | 0.133 | 0.136 | 0.14  | ... | 0.135 |
| Exp. u       | 0.131 | 0.132 | 0.136 | 0.14  | ... | 0.13  |
| u (DSP)      | 4281  | 4342  | 4441  | 4576  | ... | 4435  |
| Exp. u (DSP) | 4280  | 4341  | 4441  | 4576  | ... | 4260  |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance u   | $\pm 5,3711e-03$ ( $\pm 176$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 117 |
| Max CPU cycles  | 117 |
| Avg CPU cycles  | 117 |



**Verification: SinGen FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block SinGen.

| Test results |       |       |       |       |     |       |
|--------------|-------|-------|-------|-------|-----|-------|
| Time step    | 1     | 2     | 3     | 4     | ... | 200   |
| CPU cycles   | 87    | 87    | 87    | 87    | ... | 87    |
| Inputs       |       |       |       |       |     |       |
| A (DSP)      | 164   | 328   | 492   | 655   | ... | 32767 |
| f (DSP)      | 32767 | 32767 | 32767 | 32767 | ... | 32767 |
| A            | 0.005 | 0.01  | 0.015 | 0.02  | ... | 1     |
| f            | 1     | 1     | 1     | 1     | ... | 1     |
| Parameters   |       |       |       |       |     |       |
| fmax         | 200   |       |       |       |     |       |
| Offset       | 0.13  |       |       |       |     |       |
| Phase        | 0     |       |       |       |     |       |
| ts_fact      | 1     |       |       |       |     |       |
| Outputs      |       |       |       |       |     |       |
| u            | 0.131 | 0.133 | 0.136 | 0.14  | ... | 0.135 |
| Exp. u       | 0.131 | 0.132 | 0.136 | 0.14  | ... | 0.13  |
| u (DSP)      | 4281  | 4342  | 4441  | 4576  | ... | 4435  |
| Exp. u (DSP) | 4280  | 4341  | 4441  | 4576  | ... | 4260  |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance u   | $\pm 5,3711\text{e-}03$ ( $\pm 176$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 87 |
| Max CPU cycles  | 87 |
| Avg CPU cycles  | 87 |

**Verification: SinGen FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block SinGen.

| Test results |       |       |       |       |     |       |
|--------------|-------|-------|-------|-------|-----|-------|
| Time step    | 1     | 2     | 3     | 4     | ... | 200   |
| CPU cycles   | 136   | 130   | 130   | 130   | ... | 130   |
| Inputs       |       |       |       |       |     |       |
| A (DSP)      | 164   | 328   | 492   | 655   | ... | 32767 |
| f (DSP)      | 32767 | 32767 | 32767 | 32767 | ... | 32767 |
| A            | 0.005 | 0.01  | 0.015 | 0.02  | ... | 1     |
| f            | 1     | 1     | 1     | 1     | ... | 1     |
| Parameters   |       |       |       |       |     |       |
| fmax         | 200   |       |       |       |     |       |
| Offset       | 0.13  |       |       |       |     |       |
| Phase        | 0     |       |       |       |     |       |
| ts_fact      | 1     |       |       |       |     |       |
| Outputs      |       |       |       |       |     |       |
| u            | 0.131 | 0.133 | 0.136 | 0.14  | ... | 0.135 |
| Exp. u       | 0.131 | 0.132 | 0.136 | 0.14  | ... | 0.13  |
| u (DSP)      | 4281  | 4342  | 4441  | 4576  | ... | 4435  |
| Exp. u (DSP) | 4280  | 4341  | 4441  | 4576  | ... | 4260  |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance u   | $\pm 5,3711e-03$ ( $\pm 176$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 130 |
| Max CPU cycles  | 136 |
| Avg CPU cycles  | 131 |

**Verification: SinGen FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block SinGen.

| Test results |       |       |       |       |     |       |
|--------------|-------|-------|-------|-------|-----|-------|
| Time step    | 1     | 2     | 3     | 4     | ... | 200   |
| CPU cycles   | 117   | 117   | 117   | 117   | ... | 117   |
| Inputs       |       |       |       |       |     |       |
| A (DSP)      | 164   | 328   | 492   | 655   | ... | 32767 |
| f (DSP)      | 32767 | 32767 | 32767 | 32767 | ... | 32767 |
| A            | 0.005 | 0.01  | 0.015 | 0.02  | ... | 1     |
| f            | 1     | 1     | 1     | 1     | ... | 1     |
| Parameters   |       |       |       |       |     |       |
| fmax         | 200   |       |       |       |     |       |
| Offset       | 0.13  |       |       |       |     |       |
| Phase        | 0     |       |       |       |     |       |
| ts_fact      | 1     |       |       |       |     |       |
| Outputs      |       |       |       |       |     |       |
| u            | 0.131 | 0.133 | 0.136 | 0.14  | ... | 0.135 |
| Exp. u       | 0.131 | 0.132 | 0.136 | 0.14  | ... | 0.13  |
| u (DSP)      | 4281  | 4342  | 4441  | 4576  | ... | 4435  |
| Exp. u (DSP) | 4280  | 4341  | 4441  | 4576  | ... | 4260  |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance u   | $\pm 5,3711e-03$ ( $\pm 176$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 117 |
| Max CPU cycles  | 117 |
| Avg CPU cycles  | 117 |

**Verification: SinGen FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block SinGen.

| Test results |       |       |       |       |     |       |
|--------------|-------|-------|-------|-------|-----|-------|
| Time step    | 1     | 2     | 3     | 4     | ... | 200   |
| CPU cycles   | 80    | 80    | 80    | 80    | ... | 80    |
| Inputs       |       |       |       |       |     |       |
| A (DSP)      | 164   | 328   | 492   | 655   | ... | 32767 |
| f (DSP)      | 32767 | 32767 | 32767 | 32767 | ... | 32767 |
| A            | 0.005 | 0.01  | 0.015 | 0.02  | ... | 1     |
| f            | 1     | 1     | 1     | 1     | ... | 1     |
| Parameters   |       |       |       |       |     |       |
| fmax         | 200   |       |       |       |     |       |
| Offset       | 0.13  |       |       |       |     |       |
| Phase        | 0     |       |       |       |     |       |
| ts_fact      | 1     |       |       |       |     |       |
| Outputs      |       |       |       |       |     |       |
| u            | 0.131 | 0.133 | 0.136 | 0.14  | ... | 0.135 |
| Exp. u       | 0.131 | 0.132 | 0.136 | 0.14  | ... | 0.13  |
| u (DSP)      | 4281  | 4342  | 4441  | 4576  | ... | 4435  |
| Exp. u (DSP) | 4280  | 4341  | 4441  | 4576  | ... | 4260  |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance u   | $\pm 5,3711e-03$ ( $\pm 176$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 80 |
| Max CPU cycles  | 80 |
| Avg CPU cycles  | 80 |

**Verification: SinGen FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block SinGen.

| Test results |       |       |       |       |     |       |
|--------------|-------|-------|-------|-------|-----|-------|
| Time step    | 1     | 2     | 3     | 4     | ... | 200   |
| CPU cycles   | 108   | 108   | 108   | 108   | ... | 108   |
| Inputs       |       |       |       |       |     |       |
| A (DSP)      | 164   | 328   | 492   | 655   | ... | 32767 |
| f (DSP)      | 32767 | 32767 | 32767 | 32767 | ... | 32767 |
| A            | 0.005 | 0.01  | 0.015 | 0.02  | ... | 1     |
| f            | 1     | 1     | 1     | 1     | ... | 1     |
| Parameters   |       |       |       |       |     |       |
| fmax         | 200   |       |       |       |     |       |
| Offset       | 0.13  |       |       |       |     |       |
| Phase        | 0     |       |       |       |     |       |
| ts_fact      | 1     |       |       |       |     |       |
| Outputs      |       |       |       |       |     |       |
| u            | 0.131 | 0.133 | 0.136 | 0.14  | ... | 0.135 |
| Exp. u       | 0.131 | 0.132 | 0.136 | 0.14  | ... | 0.13  |
| u (DSP)      | 4281  | 4342  | 4441  | 4576  | ... | 4435  |
| Exp. u (DSP) | 4280  | 4341  | 4441  | 4576  | ... | 4260  |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance u   | $\pm 5,3711e-03$ ( $\pm 176$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 108 |
| Max CPU cycles  | 108 |
| Avg CPU cycles  | 108 |

**Verification: SinGen FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block SinGen.

| Test results |       |       |       |       |     |       |
|--------------|-------|-------|-------|-------|-----|-------|
| Time step    | 1     | 2     | 3     | 4     | ... | 200   |
| CPU cycles   | 148   | 123   | 123   | 123   | ... | 123   |
| Inputs       |       |       |       |       |     |       |
| A (DSP)      | 164   | 328   | 492   | 655   | ... | 32767 |
| f (DSP)      | 32767 | 32767 | 32767 | 32767 | ... | 32767 |
| A            | 0.005 | 0.01  | 0.015 | 0.02  | ... | 1     |
| f            | 1     | 1     | 1     | 1     | ... | 1     |
| Parameters   |       |       |       |       |     |       |
| fmax         | 200   |       |       |       |     |       |
| Offset       | 0.13  |       |       |       |     |       |
| Phase        | 0     |       |       |       |     |       |
| ts_fact      | 1     |       |       |       |     |       |
| Outputs      |       |       |       |       |     |       |
| u            | 0.131 | 0.133 | 0.136 | 0.14  | ... | 0.135 |
| Exp. u       | 0.131 | 0.132 | 0.136 | 0.14  | ... | 0.13  |
| u (DSP)      | 4281  | 4342  | 4441  | 4576  | ... | 4435  |
| Exp. u (DSP) | 4280  | 4341  | 4441  | 4576  | ... | 4260  |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance u   | $\pm 5,3711e-03$ ( $\pm 176$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 123 |
| Max CPU cycles  | 148 |
| Avg CPU cycles  | 123 |

**Verification: SinGen FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block SinGen.

| Test results |       |       |       |       |     |       |
|--------------|-------|-------|-------|-------|-----|-------|
| Time step    | 1     | 2     | 3     | 4     | ... | 200   |
| CPU cycles   | 98    | 98    | 98    | 98    | ... | 98    |
| Inputs       |       |       |       |       |     |       |
| A (DSP)      | 164   | 328   | 492   | 655   | ... | 32767 |
| f (DSP)      | 32767 | 32767 | 32767 | 32767 | ... | 32767 |
| A            | 0.005 | 0.01  | 0.015 | 0.02  | ... | 1     |
| f            | 1     | 1     | 1     | 1     | ... | 1     |
| Parameters   |       |       |       |       |     |       |
| fmax         | 200   |       |       |       |     |       |
| Offset       | 0.13  |       |       |       |     |       |
| Phase        | 0     |       |       |       |     |       |
| ts_fact      | 1     |       |       |       |     |       |
| Outputs      |       |       |       |       |     |       |
| u            | 0.131 | 0.133 | 0.136 | 0.14  | ... | 0.135 |
| Exp. u       | 0.131 | 0.132 | 0.136 | 0.14  | ... | 0.13  |
| u (DSP)      | 4281  | 4342  | 4441  | 4576  | ... | 4435  |
| Exp. u (DSP) | 4280  | 4341  | 4441  | 4576  | ... | 4260  |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance u   | $\pm 5,3711e-03$ ( $\pm 176$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 98  |
| Max CPU cycles  | 101 |
| Avg CPU cycles  | 98  |

**Verification: SinGen FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block SinGen.

| Test results |            |            |     |            |
|--------------|------------|------------|-----|------------|
| Time step    | 1          | 2          | ... | 200        |
| CPU cycles   | 244        | 244        | ... | 244        |
| Inputs       |            |            |     |            |
| A (DSP)      | 10737418   | 21474836   | ... | 2147483647 |
| f (DSP)      | 2147483647 | 2147483647 | ... | 2147483647 |
| A            | 0.005      | 0.01       | ... | 1          |
| f            | 1          | 1          | ... | 1          |
| Parameters   |            |            |     |            |
| fmax         | 200        |            |     |            |
| Offset       | 0.13       |            |     |            |
| Phase        | 0          |            |     |            |
| ts_fact      | 1          |            |     |            |
| Outputs      |            |            |     |            |
| u            | 0.131      | 0.132      | ... | 0.13       |
| Exp. u       | 0.131      | 0.132      | ... | 0.13       |
| u (DSP)      | 280518584  | 284513150  | ... | 279172924  |
| Exp. u (DSP) | 280518630  | 284513449  | ... | 279172874  |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance u   | $\pm 6,9849e-05$ ( $\pm 150000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 244 |
| Max CPU cycles  | 244 |
| Avg CPU cycles  | 244 |



**Verification: SinGen FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block SinGen.

| Test results |            |            |     |            |
|--------------|------------|------------|-----|------------|
| Time step    | 1          | 2          | ... | 200        |
| CPU cycles   | 97         | 97         | ... | 97         |
| Inputs       |            |            |     |            |
| A (DSP)      | 10737418   | 21474836   | ... | 2147483647 |
| f (DSP)      | 2147483647 | 2147483647 | ... | 2147483647 |
| A            | 0.005      | 0.01       | ... | 1          |
| f            | 1          | 1          | ... | 1          |
| Parameters   |            |            |     |            |
| fmax         | 200        |            |     |            |
| Offset       | 0.13       |            |     |            |
| Phase        | 0          |            |     |            |
| ts_fact      | 1          |            |     |            |
| Outputs      |            |            |     |            |
| u            | 0.131      | 0.132      | ... | 0.13       |
| Exp. u       | 0.131      | 0.132      | ... | 0.13       |
| u (DSP)      | 280518584  | 284513150  | ... | 279172924  |
| Exp. u (DSP) | 280518630  | 284513449  | ... | 279172874  |

| Test settings |                                             |
|---------------|---------------------------------------------|
| Tolerance u   | $\pm 6,9849\text{e-}05$ ( $\pm 150000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 97 |
| Max CPU cycles  | 97 |
| Avg CPU cycles  | 97 |

**Verification: SinGen FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block SinGen.

| Test results |            |            |     |            |
|--------------|------------|------------|-----|------------|
| Time step    | 1          | 2          | ... | 200        |
| CPU cycles   | 159        | 154        | ... | 154        |
| Inputs       |            |            |     |            |
| A (DSP)      | 10737418   | 21474836   | ... | 2147483647 |
| f (DSP)      | 2147483647 | 2147483647 | ... | 2147483647 |
| A            | 0.005      | 0.01       | ... | 1          |
| f            | 1          | 1          | ... | 1          |
| Parameters   |            |            |     |            |
| fmax         | 200        |            |     |            |
| Offset       | 0.13       |            |     |            |
| Phase        | 0          |            |     |            |
| ts_fact      | 1          |            |     |            |
| Outputs      |            |            |     |            |
| u            | 0.131      | 0.132      | ... | 0.13       |
| Exp. u       | 0.131      | 0.132      | ... | 0.13       |
| u (DSP)      | 280518584  | 284513150  | ... | 279172924  |
| Exp. u (DSP) | 280518630  | 284513449  | ... | 279172874  |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance u   | $\pm 6,9849e-05$ ( $\pm 150000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 154 |
| Max CPU cycles  | 159 |
| Avg CPU cycles  | 156 |

**Verification: SinGen FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block SinGen.

| Test results |            |            |     |            |
|--------------|------------|------------|-----|------------|
| Time step    | 1          | 2          | ... | 200        |
| CPU cycles   | 343        | 343        | ... | 343        |
| Inputs       |            |            |     |            |
| A (DSP)      | 10737418   | 21474836   | ... | 2147483647 |
| f (DSP)      | 2147483647 | 2147483647 | ... | 2147483647 |
| A            | 0.005      | 0.01       | ... | 1          |
| f            | 1          | 1          | ... | 1          |
| Parameters   |            |            |     |            |
| fmax         | 200        |            |     |            |
| Offset       | 0.13       |            |     |            |
| Phase        | 0          |            |     |            |
| ts_fact      | 1          |            |     |            |
| Outputs      |            |            |     |            |
| u            | 0.131      | 0.132      | ... | 0.13       |
| Exp. u       | 0.131      | 0.132      | ... | 0.13       |
| u (DSP)      | 280518584  | 284513150  | ... | 279172924  |
| Exp. u (DSP) | 280518630  | 284513449  | ... | 279172874  |

| Test settings |                                             |
|---------------|---------------------------------------------|
| Tolerance u   | $\pm 6,9849\text{e-}05$ ( $\pm 150000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 343 |
| Max CPU cycles  | 402 |
| Avg CPU cycles  | 344 |

**Verification: SinGen FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block SinGen.

| Test results |            |            |     |            |
|--------------|------------|------------|-----|------------|
| Time step    | 1          | 2          | ... | 200        |
| CPU cycles   | 107        | 107        | ... | 105        |
| Inputs       |            |            |     |            |
| A (DSP)      | 10737418   | 21474836   | ... | 2147483647 |
| f (DSP)      | 2147483647 | 2147483647 | ... | 2147483647 |
| A            | 0.005      | 0.01       | ... | 1          |
| f            | 1          | 1          | ... | 1          |
| Parameters   |            |            |     |            |
| fmax         | 200        |            |     |            |
| Offset       | 0.13       |            |     |            |
| Phase        | 0          |            |     |            |
| ts_fact      | 1          |            |     |            |
| Outputs      |            |            |     |            |
| u            | 0.131      | 0.132      | ... | 0.13       |
| Exp. u       | 0.131      | 0.132      | ... | 0.13       |
| u (DSP)      | 280518584  | 284513150  | ... | 279172924  |
| Exp. u (DSP) | 280518630  | 284513449  | ... | 279172874  |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance u   | $\pm 6,9849e-05$ ( $\pm 150000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 105 |
| Max CPU cycles  | 108 |
| Avg CPU cycles  | 107 |

**Verification: SinGen FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block SinGen.

| Test results |            |            |     |            |
|--------------|------------|------------|-----|------------|
| Time step    | 1          | 2          | ... | 200        |
| CPU cycles   | 482        | 482        | ... | 482        |
| Inputs       |            |            |     |            |
| A (DSP)      | 10737418   | 21474836   | ... | 2147483647 |
| f (DSP)      | 2147483647 | 2147483647 | ... | 2147483647 |
| A            | 0.005      | 0.01       | ... | 1          |
| f            | 1          | 1          | ... | 1          |
| Parameters   |            |            |     |            |
| fmax         | 200        |            |     |            |
| Offset       | 0.13       |            |     |            |
| Phase        | 0          |            |     |            |
| ts_fact      | 1          |            |     |            |
| Outputs      |            |            |     |            |
| u            | 0.131      | 0.132      | ... | 0.13       |
| Exp. u       | 0.131      | 0.132      | ... | 0.13       |
| u (DSP)      | 280518584  | 284513150  | ... | 279172924  |
| Exp. u (DSP) | 280518630  | 284513449  | ... | 279172874  |

| Test settings |                                             |
|---------------|---------------------------------------------|
| Tolerance u   | $\pm 6,9849\text{e-}05$ ( $\pm 150000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 482 |
| Max CPU cycles  | 496 |
| Avg CPU cycles  | 489 |

**Verification: SinGen FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block SinGen.

| Test results |            |            |     |            |
|--------------|------------|------------|-----|------------|
| Time step    | 1          | 2          | ... | 200        |
| CPU cycles   | 190        | 155        | ... | 155        |
| Inputs       |            |            |     |            |
| A (DSP)      | 10737418   | 21474836   | ... | 2147483647 |
| f (DSP)      | 2147483647 | 2147483647 | ... | 2147483647 |
| A            | 0.005      | 0.01       | ... | 1          |
| f            | 1          | 1          | ... | 1          |
| Parameters   |            |            |     |            |
| fmax         | 200        |            |     |            |
| Offset       | 0.13       |            |     |            |
| Phase        | 0          |            |     |            |
| ts_fact      | 1          |            |     |            |
| Outputs      |            |            |     |            |
| u            | 0.131      | 0.132      | ... | 0.13       |
| Exp. u       | 0.131      | 0.132      | ... | 0.13       |
| u (DSP)      | 280518584  | 284513150  | ... | 279172924  |
| Exp. u (DSP) | 280518630  | 284513449  | ... | 279172874  |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance u   | $\pm 6,9849e-05$ ( $\pm 150000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 155 |
| Max CPU cycles  | 190 |
| Avg CPU cycles  | 155 |

**Verification: SinGen FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**


Inport test for General block SinGen.

| Test results |            |            |     |            |
|--------------|------------|------------|-----|------------|
| Time step    | 1          | 2          | ... | 200        |
| CPU cycles   | 212        | 208        | ... | 208        |
| Inputs       |            |            |     |            |
| A (DSP)      | 10737418   | 21474836   | ... | 2147483647 |
| f (DSP)      | 2147483647 | 2147483647 | ... | 2147483647 |
| A            | 0.005      | 0.01       | ... | 1          |
| f            | 1          | 1          | ... | 1          |
| Parameters   |            |            |     |            |
| fmax         | 200        |            |     |            |
| Offset       | 0.13       |            |     |            |
| Phase        | 0          |            |     |            |
| ts_fact      | 1          |            |     |            |
| Outputs      |            |            |     |            |
| u            | 0.131      | 0.132      | ... | 0.13       |
| Exp. u       | 0.131      | 0.132      | ... | 0.13       |
| u (DSP)      | 280518584  | 284513150  | ... | 279172924  |
| Exp. u (DSP) | 280518630  | 284513449  | ... | 279172874  |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance u   | $\pm 6,9849e-05$ ( $\pm 150000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 208 |
| Max CPU cycles  | 212 |
| Avg CPU cycles  | 208 |

## Block: TypeConv



Data Type Conversion

| Inports |  |
|---------|--|
| In      |  |

| Outports |  |
|----------|--|
| Out      |  |

### Implementations:

|                   |                                              |
|-------------------|----------------------------------------------|
| <b>FiP8_16</b>    | 8 to 16 Bit Fixed Point Implementation       |
| <b>FiP8_32</b>    | 8 to 32 Bit Fixed Point Implementation       |
| <b>FiP16_8</b>    | 16 to 8 Bit Fixed Point Implementation       |
| <b>FiP16_32</b>   | 16 to 32 Bit Fixed Point Implementation      |
| <b>FiP32_8</b>    | 32 to 8 Bit Fixed Point Implementation       |
| <b>FiP32_16</b>   | 32 to 16 Bit Fixed Point Implementation      |
| <b>Bool_FiP16</b> | Boolean to 16 Bit Fixed Point Implementation |
| <b>Bool_FiP32</b> | Boolean to 32 Bit Fixed Point Implementation |
| <b>FiP16_Bool</b> | 16 Bit Fixed Point to Boolean Implementation |
| <b>FiP32_Bool</b> | 32 Bit Fixed Point to Boolean Implementation |

### Implementation: FiP8\_16

8 to 16 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | int8 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP8\_32

8 to 32 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | int8 |



| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: FiP16\_8

16 to 8 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16\_32

16 to 32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: FiP32\_8

32 to 8 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP32\_16

32 to 16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: Bool\_FiP16

Boolean to 16 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | bool |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: Bool\_FiP32

Boolean to 32 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | bool |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: FiP16\_Bool

16 Bit Fixed Point to Boolean Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |

| Outports Data Type |      |
|--------------------|------|
| Out                | bool |

### Implementation: FiP32\_Bool

32 Bit Fixed Point to Boolean Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |      |
|--------------------|------|
| Out                | bool |

**Verification: TypeConv FiP8\_16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |       |       |       |     |        |
|-----------------------|----|-------|-------|-------|-----|--------|
| <b>Time step</b>      | 1  | 2     | 3     | 4     | ... | 8      |
| <b>CPU cycles</b>     | 56 | 56    | 56    | 56    | ... | 56     |
| <i>Inputs</i>         |    |       |       |       |     |        |
| <b>In (DSP)</b>       | 0  | 26    | 64    | 127   | ... | -127   |
| <b>In</b>             | 0  | 0.2   | 0.5   | 0.992 | ... | -0.992 |
| <i>Outputs</i>        |    |       |       |       |     |        |
| <b>Out</b>            | 0  | 0.203 | 0.5   | 0.992 | ... | -0.992 |
| <b>Exp. Out</b>       | 0  | 0.2   | 0.5   | 0.992 | ... | -0.992 |
| <b>Out (DSP)</b>      | 0  | 6656  | 16384 | 32512 | ... | -32512 |
| <b>Exp. Out (DSP)</b> | 0  | 6553  | 16384 | 32512 | ... | -32512 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 256$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 56 |
| Avg CPU cycles  | 56 |

## Verification: TypeConv FiP8\_16 CPU TM4C123GH6

Date of Test 2026-06-19  
Target controller TM4C123GH6

### Test case: Inport test

OK

Inport test for General block TypeConv.

| Test results   |    |       |       |       |     |        |
|----------------|----|-------|-------|-------|-----|--------|
| Time step      | 1  | 2     | 3     | 4     | ... | 8      |
| CPU cycles     | 25 | 25    | 25    | 25    | ... | 25     |
| Inputs         |    |       |       |       |     |        |
| In (DSP)       | 0  | 26    | 64    | 127   | ... | -127   |
| In             | 0  | 0.2   | 0.5   | 0.992 | ... | -0.992 |
| Outputs        |    |       |       |       |     |        |
| Out            | 0  | 0.203 | 0.5   | 0.992 | ... | -0.992 |
| Exp. Out       | 0  | 0.2   | 0.5   | 0.992 | ... | -0.992 |
| Out (DSP)      | 0  | 6656  | 16384 | 32512 | ... | -32512 |
| Exp. Out (DSP) | 0  | 6553  | 16384 | 32512 | ... | -32512 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 256$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 25 |
| Max CPU cycles  | 25 |
| Avg CPU cycles  | 25 |

## Verification: TypeConv FiP8\_16 CPU STM32G474RE

Date of Test 2026-06-19  
Target controller STM32G474RE

### Test case: Inport test

OK

Inport test for General block TypeConv.

| Test results   |    |       |       |       |     |        |
|----------------|----|-------|-------|-------|-----|--------|
| Time step      | 1  | 2     | 3     | 4     | ... | 8      |
| CPU cycles     | 57 | 57    | 57    | 57    | ... | 57     |
| Inputs         |    |       |       |       |     |        |
| In (DSP)       | 0  | 26    | 64    | 127   | ... | -127   |
| In             | 0  | 0.2   | 0.5   | 0.992 | ... | -0.992 |
| Outputs        |    |       |       |       |     |        |
| Out            | 0  | 0.203 | 0.5   | 0.992 | ... | -0.992 |
| Exp. Out       | 0  | 0.2   | 0.5   | 0.992 | ... | -0.992 |
| Out (DSP)      | 0  | 6656  | 16384 | 32512 | ... | -32512 |
| Exp. Out (DSP) | 0  | 6553  | 16384 | 32512 | ... | -32512 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 256$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 57 |

**Verification: TypeConv FiP8\_16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |       |       |       |     |        |
|-----------------------|----|-------|-------|-------|-----|--------|
| <b>Time step</b>      | 1  | 2     | 3     | 4     | ... | 8      |
| <b>CPU cycles</b>     | 48 | 48    | 48    | 48    | ... | 48     |
| <i>Inputs</i>         |    |       |       |       |     |        |
| <b>In (DSP)</b>       | 0  | 26    | 64    | 127   | ... | -127   |
| <b>In</b>             | 0  | 0.2   | 0.5   | 0.992 | ... | -0.992 |
| <i>Outputs</i>        |    |       |       |       |     |        |
| <b>Out</b>            | 0  | 0.203 | 0.5   | 0.992 | ... | -0.992 |
| <b>Exp. Out</b>       | 0  | 0.2   | 0.5   | 0.992 | ... | -0.992 |
| <b>Out (DSP)</b>      | 0  | 6656  | 16384 | 32512 | ... | -32512 |
| <b>Exp. Out (DSP)</b> | 0  | 6553  | 16384 | 32512 | ... | -32512 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 256$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 48 |
| Max CPU cycles  | 48 |
| Avg CPU cycles  | 48 |

**Verification: TypeConv FiP8\_16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |       |       |       |     |        |
|-----------------------|----|-------|-------|-------|-----|--------|
| <b>Time step</b>      | 1  | 2     | 3     | 4     | ... | 8      |
| <b>CPU cycles</b>     | 29 | 29    | 29    | 29    | ... | 29     |
| <i>Inputs</i>         |    |       |       |       |     |        |
| <b>In (DSP)</b>       | 0  | 26    | 64    | 127   | ... | -127   |
| <b>In</b>             | 0  | 0.2   | 0.5   | 0.992 | ... | -0.992 |
| <i>Outputs</i>        |    |       |       |       |     |        |
| <b>Out</b>            | 0  | 0.203 | 0.5   | 0.992 | ... | -0.992 |
| <b>Exp. Out</b>       | 0  | 0.2   | 0.5   | 0.992 | ... | -0.992 |
| <b>Out (DSP)</b>      | 0  | 6656  | 16384 | 32512 | ... | -32512 |
| <b>Exp. Out (DSP)</b> | 0  | 6553  | 16384 | 32512 | ... | -32512 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 256$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 29 |
| Avg CPU cycles  | 29 |



**Verification: TypeConv FiP8\_16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |       |       |       |     |        |
|-----------------------|----|-------|-------|-------|-----|--------|
| <b>Time step</b>      | 1  | 2     | 3     | 4     | ... | 8      |
| <b>CPU cycles</b>     | 42 | 42    | 42    | 42    | ... | 42     |
| <i>Inputs</i>         |    |       |       |       |     |        |
| <b>In (DSP)</b>       | 0  | 26    | 64    | 127   | ... | -127   |
| <b>In</b>             | 0  | 0.2   | 0.5   | 0.992 | ... | -0.992 |
| <i>Outputs</i>        |    |       |       |       |     |        |
| <b>Out</b>            | 0  | 0.203 | 0.5   | 0.992 | ... | -0.992 |
| <b>Exp. Out</b>       | 0  | 0.2   | 0.5   | 0.992 | ... | -0.992 |
| <b>Out (DSP)</b>      | 0  | 6656  | 16384 | 32512 | ... | -32512 |
| <b>Exp. Out (DSP)</b> | 0  | 6553  | 16384 | 32512 | ... | -32512 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 256$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 42 |
| Max CPU cycles  | 42 |
| Avg CPU cycles  | 42 |

**Verification: TypeConv FiP8\_16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |       |       |       |     |        |
|-----------------------|----|-------|-------|-------|-----|--------|
| <b>Time step</b>      | 1  | 2     | 3     | 4     | ... | 8      |
| <b>CPU cycles</b>     | 66 | 56    | 56    | 56    | ... | 56     |
| <i>Inputs</i>         |    |       |       |       |     |        |
| <b>In (DSP)</b>       | 0  | 26    | 64    | 127   | ... | -127   |
| <b>In</b>             | 0  | 0.2   | 0.5   | 0.992 | ... | -0.992 |
| <i>Outputs</i>        |    |       |       |       |     |        |
| <b>Out</b>            | 0  | 0.203 | 0.5   | 0.992 | ... | -0.992 |
| <b>Exp. Out</b>       | 0  | 0.2   | 0.5   | 0.992 | ... | -0.992 |
| <b>Out (DSP)</b>      | 0  | 6656  | 16384 | 32512 | ... | -32512 |
| <b>Exp. Out (DSP)</b> | 0  | 6553  | 16384 | 32512 | ... | -32512 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 256$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 66 |
| Avg CPU cycles  | 57 |

**Verification: TypeConv FiP8\_16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |       |       |       |     |        |
|-----------------------|----|-------|-------|-------|-----|--------|
| <b>Time step</b>      | 1  | 2     | 3     | 4     | ... | 8      |
| <b>CPU cycles</b>     | 39 | 39    | 39    | 39    | ... | 39     |
| <i>Inputs</i>         |    |       |       |       |     |        |
| <b>In (DSP)</b>       | 0  | 26    | 64    | 127   | ... | -127   |
| <b>In</b>             | 0  | 0.2   | 0.5   | 0.992 | ... | -0.992 |
| <i>Outputs</i>        |    |       |       |       |     |        |
| <b>Out</b>            | 0  | 0.203 | 0.5   | 0.992 | ... | -0.992 |
| <b>Exp. Out</b>       | 0  | 0.2   | 0.5   | 0.992 | ... | -0.992 |
| <b>Out (DSP)</b>      | 0  | 6656  | 16384 | 32512 | ... | -32512 |
| <b>Exp. Out (DSP)</b> | 0  | 6553  | 16384 | 32512 | ... | -32512 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 256$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 39 |
| Max CPU cycles  | 39 |
| Avg CPU cycles  | 39 |

**Verification: TypeConv FiP8\_32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |             |
|-----------------------|----|-----------|-----|-------------|
| <b>Time step</b>      | 1  | 2         | ... | 8           |
| <b>CPU cycles</b>     | 57 | 57        | ... | 57          |
| <i>Inputs</i>         |    |           |     |             |
| <b>In (DSP)</b>       | 0  | 26        | ... | -127        |
| <b>In</b>             | 0  | 0.2       | ... | -0.992      |
| <i>Outputs</i>        |    |           |     |             |
| <b>Out</b>            | 0  | 0.203     | ... | -0.992      |
| <b>Exp. Out</b>       | 0  | 0.2       | ... | -0.992      |
| <b>Out (DSP)</b>      | 0  | 436207616 | ... | -2130706432 |
| <b>Exp. Out (DSP)</b> | 0  | 429496729 | ... | -2130706432 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 16777216$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 57 |

## Verification: TypeConv FiP8\_32 CPU TM4C123GH6

Date of Test 2026-06-19  
Target controller TM4C123GH6

### Test case: Inport test

OK

Inport test for General block TypeConv.

| Test results   |    |           |     |             |
|----------------|----|-----------|-----|-------------|
| Time step      | 1  | 2         | ... | 8           |
| CPU cycles     | 25 | 25        | ... | 25          |
| Inputs         |    |           |     |             |
| In (DSP)       | 0  | 26        | ... | -127        |
| In             | 0  | 0.2       | ... | -0.992      |
| Outputs        |    |           |     |             |
| Out            | 0  | 0.203     | ... | -0.992      |
| Exp. Out       | 0  | 0.2       | ... | -0.992      |
| Out (DSP)      | 0  | 436207616 | ... | -2130706432 |
| Exp. Out (DSP) | 0  | 429496729 | ... | -2130706432 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 16777216$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 25 |
| Max CPU cycles  | 25 |
| Avg CPU cycles  | 25 |

**Verification: TypeConv FiP8\_32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |             |
|-----------------------|----|-----------|-----|-------------|
| <b>Time step</b>      | 1  | 2         | ... | 8           |
| <b>CPU cycles</b>     | 57 | 57        | ... | 57          |
| <i>Inputs</i>         |    |           |     |             |
| <b>In (DSP)</b>       | 0  | 26        | ... | -127        |
| <b>In</b>             | 0  | 0.2       | ... | -0.992      |
| <i>Outputs</i>        |    |           |     |             |
| <b>Out</b>            | 0  | 0.203     | ... | -0.992      |
| <b>Exp. Out</b>       | 0  | 0.2       | ... | -0.992      |
| <b>Out (DSP)</b>      | 0  | 436207616 | ... | -2130706432 |
| <b>Exp. Out (DSP)</b> | 0  | 429496729 | ... | -2130706432 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 16777216$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 57 |

**Verification: TypeConv FiP8\_32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |             |
|-----------------------|----|-----------|-----|-------------|
| <b>Time step</b>      | 1  | 2         | ... | 8           |
| <b>CPU cycles</b>     | 48 | 48        | ... | 48          |
| <i>Inputs</i>         |    |           |     |             |
| <b>In (DSP)</b>       | 0  | 26        | ... | -127        |
| <b>In</b>             | 0  | 0.2       | ... | -0.992      |
| <i>Outputs</i>        |    |           |     |             |
| <b>Out</b>            | 0  | 0.203     | ... | -0.992      |
| <b>Exp. Out</b>       | 0  | 0.2       | ... | -0.992      |
| <b>Out (DSP)</b>      | 0  | 436207616 | ... | -2130706432 |
| <b>Exp. Out (DSP)</b> | 0  | 429496729 | ... | -2130706432 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 16777216$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 48 |
| Max CPU cycles  | 48 |
| Avg CPU cycles  | 48 |

**Verification: TypeConv FiP8\_32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |             |
|-----------------------|----|-----------|-----|-------------|
| <b>Time step</b>      | 1  | 2         | ... | 8           |
| <b>CPU cycles</b>     | 29 | 29        | ... | 29          |
| <i>Inputs</i>         |    |           |     |             |
| <b>In (DSP)</b>       | 0  | 26        | ... | -127        |
| <b>In</b>             | 0  | 0.2       | ... | -0.992      |
| <i>Outputs</i>        |    |           |     |             |
| <b>Out</b>            | 0  | 0.203     | ... | -0.992      |
| <b>Exp. Out</b>       | 0  | 0.2       | ... | -0.992      |
| <b>Out (DSP)</b>      | 0  | 436207616 | ... | -2130706432 |
| <b>Exp. Out (DSP)</b> | 0  | 429496729 | ... | -2130706432 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 16777216$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 29 |
| Avg CPU cycles  | 29 |



**Verification: TypeConv FiP8\_32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |             |
|-----------------------|----|-----------|-----|-------------|
| <b>Time step</b>      | 1  | 2         | ... | 8           |
| <b>CPU cycles</b>     | 45 | 45        | ... | 45          |
| <i>Inputs</i>         |    |           |     |             |
| <b>In (DSP)</b>       | 0  | 26        | ... | -127        |
| <b>In</b>             | 0  | 0.2       | ... | -0.992      |
| <i>Outputs</i>        |    |           |     |             |
| <b>Out</b>            | 0  | 0.203     | ... | -0.992      |
| <b>Exp. Out</b>       | 0  | 0.2       | ... | -0.992      |
| <b>Out (DSP)</b>      | 0  | 436207616 | ... | -2130706432 |
| <b>Exp. Out (DSP)</b> | 0  | 429496729 | ... | -2130706432 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 16777216$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 45 |
| Max CPU cycles  | 45 |
| Avg CPU cycles  | 45 |

**Verification: TypeConv FiP8\_32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |             |
|-----------------------|----|-----------|-----|-------------|
| <b>Time step</b>      | 1  | 2         | ... | 8           |
| <b>CPU cycles</b>     | 56 | 56        | ... | 56          |
| <i>Inputs</i>         |    |           |     |             |
| <b>In (DSP)</b>       | 0  | 26        | ... | -127        |
| <b>In</b>             | 0  | 0.2       | ... | -0.992      |
| <i>Outputs</i>        |    |           |     |             |
| <b>Out</b>            | 0  | 0.203     | ... | -0.992      |
| <b>Exp. Out</b>       | 0  | 0.2       | ... | -0.992      |
| <b>Out (DSP)</b>      | 0  | 436207616 | ... | -2130706432 |
| <b>Exp. Out (DSP)</b> | 0  | 429496729 | ... | -2130706432 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 16777216$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 56 |
| Avg CPU cycles  | 56 |

**Verification: TypeConv FiP8\_32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |             |
|-----------------------|----|-----------|-----|-------------|
| <b>Time step</b>      | 1  | 2         | ... | 8           |
| <b>CPU cycles</b>     | 38 | 38        | ... | 38          |
| <i>Inputs</i>         |    |           |     |             |
| <b>In (DSP)</b>       | 0  | 26        | ... | -127        |
| <b>In</b>             | 0  | 0.2       | ... | -0.992      |
| <i>Outputs</i>        |    |           |     |             |
| <b>Out</b>            | 0  | 0.203     | ... | -0.992      |
| <b>Exp. Out</b>       | 0  | 0.2       | ... | -0.992      |
| <b>Out (DSP)</b>      | 0  | 436207616 | ... | -2130706432 |
| <b>Exp. Out (DSP)</b> | 0  | 429496729 | ... | -2130706432 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 7,8125e-03$ ( $\pm 16777216$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 38 |
| Max CPU cycles  | 38 |
| Avg CPU cycles  | 38 |

**Verification: TypeConv FiP16\_8 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |       |       |       |     |        |
|-----------------------|----|-------|-------|-------|-----|--------|
| <b>Time step</b>      | 1  | 2     | 3     | 4     | ... | 8      |
| <b>CPU cycles</b>     | 62 | 62    | 62    | 62    | ... | 65     |
| <i>Inputs</i>         |    |       |       |       |     |        |
| <b>In (DSP)</b>       | 0  | 6554  | 16384 | 32767 | ... | -32768 |
| <b>In</b>             | 0  | 0.2   | 0.5   | 1     | ... | -1     |
| <i>Outputs</i>        |    |       |       |       |     |        |
| <b>Out</b>            | 0  | 0.195 | 0.5   | 0.992 | ... | -0.992 |
| <b>Exp. Out</b>       | 0  | 0.195 | 0.5   | 0.992 | ... | -0.992 |
| <b>Out (DSP)</b>      | 0  | 25    | 64    | 127   | ... | -127   |
| <b>Exp. Out (DSP)</b> | 0  | 25    | 64    | 127   | ... | -127   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 65 |
| Avg CPU cycles  | 62 |

**Verification: TypeConv FiP16\_8 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |       |       |       |     |        |
|-----------------------|----|-------|-------|-------|-----|--------|
| <b>Time step</b>      | 1  | 2     | 3     | 4     | ... | 8      |
| <b>CPU cycles</b>     | 29 | 29    | 29    | 29    | ... | 29     |
| <i>Inputs</i>         |    |       |       |       |     |        |
| <b>In (DSP)</b>       | 0  | 6554  | 16384 | 32767 | ... | -32768 |
| <b>In</b>             | 0  | 0.2   | 0.5   | 1     | ... | -1     |
| <i>Outputs</i>        |    |       |       |       |     |        |
| <b>Out</b>            | 0  | 0.195 | 0.5   | 0.992 | ... | -0.992 |
| <b>Exp. Out</b>       | 0  | 0.195 | 0.5   | 0.992 | ... | -0.992 |
| <b>Out (DSP)</b>      | 0  | 25    | 64    | 127   | ... | -127   |
| <b>Exp. Out (DSP)</b> | 0  | 25    | 64    | 127   | ... | -127   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 29 |
| Avg CPU cycles  | 29 |

**Verification: TypeConv FiP16\_8 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |       |       |       |     |        |
|-----------------------|----|-------|-------|-------|-----|--------|
| <b>Time step</b>      | 1  | 2     | 3     | 4     | ... | 8      |
| <b>CPU cycles</b>     | 62 | 62    | 62    | 62    | ... | 62     |
| <i>Inputs</i>         |    |       |       |       |     |        |
| <b>In (DSP)</b>       | 0  | 6554  | 16384 | 32767 | ... | -32768 |
| <b>In</b>             | 0  | 0.2   | 0.5   | 1     | ... | -1     |
| <i>Outputs</i>        |    |       |       |       |     |        |
| <b>Out</b>            | 0  | 0.195 | 0.5   | 0.992 | ... | -0.992 |
| <b>Exp. Out</b>       | 0  | 0.195 | 0.5   | 0.992 | ... | -0.992 |
| <b>Out (DSP)</b>      | 0  | 25    | 64    | 127   | ... | -127   |
| <b>Exp. Out (DSP)</b> | 0  | 25    | 64    | 127   | ... | -127   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 62 |
| Avg CPU cycles  | 62 |

**Verification: TypeConv FiP16\_8 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |       |       |       |     |        |
|-----------------------|----|-------|-------|-------|-----|--------|
| <b>Time step</b>      | 1  | 2     | 3     | 4     | ... | 8      |
| <b>CPU cycles</b>     | 53 | 53    | 53    | 53    | ... | 60     |
| <i>Inputs</i>         |    |       |       |       |     |        |
| <b>In (DSP)</b>       | 0  | 6554  | 16384 | 32767 | ... | -32768 |
| <b>In</b>             | 0  | 0.2   | 0.5   | 1     | ... | -1     |
| <i>Outputs</i>        |    |       |       |       |     |        |
| <b>Out</b>            | 0  | 0.195 | 0.5   | 0.992 | ... | -0.992 |
| <b>Exp. Out</b>       | 0  | 0.195 | 0.5   | 0.992 | ... | -0.992 |
| <b>Out (DSP)</b>      | 0  | 25    | 64    | 127   | ... | -127   |
| <b>Exp. Out (DSP)</b> | 0  | 25    | 64    | 127   | ... | -127   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 53 |
| Max CPU cycles  | 60 |
| Avg CPU cycles  | 54 |

**Verification: TypeConv FiP16\_8 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |       |       |       |     |        |
|-----------------------|----|-------|-------|-------|-----|--------|
| <b>Time step</b>      | 1  | 2     | 3     | 4     | ... | 8      |
| <b>CPU cycles</b>     | 31 | 31    | 31    | 31    | ... | 31     |
| <i>Inputs</i>         |    |       |       |       |     |        |
| <b>In (DSP)</b>       | 0  | 6554  | 16384 | 32767 | ... | -32768 |
| <b>In</b>             | 0  | 0.2   | 0.5   | 1     | ... | -1     |
| <i>Outputs</i>        |    |       |       |       |     |        |
| <b>Out</b>            | 0  | 0.195 | 0.5   | 0.992 | ... | -0.992 |
| <b>Exp. Out</b>       | 0  | 0.195 | 0.5   | 0.992 | ... | -0.992 |
| <b>Out (DSP)</b>      | 0  | 25    | 64    | 127   | ... | -127   |
| <b>Exp. Out (DSP)</b> | 0  | 25    | 64    | 127   | ... | -127   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 31 |
| Avg CPU cycles  | 31 |



**Verification: TypeConv FiP16\_8 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |       |       |       |     |        |
|-----------------------|----|-------|-------|-------|-----|--------|
| <b>Time step</b>      | 1  | 2     | 3     | 4     | ... | 8      |
| <b>CPU cycles</b>     | 45 | 45    | 45    | 45    | ... | 48     |
| <i>Inputs</i>         |    |       |       |       |     |        |
| <b>In (DSP)</b>       | 0  | 6554  | 16384 | 32767 | ... | -32768 |
| <b>In</b>             | 0  | 0.2   | 0.5   | 1     | ... | -1     |
| <i>Outputs</i>        |    |       |       |       |     |        |
| <b>Out</b>            | 0  | 0.195 | 0.5   | 0.992 | ... | -0.992 |
| <b>Exp. Out</b>       | 0  | 0.195 | 0.5   | 0.992 | ... | -0.992 |
| <b>Out (DSP)</b>      | 0  | 25    | 64    | 127   | ... | -127   |
| <b>Exp. Out (DSP)</b> | 0  | 25    | 64    | 127   | ... | -127   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 45 |
| Max CPU cycles  | 48 |
| Avg CPU cycles  | 45 |

**Verification: TypeConv FiP16\_8 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |       |       |       |     |        |
|-----------------------|----|-------|-------|-------|-----|--------|
| <b>Time step</b>      | 1  | 2     | 3     | 4     | ... | 8      |
| <b>CPU cycles</b>     | 69 | 59    | 59    | 59    | ... | 59     |
| <i>Inputs</i>         |    |       |       |       |     |        |
| <b>In (DSP)</b>       | 0  | 6554  | 16384 | 32767 | ... | -32768 |
| <b>In</b>             | 0  | 0.2   | 0.5   | 1     | ... | -1     |
| <i>Outputs</i>        |    |       |       |       |     |        |
| <b>Out</b>            | 0  | 0.195 | 0.5   | 0.992 | ... | -0.992 |
| <b>Exp. Out</b>       | 0  | 0.195 | 0.5   | 0.992 | ... | -0.992 |
| <b>Out (DSP)</b>      | 0  | 25    | 64    | 127   | ... | -127   |
| <b>Exp. Out (DSP)</b> | 0  | 25    | 64    | 127   | ... | -127   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 69 |
| Avg CPU cycles  | 60 |

**Verification: TypeConv FiP16\_8 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |       |       |       |     |        |
|-----------------------|----|-------|-------|-------|-----|--------|
| <b>Time step</b>      | 1  | 2     | 3     | 4     | ... | 8      |
| <b>CPU cycles</b>     | 42 | 42    | 42    | 42    | ... | 52     |
| <i>Inputs</i>         |    |       |       |       |     |        |
| <b>In (DSP)</b>       | 0  | 6554  | 16384 | 32767 | ... | -32768 |
| <b>In</b>             | 0  | 0.2   | 0.5   | 1     | ... | -1     |
| <i>Outputs</i>        |    |       |       |       |     |        |
| <b>Out</b>            | 0  | 0.195 | 0.5   | 0.992 | ... | -0.992 |
| <b>Exp. Out</b>       | 0  | 0.195 | 0.5   | 0.992 | ... | -0.992 |
| <b>Out (DSP)</b>      | 0  | 25    | 64    | 127   | ... | -127   |
| <b>Exp. Out (DSP)</b> | 0  | 25    | 64    | 127   | ... | -127   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 42 |
| Max CPU cycles  | 52 |
| Avg CPU cycles  | 44 |

**Verification: TypeConv FiP16\_32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |             |
|-----------------------|----|-----------|-----|-------------|
| <b>Time step</b>      | 1  | 2         | ... | 8           |
| <b>CPU cycles</b>     | 56 | 56        | ... | 56          |
| <i>Inputs</i>         |    |           |     |             |
| <b>In (DSP)</b>       | 0  | 6554      | ... | -32768      |
| <b>In</b>             | 0  | 0.2       | ... | -1          |
| <i>Outputs</i>        |    |           |     |             |
| <b>Out</b>            | 0  | 0.2       | ... | -1          |
| <b>Exp. Out</b>       | 0  | 0.2       | ... | -1          |
| <b>Out (DSP)</b>      | 0  | 429522944 | ... | -2147483648 |
| <b>Exp. Out (DSP)</b> | 0  | 429496729 | ... | -2147483648 |

| Test settings |                                            |
|---------------|--------------------------------------------|
| Tolerance Out | $\pm 3,0518\text{e-}05$ ( $\pm 65536$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 56 |
| Avg CPU cycles  | 56 |

**Verification: TypeConv FiP16\_32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |             |
|-----------------------|----|-----------|-----|-------------|
| <b>Time step</b>      | 1  | 2         | ... | 8           |
| <b>CPU cycles</b>     | 25 | 25        | ... | 25          |
| <i>Inputs</i>         |    |           |     |             |
| <b>In (DSP)</b>       | 0  | 6554      | ... | -32768      |
| <b>In</b>             | 0  | 0.2       | ... | -1          |
| <i>Outputs</i>        |    |           |     |             |
| <b>Out</b>            | 0  | 0.2       | ... | -1          |
| <b>Exp. Out</b>       | 0  | 0.2       | ... | -1          |
| <b>Out (DSP)</b>      | 0  | 429522944 | ... | -2147483648 |
| <b>Exp. Out (DSP)</b> | 0  | 429496729 | ... | -2147483648 |

| Test settings |                                            |
|---------------|--------------------------------------------|
| Tolerance Out | $\pm 3,0518\text{e-}05$ ( $\pm 65536$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 25 |
| Max CPU cycles  | 25 |
| Avg CPU cycles  | 25 |

**Verification: TypeConv FiP16\_32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |             |
|-----------------------|----|-----------|-----|-------------|
| <b>Time step</b>      | 1  | 2         | ... | 8           |
| <b>CPU cycles</b>     | 57 | 57        | ... | 57          |
| <i>Inputs</i>         |    |           |     |             |
| <b>In (DSP)</b>       | 0  | 6554      | ... | -32768      |
| <b>In</b>             | 0  | 0.2       | ... | -1          |
| <i>Outputs</i>        |    |           |     |             |
| <b>Out</b>            | 0  | 0.2       | ... | -1          |
| <b>Exp. Out</b>       | 0  | 0.2       | ... | -1          |
| <b>Out (DSP)</b>      | 0  | 429522944 | ... | -2147483648 |
| <b>Exp. Out (DSP)</b> | 0  | 429496729 | ... | -2147483648 |

| Test settings |                                            |
|---------------|--------------------------------------------|
| Tolerance Out | $\pm 3,0518\text{e-}05$ ( $\pm 65536$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 57 |

**Verification: TypeConv FiP16\_32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |             |
|-----------------------|----|-----------|-----|-------------|
| <b>Time step</b>      | 1  | 2         | ... | 8           |
| <b>CPU cycles</b>     | 48 | 48        | ... | 48          |
| <i>Inputs</i>         |    |           |     |             |
| <b>In (DSP)</b>       | 0  | 6554      | ... | -32768      |
| <b>In</b>             | 0  | 0.2       | ... | -1          |
| <i>Outputs</i>        |    |           |     |             |
| <b>Out</b>            | 0  | 0.2       | ... | -1          |
| <b>Exp. Out</b>       | 0  | 0.2       | ... | -1          |
| <b>Out (DSP)</b>      | 0  | 429522944 | ... | -2147483648 |
| <b>Exp. Out (DSP)</b> | 0  | 429496729 | ... | -2147483648 |

| Test settings |                                            |
|---------------|--------------------------------------------|
| Tolerance Out | $\pm 3,0518\text{e-}05$ ( $\pm 65536$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 48 |
| Max CPU cycles  | 48 |
| Avg CPU cycles  | 48 |

**Verification: TypeConv FiP16\_32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |             |
|-----------------------|----|-----------|-----|-------------|
| <b>Time step</b>      | 1  | 2         | ... | 8           |
| <b>CPU cycles</b>     | 29 | 29        | ... | 29          |
| <i>Inputs</i>         |    |           |     |             |
| <b>In (DSP)</b>       | 0  | 6554      | ... | -32768      |
| <b>In</b>             | 0  | 0.2       | ... | -1          |
| <i>Outputs</i>        |    |           |     |             |
| <b>Out</b>            | 0  | 0.2       | ... | -1          |
| <b>Exp. Out</b>       | 0  | 0.2       | ... | -1          |
| <b>Out (DSP)</b>      | 0  | 429522944 | ... | -2147483648 |
| <b>Exp. Out (DSP)</b> | 0  | 429496729 | ... | -2147483648 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 65536$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 29 |
| Avg CPU cycles  | 29 |



**Verification: TypeConv FiP16\_32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |             |
|-----------------------|----|-----------|-----|-------------|
| <b>Time step</b>      | 1  | 2         | ... | 8           |
| <b>CPU cycles</b>     | 43 | 43        | ... | 43          |
| <i>Inputs</i>         |    |           |     |             |
| <b>In (DSP)</b>       | 0  | 6554      | ... | -32768      |
| <b>In</b>             | 0  | 0.2       | ... | -1          |
| <i>Outputs</i>        |    |           |     |             |
| <b>Out</b>            | 0  | 0.2       | ... | -1          |
| <b>Exp. Out</b>       | 0  | 0.2       | ... | -1          |
| <b>Out (DSP)</b>      | 0  | 429522944 | ... | -2147483648 |
| <b>Exp. Out (DSP)</b> | 0  | 429496729 | ... | -2147483648 |

| Test settings |                                            |
|---------------|--------------------------------------------|
| Tolerance Out | $\pm 3,0518\text{e-}05$ ( $\pm 65536$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 43 |
| Max CPU cycles  | 43 |
| Avg CPU cycles  | 43 |

**Verification: TypeConv FiP16\_32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |             |
|-----------------------|----|-----------|-----|-------------|
| <b>Time step</b>      | 1  | 2         | ... | 8           |
| <b>CPU cycles</b>     | 56 | 56        | ... | 56          |
| <i>Inputs</i>         |    |           |     |             |
| <b>In (DSP)</b>       | 0  | 6554      | ... | -32768      |
| <b>In</b>             | 0  | 0.2       | ... | -1          |
| <i>Outputs</i>        |    |           |     |             |
| <b>Out</b>            | 0  | 0.2       | ... | -1          |
| <b>Exp. Out</b>       | 0  | 0.2       | ... | -1          |
| <b>Out (DSP)</b>      | 0  | 429522944 | ... | -2147483648 |
| <b>Exp. Out (DSP)</b> | 0  | 429496729 | ... | -2147483648 |

| Test settings |                                            |
|---------------|--------------------------------------------|
| Tolerance Out | $\pm 3,0518\text{e-}05$ ( $\pm 65536$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 56 |
| Avg CPU cycles  | 56 |

**Verification: TypeConv FiP16\_32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |             |
|-----------------------|----|-----------|-----|-------------|
| <b>Time step</b>      | 1  | 2         | ... | 8           |
| <b>CPU cycles</b>     | 36 | 36        | ... | 36          |
| <i>Inputs</i>         |    |           |     |             |
| <b>In (DSP)</b>       | 0  | 6554      | ... | -32768      |
| <b>In</b>             | 0  | 0.2       | ... | -1          |
| <i>Outputs</i>        |    |           |     |             |
| <b>Out</b>            | 0  | 0.2       | ... | -1          |
| <b>Exp. Out</b>       | 0  | 0.2       | ... | -1          |
| <b>Out (DSP)</b>      | 0  | 429522944 | ... | -2147483648 |
| <b>Exp. Out (DSP)</b> | 0  | 429496729 | ... | -2147483648 |

| Test settings |                                            |
|---------------|--------------------------------------------|
| Tolerance Out | $\pm 3,0518\text{e-}05$ ( $\pm 65536$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 36 |
| Max CPU cycles  | 36 |
| Avg CPU cycles  | 36 |

**Verification: TypeConv FiP32\_8 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |             |
|-----------------------|----|-----------|-----|-------------|
| <b>Time step</b>      | 1  | 2         | ... | 8           |
| <b>CPU cycles</b>     | 63 | 63        | ... | 64          |
| <i>Inputs</i>         |    |           |     |             |
| <b>In (DSP)</b>       | 0  | 429496730 | ... | -2147483648 |
| <b>In</b>             | 0  | 0.2       | ... | -1          |
| <i>Outputs</i>        |    |           |     |             |
| <b>Out</b>            | 0  | 0.195     | ... | -0.992      |
| <b>Exp. Out</b>       | 0  | 0.195     | ... | -0.992      |
| <b>Out (DSP)</b>      | 0  | 25        | ... | -127        |
| <b>Exp. Out (DSP)</b> | 0  | 25        | ... | -127        |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 63 |
| Max CPU cycles  | 64 |
| Avg CPU cycles  | 63 |

## Verification: TypeConv FiP32\_8 CPU TM4C123GH6

Date of Test 2026-06-19  
Target controller TM4C123GH6

### Test case: Inport test

OK

Inport test for General block TypeConv.

| Test results   |    |           |     |             |
|----------------|----|-----------|-----|-------------|
| Time step      | 1  | 2         | ... | 8           |
| CPU cycles     | 29 | 29        | ... | 31          |
| Inputs         |    |           |     |             |
| In (DSP)       | 0  | 429496730 | ... | -2147483648 |
| In             | 0  | 0.2       | ... | -1          |
| Outputs        |    |           |     |             |
| Out            | 0  | 0.195     | ... | -0.992      |
| Exp. Out       | 0  | 0.195     | ... | -0.992      |
| Out (DSP)      | 0  | 25        | ... | -127        |
| Exp. Out (DSP) | 0  | 25        | ... | -127        |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 31 |
| Avg CPU cycles  | 29 |

## Verification: TypeConv FiP32\_8 CPU STM32G474RE

Date of Test 2026-06-19  
Target controller STM32G474RE

### Test case: Inport test

OK

Inport test for General block TypeConv.

| Test results   |    |           |     |             |
|----------------|----|-----------|-----|-------------|
| Time step      | 1  | 2         | ... | 8           |
| CPU cycles     | 62 | 62        | ... | 62          |
| Inputs         |    |           |     |             |
| In (DSP)       | 0  | 429496730 | ... | -2147483648 |
| In             | 0  | 0.2       | ... | -1          |
| Outputs        |    |           |     |             |
| Out            | 0  | 0.195     | ... | -0.992      |
| Exp. Out       | 0  | 0.195     | ... | -0.992      |
| Out (DSP)      | 0  | 25        | ... | -127        |
| Exp. Out (DSP) | 0  | 25        | ... | -127        |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 62 |
| Avg CPU cycles  | 62 |

**Verification: TypeConv FiP32\_8 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |             |
|-----------------------|----|-----------|-----|-------------|
| <b>Time step</b>      | 1  | 2         | ... | 8           |
| <b>CPU cycles</b>     | 51 | 51        | ... | 58          |
| <i>Inputs</i>         |    |           |     |             |
| <b>In (DSP)</b>       | 0  | 429496730 | ... | -2147483648 |
| <b>In</b>             | 0  | 0.2       | ... | -1          |
| <i>Outputs</i>        |    |           |     |             |
| <b>Out</b>            | 0  | 0.195     | ... | -0.992      |
| <b>Exp. Out</b>       | 0  | 0.195     | ... | -0.992      |
| <b>Out (DSP)</b>      | 0  | 25        | ... | -127        |
| <b>Exp. Out (DSP)</b> | 0  | 25        | ... | -127        |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 51 |
| Max CPU cycles  | 58 |
| Avg CPU cycles  | 52 |

**Verification: TypeConv FiP32\_8 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |             |
|-----------------------|----|-----------|-----|-------------|
| <b>Time step</b>      | 1  | 2         | ... | 8           |
| <b>CPU cycles</b>     | 31 | 31        | ... | 31          |
| <i>Inputs</i>         |    |           |     |             |
| <b>In (DSP)</b>       | 0  | 429496730 | ... | -2147483648 |
| <b>In</b>             | 0  | 0.2       | ... | -1          |
| <i>Outputs</i>        |    |           |     |             |
| <b>Out</b>            | 0  | 0.195     | ... | -0.992      |
| <b>Exp. Out</b>       | 0  | 0.195     | ... | -0.992      |
| <b>Out (DSP)</b>      | 0  | 25        | ... | -127        |
| <b>Exp. Out (DSP)</b> | 0  | 25        | ... | -127        |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 31 |
| Avg CPU cycles  | 31 |



**Verification: TypeConv FiP32\_8 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |             |
|-----------------------|----|-----------|-----|-------------|
| <b>Time step</b>      | 1  | 2         | ... | 8           |
| <b>CPU cycles</b>     | 48 | 48        | ... | 51          |
| <i>Inputs</i>         |    |           |     |             |
| <b>In (DSP)</b>       | 0  | 429496730 | ... | -2147483648 |
| <b>In</b>             | 0  | 0.2       | ... | -1          |
| <i>Outputs</i>        |    |           |     |             |
| <b>Out</b>            | 0  | 0.195     | ... | -0.992      |
| <b>Exp. Out</b>       | 0  | 0.195     | ... | -0.992      |
| <b>Out (DSP)</b>      | 0  | 25        | ... | -127        |
| <b>Exp. Out (DSP)</b> | 0  | 25        | ... | -127        |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 48 |
| Max CPU cycles  | 51 |
| Avg CPU cycles  | 48 |

**Verification: TypeConv FiP32\_8 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |             |
|-----------------------|----|-----------|-----|-------------|
| <b>Time step</b>      | 1  | 2         | ... | 8           |
| <b>CPU cycles</b>     | 67 | 59        | ... | 59          |
| <i>Inputs</i>         |    |           |     |             |
| <b>In (DSP)</b>       | 0  | 429496730 | ... | -2147483648 |
| <b>In</b>             | 0  | 0.2       | ... | -1          |
| <i>Outputs</i>        |    |           |     |             |
| <b>Out</b>            | 0  | 0.195     | ... | -0.992      |
| <b>Exp. Out</b>       | 0  | 0.195     | ... | -0.992      |
| <b>Out (DSP)</b>      | 0  | 25        | ... | -127        |
| <b>Exp. Out (DSP)</b> | 0  | 25        | ... | -127        |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 67 |
| Avg CPU cycles  | 60 |

**Verification: TypeConv FiP32\_8 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |             |
|-----------------------|----|-----------|-----|-------------|
| <b>Time step</b>      | 1  | 2         | ... | 8           |
| <b>CPU cycles</b>     | 47 | 47        | ... | 51          |
| <i>Inputs</i>         |    |           |     |             |
| <b>In (DSP)</b>       | 0  | 429496730 | ... | -2147483648 |
| <b>In</b>             | 0  | 0.2       | ... | -1          |
| <i>Outputs</i>        |    |           |     |             |
| <b>Out</b>            | 0  | 0.195     | ... | -0.992      |
| <b>Exp. Out</b>       | 0  | 0.195     | ... | -0.992      |
| <b>Out (DSP)</b>      | 0  | 25        | ... | -127        |
| <b>Exp. Out (DSP)</b> | 0  | 25        | ... | -127        |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 47 |
| Max CPU cycles  | 51 |
| Avg CPU cycles  | 48 |

**Verification: TypeConv FiP32\_16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |             |
|-----------------------|----|-----------|-----|-------------|
| <b>Time step</b>      | 1  | 2         | ... | 8           |
| <b>CPU cycles</b>     | 61 | 61        | ... | 63          |
| <i>Inputs</i>         |    |           |     |             |
| <b>In (DSP)</b>       | 0  | 429496730 | ... | -2147483648 |
| <b>In</b>             | 0  | 0.2       | ... | -1          |
| <i>Outputs</i>        |    |           |     |             |
| <b>Out</b>            | 0  | 0.2       | ... | -1          |
| <b>Exp. Out</b>       | 0  | 0.2       | ... | -1          |
| <b>Out (DSP)</b>      | 0  | 6553      | ... | -32767      |
| <b>Exp. Out (DSP)</b> | 0  | 6553      | ... | -32767      |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 61 |
| Max CPU cycles  | 63 |
| Avg CPU cycles  | 61 |

**Verification: TypeConv FiP32\_16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |             |
|-----------------------|----|-----------|-----|-------------|
| <b>Time step</b>      | 1  | 2         | ... | 8           |
| <b>CPU cycles</b>     | 31 | 31        | ... | 33          |
| <i>Inputs</i>         |    |           |     |             |
| <b>In (DSP)</b>       | 0  | 429496730 | ... | -2147483648 |
| <b>In</b>             | 0  | 0.2       | ... | -1          |
| <i>Outputs</i>        |    |           |     |             |
| <b>Out</b>            | 0  | 0.2       | ... | -1          |
| <b>Exp. Out</b>       | 0  | 0.2       | ... | -1          |
| <b>Out (DSP)</b>      | 0  | 6553      | ... | -32767      |
| <b>Exp. Out (DSP)</b> | 0  | 6553      | ... | -32767      |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 33 |
| Avg CPU cycles  | 31 |

**Verification: TypeConv FiP32\_16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |             |
|-----------------------|----|-----------|-----|-------------|
| <b>Time step</b>      | 1  | 2         | ... | 8           |
| <b>CPU cycles</b>     | 62 | 62        | ... | 67          |
| <i>Inputs</i>         |    |           |     |             |
| <b>In (DSP)</b>       | 0  | 429496730 | ... | -2147483648 |
| <b>In</b>             | 0  | 0.2       | ... | -1          |
| <i>Outputs</i>        |    |           |     |             |
| <b>Out</b>            | 0  | 0.2       | ... | -1          |
| <b>Exp. Out</b>       | 0  | 0.2       | ... | -1          |
| <b>Out (DSP)</b>      | 0  | 6553      | ... | -32767      |
| <b>Exp. Out (DSP)</b> | 0  | 6553      | ... | -32767      |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 67 |
| Avg CPU cycles  | 63 |

**Verification: TypeConv FiP32\_16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |             |
|-----------------------|----|-----------|-----|-------------|
| <b>Time step</b>      | 1  | 2         | ... | 8           |
| <b>CPU cycles</b>     | 52 | 52        | ... | 60          |
| <i>Inputs</i>         |    |           |     |             |
| <b>In (DSP)</b>       | 0  | 429496730 | ... | -2147483648 |
| <b>In</b>             | 0  | 0.2       | ... | -1          |
| <i>Outputs</i>        |    |           |     |             |
| <b>Out</b>            | 0  | 0.2       | ... | -1          |
| <b>Exp. Out</b>       | 0  | 0.2       | ... | -1          |
| <b>Out (DSP)</b>      | 0  | 6553      | ... | -32767      |
| <b>Exp. Out (DSP)</b> | 0  | 6553      | ... | -32767      |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 52 |
| Max CPU cycles  | 60 |
| Avg CPU cycles  | 54 |

**Verification: TypeConv FiP32\_16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |             |
|-----------------------|----|-----------|-----|-------------|
| <b>Time step</b>      | 1  | 2         | ... | 8           |
| <b>CPU cycles</b>     | 31 | 31        | ... | 31          |
| <i>Inputs</i>         |    |           |     |             |
| <b>In (DSP)</b>       | 0  | 429496730 | ... | -2147483648 |
| <b>In</b>             | 0  | 0.2       | ... | -1          |
| <i>Outputs</i>        |    |           |     |             |
| <b>Out</b>            | 0  | 0.2       | ... | -1          |
| <b>Exp. Out</b>       | 0  | 0.2       | ... | -1          |
| <b>Out (DSP)</b>      | 0  | 6553      | ... | -32767      |
| <b>Exp. Out (DSP)</b> | 0  | 6553      | ... | -32767      |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 31 |
| Avg CPU cycles  | 31 |



**Verification: TypeConv FiP32\_16 CPU dsPIC33EP256MC502**

|                          |                   |
|--------------------------|-------------------|
| <b>Date of Test</b>      | 2026-06-19        |
| <b>Target controller</b> | dsPIC33EP256MC502 |

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |             |
|-----------------------|----|-----------|-----|-------------|
| <b>Time step</b>      | 1  | 2         | ... | 8           |
| <b>CPU cycles</b>     | 47 | 47        | ... | 51          |
| <i>Inputs</i>         |    |           |     |             |
| <b>In (DSP)</b>       | 0  | 429496730 | ... | -2147483648 |
| <b>In</b>             | 0  | 0.2       | ... | -1          |
| <i>Outputs</i>        |    |           |     |             |
| <b>Out</b>            | 0  | 0.2       | ... | -1          |
| <b>Exp. Out</b>       | 0  | 0.2       | ... | -1          |
| <b>Out (DSP)</b>      | 0  | 6553      | ... | -32767      |
| <b>Exp. Out (DSP)</b> | 0  | 6553      | ... | -32767      |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 47 |
| Max CPU cycles  | 51 |
| Avg CPU cycles  | 48 |

**Verification: TypeConv FiP32\_16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |             |
|-----------------------|----|-----------|-----|-------------|
| <b>Time step</b>      | 1  | 2         | ... | 8           |
| <b>CPU cycles</b>     | 65 | 65        | ... | 65          |
| <i>Inputs</i>         |    |           |     |             |
| <b>In (DSP)</b>       | 0  | 429496730 | ... | -2147483648 |
| <b>In</b>             | 0  | 0.2       | ... | -1          |
| <i>Outputs</i>        |    |           |     |             |
| <b>Out</b>            | 0  | 0.2       | ... | -1          |
| <b>Exp. Out</b>       | 0  | 0.2       | ... | -1          |
| <b>Out (DSP)</b>      | 0  | 6553      | ... | -32767      |
| <b>Exp. Out (DSP)</b> | 0  | 6553      | ... | -32767      |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 65 |
| Max CPU cycles  | 65 |
| Avg CPU cycles  | 65 |

**Verification: TypeConv FiP32\_16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |             |
|-----------------------|----|-----------|-----|-------------|
| <b>Time step</b>      | 1  | 2         | ... | 8           |
| <b>CPU cycles</b>     | 41 | 41        | ... | 51          |
| <i>Inputs</i>         |    |           |     |             |
| <b>In (DSP)</b>       | 0  | 429496730 | ... | -2147483648 |
| <b>In</b>             | 0  | 0.2       | ... | -1          |
| <i>Outputs</i>        |    |           |     |             |
| <b>Out</b>            | 0  | 0.2       | ... | -1          |
| <b>Exp. Out</b>       | 0  | 0.2       | ... | -1          |
| <b>Out (DSP)</b>      | 0  | 6553      | ... | -32767      |
| <b>Exp. Out (DSP)</b> | 0  | 6553      | ... | -32767      |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 41 |
| Max CPU cycles  | 51 |
| Avg CPU cycles  | 43 |

**Verification: TypeConv Bool\_FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |       |
|-----------------------|----|-------|
| <b>Time step</b>      | 1  | 2     |
| <b>CPU cycles</b>     | 60 | 63    |
| <i>Inputs</i>         |    |       |
| <b>In (DSP)</b>       | 0  | 1     |
| <b>In</b>             | 0  | 1     |
| <i>Outputs</i>        |    |       |
| <b>Out</b>            | 0  | 1     |
| <b>Exp. Out</b>       | 0  | 1     |
| <b>Out (DSP)</b>      | 0  | 32767 |
| <b>Exp. Out (DSP)</b> | 0  | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 60 |
| Max CPU cycles  | 63 |
| Avg CPU cycles  | 61 |

## Verification: TypeConv Bool\_FiP16 CPU TM4C123GH6

Date of Test 2026-06-19  
Target controller TM4C123GH6

### Test case: Inport test

OK

Inport test for General block TypeConv.

| Test results   |    |       |
|----------------|----|-------|
| Time step      | 1  | 2     |
| CPU cycles     | 31 | 31    |
| Inputs         |    |       |
| In (DSP)       | 0  | 1     |
| In             | 0  | 1     |
| Outputs        |    |       |
| Out            | 0  | 1     |
| Exp. Out       | 0  | 1     |
| Out (DSP)      | 0  | 32767 |
| Exp. Out (DSP) | 0  | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 31 |
| Avg CPU cycles  | 31 |

**Verification: TypeConv Bool\_FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |       |
|-----------------------|----|-------|
| <b>Time step</b>      | 1  | 2     |
| <b>CPU cycles</b>     | 62 | 62    |
| <i>Inputs</i>         |    |       |
| <b>In (DSP)</b>       | 0  | 1     |
| <b>In</b>             | 0  | 1     |
| <i>Outputs</i>        |    |       |
| <b>Out</b>            | 0  | 1     |
| <b>Exp. Out</b>       | 0  | 1     |
| <b>Out (DSP)</b>      | 0  | 32767 |
| <b>Exp. Out (DSP)</b> | 0  | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 62 |
| Avg CPU cycles  | 62 |

**Verification: TypeConv Bool\_FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |       |
|-----------------------|----|-------|
| <b>Time step</b>      | 1  | 2     |
| <b>CPU cycles</b>     | 51 | 51    |
| <i>Inputs</i>         |    |       |
| <b>In (DSP)</b>       | 0  | 1     |
| <b>In</b>             | 0  | 1     |
| <i>Outputs</i>        |    |       |
| <b>Out</b>            | 0  | 1     |
| <b>Exp. Out</b>       | 0  | 1     |
| <b>Out (DSP)</b>      | 0  | 32767 |
| <b>Exp. Out (DSP)</b> | 0  | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 51 |
| Max CPU cycles  | 51 |
| Avg CPU cycles  | 51 |

**Verification: TypeConv Bool\_FiP16 CPU PIC32MX170F256**

---

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |       |
|-----------------------|----|-------|
| <b>Time step</b>      | 1  | 2     |
| <b>CPU cycles</b>     | 29 | 29    |
| <i>Inputs</i>         |    |       |
| <b>In (DSP)</b>       | 0  | 1     |
| <b>In</b>             | 0  | 1     |
| <i>Outputs</i>        |    |       |
| <b>Out</b>            | 0  | 1     |
| <b>Exp. Out</b>       | 0  | 1     |
| <b>Out (DSP)</b>      | 0  | 32767 |
| <b>Exp. Out (DSP)</b> | 0  | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 29 |
| Avg CPU cycles  | 29 |



**Verification: TypeConv Bool\_FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |       |
|-----------------------|----|-------|
| <b>Time step</b>      | 1  | 2     |
| <b>CPU cycles</b>     | 43 | 46    |
| <i>Inputs</i>         |    |       |
| <b>In (DSP)</b>       | 0  | 1     |
| <b>In</b>             | 0  | 1     |
| <i>Outputs</i>        |    |       |
| <b>Out</b>            | 0  | 1     |
| <b>Exp. Out</b>       | 0  | 1     |
| <b>Out (DSP)</b>      | 0  | 32767 |
| <b>Exp. Out (DSP)</b> | 0  | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 43 |
| Max CPU cycles  | 46 |
| Avg CPU cycles  | 44 |

**Verification: TypeConv Bool\_FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |       |
|-----------------------|----|-------|
| <b>Time step</b>      | 1  | 2     |
| <b>CPU cycles</b>     | 56 | 60    |
| <i>Inputs</i>         |    |       |
| <b>In (DSP)</b>       | 0  | 1     |
| <b>In</b>             | 0  | 1     |
| <i>Outputs</i>        |    |       |
| <b>Out</b>            | 0  | 1     |
| <b>Exp. Out</b>       | 0  | 1     |
| <b>Out (DSP)</b>      | 0  | 32767 |
| <b>Exp. Out (DSP)</b> | 0  | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 60 |
| Avg CPU cycles  | 58 |

**Verification: TypeConv Bool\_FiP16 CPU TMS320F28379D**

---

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |       |
|-----------------------|----|-------|
| <b>Time step</b>      | 1  | 2     |
| <b>CPU cycles</b>     | 40 | 46    |
| <i>Inputs</i>         |    |       |
| <b>In (DSP)</b>       | 0  | 1     |
| <b>In</b>             | 0  | 1     |
| <i>Outputs</i>        |    |       |
| <b>Out</b>            | 0  | 1     |
| <b>Exp. Out</b>       | 0  | 1     |
| <b>Out (DSP)</b>      | 0  | 32767 |
| <b>Exp. Out (DSP)</b> | 0  | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 40 |
| Max CPU cycles  | 46 |
| Avg CPU cycles  | 43 |

**Verification: TypeConv Bool\_FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |            |
|-----------------------|----|------------|
| <b>Time step</b>      | 1  | 2          |
| <b>CPU cycles</b>     | 65 | 66         |
| <i>Inputs</i>         |    |            |
| <b>In (DSP)</b>       | 0  | 1          |
| <b>In</b>             | 0  | 1          |
| <i>Outputs</i>        |    |            |
| <b>Out</b>            | 0  | 1          |
| <b>Exp. Out</b>       | 0  | 1          |
| <b>Out (DSP)</b>      | 0  | 2147483647 |
| <b>Exp. Out (DSP)</b> | 0  | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 65 |
| Max CPU cycles  | 66 |
| Avg CPU cycles  | 65 |

**Verification: TypeConv Bool\_FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |            |
|-----------------------|----|------------|
| <b>Time step</b>      | 1  | 2          |
| <b>CPU cycles</b>     | 31 | 31         |
| <i>Inputs</i>         |    |            |
| <b>In (DSP)</b>       | 0  | 1          |
| <b>In</b>             | 0  | 1          |
| <i>Outputs</i>        |    |            |
| <b>Out</b>            | 0  | 1          |
| <b>Exp. Out</b>       | 0  | 1          |
| <b>Out (DSP)</b>      | 0  | 2147483647 |
| <b>Exp. Out (DSP)</b> | 0  | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 31 |
| Avg CPU cycles  | 31 |

**Verification: TypeConv Bool\_FiP32 CPU STM32G474RE**

---

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |            |
|-----------------------|----|------------|
| <b>Time step</b>      | 1  | 2          |
| <b>CPU cycles</b>     | 57 | 57         |
| <i>Inputs</i>         |    |            |
| <b>In (DSP)</b>       | 0  | 1          |
| <b>In</b>             | 0  | 1          |
| <i>Outputs</i>        |    |            |
| <b>Out</b>            | 0  | 1          |
| <b>Exp. Out</b>       | 0  | 1          |
| <b>Out (DSP)</b>      | 0  | 2147483647 |
| <b>Exp. Out (DSP)</b> | 0  | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 57 |

**Verification: TypeConv Bool\_FiP32 CPU STM32F072RB**

---

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |            |
|-----------------------|----|------------|
| <b>Time step</b>      | 1  | 2          |
| <b>CPU cycles</b>     | 51 | 51         |
| <i>Inputs</i>         |    |            |
| <b>In (DSP)</b>       | 0  | 1          |
| <b>In</b>             | 0  | 1          |
| <i>Outputs</i>        |    |            |
| <b>Out</b>            | 0  | 1          |
| <b>Exp. Out</b>       | 0  | 1          |
| <b>Out (DSP)</b>      | 0  | 2147483647 |
| <b>Exp. Out (DSP)</b> | 0  | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 51 |
| Max CPU cycles  | 51 |
| Avg CPU cycles  | 51 |

**Verification: TypeConv Bool\_FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |            |
|-----------------------|----|------------|
| <b>Time step</b>      | 1  | 2          |
| <b>CPU cycles</b>     | 30 | 32         |
| <i>Inputs</i>         |    |            |
| <b>In (DSP)</b>       | 0  | 1          |
| <b>In</b>             | 0  | 1          |
| <i>Outputs</i>        |    |            |
| <b>Out</b>            | 0  | 1          |
| <b>Exp. Out</b>       | 0  | 1          |
| <b>Out (DSP)</b>      | 0  | 2147483647 |
| <b>Exp. Out (DSP)</b> | 0  | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 30 |
| Max CPU cycles  | 32 |
| Avg CPU cycles  | 31 |



**Verification: TypeConv Bool\_FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |            |
|-----------------------|----|------------|
| <b>Time step</b>      | 1  | 2          |
| <b>CPU cycles</b>     | 44 | 48         |
| <i>Inputs</i>         |    |            |
| <b>In (DSP)</b>       | 0  | 1          |
| <b>In</b>             | 0  | 1          |
| <i>Outputs</i>        |    |            |
| <b>Out</b>            | 0  | 1          |
| <b>Exp. Out</b>       | 0  | 1          |
| <b>Out (DSP)</b>      | 0  | 2147483647 |
| <b>Exp. Out (DSP)</b> | 0  | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 44 |
| Max CPU cycles  | 48 |
| Avg CPU cycles  | 46 |

**Verification: TypeConv Bool\_FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |            |
|-----------------------|----|------------|
| <b>Time step</b>      | 1  | 2          |
| <b>CPU cycles</b>     | 56 | 60         |
| <i>Inputs</i>         |    |            |
| <b>In (DSP)</b>       | 0  | 1          |
| <b>In</b>             | 0  | 1          |
| <i>Outputs</i>        |    |            |
| <b>Out</b>            | 0  | 1          |
| <b>Exp. Out</b>       | 0  | 1          |
| <b>Out (DSP)</b>      | 0  | 2147483647 |
| <b>Exp. Out (DSP)</b> | 0  | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 60 |
| Avg CPU cycles  | 58 |

**Verification: TypeConv Bool\_FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |            |
|-----------------------|----|------------|
| <b>Time step</b>      | 1  | 2          |
| <b>CPU cycles</b>     | 48 | 54         |
| <i>Inputs</i>         |    |            |
| <b>In (DSP)</b>       | 0  | 1          |
| <b>In</b>             | 0  | 1          |
| <i>Outputs</i>        |    |            |
| <b>Out</b>            | 0  | 1          |
| <b>Exp. Out</b>       | 0  | 1          |
| <b>Out (DSP)</b>      | 0  | 2147483647 |
| <b>Exp. Out (DSP)</b> | 0  | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 48 |
| Max CPU cycles  | 54 |
| Avg CPU cycles  | 51 |

**Verification: TypeConv FiP16\_Bool CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |      |       |       |     |        |
|-----------------------|----|------|-------|-------|-----|--------|
| <b>Time step</b>      | 1  | 2    | 3     | 4     | ... | 8      |
| <b>CPU cycles</b>     | 60 | 63   | 63    | 63    | ... | 63     |
| <i>Inputs</i>         |    |      |       |       |     |        |
| <b>In (DSP)</b>       | 0  | 6554 | 16384 | 32767 | ... | -32768 |
| <b>In</b>             | 0  | 0.2  | 0.5   | 1     | ... | -1     |
| <i>Outputs</i>        |    |      |       |       |     |        |
| <b>Out</b>            | 0  | 1    | 1     | 1     | ... | 1      |
| <b>Exp. Out</b>       | 0  | 1    | 1     | 1     | ... | 1      |
| <b>Out (DSP)</b>      | 0  | 1    | 1     | 1     | ... | 1      |
| <b>Exp. Out (DSP)</b> | 0  | 1    | 1     | 1     | ... | 1      |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 60 |
| Max CPU cycles  | 63 |
| Avg CPU cycles  | 62 |

**Verification: TypeConv FiP16\_Bool CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |      |       |       |     |        |
|-----------------------|----|------|-------|-------|-----|--------|
| <b>Time step</b>      | 1  | 2    | 3     | 4     | ... | 8      |
| <b>CPU cycles</b>     | 29 | 29   | 29    | 29    | ... | 29     |
| <i>Inputs</i>         |    |      |       |       |     |        |
| <b>In (DSP)</b>       | 0  | 6554 | 16384 | 32767 | ... | -32768 |
| <b>In</b>             | 0  | 0.2  | 0.5   | 1     | ... | -1     |
| <i>Outputs</i>        |    |      |       |       |     |        |
| <b>Out</b>            | 0  | 1    | 1     | 1     | ... | 1      |
| <b>Exp. Out</b>       | 0  | 1    | 1     | 1     | ... | 1      |
| <b>Out (DSP)</b>      | 0  | 1    | 1     | 1     | ... | 1      |
| <b>Exp. Out (DSP)</b> | 0  | 1    | 1     | 1     | ... | 1      |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 29 |
| Avg CPU cycles  | 29 |

**Verification: TypeConv FiP16\_Bool CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |      |       |       |     |        |
|-----------------------|----|------|-------|-------|-----|--------|
| <b>Time step</b>      | 1  | 2    | 3     | 4     | ... | 8      |
| <b>CPU cycles</b>     | 57 | 57   | 57    | 57    | ... | 57     |
| <i>Inputs</i>         |    |      |       |       |     |        |
| <b>In (DSP)</b>       | 0  | 6554 | 16384 | 32767 | ... | -32768 |
| <b>In</b>             | 0  | 0.2  | 0.5   | 1     | ... | -1     |
| <i>Outputs</i>        |    |      |       |       |     |        |
| <b>Out</b>            | 0  | 1    | 1     | 1     | ... | 1      |
| <b>Exp. Out</b>       | 0  | 1    | 1     | 1     | ... | 1      |
| <b>Out (DSP)</b>      | 0  | 1    | 1     | 1     | ... | 1      |
| <b>Exp. Out (DSP)</b> | 0  | 1    | 1     | 1     | ... | 1      |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 57 |

**Verification: TypeConv FiP16\_Bool CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |      |       |       |     |        |
|-----------------------|----|------|-------|-------|-----|--------|
| <b>Time step</b>      | 1  | 2    | 3     | 4     | ... | 8      |
| <b>CPU cycles</b>     | 49 | 49   | 49    | 49    | ... | 49     |
| <i>Inputs</i>         |    |      |       |       |     |        |
| <b>In (DSP)</b>       | 0  | 6554 | 16384 | 32767 | ... | -32768 |
| <b>In</b>             | 0  | 0.2  | 0.5   | 1     | ... | -1     |
| <i>Outputs</i>        |    |      |       |       |     |        |
| <b>Out</b>            | 0  | 1    | 1     | 1     | ... | 1      |
| <b>Exp. Out</b>       | 0  | 1    | 1     | 1     | ... | 1      |
| <b>Out (DSP)</b>      | 0  | 1    | 1     | 1     | ... | 1      |
| <b>Exp. Out (DSP)</b> | 0  | 1    | 1     | 1     | ... | 1      |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 49 |
| Max CPU cycles  | 49 |
| Avg CPU cycles  | 49 |

**Verification: TypeConv FiP16\_Bool CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |      |       |       |     |        |
|-----------------------|----|------|-------|-------|-----|--------|
| <b>Time step</b>      | 1  | 2    | 3     | 4     | ... | 8      |
| <b>CPU cycles</b>     | 29 | 29   | 29    | 29    | ... | 29     |
| <i>Inputs</i>         |    |      |       |       |     |        |
| <b>In (DSP)</b>       | 0  | 6554 | 16384 | 32767 | ... | -32768 |
| <b>In</b>             | 0  | 0.2  | 0.5   | 1     | ... | -1     |
| <i>Outputs</i>        |    |      |       |       |     |        |
| <b>Out</b>            | 0  | 1    | 1     | 1     | ... | 1      |
| <b>Exp. Out</b>       | 0  | 1    | 1     | 1     | ... | 1      |
| <b>Out (DSP)</b>      | 0  | 1    | 1     | 1     | ... | 1      |
| <b>Exp. Out (DSP)</b> | 0  | 1    | 1     | 1     | ... | 1      |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 29 |
| Avg CPU cycles  | 29 |



**Verification: TypeConv FiP16\_Bool CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |      |       |       |     |        |
|-----------------------|----|------|-------|-------|-----|--------|
| <b>Time step</b>      | 1  | 2    | 3     | 4     | ... | 8      |
| <b>CPU cycles</b>     | 43 | 47   | 47    | 47    | ... | 47     |
| <i>Inputs</i>         |    |      |       |       |     |        |
| <b>In (DSP)</b>       | 0  | 6554 | 16384 | 32767 | ... | -32768 |
| <b>In</b>             | 0  | 0.2  | 0.5   | 1     | ... | -1     |
| <i>Outputs</i>        |    |      |       |       |     |        |
| <b>Out</b>            | 0  | 1    | 1     | 1     | ... | 1      |
| <b>Exp. Out</b>       | 0  | 1    | 1     | 1     | ... | 1      |
| <b>Out (DSP)</b>      | 0  | 1    | 1     | 1     | ... | 1      |
| <b>Exp. Out (DSP)</b> | 0  | 1    | 1     | 1     | ... | 1      |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 43 |
| Max CPU cycles  | 47 |
| Avg CPU cycles  | 46 |

**Verification: TypeConv FiP16\_Bool CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |      |       |       |     |        |
|-----------------------|----|------|-------|-------|-----|--------|
| <b>Time step</b>      | 1  | 2    | 3     | 4     | ... | 8      |
| <b>CPU cycles</b>     | 66 | 59   | 59    | 59    | ... | 59     |
| <i>Inputs</i>         |    |      |       |       |     |        |
| <b>In (DSP)</b>       | 0  | 6554 | 16384 | 32767 | ... | -32768 |
| <b>In</b>             | 0  | 0.2  | 0.5   | 1     | ... | -1     |
| <i>Outputs</i>        |    |      |       |       |     |        |
| <b>Out</b>            | 0  | 1    | 1     | 1     | ... | 1      |
| <b>Exp. Out</b>       | 0  | 1    | 1     | 1     | ... | 1      |
| <b>Out (DSP)</b>      | 0  | 1    | 1     | 1     | ... | 1      |
| <b>Exp. Out (DSP)</b> | 0  | 1    | 1     | 1     | ... | 1      |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 66 |
| Avg CPU cycles  | 59 |

**Verification: TypeConv FiP16\_Bool CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |      |       |       |     |        |
|-----------------------|----|------|-------|-------|-----|--------|
| <b>Time step</b>      | 1  | 2    | 3     | 4     | ... | 8      |
| <b>CPU cycles</b>     | 40 | 46   | 46    | 46    | ... | 46     |
| <i>Inputs</i>         |    |      |       |       |     |        |
| <b>In (DSP)</b>       | 0  | 6554 | 16384 | 32767 | ... | -32768 |
| <b>In</b>             | 0  | 0.2  | 0.5   | 1     | ... | -1     |
| <i>Outputs</i>        |    |      |       |       |     |        |
| <b>Out</b>            | 0  | 1    | 1     | 1     | ... | 1      |
| <b>Exp. Out</b>       | 0  | 1    | 1     | 1     | ... | 1      |
| <b>Out (DSP)</b>      | 0  | 1    | 1     | 1     | ... | 1      |
| <b>Exp. Out (DSP)</b> | 0  | 1    | 1     | 1     | ... | 1      |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 40 |
| Max CPU cycles  | 46 |
| Avg CPU cycles  | 45 |

**Verification: TypeConv FiP32\_Bool CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |            |
|-----------------------|----|-----------|-----|------------|
| <b>Time step</b>      | 1  | 2         | ... | 7          |
| <b>CPU cycles</b>     | 60 | 63        | ... | 63         |
| <i>Inputs</i>         |    |           |     |            |
| <b>In (DSP)</b>       | 0  | 429496730 | ... | -429496730 |
| <b>In</b>             | 0  | 0.2       | ... | -0.2       |
| <i>Outputs</i>        |    |           |     |            |
| <b>Out</b>            | 0  | 1         | ... | 1          |
| <b>Exp. Out</b>       | 0  | 1         | ... | 1          |
| <b>Out (DSP)</b>      | 0  | 1         | ... | 1          |
| <b>Exp. Out (DSP)</b> | 0  | 1         | ... | 1          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 60 |
| Max CPU cycles  | 63 |
| Avg CPU cycles  | 62 |

## Verification: TypeConv FiP32\_Bool CPU TM4C123GH6

Date of Test 2026-06-19  
Target controller TM4C123GH6

### Test case: Inport test

OK

Inport test for General block TypeConv.

| Test results   |    |           |     |            |
|----------------|----|-----------|-----|------------|
| Time step      | 1  | 2         | ... | 7          |
| CPU cycles     | 31 | 29        | ... | 29         |
| Inputs         |    |           |     |            |
| In (DSP)       | 0  | 429496730 | ... | -429496730 |
| In             | 0  | 0.2       | ... | -0.2       |
| Outputs        |    |           |     |            |
| Out            | 0  | 1         | ... | 1          |
| Exp. Out       | 0  | 1         | ... | 1          |
| Out (DSP)      | 0  | 1         | ... | 1          |
| Exp. Out (DSP) | 0  | 1         | ... | 1          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 31 |
| Avg CPU cycles  | 29 |

**Verification: TypeConv FiP32\_Bool CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |            |
|-----------------------|----|-----------|-----|------------|
| <b>Time step</b>      | 1  | 2         | ... | 7          |
| <b>CPU cycles</b>     | 57 | 57        | ... | 57         |
| <i>Inputs</i>         |    |           |     |            |
| <b>In (DSP)</b>       | 0  | 429496730 | ... | -429496730 |
| <b>In</b>             | 0  | 0.2       | ... | -0.2       |
| <i>Outputs</i>        |    |           |     |            |
| <b>Out</b>            | 0  | 1         | ... | 1          |
| <b>Exp. Out</b>       | 0  | 1         | ... | 1          |
| <b>Out (DSP)</b>      | 0  | 1         | ... | 1          |
| <b>Exp. Out (DSP)</b> | 0  | 1         | ... | 1          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 57 |

**Verification: TypeConv FiP32\_Bool CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |            |
|-----------------------|----|-----------|-----|------------|
| <b>Time step</b>      | 1  | 2         | ... | 7          |
| <b>CPU cycles</b>     | 48 | 48        | ... | 48         |
| <i>Inputs</i>         |    |           |     |            |
| <b>In (DSP)</b>       | 0  | 429496730 | ... | -429496730 |
| <b>In</b>             | 0  | 0.2       | ... | -0.2       |
| <i>Outputs</i>        |    |           |     |            |
| <b>Out</b>            | 0  | 1         | ... | 1          |
| <b>Exp. Out</b>       | 0  | 1         | ... | 1          |
| <b>Out (DSP)</b>      | 0  | 1         | ... | 1          |
| <b>Exp. Out (DSP)</b> | 0  | 1         | ... | 1          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 48 |
| Max CPU cycles  | 48 |
| Avg CPU cycles  | 48 |

**Verification: TypeConv FiP32\_ Bool CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |            |
|-----------------------|----|-----------|-----|------------|
| <b>Time step</b>      | 1  | 2         | ... | 7          |
| <b>CPU cycles</b>     | 29 | 29        | ... | 29         |
| <i>Inputs</i>         |    |           |     |            |
| <b>In (DSP)</b>       | 0  | 429496730 | ... | -429496730 |
| <b>In</b>             | 0  | 0.2       | ... | -0.2       |
| <i>Outputs</i>        |    |           |     |            |
| <b>Out</b>            | 0  | 1         | ... | 1          |
| <b>Exp. Out</b>       | 0  | 1         | ... | 1          |
| <b>Out (DSP)</b>      | 0  | 1         | ... | 1          |
| <b>Exp. Out (DSP)</b> | 0  | 1         | ... | 1          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 29 |
| Avg CPU cycles  | 29 |



**Verification: TypeConv FiP32\_Bool CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |            |
|-----------------------|----|-----------|-----|------------|
| <b>Time step</b>      | 1  | 2         | ... | 7          |
| <b>CPU cycles</b>     | 46 | 49        | ... | 49         |
| <i>Inputs</i>         |    |           |     |            |
| <b>In (DSP)</b>       | 0  | 429496730 | ... | -429496730 |
| <b>In</b>             | 0  | 0.2       | ... | -0.2       |
| <i>Outputs</i>        |    |           |     |            |
| <b>Out</b>            | 0  | 1         | ... | 1          |
| <b>Exp. Out</b>       | 0  | 1         | ... | 1          |
| <b>Out (DSP)</b>      | 0  | 1         | ... | 1          |
| <b>Exp. Out (DSP)</b> | 0  | 1         | ... | 1          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 46 |
| Max CPU cycles  | 49 |
| Avg CPU cycles  | 48 |

**Verification: TypeConv FiP32\_Bool CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |            |
|-----------------------|----|-----------|-----|------------|
| <b>Time step</b>      | 1  | 2         | ... | 7          |
| <b>CPU cycles</b>     | 56 | 59        | ... | 59         |
| <i>Inputs</i>         |    |           |     |            |
| <b>In (DSP)</b>       | 0  | 429496730 | ... | -429496730 |
| <b>In</b>             | 0  | 0.2       | ... | -0.2       |
| <i>Outputs</i>        |    |           |     |            |
| <b>Out</b>            | 0  | 1         | ... | 1          |
| <b>Exp. Out</b>       | 0  | 1         | ... | 1          |
| <b>Out (DSP)</b>      | 0  | 1         | ... | 1          |
| <b>Exp. Out (DSP)</b> | 0  | 1         | ... | 1          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 59 |
| Avg CPU cycles  | 58 |

**Verification: TypeConv FiP32\_Bool CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block TypeConv.

| Test results          |    |           |     |            |
|-----------------------|----|-----------|-----|------------|
| <b>Time step</b>      | 1  | 2         | ... | 7          |
| <b>CPU cycles</b>     | 40 | 46        | ... | 46         |
| <i>Inputs</i>         |    |           |     |            |
| <b>In (DSP)</b>       | 0  | 429496730 | ... | -429496730 |
| <b>In</b>             | 0  | 0.2       | ... | -0.2       |
| <i>Outputs</i>        |    |           |     |            |
| <b>Out</b>            | 0  | 1         | ... | 1          |
| <b>Exp. Out</b>       | 0  | 1         | ... | 1          |
| <b>Out (DSP)</b>      | 0  | 1         | ... | 1          |
| <b>Exp. Out (DSP)</b> | 0  | 1         | ... | 1          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 40 |
| Max CPU cycles  | 46 |
| Avg CPU cycles  | 45 |

## Block: uConstant

---



Constant value.

| Outputs |                 |
|---------|-----------------|
| Out     | Constant output |

| Mask Parameters |    |                 |
|-----------------|----|-----------------|
| Name            | ID | Description     |
| Value           | 1  | Constant factor |

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>Bool</b>    | Boolean Integration                  |
| <b>Int8</b>    | 8 Bit Integer Implementation         |
| <b>Int16</b>   | 16 Bit Integer Implementation        |
| <b>Int32</b>   | 32 Bit Integer Implementation        |
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: Bool

---

Boolean Integration

| Outputs Data Type |      |
|-------------------|------|
| Out               | bool |

### Implementation: Int8

---

8 Bit Integer Implementation

| Outputs Data Type |      |
|-------------------|------|
| Out               | int8 |

### Implementation: Int16

---

16 Bit Integer Implementation

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: Int32

32 Bit Integer Implementation

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: FiP8

8 Bit Fixed Point Implementation

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

16 Bit Fixed Point Implementation

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

## Implementation: Float64

---

64 Bit Floating Point Implementation

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: uConstant Bool CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results                 |   |    |   |     |     |  |      |
|------------------------------|---|----|---|-----|-----|--|------|
| <b>Time step</b>             | 1 | 2  | 3 | 4   | ... |  | 7    |
| <i>Mask parameters</i>       |   |    |   |     |     |  |      |
| <b>Value</b>                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| <i>Controller parameters</i> |   |    |   |     |     |  |      |
| <b>K</b>                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| <b>Exp. K</b>                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results                 |   |    |   |     |     |  |      |
|------------------------------|---|----|---|-----|-----|--|------|
| <b>Time step</b>             | 1 | 2  | 3 | 4   | ... |  | 7    |
| <i>Mask parameters</i>       |   |    |   |     |     |  |      |
| <b>Value</b>                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| <i>Controller parameters</i> |   |    |   |     |     |  |      |
| <b>K</b>                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| <b>Exp. K</b>                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 787 |
| Max CPU cycles  | 817 |
| Avg CPU cycles  | 812 |

**Verification: uConstant Bool CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results                 |   |    |   |     |     |  |      |
|------------------------------|---|----|---|-----|-----|--|------|
| <b>Time step</b>             | 1 | 2  | 3 | 4   | ... |  | 7    |
| <i>Mask parameters</i>       |   |    |   |     |     |  |      |
| <b>Value</b>                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| <i>Controller parameters</i> |   |    |   |     |     |  |      |
| <b>K</b>                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| <b>Exp. K</b>                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results                 |   |    |   |     |     |  |      |
|------------------------------|---|----|---|-----|-----|--|------|
| <b>Time step</b>             | 1 | 2  | 3 | 4   | ... |  | 7    |
| <i>Mask parameters</i>       |   |    |   |     |     |  |      |
| <b>Value</b>                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| <i>Controller parameters</i> |   |    |   |     |     |  |      |
| <b>K</b>                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| <b>Exp. K</b>                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 373 |
| Max CPU cycles  | 399 |
| Avg CPU cycles  | 393 |



**Verification: uConstant Bool CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results                 |   |    |   |     |     |  |      |
|------------------------------|---|----|---|-----|-----|--|------|
| <b>Time step</b>             | 1 | 2  | 3 | 4   | ... |  | 7    |
| <i>Mask parameters</i>       |   |    |   |     |     |  |      |
| <b>Value</b>                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| <i>Controller parameters</i> |   |    |   |     |     |  |      |
| <b>K</b>                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| <b>Exp. K</b>                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results                 |   |    |   |     |     |  |      |
|------------------------------|---|----|---|-----|-----|--|------|
| <b>Time step</b>             | 1 | 2  | 3 | 4   | ... |  | 7    |
| <i>Mask parameters</i>       |   |    |   |     |     |  |      |
| <b>Value</b>                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| <i>Controller parameters</i> |   |    |   |     |     |  |      |
| <b>K</b>                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| <b>Exp. K</b>                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 514 |
| Max CPU cycles  | 534 |
| Avg CPU cycles  | 531 |

**Verification: uConstant Bool CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results                 |   |    |   |     |     |  |      |
|------------------------------|---|----|---|-----|-----|--|------|
| <b>Time step</b>             | 1 | 2  | 3 | 4   | ... |  | 7    |
| <i>Mask parameters</i>       |   |    |   |     |     |  |      |
| <b>Value</b>                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| <i>Controller parameters</i> |   |    |   |     |     |  |      |
| <b>K</b>                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| <b>Exp. K</b>                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results                 |   |    |   |     |     |  |      |
|------------------------------|---|----|---|-----|-----|--|------|
| <b>Time step</b>             | 1 | 2  | 3 | 4   | ... |  | 7    |
| <i>Mask parameters</i>       |   |    |   |     |     |  |      |
| <b>Value</b>                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| <i>Controller parameters</i> |   |    |   |     |     |  |      |
| <b>K</b>                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| <b>Exp. K</b>                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 593 |
| Max CPU cycles  | 606 |
| Avg CPU cycles  | 594 |

**Verification: uConstant Bool CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results                 |   |    |   |     |     |  |      |
|------------------------------|---|----|---|-----|-----|--|------|
| <b>Time step</b>             | 1 | 2  | 3 | 4   | ... |  | 7    |
| <i>Mask parameters</i>       |   |    |   |     |     |  |      |
| <b>Value</b>                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| <i>Controller parameters</i> |   |    |   |     |     |  |      |
| <b>K</b>                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| <b>Exp. K</b>                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results                 |   |    |   |     |     |  |      |
|------------------------------|---|----|---|-----|-----|--|------|
| <b>Time step</b>             | 1 | 2  | 3 | 4   | ... |  | 7    |
| <i>Mask parameters</i>       |   |    |   |     |     |  |      |
| <b>Value</b>                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| <i>Controller parameters</i> |   |    |   |     |     |  |      |
| <b>K</b>                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| <b>Exp. K</b>                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 243 |
| Max CPU cycles  | 276 |
| Avg CPU cycles  | 265 |

**Verification: uConstant Bool CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results                 |   |    |   |     |     |  |      |
|------------------------------|---|----|---|-----|-----|--|------|
| <b>Time step</b>             | 1 | 2  | 3 | 4   | ... |  | 7    |
| <i>Mask parameters</i>       |   |    |   |     |     |  |      |
| <b>Value</b>                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| <i>Controller parameters</i> |   |    |   |     |     |  |      |
| <b>K</b>                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| <b>Exp. K</b>                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results                 |   |    |   |     |     |  |      |
|------------------------------|---|----|---|-----|-----|--|------|
| <b>Time step</b>             | 1 | 2  | 3 | 4   | ... |  | 7    |
| <i>Mask parameters</i>       |   |    |   |     |     |  |      |
| <b>Value</b>                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| <i>Controller parameters</i> |   |    |   |     |     |  |      |
| <b>K</b>                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| <b>Exp. K</b>                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 521 |
| Max CPU cycles  | 552 |
| Avg CPU cycles  | 528 |

**Verification: uConstant Bool CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results          |   |    |   |     |     |  |      |
|-----------------------|---|----|---|-----|-----|--|------|
| Time step             | 1 | 2  | 3 | 4   | ... |  | 7    |
| Mask parameters       |   |    |   |     |     |  |      |
| Value                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| Controller parameters |   |    |   |     |     |  |      |
| K                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| Exp. K                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results          |   |    |   |     |     |  |      |
|-----------------------|---|----|---|-----|-----|--|------|
| Time step             | 1 | 2  | 3 | 4   | ... |  | 7    |
| Mask parameters       |   |    |   |     |     |  |      |
| Value                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| Controller parameters |   |    |   |     |     |  |      |
| K                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| Exp. K                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 417 |
| Max CPU cycles  | 491 |
| Avg CPU cycles  | 434 |

**Verification: uConstant Bool CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results                 |   |    |   |     |     |  |      |
|------------------------------|---|----|---|-----|-----|--|------|
| <b>Time step</b>             | 1 | 2  | 3 | 4   | ... |  | 7    |
| <i>Mask parameters</i>       |   |    |   |     |     |  |      |
| <b>Value</b>                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| <i>Controller parameters</i> |   |    |   |     |     |  |      |
| <b>K</b>                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| <b>Exp. K</b>                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results                 |   |    |   |     |     |  |      |
|------------------------------|---|----|---|-----|-----|--|------|
| <b>Time step</b>             | 1 | 2  | 3 | 4   | ... |  | 7    |
| <i>Mask parameters</i>       |   |    |   |     |     |  |      |
| <b>Value</b>                 | 1 | -1 | 0 | 0.5 | ... |  | -2.3 |
| <i>Controller parameters</i> |   |    |   |     |     |  |      |
| <b>K</b>                     | 1 | 1  | 0 | 1   | ... |  | 1    |
| <b>Exp. K</b>                | 1 | 1  | 0 | 1   | ... |  | 1    |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 615 |
| Max CPU cycles  | 641 |
| Avg CPU cycles  | 637 |

**Verification: uConstant Int16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results          |       |       |       |       |     |        |
|-----------------------|-------|-------|-------|-------|-----|--------|
| Time step             | 1     | 2     | 3     | 4     | ... | 17     |
| Mask parameters       |       |       |       |       |     |        |
| Value                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| Controller parameters |       |       |       |       |     |        |
| K                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| Exp. K                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results          |       |       |       |       |     |        |
|-----------------------|-------|-------|-------|-------|-----|--------|
| Time step             | 1     | 2     | 3     | 4     | ... | 17     |
| Mask parameters       |       |       |       |       |     |        |
| Value                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| Controller parameters |       |       |       |       |     |        |
| K                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| Exp. K                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1188 |
| Max CPU cycles  | 1433 |
| Avg CPU cycles  | 1399 |

**Verification: uConstant Int16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results          |       |       |       |       |     |        |
|-----------------------|-------|-------|-------|-------|-----|--------|
| Time step             | 1     | 2     | 3     | 4     | ... | 17     |
| Mask parameters       |       |       |       |       |     |        |
| Value                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| Controller parameters |       |       |       |       |     |        |
| K                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| Exp. K                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results          |       |       |       |       |     |        |
|-----------------------|-------|-------|-------|-------|-----|--------|
| Time step             | 1     | 2     | 3     | 4     | ... | 17     |
| Mask parameters       |       |       |       |       |     |        |
| Value                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| Controller parameters |       |       |       |       |     |        |
| K                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| Exp. K                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 653 |
| Max CPU cycles  | 889 |
| Avg CPU cycles  | 842 |



**Verification: uConstant Int16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results          |       |       |       |       |     |        |
|-----------------------|-------|-------|-------|-------|-----|--------|
| Time step             | 1     | 2     | 3     | 4     | ... | 17     |
| Mask parameters       |       |       |       |       |     |        |
| Value                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| Controller parameters |       |       |       |       |     |        |
| K                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| Exp. K                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results          |       |       |       |       |     |        |
|-----------------------|-------|-------|-------|-------|-----|--------|
| Time step             | 1     | 2     | 3     | 4     | ... | 17     |
| Mask parameters       |       |       |       |       |     |        |
| Value                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| Controller parameters |       |       |       |       |     |        |
| K                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| Exp. K                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 860  |
| Max CPU cycles  | 1089 |
| Avg CPU cycles  | 1047 |

**Verification: uConstant Int16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results          |       |       |       |       |     |        |
|-----------------------|-------|-------|-------|-------|-----|--------|
| Time step             | 1     | 2     | 3     | 4     | ... | 17     |
| Mask parameters       |       |       |       |       |     |        |
| Value                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| Controller parameters |       |       |       |       |     |        |
| K                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| Exp. K                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results          |       |       |       |       |     |        |
|-----------------------|-------|-------|-------|-------|-----|--------|
| Time step             | 1     | 2     | 3     | 4     | ... | 17     |
| Mask parameters       |       |       |       |       |     |        |
| Value                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| Controller parameters |       |       |       |       |     |        |
| K                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| Exp. K                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 923  |
| Max CPU cycles  | 1246 |
| Avg CPU cycles  | 1199 |

**Verification: uConstant Int16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results          |       |       |       |       |     |        |
|-----------------------|-------|-------|-------|-------|-----|--------|
| Time step             | 1     | 2     | 3     | 4     | ... | 17     |
| Mask parameters       |       |       |       |       |     |        |
| Value                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| Controller parameters |       |       |       |       |     |        |
| K                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| Exp. K                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results          |       |       |       |       |     |        |
|-----------------------|-------|-------|-------|-------|-----|--------|
| Time step             | 1     | 2     | 3     | 4     | ... | 17     |
| Mask parameters       |       |       |       |       |     |        |
| Value                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| Controller parameters |       |       |       |       |     |        |
| K                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| Exp. K                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 399 |
| Max CPU cycles  | 473 |
| Avg CPU cycles  | 465 |

**Verification: uConstant Int16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results          |       |       |       |       |     |        |
|-----------------------|-------|-------|-------|-------|-----|--------|
| Time step             | 1     | 2     | 3     | 4     | ... | 17     |
| Mask parameters       |       |       |       |       |     |        |
| Value                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| Controller parameters |       |       |       |       |     |        |
| K                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| Exp. K                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results          |       |       |       |       |     |        |
|-----------------------|-------|-------|-------|-------|-----|--------|
| Time step             | 1     | 2     | 3     | 4     | ... | 17     |
| Mask parameters       |       |       |       |       |     |        |
| Value                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| Controller parameters |       |       |       |       |     |        |
| K                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| Exp. K                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1300 |
| Max CPU cycles  | 1729 |
| Avg CPU cycles  | 1607 |

**Verification: uConstant Int16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results          |       |       |       |       |     |        |
|-----------------------|-------|-------|-------|-------|-----|--------|
| Time step             | 1     | 2     | 3     | 4     | ... | 17     |
| Mask parameters       |       |       |       |       |     |        |
| Value                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| Controller parameters |       |       |       |       |     |        |
| K                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| Exp. K                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results          |       |       |       |       |     |        |
|-----------------------|-------|-------|-------|-------|-----|--------|
| Time step             | 1     | 2     | 3     | 4     | ... | 17     |
| Mask parameters       |       |       |       |       |     |        |
| Value                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| Controller parameters |       |       |       |       |     |        |
| K                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| Exp. K                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 723  |
| Max CPU cycles  | 1023 |
| Avg CPU cycles  | 895  |

**Verification: uConstant Int16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results          |       |       |       |       |     |        |
|-----------------------|-------|-------|-------|-------|-----|--------|
| Time step             | 1     | 2     | 3     | 4     | ... | 17     |
| Mask parameters       |       |       |       |       |     |        |
| Value                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| Controller parameters |       |       |       |       |     |        |
| K                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| Exp. K                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results          |       |       |       |       |     |        |
|-----------------------|-------|-------|-------|-------|-----|--------|
| Time step             | 1     | 2     | 3     | 4     | ... | 17     |
| Mask parameters       |       |       |       |       |     |        |
| Value                 | 33000 | 32768 | 32767 | 32766 | ... | -33000 |
| Controller parameters |       |       |       |       |     |        |
| K                     | 32767 | 32767 | 32767 | 32766 | ... | -32767 |
| Exp. K                | 32767 | 32767 | 32767 | 32766 | ... | -32767 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1089 |
| Max CPU cycles  | 1465 |
| Avg CPU cycles  | 1401 |

**Verification: uConstant Int32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 3,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1210 |
| Max CPU cycles  | 1456 |
| Avg CPU cycles  | 1385 |

**Verification: uConstant Int32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 3,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 677 |
| Max CPU cycles  | 893 |
| Avg CPU cycles  | 859 |



**Verification: uConstant Int32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 3,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 869  |
| Max CPU cycles  | 1132 |
| Avg CPU cycles  | 1068 |

**Verification: uConstant Int32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 3,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 953  |
| Max CPU cycles  | 1269 |
| Avg CPU cycles  | 1227 |

**Verification: uConstant Int32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 3,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 395 |
| Max CPU cycles  | 475 |
| Avg CPU cycles  | 461 |

**Verification: uConstant Int32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 3,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1321 |
| Max CPU cycles  | 1731 |
| Avg CPU cycles  | 1611 |

**Verification: uConstant Int32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 3,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 698  |
| Max CPU cycles  | 1019 |
| Avg CPU cycles  | 874  |

**Verification: uConstant Int32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results          |            |            |     |             |
|-----------------------|------------|------------|-----|-------------|
| Time step             | 1          | 2          | ... | 17          |
| Mask parameters       |            |            |     |             |
| Value                 | 3300000000 | 2147483648 | ... | -3300000000 |
| Controller parameters |            |            |     |             |
| K                     | 2147483647 | 2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | 2147483647 | ... | -2147483647 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 3,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1112 |
| Max CPU cycles  | 1484 |
| Avg CPU cycles  | 1440 |

**Verification: uConstant FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results                 |       |        |   |       |     |        |
|------------------------------|-------|--------|---|-------|-----|--------|
| <b>Time step</b>             | 1     | 2      | 3 | 4     | ... | 7      |
| <i>Mask parameters</i>       |       |        |   |       |     |        |
| <b>Value</b>                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| <i>Controller parameters</i> |       |        |   |       |     |        |
| <b>K</b>                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| <b>Exp. K</b>                | 32767 | -32768 | 0 | 16384 | ... | -32768 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results                 |       |        |   |       |     |        |
|------------------------------|-------|--------|---|-------|-----|--------|
| <b>Time step</b>             | 1     | 2      | 3 | 4     | ... | 7      |
| <i>Mask parameters</i>       |       |        |   |       |     |        |
| <b>Value</b>                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| <i>Controller parameters</i> |       |        |   |       |     |        |
| <b>K</b>                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| <b>Exp. K</b>                | 32767 | -32768 | 0 | 16384 | ... | -32768 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 854 |
| Max CPU cycles  | 871 |
| Avg CPU cycles  | 856 |

**Verification: uConstant FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results                 |       |        |   |       |     |        |
|------------------------------|-------|--------|---|-------|-----|--------|
| <b>Time step</b>             | 1     | 2      | 3 | 4     | ... | 7      |
| <i>Mask parameters</i>       |       |        |   |       |     |        |
| <b>Value</b>                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| <i>Controller parameters</i> |       |        |   |       |     |        |
| <b>K</b>                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| <b>Exp. K</b>                | 32767 | -32768 | 0 | 16384 | ... | -32768 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results                 |       |        |   |       |     |        |
|------------------------------|-------|--------|---|-------|-----|--------|
| <b>Time step</b>             | 1     | 2      | 3 | 4     | ... | 7      |
| <i>Mask parameters</i>       |       |        |   |       |     |        |
| <b>Value</b>                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| <i>Controller parameters</i> |       |        |   |       |     |        |
| <b>K</b>                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| <b>Exp. K</b>                | 32767 | -32768 | 0 | 16384 | ... | -32768 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 401 |
| Max CPU cycles  | 407 |
| Avg CPU cycles  | 404 |



**Verification: uConstant FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results                 |       |        |   |       |     |        |
|------------------------------|-------|--------|---|-------|-----|--------|
| <b>Time step</b>             | 1     | 2      | 3 | 4     | ... | 7      |
| <i>Mask parameters</i>       |       |        |   |       |     |        |
| <b>Value</b>                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| <i>Controller parameters</i> |       |        |   |       |     |        |
| <b>K</b>                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| <b>Exp. K</b>                | 32767 | -32768 | 0 | 16384 | ... | -32768 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results                 |       |        |   |       |     |        |
|------------------------------|-------|--------|---|-------|-----|--------|
| <b>Time step</b>             | 1     | 2      | 3 | 4     | ... | 7      |
| <i>Mask parameters</i>       |       |        |   |       |     |        |
| <b>Value</b>                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| <i>Controller parameters</i> |       |        |   |       |     |        |
| <b>K</b>                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| <b>Exp. K</b>                | 32767 | -32768 | 0 | 16384 | ... | -32768 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 520 |
| Max CPU cycles  | 520 |
| Avg CPU cycles  | 520 |

**Verification: uConstant FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results                 |       |        |   |       |     |        |
|------------------------------|-------|--------|---|-------|-----|--------|
| <b>Time step</b>             | 1     | 2      | 3 | 4     | ... | 7      |
| <i>Mask parameters</i>       |       |        |   |       |     |        |
| <b>Value</b>                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| <i>Controller parameters</i> |       |        |   |       |     |        |
| <b>K</b>                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| <b>Exp. K</b>                | 32767 | -32768 | 0 | 16384 | ... | -32768 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results                 |       |        |   |       |     |        |
|------------------------------|-------|--------|---|-------|-----|--------|
| <b>Time step</b>             | 1     | 2      | 3 | 4     | ... | 7      |
| <i>Mask parameters</i>       |       |        |   |       |     |        |
| <b>Value</b>                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| <i>Controller parameters</i> |       |        |   |       |     |        |
| <b>K</b>                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| <b>Exp. K</b>                | 32767 | -32768 | 0 | 16384 | ... | -32768 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 810 |
| Max CPU cycles  | 912 |
| Avg CPU cycles  | 890 |

**Verification: uConstant FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results                 |       |        |   |       |     |        |
|------------------------------|-------|--------|---|-------|-----|--------|
| <b>Time step</b>             | 1     | 2      | 3 | 4     | ... | 7      |
| <i>Mask parameters</i>       |       |        |   |       |     |        |
| <b>Value</b>                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| <i>Controller parameters</i> |       |        |   |       |     |        |
| <b>K</b>                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| <b>Exp. K</b>                | 32767 | -32768 | 0 | 16384 | ... | -32768 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results                 |       |        |   |       |     |        |
|------------------------------|-------|--------|---|-------|-----|--------|
| <b>Time step</b>             | 1     | 2      | 3 | 4     | ... | 7      |
| <i>Mask parameters</i>       |       |        |   |       |     |        |
| <b>Value</b>                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| <i>Controller parameters</i> |       |        |   |       |     |        |
| <b>K</b>                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| <b>Exp. K</b>                | 32767 | -32768 | 0 | 16384 | ... | -32768 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 384 |
| Max CPU cycles  | 405 |
| Avg CPU cycles  | 401 |

**Verification: uConstant FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results                 |       |        |   |       |     |        |
|------------------------------|-------|--------|---|-------|-----|--------|
| <b>Time step</b>             | 1     | 2      | 3 | 4     | ... | 7      |
| <i>Mask parameters</i>       |       |        |   |       |     |        |
| <b>Value</b>                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| <i>Controller parameters</i> |       |        |   |       |     |        |
| <b>K</b>                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| <b>Exp. K</b>                | 32767 | -32768 | 0 | 16384 | ... | -32768 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results                 |       |        |   |       |     |        |
|------------------------------|-------|--------|---|-------|-----|--------|
| <b>Time step</b>             | 1     | 2      | 3 | 4     | ... | 7      |
| <i>Mask parameters</i>       |       |        |   |       |     |        |
| <b>Value</b>                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| <i>Controller parameters</i> |       |        |   |       |     |        |
| <b>K</b>                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| <b>Exp. K</b>                | 32767 | -32768 | 0 | 16384 | ... | -32768 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 839  |
| Max CPU cycles  | 1291 |
| Avg CPU cycles  | 1219 |

**Verification: uConstant FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results                 |       |        |   |       |     |        |
|------------------------------|-------|--------|---|-------|-----|--------|
| <b>Time step</b>             | 1     | 2      | 3 | 4     | ... | 7      |
| <i>Mask parameters</i>       |       |        |   |       |     |        |
| <b>Value</b>                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| <i>Controller parameters</i> |       |        |   |       |     |        |
| <b>K</b>                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| <b>Exp. K</b>                | 32767 | -32768 | 0 | 16384 | ... | -32768 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results                 |       |        |   |       |     |        |
|------------------------------|-------|--------|---|-------|-----|--------|
| <b>Time step</b>             | 1     | 2      | 3 | 4     | ... | 7      |
| <i>Mask parameters</i>       |       |        |   |       |     |        |
| <b>Value</b>                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| <i>Controller parameters</i> |       |        |   |       |     |        |
| <b>K</b>                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| <b>Exp. K</b>                | 32767 | -32768 | 0 | 16384 | ... | -32768 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 397 |
| Max CPU cycles  | 473 |
| Avg CPU cycles  | 409 |

**Verification: uConstant FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results                 |       |        |   |       |     |        |
|------------------------------|-------|--------|---|-------|-----|--------|
| <b>Time step</b>             | 1     | 2      | 3 | 4     | ... | 7      |
| <i>Mask parameters</i>       |       |        |   |       |     |        |
| <b>Value</b>                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| <i>Controller parameters</i> |       |        |   |       |     |        |
| <b>K</b>                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| <b>Exp. K</b>                | 32767 | -32768 | 0 | 16384 | ... | -32768 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results                 |       |        |   |       |     |        |
|------------------------------|-------|--------|---|-------|-----|--------|
| <b>Time step</b>             | 1     | 2      | 3 | 4     | ... | 7      |
| <i>Mask parameters</i>       |       |        |   |       |     |        |
| <b>Value</b>                 | 1     | -1     | 0 | 0.5   | ... | -2.3   |
| <i>Controller parameters</i> |       |        |   |       |     |        |
| <b>K</b>                     | 32767 | -32767 | 0 | 16384 | ... | -32767 |
| <b>Exp. K</b>                | 32767 | -32768 | 0 | 16384 | ... | -32768 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 661 |
| Max CPU cycles  | 665 |
| Avg CPU cycles  | 662 |

**Verification: uConstant FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results                 |            |             |     |             |
|------------------------------|------------|-------------|-----|-------------|
| <b>Time step</b>             | 1          | 2           | ... | 7           |
| <i>Mask parameters</i>       |            |             |     |             |
| <b>Value</b>                 | 1          | -1          | ... | -2.3        |
| <i>Controller parameters</i> |            |             |     |             |
| <b>K</b>                     | 2147483647 | -2147483647 | ... | -2147483647 |
| <b>Exp. K</b>                | 2147483647 | -2147483648 | ... | -2147483648 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results                 |            |             |     |             |
|------------------------------|------------|-------------|-----|-------------|
| <b>Time step</b>             | 1          | 2           | ... | 7           |
| <i>Mask parameters</i>       |            |             |     |             |
| <b>Value</b>                 | 1          | -1          | ... | -2.3        |
| <i>Controller parameters</i> |            |             |     |             |
| <b>K</b>                     | 2147483647 | -2147483647 | ... | -2147483647 |
| <b>Exp. K</b>                | 2147483647 | -2147483648 | ... | -2147483648 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1026 |
| Max CPU cycles  | 1093 |
| Avg CPU cycles  | 1063 |

**Verification: uConstant FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results                 |            |             |     |             |
|------------------------------|------------|-------------|-----|-------------|
| <b>Time step</b>             | 1          | 2           | ... | 7           |
| <i>Mask parameters</i>       |            |             |     |             |
| <b>Value</b>                 | 1          | -1          | ... | -2.3        |
| <i>Controller parameters</i> |            |             |     |             |
| <b>K</b>                     | 2147483647 | -2147483647 | ... | -2147483647 |
| <b>Exp. K</b>                | 2147483647 | -2147483648 | ... | -2147483648 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results                 |            |             |     |             |
|------------------------------|------------|-------------|-----|-------------|
| <b>Time step</b>             | 1          | 2           | ... | 7           |
| <i>Mask parameters</i>       |            |             |     |             |
| <b>Value</b>                 | 1          | -1          | ... | -2.3        |
| <i>Controller parameters</i> |            |             |     |             |
| <b>K</b>                     | 2147483647 | -2147483647 | ... | -2147483647 |
| <b>Exp. K</b>                | 2147483647 | -2147483648 | ... | -2147483648 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 457 |
| Max CPU cycles  | 485 |
| Avg CPU cycles  | 477 |



**Verification: uConstant FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results                 |            |             |     |             |
|------------------------------|------------|-------------|-----|-------------|
| <b>Time step</b>             | 1          | 2           | ... | 7           |
| <i>Mask parameters</i>       |            |             |     |             |
| <b>Value</b>                 | 1          | -1          | ... | -2.3        |
| <i>Controller parameters</i> |            |             |     |             |
| <b>K</b>                     | 2147483647 | -2147483647 | ... | -2147483647 |
| <b>Exp. K</b>                | 2147483647 | -2147483648 | ... | -2147483648 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results                 |            |             |     |             |
|------------------------------|------------|-------------|-----|-------------|
| <b>Time step</b>             | 1          | 2           | ... | 7           |
| <i>Mask parameters</i>       |            |             |     |             |
| <b>Value</b>                 | 1          | -1          | ... | -2.3        |
| <i>Controller parameters</i> |            |             |     |             |
| <b>K</b>                     | 2147483647 | -2147483647 | ... | -2147483647 |
| <b>Exp. K</b>                | 2147483647 | -2147483648 | ... | -2147483648 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 929  |
| Max CPU cycles  | 1174 |
| Avg CPU cycles  | 1026 |

**Verification: uConstant FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results                 |            |             |     |             |
|------------------------------|------------|-------------|-----|-------------|
| <b>Time step</b>             | 1          | 2           | ... | 7           |
| <i>Mask parameters</i>       |            |             |     |             |
| <b>Value</b>                 | 1          | -1          | ... | -2.3        |
| <i>Controller parameters</i> |            |             |     |             |
| <b>K</b>                     | 2147483647 | -2147483647 | ... | -2147483647 |
| <b>Exp. K</b>                | 2147483647 | -2147483648 | ... | -2147483648 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results                 |            |             |     |             |
|------------------------------|------------|-------------|-----|-------------|
| <b>Time step</b>             | 1          | 2           | ... | 7           |
| <i>Mask parameters</i>       |            |             |     |             |
| <b>Value</b>                 | 1          | -1          | ... | -2.3        |
| <i>Controller parameters</i> |            |             |     |             |
| <b>K</b>                     | 2147483647 | -2147483647 | ... | -2147483647 |
| <b>Exp. K</b>                | 2147483647 | -2147483648 | ... | -2147483648 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1819 |
| Max CPU cycles  | 2575 |
| Avg CPU cycles  | 2263 |

**Verification: uConstant FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results                 |            |             |     |             |
|------------------------------|------------|-------------|-----|-------------|
| <b>Time step</b>             | 1          | 2           | ... | 7           |
| <i>Mask parameters</i>       |            |             |     |             |
| <b>Value</b>                 | 1          | -1          | ... | -2.3        |
| <i>Controller parameters</i> |            |             |     |             |
| <b>K</b>                     | 2147483647 | -2147483647 | ... | -2147483647 |
| <b>Exp. K</b>                | 2147483647 | -2147483648 | ... | -2147483648 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results                 |            |             |     |             |
|------------------------------|------------|-------------|-----|-------------|
| <b>Time step</b>             | 1          | 2           | ... | 7           |
| <i>Mask parameters</i>       |            |             |     |             |
| <b>Value</b>                 | 1          | -1          | ... | -2.3        |
| <i>Controller parameters</i> |            |             |     |             |
| <b>K</b>                     | 2147483647 | -2147483647 | ... | -2147483647 |
| <b>Exp. K</b>                | 2147483647 | -2147483648 | ... | -2147483648 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 729 |
| Max CPU cycles  | 922 |
| Avg CPU cycles  | 837 |

**Verification: uConstant FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results          |            |             |     |             |
|-----------------------|------------|-------------|-----|-------------|
| Time step             | 1          | 2           | ... | 7           |
| Mask parameters       |            |             |     |             |
| Value                 | 1          | -1          | ... | -2.3        |
| Controller parameters |            |             |     |             |
| K                     | 2147483647 | -2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | -2147483648 | ... | -2147483648 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results          |            |             |     |             |
|-----------------------|------------|-------------|-----|-------------|
| Time step             | 1          | 2           | ... | 7           |
| Mask parameters       |            |             |     |             |
| Value                 | 1          | -1          | ... | -2.3        |
| Controller parameters |            |             |     |             |
| K                     | 2147483647 | -2147483647 | ... | -2147483647 |
| Exp. K                | 2147483647 | -2147483648 | ... | -2147483648 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1155 |
| Max CPU cycles  | 1629 |
| Avg CPU cycles  | 1552 |

**Verification: uConstant FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results                 |            |             |     |             |
|------------------------------|------------|-------------|-----|-------------|
| <b>Time step</b>             | 1          | 2           | ... | 7           |
| <i>Mask parameters</i>       |            |             |     |             |
| <b>Value</b>                 | 1          | -1          | ... | -2.3        |
| <i>Controller parameters</i> |            |             |     |             |
| <b>K</b>                     | 2147483647 | -2147483647 | ... | -2147483647 |
| <b>Exp. K</b>                | 2147483647 | -2147483648 | ... | -2147483648 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results                 |            |             |     |             |
|------------------------------|------------|-------------|-----|-------------|
| <b>Time step</b>             | 1          | 2           | ... | 7           |
| <i>Mask parameters</i>       |            |             |     |             |
| <b>Value</b>                 | 1          | -1          | ... | -2.3        |
| <i>Controller parameters</i> |            |             |     |             |
| <b>K</b>                     | 2147483647 | -2147483647 | ... | -2147483647 |
| <b>Exp. K</b>                | 2147483647 | -2147483648 | ... | -2147483648 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 667 |
| Max CPU cycles  | 862 |
| Avg CPU cycles  | 747 |

**Verification: uConstant FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results                 |            |             |     |             |
|------------------------------|------------|-------------|-----|-------------|
| <b>Time step</b>             | 1          | 2           | ... | 7           |
| <i>Mask parameters</i>       |            |             |     |             |
| <b>Value</b>                 | 1          | -1          | ... | -2.3        |
| <i>Controller parameters</i> |            |             |     |             |
| <b>K</b>                     | 2147483647 | -2147483647 | ... | -2147483647 |
| <b>Exp. K</b>                | 2147483647 | -2147483648 | ... | -2147483648 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results                 |            |             |     |             |
|------------------------------|------------|-------------|-----|-------------|
| <b>Time step</b>             | 1          | 2           | ... | 7           |
| <i>Mask parameters</i>       |            |             |     |             |
| <b>Value</b>                 | 1          | -1          | ... | -2.3        |
| <i>Controller parameters</i> |            |             |     |             |
| <b>K</b>                     | 2147483647 | -2147483647 | ... | -2147483647 |
| <b>Exp. K</b>                | 2147483647 | -2147483648 | ... | -2147483648 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 1,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 801 |
| Max CPU cycles  | 847 |
| Avg CPU cycles  | 824 |

**Verification: uConstant Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 5,0000e-08$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1058 |
| Max CPU cycles  | 1087 |
| Avg CPU cycles  | 1067 |

**Verification: uConstant Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 5,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 519 |
| Max CPU cycles  | 535 |
| Avg CPU cycles  | 532 |



**Verification: uConstant Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 5,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 741 |
| Max CPU cycles  | 741 |
| Avg CPU cycles  | 741 |

**Verification: uConstant Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 5,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 921 |
| Max CPU cycles  | 968 |
| Avg CPU cycles  | 951 |

**Verification: uConstant Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 5,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 387 |
| Max CPU cycles  | 390 |
| Avg CPU cycles  | 388 |

**Verification: uConstant Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 5,0000e-08$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 787  |
| Max CPU cycles  | 1096 |
| Avg CPU cycles  | 1051 |

**Verification: uConstant Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 5,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 579 |
| Max CPU cycles  | 672 |
| Avg CPU cycles  | 593 |

**Verification: uConstant Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Conversion test****OK**

Conversion test for General block uConstant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test****OK**

Conversion-on-Target test for General block uConstant.

| Test results                 |   |    |     |      |
|------------------------------|---|----|-----|------|
| <b>Time step</b>             | 1 | 2  | ... | 7    |
| <i>Mask parameters</i>       |   |    |     |      |
| <b>Value</b>                 | 1 | -1 | ... | -2.3 |
| <i>Controller parameters</i> |   |    |     |      |
| <b>K</b>                     | 1 | -1 | ... | -2.3 |
| <b>Exp. K</b>                | 1 | -1 | ... | -2.3 |

| Test settings |                  |
|---------------|------------------|
| Tolerance K   | $\pm 5,0000e-08$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 817 |
| Max CPU cycles  | 826 |
| Avg CPU cycles  | 820 |

## Block: uGain

---



Amplification of input by gain factor with output wrapping.

| Inports |       |
|---------|-------|
| In      | Input |

| Outports |                 |
|----------|-----------------|
| Out      | Amplified input |

| Mask Parameters |    |                                      |
|-----------------|----|--------------------------------------|
| Name            | ID | Description                          |
| Gain            | 1  | Gain factor in floating point format |

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | int8 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |



**Verification: uGain FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block uGain.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 107   |
| CPU cycles     | 59     | 59     | 59     | 59     | ... | 59    |
| Inputs         |        |        |        |        |     |       |
| In (DSP)       | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| In             | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| Parameters     |        |        |        |        |     |       |
| Gain           | 2.1    |        |        |        |     |       |
| Outputs        |        |        |        |        |     |       |
| Out            | -0.1   | -0.06  | -0.021 | 0.019  | ... | 0.1   |
| Exp. Out       | -0.1   | -0.06  | -0.021 | 0.019  | ... | 0.1   |
| Out (DSP)      | -3276  | -1979  | -679   | 619    | ... | 3273  |
| Exp. Out (DSP) | -3277  | -1978  | -680   | 618    | ... | 3277  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,2207e-04$ ( $\pm 4$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 59 |
| Avg CPU cycles  | 59 |

**Test case: Parameter test****OK**

Parameter test for General block uGain.

| Test results   |       |       |       |        |     |        |
|----------------|-------|-------|-------|--------|-----|--------|
| Time step      | 1     | 2     | 3     | 4      | ... | 107    |
| CPU cycles     | 59    | 59    | 59    | 59     | ... | 59     |
| Inputs         |       |       |       |        |     |        |
| In (DSP)       | 13107 |       |       |        |     |        |
| In             | 0.4   |       |       |        |     |        |
| Parameters     |       |       |       |        |     |        |
| Gain           | -3.7  | -3.63 | -3.56 | -3.491 | ... | 3.7    |
| Outputs        |       |       |       |        |     |        |
| Out            | 0.52  | 0.548 | 0.576 | 0.604  | ... | -0.52  |
| Exp. Out       | 0.52  | 0.548 | 0.576 | 0.604  | ... | -0.52  |
| Out (DSP)      | 17040 | 17954 | 18869 | 19784  | ... | -17041 |
| Exp. Out (DSP) | 17039 | 17954 | 18869 | 19784  | ... | -17039 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,1553e-05$ ( $\pm 3$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 59 |
| Avg CPU cycles  | 59 |

### Test case: Conversion test

OK

Conversion test for General block uGain.

| Test results                 |        |        |        |        |     |       |
|------------------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |        |        |        |     |       |
| <b>Gain</b>                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| <i>Controller parameters</i> |        |        |        |        |     |       |
| <b>V</b>                     | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>sfr</b>                   | 11     | 11     | 11     | 11     | ... | 11    |
| <b>Exp. V</b>                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>Exp. sfr</b>              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block uGain.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| Time step             | 1      | 2      | 3      | 4      | ... | 37    |
| Mask parameters       |        |        |        |        |     |       |
| Gain                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| Controller parameters |        |        |        |        |     |       |
| V                     | -20480 | -19342 | -18204 | -17066 | ... | 20480 |
| sfr                   | 11     | 11     | 11     | 11     | ... | 11    |
| Exp. V                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| Exp. sfr              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1502 |
| Max CPU cycles  | 3610 |
| Avg CPU cycles  | 2862 |

**Verification: uGain FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block uGain.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 107   |
| CPU cycles     | 27     | 27     | 27     | 27     | ... | 27    |
| Inputs         |        |        |        |        |     |       |
| In (DSP)       | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| In             | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| Parameters     |        |        |        |        |     |       |
| Gain           | 2.1    |        |        |        |     |       |
| Outputs        |        |        |        |        |     |       |
| Out            | -0.1   | -0.06  | -0.021 | 0.019  | ... | 0.1   |
| Exp. Out       | -0.1   | -0.06  | -0.021 | 0.019  | ... | 0.1   |
| Out (DSP)      | -3276  | -1979  | -679   | 619    | ... | 3273  |
| Exp. Out (DSP) | -3277  | -1978  | -680   | 618    | ... | 3277  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,2207e-04$ ( $\pm 4$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 27 |
| Max CPU cycles  | 27 |
| Avg CPU cycles  | 27 |

**Test case: Parameter test****OK**

Parameter test for General block uGain.

| Test results   |       |       |       |        |     |        |
|----------------|-------|-------|-------|--------|-----|--------|
| Time step      | 1     | 2     | 3     | 4      | ... | 107    |
| CPU cycles     | 27    | 27    | 27    | 27     | ... | 27     |
| Inputs         |       |       |       |        |     |        |
| In (DSP)       | 13107 |       |       |        |     |        |
| In             | 0.4   |       |       |        |     |        |
| Parameters     |       |       |       |        |     |        |
| Gain           | -3.7  | -3.63 | -3.56 | -3.491 | ... | 3.7    |
| Outputs        |       |       |       |        |     |        |
| Out            | 0.52  | 0.548 | 0.576 | 0.604  | ... | -0.52  |
| Exp. Out       | 0.52  | 0.548 | 0.576 | 0.604  | ... | -0.52  |
| Out (DSP)      | 17040 | 17954 | 18869 | 19784  | ... | -17041 |
| Exp. Out (DSP) | 17039 | 17954 | 18869 | 19784  | ... | -17039 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,1553e-05$ ( $\pm 3$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 27 |
| Max CPU cycles  | 27 |
| Avg CPU cycles  | 27 |

### Test case: Conversion test

OK

Conversion test for General block uGain.

| Test results                 |        |        |        |        |     |       |
|------------------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |        |        |        |     |       |
| <b>Gain</b>                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| <i>Controller parameters</i> |        |        |        |        |     |       |
| <b>V</b>                     | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>sfr</b>                   | 11     | 11     | 11     | 11     | ... | 11    |
| <b>Exp. V</b>                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>Exp. sfr</b>              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block uGain.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| Time step             | 1      | 2      | 3      | 4      | ... | 37    |
| Mask parameters       |        |        |        |        |     |       |
| Gain                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| Controller parameters |        |        |        |        |     |       |
| V                     | -20480 | -19342 | -18204 | -17066 | ... | 20480 |
| sfr                   | 11     | 11     | 11     | 11     | ... | 11    |
| Exp. V                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| Exp. sfr              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 771  |
| Max CPU cycles  | 2031 |
| Avg CPU cycles  | 1585 |

**Verification: uGain FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block uGain.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 107   |
| CPU cycles     | 57     | 57     | 57     | 57     | ... | 57    |
| Inputs         |        |        |        |        |     |       |
| In (DSP)       | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| In             | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| Parameters     |        |        |        |        |     |       |
| Gain           | 2.1    |        |        |        |     |       |
| Outputs        |        |        |        |        |     |       |
| Out            | -0.1   | -0.06  | -0.021 | 0.019  | ... | 0.1   |
| Exp. Out       | -0.1   | -0.06  | -0.021 | 0.019  | ... | 0.1   |
| Out (DSP)      | -3276  | -1979  | -679   | 619    | ... | 3273  |
| Exp. Out (DSP) | -3277  | -1978  | -680   | 618    | ... | 3277  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,2207e-04$ ( $\pm 4$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 57 |

**Test case: Parameter test****OK**

Parameter test for General block uGain.

| Test results   |       |       |       |        |     |        |
|----------------|-------|-------|-------|--------|-----|--------|
| Time step      | 1     | 2     | 3     | 4      | ... | 107    |
| CPU cycles     | 57    | 57    | 57    | 57     | ... | 57     |
| Inputs         |       |       |       |        |     |        |
| In (DSP)       | 13107 |       |       |        |     |        |
| In             | 0.4   |       |       |        |     |        |
| Parameters     |       |       |       |        |     |        |
| Gain           | -3.7  | -3.63 | -3.56 | -3.491 | ... | 3.7    |
| Outputs        |       |       |       |        |     |        |
| Out            | 0.52  | 0.548 | 0.576 | 0.604  | ... | -0.52  |
| Exp. Out       | 0.52  | 0.548 | 0.576 | 0.604  | ... | -0.52  |
| Out (DSP)      | 17040 | 17954 | 18869 | 19784  | ... | -17041 |
| Exp. Out (DSP) | 17039 | 17954 | 18869 | 19784  | ... | -17039 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,1553e-05$ ( $\pm 3$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 57 |

### Test case: Conversion test

OK

Conversion test for General block uGain.

| Test results                 |        |        |        |        |     |       |
|------------------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |        |        |        |     |       |
| <b>Gain</b>                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| <i>Controller parameters</i> |        |        |        |        |     |       |
| <b>V</b>                     | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>sfr</b>                   | 11     | 11     | 11     | 11     | ... | 11    |
| <b>Exp. V</b>                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>Exp. sfr</b>              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |



**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block uGain.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| Time step             | 1      | 2      | 3      | 4      | ... | 37    |
| Mask parameters       |        |        |        |        |     |       |
| Gain                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| Controller parameters |        |        |        |        |     |       |
| V                     | -20480 | -19342 | -18204 | -17066 | ... | 20480 |
| sfr                   | 11     | 11     | 11     | 11     | ... | 11    |
| Exp. V                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| Exp. sfr              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 963  |
| Max CPU cycles  | 1486 |
| Avg CPU cycles  | 1301 |

**Verification: uGain FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block uGain.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 107   |
| CPU cycles     | 54     | 54     | 54     | 54     | ... | 54    |
| Inputs         |        |        |        |        |     |       |
| In (DSP)       | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| In             | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| Parameters     |        |        |        |        |     |       |
| Gain           | 2.1    |        |        |        |     |       |
| Outputs        |        |        |        |        |     |       |
| Out            | -0.1   | -0.06  | -0.021 | 0.019  | ... | 0.1   |
| Exp. Out       | -0.1   | -0.06  | -0.021 | 0.019  | ... | 0.1   |
| Out (DSP)      | -3276  | -1979  | -679   | 619    | ... | 3273  |
| Exp. Out (DSP) | -3277  | -1978  | -680   | 618    | ... | 3277  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,2207e-04$ ( $\pm 4$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 54  |
| Max CPU cycles  | 114 |
| Avg CPU cycles  | 54  |

**Test case: Parameter test****OK**

Parameter test for General block uGain.

| Test results   |       |       |       |        |     |        |
|----------------|-------|-------|-------|--------|-----|--------|
| Time step      | 1     | 2     | 3     | 4      | ... | 107    |
| CPU cycles     | 54    | 54    | 54    | 54     | ... | 54     |
| Inputs         |       |       |       |        |     |        |
| In (DSP)       | 13107 |       |       |        |     |        |
| In             | 0.4   |       |       |        |     |        |
| Parameters     |       |       |       |        |     |        |
| Gain           | -3.7  | -3.63 | -3.56 | -3.491 | ... | 3.7    |
| Outputs        |       |       |       |        |     |        |
| Out            | 0.52  | 0.548 | 0.576 | 0.604  | ... | -0.52  |
| Exp. Out       | 0.52  | 0.548 | 0.576 | 0.604  | ... | -0.52  |
| Out (DSP)      | 17040 | 17954 | 18869 | 19784  | ... | -17041 |
| Exp. Out (DSP) | 17039 | 17954 | 18869 | 19784  | ... | -17039 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,1553e-05$ ( $\pm 3$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 54 |
| Max CPU cycles  | 54 |
| Avg CPU cycles  | 54 |

### Test case: Conversion test

OK

Conversion test for General block uGain.

| Test results                 |        |        |        |        |     |       |
|------------------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |        |        |        |     |       |
| <b>Gain</b>                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| <i>Controller parameters</i> |        |        |        |        |     |       |
| <b>V</b>                     | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>sfr</b>                   | 11     | 11     | 11     | 11     | ... | 11    |
| <b>Exp. V</b>                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>Exp. sfr</b>              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block uGain.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| Time step             | 1      | 2      | 3      | 4      | ... | 37    |
| Mask parameters       |        |        |        |        |     |       |
| Gain                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| Controller parameters |        |        |        |        |     |       |
| V                     | -20480 | -19342 | -18204 | -17066 | ... | 20480 |
| sfr                   | 11     | 11     | 11     | 11     | ... | 11    |
| Exp. V                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| Exp. sfr              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1708 |
| Max CPU cycles  | 4649 |
| Avg CPU cycles  | 3707 |

**Verification: uGain FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block uGain.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 107   |
| CPU cycles     | 35     | 35     | 35     | 35     | ... | 35    |
| Inputs         |        |        |        |        |     |       |
| In (DSP)       | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| In             | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| Parameters     |        |        |        |        |     |       |
| Gain           | 2.1    |        |        |        |     |       |
| Outputs        |        |        |        |        |     |       |
| Out            | -0.1   | -0.06  | -0.021 | 0.019  | ... | 0.1   |
| Exp. Out       | -0.1   | -0.06  | -0.021 | 0.019  | ... | 0.1   |
| Out (DSP)      | -3276  | -1979  | -679   | 619    | ... | 3273  |
| Exp. Out (DSP) | -3277  | -1978  | -680   | 618    | ... | 3277  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,2207e-04$ ( $\pm 4$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 35 |
| Max CPU cycles  | 35 |
| Avg CPU cycles  | 35 |

**Test case: Parameter test****OK**

Parameter test for General block uGain.

| Test results   |       |       |       |        |     |        |
|----------------|-------|-------|-------|--------|-----|--------|
| Time step      | 1     | 2     | 3     | 4      | ... | 107    |
| CPU cycles     | 35    | 35    | 35    | 35     | ... | 35     |
| Inputs         |       |       |       |        |     |        |
| In (DSP)       | 13107 |       |       |        |     |        |
| In             | 0.4   |       |       |        |     |        |
| Parameters     |       |       |       |        |     |        |
| Gain           | -3.7  | -3.63 | -3.56 | -3.491 | ... | 3.7    |
| Outputs        |       |       |       |        |     |        |
| Out            | 0.52  | 0.548 | 0.576 | 0.604  | ... | -0.52  |
| Exp. Out       | 0.52  | 0.548 | 0.576 | 0.604  | ... | -0.52  |
| Out (DSP)      | 17040 | 17954 | 18869 | 19784  | ... | -17041 |
| Exp. Out (DSP) | 17039 | 17954 | 18869 | 19784  | ... | -17039 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,1553e-05$ ( $\pm 3$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 35 |
| Max CPU cycles  | 35 |
| Avg CPU cycles  | 35 |

### Test case: Conversion test

OK

Conversion test for General block uGain.

| Test results                 |        |        |        |        |     |       |
|------------------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |        |        |        |     |       |
| <b>Gain</b>                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| <i>Controller parameters</i> |        |        |        |        |     |       |
| <b>V</b>                     | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>sfr</b>                   | 11     | 11     | 11     | 11     | ... | 11    |
| <b>Exp. V</b>                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>Exp. sfr</b>              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block uGain.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| Time step             | 1      | 2      | 3      | 4      | ... | 37    |
| Mask parameters       |        |        |        |        |     |       |
| Gain                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| Controller parameters |        |        |        |        |     |       |
| V                     | -20480 | -19342 | -18204 | -17066 | ... | 20480 |
| sfr                   | 11     | 11     | 11     | 11     | ... | 11    |
| Exp. V                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| Exp. sfr              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 815  |
| Max CPU cycles  | 1984 |
| Avg CPU cycles  | 1588 |

**Verification: uGain FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block uGain.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 107   |
| CPU cycles     | 54     | 54     | 54     | 54     | ... | 54    |
| Inputs         |        |        |        |        |     |       |
| In (DSP)       | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| In             | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| Parameters     |        |        |        |        |     |       |
| Gain           | 2.1    |        |        |        |     |       |
| Outputs        |        |        |        |        |     |       |
| Out            | -0.1   | -0.06  | -0.021 | 0.019  | ... | 0.1   |
| Exp. Out       | -0.1   | -0.06  | -0.021 | 0.019  | ... | 0.1   |
| Out (DSP)      | -3276  | -1979  | -679   | 619    | ... | 3273  |
| Exp. Out (DSP) | -3277  | -1978  | -680   | 618    | ... | 3277  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,2207e-04$ ( $\pm 4$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 54 |
| Max CPU cycles  | 54 |
| Avg CPU cycles  | 54 |

**Test case: Parameter test****OK**

Parameter test for General block uGain.



| Test results   |       |       |       |        |     |        |
|----------------|-------|-------|-------|--------|-----|--------|
| Time step      | 1     | 2     | 3     | 4      | ... | 107    |
| CPU cycles     | 54    | 54    | 54    | 54     | ... | 54     |
| Inputs         |       |       |       |        |     |        |
| In (DSP)       | 13107 |       |       |        |     |        |
| In             | 0.4   |       |       |        |     |        |
| Parameters     |       |       |       |        |     |        |
| Gain           | -3.7  | -3.63 | -3.56 | -3.491 | ... | 3.7    |
| Outputs        |       |       |       |        |     |        |
| Out            | 0.52  | 0.548 | 0.576 | 0.604  | ... | -0.52  |
| Exp. Out       | 0.52  | 0.548 | 0.576 | 0.604  | ... | -0.52  |
| Out (DSP)      | 17040 | 17954 | 18869 | 19784  | ... | -17041 |
| Exp. Out (DSP) | 17039 | 17954 | 18869 | 19784  | ... | -17039 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 9,1553\text{e-}05$ ( $\pm 3$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 54 |
| Max CPU cycles  | 54 |
| Avg CPU cycles  | 54 |

### Test case: Conversion test

OK

Conversion test for General block uGain.

| Test results                 |        |        |        |        |     |       |
|------------------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |        |        |        |     |       |
| <b>Gain</b>                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| <i>Controller parameters</i> |        |        |        |        |     |       |
| <b>V</b>                     | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>sfr</b>                   | 11     | 11     | 11     | 11     | ... | 11    |
| <b>Exp. V</b>                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>Exp. sfr</b>              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                         |
|---------------|-------------------------|
| Tolerance V   | $\pm 0,0000\text{e+}00$ |
| Tolerance sfr | $\pm 0,0000\text{e+}00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block uGain.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| Time step             | 1      | 2      | 3      | 4      | ... | 37    |
| Mask parameters       |        |        |        |        |     |       |
| Gain                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| Controller parameters |        |        |        |        |     |       |
| V                     | -20480 | -19342 | -18204 | -17066 | ... | 20480 |
| sfr                   | 11     | 11     | 11     | 11     | ... | 11    |
| Exp. V                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| Exp. sfr              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 2593  |
| Max CPU cycles  | 10879 |
| Avg CPU cycles  | 8317  |

**Verification: uGain FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block uGain.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 107   |
| CPU cycles     | 57     | 57     | 57     | 57     | ... | 57    |
| Inputs         |        |        |        |        |     |       |
| In (DSP)       | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| In             | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| Parameters     |        |        |        |        |     |       |
| Gain           | 2.1    |        |        |        |     |       |
| Outputs        |        |        |        |        |     |       |
| Out            | -0.1   | -0.06  | -0.021 | 0.019  | ... | 0.1   |
| Exp. Out       | -0.1   | -0.06  | -0.021 | 0.019  | ... | 0.1   |
| Out (DSP)      | -3276  | -1979  | -679   | 619    | ... | 3273  |
| Exp. Out (DSP) | -3277  | -1978  | -680   | 618    | ... | 3277  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,2207e-04$ ( $\pm 4$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 57 |

**Test case: Parameter test****OK**

Parameter test for General block uGain.

| Test results   |       |       |       |        |     |        |
|----------------|-------|-------|-------|--------|-----|--------|
| Time step      | 1     | 2     | 3     | 4      | ... | 107    |
| CPU cycles     | 57    | 57    | 57    | 57     | ... | 57     |
| Inputs         |       |       |       |        |     |        |
| In (DSP)       | 13107 |       |       |        |     |        |
| In             | 0.4   |       |       |        |     |        |
| Parameters     |       |       |       |        |     |        |
| Gain           | -3.7  | -3.63 | -3.56 | -3.491 | ... | 3.7    |
| Outputs        |       |       |       |        |     |        |
| Out            | 0.52  | 0.548 | 0.576 | 0.604  | ... | -0.52  |
| Exp. Out       | 0.52  | 0.548 | 0.576 | 0.604  | ... | -0.52  |
| Out (DSP)      | 17040 | 17954 | 18869 | 19784  | ... | -17041 |
| Exp. Out (DSP) | 17039 | 17954 | 18869 | 19784  | ... | -17039 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,1553e-05$ ( $\pm 3$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 57 |

### Test case: Conversion test

OK

Conversion test for General block uGain.

| Test results                 |        |        |        |        |     |       |
|------------------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |        |        |        |     |       |
| <b>Gain</b>                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| <i>Controller parameters</i> |        |        |        |        |     |       |
| <b>V</b>                     | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>sfr</b>                   | 11     | 11     | 11     | 11     | ... | 11    |
| <b>Exp. V</b>                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>Exp. sfr</b>              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block uGain.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| Time step             | 1      | 2      | 3      | 4      | ... | 37    |
| Mask parameters       |        |        |        |        |     |       |
| Gain                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| Controller parameters |        |        |        |        |     |       |
| V                     | -20480 | -19342 | -18204 | -17066 | ... | 20480 |
| sfr                   | 11     | 11     | 11     | 11     | ... | 11    |
| Exp. V                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| Exp. sfr              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 633  |
| Max CPU cycles  | 1274 |
| Avg CPU cycles  | 947  |

**Verification: uGain FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block uGain.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 107   |
| CPU cycles     | 39     | 39     | 39     | 39     | ... | 39    |
| Inputs         |        |        |        |        |     |       |
| In (DSP)       | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| In             | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| Parameters     |        |        |        |        |     |       |
| Gain           | 2.1    |        |        |        |     |       |
| Outputs        |        |        |        |        |     |       |
| Out            | -0.1   | -0.06  | -0.021 | 0.019  | ... | 0.1   |
| Exp. Out       | -0.1   | -0.06  | -0.021 | 0.019  | ... | 0.1   |
| Out (DSP)      | -3276  | -1979  | -679   | 619    | ... | 3273  |
| Exp. Out (DSP) | -3277  | -1978  | -680   | 618    | ... | 3277  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,2207e-04$ ( $\pm 4$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 39 |
| Max CPU cycles  | 39 |
| Avg CPU cycles  | 39 |

**Test case: Parameter test****OK**

Parameter test for General block uGain.

| Test results   |       |       |       |        |     |        |
|----------------|-------|-------|-------|--------|-----|--------|
| Time step      | 1     | 2     | 3     | 4      | ... | 107    |
| CPU cycles     | 39    | 39    | 39    | 39     | ... | 39     |
| Inputs         |       |       |       |        |     |        |
| In (DSP)       | 13107 |       |       |        |     |        |
| In             | 0.4   |       |       |        |     |        |
| Parameters     |       |       |       |        |     |        |
| Gain           | -3.7  | -3.63 | -3.56 | -3.491 | ... | 3.7    |
| Outputs        |       |       |       |        |     |        |
| Out            | 0.52  | 0.548 | 0.576 | 0.604  | ... | -0.52  |
| Exp. Out       | 0.52  | 0.548 | 0.576 | 0.604  | ... | -0.52  |
| Out (DSP)      | 17040 | 17954 | 18869 | 19784  | ... | -17041 |
| Exp. Out (DSP) | 17039 | 17954 | 18869 | 19784  | ... | -17039 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,1553e-05$ ( $\pm 3$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 39 |
| Max CPU cycles  | 39 |
| Avg CPU cycles  | 39 |

### Test case: Conversion test

OK

Conversion test for General block uGain.

| Test results                 |        |        |        |        |     |       |
|------------------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>             | 1      | 2      | 3      | 4      | ... | 37    |
| <i>Mask parameters</i>       |        |        |        |        |     |       |
| <b>Gain</b>                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| <i>Controller parameters</i> |        |        |        |        |     |       |
| <b>V</b>                     | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>sfr</b>                   | 11     | 11     | 11     | 11     | ... | 11    |
| <b>Exp. V</b>                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| <b>Exp. sfr</b>              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block uGain.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| Time step             | 1      | 2      | 3      | 4      | ... | 37    |
| Mask parameters       |        |        |        |        |     |       |
| Gain                  | -10    | -9.444 | -8.889 | -8.333 | ... | 10    |
| Controller parameters |        |        |        |        |     |       |
| V                     | -20480 | -19342 | -18204 | -17066 | ... | 20480 |
| sfr                   | 11     | 11     | 11     | 11     | ... | 11    |
| Exp. V                | -20480 | -19342 | -18204 | -17067 | ... | 20480 |
| Exp. sfr              | 11     | 11     | 11     | 11     | ... | 11    |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 1,0000e+00$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1117 |
| Max CPU cycles  | 2821 |
| Avg CPU cycles  | 2226 |



**Verification: uGain FiP32 CPU TMS320F28335**

Date of Test 2026-06-19  
Target controller TMS320F28335

**Test case: Inport test****OK**

Inport test for General block uGain.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 107        |
| CPU cycles     | 62          | 62          | ... | 62         |
| Inputs         |             |             |     |            |
| In (DSP)       | -2147483648 | -2106965089 | ... | 2147483647 |
| In             | -1          | -0.981      | ... | 1          |
| Parameters     |             |             |     |            |
| Gain           | 2.1         |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -0.1        | -0.06       | ... | 0.1        |
| Exp. Out       | -0.1        | -0.06       | ... | 0.1        |
| Out (DSP)      | -214748364  | -129659391  | ... | 214748361  |
| Exp. Out (DSP) | -214748365  | -129659390  | ... | 214748365  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 62 |
| Avg CPU cycles  | 62 |

**Test case: Parameter test****OK**

Parameter test for General block uGain.

| Test results   |            |            |     |             |
|----------------|------------|------------|-----|-------------|
| Time step      | 1          | 2          | ... | 107         |
| CPU cycles     | 62         | 62         | ... | 62          |
| Inputs         |            |            |     |             |
| In (DSP)       | 858993459  |            |     |             |
| In             | 0.4        |            |     |             |
| Parameters     |            |            |     |             |
| Gain           | -3.7       | -3.63      | ... | 3.7         |
| Outputs        |            |            |     |             |
| Out            | 0.52       | 0.548      | ... | -0.52       |
| Exp. Out       | 0.52       | 0.548      | ... | -0.52       |
| Out (DSP)      | 1116691498 | 1176658965 | ... | -1116691499 |
| Exp. Out (DSP) | 1116691497 | 1176658965 | ... | -1116691497 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,3970\text{e-}09$ ( $\pm 3$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 62 |
| Avg CPU cycles  | 62 |

### Test case: Conversion test

OK

Conversion test for General block uGain.

| Test results                 |             |             |     |            |
|------------------------------|-------------|-------------|-----|------------|
| <b>Time step</b>             | 1           | 2           | ... | 37         |
| <i>Mask parameters</i>       |             |             |     |            |
| <b>Gain</b>                  | -10         | -9.444      | ... | 10         |
| <i>Controller parameters</i> |             |             |     |            |
| <b>V</b>                     | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>sfr</b>                   | 27          | 27          | ... | 27         |
| <b>Exp. V</b>                | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>Exp. sfr</b>              | 27          | 27          | ... | 27         |

| Test settings |                         |
|---------------|-------------------------|
| Tolerance V   | $\pm 0,0000\text{e}+00$ |
| Tolerance sfr | $\pm 0,0000\text{e}+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block uGain.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Gain                  | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| V                     | -1342177280 | -1267611904 | ... | 1342177280 |
| sfr                   | 27          | 27          | ... | 27         |
| Exp. V                | -1342177280 | -1267611876 | ... | 1342177280 |
| Exp. sfr              | 27          | 27          | ... | 27         |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 7,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1652 |
| Max CPU cycles  | 3809 |
| Avg CPU cycles  | 3056 |

**Verification: uGain FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block uGain.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 107        |
| CPU cycles     | 59          | 59          | ... | 59         |
| Inputs         |             |             |     |            |
| In (DSP)       | -2147483648 | -2106965089 | ... | 2147483647 |
| In             | -1          | -0.981      | ... | 1          |
| Parameters     |             |             |     |            |
| Gain           | 2.1         |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -0.1        | -0.06       | ... | 0.1        |
| Exp. Out       | -0.1        | -0.06       | ... | 0.1        |
| Out (DSP)      | -214748364  | -129659391  | ... | 214748361  |
| Exp. Out (DSP) | -214748365  | -129659390  | ... | 214748365  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 59 |
| Avg CPU cycles  | 59 |

**Test case: Parameter test****OK**

Parameter test for General block uGain.

| Test results   |            |            |     |             |
|----------------|------------|------------|-----|-------------|
| Time step      | 1          | 2          | ... | 107         |
| CPU cycles     | 59         | 59         | ... | 59          |
| Inputs         |            |            |     |             |
| In (DSP)       | 858993459  |            |     |             |
| In             | 0.4        |            |     |             |
| Parameters     |            |            |     |             |
| Gain           | -3.7       | -3.63      | ... | 3.7         |
| Outputs        |            |            |     |             |
| Out            | 0.52       | 0.548      | ... | -0.52       |
| Exp. Out       | 0.52       | 0.548      | ... | -0.52       |
| Out (DSP)      | 1116691498 | 1176658965 | ... | -1116691499 |
| Exp. Out (DSP) | 1116691497 | 1176658965 | ... | -1116691497 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,3970\text{e-}09$ ( $\pm 3$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 59 |
| Avg CPU cycles  | 59 |

### Test case: Conversion test

OK

Conversion test for General block uGain.

| Test results                 |             |             |     |            |
|------------------------------|-------------|-------------|-----|------------|
| <b>Time step</b>             | 1           | 2           | ... | 37         |
| <i>Mask parameters</i>       |             |             |     |            |
| <b>Gain</b>                  | -10         | -9.444      | ... | 10         |
| <i>Controller parameters</i> |             |             |     |            |
| <b>V</b>                     | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>sfr</b>                   | 27          | 27          | ... | 27         |
| <b>Exp. V</b>                | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>Exp. sfr</b>              | 27          | 27          | ... | 27         |

| Test settings |                         |
|---------------|-------------------------|
| Tolerance V   | $\pm 0,0000\text{e}+00$ |
| Tolerance sfr | $\pm 0,0000\text{e}+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block uGain.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Gain                  | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| V                     | -1342177280 | -1267611904 | ... | 1342177280 |
| sfr                   | 27          | 27          | ... | 27         |
| Exp. V                | -1342177280 | -1267611876 | ... | 1342177280 |
| Exp. sfr              | 27          | 27          | ... | 27         |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 7,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 725  |
| Max CPU cycles  | 1629 |
| Avg CPU cycles  | 1322 |

**Verification: uGain FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block uGain.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 107        |
| CPU cycles     | 77          | 77          | ... | 77         |
| Inputs         |             |             |     |            |
| In (DSP)       | -2147483648 | -2106965089 | ... | 2147483647 |
| In             | -1          | -0.981      | ... | 1          |
| Parameters     |             |             |     |            |
| Gain           | 2.1         |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -0.1        | -0.06       | ... | 0.1        |
| Exp. Out       | -0.1        | -0.06       | ... | 0.1        |
| Out (DSP)      | -214748364  | -129659391  | ... | 214748361  |
| Exp. Out (DSP) | -214748365  | -129659390  | ... | 214748365  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 77 |
| Max CPU cycles  | 77 |
| Avg CPU cycles  | 77 |

**Test case: Parameter test****OK**

Parameter test for General block uGain.

| Test results   |            |            |     |             |
|----------------|------------|------------|-----|-------------|
| Time step      | 1          | 2          | ... | 107         |
| CPU cycles     | 77         | 77         | ... | 77          |
| Inputs         |            |            |     |             |
| In (DSP)       | 858993459  |            |     |             |
| In             | 0.4        |            |     |             |
| Parameters     |            |            |     |             |
| Gain           | -3.7       | -3.63      | ... | 3.7         |
| Outputs        |            |            |     |             |
| Out            | 0.52       | 0.548      | ... | -0.52       |
| Exp. Out       | 0.52       | 0.548      | ... | -0.52       |
| Out (DSP)      | 1116691498 | 1176658965 | ... | -1116691499 |
| Exp. Out (DSP) | 1116691497 | 1176658965 | ... | -1116691497 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,3970\text{e-}09$ ( $\pm 3$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 77 |
| Max CPU cycles  | 77 |
| Avg CPU cycles  | 77 |

### Test case: Conversion test

OK

Conversion test for General block uGain.

| Test results                 |             |             |     |            |
|------------------------------|-------------|-------------|-----|------------|
| <b>Time step</b>             | 1           | 2           | ... | 37         |
| <i>Mask parameters</i>       |             |             |     |            |
| <b>Gain</b>                  | -10         | -9.444      | ... | 10         |
| <i>Controller parameters</i> |             |             |     |            |
| <b>V</b>                     | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>sfr</b>                   | 27          | 27          | ... | 27         |
| <b>Exp. V</b>                | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>Exp. sfr</b>              | 27          | 27          | ... | 27         |

| Test settings |                         |
|---------------|-------------------------|
| Tolerance V   | $\pm 0,0000\text{e}+00$ |
| Tolerance sfr | $\pm 0,0000\text{e}+00$ |



**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block uGain.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Gain                  | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| V                     | -1342177280 | -1267611904 | ... | 1342177280 |
| sfr                   | 27          | 27          | ... | 27         |
| Exp. V                | -1342177280 | -1267611876 | ... | 1342177280 |
| Exp. sfr              | 27          | 27          | ... | 27         |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 7,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1302 |
| Max CPU cycles  | 1870 |
| Avg CPU cycles  | 1679 |

**Verification: uGain FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block uGain.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 107        |
| CPU cycles     | 142         | 142         | ... | 142        |
| Inputs         |             |             |     |            |
| In (DSP)       | -2147483648 | -2106965089 | ... | 2147483647 |
| In             | -1          | -0.981      | ... | 1          |
| Parameters     |             |             |     |            |
| Gain           | 2.1         |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -0.1        | -0.06       | ... | 0.1        |
| Exp. Out       | -0.1        | -0.06       | ... | 0.1        |
| Out (DSP)      | -214748364  | -129659391  | ... | 214748361  |
| Exp. Out (DSP) | -214748365  | -129659390  | ... | 214748365  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 142 |
| Max CPU cycles  | 142 |
| Avg CPU cycles  | 142 |

**Test case: Parameter test****OK**

Parameter test for General block uGain.

| Test results   |            |            |     |             |
|----------------|------------|------------|-----|-------------|
| Time step      | 1          | 2          | ... | 107         |
| CPU cycles     | 142        | 142        | ... | 142         |
| Inputs         |            |            |     |             |
| In (DSP)       | 858993459  |            |     |             |
| In             | 0.4        |            |     |             |
| Parameters     |            |            |     |             |
| Gain           | -3.7       | -3.63      | ... | 3.7         |
| Outputs        |            |            |     |             |
| Out            | 0.52       | 0.548      | ... | -0.52       |
| Exp. Out       | 0.52       | 0.548      | ... | -0.52       |
| Out (DSP)      | 1116691498 | 1176658965 | ... | -1116691499 |
| Exp. Out (DSP) | 1116691497 | 1176658965 | ... | -1116691497 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,3970\text{e-}09$ ( $\pm 3$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 142 |
| Max CPU cycles  | 142 |
| Avg CPU cycles  | 142 |

### Test case: Conversion test

OK

Conversion test for General block uGain.

| Test results                 |             |             |     |            |
|------------------------------|-------------|-------------|-----|------------|
| <b>Time step</b>             | 1           | 2           | ... | 37         |
| <i>Mask parameters</i>       |             |             |     |            |
| <b>Gain</b>                  | -10         | -9.444      | ... | 10         |
| <i>Controller parameters</i> |             |             |     |            |
| <b>V</b>                     | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>sfr</b>                   | 27          | 27          | ... | 27         |
| <b>Exp. V</b>                | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>Exp. sfr</b>              | 27          | 27          | ... | 27         |

| Test settings |                         |
|---------------|-------------------------|
| Tolerance V   | $\pm 0,0000\text{e}+00$ |
| Tolerance sfr | $\pm 0,0000\text{e}+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block uGain.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Gain                  | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| V                     | -1342177280 | -1267611904 | ... | 1342177280 |
| sfr                   | 27          | 27          | ... | 27         |
| Exp. V                | -1342177280 | -1267611876 | ... | 1342177280 |
| Exp. sfr              | 27          | 27          | ... | 27         |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 7,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2741 |
| Max CPU cycles  | 5947 |
| Avg CPU cycles  | 4977 |

**Verification: uGain FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block uGain.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 107        |
| CPU cycles     | 43          | 43          | ... | 43         |
| Inputs         |             |             |     |            |
| In (DSP)       | -2147483648 | -2106965089 | ... | 2147483647 |
| In             | -1          | -0.981      | ... | 1          |
| Parameters     |             |             |     |            |
| Gain           | 2.1         |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -0.1        | -0.06       | ... | 0.1        |
| Exp. Out       | -0.1        | -0.06       | ... | 0.1        |
| Out (DSP)      | -214748364  | -129659391  | ... | 214748361  |
| Exp. Out (DSP) | -214748365  | -129659390  | ... | 214748365  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 43 |
| Max CPU cycles  | 43 |
| Avg CPU cycles  | 43 |

**Test case: Parameter test****OK**

Parameter test for General block uGain.

| Test results   |            |            |     |             |
|----------------|------------|------------|-----|-------------|
| Time step      | 1          | 2          | ... | 107         |
| CPU cycles     | 43         | 43         | ... | 43          |
| Inputs         |            |            |     |             |
| In (DSP)       | 858993459  |            |     |             |
| In             | 0.4        |            |     |             |
| Parameters     |            |            |     |             |
| Gain           | -3.7       | -3.63      | ... | 3.7         |
| Outputs        |            |            |     |             |
| Out            | 0.52       | 0.548      | ... | -0.52       |
| Exp. Out       | 0.52       | 0.548      | ... | -0.52       |
| Out (DSP)      | 1116691498 | 1176658965 | ... | -1116691499 |
| Exp. Out (DSP) | 1116691497 | 1176658965 | ... | -1116691497 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,3970\text{e-}09$ ( $\pm 3$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 43 |
| Max CPU cycles  | 43 |
| Avg CPU cycles  | 43 |

### Test case: Conversion test

OK

Conversion test for General block uGain.

| Test results                 |             |             |     |            |
|------------------------------|-------------|-------------|-----|------------|
| <b>Time step</b>             | 1           | 2           | ... | 37         |
| <i>Mask parameters</i>       |             |             |     |            |
| <b>Gain</b>                  | -10         | -9.444      | ... | 10         |
| <i>Controller parameters</i> |             |             |     |            |
| <b>V</b>                     | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>sfr</b>                   | 27          | 27          | ... | 27         |
| <b>Exp. V</b>                | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>Exp. sfr</b>              | 27          | 27          | ... | 27         |

| Test settings |                         |
|---------------|-------------------------|
| Tolerance V   | $\pm 0,0000\text{e+}00$ |
| Tolerance sfr | $\pm 0,0000\text{e+}00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block uGain.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Gain                  | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| V                     | -1342177280 | -1267611904 | ... | 1342177280 |
| sfr                   | 27          | 27          | ... | 27         |
| Exp. V                | -1342177280 | -1267611876 | ... | 1342177280 |
| Exp. sfr              | 27          | 27          | ... | 27         |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 7,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1271 |
| Max CPU cycles  | 2454 |
| Avg CPU cycles  | 2057 |

**Verification: uGain FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block uGain.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 107        |
| CPU cycles     | 450         | 450         | ... | 443        |
| Inputs         |             |             |     |            |
| In (DSP)       | -2147483648 | -2106965089 | ... | 2147483647 |
| In             | -1          | -0.981      | ... | 1          |
| Parameters     |             |             |     |            |
| Gain           | 2.1         |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -0.1        | -0.06       | ... | 0.1        |
| Exp. Out       | -0.1        | -0.06       | ... | 0.1        |
| Out (DSP)      | -214748364  | -129659391  | ... | 214748361  |
| Exp. Out (DSP) | -214748365  | -129659390  | ... | 214748365  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 443 |
| Max CPU cycles  | 450 |
| Avg CPU cycles  | 446 |

**Test case: Parameter test****OK**

Parameter test for General block uGain.



| Test results   |            |            |     |             |
|----------------|------------|------------|-----|-------------|
| Time step      | 1          | 2          | ... | 107         |
| CPU cycles     | 450        | 450        | ... | 443         |
| Inputs         |            |            |     |             |
| In (DSP)       | 858993459  |            |     |             |
| In             | 0.4        |            |     |             |
| Parameters     |            |            |     |             |
| Gain           | -3.7       | -3.63      | ... | 3.7         |
| Outputs        |            |            |     |             |
| Out            | 0.52       | 0.548      | ... | -0.52       |
| Exp. Out       | 0.52       | 0.548      | ... | -0.52       |
| Out (DSP)      | 1116691498 | 1176658965 | ... | -1116691499 |
| Exp. Out (DSP) | 1116691497 | 1176658965 | ... | -1116691497 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,3970\text{e-}09$ ( $\pm 3$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 443 |
| Max CPU cycles  | 470 |
| Avg CPU cycles  | 454 |

### Test case: Conversion test

OK

Conversion test for General block uGain.

| Test results                 |             |             |     |            |
|------------------------------|-------------|-------------|-----|------------|
| <b>Time step</b>             | 1           | 2           | ... | 37         |
| <i>Mask parameters</i>       |             |             |     |            |
| <b>Gain</b>                  | -10         | -9.444      | ... | 10         |
| <i>Controller parameters</i> |             |             |     |            |
| <b>V</b>                     | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>sfr</b>                   | 27          | 27          | ... | 27         |
| <b>Exp. V</b>                | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>Exp. sfr</b>              | 27          | 27          | ... | 27         |

| Test settings |                         |
|---------------|-------------------------|
| Tolerance V   | $\pm 0,0000\text{e}+00$ |
| Tolerance sfr | $\pm 0,0000\text{e}+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block uGain.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Gain                  | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| V                     | -1342177280 | -1267611904 | ... | 1342177280 |
| sfr                   | 27          | 27          | ... | 27         |
| Exp. V                | -1342177280 | -1267611876 | ... | 1342177280 |
| Exp. sfr              | 27          | 27          | ... | 27         |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 7,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 2999  |
| Max CPU cycles  | 11019 |
| Avg CPU cycles  | 8556  |

**Verification: uGain FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block uGain.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 107        |
| CPU cycles     | 82          | 74          | ... | 74         |
| Inputs         |             |             |     |            |
| In (DSP)       | -2147483648 | -2106965089 | ... | 2147483647 |
| In             | -1          | -0.981      | ... | 1          |
| Parameters     |             |             |     |            |
| Gain           | 2.1         |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -0.1        | -0.06       | ... | 0.1        |
| Exp. Out       | -0.1        | -0.06       | ... | 0.1        |
| Out (DSP)      | -214748364  | -129659391  | ... | 214748361  |
| Exp. Out (DSP) | -214748365  | -129659390  | ... | 214748365  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 74 |
| Max CPU cycles  | 82 |
| Avg CPU cycles  | 74 |

**Test case: Parameter test****OK**

Parameter test for General block uGain.

| Test results   |            |            |     |             |
|----------------|------------|------------|-----|-------------|
| Time step      | 1          | 2          | ... | 107         |
| CPU cycles     | 74         | 74         | ... | 74          |
| Inputs         |            |            |     |             |
| In (DSP)       | 858993459  |            |     |             |
| In             | 0.4        |            |     |             |
| Parameters     |            |            |     |             |
| Gain           | -3.7       | -3.63      | ... | 3.7         |
| Outputs        |            |            |     |             |
| Out            | 0.52       | 0.548      | ... | -0.52       |
| Exp. Out       | 0.52       | 0.548      | ... | -0.52       |
| Out (DSP)      | 1116691498 | 1176658965 | ... | -1116691499 |
| Exp. Out (DSP) | 1116691497 | 1176658965 | ... | -1116691497 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,3970\text{e-}09$ ( $\pm 3$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 74 |
| Max CPU cycles  | 74 |
| Avg CPU cycles  | 74 |

### Test case: Conversion test

OK

Conversion test for General block uGain.

| Test results                 |             |             |     |            |
|------------------------------|-------------|-------------|-----|------------|
| <b>Time step</b>             | 1           | 2           | ... | 37         |
| <i>Mask parameters</i>       |             |             |     |            |
| <b>Gain</b>                  | -10         | -9.444      | ... | 10         |
| <i>Controller parameters</i> |             |             |     |            |
| <b>V</b>                     | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>sfr</b>                   | 27          | 27          | ... | 27         |
| <b>Exp. V</b>                | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>Exp. sfr</b>              | 27          | 27          | ... | 27         |

| Test settings |                         |
|---------------|-------------------------|
| Tolerance V   | $\pm 0,0000\text{e+}00$ |
| Tolerance sfr | $\pm 0,0000\text{e+}00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block uGain.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Gain                  | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| V                     | -1342177280 | -1267611904 | ... | 1342177280 |
| sfr                   | 27          | 27          | ... | 27         |
| Exp. V                | -1342177280 | -1267611876 | ... | 1342177280 |
| Exp. sfr              | 27          | 27          | ... | 27         |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 7,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 971  |
| Max CPU cycles  | 1594 |
| Avg CPU cycles  | 1293 |

**Verification: uGain FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block uGain.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 107        |
| CPU cycles     | 42          | 42          | ... | 42         |
| Inputs         |             |             |     |            |
| In (DSP)       | -2147483648 | -2106965089 | ... | 2147483647 |
| In             | -1          | -0.981      | ... | 1          |
| Parameters     |             |             |     |            |
| Gain           | 2.1         |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -0.1        | -0.06       | ... | 0.1        |
| Exp. Out       | -0.1        | -0.06       | ... | 0.1        |
| Out (DSP)      | -214748364  | -129659391  | ... | 214748361  |
| Exp. Out (DSP) | -214748365  | -129659390  | ... | 214748365  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,3283e-09$ ( $\pm 5$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 42 |
| Max CPU cycles  | 42 |
| Avg CPU cycles  | 42 |

**Test case: Parameter test****OK**

Parameter test for General block uGain.

| Test results   |            |            |     |             |
|----------------|------------|------------|-----|-------------|
| Time step      | 1          | 2          | ... | 107         |
| CPU cycles     | 42         | 42         | ... | 42          |
| Inputs         |            |            |     |             |
| In (DSP)       | 858993459  |            |     |             |
| In             | 0.4        |            |     |             |
| Parameters     |            |            |     |             |
| Gain           | -3.7       | -3.63      | ... | 3.7         |
| Outputs        |            |            |     |             |
| Out            | 0.52       | 0.548      | ... | -0.52       |
| Exp. Out       | 0.52       | 0.548      | ... | -0.52       |
| Out (DSP)      | 1116691498 | 1176658965 | ... | -1116691499 |
| Exp. Out (DSP) | 1116691497 | 1176658965 | ... | -1116691497 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,3970\text{e-}09$ ( $\pm 3$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 42 |
| Max CPU cycles  | 42 |
| Avg CPU cycles  | 42 |

### Test case: Conversion test

OK

Conversion test for General block uGain.

| Test results                 |             |             |     |            |
|------------------------------|-------------|-------------|-----|------------|
| <b>Time step</b>             | 1           | 2           | ... | 37         |
| <i>Mask parameters</i>       |             |             |     |            |
| <b>Gain</b>                  | -10         | -9.444      | ... | 10         |
| <i>Controller parameters</i> |             |             |     |            |
| <b>V</b>                     | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>sfr</b>                   | 27          | 27          | ... | 27         |
| <b>Exp. V</b>                | -1342177280 | -1267611876 | ... | 1342177280 |
| <b>Exp. sfr</b>              | 27          | 27          | ... | 27         |

| Test settings |                         |
|---------------|-------------------------|
| Tolerance V   | $\pm 0,0000\text{e}+00$ |
| Tolerance sfr | $\pm 0,0000\text{e}+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for General block uGain.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| Time step             | 1           | 2           | ... | 37         |
| Mask parameters       |             |             |     |            |
| Gain                  | -10         | -9.444      | ... | 10         |
| Controller parameters |             |             |     |            |
| V                     | -1342177280 | -1267611904 | ... | 1342177280 |
| sfr                   | 27          | 27          | ... | 27         |
| Exp. V                | -1342177280 | -1267611876 | ... | 1342177280 |
| Exp. sfr              | 27          | 27          | ... | 27         |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 7,0000e+01$ |
| Tolerance sfr | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1228 |
| Max CPU cycles  | 2972 |
| Avg CPU cycles  | 2372 |



**Verification: uGain Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block uGain.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 107   |
| CPU cycles     | 441    | 441    | ... | 435   |
| Inputs         |        |        |     |       |
| In (DSP)       | -7.13  | -6.995 | ... | 7.13  |
| In             | -7.13  | -6.995 | ... | 7.13  |
| Parameters     |        |        |     |       |
| Gain           | 2.1    |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -2.407 | -2.124 | ... | 2.407 |
| Exp. Out       | -2.407 | -2.124 | ... | 2.407 |
| Out (DSP)      | -2.407 | -2.124 | ... | 2.407 |
| Exp. Out (DSP) | -2.407 | -2.124 | ... | 2.407 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 1,8626e-06$ ( $\pm 4000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 85  |
| Max CPU cycles  | 537 |
| Avg CPU cycles  | 315 |

**Test case: Parameter test****OK**

Parameter test for General block uGain.

| Test results   |       |       |     |        |
|----------------|-------|-------|-----|--------|
| Time step      | 1     | 2     | ... | 107    |
| CPU cycles     | 189   | 189   | ... | 179    |
| Inputs         |       |       |     |        |
| In (DSP)       | 1.257 |       |     |        |
| In             | 1.257 |       |     |        |
| Parameters     |       |       |     |        |
| Gain           | -3.7  | -3.63 | ... | 3.7    |
| Outputs        |       |       |     |        |
| Out            | 1.634 | 1.721 | ... | -1.634 |
| Exp. Out       | 1.634 | 1.721 | ... | -1.634 |
| Out (DSP)      | 1.634 | 1.721 | ... | -1.634 |
| Exp. Out (DSP) | 1.634 | 1.721 | ... | -1.634 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 1,8626e-06$ ( $\pm 4000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 85  |
| Max CPU cycles  | 189 |
| Avg CPU cycles  | 118 |

#### Test case: Conversion test

OK

Conversion test for General block uGain.

| Test results          |     |        |     |    |
|-----------------------|-----|--------|-----|----|
| <b>Time step</b>      | 1   | 2      | ... | 37 |
| Mask parameters       |     |        |     |    |
| <b>Gain</b>           | -10 | -9.444 | ... | 10 |
| Controller parameters |     |        |     |    |
| <b>V</b>              | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>         | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block uGain.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Gain</b>                  | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>V</b>                     | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>                | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 5,0000e-07$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 812 |
| Max CPU cycles  | 829 |
| Avg CPU cycles  | 812 |

**Verification: uGain Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block uGain.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 107   |
| CPU cycles     | 197    | 197    | ... | 183   |
| Inputs         |        |        |     |       |
| In (DSP)       | -7.13  | -6.995 | ... | 7.13  |
| In             | -7.13  | -6.995 | ... | 7.13  |
| Parameters     |        |        |     |       |
| Gain           | 2.1    |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -2.407 | -2.124 | ... | 2.407 |
| Exp. Out       | -2.407 | -2.124 | ... | 2.407 |
| Out (DSP)      | -2.407 | -2.124 | ... | 2.407 |
| Exp. Out (DSP) | -2.407 | -2.124 | ... | 2.407 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 1,8626e-06$ ( $\pm 4000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 67  |
| Max CPU cycles  | 221 |
| Avg CPU cycles  | 148 |

**Test case: Parameter test****OK**

Parameter test for General block uGain.

| Test results   |       |       |     |        |
|----------------|-------|-------|-----|--------|
| Time step      | 1     | 2     | ... | 107    |
| CPU cycles     | 125   | 125   | ... | 107    |
| Inputs         |       |       |     |        |
| In (DSP)       | 1.257 |       |     |        |
| In             | 1.257 |       |     |        |
| Parameters     |       |       |     |        |
| Gain           | -3.7  | -3.63 | ... | 3.7    |
| Outputs        |       |       |     |        |
| Out            | 1.634 | 1.721 | ... | -1.634 |
| Exp. Out       | 1.634 | 1.721 | ... | -1.634 |
| Out (DSP)      | 1.634 | 1.721 | ... | -1.634 |
| Exp. Out (DSP) | 1.634 | 1.721 | ... | -1.634 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 1,8626e-06$ ( $\pm 4000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 67  |
| Max CPU cycles  | 125 |
| Avg CPU cycles  | 83  |

#### Test case: Conversion test

OK

Conversion test for General block uGain.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Gain</b>                  | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>V</b>                     | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>                | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block uGain.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Gain</b>                  | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>V</b>                     | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>                | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 5,0000e-07$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 397 |
| Max CPU cycles  | 397 |
| Avg CPU cycles  | 397 |

**Verification: uGain Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block uGain.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 107   |
| CPU cycles     | 382    | 382    | ... | 383   |
| Inputs         |        |        |     |       |
| In (DSP)       | -7.13  | -6.995 | ... | 7.13  |
| In             | -7.13  | -6.995 | ... | 7.13  |
| Parameters     |        |        |     |       |
| Gain           | 2.1    |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -2.407 | -2.124 | ... | 2.407 |
| Exp. Out       | -2.407 | -2.124 | ... | 2.407 |
| Out (DSP)      | -2.407 | -2.124 | ... | 2.407 |
| Exp. Out (DSP) | -2.407 | -2.124 | ... | 2.407 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 1,8626e-06$ ( $\pm 4000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 100 |
| Max CPU cycles  | 411 |
| Avg CPU cycles  | 288 |

**Test case: Parameter test****OK**

Parameter test for General block uGain.

| Test results   |       |       |     |        |
|----------------|-------|-------|-----|--------|
| Time step      | 1     | 2     | ... | 107    |
| CPU cycles     | 235   | 235   | ... | 231    |
| Inputs         |       |       |     |        |
| In (DSP)       | 1.257 |       |     |        |
| In             | 1.257 |       |     |        |
| Parameters     |       |       |     |        |
| Gain           | -3.7  | -3.63 | ... | 3.7    |
| Outputs        |       |       |     |        |
| Out            | 1.634 | 1.721 | ... | -1.634 |
| Exp. Out       | 1.634 | 1.721 | ... | -1.634 |
| Out (DSP)      | 1.634 | 1.721 | ... | -1.634 |
| Exp. Out (DSP) | 1.634 | 1.721 | ... | -1.634 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 1,8626e-06$ ( $\pm 4000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 100 |
| Max CPU cycles  | 235 |
| Avg CPU cycles  | 144 |

#### Test case: Conversion test

OK

Conversion test for General block uGain.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Gain</b>                  | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>V</b>                     | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>                | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block uGain.



| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Gain</b>                  | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>V</b>                     | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>                | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 5,0000e-07$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 466 |
| Max CPU cycles  | 466 |
| Avg CPU cycles  | 466 |

**Verification: uGain Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block uGain.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 107   |
| CPU cycles     | 774    | 774    | ... | 701   |
| Inputs         |        |        |     |       |
| In (DSP)       | -7.13  | -6.995 | ... | 7.13  |
| In             | -7.13  | -6.995 | ... | 7.13  |
| Parameters     |        |        |     |       |
| Gain           | 2.1    |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -2.407 | -2.124 | ... | 2.407 |
| Exp. Out       | -2.407 | -2.124 | ... | 2.407 |
| Out (DSP)      | -2.407 | -2.124 | ... | 2.407 |
| Exp. Out (DSP) | -2.407 | -2.124 | ... | 2.407 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 1,8626e-06$ ( $\pm 4000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 329 |
| Max CPU cycles  | 956 |
| Avg CPU cycles  | 715 |

**Test case: Parameter test****OK**

Parameter test for General block uGain.

| Test results   |       |       |     |        |
|----------------|-------|-------|-----|--------|
| Time step      | 1     | 2     | ... | 107    |
| CPU cycles     | 827   | 827   | ... | 759    |
| Inputs         |       |       |     |        |
| In (DSP)       | 1.257 |       |     |        |
| In             | 1.257 |       |     |        |
| Parameters     |       |       |     |        |
| Gain           | -3.7  | -3.63 | ... | 3.7    |
| Outputs        |       |       |     |        |
| Out            | 1.634 | 1.721 | ... | -1.634 |
| Exp. Out       | 1.634 | 1.721 | ... | -1.634 |
| Out (DSP)      | 1.634 | 1.721 | ... | -1.634 |
| Exp. Out (DSP) | 1.634 | 1.721 | ... | -1.634 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 1,8626e-06$ ( $\pm 4000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 396 |
| Max CPU cycles  | 855 |
| Avg CPU cycles  | 539 |

#### Test case: Conversion test

OK

Conversion test for General block uGain.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Gain</b>                  | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>V</b>                     | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>                | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block uGain.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Gain</b>                  | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>V</b>                     | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>                | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 5,0000e-07$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 667 |
| Max CPU cycles  | 696 |
| Avg CPU cycles  | 694 |

**Verification: uGain Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block uGain.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 107   |
| CPU cycles     | 282    | 282    | ... | 240   |
| Inputs         |        |        |     |       |
| In (DSP)       | -7.13  | -6.995 | ... | 7.13  |
| In             | -7.13  | -6.995 | ... | 7.13  |
| Parameters     |        |        |     |       |
| Gain           | 2.1    |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -2.407 | -2.124 | ... | 2.407 |
| Exp. Out       | -2.407 | -2.124 | ... | 2.407 |
| Out (DSP)      | -2.407 | -2.124 | ... | 2.407 |
| Exp. Out (DSP) | -2.407 | -2.124 | ... | 2.407 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 1,8626e-06$ ( $\pm 4000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 161 |
| Max CPU cycles  | 345 |
| Avg CPU cycles  | 266 |

**Test case: Parameter test****OK**

Parameter test for General block uGain.

| Test results   |       |       |     |        |
|----------------|-------|-------|-----|--------|
| Time step      | 1     | 2     | ... | 107    |
| CPU cycles     | 332   | 332   | ... | 298    |
| Inputs         |       |       |     |        |
| In (DSP)       | 1.257 |       |     |        |
| In             | 1.257 |       |     |        |
| Parameters     |       |       |     |        |
| Gain           | -3.7  | -3.63 | ... | 3.7    |
| Outputs        |       |       |     |        |
| Out            | 1.634 | 1.721 | ... | -1.634 |
| Exp. Out       | 1.634 | 1.721 | ... | -1.634 |
| Out (DSP)      | 1.634 | 1.721 | ... | -1.634 |
| Exp. Out (DSP) | 1.634 | 1.721 | ... | -1.634 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 1,8626e-06$ ( $\pm 4000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 178 |
| Max CPU cycles  | 332 |
| Avg CPU cycles  | 222 |

#### Test case: Conversion test

OK

Conversion test for General block uGain.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Gain</b>                  | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>V</b>                     | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>                | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block uGain.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Gain</b>                  | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>V</b>                     | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>                | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 5,0000e-07$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 277 |
| Max CPU cycles  | 278 |
| Avg CPU cycles  | 277 |

**Verification: uGain Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block uGain.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 107   |
| CPU cycles     | 708    | 708    | ... | 610   |
| Inputs         |        |        |     |       |
| In (DSP)       | -7.13  | -6.995 | ... | 7.13  |
| In             | -7.13  | -6.995 | ... | 7.13  |
| Parameters     |        |        |     |       |
| Gain           | 2.1    |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -2.407 | -2.124 | ... | 2.407 |
| Exp. Out       | -2.407 | -2.124 | ... | 2.407 |
| Out (DSP)      | -2.407 | -2.124 | ... | 2.407 |
| Exp. Out (DSP) | -2.407 | -2.124 | ... | 2.407 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 1,8626e-06$ ( $\pm 4000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 361 |
| Max CPU cycles  | 929 |
| Avg CPU cycles  | 677 |

**Test case: Parameter test****OK**

Parameter test for General block uGain.



| Test results   |       |       |     |        |
|----------------|-------|-------|-----|--------|
| Time step      | 1     | 2     | ... | 107    |
| CPU cycles     | 872   | 872   | ... | 775    |
| Inputs         |       |       |     |        |
| In (DSP)       | 1.257 |       |     |        |
| In             | 1.257 |       |     |        |
| Parameters     |       |       |     |        |
| Gain           | -3.7  | -3.63 | ... | 3.7    |
| Outputs        |       |       |     |        |
| Out            | 1.634 | 1.721 | ... | -1.634 |
| Exp. Out       | 1.634 | 1.721 | ... | -1.634 |
| Out (DSP)      | 1.634 | 1.721 | ... | -1.634 |
| Exp. Out (DSP) | 1.634 | 1.721 | ... | -1.634 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 1,8626e-06$ ( $\pm 4000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 400 |
| Max CPU cycles  | 876 |
| Avg CPU cycles  | 531 |

#### Test case: Conversion test

OK

Conversion test for General block uGain.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Gain</b>                  | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>V</b>                     | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>                | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block uGain.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Gain</b>                  | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>V</b>                     | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>                | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 5,0000e-07$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 523 |
| Max CPU cycles  | 868 |
| Avg CPU cycles  | 856 |

**Verification: uGain Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block uGain.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 107   |
| CPU cycles     | 430    | 343    | ... | 340   |
| Inputs         |        |        |     |       |
| In (DSP)       | -7.13  | -6.995 | ... | 7.13  |
| In             | -7.13  | -6.995 | ... | 7.13  |
| Parameters     |        |        |     |       |
| Gain           | 2.1    |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -2.407 | -2.124 | ... | 2.407 |
| Exp. Out       | -2.407 | -2.124 | ... | 2.407 |
| Out (DSP)      | -2.407 | -2.124 | ... | 2.407 |
| Exp. Out (DSP) | -2.407 | -2.124 | ... | 2.407 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 1,8626e-06$ ( $\pm 4000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 98  |
| Max CPU cycles  | 430 |
| Avg CPU cycles  | 274 |

**Test case: Parameter test****OK**

Parameter test for General block uGain.

| Test results   |       |       |     |        |
|----------------|-------|-------|-----|--------|
| Time step      | 1     | 2     | ... | 107    |
| CPU cycles     | 278   | 283   | ... | 269    |
| Inputs         |       |       |     |        |
| In (DSP)       | 1.257 |       |     |        |
| In             | 1.257 |       |     |        |
| Parameters     |       |       |     |        |
| Gain           | -3.7  | -3.63 | ... | 3.7    |
| Outputs        |       |       |     |        |
| Out            | 1.634 | 1.721 | ... | -1.634 |
| Exp. Out       | 1.634 | 1.721 | ... | -1.634 |
| Out (DSP)      | 1.634 | 1.721 | ... | -1.634 |
| Exp. Out (DSP) | 1.634 | 1.721 | ... | -1.634 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 1,8626e-06$ ( $\pm 4000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 98  |
| Max CPU cycles  | 283 |
| Avg CPU cycles  | 157 |

#### Test case: Conversion test

OK

Conversion test for General block uGain.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Gain</b>                  | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>V</b>                     | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>                | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block uGain.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Gain</b>                  | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>V</b>                     | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>                | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 5,0000e-07$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 400 |
| Max CPU cycles  | 448 |
| Avg CPU cycles  | 401 |

**Verification: uGain Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block uGain.

| Test results   |        |        |     |       |
|----------------|--------|--------|-----|-------|
| Time step      | 1      | 2      | ... | 107   |
| CPU cycles     | 356    | 356    | ... | 354   |
| Inputs         |        |        |     |       |
| In (DSP)       | -7.13  | -6.995 | ... | 7.13  |
| In             | -7.13  | -6.995 | ... | 7.13  |
| Parameters     |        |        |     |       |
| Gain           | 2.1    |        |     |       |
| Outputs        |        |        |     |       |
| Out            | -2.407 | -2.124 | ... | 2.407 |
| Exp. Out       | -2.407 | -2.124 | ... | 2.407 |
| Out (DSP)      | -2.407 | -2.124 | ... | 2.407 |
| Exp. Out (DSP) | -2.407 | -2.124 | ... | 2.407 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 1,8626e-06$ ( $\pm 4000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 69  |
| Max CPU cycles  | 424 |
| Avg CPU cycles  | 251 |

**Test case: Parameter test****OK**

Parameter test for General block uGain.

| Test results   |       |       |     |        |
|----------------|-------|-------|-----|--------|
| Time step      | 1     | 2     | ... | 107    |
| CPU cycles     | 158   | 158   | ... | 146    |
| Inputs         |       |       |     |        |
| In (DSP)       | 1.257 |       |     |        |
| In             | 1.257 |       |     |        |
| Parameters     |       |       |     |        |
| Gain           | -3.7  | -3.63 | ... | 3.7    |
| Outputs        |       |       |     |        |
| Out            | 1.634 | 1.721 | ... | -1.634 |
| Exp. Out       | 1.634 | 1.721 | ... | -1.634 |
| Out (DSP)      | 1.634 | 1.721 | ... | -1.634 |
| Exp. Out (DSP) | 1.634 | 1.721 | ... | -1.634 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 1,8626e-06$ ( $\pm 4000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 69  |
| Max CPU cycles  | 158 |
| Avg CPU cycles  | 96  |

#### Test case: Conversion test

OK

Conversion test for General block uGain.

| Test results          |     |        |     |    |
|-----------------------|-----|--------|-----|----|
| <b>Time step</b>      | 1   | 2      | ... | 37 |
| Mask parameters       |     |        |     |    |
| <b>Gain</b>           | -10 | -9.444 | ... | 10 |
| Controller parameters |     |        |     |    |
| <b>V</b>              | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>         | -10 | -9.444 | ... | 10 |

| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block uGain.

| Test results                 |     |        |     |    |
|------------------------------|-----|--------|-----|----|
| <b>Time step</b>             | 1   | 2      | ... | 37 |
| <i>Mask parameters</i>       |     |        |     |    |
| <b>Gain</b>                  | -10 | -9.444 | ... | 10 |
| <i>Controller parameters</i> |     |        |     |    |
| <b>V</b>                     | -10 | -9.444 | ... | 10 |
| <b>Exp. V</b>                | -10 | -9.444 | ... | 10 |


| Test settings |                  |
|---------------|------------------|
| Tolerance V   | $\pm 5,0000e-07$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 644 |
| Max CPU cycles  | 647 |
| Avg CPU cycles  | 644 |



## Block: uRateLimiter

---



Limitation of rising and falling rate.

Function of Enable:

0: rate limiting disabled, signal is passed through

1: rate limiting enabled, signal is rate limited

0->1: preload of output with value from init input

| Inports |                                                                                                                                                                                         |
|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| In      |                                                                                                                                                                                         |
| Init    | Value which is loaded at rising flanke of enable signal                                                                                                                                 |
| Enable  | Enable == 0: Deactivation of block; Out is set to In.<br>Enable != 0: Activation of block; Out is rate limited.<br>Enable 0->1: Preloading of output; Out is set to value of Init input |

| Outports |  |
|----------|--|
| Out      |  |

| Mask Parameters |    |                                                                 |
|-----------------|----|-----------------------------------------------------------------|
| Name            | ID | Description                                                     |
| Tr              | 1  | Rising time in seconds. Slew rate will be $1/Tr$                |
| Tf              | 2  | Falling time in seconds. Slew rate will be $1/Tf$               |
| ts_fact         | 3  | Multiplication factor of base sampling time (in integer format) |

### Description:

Rising and falling time refer to a step from 0 to 1. Entries for *Tr*: *Rising time* and *Tf*: *Falling time* smaller than the actual sample time will be limited to the sample time internally.

The 16- and 32-Bit fixed point implementations are based on an internal 32-Bit wide slew-rate variable while the 8-Bit fixed point implementation uses a 16-Bit wide slew-rate variable.

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |
| Init              | int16 |
| Enable            | bool  |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |
| Init              | int32 |
| Enable            | bool  |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |
| Init              | float32 |
| Enable            | bool    |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |
| Init              | float64 |
| Enable            | bool    |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: uRateLimiter FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block uRateLimiter.

| Test results   |       |        |        |        |     |       |
|----------------|-------|--------|--------|--------|-----|-------|
| Time step      | 1     | 2      | 3      | 4      | ... | 266   |
| CPU cycles     | 83    | 83     | 83     | 83     | ... | 98    |
| Inputs         |       |        |        |        |     |       |
| In (DSP)       | 0     | -32768 | -31508 | -30247 | ... | -6554 |
| Init (DSP)     | 0     | 9830   | 9830   | 9830   | ... | 9830  |
| Enable (DSP)   | 0     | 0      | 0      | 0      | ... | 1     |
| In             | 0     | -1     | -0.962 | -0.923 | ... | -0.2  |
| Init           | 0     | 0.3    | 0.3    | 0.3    | ... | 0.3   |
| Enable         | 0     | 0      | 0      | 0      | ... | 1     |
| Parameters     |       |        |        |        |     |       |
| Tr             | 0.001 |        |        |        |     |       |
| Tf             | 0.003 |        |        |        |     |       |
| ts_fact        | 1     |        |        |        |     |       |
| Outputs        |       |        |        |        |     |       |
| Out            | 0     | -1     | -0.962 | -0.923 | ... | -0.2  |
| Exp. Out       | 0     | -1     | -0.962 | -0.923 | ... | -0.2  |
| Out (DSP)      | 0     | -32768 | -31508 | -30247 | ... | -6554 |
| Exp. Out (DSP) | 0     | -32768 | -31508 | -30247 | ... | -6554 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 83  |
| Max CPU cycles  | 128 |
| Avg CPU cycles  | 106 |

**Test case: Conversion test****OK**

Conversion test for General block uRateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block uRateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 1,0000e+00$ |
| Tolerance RateDown | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2856 |
| Max CPU cycles  | 2966 |
| Avg CPU cycles  | 2910 |

**Verification: uRateLimiter FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block uRateLimiter.

| Test results   |       |        |        |        |     |       |
|----------------|-------|--------|--------|--------|-----|-------|
| Time step      | 1     | 2      | 3      | 4      | ... | 266   |
| CPU cycles     | 51    | 51     | 51     | 51     | ... | 65    |
| Inputs         |       |        |        |        |     |       |
| In (DSP)       | 0     | -32768 | -31508 | -30247 | ... | -6554 |
| Init (DSP)     | 0     | 9830   | 9830   | 9830   | ... | 9830  |
| Enable (DSP)   | 0     | 0      | 0      | 0      | ... | 1     |
| In             | 0     | -1     | -0.962 | -0.923 | ... | -0.2  |
| Init           | 0     | 0.3    | 0.3    | 0.3    | ... | 0.3   |
| Enable         | 0     | 0      | 0      | 0      | ... | 1     |
| Parameters     |       |        |        |        |     |       |
| Tr             | 0.001 |        |        |        |     |       |
| Tf             | 0.003 |        |        |        |     |       |
| ts_fact        | 1     |        |        |        |     |       |
| Outputs        |       |        |        |        |     |       |
| Out            | 0     | -1     | -0.962 | -0.923 | ... | -0.2  |
| Exp. Out       | 0     | -1     | -0.962 | -0.923 | ... | -0.2  |
| Out (DSP)      | 0     | -32768 | -31508 | -30247 | ... | -6554 |
| Exp. Out (DSP) | 0     | -32768 | -31508 | -30247 | ... | -6554 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 51 |
| Max CPU cycles  | 81 |
| Avg CPU cycles  | 68 |

**Test case: Conversion test****OK**

Conversion test for General block uRateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block uRateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 1,0000e+00$ |
| Tolerance RateDown | $\pm 1,0000e+00$ |



| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1087 |
| Max CPU cycles  | 1097 |
| Avg CPU cycles  | 1091 |

**Verification: uRateLimiter FiP16 CPU STM32G474RE**

Date of Test 2026-06-19  
Target controller STM32G474RE

**Test case: Inport test****OK**

Inport test for General block uRateLimiter.

| Test results   |       |        |        |        |     |       |
|----------------|-------|--------|--------|--------|-----|-------|
| Time step      | 1     | 2      | 3      | 4      | ... | 266   |
| CPU cycles     | 67    | 67     | 67     | 67     | ... | 109   |
| Inputs         |       |        |        |        |     |       |
| In (DSP)       | 0     | -32768 | -31508 | -30247 | ... | -6554 |
| Init (DSP)     | 0     | 9830   | 9830   | 9830   | ... | 9830  |
| Enable (DSP)   | 0     | 0      | 0      | 0      | ... | 1     |
| In             | 0     | -1     | -0.962 | -0.923 | ... | -0.2  |
| Init           | 0     | 0.3    | 0.3    | 0.3    | ... | 0.3   |
| Enable         | 0     | 0      | 0      | 0      | ... | 1     |
| Parameters     |       |        |        |        |     |       |
| Tr             | 0.001 |        |        |        |     |       |
| Tf             | 0.003 |        |        |        |     |       |
| ts_fact        | 1     |        |        |        |     |       |
| Outputs        |       |        |        |        |     |       |
| Out            | 0     | -1     | -0.962 | -0.923 | ... | -0.2  |
| Exp. Out       | 0     | -1     | -0.962 | -0.923 | ... | -0.2  |
| Out (DSP)      | 0     | -32768 | -31508 | -30247 | ... | -6554 |
| Exp. Out (DSP) | 0     | -32768 | -31508 | -30247 | ... | -6554 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 67  |
| Max CPU cycles  | 129 |
| Avg CPU cycles  | 104 |

**Test case: Conversion test****OK**

Conversion test for General block uRateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block uRateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 1,0000e+00$ |
| Tolerance RateDown | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1654 |
| Max CPU cycles  | 1711 |
| Avg CPU cycles  | 1657 |

**Verification: uRateLimiter FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block uRateLimiter.

| Test results   |       |        |        |        |     |       |
|----------------|-------|--------|--------|--------|-----|-------|
| Time step      | 1     | 2      | 3      | 4      | ... | 266   |
| CPU cycles     | 67    | 67     | 67     | 67     | ... | 90    |
| Inputs         |       |        |        |        |     |       |
| In (DSP)       | 0     | -32768 | -31508 | -30247 | ... | -6554 |
| Init (DSP)     | 0     | 9830   | 9830   | 9830   | ... | 9830  |
| Enable (DSP)   | 0     | 0      | 0      | 0      | ... | 1     |
| In             | 0     | -1     | -0.962 | -0.923 | ... | -0.2  |
| Init           | 0     | 0.3    | 0.3    | 0.3    | ... | 0.3   |
| Enable         | 0     | 0      | 0      | 0      | ... | 1     |
| Parameters     |       |        |        |        |     |       |
| Tr             | 0.001 |        |        |        |     |       |
| Tf             | 0.003 |        |        |        |     |       |
| ts_fact        | 1     |        |        |        |     |       |
| Outputs        |       |        |        |        |     |       |
| Out            | 0     | -1     | -0.962 | -0.923 | ... | -0.2  |
| Exp. Out       | 0     | -1     | -0.962 | -0.923 | ... | -0.2  |
| Out (DSP)      | 0     | -32768 | -31508 | -30247 | ... | -6554 |
| Exp. Out (DSP) | 0     | -32768 | -31508 | -30247 | ... | -6554 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 67  |
| Max CPU cycles  | 158 |
| Avg CPU cycles  | 89  |

**Test case: Conversion test****OK**

Conversion test for General block uRateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block uRateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 1,0000e+00$ |
| Tolerance RateDown | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 6095 |
| Max CPU cycles  | 6408 |
| Avg CPU cycles  | 6235 |

**Verification: uRateLimiter FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block uRateLimiter.

| Test results   |       |        |        |        |     |       |
|----------------|-------|--------|--------|--------|-----|-------|
| Time step      | 1     | 2      | 3      | 4      | ... | 266   |
| CPU cycles     | 41    | 41     | 41     | 41     | ... | 46    |
| Inputs         |       |        |        |        |     |       |
| In (DSP)       | 0     | -32768 | -31508 | -30247 | ... | -6554 |
| Init (DSP)     | 0     | 9830   | 9830   | 9830   | ... | 9830  |
| Enable (DSP)   | 0     | 0      | 0      | 0      | ... | 1     |
| In             | 0     | -1     | -0.962 | -0.923 | ... | -0.2  |
| Init           | 0     | 0.3    | 0.3    | 0.3    | ... | 0.3   |
| Enable         | 0     | 0      | 0      | 0      | ... | 1     |
| Parameters     |       |        |        |        |     |       |
| Tr             | 0.001 |        |        |        |     |       |
| Tf             | 0.003 |        |        |        |     |       |
| ts_fact        | 1     |        |        |        |     |       |
| Outputs        |       |        |        |        |     |       |
| Out            | 0     | -1     | -0.962 | -0.923 | ... | -0.2  |
| Exp. Out       | 0     | -1     | -0.962 | -0.923 | ... | -0.2  |
| Out (DSP)      | 0     | -32768 | -31508 | -30247 | ... | -6554 |
| Exp. Out (DSP) | 0     | -32768 | -31508 | -30247 | ... | -6554 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 41 |
| Max CPU cycles  | 63 |
| Avg CPU cycles  | 50 |

**Test case: Conversion test****OK**

Conversion test for General block uRateLimiter.



| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block uRateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 1,0000e+00$ |
| Tolerance RateDown | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2067 |
| Max CPU cycles  | 2100 |
| Avg CPU cycles  | 2082 |

**Verification: uRateLimiter FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block uRateLimiter.

| Test results   |       |        |        |        |     |       |
|----------------|-------|--------|--------|--------|-----|-------|
| Time step      | 1     | 2      | 3      | 4      | ... | 266   |
| CPU cycles     | 61    | 61     | 61     | 61     | ... | 65    |
| Inputs         |       |        |        |        |     |       |
| In (DSP)       | 0     | -32768 | -31508 | -30247 | ... | -6554 |
| Init (DSP)     | 0     | 9830   | 9830   | 9830   | ... | 9830  |
| Enable (DSP)   | 0     | 0      | 0      | 0      | ... | 1     |
| In             | 0     | -1     | -0.962 | -0.923 | ... | -0.2  |
| Init           | 0     | 0.3    | 0.3    | 0.3    | ... | 0.3   |
| Enable         | 0     | 0      | 0      | 0      | ... | 1     |
| Parameters     |       |        |        |        |     |       |
| Tr             | 0.001 |        |        |        |     |       |
| Tf             | 0.003 |        |        |        |     |       |
| ts_fact        | 1     |        |        |        |     |       |
| Outputs        |       |        |        |        |     |       |
| Out            | 0     | -1     | -0.962 | -0.923 | ... | -0.2  |
| Exp. Out       | 0     | -1     | -0.962 | -0.923 | ... | -0.2  |
| Out (DSP)      | 0     | -32768 | -31508 | -30247 | ... | -6554 |
| Exp. Out (DSP) | 0     | -32768 | -31508 | -30247 | ... | -6554 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 60 |
| Max CPU cycles  | 78 |
| Avg CPU cycles  | 68 |

**Test case: Conversion test****OK**

Conversion test for General block uRateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block uRateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 1,0000e+00$ |
| Tolerance RateDown | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 4978 |
| Max CPU cycles  | 5687 |
| Avg CPU cycles  | 5633 |

**Verification: uRateLimiter FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block uRateLimiter.

| Test results   |       |        |        |        |     |       |
|----------------|-------|--------|--------|--------|-----|-------|
| Time step      | 1     | 2      | 3      | 4      | ... | 266   |
| CPU cycles     | 82    | 66     | 66     | 66     | ... | 81    |
| Inputs         |       |        |        |        |     |       |
| In (DSP)       | 0     | -32768 | -31508 | -30247 | ... | -6554 |
| Init (DSP)     | 0     | 9830   | 9830   | 9830   | ... | 9830  |
| Enable (DSP)   | 0     | 0      | 0      | 0      | ... | 1     |
| In             | 0     | -1     | -0.962 | -0.923 | ... | -0.2  |
| Init           | 0     | 0.3    | 0.3    | 0.3    | ... | 0.3   |
| Enable         | 0     | 0      | 0      | 0      | ... | 1     |
| Parameters     |       |        |        |        |     |       |
| Tr             | 0.001 |        |        |        |     |       |
| Tf             | 0.003 |        |        |        |     |       |
| ts_fact        | 1     |        |        |        |     |       |
| Outputs        |       |        |        |        |     |       |
| Out            | 0     | -1     | -0.962 | -0.923 | ... | -0.2  |
| Exp. Out       | 0     | -1     | -0.962 | -0.923 | ... | -0.2  |
| Out (DSP)      | 0     | -32768 | -31508 | -30247 | ... | -6554 |
| Exp. Out (DSP) | 0     | -32768 | -31508 | -30247 | ... | -6554 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 66 |
| Max CPU cycles  | 96 |
| Avg CPU cycles  | 81 |

**Test case: Conversion test****OK**

Conversion test for General block uRateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block uRateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 1,0000e+00$ |
| Tolerance RateDown | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1417 |
| Max CPU cycles  | 1573 |
| Avg CPU cycles  | 1421 |



**Verification: uRateLimiter FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block uRateLimiter.

| Test results   |       |        |        |        |     |       |
|----------------|-------|--------|--------|--------|-----|-------|
| Time step      | 1     | 2      | 3      | 4      | ... | 266   |
| CPU cycles     | 70    | 70     | 70     | 70     | ... | 84    |
| Inputs         |       |        |        |        |     |       |
| In (DSP)       | 0     | -32768 | -31508 | -30247 | ... | -6554 |
| Init (DSP)     | 0     | 9830   | 9830   | 9830   | ... | 9830  |
| Enable (DSP)   | 0     | 0      | 0      | 0      | ... | 1     |
| In             | 0     | -1     | -0.962 | -0.923 | ... | -0.2  |
| Init           | 0     | 0.3    | 0.3    | 0.3    | ... | 0.3   |
| Enable         | 0     | 0      | 0      | 0      | ... | 1     |
| Parameters     |       |        |        |        |     |       |
| Tr             | 0.001 |        |        |        |     |       |
| Tf             | 0.003 |        |        |        |     |       |
| ts_fact        | 1     |        |        |        |     |       |
| Outputs        |       |        |        |        |     |       |
| Out            | 0     | -1     | -0.962 | -0.923 | ... | -0.2  |
| Exp. Out       | 0     | -1     | -0.962 | -0.923 | ... | -0.2  |
| Out (DSP)      | 0     | -32768 | -31508 | -30247 | ... | -6554 |
| Exp. Out (DSP) | 0     | -32768 | -31508 | -30247 | ... | -6554 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 70  |
| Max CPU cycles  | 127 |
| Avg CPU cycles  | 97  |

**Test case: Conversion test****OK**

Conversion test for General block uRateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block uRateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 1,0000e+00$ |
| Tolerance RateDown | $\pm 1,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2163 |
| Max CPU cycles  | 2241 |
| Avg CPU cycles  | 2201 |

**Verification: uRateLimiter FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block uRateLimiter.

| Test results   |       |             |     |            |
|----------------|-------|-------------|-----|------------|
| Time step      | 1     | 2           | ... | 266        |
| CPU cycles     | 71    | 71          | ... | 87         |
| Inputs         |       |             |     |            |
| In (DSP)       | 0     | -2147483648 | ... | -429496730 |
| Init (DSP)     | 0     | 644245094   | ... | 644245094  |
| Enable (DSP)   | 0     | 0           | ... | 1          |
| In             | 0     | -1          | ... | -0.2       |
| Init           | 0     | 0.3         | ... | 0.3        |
| Enable         | 0     | 0           | ... | 1          |
| Parameters     |       |             |     |            |
| Tr             | 0.001 |             |     |            |
| Tf             | 0.003 |             |     |            |
| ts_fact        | 1     |             |     |            |
| Outputs        |       |             |     |            |
| Out            | 0     | -1          | ... | -0.2       |
| Exp. Out       | 0     | -1          | ... | -0.2       |
| Out (DSP)      | 0     | -2147483648 | ... | -429496730 |
| Exp. Out (DSP) | 0     | -2147483648 | ... | -429496730 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 1,1642e-08$ ( $\pm 25$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 71  |
| Max CPU cycles  | 105 |
| Avg CPU cycles  | 88  |

**Test case: Conversion test****OK**

Conversion test for General block uRateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block uRateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 3,0000e+00$ |
| Tolerance RateDown | $\pm 3,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2856 |
| Max CPU cycles  | 2966 |
| Avg CPU cycles  | 2910 |

**Verification: uRateLimiter FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block uRateLimiter.

| Test results   |       |             |     |            |
|----------------|-------|-------------|-----|------------|
| Time step      | 1     | 2           | ... | 266        |
| CPU cycles     | 45    | 45          | ... | 51         |
| Inputs         |       |             |     |            |
| In (DSP)       | 0     | -2147483648 | ... | -429496730 |
| Init (DSP)     | 0     | 644245094   | ... | 644245094  |
| Enable (DSP)   | 0     | 0           | ... | 1          |
| In             | 0     | -1          | ... | -0.2       |
| Init           | 0     | 0.3         | ... | 0.3        |
| Enable         | 0     | 0           | ... | 1          |
| Parameters     |       |             |     |            |
| Tr             | 0.001 |             |     |            |
| Tf             | 0.003 |             |     |            |
| ts_fact        | 1     |             |     |            |
| Outputs        |       |             |     |            |
| Out            | 0     | -1          | ... | -0.2       |
| Exp. Out       | 0     | -1          | ... | -0.2       |
| Out (DSP)      | 0     | -2147483648 | ... | -429496730 |
| Exp. Out (DSP) | 0     | -2147483648 | ... | -429496730 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 1,1642e-08$ ( $\pm 25$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 45 |
| Max CPU cycles  | 61 |
| Avg CPU cycles  | 53 |

**Test case: Conversion test****OK**

Conversion test for General block uRateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block uRateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 3,0000e+00$ |
| Tolerance RateDown | $\pm 3,0000e+00$ |



| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1087 |
| Max CPU cycles  | 1097 |
| Avg CPU cycles  | 1091 |

**Verification: uRateLimiter FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block uRateLimiter.

| Test results   |       |             |     |            |
|----------------|-------|-------------|-----|------------|
| Time step      | 1     | 2           | ... | 266        |
| CPU cycles     | 62    | 62          | ... | 97         |
| Inputs         |       |             |     |            |
| In (DSP)       | 0     | -2147483648 | ... | -429496730 |
| Init (DSP)     | 0     | 644245094   | ... | 644245094  |
| Enable (DSP)   | 0     | 0           | ... | 1          |
| In             | 0     | -1          | ... | -0.2       |
| Init           | 0     | 0.3         | ... | 0.3        |
| Enable         | 0     | 0           | ... | 1          |
| Parameters     |       |             |     |            |
| Tr             | 0.001 |             |     |            |
| Tf             | 0.003 |             |     |            |
| ts_fact        | 1     |             |     |            |
| Outputs        |       |             |     |            |
| Out            | 0     | -1          | ... | -0.2       |
| Exp. Out       | 0     | -1          | ... | -0.2       |
| Out (DSP)      | 0     | -2147483648 | ... | -429496730 |
| Exp. Out (DSP) | 0     | -2147483648 | ... | -429496730 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 1,1642e-08$ ( $\pm 25$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 62  |
| Max CPU cycles  | 112 |
| Avg CPU cycles  | 93  |

**Test case: Conversion test****OK**

Conversion test for General block uRateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |             |
|--------------------|-------------|
| Tolerance RateUp   | ±0,0000e+00 |
| Tolerance RateDown | ±0,0000e+00 |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block uRateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |             |
|--------------------|-------------|
| Tolerance RateUp   | ±3,0000e+00 |
| Tolerance RateDown | ±3,0000e+00 |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1654 |
| Max CPU cycles  | 1659 |
| Avg CPU cycles  | 1654 |

**Verification: uRateLimiter FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block uRateLimiter.

| Test results   |       |             |     |            |
|----------------|-------|-------------|-----|------------|
| Time step      | 1     | 2           | ... | 266        |
| CPU cycles     | 62    | 62          | ... | 84         |
| Inputs         |       |             |     |            |
| In (DSP)       | 0     | -2147483648 | ... | -429496730 |
| Init (DSP)     | 0     | 644245094   | ... | 644245094  |
| Enable (DSP)   | 0     | 0           | ... | 1          |
| In             | 0     | -1          | ... | -0.2       |
| Init           | 0     | 0.3         | ... | 0.3        |
| Enable         | 0     | 0           | ... | 1          |
| Parameters     |       |             |     |            |
| Tr             | 0.001 |             |     |            |
| Tf             | 0.003 |             |     |            |
| ts_fact        | 1     |             |     |            |
| Outputs        |       |             |     |            |
| Out            | 0     | -1          | ... | -0.2       |
| Exp. Out       | 0     | -1          | ... | -0.2       |
| Out (DSP)      | 0     | -2147483648 | ... | -429496730 |
| Exp. Out (DSP) | 0     | -2147483648 | ... | -429496730 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 1,1642e-08$ ( $\pm 25$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 94 |
| Avg CPU cycles  | 81 |

**Test case: Conversion test****OK**

Conversion test for General block uRateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block uRateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 3,0000e+00$ |
| Tolerance RateDown | $\pm 3,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 6095 |
| Max CPU cycles  | 6409 |
| Avg CPU cycles  | 6233 |

**Verification: uRateLimiter FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block uRateLimiter.

| Test results   |       |             |     |            |
|----------------|-------|-------------|-----|------------|
| Time step      | 1     | 2           | ... | 266        |
| CPU cycles     | 38    | 38          | ... | 45         |
| Inputs         |       |             |     |            |
| In (DSP)       | 0     | -2147483648 | ... | -429496730 |
| Init (DSP)     | 0     | 644245094   | ... | 644245094  |
| Enable (DSP)   | 0     | 0           | ... | 1          |
| In             | 0     | -1          | ... | -0.2       |
| Init           | 0     | 0.3         | ... | 0.3        |
| Enable         | 0     | 0           | ... | 1          |
| Parameters     |       |             |     |            |
| Tr             | 0.001 |             |     |            |
| Tf             | 0.003 |             |     |            |
| ts_fact        | 1     |             |     |            |
| Outputs        |       |             |     |            |
| Out            | 0     | -1          | ... | -0.2       |
| Exp. Out       | 0     | -1          | ... | -0.2       |
| Out (DSP)      | 0     | -2147483648 | ... | -429496730 |
| Exp. Out (DSP) | 0     | -2147483648 | ... | -429496730 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 1,1642e-08$ ( $\pm 25$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 38 |
| Max CPU cycles  | 54 |
| Avg CPU cycles  | 46 |

**Test case: Conversion test****OK**

Conversion test for General block uRateLimiter.



| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block uRateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 3,0000e+00$ |
| Tolerance RateDown | $\pm 3,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2067 |
| Max CPU cycles  | 2100 |
| Avg CPU cycles  | 2082 |

**Verification: uRateLimiter FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block uRateLimiter.

| Test results   |       |             |     |            |
|----------------|-------|-------------|-----|------------|
| Time step      | 1     | 2           | ... | 266        |
| CPU cycles     | 56    | 56          | ... | 69         |
| Inputs         |       |             |     |            |
| In (DSP)       | 0     | -2147483648 | ... | -429496730 |
| Init (DSP)     | 0     | 644245094   | ... | 644245094  |
| Enable (DSP)   | 0     | 0           | ... | 1          |
| In             | 0     | -1          | ... | -0.2       |
| Init           | 0     | 0.3         | ... | 0.3        |
| Enable         | 0     | 0           | ... | 1          |
| Parameters     |       |             |     |            |
| Tr             | 0.001 |             |     |            |
| Tf             | 0.003 |             |     |            |
| ts_fact        | 1     |             |     |            |
| Outputs        |       |             |     |            |
| Out            | 0     | -1          | ... | -0.2       |
| Exp. Out       | 0     | -1          | ... | -0.2       |
| Out (DSP)      | 0     | -2147483648 | ... | -429496730 |
| Exp. Out (DSP) | 0     | -2147483648 | ... | -429496730 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 1,1642e-08$ ( $\pm 25$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 78 |
| Avg CPU cycles  | 67 |

**Test case: Conversion test****OK**

Conversion test for General block uRateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block uRateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 3,0000e+00$ |
| Tolerance RateDown | $\pm 3,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 4978 |
| Max CPU cycles  | 5687 |
| Avg CPU cycles  | 5633 |

**Verification: uRateLimiter FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block uRateLimiter.

| Test results   |       |             |     |            |
|----------------|-------|-------------|-----|------------|
| Time step      | 1     | 2           | ... | 266        |
| CPU cycles     | 76    | 64          | ... | 80         |
| Inputs         |       |             |     |            |
| In (DSP)       | 0     | -2147483648 | ... | -429496730 |
| Init (DSP)     | 0     | 644245094   | ... | 644245094  |
| Enable (DSP)   | 0     | 0           | ... | 1          |
| In             | 0     | -1          | ... | -0.2       |
| Init           | 0     | 0.3         | ... | 0.3        |
| Enable         | 0     | 0           | ... | 1          |
| Parameters     |       |             |     |            |
| Tr             | 0.001 |             |     |            |
| Tf             | 0.003 |             |     |            |
| ts_fact        | 1     |             |     |            |
| Outputs        |       |             |     |            |
| Out            | 0     | -1          | ... | -0.2       |
| Exp. Out       | 0     | -1          | ... | -0.2       |
| Out (DSP)      | 0     | -2147483648 | ... | -429496730 |
| Exp. Out (DSP) | 0     | -2147483648 | ... | -429496730 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 1,1642e-08$ ( $\pm 25$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 64 |
| Max CPU cycles  | 89 |
| Avg CPU cycles  | 78 |

**Test case: Conversion test****OK**

Conversion test for General block uRateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block uRateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 3,0000e+00$ |
| Tolerance RateDown | $\pm 3,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1360 |
| Max CPU cycles  | 1529 |
| Avg CPU cycles  | 1365 |



**Verification: uRateLimiter FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block uRateLimiter.

| Test results   |       |             |     |            |
|----------------|-------|-------------|-----|------------|
| Time step      | 1     | 2           | ... | 266        |
| CPU cycles     | 58    | 58          | ... | 72         |
| Inputs         |       |             |     |            |
| In (DSP)       | 0     | -2147483648 | ... | -429496730 |
| Init (DSP)     | 0     | 644245094   | ... | 644245094  |
| Enable (DSP)   | 0     | 0           | ... | 1          |
| In             | 0     | -1          | ... | -0.2       |
| Init           | 0     | 0.3         | ... | 0.3        |
| Enable         | 0     | 0           | ... | 1          |
| Parameters     |       |             |     |            |
| Tr             | 0.001 |             |     |            |
| Tf             | 0.003 |             |     |            |
| ts_fact        | 1     |             |     |            |
| Outputs        |       |             |     |            |
| Out            | 0     | -1          | ... | -0.2       |
| Exp. Out       | 0     | -1          | ... | -0.2       |
| Out (DSP)      | 0     | -2147483648 | ... | -429496730 |
| Exp. Out (DSP) | 0     | -2147483648 | ... | -429496730 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 1,1642e-08$ ( $\pm 25$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 58 |
| Max CPU cycles  | 96 |
| Avg CPU cycles  | 76 |

**Test case: Conversion test****OK**

Conversion test for General block uRateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64425 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71583 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 0,0000e+00$ |
| Tolerance RateDown | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for General block uRateLimiter.

| Test results                 |            |            |     |       |
|------------------------------|------------|------------|-----|-------|
| <b>Time step</b>             | 1          | 2          | ... | 37    |
| <i>Mask parameters</i>       |            |            |     |       |
| <b>Tr</b>                    | -10        | -9.444     | ... | 10    |
| <b>Tf</b>                    | -9         | -8.5       | ... | 9     |
| <b>ts_fact</b>               | 3          | 3          | ... | 3     |
| <i>Controller parameters</i> |            |            |     |       |
| <b>RateUp</b>                | 2147483647 | 2147483647 | ... | 64424 |
| <b>RateDown</b>              | 2147483647 | 2147483647 | ... | 71582 |
| <b>Exp. RateUp</b>           | 2147483647 | 2147483647 | ... | 64425 |
| <b>Exp. RateDown</b>         | 2147483647 | 2147483647 | ... | 71583 |

| Test settings      |                  |
|--------------------|------------------|
| Tolerance RateUp   | $\pm 3,0000e+00$ |
| Tolerance RateDown | $\pm 3,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2163 |
| Max CPU cycles  | 2241 |
| Avg CPU cycles  | 2201 |

## Block: uSaveSignal

---



Makes the incoming signal accessible for reading with parameter numbers.

| Inports |                          |
|---------|--------------------------|
| In      | Input signal to be saved |

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>Bool</b>    | Boolean Implementation               |
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: Bool

---

Boolean Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | bool |

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | int8 |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |

### Implementation: FiP32

---

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

### Implementation: Float32

---

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

### Implementation: Float64

---

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

## Block: Xor

---



Logical XOR block.

| Inports |  |
|---------|--|
| In1     |  |
| In2     |  |

| Outports |  |
|----------|--|
| Out      |  |

### Implementations:

**Bool**     Boolean Implementation

### Implementation: Bool

---

Boolean Implementation

| Inports Data Type |      |
|-------------------|------|
| In1               | bool |
| In2               | bool |

| Outports Data Type |      |
|--------------------|------|
| Out                | bool |

**Verification: Xor Bool CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for General block Xor.

| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 25 |
| <b>CPU cycles</b>     | 58 | 58 | 58   | 58   | ... | 58 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In1 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In2 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In1</b>            | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <b>In2</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 0  | 0  | 0    | 0    | ... | 0  |
| <b>Exp. Out</b>       | 0  | 0  | 0    | 0    | ... | 0  |
| <b>Out (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 0  |
| <b>Exp. Out (DSP)</b> | 0  | 0  | 0    | 0    | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 58 |
| Max CPU cycles  | 58 |
| Avg CPU cycles  | 58 |

**Verification: Xor Bool CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for General block Xor.

| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 25 |
| <b>CPU cycles</b>     | 27 | 27 | 27   | 27   | ... | 27 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In1 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In2 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In1</b>            | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <b>In2</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 0  | 0  | 0    | 0    | ... | 0  |
| <b>Exp. Out</b>       | 0  | 0  | 0    | 0    | ... | 0  |
| <b>Out (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 0  |
| <b>Exp. Out (DSP)</b> | 0  | 0  | 0    | 0    | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 27 |
| Max CPU cycles  | 27 |
| Avg CPU cycles  | 27 |



**Verification: Xor Bool CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for General block Xor.

| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 25 |
| <b>CPU cycles</b>     | 57 | 57 | 57   | 57   | ... | 57 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In1 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In2 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In1</b>            | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <b>In2</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 0  | 0  | 0    | 0    | ... | 0  |
| <b>Exp. Out</b>       | 0  | 0  | 0    | 0    | ... | 0  |
| <b>Out (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 0  |
| <b>Exp. Out (DSP)</b> | 0  | 0  | 0    | 0    | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 57 |

**Verification: Xor Bool CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for General block Xor.

| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 25 |
| <b>CPU cycles</b>     | 51 | 51 | 51   | 51   | ... | 51 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In1 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In2 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In1</b>            | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <b>In2</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 0  | 0  | 0    | 0    | ... | 0  |
| <b>Exp. Out</b>       | 0  | 0  | 0    | 0    | ... | 0  |
| <b>Out (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 0  |
| <b>Exp. Out (DSP)</b> | 0  | 0  | 0    | 0    | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 51 |
| Max CPU cycles  | 51 |
| Avg CPU cycles  | 51 |

**Verification: Xor Bool CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for General block Xor.

| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 25 |
| <b>CPU cycles</b>     | 32 | 32 | 32   | 32   | ... | 32 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In1 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In2 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In1</b>            | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <b>In2</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 0  | 0  | 0    | 0    | ... | 0  |
| <b>Exp. Out</b>       | 0  | 0  | 0    | 0    | ... | 0  |
| <b>Out (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 0  |
| <b>Exp. Out (DSP)</b> | 0  | 0  | 0    | 0    | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 32 |
| Max CPU cycles  | 32 |
| Avg CPU cycles  | 32 |

**Verification: Xor Bool CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for General block Xor.

| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 25 |
| <b>CPU cycles</b>     | 42 | 42 | 42   | 42   | ... | 42 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In1 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In2 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In1</b>            | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <b>In2</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 0  | 0  | 0    | 0    | ... | 0  |
| <b>Exp. Out</b>       | 0  | 0  | 0    | 0    | ... | 0  |
| <b>Out (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 0  |
| <b>Exp. Out (DSP)</b> | 0  | 0  | 0    | 0    | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 42 |
| Max CPU cycles  | 42 |
| Avg CPU cycles  | 42 |

**Verification: Xor Bool CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for General block Xor.

| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 25 |
| <b>CPU cycles</b>     | 67 | 56 | 56   | 56   | ... | 56 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In1 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In2 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In1</b>            | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <b>In2</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 0  | 0  | 0    | 0    | ... | 0  |
| <b>Exp. Out</b>       | 0  | 0  | 0    | 0    | ... | 0  |
| <b>Out (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 0  |
| <b>Exp. Out (DSP)</b> | 0  | 0  | 0    | 0    | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 67 |
| Avg CPU cycles  | 56 |

**Verification: Xor Bool CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for General block Xor.


| Test results          |    |    |      |      |     |    |
|-----------------------|----|----|------|------|-----|----|
| <b>Time step</b>      | 1  | 2  | 3    | 4    | ... | 25 |
| <b>CPU cycles</b>     | 40 | 40 | 40   | 40   | ... | 40 |
| <i>Inputs</i>         |    |    |      |      |     |    |
| <b>In1 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In2 (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 1  |
| <b>In1</b>            | 0  | -1 | -0.5 | -0.2 | ... | 1  |
| <b>In2</b>            | 0  | 0  | 0    | 0    | ... | 1  |
| <i>Outputs</i>        |    |    |      |      |     |    |
| <b>Out</b>            | 0  | 0  | 0    | 0    | ... | 0  |
| <b>Exp. Out</b>       | 0  | 0  | 0    | 0    | ... | 0  |
| <b>Out (DSP)</b>      | 0  | 0  | 0    | 0    | ... | 0  |
| <b>Exp. Out (DSP)</b> | 0  | 0  | 0    | 0    | ... | 0  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 0,0000e+00$ ( $\pm 0$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 40 |
| Max CPU cycles  | 40 |
| Avg CPU cycles  | 40 |

## 6 Math

This library contains blocks for computation of common mathematical functions.



## Block: Abs

---



Calculation of absolute value of input.

| Inports |         |
|---------|---------|
| In      | Input u |

| Outports |                     |
|----------|---------------------|
| Out      | Absolute value of u |

### Description:

Calculation:

$$\text{Out} = |\text{In}|$$

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | int8 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |



| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: Abs FiP16 CPU TMS320F28335****Date of Test** 2026-06-19**Target controller** TMS320F28335**Test case: Inport test****OK**

Inport test for Math block Abs.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 107   |
| <b>CPU cycles</b>     | 59     | 59     | 59     | 59     | ... | 62    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32768 | -32768 | -32768 | ... | 32767 |
| <b>In</b>             | -1     | -1     | -1     | -1     | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 1      | 1      | 1      | 1      | ... | 1     |
| <b>Exp. Out</b>       | 1      | 1      | 1      | 1      | ... | 1     |
| <b>Out (DSP)</b>      | 32767  | 32767  | 32767  | 32767  | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 32767  | 32767  | 32767  | 32767  | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 62 |
| Avg CPU cycles  | 61 |

**Verification: Abs FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Abs.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 107   |
| <b>CPU cycles</b>     | 31     | 31     | 31     | 31     | ... | 29    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32768 | -32768 | -32768 | ... | 32767 |
| <b>In</b>             | -1     | -1     | -1     | -1     | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 1      | 1      | 1      | 1      | ... | 1     |
| <b>Exp. Out</b>       | 1      | 1      | 1      | 1      | ... | 1     |
| <b>Out (DSP)</b>      | 32767  | 32767  | 32767  | 32767  | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 32767  | 32767  | 32767  | 32767  | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 35 |
| Avg CPU cycles  | 30 |

**Verification: Abs FiP16 CPU STM32G474RE**

|                   |             |
|-------------------|-------------|
| Date of Test      | 2026-06-19  |
| Target controller | STM32G474RE |

**Test case: Inport test**

OK

Inport test for Math block Abs.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 107   |
| CPU cycles     | 76     | 76     | 76     | 76     | ... | 66    |
| Inputs         |        |        |        |        |     |       |
| In (DSP)       | -32768 | -32768 | -32768 | -32768 | ... | 32767 |
| In             | -1     | -1     | -1     | -1     | ... | 1     |
| Outputs        |        |        |        |        |     |       |
| Out            | 1      | 1      | 1      | 1      | ... | 1     |
| Exp. Out       | 1      | 1      | 1      | 1      | ... | 1     |
| Out (DSP)      | 32767  | 32767  | 32767  | 32767  | ... | 32767 |
| Exp. Out (DSP) | 32767  | 32767  | 32767  | 32767  | ... | 32767 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 3,0518\text{e-}05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 66 |
| Max CPU cycles  | 76 |
| Avg CPU cycles  | 68 |

**Verification: Abs FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Abs.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 107   |
| <b>CPU cycles</b>     | 64     | 64     | 64     | 64     | ... | 54    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32768 | -32768 | -32768 | ... | 32767 |
| <b>In</b>             | -1     | -1     | -1     | -1     | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 1      | 1      | 1      | 1      | ... | 1     |
| <b>Exp. Out</b>       | 1      | 1      | 1      | 1      | ... | 1     |
| <b>Out (DSP)</b>      | 32767  | 32767  | 32767  | 32767  | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 32767  | 32767  | 32767  | 32767  | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 54 |
| Max CPU cycles  | 64 |
| Avg CPU cycles  | 57 |

**Verification: Abs FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Abs.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 107   |
| <b>CPU cycles</b>     | 30     | 30     | 30     | 30     | ... | 32    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32768 | -32768 | -32768 | ... | 32767 |
| <b>In</b>             | -1     | -1     | -1     | -1     | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 1      | 1      | 1      | 1      | ... | 1     |
| <b>Exp. Out</b>       | 1      | 1      | 1      | 1      | ... | 1     |
| <b>Out (DSP)</b>      | 32767  | 32767  | 32767  | 32767  | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 32767  | 32767  | 32767  | 32767  | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 30 |
| Max CPU cycles  | 33 |
| Avg CPU cycles  | 32 |

**Verification: Abs FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Abs.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 107   |
| <b>CPU cycles</b>     | 44     | 44     | 44     | 44     | ... | 42    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32768 | -32768 | -32768 | ... | 32767 |
| <b>In</b>             | -1     | -1     | -1     | -1     | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 1      | 1      | 1      | 1      | ... | 1     |
| <b>Exp. Out</b>       | 1      | 1      | 1      | 1      | ... | 1     |
| <b>Out (DSP)</b>      | 32767  | 32767  | 32767  | 32767  | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 32767  | 32767  | 32767  | 32767  | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 42 |
| Max CPU cycles  | 44 |
| Avg CPU cycles  | 42 |

**Verification: Abs FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Abs.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 107   |
| <b>CPU cycles</b>     | 60     | 60     | 60     | 60     | ... | 61    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32768 | -32768 | -32768 | ... | 32767 |
| <b>In</b>             | -1     | -1     | -1     | -1     | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 1      | 1      | 1      | 1      | ... | 1     |
| <b>Exp. Out</b>       | 1      | 1      | 1      | 1      | ... | 1     |
| <b>Out (DSP)</b>      | 32767  | 32767  | 32767  | 32767  | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 32767  | 32767  | 32767  | 32767  | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 60 |
| Max CPU cycles  | 62 |
| Avg CPU cycles  | 61 |



**Verification: Abs FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Abs.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 107   |
| <b>CPU cycles</b>     | 59     | 59     | 59     | 59     | ... | 58    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32768 | -32768 | -32768 | ... | 32767 |
| <b>In</b>             | -1     | -1     | -1     | -1     | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 1      | 1      | 1      | 1      | ... | 1     |
| <b>Exp. Out</b>       | 1      | 1      | 1      | 1      | ... | 1     |
| <b>Out (DSP)</b>      | 32767  | 32767  | 32767  | 32767  | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 32767  | 32767  | 32767  | 32767  | ... | 32767 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 3,0518\text{e-}05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 58 |
| Max CPU cycles  | 59 |
| Avg CPU cycles  | 58 |

**Verification: Abs FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Abs.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 107        |
| <b>CPU cycles</b>     | 63          | 63          | ... | 64         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2147483648 | ... | 2147483647 |
| <b>In</b>             | -1          | -1          | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 1           | ... | 1          |
| <b>Exp. Out</b>       | 1           | 1           | ... | 1          |
| <b>Out (DSP)</b>      | 2147483647  | 2147483647  | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2147483647  | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 63 |
| Max CPU cycles  | 64 |
| Avg CPU cycles  | 63 |

**Verification: Abs FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Abs.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 107        |
| <b>CPU cycles</b>     | 29          | 29          | ... | 31         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2147483648 | ... | 2147483647 |
| <b>In</b>             | -1          | -1          | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 1           | ... | 1          |
| <b>Exp. Out</b>       | 1           | 1           | ... | 1          |
| <b>Out (DSP)</b>      | 2147483647  | 2147483647  | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2147483647  | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 33 |
| Avg CPU cycles  | 31 |

**Verification: Abs FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Abs.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 107        |
| <b>CPU cycles</b>     | 71          | 71          | ... | 66         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2147483648 | ... | 2147483647 |
| <b>In</b>             | -1          | -1          | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 1           | ... | 1          |
| <b>Exp. Out</b>       | 1           | 1           | ... | 1          |
| <b>Out (DSP)</b>      | 2147483647  | 2147483647  | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2147483647  | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 66 |
| Max CPU cycles  | 71 |
| Avg CPU cycles  | 66 |

**Verification: Abs FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Abs.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 107        |
| <b>CPU cycles</b>     | 63          | 63          | ... | 53         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2147483648 | ... | 2147483647 |
| <b>In</b>             | -1          | -1          | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 1           | ... | 1          |
| <b>Exp. Out</b>       | 1           | 1           | ... | 1          |
| <b>Out (DSP)</b>      | 2147483647  | 2147483647  | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2147483647  | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 53 |
| Max CPU cycles  | 63 |
| Avg CPU cycles  | 53 |

**Verification: Abs FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Abs.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 107        |
| <b>CPU cycles</b>     | 32          | 32          | ... | 32         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2147483648 | ... | 2147483647 |
| <b>In</b>             | -1          | -1          | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 1           | ... | 1          |
| <b>Exp. Out</b>       | 1           | 1           | ... | 1          |
| <b>Out (DSP)</b>      | 2147483647  | 2147483647  | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2147483647  | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 32 |
| Max CPU cycles  | 32 |
| Avg CPU cycles  | 32 |

**Verification: Abs FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Abs.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 107        |
| <b>CPU cycles</b>     | 49          | 49          | ... | 47         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2147483648 | ... | 2147483647 |
| <b>In</b>             | -1          | -1          | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 1           | ... | 1          |
| <b>Exp. Out</b>       | 1           | 1           | ... | 1          |
| <b>Out (DSP)</b>      | 2147483647  | 2147483647  | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2147483647  | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 47 |
| Max CPU cycles  | 52 |
| Avg CPU cycles  | 48 |

**Verification: Abs FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Abs.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 107        |
| <b>CPU cycles</b>     | 67          | 59          | ... | 59         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2147483648 | ... | 2147483647 |
| <b>In</b>             | -1          | -1          | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 1           | ... | 1          |
| <b>Exp. Out</b>       | 1           | 1           | ... | 1          |
| <b>Out (DSP)</b>      | 2147483647  | 2147483647  | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2147483647  | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 67 |
| Avg CPU cycles  | 59 |



**Verification: Abs FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Abs.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 107        |
| <b>CPU cycles</b>     | 65          | 65          | ... | 60         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2147483648 | ... | 2147483647 |
| <b>In</b>             | -1          | -1          | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 1           | ... | 1          |
| <b>Exp. Out</b>       | 1           | 1           | ... | 1          |
| <b>Out (DSP)</b>      | 2147483647  | 2147483647  | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2147483647  | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 60 |
| Max CPU cycles  | 65 |
| Avg CPU cycles  | 60 |

**Verification: Abs Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Abs.

| Test results          |      |        |     |     |
|-----------------------|------|--------|-----|-----|
| <b>Time step</b>      | 1    | 2      | ... | 107 |
| <b>CPU cycles</b>     | 53   | 53     | ... | 53  |
| <i>Inputs</i>         |      |        |     |     |
| <b>In (DSP)</b>       | -1.3 | -1.268 | ... | 2.1 |
| <b>In</b>             | -1.3 | -1.268 | ... | 2.1 |
| <i>Outputs</i>        |      |        |     |     |
| <b>Out</b>            | 1.3  | 1.268  | ... | 2.1 |
| <b>Exp. Out</b>       | 1.3  | 1.268  | ... | 2.1 |
| <b>Out (DSP)</b>      | 1.3  | 1.268  | ... | 2.1 |
| <b>Exp. Out (DSP)</b> | 1.3  | 1.268  | ... | 2.1 |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 1,3970\text{e-}07$ ( $\pm 300$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 53 |
| Max CPU cycles  | 53 |
| Avg CPU cycles  | 53 |

**Verification: Abs Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Abs.

| Test results          |      |        |     |     |
|-----------------------|------|--------|-----|-----|
| <b>Time step</b>      | 1    | 2      | ... | 107 |
| <b>CPU cycles</b>     | 29   | 29     | ... | 29  |
| <i>Inputs</i>         |      |        |     |     |
| <b>In (DSP)</b>       | -1.3 | -1.268 | ... | 2.1 |
| <b>In</b>             | -1.3 | -1.268 | ... | 2.1 |
| <i>Outputs</i>        |      |        |     |     |
| <b>Out</b>            | 1.3  | 1.268  | ... | 2.1 |
| <b>Exp. Out</b>       | 1.3  | 1.268  | ... | 2.1 |
| <b>Out (DSP)</b>      | 1.3  | 1.268  | ... | 2.1 |
| <b>Exp. Out (DSP)</b> | 1.3  | 1.268  | ... | 2.1 |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 1,3970\text{e-}07$ ( $\pm 300$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 29 |
| Avg CPU cycles  | 29 |

**Verification: Abs Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Abs.

| Test results          |      |        |     |     |
|-----------------------|------|--------|-----|-----|
| <b>Time step</b>      | 1    | 2      | ... | 107 |
| <b>CPU cycles</b>     | 71   | 71     | ... | 71  |
| <i>Inputs</i>         |      |        |     |     |
| <b>In (DSP)</b>       | -1.3 | -1.268 | ... | 2.1 |
| <b>In</b>             | -1.3 | -1.268 | ... | 2.1 |
| <i>Outputs</i>        |      |        |     |     |
| <b>Out</b>            | 1.3  | 1.268  | ... | 2.1 |
| <b>Exp. Out</b>       | 1.3  | 1.268  | ... | 2.1 |
| <b>Out (DSP)</b>      | 1.3  | 1.268  | ... | 2.1 |
| <b>Exp. Out (DSP)</b> | 1.3  | 1.268  | ... | 2.1 |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 1,3970\text{e-}07$ ( $\pm 300$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 71 |
| Max CPU cycles  | 71 |
| Avg CPU cycles  | 71 |

**Verification: Abs Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Abs.

| Test results          |      |        |     |     |
|-----------------------|------|--------|-----|-----|
| <b>Time step</b>      | 1    | 2      | ... | 107 |
| <b>CPU cycles</b>     | 141  | 141    | ... | 138 |
| <i>Inputs</i>         |      |        |     |     |
| <b>In (DSP)</b>       | -1.3 | -1.268 | ... | 2.1 |
| <b>In</b>             | -1.3 | -1.268 | ... | 2.1 |
| <i>Outputs</i>        |      |        |     |     |
| <b>Out</b>            | 1.3  | 1.268  | ... | 2.1 |
| <b>Exp. Out</b>       | 1.3  | 1.268  | ... | 2.1 |
| <b>Out (DSP)</b>      | 1.3  | 1.268  | ... | 2.1 |
| <b>Exp. Out (DSP)</b> | 1.3  | 1.268  | ... | 2.1 |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 1,3970\text{e-}07$ ( $\pm 300$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 138 |
| Max CPU cycles  | 141 |
| Avg CPU cycles  | 139 |

**Verification: Abs Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Abs.

| Test results          |      |        |     |     |
|-----------------------|------|--------|-----|-----|
| <b>Time step</b>      | 1    | 2      | ... | 107 |
| <b>CPU cycles</b>     | 78   | 78     | ... | 78  |
| <i>Inputs</i>         |      |        |     |     |
| <b>In (DSP)</b>       | -1.3 | -1.268 | ... | 2.1 |
| <b>In</b>             | -1.3 | -1.268 | ... | 2.1 |
| <i>Outputs</i>        |      |        |     |     |
| <b>Out</b>            | 1.3  | 1.268  | ... | 2.1 |
| <b>Exp. Out</b>       | 1.3  | 1.268  | ... | 2.1 |
| <b>Out (DSP)</b>      | 1.3  | 1.268  | ... | 2.1 |
| <b>Exp. Out (DSP)</b> | 1.3  | 1.268  | ... | 2.1 |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 1,3970\text{e-}07$ ( $\pm 300$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 78 |
| Max CPU cycles  | 78 |
| Avg CPU cycles  | 78 |

**Verification: Abs Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Abs.

| Test results          |      |        |     |     |
|-----------------------|------|--------|-----|-----|
| <b>Time step</b>      | 1    | 2      | ... | 107 |
| <b>CPU cycles</b>     | 147  | 147    | ... | 153 |
| <i>Inputs</i>         |      |        |     |     |
| <b>In (DSP)</b>       | -1.3 | -1.268 | ... | 2.1 |
| <b>In</b>             | -1.3 | -1.268 | ... | 2.1 |
| <i>Outputs</i>        |      |        |     |     |
| <b>Out</b>            | 1.3  | 1.268  | ... | 2.1 |
| <b>Exp. Out</b>       | 1.3  | 1.268  | ... | 2.1 |
| <b>Out (DSP)</b>      | 1.3  | 1.268  | ... | 2.1 |
| <b>Exp. Out (DSP)</b> | 1.3  | 1.268  | ... | 2.1 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,3970e-07$ ( $\pm 300$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 147 |
| Max CPU cycles  | 153 |
| Avg CPU cycles  | 150 |

**Verification: Abs Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Abs.

| Test results          |      |        |     |     |
|-----------------------|------|--------|-----|-----|
| <b>Time step</b>      | 1    | 2      | ... | 107 |
| <b>CPU cycles</b>     | 69   | 59     | ... | 59  |
| <i>Inputs</i>         |      |        |     |     |
| <b>In (DSP)</b>       | -1.3 | -1.268 | ... | 2.1 |
| <b>In</b>             | -1.3 | -1.268 | ... | 2.1 |
| <i>Outputs</i>        |      |        |     |     |
| <b>Out</b>            | 1.3  | 1.268  | ... | 2.1 |
| <b>Exp. Out</b>       | 1.3  | 1.268  | ... | 2.1 |
| <b>Out (DSP)</b>      | 1.3  | 1.268  | ... | 2.1 |
| <b>Exp. Out (DSP)</b> | 1.3  | 1.268  | ... | 2.1 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,3970e-07$ ( $\pm 300$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 69 |
| Avg CPU cycles  | 59 |



**Verification: Abs Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Abs.

| Test results          |      |        |     |     |
|-----------------------|------|--------|-----|-----|
| <b>Time step</b>      | 1    | 2      | ... | 107 |
| <b>CPU cycles</b>     | 48   | 48     | ... | 48  |
| <i>Inputs</i>         |      |        |     |     |
| <b>In (DSP)</b>       | -1.3 | -1.268 | ... | 2.1 |
| <b>In</b>             | -1.3 | -1.268 | ... | 2.1 |
| <i>Outputs</i>        |      |        |     |     |
| <b>Out</b>            | 1.3  | 1.268  | ... | 2.1 |
| <b>Exp. Out</b>       | 1.3  | 1.268  | ... | 2.1 |
| <b>Out (DSP)</b>      | 1.3  | 1.268  | ... | 2.1 |
| <b>Exp. Out (DSP)</b> | 1.3  | 1.268  | ... | 2.1 |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 1,3970\text{e-}07$ ( $\pm 300$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 48 |
| Max CPU cycles  | 48 |
| Avg CPU cycles  | 48 |

## Block: Acos

---



Arccosine computation of input value.

| Inports |         |
|---------|---------|
| In      | Input u |

| Outports |                  |
|----------|------------------|
| Out      | Result of sin(u) |

### Description:

Calculation:

$$\text{Out} = \arccos(\text{In})$$

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | int8 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: Acos FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Acos.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 101    | 100    | 100    | 100    | ... | 86    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 1      | 0.945  | 0.921  | 0.904  | ... | 0     |
| <b>Exp. Out</b>       | 1      | 0.945  | 0.921  | 0.904  | ... | 0     |
| <b>Out (DSP)</b>      | 32760  | 30952  | 30194  | 29612  | ... | 7     |
| <b>Exp. Out (DSP)</b> | 32767  | 30950  | 30194  | 29611  | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 86  |
| Max CPU cycles  | 101 |
| Avg CPU cycles  | 92  |

**Verification: Acos FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Acos.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 65     | 65     | 65     | 65     | ... | 65    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 1      | 0.945  | 0.921  | 0.904  | ... | 0     |
| <b>Exp. Out</b>       | 1      | 0.945  | 0.921  | 0.904  | ... | 0     |
| <b>Out (DSP)</b>      | 32760  | 30952  | 30194  | 29612  | ... | 7     |
| <b>Exp. Out (DSP)</b> | 32767  | 30950  | 30194  | 29611  | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 65 |
| Max CPU cycles  | 65 |
| Avg CPU cycles  | 65 |

**Verification: Acos FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Acos.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 130    | 116    | 116    | 116    | ... | 96    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 1      | 0.945  | 0.921  | 0.904  | ... | 0     |
| <b>Exp. Out</b>       | 1      | 0.945  | 0.921  | 0.904  | ... | 0     |
| <b>Out (DSP)</b>      | 32760  | 30952  | 30194  | 29612  | ... | 7     |
| <b>Exp. Out (DSP)</b> | 32767  | 30950  | 30194  | 29611  | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 96  |
| Max CPU cycles  | 130 |
| Avg CPU cycles  | 107 |

**Verification: Acos FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Acos.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 107    | 103    | 103    | 103    | ... | 82    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 1      | 0.945  | 0.921  | 0.904  | ... | 0     |
| <b>Exp. Out</b>       | 1      | 0.945  | 0.921  | 0.904  | ... | 0     |
| <b>Out (DSP)</b>      | 32760  | 30952  | 30194  | 29612  | ... | 7     |
| <b>Exp. Out (DSP)</b> | 32767  | 30950  | 30194  | 29611  | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 82  |
| Max CPU cycles  | 107 |
| Avg CPU cycles  | 92  |

**Verification: Acos FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Acos.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 52     | 55     | 55     | 55     | ... | 51    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 1      | 0.945  | 0.921  | 0.904  | ... | 0     |
| <b>Exp. Out</b>       | 1      | 0.945  | 0.921  | 0.904  | ... | 0     |
| <b>Out (DSP)</b>      | 32760  | 30952  | 30194  | 29612  | ... | 7     |
| <b>Exp. Out (DSP)</b> | 32767  | 30950  | 30194  | 29611  | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 51 |
| Max CPU cycles  | 55 |
| Avg CPU cycles  | 52 |



**Verification: Acos FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Acos.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 72     | 71     | 71     | 71     | ... | 69    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 1      | 0.945  | 0.921  | 0.904  | ... | 0     |
| <b>Exp. Out</b>       | 1      | 0.945  | 0.921  | 0.904  | ... | 0     |
| <b>Out (DSP)</b>      | 32760  | 30952  | 30194  | 29612  | ... | 7     |
| <b>Exp. Out (DSP)</b> | 32767  | 30950  | 30194  | 29611  | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 69 |
| Max CPU cycles  | 72 |
| Avg CPU cycles  | 70 |

**Verification: Acos FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Acos.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 115    | 102    | 102    | 102    | ... | 93    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 1      | 0.945  | 0.921  | 0.904  | ... | 0     |
| <b>Exp. Out</b>       | 1      | 0.945  | 0.921  | 0.904  | ... | 0     |
| <b>Out (DSP)</b>      | 32760  | 30952  | 30194  | 29612  | ... | 7     |
| <b>Exp. Out (DSP)</b> | 32767  | 30950  | 30194  | 29611  | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 93  |
| Max CPU cycles  | 115 |
| Avg CPU cycles  | 97  |

**Verification: Acos FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Acos.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 101    | 96     | 96     | 96     | ... | 78    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 1      | 0.945  | 0.921  | 0.904  | ... | 0     |
| <b>Exp. Out</b>       | 1      | 0.945  | 0.921  | 0.904  | ... | 0     |
| <b>Out (DSP)</b>      | 32760  | 30952  | 30194  | 29612  | ... | 7     |
| <b>Exp. Out (DSP)</b> | 32767  | 30950  | 30194  | 29611  | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 78  |
| Max CPU cycles  | 101 |
| Avg CPU cycles  | 87  |

**Verification: Acos FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Acos.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 117         | 118         | ... | 100        |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 0.945       | ... | 0          |
| <b>Exp. Out</b>       | 1           | 0.945       | ... | 0          |
| <b>Out (DSP)</b>      | 2147483640  | 2028456395  | ... | 7          |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2028339448  | ... | 0          |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 9,3132e-05$ ( $\pm 200000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 100 |
| Max CPU cycles  | 118 |
| Avg CPU cycles  | 108 |

**Verification: Acos FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Acos.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 63          | 63          | ... | 57         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 0.945       | ... | 0          |
| <b>Exp. Out</b>       | 1           | 0.945       | ... | 0          |
| <b>Out (DSP)</b>      | 2147483640  | 2028456395  | ... | 7          |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2028339448  | ... | 0          |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 9,3132e-05$ ( $\pm 200000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 63 |
| Avg CPU cycles  | 59 |

**Verification: Acos FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Acos.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 150         | 127         | ... | 102        |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 0.945       | ... | 0          |
| <b>Exp. Out</b>       | 1           | 0.945       | ... | 0          |
| <b>Out (DSP)</b>      | 2147483640  | 2028456395  | ... | 7          |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2028339448  | ... | 0          |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 9,3132e-05$ ( $\pm 200000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 97  |
| Max CPU cycles  | 150 |
| Avg CPU cycles  | 114 |

**Verification: Acos FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Acos.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 175         | 167         | ... | 148        |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 0.945       | ... | 0          |
| <b>Exp. Out</b>       | 1           | 0.945       | ... | 0          |
| <b>Out (DSP)</b>      | 2147483640  | 2028456395  | ... | 7          |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2028339448  | ... | 0          |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 9,3132e-05$ ( $\pm 200000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 148 |
| Max CPU cycles  | 227 |
| Avg CPU cycles  | 158 |

**Verification: Acos FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Acos.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 66          | 68          | ... | 54         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 0.945       | ... | 0          |
| <b>Exp. Out</b>       | 1           | 0.945       | ... | 0          |
| <b>Out (DSP)</b>      | 2147483640  | 2028456395  | ... | 7          |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2028339448  | ... | 0          |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 9,3132e-05$ ( $\pm 200000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 53 |
| Max CPU cycles  | 68 |
| Avg CPU cycles  | 60 |



**Verification: Acos FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Acos.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 221         | 223         | ... | 213        |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 0.945       | ... | 0          |
| <b>Exp. Out</b>       | 1           | 0.945       | ... | 0          |
| <b>Out (DSP)</b>      | 2147483640  | 2028456395  | ... | 7          |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2028339448  | ... | 0          |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 9,3132e-05$ ( $\pm 200000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 213 |
| Max CPU cycles  | 223 |
| Avg CPU cycles  | 217 |

**Verification: Acos FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Acos.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 123         | 109         | ... | 100        |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 0.945       | ... | 0          |
| <b>Exp. Out</b>       | 1           | 0.945       | ... | 0          |
| <b>Out (DSP)</b>      | 2147483640  | 2028456395  | ... | 7          |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2028339448  | ... | 0          |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 9,3132e-05$ ( $\pm 200000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 100 |
| Max CPU cycles  | 123 |
| Avg CPU cycles  | 104 |

**Verification: Acos FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Acos.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 116         | 118         | ... | 96         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 0.945       | ... | 0          |
| <b>Exp. Out</b>       | 1           | 0.945       | ... | 0          |
| <b>Out (DSP)</b>      | 2147483640  | 2028456395  | ... | 7          |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2028339448  | ... | 0          |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 9,3132e-05$ ( $\pm 200000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 91  |
| Max CPU cycles  | 121 |
| Avg CPU cycles  | 105 |

**Verification: Acos Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Acos.

| Test results          |       |        |     |     |
|-----------------------|-------|--------|-----|-----|
| <b>Time step</b>      | 1     | 2      | ... | 133 |
| <b>CPU cycles</b>     | 167   | 652    | ... | 151 |
| <i>Inputs</i>         |       |        |     |     |
| <b>In (DSP)</b>       | -1    | -0.985 | ... | 1   |
| <b>In</b>             | -1    | -0.985 | ... | 1   |
| <i>Outputs</i>        |       |        |     |     |
| <b>Out</b>            | 3.142 | 2.967  | ... | 0   |
| <b>Exp. Out</b>       | 3.142 | 2.967  | ... | 0   |
| <b>Out (DSP)</b>      | 3.142 | 2.967  | ... | 0   |
| <b>Exp. Out (DSP)</b> | 3.142 | 2.967  | ... | 0   |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 2,7940\text{e-}07$ ( $\pm 600$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 151 |
| Max CPU cycles  | 935 |
| Avg CPU cycles  | 641 |

**Verification: Acos Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Acos.

| Test results          |       |        |     |     |
|-----------------------|-------|--------|-----|-----|
| <b>Time step</b>      | 1     | 2      | ... | 133 |
| <b>CPU cycles</b>     | 83    | 169    | ... | 83  |
| <i>Inputs</i>         |       |        |     |     |
| <b>In (DSP)</b>       | -1    | -0.985 | ... | 1   |
| <b>In</b>             | -1    | -0.985 | ... | 1   |
| <i>Outputs</i>        |       |        |     |     |
| <b>Out</b>            | 3.142 | 2.967  | ... | 0   |
| <b>Exp. Out</b>       | 3.142 | 2.967  | ... | 0   |
| <b>Out (DSP)</b>      | 3.142 | 2.967  | ... | 0   |
| <b>Exp. Out (DSP)</b> | 3.142 | 2.967  | ... | 0   |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 2,7940\text{e-}07$ ( $\pm 600$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 83  |
| Max CPU cycles  | 187 |
| Avg CPU cycles  | 163 |

**Verification: Acos Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Acos.

| Test results          |       |        |     |     |
|-----------------------|-------|--------|-----|-----|
| <b>Time step</b>      | 1     | 2      | ... | 133 |
| <b>CPU cycles</b>     | 218   | 385    | ... | 218 |
| <i>Inputs</i>         |       |        |     |     |
| <b>In (DSP)</b>       | -1    | -0.985 | ... | 1   |
| <b>In</b>             | -1    | -0.985 | ... | 1   |
| <i>Outputs</i>        |       |        |     |     |
| <b>Out</b>            | 3.142 | 2.967  | ... | 0   |
| <b>Exp. Out</b>       | 3.142 | 2.967  | ... | 0   |
| <b>Out (DSP)</b>      | 3.142 | 2.967  | ... | 0   |
| <b>Exp. Out (DSP)</b> | 3.142 | 2.967  | ... | 0   |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 2,7940\text{e-}07$ ( $\pm 600$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 218 |
| Max CPU cycles  | 444 |
| Avg CPU cycles  | 367 |

**Verification: Acos Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Acos.

| Test results          |       |        |     |     |
|-----------------------|-------|--------|-----|-----|
| <b>Time step</b>      | 1     | 2      | ... | 133 |
| <b>CPU cycles</b>     | 241   | 5330   | ... | 240 |
| <i>Inputs</i>         |       |        |     |     |
| <b>In (DSP)</b>       | -1    | -0.985 | ... | 1   |
| <b>In</b>             | -1    | -0.985 | ... | 1   |
| <i>Outputs</i>        |       |        |     |     |
| <b>Out</b>            | 3.142 | 2.967  | ... | 0   |
| <b>Exp. Out</b>       | 3.142 | 2.967  | ... | 0   |
| <b>Out (DSP)</b>      | 3.142 | 2.967  | ... | 0   |
| <b>Exp. Out (DSP)</b> | 3.142 | 2.967  | ... | 0   |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 2,7940\text{e-}07$ ( $\pm 600$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 240  |
| Max CPU cycles  | 6329 |
| Avg CPU cycles  | 5152 |

**Verification: Acos Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Acos.

| Test results          |       |        |     |     |
|-----------------------|-------|--------|-----|-----|
| <b>Time step</b>      | 1     | 2      | ... | 133 |
| <b>CPU cycles</b>     | 349   | 649    | ... | 333 |
| <i>Inputs</i>         |       |        |     |     |
| <b>In (DSP)</b>       | -1    | -0.985 | ... | 1   |
| <b>In</b>             | -1    | -0.985 | ... | 1   |
| <i>Outputs</i>        |       |        |     |     |
| <b>Out</b>            | 3.142 | 2.967  | ... | 0   |
| <b>Exp. Out</b>       | 3.142 | 2.967  | ... | 0   |
| <b>Out (DSP)</b>      | 3.142 | 2.967  | ... | 0   |
| <b>Exp. Out (DSP)</b> | 3.142 | 2.967  | ... | 0   |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 2,7940\text{e-}07$ ( $\pm 600$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 333 |
| Max CPU cycles  | 776 |
| Avg CPU cycles  | 710 |



**Verification: Acos Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Acos.

| Test results          |       |        |     |      |
|-----------------------|-------|--------|-----|------|
| <b>Time step</b>      | 1     | 2      | ... | 133  |
| <b>CPU cycles</b>     | 2060  | 3858   | ... | 1940 |
| <i>Inputs</i>         |       |        |     |      |
| <b>In (DSP)</b>       | -1    | -0.985 | ... | 1    |
| <b>In</b>             | -1    | -0.985 | ... | 1    |
| <i>Outputs</i>        |       |        |     |      |
| <b>Out</b>            | 3.142 | 2.967  | ... | 0    |
| <b>Exp. Out</b>       | 3.142 | 2.967  | ... | 0    |
| <b>Out (DSP)</b>      | 3.142 | 2.967  | ... | 0    |
| <b>Exp. Out (DSP)</b> | 3.142 | 2.967  | ... | 0    |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 2,7940\text{e-}07$ ( $\pm 600$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 443  |
| Max CPU cycles  | 3858 |
| Avg CPU cycles  | 3088 |

**Verification: Acos Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Acos.

| Test results          |       |        |     |     |
|-----------------------|-------|--------|-----|-----|
| <b>Time step</b>      | 1     | 2      | ... | 133 |
| <b>CPU cycles</b>     | 235   | 601    | ... | 181 |
| <i>Inputs</i>         |       |        |     |     |
| <b>In (DSP)</b>       | -1    | -0.985 | ... | 1   |
| <b>In</b>             | -1    | -0.985 | ... | 1   |
| <i>Outputs</i>        |       |        |     |     |
| <b>Out</b>            | 3.142 | 2.967  | ... | 0   |
| <b>Exp. Out</b>       | 3.142 | 2.967  | ... | 0   |
| <b>Out (DSP)</b>      | 3.142 | 2.967  | ... | 0   |
| <b>Exp. Out (DSP)</b> | 3.142 | 2.967  | ... | 0   |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 2,7940\text{e-}07$ ( $\pm 600$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 175 |
| Max CPU cycles  | 601 |
| Avg CPU cycles  | 412 |

**Verification: Acos Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Acos.

| Test results          |       |        |     |     |
|-----------------------|-------|--------|-----|-----|
| <b>Time step</b>      | 1     | 2      | ... | 133 |
| <b>CPU cycles</b>     | 127   | 467    | ... | 117 |
| <i>Inputs</i>         |       |        |     |     |
| <b>In (DSP)</b>       | -1    | -0.985 | ... | 1   |
| <b>In</b>             | -1    | -0.985 | ... | 1   |
| <i>Outputs</i>        |       |        |     |     |
| <b>Out</b>            | 3.142 | 2.967  | ... | 0   |
| <b>Exp. Out</b>       | 3.142 | 2.967  | ... | 0   |
| <b>Out (DSP)</b>      | 3.142 | 2.967  | ... | 0   |
| <b>Exp. Out (DSP)</b> | 3.142 | 2.967  | ... | 0   |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 2,7940\text{e-}07$ ( $\pm 600$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 117 |
| Max CPU cycles  | 719 |
| Avg CPU cycles  | 480 |

## Block: Add

---



Addition of input 1 and input 2.

| Inports |          |
|---------|----------|
| In1     | Addend 1 |
| In2     | Addend 2 |

| Outports |     |
|----------|-----|
| Out      | Sum |

### Description:

Calculation:

$$\text{Out} = \text{In}_1 + \text{In}_2$$

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In1               | int8 |
| In2               | int8 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In1               | int16 |
| In2               | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In1               | int32 |
| In2               | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In1               | float32 |
| In2               | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In1               | float64 |
| In2               | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: Add FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Add.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 68     | 68     | 68     | 68     | ... | 65    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In1 (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>In2 (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>In1</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>In2</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -0     | 0      | 0      | 0      | ... | 1     |
| <b>Exp. Out</b>       | 0      | 0      | 0      | 0      | ... | 1     |
| <b>Out (DSP)</b>      | -1     | 0      | 0      | 0      | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 0      | 0      | 0      | 0      | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 65 |
| Max CPU cycles  | 68 |
| Avg CPU cycles  | 67 |

**Verification: Add FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Add.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 37     | 37     | 37     | 37     | ... | 31    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In1 (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>In2 (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>In1</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>In2</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -0     | 0      | 0      | 0      | ... | 1     |
| <b>Exp. Out</b>       | 0      | 0      | 0      | 0      | ... | 1     |
| <b>Out (DSP)</b>      | -1     | 0      | 0      | 0      | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 0      | 0      | 0      | 0      | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 37 |
| Avg CPU cycles  | 36 |

**Verification: Add FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Add.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 81     | 81     | 81     | 81     | ... | 81    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In1 (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>In2 (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>In1</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>In2</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -0     | 0      | 0      | 0      | ... | 1     |
| <b>Exp. Out</b>       | 0      | 0      | 0      | 0      | ... | 1     |
| <b>Out (DSP)</b>      | -1     | 0      | 0      | 0      | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 0      | 0      | 0      | 0      | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 81 |
| Max CPU cycles  | 81 |
| Avg CPU cycles  | 81 |



**Verification: Add FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Add.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 66     | 66     | 66     | 66     | ... | 67    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In1 (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>In2 (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>In1</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>In2</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -0     | 0      | 0      | 0      | ... | 1     |
| <b>Exp. Out</b>       | 0      | 0      | 0      | 0      | ... | 1     |
| <b>Out (DSP)</b>      | -1     | 0      | 0      | 0      | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 0      | 0      | 0      | 0      | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 65  |
| Max CPU cycles  | 126 |
| Avg CPU cycles  | 66  |

**Verification: Add FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Add.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 39     | 39     | 39     | 39     | ... | 39    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In1 (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>In2 (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>In1</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>In2</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -0     | 0      | 0      | 0      | ... | 1     |
| <b>Exp. Out</b>       | 0      | 0      | 0      | 0      | ... | 1     |
| <b>Out (DSP)</b>      | -1     | 0      | 0      | 0      | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 0      | 0      | 0      | 0      | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 39 |
| Max CPU cycles  | 39 |
| Avg CPU cycles  | 39 |

**Verification: Add FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Add.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 59     | 59     | 59     | 59     | ... | 58    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In1 (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>In2 (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>In1</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>In2</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -0     | 0      | 0      | 0      | ... | 1     |
| <b>Exp. Out</b>       | 0      | 0      | 0      | 0      | ... | 1     |
| <b>Out (DSP)</b>      | -1     | 0      | 0      | 0      | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 0      | 0      | 0      | 0      | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 58 |
| Max CPU cycles  | 59 |
| Avg CPU cycles  | 58 |

**Verification: Add FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Add.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 76     | 69     | 69     | 69     | ... | 69    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In1 (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>In2 (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>In1</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>In2</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -0     | 0      | 0      | 0      | ... | 1     |
| <b>Exp. Out</b>       | 0      | 0      | 0      | 0      | ... | 1     |
| <b>Out (DSP)</b>      | -1     | 0      | 0      | 0      | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 0      | 0      | 0      | 0      | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 69 |
| Max CPU cycles  | 76 |
| Avg CPU cycles  | 69 |

**Verification: Add FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Add.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 69     | 69     | 69     | 69     | ... | 63    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In1 (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>In2 (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>In1</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>In2</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -0     | 0      | 0      | 0      | ... | 1     |
| <b>Exp. Out</b>       | 0      | 0      | 0      | 0      | ... | 1     |
| <b>Out (DSP)</b>      | -1     | 0      | 0      | 0      | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 0      | 0      | 0      | 0      | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 63 |
| Max CPU cycles  | 69 |
| Avg CPU cycles  | 68 |

**Verification: Add FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Add.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 159         | 159         | ... | 112        |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -0          | 0           | ... | 1          |
| <b>Exp. Out</b>       | 0           | 0           | ... | 1          |
| <b>Out (DSP)</b>      | -1          | 0           | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 0           | 0           | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 112 |
| Max CPU cycles  | 165 |
| Avg CPU cycles  | 153 |

**Verification: Add FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Add.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 57          | 57          | ... | 51         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -0          | 0           | ... | 1          |
| <b>Exp. Out</b>       | 0           | 0           | ... | 1          |
| <b>Out (DSP)</b>      | -1          | 0           | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 0           | 0           | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 51 |
| Max CPU cycles  | 61 |
| Avg CPU cycles  | 56 |

**Verification: Add FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Add.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 91          | 91          | ... | 91         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -0          | 0           | ... | 1          |
| <b>Exp. Out</b>       | 0           | 0           | ... | 1          |
| <b>Out (DSP)</b>      | -1          | 0           | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 0           | 0           | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 91  |
| Max CPU cycles  | 153 |
| Avg CPU cycles  | 91  |



**Verification: Add FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Add.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 87          | 81          | ... | 86         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -0          | 0           | ... | 1          |
| <b>Exp. Out</b>       | 0           | 0           | ... | 1          |
| <b>Out (DSP)</b>      | -1          | 0           | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 0           | 0           | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 81  |
| Max CPU cycles  | 141 |
| Avg CPU cycles  | 82  |

**Verification: Add FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Add.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 49          | 48          | ... | 49         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -0          | 0           | ... | 1          |
| <b>Exp. Out</b>       | 0           | 0           | ... | 1          |
| <b>Out (DSP)</b>      | -1          | 0           | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 0           | 0           | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 48 |
| Max CPU cycles  | 51 |
| Avg CPU cycles  | 48 |

**Verification: Add FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Add.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 81          | 81          | ... | 82         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -0          | 0           | ... | 1          |
| <b>Exp. Out</b>       | 0           | 0           | ... | 1          |
| <b>Out (DSP)</b>      | -1          | 0           | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 0           | 0           | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 81 |
| Max CPU cycles  | 82 |
| Avg CPU cycles  | 81 |

**Verification: Add FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Add.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 86          | 87          | ... | 87         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -0          | 0           | ... | 1          |
| <b>Exp. Out</b>       | 0           | 0           | ... | 1          |
| <b>Out (DSP)</b>      | -1          | 0           | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 0           | 0           | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 86 |
| Max CPU cycles  | 87 |
| Avg CPU cycles  | 86 |

**Verification: Add FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Add.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 152         | 152         | ... | 106        |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -0          | 0           | ... | 1          |
| <b>Exp. Out</b>       | 0           | 0           | ... | 1          |
| <b>Out (DSP)</b>      | -1          | 0           | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 0           | 0           | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 106 |
| Max CPU cycles  | 154 |
| Avg CPU cycles  | 146 |

**Verification: Add Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Add.

| Test results          |    |        |     |     |
|-----------------------|----|--------|-----|-----|
| <b>Time step</b>      | 1  | 2      | ... | 214 |
| <b>CPU cycles</b>     | 53 | 53     | ... | 53  |
| <i>Inputs</i>         |    |        |     |     |
| <b>In1 (DSP)</b>      | -2 | -1.962 | ... | 2   |
| <b>In2 (DSP)</b>      | 2  | 1.962  | ... | 2   |
| <b>In1</b>            | -2 | -1.962 | ... | 2   |
| <b>In2</b>            | 2  | 1.962  | ... | 2   |
| <i>Outputs</i>        |    |        |     |     |
| <b>Out</b>            | 0  | 0      | ... | 4   |
| <b>Exp. Out</b>       | 0  | 0      | ... | 4   |
| <b>Out (DSP)</b>      | 0  | 0      | ... | 4   |
| <b>Exp. Out (DSP)</b> | 0  | 0      | ... | 4   |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance Out | $\pm 5,1223\text{e-}07$ ( $\pm 1100$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 53 |
| Max CPU cycles  | 53 |
| Avg CPU cycles  | 53 |

**Verification: Add Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Add.

| Test results          |    |        |     |     |
|-----------------------|----|--------|-----|-----|
| <b>Time step</b>      | 1  | 2      | ... | 214 |
| <b>CPU cycles</b>     | 29 | 29     | ... | 29  |
| <i>Inputs</i>         |    |        |     |     |
| <b>In1 (DSP)</b>      | -2 | -1.962 | ... | 2   |
| <b>In2 (DSP)</b>      | 2  | 1.962  | ... | 2   |
| <b>In1</b>            | -2 | -1.962 | ... | 2   |
| <b>In2</b>            | 2  | 1.962  | ... | 2   |
| <i>Outputs</i>        |    |        |     |     |
| <b>Out</b>            | 0  | 0      | ... | 4   |
| <b>Exp. Out</b>       | 0  | 0      | ... | 4   |
| <b>Out (DSP)</b>      | 0  | 0      | ... | 4   |
| <b>Exp. Out (DSP)</b> | 0  | 0      | ... | 4   |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 5,1223e-07$ ( $\pm 1100$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 29 |
| Avg CPU cycles  | 29 |

**Verification: Add Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Add.

| Test results          |    |        |     |     |
|-----------------------|----|--------|-----|-----|
| <b>Time step</b>      | 1  | 2      | ... | 214 |
| <b>CPU cycles</b>     | 66 | 66     | ... | 66  |
| <i>Inputs</i>         |    |        |     |     |
| <b>In1 (DSP)</b>      | -2 | -1.962 | ... | 2   |
| <b>In2 (DSP)</b>      | 2  | 1.962  | ... | 2   |
| <b>In1</b>            | -2 | -1.962 | ... | 2   |
| <b>In2</b>            | 2  | 1.962  | ... | 2   |
| <i>Outputs</i>        |    |        |     |     |
| <b>Out</b>            | 0  | 0      | ... | 4   |
| <b>Exp. Out</b>       | 0  | 0      | ... | 4   |
| <b>Out (DSP)</b>      | 0  | 0      | ... | 4   |
| <b>Exp. Out (DSP)</b> | 0  | 0      | ... | 4   |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 5,1223e-07$ ( $\pm 1100$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 66 |
| Max CPU cycles  | 66 |
| Avg CPU cycles  | 66 |



**Verification: Add Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Add.

| Test results          |     |        |     |     |
|-----------------------|-----|--------|-----|-----|
| <b>Time step</b>      | 1   | 2      | ... | 214 |
| <b>CPU cycles</b>     | 144 | 144    | ... | 147 |
| <i>Inputs</i>         |     |        |     |     |
| <b>In1 (DSP)</b>      | -2  | -1.962 | ... | 2   |
| <b>In2 (DSP)</b>      | 2   | 1.962  | ... | 2   |
| <b>In1</b>            | -2  | -1.962 | ... | 2   |
| <b>In2</b>            | 2   | 1.962  | ... | 2   |
| <i>Outputs</i>        |     |        |     |     |
| <b>Out</b>            | 0   | 0      | ... | 4   |
| <b>Exp. Out</b>       | 0   | 0      | ... | 4   |
| <b>Out (DSP)</b>      | 0   | 0      | ... | 4   |
| <b>Exp. Out (DSP)</b> | 0   | 0      | ... | 4   |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 5,1223e-07$ ( $\pm 1100$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 144 |
| Max CPU cycles  | 147 |
| Avg CPU cycles  | 145 |

**Verification: Add Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Add.

| Test results          |    |        |     |     |
|-----------------------|----|--------|-----|-----|
| <b>Time step</b>      | 1  | 2      | ... | 214 |
| <b>CPU cycles</b>     | 86 | 86     | ... | 102 |
| <i>Inputs</i>         |    |        |     |     |
| <b>In1 (DSP)</b>      | -2 | -1.962 | ... | 2   |
| <b>In2 (DSP)</b>      | 2  | 1.962  | ... | 2   |
| <b>In1</b>            | -2 | -1.962 | ... | 2   |
| <b>In2</b>            | 2  | 1.962  | ... | 2   |
| <i>Outputs</i>        |    |        |     |     |
| <b>Out</b>            | 0  | 0      | ... | 4   |
| <b>Exp. Out</b>       | 0  | 0      | ... | 4   |
| <b>Out (DSP)</b>      | 0  | 0      | ... | 4   |
| <b>Exp. Out (DSP)</b> | 0  | 0      | ... | 4   |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 5,1223e-07$ ( $\pm 1100$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 72  |
| Max CPU cycles  | 102 |
| Avg CPU cycles  | 93  |

**Verification: Add Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Add.

| Test results          |     |        |     |     |
|-----------------------|-----|--------|-----|-----|
| <b>Time step</b>      | 1   | 2      | ... | 214 |
| <b>CPU cycles</b>     | 240 | 240    | ... | 203 |
| <i>Inputs</i>         |     |        |     |     |
| <b>In1 (DSP)</b>      | -2  | -1.962 | ... | 2   |
| <b>In2 (DSP)</b>      | 2   | 1.962  | ... | 2   |
| <b>In1</b>            | -2  | -1.962 | ... | 2   |
| <b>In2</b>            | 2   | 1.962  | ... | 2   |
| <i>Outputs</i>        |     |        |     |     |
| <b>Out</b>            | 0   | 0      | ... | 4   |
| <b>Exp. Out</b>       | 0   | 0      | ... | 4   |
| <b>Out (DSP)</b>      | 0   | 0      | ... | 4   |
| <b>Exp. Out (DSP)</b> | 0   | 0      | ... | 4   |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 5,1223e-07$ ( $\pm 1100$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 203 |
| Max CPU cycles  | 240 |
| Avg CPU cycles  | 221 |

**Verification: Add Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Add.

| Test results          |    |        |     |     |
|-----------------------|----|--------|-----|-----|
| <b>Time step</b>      | 1  | 2      | ... | 214 |
| <b>CPU cycles</b>     | 68 | 57     | ... | 57  |
| <i>Inputs</i>         |    |        |     |     |
| <b>In1 (DSP)</b>      | -2 | -1.962 | ... | 2   |
| <b>In2 (DSP)</b>      | 2  | 1.962  | ... | 2   |
| <b>In1</b>            | -2 | -1.962 | ... | 2   |
| <b>In2</b>            | 2  | 1.962  | ... | 2   |
| <i>Outputs</i>        |    |        |     |     |
| <b>Out</b>            | 0  | 0      | ... | 4   |
| <b>Exp. Out</b>       | 0  | 0      | ... | 4   |
| <b>Out (DSP)</b>      | 0  | 0      | ... | 4   |
| <b>Exp. Out (DSP)</b> | 0  | 0      | ... | 4   |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 5,1223e-07$ ( $\pm 1100$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 68 |
| Avg CPU cycles  | 57 |

**Verification: Add Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Add.

| Test results          |    |        |     |     |
|-----------------------|----|--------|-----|-----|
| <b>Time step</b>      | 1  | 2      | ... | 214 |
| <b>CPU cycles</b>     | 47 | 47     | ... | 47  |
| <i>Inputs</i>         |    |        |     |     |
| <b>In1 (DSP)</b>      | -2 | -1.962 | ... | 2   |
| <b>In2 (DSP)</b>      | 2  | 1.962  | ... | 2   |
| <b>In1</b>            | -2 | -1.962 | ... | 2   |
| <b>In2</b>            | 2  | 1.962  | ... | 2   |
| <i>Outputs</i>        |    |        |     |     |
| <b>Out</b>            | 0  | 0      | ... | 4   |
| <b>Exp. Out</b>       | 0  | 0      | ... | 4   |
| <b>Out (DSP)</b>      | 0  | 0      | ... | 4   |
| <b>Exp. Out (DSP)</b> | 0  | 0      | ... | 4   |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 5,1223e-07$ ( $\pm 1100$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 47 |
| Max CPU cycles  | 47 |
| Avg CPU cycles  | 47 |

## Block: Asin

---



Arcsine computation of input value.

| Inports |         |
|---------|---------|
| In      | Input u |

| Outports |                  |
|----------|------------------|
| Out      | Result of sin(u) |

### Description:

Calculation:

$$\text{Out} = \arcsin(\text{In})$$

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | int8 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: Asin FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Asin.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 98     | 97     | 97     | 97     | ... | 86    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -0.5   | -0.445 | -0.421 | -0.404 | ... | 0.5   |
| <b>Exp. Out</b>       | -0.5   | -0.445 | -0.421 | -0.404 | ... | 0.5   |
| <b>Out (DSP)</b>      | -16376 | -14569 | -13810 | -13228 | ... | 16376 |
| <b>Exp. Out (DSP)</b> | -16384 | -14566 | -13810 | -13227 | ... | 16384 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 86 |
| Max CPU cycles  | 98 |
| Avg CPU cycles  | 91 |



**Verification: Asin FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Asin.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 65     | 65     | 65     | 65     | ... | 65    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -0.5   | -0.445 | -0.421 | -0.404 | ... | 0.5   |
| <b>Exp. Out</b>       | -0.5   | -0.445 | -0.421 | -0.404 | ... | 0.5   |
| <b>Out (DSP)</b>      | -16376 | -14569 | -13810 | -13228 | ... | 16376 |
| <b>Exp. Out (DSP)</b> | -16384 | -14566 | -13810 | -13227 | ... | 16384 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 65 |
| Max CPU cycles  | 65 |
| Avg CPU cycles  | 65 |

**Verification: Asin FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Asin.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 130    | 107    | 107    | 107    | ... | 101   |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -0.5   | -0.445 | -0.421 | -0.404 | ... | 0.5   |
| <b>Exp. Out</b>       | -0.5   | -0.445 | -0.421 | -0.404 | ... | 0.5   |
| <b>Out (DSP)</b>      | -16376 | -14569 | -13810 | -13228 | ... | 16376 |
| <b>Exp. Out (DSP)</b> | -16384 | -14566 | -13810 | -13227 | ... | 16384 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 96  |
| Max CPU cycles  | 130 |
| Avg CPU cycles  | 102 |

**Verification: Asin FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Asin.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 102    | 97     | 97     | 97     | ... | 80    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -0.5   | -0.445 | -0.421 | -0.404 | ... | 0.5   |
| <b>Exp. Out</b>       | -0.5   | -0.445 | -0.421 | -0.404 | ... | 0.5   |
| <b>Out (DSP)</b>      | -16376 | -14569 | -13810 | -13228 | ... | 16376 |
| <b>Exp. Out (DSP)</b> | -16384 | -14566 | -13810 | -13227 | ... | 16384 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 80  |
| Max CPU cycles  | 102 |
| Avg CPU cycles  | 88  |

**Verification: Asin FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Asin.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 52     | 55     | 55     | 55     | ... | 51    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -0.5   | -0.445 | -0.421 | -0.404 | ... | 0.5   |
| <b>Exp. Out</b>       | -0.5   | -0.445 | -0.421 | -0.404 | ... | 0.5   |
| <b>Out (DSP)</b>      | -16376 | -14569 | -13810 | -13228 | ... | 16376 |
| <b>Exp. Out (DSP)</b> | -16384 | -14566 | -13810 | -13227 | ... | 16384 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 51 |
| Max CPU cycles  | 55 |
| Avg CPU cycles  | 52 |

**Verification: Asin FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Asin.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 71     | 70     | 70     | 70     | ... | 69    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -0.5   | -0.445 | -0.421 | -0.404 | ... | 0.5   |
| <b>Exp. Out</b>       | -0.5   | -0.445 | -0.421 | -0.404 | ... | 0.5   |
| <b>Out (DSP)</b>      | -16376 | -14569 | -13810 | -13228 | ... | 16376 |
| <b>Exp. Out (DSP)</b> | -16384 | -14566 | -13810 | -13227 | ... | 16384 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 69 |
| Max CPU cycles  | 71 |
| Avg CPU cycles  | 69 |

**Verification: Asin FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Asin.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 121    | 101    | 101    | 101    | ... | 95    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -0.5   | -0.445 | -0.421 | -0.404 | ... | 0.5   |
| <b>Exp. Out</b>       | -0.5   | -0.445 | -0.421 | -0.404 | ... | 0.5   |
| <b>Out (DSP)</b>      | -16376 | -14569 | -13810 | -13228 | ... | 16376 |
| <b>Exp. Out (DSP)</b> | -16384 | -14566 | -13810 | -13227 | ... | 16384 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 93  |
| Max CPU cycles  | 121 |
| Avg CPU cycles  | 97  |

**Verification: Asin FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Asin.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 97     | 95     | 92     | 95     | ... | 76    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -0.5   | -0.445 | -0.421 | -0.404 | ... | 0.5   |
| <b>Exp. Out</b>       | -0.5   | -0.445 | -0.421 | -0.404 | ... | 0.5   |
| <b>Out (DSP)</b>      | -16376 | -14569 | -13810 | -13228 | ... | 16376 |
| <b>Exp. Out (DSP)</b> | -16384 | -14566 | -13810 | -13227 | ... | 16384 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 2,4414e-04$ ( $\pm 8$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 76 |
| Max CPU cycles  | 97 |
| Avg CPU cycles  | 84 |

**Verification: Asin FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Asin.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 112         | 112         | ... | 98         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -0.5        | -0.445      | ... | 0.5        |
| <b>Exp. Out</b>       | -0.5        | -0.445      | ... | 0.5        |
| <b>Out (DSP)</b>      | -1073741816 | -954714571  | ... | 1073741816 |
| <b>Exp. Out (DSP)</b> | -1073741824 | -954597624  | ... | 1073741824 |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 9,3132e-05$ ( $\pm 200000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 98  |
| Max CPU cycles  | 112 |
| Avg CPU cycles  | 104 |



**Verification: Asin FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Asin.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 61          | 61          | ... | 57         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -0.5        | -0.445      | ... | 0.5        |
| <b>Exp. Out</b>       | -0.5        | -0.445      | ... | 0.5        |
| <b>Out (DSP)</b>      | -1073741816 | -954714571  | ... | 1073741816 |
| <b>Exp. Out (DSP)</b> | -1073741824 | -954597624  | ... | 1073741824 |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 9,3132e-05$ ( $\pm 200000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 61 |
| Avg CPU cycles  | 58 |

**Verification: Asin FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Asin.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 139         | 130         | ... | 96         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -0.5        | -0.445      | ... | 0.5        |
| <b>Exp. Out</b>       | -0.5        | -0.445      | ... | 0.5        |
| <b>Out (DSP)</b>      | -1073741816 | -954714571  | ... | 1073741816 |
| <b>Exp. Out (DSP)</b> | -1073741824 | -954597624  | ... | 1073741824 |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 9,3132e-05$ ( $\pm 200000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 96  |
| Max CPU cycles  | 139 |
| Avg CPU cycles  | 113 |

**Verification: Asin FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Asin.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 171         | 163         | ... | 148        |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -0.5        | -0.445      | ... | 0.5        |
| <b>Exp. Out</b>       | -0.5        | -0.445      | ... | 0.5        |
| <b>Out (DSP)</b>      | -1073741816 | -954714571  | ... | 1073741816 |
| <b>Exp. Out (DSP)</b> | -1073741824 | -954597624  | ... | 1073741824 |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 9,3132e-05$ ( $\pm 200000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 148 |
| Max CPU cycles  | 171 |
| Avg CPU cycles  | 155 |

**Verification: Asin FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Asin.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 64          | 66          | ... | 54         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -0.5        | -0.445      | ... | 0.5        |
| <b>Exp. Out</b>       | -0.5        | -0.445      | ... | 0.5        |
| <b>Out (DSP)</b>      | -1073741816 | -954714571  | ... | 1073741816 |
| <b>Exp. Out (DSP)</b> | -1073741824 | -954597624  | ... | 1073741824 |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 9,3132e-05$ ( $\pm 200000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 53 |
| Max CPU cycles  | 66 |
| Avg CPU cycles  | 59 |

**Verification: Asin FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Asin.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 212         | 214         | ... | 206        |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -0.5        | -0.445      | ... | 0.5        |
| <b>Exp. Out</b>       | -0.5        | -0.445      | ... | 0.5        |
| <b>Out (DSP)</b>      | -1073741816 | -954714571  | ... | 1073741816 |
| <b>Exp. Out (DSP)</b> | -1073741824 | -954597624  | ... | 1073741824 |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 9,3132e-05$ ( $\pm 200000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 206 |
| Max CPU cycles  | 214 |
| Avg CPU cycles  | 209 |

**Verification: Asin FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Asin.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 110         | 108         | ... | 100        |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -0.5        | -0.445      | ... | 0.5        |
| <b>Exp. Out</b>       | -0.5        | -0.445      | ... | 0.5        |
| <b>Out (DSP)</b>      | -1073741816 | -954714571  | ... | 1073741816 |
| <b>Exp. Out (DSP)</b> | -1073741824 | -954597624  | ... | 1073741824 |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 9,3132e-05$ ( $\pm 200000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 100 |
| Max CPU cycles  | 111 |
| Avg CPU cycles  | 104 |

**Verification: Asin FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Asin.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 110         | 115         | ... | 91         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -0.5        | -0.445      | ... | 0.5        |
| <b>Exp. Out</b>       | -0.5        | -0.445      | ... | 0.5        |
| <b>Out (DSP)</b>      | -1073741816 | -954714571  | ... | 1073741816 |
| <b>Exp. Out (DSP)</b> | -1073741824 | -954597624  | ... | 1073741824 |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 9,3132e-05$ ( $\pm 200000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 91  |
| Max CPU cycles  | 118 |
| Avg CPU cycles  | 103 |

**Verification: Asin Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Asin.

| Test results          |        |        |     |       |
|-----------------------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | ... | 133   |
| <b>CPU cycles</b>     | 549    | 5130   | ... | 549   |
| <i>Inputs</i>         |        |        |     |       |
| <b>In (DSP)</b>       | -1     | -0.985 | ... | 1     |
| <b>In</b>             | -1     | -0.985 | ... | 1     |
| <i>Outputs</i>        |        |        |     |       |
| <b>Out</b>            | -1.571 | -1.396 | ... | 1.571 |
| <b>Exp. Out</b>       | -1.571 | -1.396 | ... | 1.571 |
| <b>Out (DSP)</b>      | -1.571 | -1.396 | ... | 1.571 |
| <b>Exp. Out (DSP)</b> | -1.571 | -1.396 | ... | 1.571 |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 2,7940\text{e-}07$ ( $\pm 600$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 180  |
| Max CPU cycles  | 5190 |
| Avg CPU cycles  | 2794 |



**Verification: Asin Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Asin.

| Test results          |        |        |     |       |
|-----------------------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | ... | 133   |
| <b>CPU cycles</b>     | 259    | 1957   | ... | 259   |
| <i>Inputs</i>         |        |        |     |       |
| <b>In (DSP)</b>       | -1     | -0.985 | ... | 1     |
| <b>In</b>             | -1     | -0.985 | ... | 1     |
| <i>Outputs</i>        |        |        |     |       |
| <b>Out</b>            | -1.571 | -1.396 | ... | 1.571 |
| <b>Exp. Out</b>       | -1.571 | -1.396 | ... | 1.571 |
| <b>Out (DSP)</b>      | -1.571 | -1.396 | ... | 1.571 |
| <b>Exp. Out (DSP)</b> | -1.571 | -1.396 | ... | 1.571 |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 2,7940\text{e-}07$ ( $\pm 600$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 109  |
| Max CPU cycles  | 2057 |
| Avg CPU cycles  | 1055 |

**Verification: Asin Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Asin.

| Test results          |        |        |     |       |
|-----------------------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | ... | 133   |
| <b>CPU cycles</b>     | 214    | 387    | ... | 214   |
| <i>Inputs</i>         |        |        |     |       |
| <b>In (DSP)</b>       | -1     | -0.985 | ... | 1     |
| <b>In</b>             | -1     | -0.985 | ... | 1     |
| <i>Outputs</i>        |        |        |     |       |
| <b>Out</b>            | -1.571 | -1.396 | ... | 1.571 |
| <b>Exp. Out</b>       | -1.571 | -1.396 | ... | 1.571 |
| <b>Out (DSP)</b>      | -1.571 | -1.396 | ... | 1.571 |
| <b>Exp. Out (DSP)</b> | -1.571 | -1.396 | ... | 1.571 |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 2,7940\text{e-}07$ ( $\pm 600$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 214 |
| Max CPU cycles  | 446 |
| Avg CPU cycles  | 383 |

**Verification: Asin Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Asin.

| Test results          |        |        |     |       |
|-----------------------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | ... | 133   |
| <b>CPU cycles</b>     | 717    | 5326   | ... | 717   |
| <i>Inputs</i>         |        |        |     |       |
| <b>In (DSP)</b>       | -1     | -0.985 | ... | 1     |
| <b>In</b>             | -1     | -0.985 | ... | 1     |
| <i>Outputs</i>        |        |        |     |       |
| <b>Out</b>            | -1.571 | -1.396 | ... | 1.571 |
| <b>Exp. Out</b>       | -1.571 | -1.396 | ... | 1.571 |
| <b>Out (DSP)</b>      | -1.571 | -1.396 | ... | 1.571 |
| <b>Exp. Out (DSP)</b> | -1.571 | -1.396 | ... | 1.571 |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 2,7940\text{e-}07$ ( $\pm 600$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 430  |
| Max CPU cycles  | 7053 |
| Avg CPU cycles  | 5554 |

**Verification: Asin Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Asin.

| Test results          |        |        |     |       |
|-----------------------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | ... | 133   |
| <b>CPU cycles</b>     | 370    | 746    | ... | 370   |
| <i>Inputs</i>         |        |        |     |       |
| <b>In (DSP)</b>       | -1     | -0.985 | ... | 1     |
| <b>In</b>             | -1     | -0.985 | ... | 1     |
| <i>Outputs</i>        |        |        |     |       |
| <b>Out</b>            | -1.571 | -1.396 | ... | 1.571 |
| <b>Exp. Out</b>       | -1.571 | -1.396 | ... | 1.571 |
| <b>Out (DSP)</b>      | -1.571 | -1.396 | ... | 1.571 |
| <b>Exp. Out (DSP)</b> | -1.571 | -1.396 | ... | 1.571 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 2,7940e-07$ ( $\pm 600$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 370 |
| Max CPU cycles  | 763 |
| Avg CPU cycles  | 658 |

**Verification: Asin Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Asin.

| Test results          |        |        |     |       |
|-----------------------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | ... | 133   |
| <b>CPU cycles</b>     | 2054   | 3838   | ... | 2054  |
| <i>Inputs</i>         |        |        |     |       |
| <b>In (DSP)</b>       | -1     | -0.985 | ... | 1     |
| <b>In</b>             | -1     | -0.985 | ... | 1     |
| <i>Outputs</i>        |        |        |     |       |
| <b>Out</b>            | -1.571 | -1.396 | ... | 1.571 |
| <b>Exp. Out</b>       | -1.571 | -1.396 | ... | 1.571 |
| <b>Out (DSP)</b>      | -1.571 | -1.396 | ... | 1.571 |
| <b>Exp. Out (DSP)</b> | -1.571 | -1.396 | ... | 1.571 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 2,7940e-07$ ( $\pm 600$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 321  |
| Max CPU cycles  | 3838 |
| Avg CPU cycles  | 3030 |

**Verification: Asin Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Asin.

| Test results          |        |        |     |       |
|-----------------------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | ... | 133   |
| <b>CPU cycles</b>     | 255    | 664    | ... | 195   |
| <i>Inputs</i>         |        |        |     |       |
| <b>In (DSP)</b>       | -1     | -0.985 | ... | 1     |
| <b>In</b>             | -1     | -0.985 | ... | 1     |
| <i>Outputs</i>        |        |        |     |       |
| <b>Out</b>            | -1.571 | -1.396 | ... | 1.571 |
| <b>Exp. Out</b>       | -1.571 | -1.396 | ... | 1.571 |
| <b>Out (DSP)</b>      | -1.571 | -1.396 | ... | 1.571 |
| <b>Exp. Out (DSP)</b> | -1.571 | -1.396 | ... | 1.571 |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 2,7940\text{e-}07$ ( $\pm 600$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 191 |
| Max CPU cycles  | 664 |
| Avg CPU cycles  | 429 |

**Verification: Asin Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**


Inport test for Math block Asin.

| Test results          |        |        |     |       |
|-----------------------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | ... | 133   |
| <b>CPU cycles</b>     | 402    | 6717   | ... | 402   |
| <i>Inputs</i>         |        |        |     |       |
| <b>In (DSP)</b>       | -1     | -0.985 | ... | 1     |
| <b>In</b>             | -1     | -0.985 | ... | 1     |
| <i>Outputs</i>        |        |        |     |       |
| <b>Out</b>            | -1.571 | -1.396 | ... | 1.571 |
| <b>Exp. Out</b>       | -1.571 | -1.396 | ... | 1.571 |
| <b>Out (DSP)</b>      | -1.571 | -1.396 | ... | 1.571 |
| <b>Exp. Out (DSP)</b> | -1.571 | -1.396 | ... | 1.571 |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 2,7940\text{e-}07$ ( $\pm 600$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 139  |
| Max CPU cycles  | 6799 |
| Avg CPU cycles  | 3544 |

## Block: Atan2



Computation of the angle between the inputs x and y.

| Inports |  |
|---------|--|
| y       |  |
| x       |  |

| Outports |                      |
|----------|----------------------|
| Out      | Result of atan2(y/x) |

### Description:

Calculation:

$$\text{Out} = \begin{cases} \arctan\left(\frac{y}{x}\right) & x > 0 \\ \arctan\left(\frac{y}{x}\right) + \pi & x < 0, y \geq 0 \\ \arctan\left(\frac{y}{x}\right) - \pi & x < 0, y < 0 \\ +\frac{\pi}{2} & x = 0, y > 0 \\ -\frac{\pi}{2} & x = 0, y < 0 \\ 0 & x = 0, y = 0 \end{cases}$$

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP8

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| y                 | int8 |
| x                 | int8 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |



### Implementation: FiP16

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| y                 | int16 |
| x                 | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| y                 | int32 |
| x                 | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| y                 | float32 |
| x                 | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| y                 | float64 |
| x                 | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: Atan2 FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Atan2.

| Test results          |    |       |        |       |     |        |
|-----------------------|----|-------|--------|-------|-----|--------|
| <b>Time step</b>      | 1  | 2     | 3      | 4     | ... | 315    |
| <b>CPU cycles</b>     | 88 | 223   | 221    | 216   | ... | 218    |
| <i>Inputs</i>         |    |       |        |       |     |        |
| <b>y (DSP)</b>        | 0  | 32767 | -32768 | 0     | ... | 2723   |
| <b>x (DSP)</b>        | 0  | 0     | 0      | 32767 | ... | -32655 |
| <b>y</b>              | 0  | 1     | -1     | 0     | ... | 0.083  |
| <b>x</b>              | 0  | 0     | 0      | 1     | ... | -0.997 |
| <i>Outputs</i>        |    |       |        |       |     |        |
| <b>Out</b>            | 0  | 0.5   | -0.5   | 0     | ... | 0.973  |
| <b>Exp. Out</b>       | 0  | 0.5   | -0.5   | 0     | ... | 0.974  |
| <b>Out (DSP)</b>      | 0  | 16383 | -16385 | 0     | ... | 31898  |
| <b>Exp. Out (DSP)</b> | 0  | 16384 | -16384 | 0     | ... | 31900  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 7,6294e-04$ ( $\pm 25$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 88  |
| Max CPU cycles  | 234 |
| Avg CPU cycles  | 201 |

**Verification: Atan2 FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Atan2.

| Test results          |    |       |        |       |     |        |
|-----------------------|----|-------|--------|-------|-----|--------|
| <b>Time step</b>      | 1  | 2     | 3      | 4     | ... | 315    |
| <b>CPU cycles</b>     | 57 | 105   | 107    | 103   | ... | 109    |
| <i>Inputs</i>         |    |       |        |       |     |        |
| <b>y (DSP)</b>        | 0  | 32767 | -32768 | 0     | ... | 2723   |
| <b>x (DSP)</b>        | 0  | 0     | 0      | 32767 | ... | -32655 |
| <b>y</b>              | 0  | 1     | -1     | 0     | ... | 0.083  |
| <b>x</b>              | 0  | 0     | 0      | 1     | ... | -0.997 |
| <i>Outputs</i>        |    |       |        |       |     |        |
| <b>Out</b>            | 0  | 0.5   | -0.5   | 0     | ... | 0.973  |
| <b>Exp. Out</b>       | 0  | 0.5   | -0.5   | 0     | ... | 0.974  |
| <b>Out (DSP)</b>      | 0  | 16383 | -16385 | 0     | ... | 31898  |
| <b>Exp. Out (DSP)</b> | 0  | 16384 | -16384 | 0     | ... | 31900  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 7,6294e-04$ ( $\pm 25$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 57  |
| Max CPU cycles  | 121 |
| Avg CPU cycles  | 105 |

**Verification: Atan2 FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Atan2.

| Test results          |     |       |        |       |     |        |
|-----------------------|-----|-------|--------|-------|-----|--------|
| <b>Time step</b>      | 1   | 2     | 3      | 4     | ... | 315    |
| <b>CPU cycles</b>     | 100 | 164   | 179    | 186   | ... | 211    |
| <i>Inputs</i>         |     |       |        |       |     |        |
| <b>y (DSP)</b>        | 0   | 32767 | -32768 | 0     | ... | 2723   |
| <b>x (DSP)</b>        | 0   | 0     | 0      | 32767 | ... | -32655 |
| <b>y</b>              | 0   | 1     | -1     | 0     | ... | 0.083  |
| <b>x</b>              | 0   | 0     | 0      | 1     | ... | -0.997 |
| <i>Outputs</i>        |     |       |        |       |     |        |
| <b>Out</b>            | 0   | 0.5   | -0.5   | 0     | ... | 0.973  |
| <b>Exp. Out</b>       | 0   | 0.5   | -0.5   | 0     | ... | 0.974  |
| <b>Out (DSP)</b>      | 0   | 16383 | -16385 | 0     | ... | 31898  |
| <b>Exp. Out (DSP)</b> | 0   | 16384 | -16384 | 0     | ... | 31900  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 7,6294e-04$ ( $\pm 25$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 100 |
| Max CPU cycles  | 213 |
| Avg CPU cycles  | 181 |

**Verification: Atan2 FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Atan2.

| Test results          |    |       |        |       |     |        |
|-----------------------|----|-------|--------|-------|-----|--------|
| <b>Time step</b>      | 1  | 2     | 3      | 4     | ... | 315    |
| <b>CPU cycles</b>     | 94 | 161   | 177    | 168   | ... | 284    |
| <i>Inputs</i>         |    |       |        |       |     |        |
| <b>y (DSP)</b>        | 0  | 32767 | -32768 | 0     | ... | 2723   |
| <b>x (DSP)</b>        | 0  | 0     | 0      | 32767 | ... | -32655 |
| <b>y</b>              | 0  | 1     | -1     | 0     | ... | 0.083  |
| <b>x</b>              | 0  | 0     | 0      | 1     | ... | -0.997 |
| <i>Outputs</i>        |    |       |        |       |     |        |
| <b>Out</b>            | 0  | 0.5   | -0.5   | 0     | ... | 0.973  |
| <b>Exp. Out</b>       | 0  | 0.5   | -0.5   | 0     | ... | 0.974  |
| <b>Out (DSP)</b>      | 0  | 16383 | -16385 | 0     | ... | 31898  |
| <b>Exp. Out (DSP)</b> | 0  | 16384 | -16384 | 0     | ... | 31900  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 7,6294e-04$ ( $\pm 25$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 94  |
| Max CPU cycles  | 328 |
| Avg CPU cycles  | 228 |

**Verification: Atan2 FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Atan2.

| Test results          |    |       |        |       |     |        |
|-----------------------|----|-------|--------|-------|-----|--------|
| <b>Time step</b>      | 1  | 2     | 3      | 4     | ... | 315    |
| <b>CPU cycles</b>     | 39 | 86    | 86     | 90    | ... | 117    |
| <i>Inputs</i>         |    |       |        |       |     |        |
| <b>y (DSP)</b>        | 0  | 32767 | -32768 | 0     | ... | 2723   |
| <b>x (DSP)</b>        | 0  | 0     | 0      | 32767 | ... | -32655 |
| <b>y</b>              | 0  | 1     | -1     | 0     | ... | 0.083  |
| <b>x</b>              | 0  | 0     | 0      | 1     | ... | -0.997 |
| <i>Outputs</i>        |    |       |        |       |     |        |
| <b>Out</b>            | 0  | 0.5   | -0.5   | 0     | ... | 0.973  |
| <b>Exp. Out</b>       | 0  | 0.5   | -0.5   | 0     | ... | 0.974  |
| <b>Out (DSP)</b>      | 0  | 16383 | -16385 | 0     | ... | 31898  |
| <b>Exp. Out (DSP)</b> | 0  | 16384 | -16384 | 0     | ... | 31900  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 7,6294e-04$ ( $\pm 25$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 39  |
| Max CPU cycles  | 119 |
| Avg CPU cycles  | 96  |

**Verification: Atan2 FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Atan2.

| Test results          |    |       |        |       |     |        |
|-----------------------|----|-------|--------|-------|-----|--------|
| <b>Time step</b>      | 1  | 2     | 3      | 4     | ... | 315    |
| <b>CPU cycles</b>     | 62 | 134   | 132    | 123   | ... | 143    |
| <i>Inputs</i>         |    |       |        |       |     |        |
| <b>y (DSP)</b>        | 0  | 32767 | -32768 | 0     | ... | 2723   |
| <b>x (DSP)</b>        | 0  | 0     | 0      | 32767 | ... | -32655 |
| <b>y</b>              | 0  | 1     | -1     | 0     | ... | 0.083  |
| <b>x</b>              | 0  | 0     | 0      | 1     | ... | -0.997 |
| <i>Outputs</i>        |    |       |        |       |     |        |
| <b>Out</b>            | 0  | 0.5   | -0.5   | 0     | ... | 0.973  |
| <b>Exp. Out</b>       | 0  | 0.5   | -0.5   | 0     | ... | 0.974  |
| <b>Out (DSP)</b>      | 0  | 16383 | -16385 | 0     | ... | 31898  |
| <b>Exp. Out (DSP)</b> | 0  | 16384 | -16384 | 0     | ... | 31900  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 7,6294e-04$ ( $\pm 25$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 62  |
| Max CPU cycles  | 150 |
| Avg CPU cycles  | 124 |



**Verification: Atan2 FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Atan2.

| Test results          |     |       |        |       |     |        |
|-----------------------|-----|-------|--------|-------|-----|--------|
| <b>Time step</b>      | 1   | 2     | 3      | 4     | ... | 315    |
| <b>CPU cycles</b>     | 113 | 151   | 145    | 135   | ... | 150    |
| <i>Inputs</i>         |     |       |        |       |     |        |
| <b>y (DSP)</b>        | 0   | 32767 | -32768 | 0     | ... | 2723   |
| <b>x (DSP)</b>        | 0   | 0     | 0      | 32767 | ... | -32655 |
| <b>y</b>              | 0   | 1     | -1     | 0     | ... | 0.083  |
| <b>x</b>              | 0   | 0     | 0      | 1     | ... | -0.997 |
| <i>Outputs</i>        |     |       |        |       |     |        |
| <b>Out</b>            | 0   | 0.5   | -0.5   | 0     | ... | 0.973  |
| <b>Exp. Out</b>       | 0   | 0.5   | -0.5   | 0     | ... | 0.974  |
| <b>Out (DSP)</b>      | 0   | 16383 | -16385 | 0     | ... | 31898  |
| <b>Exp. Out (DSP)</b> | 0   | 16384 | -16384 | 0     | ... | 31900  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 7,6294e-04$ ( $\pm 25$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 83  |
| Max CPU cycles  | 160 |
| Avg CPU cycles  | 137 |

**Verification: Atan2 FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Atan2.

| Test results          |    |       |        |       |     |        |
|-----------------------|----|-------|--------|-------|-----|--------|
| <b>Time step</b>      | 1  | 2     | 3      | 4     | ... | 315    |
| <b>CPU cycles</b>     | 86 | 215   | 215    | 214   | ... | 211    |
| <i>Inputs</i>         |    |       |        |       |     |        |
| <b>y (DSP)</b>        | 0  | 32767 | -32768 | 0     | ... | 2723   |
| <b>x (DSP)</b>        | 0  | 0     | 0      | 32767 | ... | -32655 |
| <b>y</b>              | 0  | 1     | -1     | 0     | ... | 0.083  |
| <b>x</b>              | 0  | 0     | 0      | 1     | ... | -0.997 |
| <i>Outputs</i>        |    |       |        |       |     |        |
| <b>Out</b>            | 0  | 0.5   | -0.5   | 0     | ... | 0.973  |
| <b>Exp. Out</b>       | 0  | 0.5   | -0.5   | 0     | ... | 0.974  |
| <b>Out (DSP)</b>      | 0  | 16383 | -16385 | 0     | ... | 31898  |
| <b>Exp. Out (DSP)</b> | 0  | 16384 | -16384 | 0     | ... | 31900  |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 7,6294e-04$ ( $\pm 25$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 86  |
| Max CPU cycles  | 240 |
| Avg CPU cycles  | 198 |

**Verification: Atan2 FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Atan2.

| Test results          |    |            |     |             |
|-----------------------|----|------------|-----|-------------|
| <b>Time step</b>      | 1  | 2          | ... | 315         |
| <b>CPU cycles</b>     | 99 | 303        | ... | 411         |
| <i>Inputs</i>         |    |            |     |             |
| <b>y (DSP)</b>        | 0  | 2147483647 | ... | 178433134   |
| <b>x (DSP)</b>        | 0  | 0          | ... | -2140057858 |
| <b>y</b>              | 0  | 1          | ... | 0.083       |
| <b>x</b>              | 0  | 0          | ... | -0.997      |
| <i>Outputs</i>        |    |            |     |             |
| <b>Out</b>            | 0  | 0.5        | ... | 0.973       |
| <b>Exp. Out</b>       | 0  | 0.5        | ... | 0.974       |
| <b>Out (DSP)</b>      | 0  | 1073741823 | ... | 2090479220  |
| <b>Exp. Out (DSP)</b> | 0  | 1073741824 | ... | 2090621061  |

| Test settings |                                       |
|---------------|---------------------------------------|
| Tolerance Out | $\pm 6,5193e-04$ ( $\pm 1400000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 99  |
| Max CPU cycles  | 420 |
| Avg CPU cycles  | 336 |

**Verification: Atan2 FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Atan2.

| Test results          |    |            |     |             |
|-----------------------|----|------------|-----|-------------|
| <b>Time step</b>      | 1  | 2          | ... | 315         |
| <b>CPU cycles</b>     | 59 | 217        | ... | 577         |
| <i>Inputs</i>         |    |            |     |             |
| <b>y (DSP)</b>        | 0  | 2147483647 | ... | 178433134   |
| <b>x (DSP)</b>        | 0  | 0          | ... | -2140057858 |
| <b>y</b>              | 0  | 1          | ... | 0.083       |
| <b>x</b>              | 0  | 0          | ... | -0.997      |
| <i>Outputs</i>        |    |            |     |             |
| <b>Out</b>            | 0  | 0.5        | ... | 0.973       |
| <b>Exp. Out</b>       | 0  | 0.5        | ... | 0.974       |
| <b>Out (DSP)</b>      | 0  | 1073741823 | ... | 2090479220  |
| <b>Exp. Out (DSP)</b> | 0  | 1073741824 | ... | 2090621061  |

| Test settings |                                       |
|---------------|---------------------------------------|
| Tolerance Out | $\pm 6,5193e-04$ ( $\pm 1400000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 59  |
| Max CPU cycles  | 645 |
| Avg CPU cycles  | 447 |

**Verification: Atan2 FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Atan2.

| Test results          |    |            |     |             |
|-----------------------|----|------------|-----|-------------|
| <b>Time step</b>      | 1  | 2          | ... | 315         |
| <b>CPU cycles</b>     | 98 | 335        | ... | 376         |
| <i>Inputs</i>         |    |            |     |             |
| <b>y (DSP)</b>        | 0  | 2147483647 | ... | 178433134   |
| <b>x (DSP)</b>        | 0  | 0          | ... | -2140057858 |
| <b>y</b>              | 0  | 1          | ... | 0.083       |
| <b>x</b>              | 0  | 0          | ... | -0.997      |
| <i>Outputs</i>        |    |            |     |             |
| <b>Out</b>            | 0  | 0.5        | ... | 0.973       |
| <b>Exp. Out</b>       | 0  | 0.5        | ... | 0.974       |
| <b>Out (DSP)</b>      | 0  | 1073741823 | ... | 2090479220  |
| <b>Exp. Out (DSP)</b> | 0  | 1073741824 | ... | 2090621061  |

| Test settings |                                       |
|---------------|---------------------------------------|
| Tolerance Out | $\pm 6,5193e-04$ ( $\pm 1400000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 98  |
| Max CPU cycles  | 431 |
| Avg CPU cycles  | 322 |

**Verification: Atan2 FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Atan2.

| Test results          |    |            |     |             |
|-----------------------|----|------------|-----|-------------|
| <b>Time step</b>      | 1  | 2          | ... | 315         |
| <b>CPU cycles</b>     | 88 | 441        | ... | 1101        |
| <i>Inputs</i>         |    |            |     |             |
| <b>y (DSP)</b>        | 0  | 2147483647 | ... | 178433134   |
| <b>x (DSP)</b>        | 0  | 0          | ... | -2140057858 |
| <b>y</b>              | 0  | 1          | ... | 0.083       |
| <b>x</b>              | 0  | 0          | ... | -0.997      |
| <i>Outputs</i>        |    |            |     |             |
| <b>Out</b>            | 0  | 0.5        | ... | 0.973       |
| <b>Exp. Out</b>       | 0  | 0.5        | ... | 0.974       |
| <b>Out (DSP)</b>      | 0  | 1073741823 | ... | 2090479220  |
| <b>Exp. Out (DSP)</b> | 0  | 1073741824 | ... | 2090621061  |

| Test settings |                                       |
|---------------|---------------------------------------|
| Tolerance Out | $\pm 6,5193e-04$ ( $\pm 1400000$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 88   |
| Max CPU cycles  | 1229 |
| Avg CPU cycles  | 797  |

**Verification: Atan2 FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Atan2.

| Test results          |    |            |     |             |
|-----------------------|----|------------|-----|-------------|
| <b>Time step</b>      | 1  | 2          | ... | 315         |
| <b>CPU cycles</b>     | 59 | 167        | ... | 221         |
| <i>Inputs</i>         |    |            |     |             |
| <b>y (DSP)</b>        | 0  | 2147483647 | ... | 178433134   |
| <b>x (DSP)</b>        | 0  | 0          | ... | -2140057858 |
| <b>y</b>              | 0  | 1          | ... | 0.083       |
| <b>x</b>              | 0  | 0          | ... | -0.997      |
| <i>Outputs</i>        |    |            |     |             |
| <b>Out</b>            | 0  | 0.5        | ... | 0.973       |
| <b>Exp. Out</b>       | 0  | 0.5        | ... | 0.974       |
| <b>Out (DSP)</b>      | 0  | 1073741823 | ... | 2090479220  |
| <b>Exp. Out (DSP)</b> | 0  | 1073741824 | ... | 2090621061  |

| Test settings |                                       |
|---------------|---------------------------------------|
| Tolerance Out | $\pm 6,5193e-04$ ( $\pm 1400000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 59  |
| Max CPU cycles  | 236 |
| Avg CPU cycles  | 181 |

**Verification: Atan2 FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Atan2.

| Test results          |    |            |     |             |
|-----------------------|----|------------|-----|-------------|
| <b>Time step</b>      | 1  | 2          | ... | 315         |
| <b>CPU cycles</b>     | 85 | 9391       | ... | 9931        |
| <i>Inputs</i>         |    |            |     |             |
| <b>y (DSP)</b>        | 0  | 2147483647 | ... | 178433134   |
| <b>x (DSP)</b>        | 0  | 0          | ... | -2140057858 |
| <b>y</b>              | 0  | 1          | ... | 0.083       |
| <b>x</b>              | 0  | 0          | ... | -0.997      |
| <i>Outputs</i>        |    |            |     |             |
| <b>Out</b>            | 0  | 0.5        | ... | 0.973       |
| <b>Exp. Out</b>       | 0  | 0.5        | ... | 0.974       |
| <b>Out (DSP)</b>      | 0  | 1073741823 | ... | 2090479220  |
| <b>Exp. Out (DSP)</b> | 0  | 1073741824 | ... | 2090621061  |

| Test settings |                                       |
|---------------|---------------------------------------|
| Tolerance Out | $\pm 6,5193e-04$ ( $\pm 1400000$ LSB) |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 85    |
| Max CPU cycles  | 10093 |
| Avg CPU cycles  | 7695  |



**Verification: Atan2 FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Atan2.

| Test results          |     |            |     |             |
|-----------------------|-----|------------|-----|-------------|
| <b>Time step</b>      | 1   | 2          | ... | 315         |
| <b>CPU cycles</b>     | 128 | 373        | ... | 355         |
| <i>Inputs</i>         |     |            |     |             |
| <b>y (DSP)</b>        | 0   | 2147483647 | ... | 178433134   |
| <b>x (DSP)</b>        | 0   | 0          | ... | -2140057858 |
| <b>y</b>              | 0   | 1          | ... | 0.083       |
| <b>x</b>              | 0   | 0          | ... | -0.997      |
| <i>Outputs</i>        |     |            |     |             |
| <b>Out</b>            | 0   | 0.5        | ... | 0.973       |
| <b>Exp. Out</b>       | 0   | 0.5        | ... | 0.974       |
| <b>Out (DSP)</b>      | 0   | 1073741823 | ... | 2090479220  |
| <b>Exp. Out (DSP)</b> | 0   | 1073741824 | ... | 2090621061  |

| Test settings |                                       |
|---------------|---------------------------------------|
| Tolerance Out | $\pm 6,5193e-04$ ( $\pm 1400000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 92  |
| Max CPU cycles  | 378 |
| Avg CPU cycles  | 298 |

**Verification: Atan2 FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Atan2.

| Test results          |     |            |     |             |
|-----------------------|-----|------------|-----|-------------|
| <b>Time step</b>      | 1   | 2          | ... | 315         |
| <b>CPU cycles</b>     | 100 | 288        | ... | 392         |
| <i>Inputs</i>         |     |            |     |             |
| <b>y (DSP)</b>        | 0   | 2147483647 | ... | 178433134   |
| <b>x (DSP)</b>        | 0   | 0          | ... | -2140057858 |
| <b>y</b>              | 0   | 1          | ... | 0.083       |
| <b>x</b>              | 0   | 0          | ... | -0.997      |
| <i>Outputs</i>        |     |            |     |             |
| <b>Out</b>            | 0   | 0.5        | ... | 0.973       |
| <b>Exp. Out</b>       | 0   | 0.5        | ... | 0.974       |
| <b>Out (DSP)</b>      | 0   | 1073741823 | ... | 2090479220  |
| <b>Exp. Out (DSP)</b> | 0   | 1073741824 | ... | 2090621061  |

| Test settings |                                       |
|---------------|---------------------------------------|
| Tolerance Out | $\pm 6,5193e-04$ ( $\pm 1400000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 100 |
| Max CPU cycles  | 412 |
| Avg CPU cycles  | 323 |

**Verification: Atan2 Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Atan2.

| Test results          |     |       |     |        |
|-----------------------|-----|-------|-----|--------|
| <b>Time step</b>      | 1   | 2     | ... | 315    |
| <b>CPU cycles</b>     | 187 | 220   | ... | 818    |
| <i>Inputs</i>         |     |       |     |        |
| <b>y (DSP)</b>        | 0   | 2     | ... | 0.166  |
| <b>x (DSP)</b>        | 0   | 0     | ... | -1.993 |
| <b>y</b>              | 0   | 2     | ... | 0.166  |
| <b>x</b>              | 0   | 0     | ... | -1.993 |
| <i>Outputs</i>        |     |       |     |        |
| <b>Out</b>            | 0   | 1.571 | ... | 3.058  |
| <b>Exp. Out</b>       | 0   | 1.571 | ... | 3.058  |
| <b>Out (DSP)</b>      | 0   | 1.571 | ... | 3.058  |
| <b>Exp. Out (DSP)</b> | 0   | 1.571 | ... | 3.058  |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 2,5611\text{e-}07$ ( $\pm 550$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 187  |
| Max CPU cycles  | 1172 |
| Avg CPU cycles  | 899  |

**Verification: Atan2 Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Atan2.

| Test results          |    |       |     |        |
|-----------------------|----|-------|-----|--------|
| <b>Time step</b>      | 1  | 2     | ... | 315    |
| <b>CPU cycles</b>     | 93 | 101   | ... | 235    |
| <i>Inputs</i>         |    |       |     |        |
| <b>y (DSP)</b>        | 0  | 2     | ... | 0.166  |
| <b>x (DSP)</b>        | 0  | 0     | ... | -1.993 |
| <b>y</b>              | 0  | 2     | ... | 0.166  |
| <b>x</b>              | 0  | 0     | ... | -1.993 |
| <i>Outputs</i>        |    |       |     |        |
| <b>Out</b>            | 0  | 1.571 | ... | 3.058  |
| <b>Exp. Out</b>       | 0  | 1.571 | ... | 3.058  |
| <b>Out (DSP)</b>      | 0  | 1.571 | ... | 3.058  |
| <b>Exp. Out (DSP)</b> | 0  | 1.571 | ... | 3.058  |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 2,5611\text{e-}07$ ( $\pm 550$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 93  |
| Max CPU cycles  | 289 |
| Avg CPU cycles  | 242 |

**Verification: Atan2 Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Atan2.

| Test results          |     |       |     |        |
|-----------------------|-----|-------|-----|--------|
| <b>Time step</b>      | 1   | 2     | ... | 315    |
| <b>CPU cycles</b>     | 157 | 176   | ... | 433    |
| <i>Inputs</i>         |     |       |     |        |
| <b>y (DSP)</b>        | 0   | 2     | ... | 0.166  |
| <b>x (DSP)</b>        | 0   | 0     | ... | -1.993 |
| <b>y</b>              | 0   | 2     | ... | 0.166  |
| <b>x</b>              | 0   | 0     | ... | -1.993 |
| <i>Outputs</i>        |     |       |     |        |
| <b>Out</b>            | 0   | 1.571 | ... | 3.058  |
| <b>Exp. Out</b>       | 0   | 1.571 | ... | 3.058  |
| <b>Out (DSP)</b>      | 0   | 1.571 | ... | 3.058  |
| <b>Exp. Out (DSP)</b> | 0   | 1.571 | ... | 3.058  |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 2,5611e-07$ ( $\pm 550$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 157 |
| Max CPU cycles  | 528 |
| Avg CPU cycles  | 441 |

**Verification: Atan2 Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Atan2.

| Test results          |     |       |     |        |
|-----------------------|-----|-------|-----|--------|
| <b>Time step</b>      | 1   | 2     | ... | 315    |
| <b>CPU cycles</b>     | 135 | 145   | ... | 5077   |
| <i>Inputs</i>         |     |       |     |        |
| <b>y (DSP)</b>        | 0   | 2     | ... | 0.166  |
| <b>x (DSP)</b>        | 0   | 0     | ... | -1.993 |
| <b>y</b>              | 0   | 2     | ... | 0.166  |
| <b>x</b>              | 0   | 0     | ... | -1.993 |
| <i>Outputs</i>        |     |       |     |        |
| <b>Out</b>            | 0   | 1.571 | ... | 3.058  |
| <b>Exp. Out</b>       | 0   | 1.571 | ... | 3.058  |
| <b>Out (DSP)</b>      | 0   | 1.571 | ... | 3.058  |
| <b>Exp. Out (DSP)</b> | 0   | 1.571 | ... | 3.058  |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 2,5611\text{e-}07$ ( $\pm 550$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 135  |
| Max CPU cycles  | 6555 |
| Avg CPU cycles  | 4608 |

**Verification: Atan2 Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Atan2.

| Test results          |     |       |     |        |
|-----------------------|-----|-------|-----|--------|
| <b>Time step</b>      | 1   | 2     | ... | 315    |
| <b>CPU cycles</b>     | 237 | 272   | ... | 666    |
| <i>Inputs</i>         |     |       |     |        |
| <b>y (DSP)</b>        | 0   | 2     | ... | 0.166  |
| <b>x (DSP)</b>        | 0   | 0     | ... | -1.993 |
| <b>y</b>              | 0   | 2     | ... | 0.166  |
| <b>x</b>              | 0   | 0     | ... | -1.993 |
| <i>Outputs</i>        |     |       |     |        |
| <b>Out</b>            | 0   | 1.571 | ... | 3.058  |
| <b>Exp. Out</b>       | 0   | 1.571 | ... | 3.058  |
| <b>Out (DSP)</b>      | 0   | 1.571 | ... | 3.058  |
| <b>Exp. Out (DSP)</b> | 0   | 1.571 | ... | 3.058  |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 2,5611\text{e-}07$ ( $\pm 550$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 237 |
| Max CPU cycles  | 782 |
| Avg CPU cycles  | 612 |

**Verification: Atan2 Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Atan2.

| Test results          |     |       |     |        |
|-----------------------|-----|-------|-----|--------|
| <b>Time step</b>      | 1   | 2     | ... | 315    |
| <b>CPU cycles</b>     | 265 | 438   | ... | 3148   |
| <i>Inputs</i>         |     |       |     |        |
| <b>y (DSP)</b>        | 0   | 2     | ... | 0.166  |
| <b>x (DSP)</b>        | 0   | 0     | ... | -1.993 |
| <b>y</b>              | 0   | 2     | ... | 0.166  |
| <b>x</b>              | 0   | 0     | ... | -1.993 |
| <i>Outputs</i>        |     |       |     |        |
| <b>Out</b>            | 0   | 1.571 | ... | 3.058  |
| <b>Exp. Out</b>       | 0   | 1.571 | ... | 3.058  |
| <b>Out (DSP)</b>      | 0   | 1.571 | ... | 3.058  |
| <b>Exp. Out (DSP)</b> | 0   | 1.571 | ... | 3.058  |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 2,5611\text{e-}07$ ( $\pm 550$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 265  |
| Max CPU cycles  | 5161 |
| Avg CPU cycles  | 3703 |



**Verification: Atan2 Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Atan2.

| Test results          |     |       |     |        |
|-----------------------|-----|-------|-----|--------|
| <b>Time step</b>      | 1   | 2     | ... | 315    |
| <b>CPU cycles</b>     | 166 | 130   | ... | 292    |
| <i>Inputs</i>         |     |       |     |        |
| <b>y (DSP)</b>        | 0   | 2     | ... | 0.166  |
| <b>x (DSP)</b>        | 0   | 0     | ... | -1.993 |
| <b>y</b>              | 0   | 2     | ... | 0.166  |
| <b>x</b>              | 0   | 0     | ... | -1.993 |
| <i>Outputs</i>        |     |       |     |        |
| <b>Out</b>            | 0   | 1.571 | ... | 3.058  |
| <b>Exp. Out</b>       | 0   | 1.571 | ... | 3.058  |
| <b>Out (DSP)</b>      | 0   | 1.571 | ... | 3.058  |
| <b>Exp. Out (DSP)</b> | 0   | 1.571 | ... | 3.058  |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 2,5611e-07$ ( $\pm 550$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 117 |
| Max CPU cycles  | 414 |
| Avg CPU cycles  | 301 |

**Verification: Atan2 Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Atan2.

| Test results          |     |       |     |        |
|-----------------------|-----|-------|-----|--------|
| <b>Time step</b>      | 1   | 2     | ... | 315    |
| <b>CPU cycles</b>     | 147 | 180   | ... | 622    |
| <i>Inputs</i>         |     |       |     |        |
| <b>y (DSP)</b>        | 0   | 2     | ... | 0.166  |
| <b>x (DSP)</b>        | 0   | 0     | ... | -1.993 |
| <b>y</b>              | 0   | 2     | ... | 0.166  |
| <b>x</b>              | 0   | 0     | ... | -1.993 |
| <i>Outputs</i>        |     |       |     |        |
| <b>Out</b>            | 0   | 1.571 | ... | 3.058  |
| <b>Exp. Out</b>       | 0   | 1.571 | ... | 3.058  |
| <b>Out (DSP)</b>      | 0   | 1.571 | ... | 3.058  |
| <b>Exp. Out (DSP)</b> | 0   | 1.571 | ... | 3.058  |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 2,5611\text{e-}07$ ( $\pm 550$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 147 |
| Max CPU cycles  | 909 |
| Avg CPU cycles  | 692 |

## Block: Average



Calculation of moving average value over n numbers.

| Inports |             |
|---------|-------------|
| In      | Input value |

| Outports |                |
|----------|----------------|
| Out      | Averaged value |

| Mask Parameters |    |                                                                 |
|-----------------|----|-----------------------------------------------------------------|
| Name            | ID | Description                                                     |
| n               | 1  | Number of points to be averaged over                            |
| ts_fact         | 2  | Multiplication factor of base sampling time (in integer format) |

### Description:

Calculation:

$$\text{Out}_k = \frac{1}{n} \sum_{i=k-n}^k \text{In}_i$$

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP8

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | int8 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

---

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

---

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

---

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: Average FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |        |       |    |        |     |        |
|----------------|--------|-------|----|--------|-----|--------|
| Time step      | 1      | 2     | 3  | 4      | ... | 113    |
| CPU cycles     | 87     | 87    | 87 | 87     | ... | 87     |
| Inputs         |        |       |    |        |     |        |
| In (DSP)       | -145   | 2369  | 4  | -2087  | ... | -1015  |
| In             | -0.004 | 0.072 | 0  | -0.064 | ... | -0.031 |
| Parameters     |        |       |    |        |     |        |
| n              | 1      |       |    |        |     |        |
| ts_fact        | 1      |       |    |        |     |        |
| Outputs        |        |       |    |        |     |        |
| Out            | -0.004 | 0.072 | 0  | -0.064 | ... | -0.031 |
| Exp. Out       | -0.004 | 0.072 | 0  | -0.064 | ... | -0.031 |
| Out (DSP)      | -145   | 2369  | 4  | -2087  | ... | -1015  |
| Exp. Out (DSP) | -145   | 2369  | 4  | -2087  | ... | -1015  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 87 |
| Max CPU cycles  | 87 |
| Avg CPU cycles  | 87 |

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 113    |
| CPU cycles     | 87     | 87     | 87     | 87     | ... | 87     |
| Inputs         |        |        |        |        |     |        |
| In (DSP)       | -4188  | 340    | -3895  | 355    | ... | -3177  |
| In             | -0.128 | 0.01   | -0.119 | 0.011  | ... | -0.097 |
| Parameters     |        |        |        |        |     |        |
| n              | 4      |        |        |        |     |        |
| ts_fact        | 1      |        |        |        |     |        |
| Outputs        |        |        |        |        |     |        |
| Out            | -0.032 | -0.029 | -0.059 | -0.056 | ... | 0.091  |
| Exp. Out       | -0.032 | -0.029 | -0.059 | -0.056 | ... | 0.091  |
| Out (DSP)      | -1047  | -962   | -1936  | -1847  | ... | 2994   |
| Exp. Out (DSP) | -1047  | -962   | -1936  | -1847  | ... | 2994   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 87 |
| Max CPU cycles  | 87 |
| Avg CPU cycles  | 87 |

### Test case: Inport test

OK

Inport test for Math block Average.

| Test results   |       |        |       |        |     |       |
|----------------|-------|--------|-------|--------|-----|-------|
| Time step      | 1     | 2      | 3     | 4      | ... | 113   |
| CPU cycles     | 87    | 87     | 87    | 87     | ... | 87    |
| Inputs         |       |        |       |        |     |       |
| In (DSP)       | 4496  | -3777  | 1239  | -7107  | ... | 2679  |
| In             | 0.137 | -0.115 | 0.038 | -0.217 | ... | 0.082 |
| Parameters     |       |        |       |        |     |       |
| n              | 32    |        |       |        |     |       |
| ts_fact        | 1     |        |       |        |     |       |
| Outputs        |       |        |       |        |     |       |
| Out            | 0.004 | 0.001  | 0.002 | -0.005 | ... | 0.528 |
| Exp. Out       | 0.004 | 0.001  | 0.002 | -0.005 | ... | 0.528 |
| Out (DSP)      | 140   | 22     | 61    | -161   | ... | 17314 |
| Exp. Out (DSP) | 141   | 22     | 61    | -161   | ... | 17315 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 87 |
| Max CPU cycles  | 87 |
| Avg CPU cycles  | 87 |

### Test case: Conversion test

OK

Conversion test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| <b>Time step</b>             | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| Time step                    | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 6543 |
| Max CPU cycles  | 6578 |
| Avg CPU cycles  | 6561 |



**Verification: Average FiP16 CPU TM4C123GH6**

Date of Test 2026-06-19  
Target controller TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |        |       |    |        |     |        |
|----------------|--------|-------|----|--------|-----|--------|
| Time step      | 1      | 2     | 3  | 4      | ... | 113    |
| CPU cycles     | 61     | 61    | 61 | 61     | ... | 61     |
| Inputs         |        |       |    |        |     |        |
| In (DSP)       | -145   | 2369  | 4  | -2087  | ... | -1015  |
| In             | -0.004 | 0.072 | 0  | -0.064 | ... | -0.031 |
| Parameters     |        |       |    |        |     |        |
| n              | 1      |       |    |        |     |        |
| ts_fact        | 1      |       |    |        |     |        |
| Outputs        |        |       |    |        |     |        |
| Out            | -0.004 | 0.072 | 0  | -0.064 | ... | -0.031 |
| Exp. Out       | -0.004 | 0.072 | 0  | -0.064 | ... | -0.031 |
| Out (DSP)      | -145   | 2369  | 4  | -2087  | ... | -1015  |
| Exp. Out (DSP) | -145   | 2369  | 4  | -2087  | ... | -1015  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 61 |
| Max CPU cycles  | 61 |
| Avg CPU cycles  | 61 |

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 113    |
| CPU cycles     | 61     | 61     | 61     | 61     | ... | 61     |
| Inputs         |        |        |        |        |     |        |
| In (DSP)       | -4188  | 340    | -3895  | 355    | ... | -3177  |
| In             | -0.128 | 0.01   | -0.119 | 0.011  | ... | -0.097 |
| Parameters     |        |        |        |        |     |        |
| n              | 4      |        |        |        |     |        |
| ts_fact        | 1      |        |        |        |     |        |
| Outputs        |        |        |        |        |     |        |
| Out            | -0.032 | -0.029 | -0.059 | -0.056 | ... | 0.091  |
| Exp. Out       | -0.032 | -0.029 | -0.059 | -0.056 | ... | 0.091  |
| Out (DSP)      | -1047  | -962   | -1936  | -1847  | ... | 2994   |
| Exp. Out (DSP) | -1047  | -962   | -1936  | -1847  | ... | 2994   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 61 |
| Max CPU cycles  | 61 |
| Avg CPU cycles  | 61 |

### Test case: Inport test

OK

Inport test for Math block Average.

| Test results   |       |        |       |        |     |       |
|----------------|-------|--------|-------|--------|-----|-------|
| Time step      | 1     | 2      | 3     | 4      | ... | 113   |
| CPU cycles     | 61    | 61     | 61    | 61     | ... | 61    |
| Inputs         |       |        |       |        |     |       |
| In (DSP)       | 4496  | -3777  | 1239  | -7107  | ... | 2679  |
| In             | 0.137 | -0.115 | 0.038 | -0.217 | ... | 0.082 |
| Parameters     |       |        |       |        |     |       |
| n              | 32    |        |       |        |     |       |
| ts_fact        | 1     |        |       |        |     |       |
| Outputs        |       |        |       |        |     |       |
| Out            | 0.004 | 0.001  | 0.002 | -0.005 | ... | 0.528 |
| Exp. Out       | 0.004 | 0.001  | 0.002 | -0.005 | ... | 0.528 |
| Out (DSP)      | 140   | 22     | 61    | -161   | ... | 17314 |
| Exp. Out (DSP) | 141   | 22     | 61    | -161   | ... | 17315 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 61 |
| Max CPU cycles  | 61 |
| Avg CPU cycles  | 61 |

### Test case: Conversion test

OK

Conversion test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| <b>Time step</b>             | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| Time step                    | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2613 |
| Max CPU cycles  | 2619 |
| Avg CPU cycles  | 2617 |

**Verification: Average FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |        |       |    |        |     |        |
|----------------|--------|-------|----|--------|-----|--------|
| Time step      | 1      | 2     | 3  | 4      | ... | 113    |
| CPU cycles     | 92     | 92    | 92 | 92     | ... | 92     |
| Inputs         |        |       |    |        |     |        |
| In (DSP)       | -145   | 2369  | 4  | -2087  | ... | -1015  |
| In             | -0.004 | 0.072 | 0  | -0.064 | ... | -0.031 |
| Parameters     |        |       |    |        |     |        |
| n              | 1      |       |    |        |     |        |
| ts_fact        | 1      |       |    |        |     |        |
| Outputs        |        |       |    |        |     |        |
| Out            | -0.004 | 0.072 | 0  | -0.064 | ... | -0.031 |
| Exp. Out       | -0.004 | 0.072 | 0  | -0.064 | ... | -0.031 |
| Out (DSP)      | -145   | 2369  | 4  | -2087  | ... | -1015  |
| Exp. Out (DSP) | -145   | 2369  | 4  | -2087  | ... | -1015  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 92 |
| Max CPU cycles  | 92 |
| Avg CPU cycles  | 92 |

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 113    |
| CPU cycles     | 92     | 92     | 92     | 92     | ... | 92     |
| Inputs         |        |        |        |        |     |        |
| In (DSP)       | -4188  | 340    | -3895  | 355    | ... | -3177  |
| In             | -0.128 | 0.01   | -0.119 | 0.011  | ... | -0.097 |
| Parameters     |        |        |        |        |     |        |
| n              | 4      |        |        |        |     |        |
| ts_fact        | 1      |        |        |        |     |        |
| Outputs        |        |        |        |        |     |        |
| Out            | -0.032 | -0.029 | -0.059 | -0.056 | ... | 0.091  |
| Exp. Out       | -0.032 | -0.029 | -0.059 | -0.056 | ... | 0.091  |
| Out (DSP)      | -1047  | -962   | -1936  | -1847  | ... | 2994   |
| Exp. Out (DSP) | -1047  | -962   | -1936  | -1847  | ... | 2994   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 92 |
| Max CPU cycles  | 92 |
| Avg CPU cycles  | 92 |

### Test case: Inport test

OK

Inport test for Math block Average.

| Test results   |       |        |       |        |     |       |
|----------------|-------|--------|-------|--------|-----|-------|
| Time step      | 1     | 2      | 3     | 4      | ... | 113   |
| CPU cycles     | 92    | 92     | 92    | 92     | ... | 92    |
| Inputs         |       |        |       |        |     |       |
| In (DSP)       | 4496  | -3777  | 1239  | -7107  | ... | 2679  |
| In             | 0.137 | -0.115 | 0.038 | -0.217 | ... | 0.082 |
| Parameters     |       |        |       |        |     |       |
| n              | 32    |        |       |        |     |       |
| ts_fact        | 1     |        |       |        |     |       |
| Outputs        |       |        |       |        |     |       |
| Out            | 0.004 | 0.001  | 0.002 | -0.005 | ... | 0.528 |
| Exp. Out       | 0.004 | 0.001  | 0.002 | -0.005 | ... | 0.528 |
| Out (DSP)      | 140   | 22     | 61    | -161   | ... | 17314 |
| Exp. Out (DSP) | 141   | 22     | 61    | -161   | ... | 17315 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 92 |
| Max CPU cycles  | 92 |
| Avg CPU cycles  | 92 |

### Test case: Conversion test

OK

Conversion test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| <b>Time step</b>             | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| Time step                    | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3379 |
| Max CPU cycles  | 3391 |
| Avg CPU cycles  | 3383 |



**Verification: Average FiP16 CPU STM32F072RB**

Date of Test 2026-06-19  
Target controller STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |        |       |    |        |     |        |
|----------------|--------|-------|----|--------|-----|--------|
| Time step      | 1      | 2     | 3  | 4      | ... | 113    |
| CPU cycles     | 84     | 84    | 84 | 84     | ... | 84     |
| Inputs         |        |       |    |        |     |        |
| In (DSP)       | -145   | 2369  | 4  | -2087  | ... | -1015  |
| In             | -0.004 | 0.072 | 0  | -0.064 | ... | -0.031 |
| Parameters     |        |       |    |        |     |        |
| n              | 1      |       |    |        |     |        |
| ts_fact        | 1      |       |    |        |     |        |
| Outputs        |        |       |    |        |     |        |
| Out            | -0.004 | 0.072 | 0  | -0.064 | ... | -0.031 |
| Exp. Out       | -0.004 | 0.072 | 0  | -0.064 | ... | -0.031 |
| Out (DSP)      | -145   | 2369  | 4  | -2087  | ... | -1015  |
| Exp. Out (DSP) | -145   | 2369  | 4  | -2087  | ... | -1015  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 84 |
| Max CPU cycles  | 84 |
| Avg CPU cycles  | 84 |

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 113    |
| CPU cycles     | 84     | 84     | 84     | 84     | ... | 84     |
| Inputs         |        |        |        |        |     |        |
| In (DSP)       | -4188  | 340    | -3895  | 355    | ... | -3177  |
| In             | -0.128 | 0.01   | -0.119 | 0.011  | ... | -0.097 |
| Parameters     |        |        |        |        |     |        |
| n              | 4      |        |        |        |     |        |
| ts_fact        | 1      |        |        |        |     |        |
| Outputs        |        |        |        |        |     |        |
| Out            | -0.032 | -0.029 | -0.059 | -0.056 | ... | 0.091  |
| Exp. Out       | -0.032 | -0.029 | -0.059 | -0.056 | ... | 0.091  |
| Out (DSP)      | -1047  | -962   | -1936  | -1847  | ... | 2994   |
| Exp. Out (DSP) | -1047  | -962   | -1936  | -1847  | ... | 2994   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 84 |
| Max CPU cycles  | 84 |
| Avg CPU cycles  | 84 |

### Test case: Inport test

OK

Inport test for Math block Average.

| Test results   |       |        |       |        |     |       |
|----------------|-------|--------|-------|--------|-----|-------|
| Time step      | 1     | 2      | 3     | 4      | ... | 113   |
| CPU cycles     | 84    | 84     | 84    | 84     | ... | 84    |
| Inputs         |       |        |       |        |     |       |
| In (DSP)       | 4496  | -3777  | 1239  | -7107  | ... | 2679  |
| In             | 0.137 | -0.115 | 0.038 | -0.217 | ... | 0.082 |
| Parameters     |       |        |       |        |     |       |
| n              | 32    |        |       |        |     |       |
| ts_fact        | 1     |        |       |        |     |       |
| Outputs        |       |        |       |        |     |       |
| Out            | 0.004 | 0.001  | 0.002 | -0.005 | ... | 0.528 |
| Exp. Out       | 0.004 | 0.001  | 0.002 | -0.005 | ... | 0.528 |
| Out (DSP)      | 140   | 22     | 61    | -161   | ... | 17314 |
| Exp. Out (DSP) | 141   | 22     | 61    | -161   | ... | 17315 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 84 |
| Max CPU cycles  | 84 |
| Avg CPU cycles  | 84 |

### Test case: Conversion test

OK

Conversion test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| <b>Time step</b>             | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| Time step                    | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 4342 |
| Max CPU cycles  | 4351 |
| Avg CPU cycles  | 4348 |

**Verification: Average FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |        |       |    |        |     |        |
|----------------|--------|-------|----|--------|-----|--------|
| Time step      | 1      | 2     | 3  | 4      | ... | 113    |
| CPU cycles     | 58     | 58    | 58 | 58     | ... | 58     |
| Inputs         |        |       |    |        |     |        |
| In (DSP)       | -145   | 2369  | 4  | -2087  | ... | -1015  |
| In             | -0.004 | 0.072 | 0  | -0.064 | ... | -0.031 |
| Parameters     |        |       |    |        |     |        |
| n              | 1      |       |    |        |     |        |
| ts_fact        | 1      |       |    |        |     |        |
| Outputs        |        |       |    |        |     |        |
| Out            | -0.004 | 0.072 | 0  | -0.064 | ... | -0.031 |
| Exp. Out       | -0.004 | 0.072 | 0  | -0.064 | ... | -0.031 |
| Out (DSP)      | -145   | 2369  | 4  | -2087  | ... | -1015  |
| Exp. Out (DSP) | -145   | 2369  | 4  | -2087  | ... | -1015  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 58 |
| Max CPU cycles  | 58 |
| Avg CPU cycles  | 58 |

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 113    |
| CPU cycles     | 56     | 56     | 56     | 58     | ... | 56     |
| Inputs         |        |        |        |        |     |        |
| In (DSP)       | -4188  | 340    | -3895  | 355    | ... | -3177  |
| In             | -0.128 | 0.01   | -0.119 | 0.011  | ... | -0.097 |
| Parameters     |        |        |        |        |     |        |
| n              | 4      |        |        |        |     |        |
| ts_fact        | 1      |        |        |        |     |        |
| Outputs        |        |        |        |        |     |        |
| Out            | -0.032 | -0.029 | -0.059 | -0.056 | ... | 0.091  |
| Exp. Out       | -0.032 | -0.029 | -0.059 | -0.056 | ... | 0.091  |
| Out (DSP)      | -1047  | -962   | -1936  | -1847  | ... | 2994   |
| Exp. Out (DSP) | -1047  | -962   | -1936  | -1847  | ... | 2994   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 58 |
| Avg CPU cycles  | 56 |

### Test case: Inport test

OK

Inport test for Math block Average.

| Test results   |       |        |       |        |     |       |
|----------------|-------|--------|-------|--------|-----|-------|
| Time step      | 1     | 2      | 3     | 4      | ... | 113   |
| CPU cycles     | 56    | 56     | 56    | 56     | ... | 56    |
| Inputs         |       |        |       |        |     |       |
| In (DSP)       | 4496  | -3777  | 1239  | -7107  | ... | 2679  |
| In             | 0.137 | -0.115 | 0.038 | -0.217 | ... | 0.082 |
| Parameters     |       |        |       |        |     |       |
| n              | 32    |        |       |        |     |       |
| ts_fact        | 1     |        |       |        |     |       |
| Outputs        |       |        |       |        |     |       |
| Out            | 0.004 | 0.001  | 0.002 | -0.005 | ... | 0.528 |
| Exp. Out       | 0.004 | 0.001  | 0.002 | -0.005 | ... | 0.528 |
| Out (DSP)      | 140   | 22     | 61    | -161   | ... | 17314 |
| Exp. Out (DSP) | 141   | 22     | 61    | -161   | ... | 17315 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 58 |
| Avg CPU cycles  | 56 |

### Test case: Conversion test

OK

Conversion test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| <b>Time step</b>             | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| Time step                    | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3676 |
| Max CPU cycles  | 3678 |
| Avg CPU cycles  | 3677 |



**Verification: Average FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |        |       |    |        |     |        |
|----------------|--------|-------|----|--------|-----|--------|
| Time step      | 1      | 2     | 3  | 4      | ... | 113    |
| CPU cycles     | 72     | 72    | 72 | 72     | ... | 72     |
| Inputs         |        |       |    |        |     |        |
| In (DSP)       | -145   | 2369  | 4  | -2087  | ... | -1015  |
| In             | -0.004 | 0.072 | 0  | -0.064 | ... | -0.031 |
| Parameters     |        |       |    |        |     |        |
| n              | 1      |       |    |        |     |        |
| ts_fact        | 1      |       |    |        |     |        |
| Outputs        |        |       |    |        |     |        |
| Out            | -0.004 | 0.072 | 0  | -0.064 | ... | -0.031 |
| Exp. Out       | -0.004 | 0.072 | 0  | -0.064 | ... | -0.031 |
| Out (DSP)      | -145   | 2369  | 4  | -2087  | ... | -1015  |
| Exp. Out (DSP) | -145   | 2369  | 4  | -2087  | ... | -1015  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 72 |
| Max CPU cycles  | 72 |
| Avg CPU cycles  | 72 |

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 113    |
| CPU cycles     | 73     | 73     | 73     | 72     | ... | 73     |
| Inputs         |        |        |        |        |     |        |
| In (DSP)       | -4188  | 340    | -3895  | 355    | ... | -3177  |
| In             | -0.128 | 0.01   | -0.119 | 0.011  | ... | -0.097 |
| Parameters     |        |        |        |        |     |        |
| n              | 4      |        |        |        |     |        |
| ts_fact        | 1      |        |        |        |     |        |
| Outputs        |        |        |        |        |     |        |
| Out            | -0.032 | -0.029 | -0.059 | -0.056 | ... | 0.091  |
| Exp. Out       | -0.032 | -0.029 | -0.059 | -0.056 | ... | 0.091  |
| Out (DSP)      | -1047  | -962   | -1936  | -1847  | ... | 2994   |
| Exp. Out (DSP) | -1047  | -962   | -1936  | -1847  | ... | 2994   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 72 |
| Max CPU cycles  | 73 |
| Avg CPU cycles  | 72 |

### Test case: Inport test

OK

Inport test for Math block Average.

| Test results   |       |        |       |        |     |       |
|----------------|-------|--------|-------|--------|-----|-------|
| Time step      | 1     | 2      | 3     | 4      | ... | 113   |
| CPU cycles     | 73    | 73     | 73    | 73     | ... | 73    |
| Inputs         |       |        |       |        |     |       |
| In (DSP)       | 4496  | -3777  | 1239  | -7107  | ... | 2679  |
| In             | 0.137 | -0.115 | 0.038 | -0.217 | ... | 0.082 |
| Parameters     |       |        |       |        |     |       |
| n              | 32    |        |       |        |     |       |
| ts_fact        | 1     |        |       |        |     |       |
| Outputs        |       |        |       |        |     |       |
| Out            | 0.004 | 0.001  | 0.002 | -0.005 | ... | 0.528 |
| Exp. Out       | 0.004 | 0.001  | 0.002 | -0.005 | ... | 0.528 |
| Out (DSP)      | 140   | 22     | 61    | -161   | ... | 17314 |
| Exp. Out (DSP) | 141   | 22     | 61    | -161   | ... | 17315 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 72 |
| Max CPU cycles  | 73 |
| Avg CPU cycles  | 72 |

### Test case: Conversion test

OK

Conversion test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| <b>Time step</b>             | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| Time step                    | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3345 |
| Max CPU cycles  | 3348 |
| Avg CPU cycles  | 3347 |

**Verification: Average FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |        |       |    |        |     |        |
|----------------|--------|-------|----|--------|-----|--------|
| Time step      | 1      | 2     | 3  | 4      | ... | 113    |
| CPU cycles     | 98     | 87    | 87 | 87     | ... | 87     |
| Inputs         |        |       |    |        |     |        |
| In (DSP)       | -145   | 2369  | 4  | -2087  | ... | -1015  |
| In             | -0.004 | 0.072 | 0  | -0.064 | ... | -0.031 |
| Parameters     |        |       |    |        |     |        |
| n              | 1      |       |    |        |     |        |
| ts_fact        | 1      |       |    |        |     |        |
| Outputs        |        |       |    |        |     |        |
| Out            | -0.004 | 0.072 | 0  | -0.064 | ... | -0.031 |
| Exp. Out       | -0.004 | 0.072 | 0  | -0.064 | ... | -0.031 |
| Out (DSP)      | -145   | 2369  | 4  | -2087  | ... | -1015  |
| Exp. Out (DSP) | -145   | 2369  | 4  | -2087  | ... | -1015  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 87 |
| Max CPU cycles  | 98 |
| Avg CPU cycles  | 87 |

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 113    |
| CPU cycles     | 87     | 87     | 87     | 87     | ... | 87     |
| Inputs         |        |        |        |        |     |        |
| In (DSP)       | -4188  | 340    | -3895  | 355    | ... | -3177  |
| In             | -0.128 | 0.01   | -0.119 | 0.011  | ... | -0.097 |
| Parameters     |        |        |        |        |     |        |
| n              | 4      |        |        |        |     |        |
| ts_fact        | 1      |        |        |        |     |        |
| Outputs        |        |        |        |        |     |        |
| Out            | -0.032 | -0.029 | -0.059 | -0.056 | ... | 0.091  |
| Exp. Out       | -0.032 | -0.029 | -0.059 | -0.056 | ... | 0.091  |
| Out (DSP)      | -1047  | -962   | -1936  | -1847  | ... | 2994   |
| Exp. Out (DSP) | -1047  | -962   | -1936  | -1847  | ... | 2994   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 87 |
| Max CPU cycles  | 87 |
| Avg CPU cycles  | 87 |

### Test case: Inport test

OK

Inport test for Math block Average.

| Test results   |       |        |       |        |     |       |
|----------------|-------|--------|-------|--------|-----|-------|
| Time step      | 1     | 2      | 3     | 4      | ... | 113   |
| CPU cycles     | 87    | 87     | 87    | 87     | ... | 87    |
| Inputs         |       |        |       |        |     |       |
| In (DSP)       | 4496  | -3777  | 1239  | -7107  | ... | 2679  |
| In             | 0.137 | -0.115 | 0.038 | -0.217 | ... | 0.082 |
| Parameters     |       |        |       |        |     |       |
| n              | 32    |        |       |        |     |       |
| ts_fact        | 1     |        |       |        |     |       |
| Outputs        |       |        |       |        |     |       |
| Out            | 0.004 | 0.001  | 0.002 | -0.005 | ... | 0.528 |
| Exp. Out       | 0.004 | 0.001  | 0.002 | -0.005 | ... | 0.528 |
| Out (DSP)      | 140   | 22     | 61    | -161   | ... | 17314 |
| Exp. Out (DSP) | 141   | 22     | 61    | -161   | ... | 17315 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 87 |
| Max CPU cycles  | 87 |
| Avg CPU cycles  | 87 |

### Test case: Conversion test

OK

Conversion test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| <b>Time step</b>             | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| Time step                    | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 3834 |
| Max CPU cycles  | 3938 |
| Avg CPU cycles  | 3862 |



**Verification: Average FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |        |       |    |        |     |        |
|----------------|--------|-------|----|--------|-----|--------|
| Time step      | 1      | 2     | 3  | 4      | ... | 113    |
| CPU cycles     | 83     | 83    | 83 | 83     | ... | 83     |
| Inputs         |        |       |    |        |     |        |
| In (DSP)       | -145   | 2369  | 4  | -2087  | ... | -1015  |
| In             | -0.004 | 0.072 | 0  | -0.064 | ... | -0.031 |
| Parameters     |        |       |    |        |     |        |
| n              | 1      |       |    |        |     |        |
| ts_fact        | 1      |       |    |        |     |        |
| Outputs        |        |       |    |        |     |        |
| Out            | -0.004 | 0.072 | 0  | -0.064 | ... | -0.031 |
| Exp. Out       | -0.004 | 0.072 | 0  | -0.064 | ... | -0.031 |
| Out (DSP)      | -145   | 2369  | 4  | -2087  | ... | -1015  |
| Exp. Out (DSP) | -145   | 2369  | 4  | -2087  | ... | -1015  |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 3,0518\text{e-}05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 83 |
| Max CPU cycles  | 83 |
| Avg CPU cycles  | 83 |

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 113    |
| CPU cycles     | 87     | 87     | 87     | 83     | ... | 87     |
| Inputs         |        |        |        |        |     |        |
| In (DSP)       | -4188  | 340    | -3895  | 355    | ... | -3177  |
| In             | -0.128 | 0.01   | -0.119 | 0.011  | ... | -0.097 |
| Parameters     |        |        |        |        |     |        |
| n              | 4      |        |        |        |     |        |
| ts_fact        | 1      |        |        |        |     |        |
| Outputs        |        |        |        |        |     |        |
| Out            | -0.032 | -0.029 | -0.059 | -0.056 | ... | 0.091  |
| Exp. Out       | -0.032 | -0.029 | -0.059 | -0.056 | ... | 0.091  |
| Out (DSP)      | -1047  | -962   | -1936  | -1847  | ... | 2994   |
| Exp. Out (DSP) | -1047  | -962   | -1936  | -1847  | ... | 2994   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 83 |
| Max CPU cycles  | 87 |
| Avg CPU cycles  | 86 |

### Test case: Inport test

OK

Inport test for Math block Average.

| Test results   |       |        |       |        |     |       |
|----------------|-------|--------|-------|--------|-----|-------|
| Time step      | 1     | 2      | 3     | 4      | ... | 113   |
| CPU cycles     | 87    | 87     | 87    | 87     | ... | 87    |
| Inputs         |       |        |       |        |     |       |
| In (DSP)       | 4496  | -3777  | 1239  | -7107  | ... | 2679  |
| In             | 0.137 | -0.115 | 0.038 | -0.217 | ... | 0.082 |
| Parameters     |       |        |       |        |     |       |
| n              | 32    |        |       |        |     |       |
| ts_fact        | 1     |        |       |        |     |       |
| Outputs        |       |        |       |        |     |       |
| Out            | 0.004 | 0.001  | 0.002 | -0.005 | ... | 0.528 |
| Exp. Out       | 0.004 | 0.001  | 0.002 | -0.005 | ... | 0.528 |
| Out (DSP)      | 140   | 22     | 61    | -161   | ... | 17314 |
| Exp. Out (DSP) | 141   | 22     | 61    | -161   | ... | 17315 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 83 |
| Max CPU cycles  | 87 |
| Avg CPU cycles  | 86 |

### Test case: Conversion test

OK

Conversion test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| <b>Time step</b>             | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| Time step                    | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 5900 |
| Max CPU cycles  | 5935 |
| Avg CPU cycles  | 5918 |

**Verification: Average FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |          |           |     |           |
|----------------|----------|-----------|-----|-----------|
| Time step      | 1        | 2         | ... | 113       |
| CPU cycles     | 105      | 105       | ... | 105       |
| Inputs         |          |           |     |           |
| In (DSP)       | -9515881 | 155233746 | ... | -66486533 |
| In             | -0.004   | 0.072     | ... | -0.031    |
| Parameters     |          |           |     |           |
| n              | 1        |           |     |           |
| ts_fact        | 1        |           |     |           |
| Outputs        |          |           |     |           |
| Out            | -0.004   | 0.072     | ... | -0.031    |
| Exp. Out       | -0.004   | 0.072     | ... | -0.031    |
| Out (DSP)      | -9515881 | 155233746 | ... | -66486533 |
| Exp. Out (DSP) | -9515881 | 155233746 | ... | -66486533 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 105 |
| Max CPU cycles  | 105 |
| Avg CPU cycles  | 105 |

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |            |           |     |            |
|----------------|------------|-----------|-----|------------|
| Time step      | 1          | 2         | ... | 113        |
| CPU cycles     | 106        | 106       | ... | 106        |
| Inputs         |            |           |     |            |
| In (DSP)       | -274451780 | 22274693  | ... | -208184544 |
| In             | -0.128     | 0.01      | ... | -0.097     |
| Parameters     |            |           |     |            |
| n              | 4          |           |     |            |
| ts_fact        | 1          |           |     |            |
| Outputs        |            |           |     |            |
| Out            | -0.032     | -0.029    | ... | 0.091      |
| Exp. Out       | -0.032     | -0.029    | ... | 0.091      |
| Out (DSP)      | -68612945  | -63044272 | ... | 196244641  |
| Exp. Out (DSP) | -68612945  | -63044272 | ... | 196244642  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 105 |
| Max CPU cycles  | 106 |
| Avg CPU cycles  | 105 |

### Test case: Inport test

OK

Inport test for Math block Average.

| Test results   |           |            |     |            |
|----------------|-----------|------------|-----|------------|
| Time step      | 1         | 2          | ... | 113        |
| CPU cycles     | 106       | 106        | ... | 106        |
| Inputs         |           |            |     |            |
| In (DSP)       | 294667413 | -247518422 | ... | 175553610  |
| In             | 0.137     | -0.115     | ... | 0.082      |
| Parameters     |           |            |     |            |
| n              | 32        |            |     |            |
| ts_fact        | 1         |            |     |            |
| Outputs        |           |            |     |            |
| Out            | 0.004     | 0.001      | ... | 0.528      |
| Exp. Out       | 0.004     | 0.001      | ... | 0.528      |
| Out (DSP)      | 9208356   | 1473405    | ... | 1134727469 |
| Exp. Out (DSP) | 9208357   | 1473406    | ... | 1134727470 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 105 |
| Max CPU cycles  | 106 |
| Avg CPU cycles  | 105 |

### Test case: Conversion test

OK

Conversion test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| <b>Time step</b>             | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| Time step                    | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 7336 |
| Max CPU cycles  | 7370 |
| Avg CPU cycles  | 7354 |



**Verification: Average FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |          |           |     |           |
|----------------|----------|-----------|-----|-----------|
| Time step      | 1        | 2         | ... | 113       |
| CPU cycles     | 99       | 99        | ... | 99        |
| Inputs         |          |           |     |           |
| In (DSP)       | -9515881 | 155233746 | ... | -66486533 |
| In             | -0.004   | 0.072     | ... | -0.031    |
| Parameters     |          |           |     |           |
| n              | 1        |           |     |           |
| ts_fact        | 1        |           |     |           |
| Outputs        |          |           |     |           |
| Out            | -0.004   | 0.072     | ... | -0.031    |
| Exp. Out       | -0.004   | 0.072     | ... | -0.031    |
| Out (DSP)      | -9515881 | 155233746 | ... | -66486533 |
| Exp. Out (DSP) | -9515881 | 155233746 | ... | -66486533 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 99 |
| Max CPU cycles  | 99 |
| Avg CPU cycles  | 99 |

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |            |           |     |            |
|----------------|------------|-----------|-----|------------|
| Time step      | 1          | 2         | ... | 113        |
| CPU cycles     | 99         | 99        | ... | 99         |
| Inputs         |            |           |     |            |
| In (DSP)       | -274451780 | 22274693  | ... | -208184544 |
| In             | -0.128     | 0.01      | ... | -0.097     |
| Parameters     |            |           |     |            |
| n              | 4          |           |     |            |
| ts_fact        | 1          |           |     |            |
| Outputs        |            |           |     |            |
| Out            | -0.032     | -0.029    | ... | 0.091      |
| Exp. Out       | -0.032     | -0.029    | ... | 0.091      |
| Out (DSP)      | -68612945  | -63044272 | ... | 196244641  |
| Exp. Out (DSP) | -68612945  | -63044272 | ... | 196244642  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 99 |
| Max CPU cycles  | 99 |
| Avg CPU cycles  | 99 |

### Test case: Inport test

OK

Inport test for Math block Average.

| Test results   |           |            |     |            |
|----------------|-----------|------------|-----|------------|
| Time step      | 1         | 2          | ... | 113        |
| CPU cycles     | 99        | 99         | ... | 99         |
| Inputs         |           |            |     |            |
| In (DSP)       | 294667413 | -247518422 | ... | 175553610  |
| In             | 0.137     | -0.115     | ... | 0.082      |
| Parameters     |           |            |     |            |
| n              | 32        |            |     |            |
| ts_fact        | 1         |            |     |            |
| Outputs        |           |            |     |            |
| Out            | 0.004     | 0.001      | ... | 0.528      |
| Exp. Out       | 0.004     | 0.001      | ... | 0.528      |
| Out (DSP)      | 9208356   | 1473405    | ... | 1134727469 |
| Exp. Out (DSP) | 9208357   | 1473406    | ... | 1134727470 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 99 |
| Max CPU cycles  | 99 |
| Avg CPU cycles  | 99 |

### Test case: Conversion test

OK

Conversion test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| <b>Time step</b>             | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| Time step                    | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2617 |
| Max CPU cycles  | 2623 |
| Avg CPU cycles  | 2621 |

**Verification: Average FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |          |           |     |           |
|----------------|----------|-----------|-----|-----------|
| Time step      | 1        | 2         | ... | 113       |
| CPU cycles     | 106      | 106       | ... | 106       |
| Inputs         |          |           |     |           |
| In (DSP)       | -9515881 | 155233746 | ... | -66486533 |
| In             | -0.004   | 0.072     | ... | -0.031    |
| Parameters     |          |           |     |           |
| n              | 1        |           |     |           |
| ts_fact        | 1        |           |     |           |
| Outputs        |          |           |     |           |
| Out            | -0.004   | 0.072     | ... | -0.031    |
| Exp. Out       | -0.004   | 0.072     | ... | -0.031    |
| Out (DSP)      | -9515881 | 155233746 | ... | -66486533 |
| Exp. Out (DSP) | -9515881 | 155233746 | ... | -66486533 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 106 |
| Max CPU cycles  | 106 |
| Avg CPU cycles  | 106 |

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |            |           |     |            |
|----------------|------------|-----------|-----|------------|
| Time step      | 1          | 2         | ... | 113        |
| CPU cycles     | 106        | 106       | ... | 106        |
| Inputs         |            |           |     |            |
| In (DSP)       | -274451780 | 22274693  | ... | -208184544 |
| In             | -0.128     | 0.01      | ... | -0.097     |
| Parameters     |            |           |     |            |
| n              | 4          |           |     |            |
| ts_fact        | 1          |           |     |            |
| Outputs        |            |           |     |            |
| Out            | -0.032     | -0.029    | ... | 0.091      |
| Exp. Out       | -0.032     | -0.029    | ... | 0.091      |
| Out (DSP)      | -68612945  | -63044272 | ... | 196244641  |
| Exp. Out (DSP) | -68612945  | -63044272 | ... | 196244642  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 106 |
| Max CPU cycles  | 106 |
| Avg CPU cycles  | 106 |

### Test case: Inport test

OK

Inport test for Math block Average.

| Test results   |           |            |     |            |
|----------------|-----------|------------|-----|------------|
| Time step      | 1         | 2          | ... | 113        |
| CPU cycles     | 106       | 106        | ... | 106        |
| Inputs         |           |            |     |            |
| In (DSP)       | 294667413 | -247518422 | ... | 175553610  |
| In             | 0.137     | -0.115     | ... | 0.082      |
| Parameters     |           |            |     |            |
| n              | 32        |            |     |            |
| ts_fact        | 1         |            |     |            |
| Outputs        |           |            |     |            |
| Out            | 0.004     | 0.001      | ... | 0.528      |
| Exp. Out       | 0.004     | 0.001      | ... | 0.528      |
| Out (DSP)      | 9208356   | 1473405    | ... | 1134727469 |
| Exp. Out (DSP) | 9208357   | 1473406    | ... | 1134727470 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 106 |
| Max CPU cycles  | 106 |
| Avg CPU cycles  | 106 |

### Test case: Conversion test

OK

Conversion test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| <b>Time step</b>             | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| Time step                    | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 7774 |
| Max CPU cycles  | 7834 |
| Avg CPU cycles  | 7794 |



**Verification: Average FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |          |           |     |           |
|----------------|----------|-----------|-----|-----------|
| Time step      | 1        | 2         | ... | 113       |
| CPU cycles     | 111      | 111       | ... | 111       |
| Inputs         |          |           |     |           |
| In (DSP)       | -9515881 | 155233746 | ... | -66486533 |
| In             | -0.004   | 0.072     | ... | -0.031    |
| Parameters     |          |           |     |           |
| n              | 1        |           |     |           |
| ts_fact        | 1        |           |     |           |
| Outputs        |          |           |     |           |
| Out            | -0.004   | 0.072     | ... | -0.031    |
| Exp. Out       | -0.004   | 0.072     | ... | -0.031    |
| Out (DSP)      | -9515881 | 155233746 | ... | -66486533 |
| Exp. Out (DSP) | -9515881 | 155233746 | ... | -66486533 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 111 |
| Max CPU cycles  | 111 |
| Avg CPU cycles  | 111 |

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |            |           |     |            |
|----------------|------------|-----------|-----|------------|
| Time step      | 1          | 2         | ... | 113        |
| CPU cycles     | 111        | 111       | ... | 111        |
| Inputs         |            |           |     |            |
| In (DSP)       | -274451780 | 22274693  | ... | -208184544 |
| In             | -0.128     | 0.01      | ... | -0.097     |
| Parameters     |            |           |     |            |
| n              | 4          |           |     |            |
| ts_fact        | 1          |           |     |            |
| Outputs        |            |           |     |            |
| Out            | -0.032     | -0.029    | ... | 0.091      |
| Exp. Out       | -0.032     | -0.029    | ... | 0.091      |
| Out (DSP)      | -68612945  | -63044272 | ... | 196244641  |
| Exp. Out (DSP) | -68612945  | -63044272 | ... | 196244642  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 111 |
| Max CPU cycles  | 111 |
| Avg CPU cycles  | 111 |

### Test case: Inport test

OK

Inport test for Math block Average.

| Test results   |           |            |     |            |
|----------------|-----------|------------|-----|------------|
| Time step      | 1         | 2          | ... | 113        |
| CPU cycles     | 111       | 111        | ... | 111        |
| Inputs         |           |            |     |            |
| In (DSP)       | 294667413 | -247518422 | ... | 175553610  |
| In             | 0.137     | -0.115     | ... | 0.082      |
| Parameters     |           |            |     |            |
| n              | 32        |            |     |            |
| ts_fact        | 1         |            |     |            |
| Outputs        |           |            |     |            |
| Out            | 0.004     | 0.001      | ... | 0.528      |
| Exp. Out       | 0.004     | 0.001      | ... | 0.528      |
| Out (DSP)      | 9208356   | 1473405    | ... | 1134727469 |
| Exp. Out (DSP) | 9208357   | 1473406    | ... | 1134727470 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 111 |
| Max CPU cycles  | 111 |
| Avg CPU cycles  | 111 |

### Test case: Conversion test

OK

Conversion test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| <b>Time step</b>             | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| Time step                    | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 13060 |
| Max CPU cycles  | 13069 |
| Avg CPU cycles  | 13066 |

**Verification: Average FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |          |           |     |           |
|----------------|----------|-----------|-----|-----------|
| Time step      | 1        | 2         | ... | 113       |
| CPU cycles     | 74       | 74        | ... | 74        |
| Inputs         |          |           |     |           |
| In (DSP)       | -9515881 | 155233746 | ... | -66486533 |
| In             | -0.004   | 0.072     | ... | -0.031    |
| Parameters     |          |           |     |           |
| n              | 1        |           |     |           |
| ts_fact        | 1        |           |     |           |
| Outputs        |          |           |     |           |
| Out            | -0.004   | 0.072     | ... | -0.031    |
| Exp. Out       | -0.004   | 0.072     | ... | -0.031    |
| Out (DSP)      | -9515881 | 155233746 | ... | -66486533 |
| Exp. Out (DSP) | -9515881 | 155233746 | ... | -66486533 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 74 |
| Max CPU cycles  | 74 |
| Avg CPU cycles  | 74 |

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |            |           |     |            |
|----------------|------------|-----------|-----|------------|
| Time step      | 1          | 2         | ... | 113        |
| CPU cycles     | 72         | 72        | ... | 72         |
| Inputs         |            |           |     |            |
| In (DSP)       | -274451780 | 22274693  | ... | -208184544 |
| In             | -0.128     | 0.01      | ... | -0.097     |
| Parameters     |            |           |     |            |
| n              | 4          |           |     |            |
| ts_fact        | 1          |           |     |            |
| Outputs        |            |           |     |            |
| Out            | -0.032     | -0.029    | ... | 0.091      |
| Exp. Out       | -0.032     | -0.029    | ... | 0.091      |
| Out (DSP)      | -68612945  | -63044272 | ... | 196244641  |
| Exp. Out (DSP) | -68612945  | -63044272 | ... | 196244642  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 72 |
| Max CPU cycles  | 74 |
| Avg CPU cycles  | 72 |

### Test case: Inport test

OK

Inport test for Math block Average.

| Test results   |           |            |     |            |
|----------------|-----------|------------|-----|------------|
| Time step      | 1         | 2          | ... | 113        |
| CPU cycles     | 72        | 72         | ... | 72         |
| Inputs         |           |            |     |            |
| In (DSP)       | 294667413 | -247518422 | ... | 175553610  |
| In             | 0.137     | -0.115     | ... | 0.082      |
| Parameters     |           |            |     |            |
| n              | 32        |            |     |            |
| ts_fact        | 1         |            |     |            |
| Outputs        |           |            |     |            |
| Out            | 0.004     | 0.001      | ... | 0.528      |
| Exp. Out       | 0.004     | 0.001      | ... | 0.528      |
| Out (DSP)      | 9208356   | 1473405    | ... | 1134727469 |
| Exp. Out (DSP) | 9208357   | 1473406    | ... | 1134727470 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 72 |
| Max CPU cycles  | 74 |
| Avg CPU cycles  | 72 |

### Test case: Conversion test

OK

Conversion test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| <b>Time step</b>             | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| Time step                    | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1375 |
| Max CPU cycles  | 1377 |
| Avg CPU cycles  | 1376 |



**Verification: Average FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |          |           |     |           |
|----------------|----------|-----------|-----|-----------|
| Time step      | 1        | 2         | ... | 113       |
| CPU cycles     | 87       | 87        | ... | 87        |
| Inputs         |          |           |     |           |
| In (DSP)       | -9515881 | 155233746 | ... | -66486533 |
| In             | -0.004   | 0.072     | ... | -0.031    |
| Parameters     |          |           |     |           |
| n              | 1        |           |     |           |
| ts_fact        | 1        |           |     |           |
| Outputs        |          |           |     |           |
| Out            | -0.004   | 0.072     | ... | -0.031    |
| Exp. Out       | -0.004   | 0.072     | ... | -0.031    |
| Out (DSP)      | -9515881 | 155233746 | ... | -66486533 |
| Exp. Out (DSP) | -9515881 | 155233746 | ... | -66486533 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 87 |
| Max CPU cycles  | 87 |
| Avg CPU cycles  | 87 |

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |            |           |     |            |
|----------------|------------|-----------|-----|------------|
| Time step      | 1          | 2         | ... | 113        |
| CPU cycles     | 108        | 108       | ... | 108        |
| Inputs         |            |           |     |            |
| In (DSP)       | -274451780 | 22274693  | ... | -208184544 |
| In             | -0.128     | 0.01      | ... | -0.097     |
| Parameters     |            |           |     |            |
| n              | 4          |           |     |            |
| ts_fact        | 1          |           |     |            |
| Outputs        |            |           |     |            |
| Out            | -0.032     | -0.029    | ... | 0.091      |
| Exp. Out       | -0.032     | -0.029    | ... | 0.091      |
| Out (DSP)      | -68612945  | -63044272 | ... | 196244641  |
| Exp. Out (DSP) | -68612945  | -63044272 | ... | 196244642  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 107 |
| Max CPU cycles  | 108 |
| Avg CPU cycles  | 107 |

### Test case: Inport test

OK

Inport test for Math block Average.

| Test results   |           |            |     |            |
|----------------|-----------|------------|-----|------------|
| Time step      | 1         | 2          | ... | 113        |
| CPU cycles     | 138       | 138        | ... | 138        |
| Inputs         |           |            |     |            |
| In (DSP)       | 294667413 | -247518422 | ... | 175553610  |
| In             | 0.137     | -0.115     | ... | 0.082      |
| Parameters     |           |            |     |            |
| n              | 32        |            |     |            |
| ts_fact        | 1         |            |     |            |
| Outputs        |           |            |     |            |
| Out            | 0.004     | 0.001      | ... | 0.528      |
| Exp. Out       | 0.004     | 0.001      | ... | 0.528      |
| Out (DSP)      | 9208356   | 1473405    | ... | 1134727469 |
| Exp. Out (DSP) | 9208357   | 1473406    | ... | 1134727470 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 137 |
| Max CPU cycles  | 138 |
| Avg CPU cycles  | 137 |

### Test case: Conversion test

OK

Conversion test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| <b>Time step</b>             | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| Time step                    | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2321 |
| Max CPU cycles  | 2324 |
| Avg CPU cycles  | 2323 |

**Verification: Average FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |          |           |     |           |
|----------------|----------|-----------|-----|-----------|
| Time step      | 1        | 2         | ... | 113       |
| CPU cycles     | 114      | 102       | ... | 102       |
| Inputs         |          |           |     |           |
| In (DSP)       | -9515881 | 155233746 | ... | -66486533 |
| In             | -0.004   | 0.072     | ... | -0.031    |
| Parameters     |          |           |     |           |
| n              | 1        |           |     |           |
| ts_fact        | 1        |           |     |           |
| Outputs        |          |           |     |           |
| Out            | -0.004   | 0.072     | ... | -0.031    |
| Exp. Out       | -0.004   | 0.072     | ... | -0.031    |
| Out (DSP)      | -9515881 | 155233746 | ... | -66486533 |
| Exp. Out (DSP) | -9515881 | 155233746 | ... | -66486533 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 102 |
| Max CPU cycles  | 114 |
| Avg CPU cycles  | 102 |

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |            |           |     |            |
|----------------|------------|-----------|-----|------------|
| Time step      | 1          | 2         | ... | 113        |
| CPU cycles     | 102        | 102       | ... | 102        |
| Inputs         |            |           |     |            |
| In (DSP)       | -274451780 | 22274693  | ... | -208184544 |
| In             | -0.128     | 0.01      | ... | -0.097     |
| Parameters     |            |           |     |            |
| n              | 4          |           |     |            |
| ts_fact        | 1          |           |     |            |
| Outputs        |            |           |     |            |
| Out            | -0.032     | -0.029    | ... | 0.091      |
| Exp. Out       | -0.032     | -0.029    | ... | 0.091      |
| Out (DSP)      | -68612945  | -63044272 | ... | 196244641  |
| Exp. Out (DSP) | -68612945  | -63044272 | ... | 196244642  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 102 |
| Max CPU cycles  | 102 |
| Avg CPU cycles  | 102 |

### Test case: Inport test

OK

Inport test for Math block Average.

| Test results   |           |            |     |            |
|----------------|-----------|------------|-----|------------|
| Time step      | 1         | 2          | ... | 113        |
| CPU cycles     | 102       | 102        | ... | 102        |
| Inputs         |           |            |     |            |
| In (DSP)       | 294667413 | -247518422 | ... | 175553610  |
| In             | 0.137     | -0.115     | ... | 0.082      |
| Parameters     |           |            |     |            |
| n              | 32        |            |     |            |
| ts_fact        | 1         |            |     |            |
| Outputs        |           |            |     |            |
| Out            | 0.004     | 0.001      | ... | 0.528      |
| Exp. Out       | 0.004     | 0.001      | ... | 0.528      |
| Out (DSP)      | 9208356   | 1473405    | ... | 1134727469 |
| Exp. Out (DSP) | 9208357   | 1473406    | ... | 1134727470 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 102 |
| Max CPU cycles  | 102 |
| Avg CPU cycles  | 102 |

### Test case: Conversion test

OK

Conversion test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| <b>Time step</b>             | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| Time step                    | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1769 |
| Max CPU cycles  | 1846 |
| Avg CPU cycles  | 1792 |



**Verification: Average FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |          |           |     |           |
|----------------|----------|-----------|-----|-----------|
| Time step      | 1        | 2         | ... | 113       |
| CPU cycles     | 98       | 98        | ... | 98        |
| Inputs         |          |           |     |           |
| In (DSP)       | -9515881 | 155233746 | ... | -66486533 |
| In             | -0.004   | 0.072     | ... | -0.031    |
| Parameters     |          |           |     |           |
| n              | 1        |           |     |           |
| ts_fact        | 1        |           |     |           |
| Outputs        |          |           |     |           |
| Out            | -0.004   | 0.072     | ... | -0.031    |
| Exp. Out       | -0.004   | 0.072     | ... | -0.031    |
| Out (DSP)      | -9515881 | 155233746 | ... | -66486533 |
| Exp. Out (DSP) | -9515881 | 155233746 | ... | -66486533 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 98 |
| Max CPU cycles  | 98 |
| Avg CPU cycles  | 98 |

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |            |           |     |            |
|----------------|------------|-----------|-----|------------|
| Time step      | 1          | 2         | ... | 113        |
| CPU cycles     | 102        | 102       | ... | 102        |
| Inputs         |            |           |     |            |
| In (DSP)       | -274451780 | 22274693  | ... | -208184544 |
| In             | -0.128     | 0.01      | ... | -0.097     |
| Parameters     |            |           |     |            |
| n              | 4          |           |     |            |
| ts_fact        | 1          |           |     |            |
| Outputs        |            |           |     |            |
| Out            | -0.032     | -0.029    | ... | 0.091      |
| Exp. Out       | -0.032     | -0.029    | ... | 0.091      |
| Out (DSP)      | -68612945  | -63044272 | ... | 196244641  |
| Exp. Out (DSP) | -68612945  | -63044272 | ... | 196244642  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 98  |
| Max CPU cycles  | 102 |
| Avg CPU cycles  | 101 |

### Test case: Inport test

OK

Inport test for Math block Average.

| Test results   |           |            |     |            |
|----------------|-----------|------------|-----|------------|
| Time step      | 1         | 2          | ... | 113        |
| CPU cycles     | 102       | 102        | ... | 102        |
| Inputs         |           |            |     |            |
| In (DSP)       | 294667413 | -247518422 | ... | 175553610  |
| In             | 0.137     | -0.115     | ... | 0.082      |
| Parameters     |           |            |     |            |
| n              | 32        |            |     |            |
| ts_fact        | 1         |            |     |            |
| Outputs        |           |            |     |            |
| Out            | 0.004     | 0.001      | ... | 0.528      |
| Exp. Out       | 0.004     | 0.001      | ... | 0.528      |
| Out (DSP)      | 9208356   | 1473405    | ... | 1134727469 |
| Exp. Out (DSP) | 9208357   | 1473406    | ... | 1134727470 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 98  |
| Max CPU cycles  | 102 |
| Avg CPU cycles  | 101 |

### Test case: Conversion test

OK

Conversion test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| <b>Time step</b>             | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| Time step                    | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>sfrn</b>                  | 0 | 1 | 2 | 8   |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. sfrn</b>             | 0 | 1 | 2 | 8   |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sfrn | $\pm 0,0000e+00$ |
| Tolerance n    | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 6034 |
| Max CPU cycles  | 6058 |
| Avg CPU cycles  | 6047 |

**Verification: Average Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |        |       |     |        |
|----------------|--------|-------|-----|--------|
| Time step      | 1      | 2     | ... | 113    |
| CPU cycles     | 355    | 355   | ... | 355    |
| Inputs         |        |       |     |        |
| In (DSP)       | -0.004 | 0.072 | ... | -0.031 |
| In             | -0.004 | 0.072 | ... | -0.031 |
| Parameters     |        |       |     |        |
| n              | 1      |       |     |        |
| ts_fact        | 1      |       |     |        |
| Outputs        |        |       |     |        |
| Out            | -0.004 | 0.072 | ... | -0.031 |
| Exp. Out       | -0.004 | 0.072 | ... | -0.031 |
| Out (DSP)      | -0.004 | 0.072 | ... | -0.031 |
| Exp. Out (DSP) | -0.004 | 0.072 | ... | -0.031 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 4,6566e-08$ ( $\pm 100$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 355 |
| Max CPU cycles  | 355 |
| Avg CPU cycles  | 355 |

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |        |        |     |        |
|----------------|--------|--------|-----|--------|
| Time step      | 1      | 2      | ... | 113    |
| CPU cycles     | 356    | 356    | ... | 356    |
| Inputs         |        |        |     |        |
| In (DSP)       | -0.128 | 0.01   | ... | -0.097 |
| In             | -0.128 | 0.01   | ... | -0.097 |
| Parameters     |        |        |     |        |
| n              | 4      |        |     |        |
| ts_fact        | 1      |        |     |        |
| Outputs        |        |        |     |        |
| Out            | -0.032 | -0.029 | ... | 0.091  |
| Exp. Out       | -0.032 | -0.029 | ... | 0.091  |
| Out (DSP)      | -0.032 | -0.029 | ... | 0.091  |
| Exp. Out (DSP) | -0.032 | -0.029 | ... | 0.091  |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}07$ ( $\pm 1500$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 355 |
| Max CPU cycles  | 356 |
| Avg CPU cycles  | 355 |

### Test case: Inport test

OK

Inport test for Math block Average.

| Test results   |       |        |     |       |
|----------------|-------|--------|-----|-------|
| Time step      | 1     | 2      | ... | 113   |
| CPU cycles     | 356   | 356    | ... | 356   |
| Inputs         |       |        |     |       |
| In (DSP)       | 0.137 | -0.115 | ... | 0.082 |
| In             | 0.137 | -0.115 | ... | 0.082 |
| Parameters     |       |        |     |       |
| n              | 32    |        |     |       |
| ts_fact        | 1     |        |     |       |
| Outputs        |       |        |     |       |
| Out            | 0.004 | 0.001  | ... | 0.528 |
| Exp. Out       | 0.004 | 0.001  | ... | 0.528 |
| Out (DSP)      | 0.004 | 0.001  | ... | 0.528 |
| Exp. Out (DSP) | 0.004 | 0.001  | ... | 0.528 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 355 |
| Max CPU cycles  | 356 |
| Avg CPU cycles  | 355 |

### Test case: Conversion test

OK

Conversion test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| <b>Time step</b>             | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings |                  |
|---------------|------------------|
| Tolerance n   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Math block Average.

| Test results          |   |   |   |     |
|-----------------------|---|---|---|-----|
| Time step             | 1 | 2 | 3 | 4   |
| Mask parameters       |   |   |   |     |
| n                     | 1 | 2 | 4 | 256 |
| ts_fact               | 1 | 1 | 1 | 1   |
| Controller parameters |   |   |   |     |
| n                     | 1 | 2 | 4 | 256 |
| Exp. n                | 1 | 2 | 4 | 256 |

| Test settings |                  |
|---------------|------------------|
| Tolerance n   | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 8067 |
| Max CPU cycles  | 8111 |
| Avg CPU cycles  | 8087 |



## Verification: Average Float32 CPU TM4C123GH6

Date of Test 2026-06-19  
Target controller TM4C123GH6

### Test case: Inport test

OK

Inport test for Math block Average.

| Test results   |        |       |     |        |
|----------------|--------|-------|-----|--------|
| Time step      | 1      | 2     | ... | 113    |
| CPU cycles     | 81     | 81    | ... | 81     |
| Inputs         |        |       |     |        |
| In (DSP)       | -0.004 | 0.072 | ... | -0.031 |
| In             | -0.004 | 0.072 | ... | -0.031 |
| Parameters     |        |       |     |        |
| n              | 1      |       |     |        |
| ts_fact        | 1      |       |     |        |
| Outputs        |        |       |     |        |
| Out            | -0.004 | 0.072 | ... | -0.031 |
| Exp. Out       | -0.004 | 0.072 | ... | -0.031 |
| Out (DSP)      | -0.004 | 0.072 | ... | -0.031 |
| Exp. Out (DSP) | -0.004 | 0.072 | ... | -0.031 |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 4,6566\text{e-}08$ ( $\pm 100$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 81 |
| Max CPU cycles  | 81 |
| Avg CPU cycles  | 81 |

### Test case: Inport test

OK

Inport test for Math block Average.

| Test results   |        |        |     |        |
|----------------|--------|--------|-----|--------|
| Time step      | 1      | 2      | ... | 113    |
| CPU cycles     | 81     | 81     | ... | 81     |
| Inputs         |        |        |     |        |
| In (DSP)       | -0.128 | 0.01   | ... | -0.097 |
| In             | -0.128 | 0.01   | ... | -0.097 |
| Parameters     |        |        |     |        |
| n              | 4      |        |     |        |
| ts_fact        | 1      |        |     |        |
| Outputs        |        |        |     |        |
| Out            | -0.032 | -0.029 | ... | 0.091  |
| Exp. Out       | -0.032 | -0.029 | ... | 0.091  |
| Out (DSP)      | -0.032 | -0.029 | ... | 0.091  |
| Exp. Out (DSP) | -0.032 | -0.029 | ... | 0.091  |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}07$ ( $\pm 1500$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 81 |
| Max CPU cycles  | 81 |
| Avg CPU cycles  | 81 |

### Test case: Inport test

OK

Inport test for Math block Average.

| Test results   |       |        |     |       |
|----------------|-------|--------|-----|-------|
| Time step      | 1     | 2      | ... | 113   |
| CPU cycles     | 81    | 81     | ... | 81    |
| Inputs         |       |        |     |       |
| In (DSP)       | 0.137 | -0.115 | ... | 0.082 |
| In             | 0.137 | -0.115 | ... | 0.082 |
| Parameters     |       |        |     |       |
| n              | 32    |        |     |       |
| ts_fact        | 1     |        |     |       |
| Outputs        |       |        |     |       |
| Out            | 0.004 | 0.001  | ... | 0.528 |
| Exp. Out       | 0.004 | 0.001  | ... | 0.528 |
| Out (DSP)      | 0.004 | 0.001  | ... | 0.528 |
| Exp. Out (DSP) | 0.004 | 0.001  | ... | 0.528 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 81 |
| Max CPU cycles  | 81 |
| Avg CPU cycles  | 81 |

### Test case: Conversion test

OK

Conversion test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| <b>Time step</b>             | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings |                  |
|---------------|------------------|
| Tolerance n   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Math block Average.

| Test results          |   |   |   |     |
|-----------------------|---|---|---|-----|
| Time step             | 1 | 2 | 3 | 4   |
| Mask parameters       |   |   |   |     |
| n                     | 1 | 2 | 4 | 256 |
| ts_fact               | 1 | 1 | 1 | 1   |
| Controller parameters |   |   |   |     |
| n                     | 1 | 2 | 4 | 256 |
| Exp. n                | 1 | 2 | 4 | 256 |

| Test settings |                  |
|---------------|------------------|
| Tolerance n   | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2991 |
| Max CPU cycles  | 2993 |
| Avg CPU cycles  | 2992 |

**Verification: Average Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |        |       |     |        |
|----------------|--------|-------|-----|--------|
| Time step      | 1      | 2     | ... | 113    |
| CPU cycles     | 112    | 112   | ... | 112    |
| Inputs         |        |       |     |        |
| In (DSP)       | -0.004 | 0.072 | ... | -0.031 |
| In             | -0.004 | 0.072 | ... | -0.031 |
| Parameters     |        |       |     |        |
| n              | 1      |       |     |        |
| ts_fact        | 1      |       |     |        |
| Outputs        |        |       |     |        |
| Out            | -0.004 | 0.072 | ... | -0.031 |
| Exp. Out       | -0.004 | 0.072 | ... | -0.031 |
| Out (DSP)      | -0.004 | 0.072 | ... | -0.031 |
| Exp. Out (DSP) | -0.004 | 0.072 | ... | -0.031 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 4,6566e-08$ ( $\pm 100$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 112 |
| Max CPU cycles  | 112 |
| Avg CPU cycles  | 112 |

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |        |        |     |        |
|----------------|--------|--------|-----|--------|
| Time step      | 1      | 2      | ... | 113    |
| CPU cycles     | 112    | 112    | ... | 112    |
| Inputs         |        |        |     |        |
| In (DSP)       | -0.128 | 0.01   | ... | -0.097 |
| In             | -0.128 | 0.01   | ... | -0.097 |
| Parameters     |        |        |     |        |
| n              | 4      |        |     |        |
| ts_fact        | 1      |        |     |        |
| Outputs        |        |        |     |        |
| Out            | -0.032 | -0.029 | ... | 0.091  |
| Exp. Out       | -0.032 | -0.029 | ... | 0.091  |
| Out (DSP)      | -0.032 | -0.029 | ... | 0.091  |
| Exp. Out (DSP) | -0.032 | -0.029 | ... | 0.091  |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}07$ ( $\pm 1500$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 112 |
| Max CPU cycles  | 112 |
| Avg CPU cycles  | 112 |

### Test case: Inport test

OK

Inport test for Math block Average.

| Test results   |       |        |     |       |
|----------------|-------|--------|-----|-------|
| Time step      | 1     | 2      | ... | 113   |
| CPU cycles     | 112   | 112    | ... | 112   |
| Inputs         |       |        |     |       |
| In (DSP)       | 0.137 | -0.115 | ... | 0.082 |
| In             | 0.137 | -0.115 | ... | 0.082 |
| Parameters     |       |        |     |       |
| n              | 32    |        |     |       |
| ts_fact        | 1     |        |     |       |
| Outputs        |       |        |     |       |
| Out            | 0.004 | 0.001  | ... | 0.528 |
| Exp. Out       | 0.004 | 0.001  | ... | 0.528 |
| Out (DSP)      | 0.004 | 0.001  | ... | 0.528 |
| Exp. Out (DSP) | 0.004 | 0.001  | ... | 0.528 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 112 |
| Max CPU cycles  | 112 |
| Avg CPU cycles  | 112 |

### Test case: Conversion test

OK

Conversion test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| <b>Time step</b>             | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings |                  |
|---------------|------------------|
| Tolerance n   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Math block Average.

| Test results          |   |   |   |     |
|-----------------------|---|---|---|-----|
| Time step             | 1 | 2 | 3 | 4   |
| Mask parameters       |   |   |   |     |
| n                     | 1 | 2 | 4 | 256 |
| ts_fact               | 1 | 1 | 1 | 1   |
| Controller parameters |   |   |   |     |
| n                     | 1 | 2 | 4 | 256 |
| Exp. n                | 1 | 2 | 4 | 256 |

| Test settings |                  |
|---------------|------------------|
| Tolerance n   | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 7763 |
| Max CPU cycles  | 7835 |
| Avg CPU cycles  | 7783 |



**Verification: Average Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |        |       |     |        |
|----------------|--------|-------|-----|--------|
| Time step      | 1      | 2     | ... | 113    |
| CPU cycles     | 903    | 902   | ... | 899    |
| Inputs         |        |       |     |        |
| In (DSP)       | -0.004 | 0.072 | ... | -0.031 |
| In             | -0.004 | 0.072 | ... | -0.031 |
| Parameters     |        |       |     |        |
| n              | 1      |       |     |        |
| ts_fact        | 1      |       |     |        |
| Outputs        |        |       |     |        |
| Out            | -0.004 | 0.072 | ... | -0.031 |
| Exp. Out       | -0.004 | 0.072 | ... | -0.031 |
| Out (DSP)      | -0.004 | 0.072 | ... | -0.031 |
| Exp. Out (DSP) | -0.004 | 0.072 | ... | -0.031 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 4,6566e-08$ ( $\pm 100$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 899 |
| Max CPU cycles  | 961 |
| Avg CPU cycles  | 901 |

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |        |        |     |        |
|----------------|--------|--------|-----|--------|
| Time step      | 1      | 2      | ... | 113    |
| CPU cycles     | 903    | 991    | ... | 1023   |
| Inputs         |        |        |     |        |
| In (DSP)       | -0.128 | 0.01   | ... | -0.097 |
| In             | -0.128 | 0.01   | ... | -0.097 |
| Parameters     |        |        |     |        |
| n              | 4      |        |     |        |
| ts_fact        | 1      |        |     |        |
| Outputs        |        |        |     |        |
| Out            | -0.032 | -0.029 | ... | 0.091  |
| Exp. Out       | -0.032 | -0.029 | ... | 0.091  |
| Out (DSP)      | -0.032 | -0.029 | ... | 0.091  |
| Exp. Out (DSP) | -0.032 | -0.029 | ... | 0.091  |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}07$ ( $\pm 1500$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 903  |
| Max CPU cycles  | 1061 |
| Avg CPU cycles  | 1001 |

### Test case: Inport test

OK

Inport test for Math block Average.

| Test results   |       |        |     |       |
|----------------|-------|--------|-----|-------|
| Time step      | 1     | 2      | ... | 113   |
| CPU cycles     | 906   | 984    | ... | 992   |
| Inputs         |       |        |     |       |
| In (DSP)       | 0.137 | -0.115 | ... | 0.082 |
| In             | 0.137 | -0.115 | ... | 0.082 |
| Parameters     |       |        |     |       |
| n              | 32    |        |     |       |
| ts_fact        | 1     |        |     |       |
| Outputs        |       |        |     |       |
| Out            | 0.004 | 0.001  | ... | 0.528 |
| Exp. Out       | 0.004 | 0.001  | ... | 0.528 |
| Out (DSP)      | 0.004 | 0.001  | ... | 0.528 |
| Exp. Out (DSP) | 0.004 | 0.001  | ... | 0.528 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 906  |
| Max CPU cycles  | 1052 |
| Avg CPU cycles  | 982  |

### Test case: Conversion test

OK

Conversion test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| <b>Time step</b>             | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings |                  |
|---------------|------------------|
| Tolerance n   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Math block Average.

| Test results          |   |   |   |     |
|-----------------------|---|---|---|-----|
| Time step             | 1 | 2 | 3 | 4   |
| Mask parameters       |   |   |   |     |
| n                     | 1 | 2 | 4 | 256 |
| ts_fact               | 1 | 1 | 1 | 1   |
| Controller parameters |   |   |   |     |
| n                     | 1 | 2 | 4 | 256 |
| Exp. n                | 1 | 2 | 4 | 256 |

| Test settings |                  |
|---------------|------------------|
| Tolerance n   | $\pm 0,0000e+00$ |

| Test statistics |       |
|-----------------|-------|
| Min CPU cycles  | 13049 |
| Max CPU cycles  | 13058 |
| Avg CPU cycles  | 13055 |

**Verification: Average Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |        |       |     |        |
|----------------|--------|-------|-----|--------|
| Time step      | 1      | 2     | ... | 113    |
| CPU cycles     | 322    | 330   | ... | 330    |
| Inputs         |        |       |     |        |
| In (DSP)       | -0.004 | 0.072 | ... | -0.031 |
| In             | -0.004 | 0.072 | ... | -0.031 |
| Parameters     |        |       |     |        |
| n              | 1      |       |     |        |
| ts_fact        | 1      |       |     |        |
| Outputs        |        |       |     |        |
| Out            | -0.004 | 0.072 | ... | -0.031 |
| Exp. Out       | -0.004 | 0.072 | ... | -0.031 |
| Out (DSP)      | -0.004 | 0.072 | ... | -0.031 |
| Exp. Out (DSP) | -0.004 | 0.072 | ... | -0.031 |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 4,6566\text{e-}08$ ( $\pm 100$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 307 |
| Max CPU cycles  | 330 |
| Avg CPU cycles  | 329 |

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |        |        |     |        |
|----------------|--------|--------|-----|--------|
| Time step      | 1      | 2      | ... | 113    |
| CPU cycles     | 320    | 345    | ... | 374    |
| Inputs         |        |        |     |        |
| In (DSP)       | -0.128 | 0.01   | ... | -0.097 |
| In             | -0.128 | 0.01   | ... | -0.097 |
| Parameters     |        |        |     |        |
| n              | 4      |        |     |        |
| ts_fact        | 1      |        |     |        |
| Outputs        |        |        |     |        |
| Out            | -0.032 | -0.029 | ... | 0.091  |
| Exp. Out       | -0.032 | -0.029 | ... | 0.091  |
| Out (DSP)      | -0.032 | -0.029 | ... | 0.091  |
| Exp. Out (DSP) | -0.032 | -0.029 | ... | 0.091  |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}07$ ( $\pm 1500$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 320 |
| Max CPU cycles  | 377 |
| Avg CPU cycles  | 369 |

### Test case: Inport test

OK

Inport test for Math block Average.

| Test results   |       |        |     |       |
|----------------|-------|--------|-----|-------|
| Time step      | 1     | 2      | ... | 113   |
| CPU cycles     | 320   | 345    | ... | 367   |
| Inputs         |       |        |     |       |
| In (DSP)       | 0.137 | -0.115 | ... | 0.082 |
| In             | 0.137 | -0.115 | ... | 0.082 |
| Parameters     |       |        |     |       |
| n              | 32    |        |     |       |
| ts_fact        | 1     |        |     |       |
| Outputs        |       |        |     |       |
| Out            | 0.004 | 0.001  | ... | 0.528 |
| Exp. Out       | 0.004 | 0.001  | ... | 0.528 |
| Out (DSP)      | 0.004 | 0.001  | ... | 0.528 |
| Exp. Out (DSP) | 0.004 | 0.001  | ... | 0.528 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 320 |
| Max CPU cycles  | 377 |
| Avg CPU cycles  | 359 |

### Test case: Conversion test

OK

Conversion test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| <b>Time step</b>             | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings |                  |
|---------------|------------------|
| Tolerance n   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Math block Average.

| Test results          |   |   |   |     |
|-----------------------|---|---|---|-----|
| Time step             | 1 | 2 | 3 | 4   |
| Mask parameters       |   |   |   |     |
| n                     | 1 | 2 | 4 | 256 |
| ts_fact               | 1 | 1 | 1 | 1   |
| Controller parameters |   |   |   |     |
| n                     | 1 | 2 | 4 | 256 |
| Exp. n                | 1 | 2 | 4 | 256 |

| Test settings |                  |
|---------------|------------------|
| Tolerance n   | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1360 |
| Max CPU cycles  | 1361 |
| Avg CPU cycles  | 1360 |



**Verification: Average Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |        |       |     |        |
|----------------|--------|-------|-----|--------|
| Time step      | 1      | 2     | ... | 113    |
| CPU cycles     | 1153   | 1170  | ... | 1174   |
| Inputs         |        |       |     |        |
| In (DSP)       | -0.004 | 0.072 | ... | -0.031 |
| In             | -0.004 | 0.072 | ... | -0.031 |
| Parameters     |        |       |     |        |
| n              | 1      |       |     |        |
| ts_fact        | 1      |       |     |        |
| Outputs        |        |       |     |        |
| Out            | -0.004 | 0.072 | ... | -0.031 |
| Exp. Out       | -0.004 | 0.072 | ... | -0.031 |
| Out (DSP)      | -0.004 | 0.072 | ... | -0.031 |
| Exp. Out (DSP) | -0.004 | 0.072 | ... | -0.031 |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 4,6566\text{e-}08$ ( $\pm 100$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1153 |
| Max CPU cycles  | 1192 |
| Avg CPU cycles  | 1174 |

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |        |        |     |        |
|----------------|--------|--------|-----|--------|
| Time step      | 1      | 2      | ... | 113    |
| CPU cycles     | 1137   | 1175   | ... | 1218   |
| Inputs         |        |        |     |        |
| In (DSP)       | -0.128 | 0.01   | ... | -0.097 |
| In             | -0.128 | 0.01   | ... | -0.097 |
| Parameters     |        |        |     |        |
| n              | 4      |        |     |        |
| ts_fact        | 1      |        |     |        |
| Outputs        |        |        |     |        |
| Out            | -0.032 | -0.029 | ... | 0.091  |
| Exp. Out       | -0.032 | -0.029 | ... | 0.091  |
| Out (DSP)      | -0.032 | -0.029 | ... | 0.091  |
| Exp. Out (DSP) | -0.032 | -0.029 | ... | 0.091  |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}07$ ( $\pm 1500$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1129 |
| Max CPU cycles  | 1254 |
| Avg CPU cycles  | 1203 |

### Test case: Inport test

OK

Inport test for Math block Average.

| Test results   |       |        |     |       |
|----------------|-------|--------|-----|-------|
| Time step      | 1     | 2      | ... | 113   |
| CPU cycles     | 1091  | 1147   | ... | 1263  |
| Inputs         |       |        |     |       |
| In (DSP)       | 0.137 | -0.115 | ... | 0.082 |
| In             | 0.137 | -0.115 | ... | 0.082 |
| Parameters     |       |        |     |       |
| n              | 32    |        |     |       |
| ts_fact        | 1     |        |     |       |
| Outputs        |       |        |     |       |
| Out            | 0.004 | 0.001  | ... | 0.528 |
| Exp. Out       | 0.004 | 0.001  | ... | 0.528 |
| Out (DSP)      | 0.004 | 0.001  | ... | 0.528 |
| Exp. Out (DSP) | 0.004 | 0.001  | ... | 0.528 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1086 |
| Max CPU cycles  | 1343 |
| Avg CPU cycles  | 1208 |

### Test case: Conversion test

OK

Conversion test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| <b>Time step</b>             | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings |                  |
|---------------|------------------|
| Tolerance n   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Math block Average.

| Test results          |   |   |   |     |
|-----------------------|---|---|---|-----|
| Time step             | 1 | 2 | 3 | 4   |
| Mask parameters       |   |   |   |     |
| n                     | 1 | 2 | 4 | 256 |
| ts_fact               | 1 | 1 | 1 | 1   |
| Controller parameters |   |   |   |     |
| n                     | 1 | 2 | 4 | 256 |
| Exp. n                | 1 | 2 | 4 | 256 |

| Test settings |                  |
|---------------|------------------|
| Tolerance n   | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 2314 |
| Max CPU cycles  | 2317 |
| Avg CPU cycles  | 2315 |

**Verification: Average Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |        |       |     |        |
|----------------|--------|-------|-----|--------|
| Time step      | 1      | 2     | ... | 113    |
| CPU cycles     | 114    | 99    | ... | 99     |
| Inputs         |        |       |     |        |
| In (DSP)       | -0.004 | 0.072 | ... | -0.031 |
| In             | -0.004 | 0.072 | ... | -0.031 |
| Parameters     |        |       |     |        |
| n              | 1      |       |     |        |
| ts_fact        | 1      |       |     |        |
| Outputs        |        |       |     |        |
| Out            | -0.004 | 0.072 | ... | -0.031 |
| Exp. Out       | -0.004 | 0.072 | ... | -0.031 |
| Out (DSP)      | -0.004 | 0.072 | ... | -0.031 |
| Exp. Out (DSP) | -0.004 | 0.072 | ... | -0.031 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 4,6566e-08$ ( $\pm 100$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 99  |
| Max CPU cycles  | 114 |
| Avg CPU cycles  | 99  |

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |        |        |     |        |
|----------------|--------|--------|-----|--------|
| Time step      | 1      | 2      | ... | 113    |
| CPU cycles     | 99     | 99     | ... | 99     |
| Inputs         |        |        |     |        |
| In (DSP)       | -0.128 | 0.01   | ... | -0.097 |
| In             | -0.128 | 0.01   | ... | -0.097 |
| Parameters     |        |        |     |        |
| n              | 4      |        |     |        |
| ts_fact        | 1      |        |     |        |
| Outputs        |        |        |     |        |
| Out            | -0.032 | -0.029 | ... | 0.091  |
| Exp. Out       | -0.032 | -0.029 | ... | 0.091  |
| Out (DSP)      | -0.032 | -0.029 | ... | 0.091  |
| Exp. Out (DSP) | -0.032 | -0.029 | ... | 0.091  |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}07$ ( $\pm 1500$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 99 |
| Max CPU cycles  | 99 |
| Avg CPU cycles  | 99 |

### Test case: Inport test

OK

Inport test for Math block Average.

| Test results   |       |        |     |       |
|----------------|-------|--------|-----|-------|
| Time step      | 1     | 2      | ... | 113   |
| CPU cycles     | 99    | 99     | ... | 99    |
| Inputs         |       |        |     |       |
| In (DSP)       | 0.137 | -0.115 | ... | 0.082 |
| In             | 0.137 | -0.115 | ... | 0.082 |
| Parameters     |       |        |     |       |
| n              | 32    |        |     |       |
| ts_fact        | 1     |        |     |       |
| Outputs        |       |        |     |       |
| Out            | 0.004 | 0.001  | ... | 0.528 |
| Exp. Out       | 0.004 | 0.001  | ... | 0.528 |
| Out (DSP)      | 0.004 | 0.001  | ... | 0.528 |
| Exp. Out (DSP) | 0.004 | 0.001  | ... | 0.528 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 99 |
| Max CPU cycles  | 99 |
| Avg CPU cycles  | 99 |

### Test case: Conversion test

OK

Conversion test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| <b>Time step</b>             | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings |                  |
|---------------|------------------|
| Tolerance n   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Math block Average.

| Test results          |   |   |   |     |
|-----------------------|---|---|---|-----|
| Time step             | 1 | 2 | 3 | 4   |
| Mask parameters       |   |   |   |     |
| n                     | 1 | 2 | 4 | 256 |
| ts_fact               | 1 | 1 | 1 | 1   |
| Controller parameters |   |   |   |     |
| n                     | 1 | 2 | 4 | 256 |
| Exp. n                | 1 | 2 | 4 | 256 |

| Test settings |                  |
|---------------|------------------|
| Tolerance n   | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1771 |
| Max CPU cycles  | 1859 |
| Avg CPU cycles  | 1797 |



**Verification: Average Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |        |       |     |        |
|----------------|--------|-------|-----|--------|
| Time step      | 1      | 2     | ... | 113    |
| CPU cycles     | 335    | 335   | ... | 335    |
| Inputs         |        |       |     |        |
| In (DSP)       | -0.004 | 0.072 | ... | -0.031 |
| In             | -0.004 | 0.072 | ... | -0.031 |
| Parameters     |        |       |     |        |
| n              | 1      |       |     |        |
| ts_fact        | 1      |       |     |        |
| Outputs        |        |       |     |        |
| Out            | -0.004 | 0.072 | ... | -0.031 |
| Exp. Out       | -0.004 | 0.072 | ... | -0.031 |
| Out (DSP)      | -0.004 | 0.072 | ... | -0.031 |
| Exp. Out (DSP) | -0.004 | 0.072 | ... | -0.031 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 4,6566e-08$ ( $\pm 100$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 335 |
| Max CPU cycles  | 335 |
| Avg CPU cycles  | 335 |

**Test case: Inport test****OK**

Inport test for Math block Average.

| Test results   |        |        |     |        |
|----------------|--------|--------|-----|--------|
| Time step      | 1      | 2      | ... | 113    |
| CPU cycles     | 341    | 341    | ... | 341    |
| Inputs         |        |        |     |        |
| In (DSP)       | -0.128 | 0.01   | ... | -0.097 |
| In             | -0.128 | 0.01   | ... | -0.097 |
| Parameters     |        |        |     |        |
| n              | 4      |        |     |        |
| ts_fact        | 1      |        |     |        |
| Outputs        |        |        |     |        |
| Out            | -0.032 | -0.029 | ... | 0.091  |
| Exp. Out       | -0.032 | -0.029 | ... | 0.091  |
| Out (DSP)      | -0.032 | -0.029 | ... | 0.091  |
| Exp. Out (DSP) | -0.032 | -0.029 | ... | 0.091  |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}07$ ( $\pm 1500$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 335 |
| Max CPU cycles  | 341 |
| Avg CPU cycles  | 339 |

### Test case: Inport test

OK

Inport test for Math block Average.

| Test results   |       |        |     |       |
|----------------|-------|--------|-----|-------|
| Time step      | 1     | 2      | ... | 113   |
| CPU cycles     | 341   | 341    | ... | 341   |
| Inputs         |       |        |     |       |
| In (DSP)       | 0.137 | -0.115 | ... | 0.082 |
| In             | 0.137 | -0.115 | ... | 0.082 |
| Parameters     |       |        |     |       |
| n              | 32    |        |     |       |
| ts_fact        | 1     |        |     |       |
| Outputs        |       |        |     |       |
| Out            | 0.004 | 0.001  | ... | 0.528 |
| Exp. Out       | 0.004 | 0.001  | ... | 0.528 |
| Out (DSP)      | 0.004 | 0.001  | ... | 0.528 |
| Exp. Out (DSP) | 0.004 | 0.001  | ... | 0.528 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 4,6566e-07$ ( $\pm 1000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 335 |
| Max CPU cycles  | 341 |
| Avg CPU cycles  | 340 |

### Test case: Conversion test

OK

Conversion test for Math block Average.

| Test results                 |   |   |   |     |
|------------------------------|---|---|---|-----|
| <b>Time step</b>             | 1 | 2 | 3 | 4   |
| <i>Mask parameters</i>       |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>ts_fact</b>               | 1 | 1 | 1 | 1   |
| <i>Controller parameters</i> |   |   |   |     |
| <b>n</b>                     | 1 | 2 | 4 | 256 |
| <b>Exp. n</b>                | 1 | 2 | 4 | 256 |

| Test settings |                  |
|---------------|------------------|
| Tolerance n   | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Math block Average.

| Test results          |   |   |   |     |
|-----------------------|---|---|---|-----|
| Time step             | 1 | 2 | 3 | 4   |
| Mask parameters       |   |   |   |     |
| n                     | 1 | 2 | 4 | 256 |
| ts_fact               | 1 | 1 | 1 | 1   |
| Controller parameters |   |   |   |     |
| n                     | 1 | 2 | 4 | 256 |
| Exp. n                | 1 | 2 | 4 | 256 |

| Test settings |                  |
|---------------|------------------|
| Tolerance n   | $\pm 0,0000e+00$ |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 5899 |
| Max CPU cycles  | 5924 |
| Avg CPU cycles  | 5913 |

## Block: Cos

---



Cosine computation of input value.


| Inports  |                  |
|----------|------------------|
| In       | Input u          |
| Outports |                  |
| Out      | Result of cos(u) |

### Description:

Calculation:

$$\text{Out} = \cos(\text{In})$$

Error for 16 Bit Fixed Point Implementation:



### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | int8 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: Cos FiP16 CPU TMS320F28335****Date of Test** 2026-06-19**Target controller** TMS320F28335**Test case: Inport test****OK**

Inport test for Math block Cos.

| Test results          |        |        |        |        |     |        |
|-----------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133    |
| <b>CPU cycles</b>     | 76     | 76     | 76     | 76     | ... | 76     |
| <i>Inputs</i>         |        |        |        |        |     |        |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767  |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1      |
| <i>Outputs</i>        |        |        |        |        |     |        |
| <b>Out</b>            | -1     | -0.999 | -0.995 | -0.99  | ... | -1     |
| <b>Exp. Out</b>       | -1     | -0.999 | -0.995 | -0.99  | ... | -1     |
| <b>Out (DSP)</b>      | -32767 | -32730 | -32618 | -32433 | ... | -32767 |
| <b>Exp. Out (DSP)</b> | -32768 | -32731 | -32620 | -32434 | ... | -32768 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,2207\text{e-}04$ ( $\pm 4$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 76 |
| Max CPU cycles  | 76 |
| Avg CPU cycles  | 76 |



**Verification: Cos FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Cos.

| Test results          |        |        |        |        |     |        |
|-----------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133    |
| <b>CPU cycles</b>     | 59     | 59     | 59     | 59     | ... | 59     |
| <i>Inputs</i>         |        |        |        |        |     |        |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767  |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1      |
| <i>Outputs</i>        |        |        |        |        |     |        |
| <b>Out</b>            | -1     | -0.999 | -0.995 | -0.99  | ... | -1     |
| <b>Exp. Out</b>       | -1     | -0.999 | -0.995 | -0.99  | ... | -1     |
| <b>Out (DSP)</b>      | -32767 | -32730 | -32618 | -32433 | ... | -32767 |
| <b>Exp. Out (DSP)</b> | -32768 | -32731 | -32620 | -32434 | ... | -32768 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,2207\text{e-}04$ ( $\pm 4$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 59 |
| Avg CPU cycles  | 59 |

**Verification: Cos FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Cos.

| Test results          |        |        |        |        |     |        |
|-----------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133    |
| <b>CPU cycles</b>     | 96     | 96     | 96     | 96     | ... | 96     |
| <i>Inputs</i>         |        |        |        |        |     |        |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767  |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1      |
| <i>Outputs</i>        |        |        |        |        |     |        |
| <b>Out</b>            | -1     | -0.999 | -0.995 | -0.99  | ... | -1     |
| <b>Exp. Out</b>       | -1     | -0.999 | -0.995 | -0.99  | ... | -1     |
| <b>Out (DSP)</b>      | -32767 | -32730 | -32618 | -32433 | ... | -32767 |
| <b>Exp. Out (DSP)</b> | -32768 | -32731 | -32620 | -32434 | ... | -32768 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,2207\text{e-}04$ ( $\pm 4$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 96  |
| Max CPU cycles  | 101 |
| Avg CPU cycles  | 97  |

**Verification: Cos FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Cos.

| Test results          |        |        |        |        |     |        |
|-----------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133    |
| <b>CPU cycles</b>     | 75     | 75     | 75     | 75     | ... | 75     |
| <i>Inputs</i>         |        |        |        |        |     |        |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767  |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1      |
| <i>Outputs</i>        |        |        |        |        |     |        |
| <b>Out</b>            | -1     | -0.999 | -0.995 | -0.99  | ... | -1     |
| <b>Exp. Out</b>       | -1     | -0.999 | -0.995 | -0.99  | ... | -1     |
| <b>Out (DSP)</b>      | -32767 | -32730 | -32618 | -32433 | ... | -32767 |
| <b>Exp. Out (DSP)</b> | -32768 | -32731 | -32620 | -32434 | ... | -32768 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,2207\text{e-}04$ ( $\pm 4$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 75 |
| Max CPU cycles  | 75 |
| Avg CPU cycles  | 75 |

**Verification: Cos FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Cos.

| Test results          |        |        |        |        |     |        |
|-----------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133    |
| <b>CPU cycles</b>     | 50     | 50     | 50     | 50     | ... | 50     |
| <i>Inputs</i>         |        |        |        |        |     |        |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767  |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1      |
| <i>Outputs</i>        |        |        |        |        |     |        |
| <b>Out</b>            | -1     | -0.999 | -0.995 | -0.99  | ... | -1     |
| <b>Exp. Out</b>       | -1     | -0.999 | -0.995 | -0.99  | ... | -1     |
| <b>Out (DSP)</b>      | -32767 | -32730 | -32618 | -32433 | ... | -32767 |
| <b>Exp. Out (DSP)</b> | -32768 | -32731 | -32620 | -32434 | ... | -32768 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,2207\text{e-}04$ ( $\pm 4$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 50 |
| Max CPU cycles  | 50 |
| Avg CPU cycles  | 50 |

**Verification: Cos FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Cos.

| Test results          |        |        |        |        |     |        |
|-----------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133    |
| <b>CPU cycles</b>     | 62     | 62     | 62     | 62     | ... | 62     |
| <i>Inputs</i>         |        |        |        |        |     |        |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767  |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1      |
| <i>Outputs</i>        |        |        |        |        |     |        |
| <b>Out</b>            | -1     | -0.999 | -0.995 | -0.99  | ... | -1     |
| <b>Exp. Out</b>       | -1     | -0.999 | -0.995 | -0.99  | ... | -1     |
| <b>Out (DSP)</b>      | -32767 | -32730 | -32618 | -32433 | ... | -32767 |
| <b>Exp. Out (DSP)</b> | -32768 | -32731 | -32620 | -32434 | ... | -32768 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,2207\text{e-}04$ ( $\pm 4$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 62 |
| Avg CPU cycles  | 62 |

**Verification: Cos FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Cos.

| Test results          |        |        |        |        |     |        |
|-----------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133    |
| <b>CPU cycles</b>     | 94     | 89     | 89     | 89     | ... | 89     |
| <i>Inputs</i>         |        |        |        |        |     |        |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767  |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1      |
| <i>Outputs</i>        |        |        |        |        |     |        |
| <b>Out</b>            | -1     | -0.999 | -0.995 | -0.99  | ... | -1     |
| <b>Exp. Out</b>       | -1     | -0.999 | -0.995 | -0.99  | ... | -1     |
| <b>Out (DSP)</b>      | -32767 | -32730 | -32618 | -32433 | ... | -32767 |
| <b>Exp. Out (DSP)</b> | -32768 | -32731 | -32620 | -32434 | ... | -32768 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,2207e-04$ ( $\pm 4$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 89 |
| Max CPU cycles  | 94 |
| Avg CPU cycles  | 89 |

**Verification: Cos FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Cos.

| Test results          |        |        |        |        |     |        |
|-----------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133    |
| <b>CPU cycles</b>     | 64     | 64     | 64     | 64     | ... | 64     |
| <i>Inputs</i>         |        |        |        |        |     |        |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767  |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1      |
| <i>Outputs</i>        |        |        |        |        |     |        |
| <b>Out</b>            | -1     | -0.999 | -0.995 | -0.99  | ... | -1     |
| <b>Exp. Out</b>       | -1     | -0.999 | -0.995 | -0.99  | ... | -1     |
| <b>Out (DSP)</b>      | -32767 | -32730 | -32618 | -32433 | ... | -32767 |
| <b>Exp. Out (DSP)</b> | -32768 | -32731 | -32620 | -32434 | ... | -32768 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,2207\text{e-}04$ ( $\pm 4$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 64 |
| Max CPU cycles  | 69 |
| Avg CPU cycles  | 64 |

**Verification: Cos FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Cos.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>      | 1           | 2           | ... | 133         |
| <b>CPU cycles</b>     | 88          | 88          | ... | 88          |
| <i>Inputs</i>         |             |             |     |             |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647  |
| <b>In</b>             | -1          | -0.985      | ... | 1           |
| <i>Outputs</i>        |             |             |     |             |
| <b>Out</b>            | -1          | -0.999      | ... | -1          |
| <b>Exp. Out</b>       | -1          | -0.999      | ... | -1          |
| <b>Out (DSP)</b>      | -2147483647 | -2145014483 | ... | -2147483647 |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2145051277 | ... | -2147483648 |

| Test settings |                                             |
|---------------|---------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}05$ ( $\pm 150000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 88 |
| Max CPU cycles  | 88 |
| Avg CPU cycles  | 88 |



**Verification: Cos FIP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Cos.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>      | 1           | 2           | ... | 133         |
| <b>CPU cycles</b>     | 53          | 53          | ... | 53          |
| <i>Inputs</i>         |             |             |     |             |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647  |
| <b>In</b>             | -1          | -0.985      | ... | 1           |
| <i>Outputs</i>        |             |             |     |             |
| <b>Out</b>            | -1          | -0.999      | ... | -1          |
| <b>Exp. Out</b>       | -1          | -0.999      | ... | -1          |
| <b>Out (DSP)</b>      | -2147483647 | -2145014483 | ... | -2147483647 |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2145051277 | ... | -2147483648 |

| Test settings |                                             |
|---------------|---------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}05$ ( $\pm 150000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 53 |
| Max CPU cycles  | 53 |
| Avg CPU cycles  | 53 |

**Verification: Cos FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Cos.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>      | 1           | 2           | ... | 133         |
| <b>CPU cycles</b>     | 91          | 91          | ... | 91          |
| <i>Inputs</i>         |             |             |     |             |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647  |
| <b>In</b>             | -1          | -0.985      | ... | 1           |
| <i>Outputs</i>        |             |             |     |             |
| <b>Out</b>            | -1          | -0.999      | ... | -1          |
| <b>Exp. Out</b>       | -1          | -0.999      | ... | -1          |
| <b>Out (DSP)</b>      | -2147483647 | -2145014483 | ... | -2147483647 |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2145051277 | ... | -2147483648 |

| Test settings |                                             |
|---------------|---------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}05$ ( $\pm 150000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 91 |
| Max CPU cycles  | 96 |
| Avg CPU cycles  | 93 |

**Verification: Cos FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Cos.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>      | 1           | 2           | ... | 133         |
| <b>CPU cycles</b>     | 148         | 148         | ... | 148         |
| <i>Inputs</i>         |             |             |     |             |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647  |
| <b>In</b>             | -1          | -0.985      | ... | 1           |
| <i>Outputs</i>        |             |             |     |             |
| <b>Out</b>            | -1          | -0.999      | ... | -1          |
| <b>Exp. Out</b>       | -1          | -0.999      | ... | -1          |
| <b>Out (DSP)</b>      | -2147483647 | -2145014483 | ... | -2147483647 |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2145051277 | ... | -2147483648 |

| Test settings |                                             |
|---------------|---------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}05$ ( $\pm 150000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 148 |
| Max CPU cycles  | 148 |
| Avg CPU cycles  | 148 |

**Verification: Cos FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Cos.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>      | 1           | 2           | ... | 133         |
| <b>CPU cycles</b>     | 52          | 53          | ... | 52          |
| <i>Inputs</i>         |             |             |     |             |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647  |
| <b>In</b>             | -1          | -0.985      | ... | 1           |
| <i>Outputs</i>        |             |             |     |             |
| <b>Out</b>            | -1          | -0.999      | ... | -1          |
| <b>Exp. Out</b>       | -1          | -0.999      | ... | -1          |
| <b>Out (DSP)</b>      | -2147483647 | -2145014483 | ... | -2147483647 |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2145051277 | ... | -2147483648 |

| Test settings |                                             |
|---------------|---------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}05$ ( $\pm 150000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 52 |
| Max CPU cycles  | 53 |
| Avg CPU cycles  | 52 |

**Verification: Cos FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Cos.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>      | 1           | 2           | ... | 133         |
| <b>CPU cycles</b>     | 204         | 211         | ... | 204         |
| <i>Inputs</i>         |             |             |     |             |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647  |
| <b>In</b>             | -1          | -0.985      | ... | 1           |
| <i>Outputs</i>        |             |             |     |             |
| <b>Out</b>            | -1          | -0.999      | ... | -1          |
| <b>Exp. Out</b>       | -1          | -0.999      | ... | -1          |
| <b>Out (DSP)</b>      | -2147483647 | -2145014483 | ... | -2147483647 |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2145051277 | ... | -2147483648 |

| Test settings |                                             |
|---------------|---------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}05$ ( $\pm 150000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 204 |
| Max CPU cycles  | 211 |
| Avg CPU cycles  | 207 |

**Verification: Cos FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Cos.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>      | 1           | 2           | ... | 133         |
| <b>CPU cycles</b>     | 106         | 100         | ... | 100         |
| <i>Inputs</i>         |             |             |     |             |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647  |
| <b>In</b>             | -1          | -0.985      | ... | 1           |
| <i>Outputs</i>        |             |             |     |             |
| <b>Out</b>            | -1          | -0.999      | ... | -1          |
| <b>Exp. Out</b>       | -1          | -0.999      | ... | -1          |
| <b>Out (DSP)</b>      | -2147483647 | -2145014483 | ... | -2147483647 |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2145051277 | ... | -2147483648 |

| Test settings |                                             |
|---------------|---------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}05$ ( $\pm 150000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 100 |
| Max CPU cycles  | 106 |
| Avg CPU cycles  | 100 |

**Verification: Cos FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Cos.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>      | 1           | 2           | ... | 133         |
| <b>CPU cycles</b>     | 74          | 74          | ... | 74          |
| <i>Inputs</i>         |             |             |     |             |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647  |
| <b>In</b>             | -1          | -0.985      | ... | 1           |
| <i>Outputs</i>        |             |             |     |             |
| <b>Out</b>            | -1          | -0.999      | ... | -1          |
| <b>Exp. Out</b>       | -1          | -0.999      | ... | -1          |
| <b>Out (DSP)</b>      | -2147483647 | -2145014483 | ... | -2147483647 |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2145051277 | ... | -2147483648 |

| Test settings |                                             |
|---------------|---------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}05$ ( $\pm 150000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 74 |
| Max CPU cycles  | 77 |
| Avg CPU cycles  | 74 |

**Verification: Cos Float32 CPU TMS320F28335****Date of Test** 2026-06-19**Target controller** TMS320F28335**Test case: Inport test****OK**

Inport test for Math block Cos.

| Test results          |        |        |     |       |
|-----------------------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | ... | 133   |
| <b>CPU cycles</b>     | 234    | 227    | ... | 234   |
| <i>Inputs</i>         |        |        |     |       |
| <b>In (DSP)</b>       | -3.142 | -3.094 | ... | 3.142 |
| <b>In</b>             | -3.142 | -3.094 | ... | 3.142 |
| <i>Outputs</i>        |        |        |     |       |
| <b>Out</b>            | -1     | -0.999 | ... | -1    |
| <b>Exp. Out</b>       | -1     | -0.999 | ... | -1    |
| <b>Out (DSP)</b>      | -1     | -0.999 | ... | -1    |
| <b>Exp. Out (DSP)</b> | -1     | -0.999 | ... | -1    |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,3970e-07$ ( $\pm 300$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 95  |
| Max CPU cycles  | 234 |
| Avg CPU cycles  | 226 |



**Verification: Cos Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Cos.

| Test results          |        |        |     |       |
|-----------------------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | ... | 133   |
| <b>CPU cycles</b>     | 119    | 119    | ... | 119   |
| <i>Inputs</i>         |        |        |     |       |
| <b>In (DSP)</b>       | -3.142 | -3.094 | ... | 3.142 |
| <b>In</b>             | -3.142 | -3.094 | ... | 3.142 |
| <i>Outputs</i>        |        |        |     |       |
| <b>Out</b>            | -1     | -0.999 | ... | -1    |
| <b>Exp. Out</b>       | -1     | -0.999 | ... | -1    |
| <b>Out (DSP)</b>      | -1     | -0.999 | ... | -1    |
| <b>Exp. Out (DSP)</b> | -1     | -0.999 | ... | -1    |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 1,3970\text{e-}07$ ( $\pm 300$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 53  |
| Max CPU cycles  | 119 |
| Avg CPU cycles  | 118 |

**Verification: Cos Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Cos.

| Test results          |        |        |     |       |
|-----------------------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | ... | 133   |
| <b>CPU cycles</b>     | 518    | 473    | ... | 510   |
| <i>Inputs</i>         |        |        |     |       |
| <b>In (DSP)</b>       | -3.142 | -3.094 | ... | 3.142 |
| <b>In</b>             | -3.142 | -3.094 | ... | 3.142 |
| <i>Outputs</i>        |        |        |     |       |
| <b>Out</b>            | -1     | -0.999 | ... | -1    |
| <b>Exp. Out</b>       | -1     | -0.999 | ... | -1    |
| <b>Out (DSP)</b>      | -1     | -0.999 | ... | -1    |
| <b>Exp. Out (DSP)</b> | -1     | -0.999 | ... | -1    |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,3970e-07$ ( $\pm 300$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 144 |
| Max CPU cycles  | 518 |
| Avg CPU cycles  | 362 |

**Verification: Cos Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Cos.

| Test results          |        |        |     |       |
|-----------------------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | ... | 133   |
| <b>CPU cycles</b>     | 5454   | 4578   | ... | 5439  |
| <i>Inputs</i>         |        |        |     |       |
| <b>In (DSP)</b>       | -3.142 | -3.094 | ... | 3.142 |
| <b>In</b>             | -3.142 | -3.094 | ... | 3.142 |
| <i>Outputs</i>        |        |        |     |       |
| <b>Out</b>            | -1     | -0.999 | ... | -1    |
| <b>Exp. Out</b>       | -1     | -0.999 | ... | -1    |
| <b>Out (DSP)</b>      | -1     | -0.999 | ... | -1    |
| <b>Exp. Out (DSP)</b> | -1     | -0.999 | ... | -1    |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,3970e-07$ ( $\pm 300$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 154  |
| Max CPU cycles  | 5454 |
| Avg CPU cycles  | 3818 |

**Verification: Cos Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Cos.

| Test results          |        |        |     |       |
|-----------------------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | ... | 133   |
| <b>CPU cycles</b>     | 435    | 266    | ... | 435   |
| <i>Inputs</i>         |        |        |     |       |
| <b>In (DSP)</b>       | -3.142 | -3.094 | ... | 3.142 |
| <b>In</b>             | -3.142 | -3.094 | ... | 3.142 |
| <i>Outputs</i>        |        |        |     |       |
| <b>Out</b>            | -1     | -0.999 | ... | -1    |
| <b>Exp. Out</b>       | -1     | -0.999 | ... | -1    |
| <b>Out (DSP)</b>      | -1     | -0.999 | ... | -1    |
| <b>Exp. Out (DSP)</b> | -1     | -0.999 | ... | -1    |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,3970e-07$ ( $\pm 300$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 140 |
| Max CPU cycles  | 435 |
| Avg CPU cycles  | 214 |

**Verification: Cos Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Cos.

| Test results          |        |        |     |       |
|-----------------------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | ... | 133   |
| <b>CPU cycles</b>     | 3796   | 3833   | ... | 3796  |
| <i>Inputs</i>         |        |        |     |       |
| <b>In (DSP)</b>       | -3.142 | -3.094 | ... | 3.142 |
| <b>In</b>             | -3.142 | -3.094 | ... | 3.142 |
| <i>Outputs</i>        |        |        |     |       |
| <b>Out</b>            | -1     | -0.999 | ... | -1    |
| <b>Exp. Out</b>       | -1     | -0.999 | ... | -1    |
| <b>Out (DSP)</b>      | -1     | -0.999 | ... | -1    |
| <b>Exp. Out (DSP)</b> | -1     | -0.999 | ... | -1    |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 1,3970\text{e-}07$ ( $\pm 300$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 107  |
| Max CPU cycles  | 4226 |
| Avg CPU cycles  | 3884 |

**Verification: Cos Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Cos.

| Test results          |        |        |     |       |
|-----------------------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | ... | 133   |
| <b>CPU cycles</b>     | 435    | 338    | ... | 381   |
| <i>Inputs</i>         |        |        |     |       |
| <b>In (DSP)</b>       | -3.142 | -3.094 | ... | 3.142 |
| <b>In</b>             | -3.142 | -3.094 | ... | 3.142 |
| <i>Outputs</i>        |        |        |     |       |
| <b>Out</b>            | -1     | -0.999 | ... | -1    |
| <b>Exp. Out</b>       | -1     | -0.999 | ... | -1    |
| <b>Out (DSP)</b>      | -1     | -0.999 | ... | -1    |
| <b>Exp. Out (DSP)</b> | -1     | -0.999 | ... | -1    |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,3970e-07$ ( $\pm 300$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 131 |
| Max CPU cycles  | 435 |
| Avg CPU cycles  | 245 |

**Verification: Cos Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Cos.

| Test results          |        |        |     |       |
|-----------------------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | ... | 133   |
| <b>CPU cycles</b>     | 143    | 138    | ... | 143   |
| <i>Inputs</i>         |        |        |     |       |
| <b>In (DSP)</b>       | -3.142 | -3.094 | ... | 3.142 |
| <b>In</b>             | -3.142 | -3.094 | ... | 3.142 |
| <i>Outputs</i>        |        |        |     |       |
| <b>Out</b>            | -1     | -0.999 | ... | -1    |
| <b>Exp. Out</b>       | -1     | -0.999 | ... | -1    |
| <b>Out (DSP)</b>      | -1     | -0.999 | ... | -1    |
| <b>Exp. Out (DSP)</b> | -1     | -0.999 | ... | -1    |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,3970e-07$ ( $\pm 300$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 82  |
| Max CPU cycles  | 143 |
| Avg CPU cycles  | 137 |

## Block: Div

---



Division of input Num by input Den.

| Inports |                       |
|---------|-----------------------|
| Num     | Dividend (Numerator)  |
| Den     | Divisor (Denominator) |

| Outports |          |
|----------|----------|
| Out      | Quotient |

### Description:

Calculation:

$$\text{Out} = \begin{cases} 0 & \text{Num} = 0, \text{Den} = 0 \\ \max & \text{Num} > 0, \text{Den} = 0 \\ \min & \text{Num} < 0, \text{Den} = 0 \\ \frac{\text{Num}}{\text{Den}} & \text{otherwise} \end{cases}$$

**Note:** *maxVal* and *minVal* refer to the maximum/minimum representable value of the implementation.

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| Num               | int8 |
| Den               | int8 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |



### Implementation: FiP16

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| Num               | int16 |
| Den               | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| Num               | int32 |
| Den               | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| Num               | float32 |
| Den               | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| Num               | float64 |
| Den               | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: Div FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Div.

| Test results          |     |       |       |        |     |       |
|-----------------------|-----|-------|-------|--------|-----|-------|
| <b>Time step</b>      | 1   | 2     | 3     | 4      | ... | 246   |
| <b>CPU cycles</b>     | 100 | 111   | 157   | 112    | ... | 111   |
| <i>Inputs</i>         |     |       |       |        |     |       |
| <b>Num (DSP)</b>      | 0   | 16384 | 0     | -32768 | ... | 32767 |
| <b>Den (DSP)</b>      | 0   | 0     | 16384 | 32767  | ... | 32767 |
| <b>Num</b>            | 0   | 0.5   | 0     | -1     | ... | 1     |
| <b>Den</b>            | 0   | 0     | 0.5   | 1      | ... | 1     |
| <i>Outputs</i>        |     |       |       |        |     |       |
| <b>Out</b>            | 0   | 1     | 0     | -1     | ... | 1     |
| <b>Exp. Out</b>       | 0   | 1     | 0     | -1     | ... | 1     |
| <b>Out (DSP)</b>      | 0   | 32767 | 0     | -32767 | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 0   | 32767 | 0     | -32768 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,2207e-04$ ( $\pm 4$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 100 |
| Max CPU cycles  | 157 |
| Avg CPU cycles  | 129 |

**Verification: Div FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Div.

| Test results          |    |       |       |        |     |       |
|-----------------------|----|-------|-------|--------|-----|-------|
| <b>Time step</b>      | 1  | 2     | 3     | 4      | ... | 246   |
| <b>CPU cycles</b>     | 59 | 65    | 57    | 63     | ... | 65    |
| <i>Inputs</i>         |    |       |       |        |     |       |
| <b>Num (DSP)</b>      | 0  | 16384 | 0     | -32768 | ... | 32767 |
| <b>Den (DSP)</b>      | 0  | 0     | 16384 | 32767  | ... | 32767 |
| <b>Num</b>            | 0  | 0.5   | 0     | -1     | ... | 1     |
| <b>Den</b>            | 0  | 0     | 0.5   | 1      | ... | 1     |
| <i>Outputs</i>        |    |       |       |        |     |       |
| <b>Out</b>            | 0  | 1     | 0     | -1     | ... | 1     |
| <b>Exp. Out</b>       | 0  | 1     | 0     | -1     | ... | 1     |
| <b>Out (DSP)</b>      | 0  | 32767 | 0     | -32767 | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 0  | 32767 | 0     | -32768 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,2207e-04$ ( $\pm 4$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 75 |
| Avg CPU cycles  | 65 |

**Verification: Div FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Div.

| Test results          |    |       |       |        |     |       |
|-----------------------|----|-------|-------|--------|-----|-------|
| <b>Time step</b>      | 1  | 2     | 3     | 4      | ... | 246   |
| <b>CPU cycles</b>     | 96 | 97    | 96    | 114    | ... | 97    |
| <i>Inputs</i>         |    |       |       |        |     |       |
| <b>Num (DSP)</b>      | 0  | 16384 | 0     | -32768 | ... | 32767 |
| <b>Den (DSP)</b>      | 0  | 0     | 16384 | 32767  | ... | 32767 |
| <b>Num</b>            | 0  | 0.5   | 0     | -1     | ... | 1     |
| <b>Den</b>            | 0  | 0     | 0.5   | 1      | ... | 1     |
| <i>Outputs</i>        |    |       |       |        |     |       |
| <b>Out</b>            | 0  | 1     | 0     | -1     | ... | 1     |
| <b>Exp. Out</b>       | 0  | 1     | 0     | -1     | ... | 1     |
| <b>Out (DSP)</b>      | 0  | 32767 | 0     | -32767 | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 0  | 32767 | 0     | -32768 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,2207e-04$ ( $\pm 4$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 87  |
| Max CPU cycles  | 146 |
| Avg CPU cycles  | 113 |

**Verification: Div FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Div.

| Test results          |    |       |       |        |     |       |
|-----------------------|----|-------|-------|--------|-----|-------|
| <b>Time step</b>      | 1  | 2     | 3     | 4      | ... | 246   |
| <b>CPU cycles</b>     | 88 | 106   | 103   | 113    | ... | 106   |
| <i>Inputs</i>         |    |       |       |        |     |       |
| <b>Num (DSP)</b>      | 0  | 16384 | 0     | -32768 | ... | 32767 |
| <b>Den (DSP)</b>      | 0  | 0     | 16384 | 32767  | ... | 32767 |
| <b>Num</b>            | 0  | 0.5   | 0     | -1     | ... | 1     |
| <b>Den</b>            | 0  | 0     | 0.5   | 1      | ... | 1     |
| <i>Outputs</i>        |    |       |       |        |     |       |
| <b>Out</b>            | 0  | 1     | 0     | -1     | ... | 1     |
| <b>Exp. Out</b>       | 0  | 1     | 0     | -1     | ... | 1     |
| <b>Out (DSP)</b>      | 0  | 32767 | 0     | -32767 | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 0  | 32767 | 0     | -32768 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,2207e-04$ ( $\pm 4$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 88  |
| Max CPU cycles  | 280 |
| Avg CPU cycles  | 135 |

**Verification: Div FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Div.

| Test results          |    |       |       |        |     |       |
|-----------------------|----|-------|-------|--------|-----|-------|
| <b>Time step</b>      | 1  | 2     | 3     | 4      | ... | 246   |
| <b>CPU cycles</b>     | 46 | 50    | 56    | 51     | ... | 50    |
| <i>Inputs</i>         |    |       |       |        |     |       |
| <b>Num (DSP)</b>      | 0  | 16384 | 0     | -32768 | ... | 32767 |
| <b>Den (DSP)</b>      | 0  | 0     | 16384 | 32767  | ... | 32767 |
| <b>Num</b>            | 0  | 0.5   | 0     | -1     | ... | 1     |
| <b>Den</b>            | 0  | 0     | 0.5   | 1      | ... | 1     |
| <i>Outputs</i>        |    |       |       |        |     |       |
| <b>Out</b>            | 0  | 1     | 0     | -1     | ... | 1     |
| <b>Exp. Out</b>       | 0  | 1     | 0     | -1     | ... | 1     |
| <b>Out (DSP)</b>      | 0  | 32767 | 0     | -32767 | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 0  | 32767 | 0     | -32768 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,2207e-04$ ( $\pm 4$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 36 |
| Max CPU cycles  | 81 |
| Avg CPU cycles  | 56 |

**Verification: Div FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Div.

| Test results          |    |       |       |        |     |       |
|-----------------------|----|-------|-------|--------|-----|-------|
| <b>Time step</b>      | 1  | 2     | 3     | 4      | ... | 246   |
| <b>CPU cycles</b>     | 68 | 64    | 86    | 75     | ... | 64    |
| <i>Inputs</i>         |    |       |       |        |     |       |
| <b>Num (DSP)</b>      | 0  | 16384 | 0     | -32768 | ... | 32767 |
| <b>Den (DSP)</b>      | 0  | 0     | 16384 | 32767  | ... | 32767 |
| <b>Num</b>            | 0  | 0.5   | 0     | -1     | ... | 1     |
| <b>Den</b>            | 0  | 0     | 0.5   | 1      | ... | 1     |
| <i>Outputs</i>        |    |       |       |        |     |       |
| <b>Out</b>            | 0  | 1     | 0     | -1     | ... | 1     |
| <b>Exp. Out</b>       | 0  | 1     | 0     | -1     | ... | 1     |
| <b>Out (DSP)</b>      | 0  | 32767 | 0     | -32767 | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 0  | 32767 | 0     | -32768 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,2207e-04$ ( $\pm 4$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 64 |
| Max CPU cycles  | 91 |
| Avg CPU cycles  | 75 |



**Verification: Div FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Div.

| Test results          |     |       |       |        |     |       |
|-----------------------|-----|-------|-------|--------|-----|-------|
| <b>Time step</b>      | 1   | 2     | 3     | 4      | ... | 246   |
| <b>CPU cycles</b>     | 125 | 89    | 87    | 80     | ... | 89    |
| <i>Inputs</i>         |     |       |       |        |     |       |
| <b>Num (DSP)</b>      | 0   | 16384 | 0     | -32768 | ... | 32767 |
| <b>Den (DSP)</b>      | 0   | 0     | 16384 | 32767  | ... | 32767 |
| <b>Num</b>            | 0   | 0.5   | 0     | -1     | ... | 1     |
| <b>Den</b>            | 0   | 0     | 0.5   | 1      | ... | 1     |
| <i>Outputs</i>        |     |       |       |        |     |       |
| <b>Out</b>            | 0   | 1     | 0     | -1     | ... | 1     |
| <b>Exp. Out</b>       | 0   | 1     | 0     | -1     | ... | 1     |
| <b>Out (DSP)</b>      | 0   | 32767 | 0     | -32767 | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 0   | 32767 | 0     | -32768 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,2207e-04$ ( $\pm 4$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 76  |
| Max CPU cycles  | 125 |
| Avg CPU cycles  | 91  |

**Verification: Div FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Div.

| Test results          |     |       |       |        |     |       |
|-----------------------|-----|-------|-------|--------|-----|-------|
| <b>Time step</b>      | 1   | 2     | 3     | 4      | ... | 246   |
| <b>CPU cycles</b>     | 110 | 120   | 172   | 120    | ... | 120   |
| <i>Inputs</i>         |     |       |       |        |     |       |
| <b>Num (DSP)</b>      | 0   | 16384 | 0     | -32768 | ... | 32767 |
| <b>Den (DSP)</b>      | 0   | 0     | 16384 | 32767  | ... | 32767 |
| <b>Num</b>            | 0   | 0.5   | 0     | -1     | ... | 1     |
| <b>Den</b>            | 0   | 0     | 0.5   | 1      | ... | 1     |
| <i>Outputs</i>        |     |       |       |        |     |       |
| <b>Out</b>            | 0   | 1     | 0     | -1     | ... | 1     |
| <b>Exp. Out</b>       | 0   | 1     | 0     | -1     | ... | 1     |
| <b>Out (DSP)</b>      | 0   | 32767 | 0     | -32767 | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 0   | 32767 | 0     | -32768 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,2207e-04$ ( $\pm 4$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 110 |
| Max CPU cycles  | 173 |
| Avg CPU cycles  | 141 |

**Verification: Div FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Div.

| Test results          |     |            |     |            |
|-----------------------|-----|------------|-----|------------|
| <b>Time step</b>      | 1   | 2          | ... | 246        |
| <b>CPU cycles</b>     | 112 | 126        | ... | 126        |
| <i>Inputs</i>         |     |            |     |            |
| <b>Num (DSP)</b>      | 0   | 1073741824 | ... | 2147483647 |
| <b>Den (DSP)</b>      | 0   | 0          | ... | 2147483647 |
| <b>Num</b>            | 0   | 0.5        | ... | 1          |
| <b>Den</b>            | 0   | 0          | ... | 1          |
| <i>Outputs</i>        |     |            |     |            |
| <b>Out</b>            | 0   | 1          | ... | 1          |
| <b>Exp. Out</b>       | 0   | 1          | ... | 1          |
| <b>Out (DSP)</b>      | 0   | 2147483647 | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 0   | 2147483647 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,8626e-09$ ( $\pm 4$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 112 |
| Max CPU cycles  | 327 |
| Avg CPU cycles  | 180 |

**Verification: Div FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Div.

| Test results          |    |            |     |            |
|-----------------------|----|------------|-----|------------|
| <b>Time step</b>      | 1  | 2          | ... | 246        |
| <b>CPU cycles</b>     | 61 | 63         | ... | 63         |
| <i>Inputs</i>         |    |            |     |            |
| <b>Num (DSP)</b>      | 0  | 1073741824 | ... | 2147483647 |
| <b>Den (DSP)</b>      | 0  | 0          | ... | 2147483647 |
| <b>Num</b>            | 0  | 0.5        | ... | 1          |
| <b>Den</b>            | 0  | 0          | ... | 1          |
| <i>Outputs</i>        |    |            |     |            |
| <b>Out</b>            | 0  | 1          | ... | 1          |
| <b>Exp. Out</b>       | 0  | 1          | ... | 1          |
| <b>Out (DSP)</b>      | 0  | 2147483647 | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 0  | 2147483647 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,8626e-09$ ( $\pm 4$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 61  |
| Max CPU cycles  | 583 |
| Avg CPU cycles  | 188 |

**Verification: Div FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Div.

| Test results          |     |            |     |            |
|-----------------------|-----|------------|-----|------------|
| <b>Time step</b>      | 1   | 2          | ... | 246        |
| <b>CPU cycles</b>     | 105 | 109        | ... | 109        |
| <i>Inputs</i>         |     |            |     |            |
| <b>Num (DSP)</b>      | 0   | 1073741824 | ... | 2147483647 |
| <b>Den (DSP)</b>      | 0   | 0          | ... | 2147483647 |
| <b>Num</b>            | 0   | 0.5        | ... | 1          |
| <b>Den</b>            | 0   | 0          | ... | 1          |
| <i>Outputs</i>        |     |            |     |            |
| <b>Out</b>            | 0   | 1          | ... | 1          |
| <b>Exp. Out</b>       | 0   | 1          | ... | 1          |
| <b>Out (DSP)</b>      | 0   | 2147483647 | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 0   | 2147483647 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,8626e-09$ ( $\pm 4$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 100 |
| Max CPU cycles  | 325 |
| Avg CPU cycles  | 184 |

**Verification: Div FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Div.

| Test results          |    |            |     |            |
|-----------------------|----|------------|-----|------------|
| <b>Time step</b>      | 1  | 2          | ... | 246        |
| <b>CPU cycles</b>     | 84 | 95         | ... | 95         |
| <i>Inputs</i>         |    |            |     |            |
| <b>Num (DSP)</b>      | 0  | 1073741824 | ... | 2147483647 |
| <b>Den (DSP)</b>      | 0  | 0          | ... | 2147483647 |
| <b>Num</b>            | 0  | 0.5        | ... | 1          |
| <b>Den</b>            | 0  | 0          | ... | 1          |
| <i>Outputs</i>        |    |            |     |            |
| <b>Out</b>            | 0  | 1          | ... | 1          |
| <b>Exp. Out</b>       | 0  | 1          | ... | 1          |
| <b>Out (DSP)</b>      | 0  | 2147483647 | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 0  | 2147483647 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,8626e-09$ ( $\pm 4$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 84  |
| Max CPU cycles  | 989 |
| Avg CPU cycles  | 316 |

**Verification: Div FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Div.

| Test results          |    |            |     |            |
|-----------------------|----|------------|-----|------------|
| <b>Time step</b>      | 1  | 2          | ... | 246        |
| <b>CPU cycles</b>     | 46 | 52         | ... | 52         |
| <i>Inputs</i>         |    |            |     |            |
| <b>Num (DSP)</b>      | 0  | 1073741824 | ... | 2147483647 |
| <b>Den (DSP)</b>      | 0  | 0          | ... | 2147483647 |
| <b>Num</b>            | 0  | 0.5        | ... | 1          |
| <b>Den</b>            | 0  | 0          | ... | 1          |
| <i>Outputs</i>        |    |            |     |            |
| <b>Out</b>            | 0  | 1          | ... | 1          |
| <b>Exp. Out</b>       | 0  | 1          | ... | 1          |
| <b>Out (DSP)</b>      | 0  | 2147483647 | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 0  | 2147483647 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,8626e-09$ ( $\pm 4$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 37  |
| Max CPU cycles  | 194 |
| Avg CPU cycles  | 90  |

**Verification: Div FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Div.

| Test results          |    |            |     |            |
|-----------------------|----|------------|-----|------------|
| <b>Time step</b>      | 1  | 2          | ... | 246        |
| <b>CPU cycles</b>     | 82 | 81         | ... | 81         |
| <i>Inputs</i>         |    |            |     |            |
| <b>Num (DSP)</b>      | 0  | 1073741824 | ... | 2147483647 |
| <b>Den (DSP)</b>      | 0  | 0          | ... | 2147483647 |
| <b>Num</b>            | 0  | 0.5        | ... | 1          |
| <b>Den</b>            | 0  | 0          | ... | 1          |
| <i>Outputs</i>        |    |            |     |            |
| <b>Out</b>            | 0  | 1          | ... | 1          |
| <b>Exp. Out</b>       | 0  | 1          | ... | 1          |
| <b>Out (DSP)</b>      | 0  | 2147483647 | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 0  | 2147483647 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,8626e-09$ ( $\pm 4$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 81   |
| Max CPU cycles  | 9822 |
| Avg CPU cycles  | 3490 |



**Verification: Div FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Div.

| Test results          |    |            |     |            |
|-----------------------|----|------------|-----|------------|
| <b>Time step</b>      | 1  | 2          | ... | 246        |
| <b>CPU cycles</b>     | 99 | 81         | ... | 81         |
| <i>Inputs</i>         |    |            |     |            |
| <b>Num (DSP)</b>      | 0  | 1073741824 | ... | 2147483647 |
| <b>Den (DSP)</b>      | 0  | 0          | ... | 2147483647 |
| <b>Num</b>            | 0  | 0.5        | ... | 1          |
| <b>Den</b>            | 0  | 0          | ... | 1          |
| <i>Outputs</i>        |    |            |     |            |
| <b>Out</b>            | 0  | 1          | ... | 1          |
| <b>Exp. Out</b>       | 0  | 1          | ... | 1          |
| <b>Out (DSP)</b>      | 0  | 2147483647 | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 0  | 2147483647 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,8626e-09$ ( $\pm 4$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 71  |
| Max CPU cycles  | 264 |
| Avg CPU cycles  | 141 |

**Verification: Div FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Div.

| Test results          |     |            |     |            |
|-----------------------|-----|------------|-----|------------|
| <b>Time step</b>      | 1   | 2          | ... | 246        |
| <b>CPU cycles</b>     | 127 | 147        | ... | 147        |
| <i>Inputs</i>         |     |            |     |            |
| <b>Num (DSP)</b>      | 0   | 1073741824 | ... | 2147483647 |
| <b>Den (DSP)</b>      | 0   | 0          | ... | 2147483647 |
| <b>Num</b>            | 0   | 0.5        | ... | 1          |
| <b>Den</b>            | 0   | 0          | ... | 1          |
| <i>Outputs</i>        |     |            |     |            |
| <b>Out</b>            | 0   | 1          | ... | 1          |
| <b>Exp. Out</b>       | 0   | 1          | ... | 1          |
| <b>Out (DSP)</b>      | 0   | 2147483647 | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 0   | 2147483647 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 1,8626e-09$ ( $\pm 4$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 127 |
| Max CPU cycles  | 307 |
| Avg CPU cycles  | 190 |

### Verification: Div Float32 CPU TMS320F28335

|                     |            |
|---------------------|------------|
| <b>Date of Test</b> | 2026-06-19 |
|---------------------|------------|

**Target controller** TMS320F28335

OK

Inport test for Math block Div.

[illegible]

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 1,3970\text{e-}07$ ( $\pm 300$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 83  |
| Max CPU cycles  | 328 |
| Avg CPU cycles  | 289 |

## Verification: Div Float32 CPU TM4C123GH6

|              |            |
|--------------|------------|
| Date of Test | 2026-06-19 |
|--------------|------------|

**Target controller**      TM4C123GH6

**Test case: Inport test** OK

OK

Inport test for Math block Div.

[illegible]

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 1,3970\text{e-}07$ ( $\pm 300$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 43 |
| Max CPU cycles  | 55 |
| Avg CPU cycles  | 54 |

### Verification: Div Float32 CPU STM32G474RE

**Date of Test** 2026-06-19

**Target controller** STM32G474RE

OK

Inport test for Math block Div.

[illegible]

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 1,3970\text{e-}07$ ( $\pm 300$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 77 |
| Max CPU cycles  | 98 |
| Avg CPU cycles  | 91 |

### Verification: Div Float32 CPU STM32F072RB

|                   |             |
|-------------------|-------------|
| Date of Test      | 2026-06-19  |
| Target controller | STM32F072RB |

**Test case: Inport test** OK

OK

Inport test for Math block Div.

[illegible]

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 1,3970\text{e-}07$ ( $\pm 300$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 218 |
| Max CPU cycles  | 757 |
| Avg CPU cycles  | 608 |

### Verification: Div Float32 CPU PIC32MX170F256

|                     |            |
|---------------------|------------|
| <b>Date of Test</b> | 2026-06-19 |
|---------------------|------------|

**Target controller** PIC32MX170F256

**Test case: Inport test** OK

OK

Inport test for Math block Div.

[illegible]

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 1,3970\text{e-}07$ ( $\pm 300$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 91  |
| Max CPU cycles  | 228 |
| Avg CPU cycles  | 198 |

## Verification: Div Float32 CPU dsPIC33EP256MC502

|                          |                   |
|--------------------------|-------------------|
| <b>Date of Test</b>      | 2026-06-19        |
| <b>Target controller</b> | dsPIC33EP256MC502 |

### Test case: Inport test

OK

Inport test for Math block Div.

[illegible]

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 1,3970\text{e-}07$ ( $\pm 300$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 254 |
| Max CPU cycles  | 658 |
| Avg CPU cycles  | 553 |



**Verification: Div Float32 CPU XMC4800-F144K2048**

|                   |                   |
|-------------------|-------------------|
| Date of Test      | 2026-06-19        |
| Target controller | XMC4800-F144K2048 |

**Test case: Inport test** OK

OK

Inport test for Math block Div.

[illegible]

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 1,3970\text{e-}07$ ( $\pm 300$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 72 |
| Max CPU cycles  | 87 |
| Avg CPU cycles  | 81 |

## Verification: Div Float32 CPU TMS320F28379D

|                     |            |
|---------------------|------------|
| <b>Date of Test</b> | 2026-06-22 |
|---------------------|------------|

**Target controller** TMS320F28379D

**Test case: Inport test** OK

OK

Inport test for Math block Div.

[illegible]

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,3970e-07$ ( $\pm 300$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 87  |
| Max CPU cycles  | 306 |
| Avg CPU cycles  | 268 |

## Block: Exp



Computation of the exponential of the input.

| Inports  |                  |
|----------|------------------|
| In       | Input u          |
| Outports |                  |
| Out      | Result of exp(u) |

### Description:


Calculation Floating Point Implementation:

$$\text{Out} = e^{\text{In}}$$

Calculation Fixed Point Implementation:

$$\text{Out} = \begin{cases} e^{\text{In}} & \text{In} \leq 0 \\ 1 & \text{In} > 0 \end{cases}$$

Error for 16 Bit Fixed Point Implementation:



### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | int8 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

---

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

---

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

## Implementation: Float64

---

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: Exp FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Exp.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 85     | 85     | 85     | 85     | ... | 59    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 0.368  | 0.374  | 0.379  | 0.385  | ... | 1     |
| <b>Exp. Out</b>       | 0.368  | 0.373  | 0.379  | 0.385  | ... | 1     |
| <b>Out (DSP)</b>      | 12055  | 12239  | 12425  | 12615  | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 12055  | 12239  | 12426  | 12615  | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 85 |
| Avg CPU cycles  | 72 |

**Verification: Exp FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Exp.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 57     | 57     | 57     | 57     | ... | 41    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 0.368  | 0.374  | 0.379  | 0.385  | ... | 1     |
| <b>Exp. Out</b>       | 0.368  | 0.373  | 0.379  | 0.385  | ... | 1     |
| <b>Out (DSP)</b>      | 12055  | 12239  | 12425  | 12615  | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 12055  | 12239  | 12426  | 12615  | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 41 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 49 |

**Verification: Exp FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Exp.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 92     | 92     | 97     | 92     | ... | 66    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 0.368  | 0.374  | 0.379  | 0.385  | ... | 1     |
| <b>Exp. Out</b>       | 0.368  | 0.373  | 0.379  | 0.385  | ... | 1     |
| <b>Out (DSP)</b>      | 12055  | 12239  | 12425  | 12615  | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 12055  | 12239  | 12426  | 12615  | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 66 |
| Max CPU cycles  | 97 |
| Avg CPU cycles  | 79 |



**Verification: Exp FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Exp.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 84     | 84     | 84     | 84     | ... | 58    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 0.368  | 0.374  | 0.379  | 0.385  | ... | 1     |
| <b>Exp. Out</b>       | 0.368  | 0.373  | 0.379  | 0.385  | ... | 1     |
| <b>Out (DSP)</b>      | 12055  | 12239  | 12425  | 12615  | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 12055  | 12239  | 12426  | 12615  | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 58 |
| Max CPU cycles  | 84 |
| Avg CPU cycles  | 71 |

**Verification: Exp FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Exp.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 52     | 52     | 52     | 52     | ... | 30    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 0.368  | 0.374  | 0.379  | 0.385  | ... | 1     |
| <b>Exp. Out</b>       | 0.368  | 0.373  | 0.379  | 0.385  | ... | 1     |
| <b>Out (DSP)</b>      | 12055  | 12239  | 12425  | 12615  | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 12055  | 12239  | 12426  | 12615  | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 30 |
| Max CPU cycles  | 52 |
| Avg CPU cycles  | 41 |

**Verification: Exp FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Exp.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 67     | 67     | 67     | 67     | ... | 40    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 0.368  | 0.374  | 0.379  | 0.385  | ... | 1     |
| <b>Exp. Out</b>       | 0.368  | 0.373  | 0.379  | 0.385  | ... | 1     |
| <b>Out (DSP)</b>      | 12055  | 12239  | 12425  | 12615  | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 12055  | 12239  | 12426  | 12615  | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 40 |
| Max CPU cycles  | 67 |
| Avg CPU cycles  | 53 |

**Verification: Exp FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Exp.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 101    | 94     | 94     | 94     | ... | 59    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 0.368  | 0.374  | 0.379  | 0.385  | ... | 1     |
| <b>Exp. Out</b>       | 0.368  | 0.373  | 0.379  | 0.385  | ... | 1     |
| <b>Out (DSP)</b>      | 12055  | 12239  | 12425  | 12615  | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 12055  | 12239  | 12426  | 12615  | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 59  |
| Max CPU cycles  | 101 |
| Avg CPU cycles  | 76  |

**Verification: Exp FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Exp.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 78     | 78     | 78     | 78     | ... | 58    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 0.368  | 0.374  | 0.379  | 0.385  | ... | 1     |
| <b>Exp. Out</b>       | 0.368  | 0.373  | 0.379  | 0.385  | ... | 1     |
| <b>Out (DSP)</b>      | 12055  | 12239  | 12425  | 12615  | ... | 32767 |
| <b>Exp. Out (DSP)</b> | 12055  | 12239  | 12426  | 12615  | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 58 |
| Max CPU cycles  | 81 |
| Avg CPU cycles  | 68 |

**Verification: Exp FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Exp.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 97          | 97          | ... | 61         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 0.368       | 0.373       | ... | 1          |
| <b>Exp. Out</b>       | 0.368       | 0.373       | ... | 1          |
| <b>Out (DSP)</b>      | 790015084   | 802077541   | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 790015084   | 802076151   | ... | 2147483647 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 7,4506e-06$ ( $\pm 16000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 61 |
| Max CPU cycles  | 97 |
| Avg CPU cycles  | 79 |

**Verification: Exp FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Exp.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 55          | 55          | ... | 39         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 0.368       | 0.373       | ... | 1          |
| <b>Exp. Out</b>       | 0.368       | 0.373       | ... | 1          |
| <b>Out (DSP)</b>      | 790015084   | 802077541   | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 790015084   | 802076151   | ... | 2147483647 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 7,4506e-06$ ( $\pm 16000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 39 |
| Max CPU cycles  | 55 |
| Avg CPU cycles  | 47 |

**Verification: Exp FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Exp.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 101         | 96          | ... | 61         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 0.368       | 0.373       | ... | 1          |
| <b>Exp. Out</b>       | 0.368       | 0.373       | ... | 1          |
| <b>Out (DSP)</b>      | 790015084   | 802077541   | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 790015084   | 802076151   | ... | 2147483647 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 7,4506e-06$ ( $\pm 16000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 61  |
| Max CPU cycles  | 101 |
| Avg CPU cycles  | 79  |



**Verification: Exp FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Exp.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 155         | 155         | ... | 62         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 0.368       | 0.373       | ... | 1          |
| <b>Exp. Out</b>       | 0.368       | 0.373       | ... | 1          |
| <b>Out (DSP)</b>      | 790015084   | 802077541   | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 790015084   | 802076151   | ... | 2147483647 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 7,4506e-06$ ( $\pm 16000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 62  |
| Max CPU cycles  | 155 |
| Avg CPU cycles  | 108 |

**Verification: Exp FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Exp.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 53          | 54          | ... | 31         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 0.368       | 0.373       | ... | 1          |
| <b>Exp. Out</b>       | 0.368       | 0.373       | ... | 1          |
| <b>Out (DSP)</b>      | 790015084   | 802077541   | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 790015084   | 802076151   | ... | 2147483647 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 7,4506e-06$ ( $\pm 16000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 54 |
| Avg CPU cycles  | 42 |

**Verification: Exp FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Exp.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 207         | 207         | ... | 60         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 0.368       | 0.373       | ... | 1          |
| <b>Exp. Out</b>       | 0.368       | 0.373       | ... | 1          |
| <b>Out (DSP)</b>      | 790015084   | 802077541   | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 790015084   | 802076151   | ... | 2147483647 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 7,4506e-06$ ( $\pm 16000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 60  |
| Max CPU cycles  | 207 |
| Avg CPU cycles  | 134 |

**Verification: Exp FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Exp.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 111         | 101         | ... | 58         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 0.368       | 0.373       | ... | 1          |
| <b>Exp. Out</b>       | 0.368       | 0.373       | ... | 1          |
| <b>Out (DSP)</b>      | 790015084   | 802077541   | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 790015084   | 802076151   | ... | 2147483647 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 7,4506e-06$ ( $\pm 16000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 58  |
| Max CPU cycles  | 111 |
| Avg CPU cycles  | 79  |

**Verification: Exp FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Exp.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 94          | 91          | ... | 57         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 0.368       | 0.373       | ... | 1          |
| <b>Exp. Out</b>       | 0.368       | 0.373       | ... | 1          |
| <b>Out (DSP)</b>      | 790015084   | 802077541   | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | 790015084   | 802076151   | ... | 2147483647 |

| Test settings |                                     |
|---------------|-------------------------------------|
| Tolerance Out | $\pm 7,4506e-06$ ( $\pm 16000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 94 |
| Avg CPU cycles  | 74 |

**Verification: Exp Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Exp.

| Test results          |       |        |     |       |
|-----------------------|-------|--------|-----|-------|
| <b>Time step</b>      | 1     | 2      | ... | 133   |
| <b>CPU cycles</b>     | 615   | 615    | ... | 615   |
| <i>Inputs</i>         |       |        |     |       |
| <b>In (DSP)</b>       | -1    | -0.985 | ... | 1     |
| <b>In</b>             | -1    | -0.985 | ... | 1     |
| <i>Outputs</i>        |       |        |     |       |
| <b>Out</b>            | 0.368 | 0.373  | ... | 2.718 |
| <b>Exp. Out</b>       | 0.368 | 0.373  | ... | 2.718 |
| <b>Out (DSP)</b>      | 0.368 | 0.373  | ... | 2.718 |
| <b>Exp. Out (DSP)</b> | 0.368 | 0.373  | ... | 2.718 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 2,3283e-07$ ( $\pm 500$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 193 |
| Max CPU cycles  | 615 |
| Avg CPU cycles  | 582 |

**Verification: Exp Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Exp.

| Test results          |       |        |     |       |
|-----------------------|-------|--------|-----|-------|
| <b>Time step</b>      | 1     | 2      | ... | 133   |
| <b>CPU cycles</b>     | 165   | 165    | ... | 165   |
| <i>Inputs</i>         |       |        |     |       |
| <b>In (DSP)</b>       | -1    | -0.985 | ... | 1     |
| <b>In</b>             | -1    | -0.985 | ... | 1     |
| <i>Outputs</i>        |       |        |     |       |
| <b>Out</b>            | 0.368 | 0.373  | ... | 2.718 |
| <b>Exp. Out</b>       | 0.368 | 0.373  | ... | 2.718 |
| <b>Out (DSP)</b>      | 0.368 | 0.373  | ... | 2.718 |
| <b>Exp. Out (DSP)</b> | 0.368 | 0.373  | ... | 2.718 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 2,3283e-07$ ( $\pm 500$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 89  |
| Max CPU cycles  | 165 |
| Avg CPU cycles  | 155 |

**Verification: Exp Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Exp.

| Test results          |       |        |     |       |
|-----------------------|-------|--------|-----|-------|
| <b>Time step</b>      | 1     | 2      | ... | 133   |
| <b>CPU cycles</b>     | 398   | 398    | ... | 398   |
| <i>Inputs</i>         |       |        |     |       |
| <b>In (DSP)</b>       | -1    | -0.985 | ... | 1     |
| <b>In</b>             | -1    | -0.985 | ... | 1     |
| <i>Outputs</i>        |       |        |     |       |
| <b>Out</b>            | 0.368 | 0.373  | ... | 2.718 |
| <b>Exp. Out</b>       | 0.368 | 0.373  | ... | 2.718 |
| <b>Out (DSP)</b>      | 0.368 | 0.373  | ... | 2.718 |
| <b>Exp. Out (DSP)</b> | 0.368 | 0.373  | ... | 2.718 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 2,3283e-07$ ( $\pm 500$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 288 |
| Max CPU cycles  | 398 |
| Avg CPU cycles  | 385 |



**Verification: Exp Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Exp.

| Test results          |       |        |     |       |
|-----------------------|-------|--------|-----|-------|
| <b>Time step</b>      | 1     | 2      | ... | 133   |
| <b>CPU cycles</b>     | 3759  | 3824   | ... | 3762  |
| <i>Inputs</i>         |       |        |     |       |
| <b>In (DSP)</b>       | -1    | -0.985 | ... | 1     |
| <b>In</b>             | -1    | -0.985 | ... | 1     |
| <i>Outputs</i>        |       |        |     |       |
| <b>Out</b>            | 0.368 | 0.373  | ... | 2.718 |
| <b>Exp. Out</b>       | 0.368 | 0.373  | ... | 2.718 |
| <b>Out (DSP)</b>      | 0.368 | 0.373  | ... | 2.718 |
| <b>Exp. Out (DSP)</b> | 0.368 | 0.373  | ... | 2.718 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 2,3283e-07$ ( $\pm 500$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 613  |
| Max CPU cycles  | 3867 |
| Avg CPU cycles  | 3602 |

**Verification: Exp Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Exp.

| Test results          |       |        |     |       |
|-----------------------|-------|--------|-----|-------|
| <b>Time step</b>      | 1     | 2      | ... | 133   |
| <b>CPU cycles</b>     | 254   | 249    | ... | 252   |
| <i>Inputs</i>         |       |        |     |       |
| <b>In (DSP)</b>       | -1    | -0.985 | ... | 1     |
| <b>In</b>             | -1    | -0.985 | ... | 1     |
| <i>Outputs</i>        |       |        |     |       |
| <b>Out</b>            | 0.368 | 0.373  | ... | 2.718 |
| <b>Exp. Out</b>       | 0.368 | 0.373  | ... | 2.718 |
| <b>Out (DSP)</b>      | 0.368 | 0.373  | ... | 2.718 |
| <b>Exp. Out (DSP)</b> | 0.368 | 0.373  | ... | 2.718 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 2,3283e-07$ ( $\pm 500$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 114 |
| Max CPU cycles  | 257 |
| Avg CPU cycles  | 249 |

**Verification: Exp Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Exp.

| Test results          |       |        |     |       |
|-----------------------|-------|--------|-----|-------|
| <b>Time step</b>      | 1     | 2      | ... | 133   |
| <b>CPU cycles</b>     | 4035  | 3980   | ... | 4019  |
| <i>Inputs</i>         |       |        |     |       |
| <b>In (DSP)</b>       | -1    | -0.985 | ... | 1     |
| <b>In</b>             | -1    | -0.985 | ... | 1     |
| <i>Outputs</i>        |       |        |     |       |
| <b>Out</b>            | 0.368 | 0.373  | ... | 2.718 |
| <b>Exp. Out</b>       | 0.368 | 0.373  | ... | 2.718 |
| <b>Out (DSP)</b>      | 0.368 | 0.373  | ... | 2.718 |
| <b>Exp. Out (DSP)</b> | 0.368 | 0.373  | ... | 2.718 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 2,3283e-07$ ( $\pm 500$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 400  |
| Max CPU cycles  | 4430 |
| Avg CPU cycles  | 3816 |

**Verification: Exp Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Exp.

| Test results          |       |        |     |       |
|-----------------------|-------|--------|-----|-------|
| <b>Time step</b>      | 1     | 2      | ... | 133   |
| <b>CPU cycles</b>     | 460   | 345    | ... | 329   |
| <i>Inputs</i>         |       |        |     |       |
| <b>In (DSP)</b>       | -1    | -0.985 | ... | 1     |
| <b>In</b>             | -1    | -0.985 | ... | 1     |
| <i>Outputs</i>        |       |        |     |       |
| <b>Out</b>            | 0.368 | 0.373  | ... | 2.718 |
| <b>Exp. Out</b>       | 0.368 | 0.373  | ... | 2.718 |
| <b>Out (DSP)</b>      | 0.368 | 0.373  | ... | 2.718 |
| <b>Exp. Out (DSP)</b> | 0.368 | 0.373  | ... | 2.718 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 2,3283e-07$ ( $\pm 500$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 220 |
| Max CPU cycles  | 460 |
| Avg CPU cycles  | 324 |

**Verification: Exp Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Exp.

| Test results          |       |        |     |       |
|-----------------------|-------|--------|-----|-------|
| <b>Time step</b>      | 1     | 2      | ... | 133   |
| <b>CPU cycles</b>     | 474   | 474    | ... | 471   |
| <i>Inputs</i>         |       |        |     |       |
| <b>In (DSP)</b>       | -1    | -0.985 | ... | 1     |
| <b>In</b>             | -1    | -0.985 | ... | 1     |
| <i>Outputs</i>        |       |        |     |       |
| <b>Out</b>            | 0.368 | 0.373  | ... | 2.718 |
| <b>Exp. Out</b>       | 0.368 | 0.373  | ... | 2.718 |
| <b>Out (DSP)</b>      | 0.368 | 0.373  | ... | 2.718 |
| <b>Exp. Out (DSP)</b> | 0.368 | 0.373  | ... | 2.718 |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 2,3283e-07$ ( $\pm 500$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 139 |
| Max CPU cycles  | 474 |
| Avg CPU cycles  | 452 |

## Block: L2Norm

---



Calculation of L2-norm (euclidean norm).

| Inports |          |
|---------|----------|
| u1      | Input u1 |
| u2      | Input u2 |

| Outports |                             |
|----------|-----------------------------|
| Out      | Euclidean norm of u1 and u2 |

### Description:

Calculation:

$$\text{Out} = \|u\| = \sqrt{u_1^2 + u_2^2}$$

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| u1                | int8 |
| u2                | int8 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| u1                | int16 |
| u2                | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| u1                | int32 |
| u2                | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| u1                | float32 |
| u2                | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| u1                | float64 |
| u2                | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: L2Norm FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block L2Norm.

| Test results          |     |       |       |       |     |       |
|-----------------------|-----|-------|-------|-------|-----|-------|
| <b>Time step</b>      | 1   | 2     | 3     | 4     | ... | 94    |
| <b>CPU cycles</b>     | 105 | 105   | 105   | 102   | ... | 105   |
| <i>Inputs</i>         |     |       |       |       |     |       |
| <b>u1 (DSP)</b>       | 0   | 32767 | 0     | 32767 | ... | 26214 |
| <b>u2 (DSP)</b>       | 0   | 0     | 32767 | 32767 | ... | 6554  |
| <b>u1</b>             | 0   | 1     | 0     | 1     | ... | 0.8   |
| <b>u2</b>             | 0   | 0     | 1     | 1     | ... | 0.2   |
| <i>Outputs</i>        |     |       |       |       |     |       |
| <b>Out</b>            | 0   | 1     | 1     | 1     | ... | 0.825 |
| <b>Exp. Out</b>       | 0   | 1     | 1     | 1     | ... | 0.825 |
| <b>Out (DSP)</b>      | 0   | 32766 | 32766 | 32766 | ... | 27020 |
| <b>Exp. Out (DSP)</b> | 0   | 32767 | 32767 | 32767 | ... | 27021 |

| Test settings |                                         |
|---------------|-----------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}03$ ( $\pm 50$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 102 |
| Max CPU cycles  | 105 |
| Avg CPU cycles  | 104 |



**Verification: L2Norm FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block L2Norm.

| Test results          |    |       |       |       |     |       |
|-----------------------|----|-------|-------|-------|-----|-------|
| <b>Time step</b>      | 1  | 2     | 3     | 4     | ... | 94    |
| <b>CPU cycles</b>     | 69 | 69    | 69    | 65    | ... | 69    |
| <i>Inputs</i>         |    |       |       |       |     |       |
| <b>u1 (DSP)</b>       | 0  | 32767 | 0     | 32767 | ... | 26214 |
| <b>u2 (DSP)</b>       | 0  | 0     | 32767 | 32767 | ... | 6554  |
| <b>u1</b>             | 0  | 1     | 0     | 1     | ... | 0.8   |
| <b>u2</b>             | 0  | 0     | 1     | 1     | ... | 0.2   |
| <i>Outputs</i>        |    |       |       |       |     |       |
| <b>Out</b>            | 0  | 1     | 1     | 1     | ... | 0.825 |
| <b>Exp. Out</b>       | 0  | 1     | 1     | 1     | ... | 0.825 |
| <b>Out (DSP)</b>      | 0  | 32766 | 32766 | 32766 | ... | 27020 |
| <b>Exp. Out (DSP)</b> | 0  | 32767 | 32767 | 32767 | ... | 27021 |

| Test settings |                                         |
|---------------|-----------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}03$ ( $\pm 50$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 65 |
| Max CPU cycles  | 69 |
| Avg CPU cycles  | 68 |

**Verification: L2Norm FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block L2Norm.

| Test results          |     |       |       |       |     |       |
|-----------------------|-----|-------|-------|-------|-----|-------|
| <b>Time step</b>      | 1   | 2     | 3     | 4     | ... | 94    |
| <b>CPU cycles</b>     | 107 | 107   | 107   | 107   | ... | 107   |
| <i>Inputs</i>         |     |       |       |       |     |       |
| <b>u1 (DSP)</b>       | 0   | 32767 | 0     | 32767 | ... | 26214 |
| <b>u2 (DSP)</b>       | 0   | 0     | 32767 | 32767 | ... | 6554  |
| <b>u1</b>             | 0   | 1     | 0     | 1     | ... | 0.8   |
| <b>u2</b>             | 0   | 0     | 1     | 1     | ... | 0.2   |
| <i>Outputs</i>        |     |       |       |       |     |       |
| <b>Out</b>            | 0   | 1     | 1     | 1     | ... | 0.825 |
| <b>Exp. Out</b>       | 0   | 1     | 1     | 1     | ... | 0.825 |
| <b>Out (DSP)</b>      | 0   | 32766 | 32766 | 32766 | ... | 27020 |
| <b>Exp. Out (DSP)</b> | 0   | 32767 | 32767 | 32767 | ... | 27021 |

| Test settings |                                         |
|---------------|-----------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}03$ ( $\pm 50$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 107 |
| Max CPU cycles  | 112 |
| Avg CPU cycles  | 107 |

**Verification: L2Norm FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block L2Norm.

| Test results          |    |       |       |       |     |       |
|-----------------------|----|-------|-------|-------|-----|-------|
| <b>Time step</b>      | 1  | 2     | 3     | 4     | ... | 94    |
| <b>CPU cycles</b>     | 95 | 95    | 95    | 96    | ... | 95    |
| <i>Inputs</i>         |    |       |       |       |     |       |
| <b>u1 (DSP)</b>       | 0  | 32767 | 0     | 32767 | ... | 26214 |
| <b>u2 (DSP)</b>       | 0  | 0     | 32767 | 32767 | ... | 6554  |
| <b>u1</b>             | 0  | 1     | 0     | 1     | ... | 0.8   |
| <b>u2</b>             | 0  | 0     | 1     | 1     | ... | 0.2   |
| <i>Outputs</i>        |    |       |       |       |     |       |
| <b>Out</b>            | 0  | 1     | 1     | 1     | ... | 0.825 |
| <b>Exp. Out</b>       | 0  | 1     | 1     | 1     | ... | 0.825 |
| <b>Out (DSP)</b>      | 0  | 32766 | 32766 | 32766 | ... | 27020 |
| <b>Exp. Out (DSP)</b> | 0  | 32767 | 32767 | 32767 | ... | 27021 |

| Test settings |                                         |
|---------------|-----------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}03$ ( $\pm 50$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 94 |
| Max CPU cycles  | 96 |
| Avg CPU cycles  | 95 |

**Verification: L2Norm FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block L2Norm.

| Test results          |    |       |       |       |     |       |
|-----------------------|----|-------|-------|-------|-----|-------|
| <b>Time step</b>      | 1  | 2     | 3     | 4     | ... | 94    |
| <b>CPU cycles</b>     | 63 | 63    | 63    | 63    | ... | 63    |
| <i>Inputs</i>         |    |       |       |       |     |       |
| <b>u1 (DSP)</b>       | 0  | 32767 | 0     | 32767 | ... | 26214 |
| <b>u2 (DSP)</b>       | 0  | 0     | 32767 | 32767 | ... | 6554  |
| <b>u1</b>             | 0  | 1     | 0     | 1     | ... | 0.8   |
| <b>u2</b>             | 0  | 0     | 1     | 1     | ... | 0.2   |
| <i>Outputs</i>        |    |       |       |       |     |       |
| <b>Out</b>            | 0  | 1     | 1     | 1     | ... | 0.825 |
| <b>Exp. Out</b>       | 0  | 1     | 1     | 1     | ... | 0.825 |
| <b>Out (DSP)</b>      | 0  | 32766 | 32766 | 32766 | ... | 27020 |
| <b>Exp. Out (DSP)</b> | 0  | 32767 | 32767 | 32767 | ... | 27021 |

| Test settings |                                         |
|---------------|-----------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}03$ ( $\pm 50$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 63 |
| Max CPU cycles  | 63 |
| Avg CPU cycles  | 63 |

**Verification: L2Norm FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block L2Norm.

| Test results          |    |       |       |       |     |       |
|-----------------------|----|-------|-------|-------|-----|-------|
| <b>Time step</b>      | 1  | 2     | 3     | 4     | ... | 94    |
| <b>CPU cycles</b>     | 90 | 90    | 90    | 89    | ... | 90    |
| <i>Inputs</i>         |    |       |       |       |     |       |
| <b>u1 (DSP)</b>       | 0  | 32767 | 0     | 32767 | ... | 26214 |
| <b>u2 (DSP)</b>       | 0  | 0     | 32767 | 32767 | ... | 6554  |
| <b>u1</b>             | 0  | 1     | 0     | 1     | ... | 0.8   |
| <b>u2</b>             | 0  | 0     | 1     | 1     | ... | 0.2   |
| <i>Outputs</i>        |    |       |       |       |     |       |
| <b>Out</b>            | 0  | 1     | 1     | 1     | ... | 0.825 |
| <b>Exp. Out</b>       | 0  | 1     | 1     | 1     | ... | 0.825 |
| <b>Out (DSP)</b>      | 0  | 32766 | 32766 | 32766 | ... | 27020 |
| <b>Exp. Out (DSP)</b> | 0  | 32767 | 32767 | 32767 | ... | 27021 |

| Test settings |                                         |
|---------------|-----------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}03$ ( $\pm 50$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 89 |
| Max CPU cycles  | 90 |
| Avg CPU cycles  | 89 |

**Verification: L2Norm FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block L2Norm.

| Test results          |     |       |       |       |     |       |
|-----------------------|-----|-------|-------|-------|-----|-------|
| <b>Time step</b>      | 1   | 2     | 3     | 4     | ... | 94    |
| <b>CPU cycles</b>     | 119 | 102   | 102   | 102   | ... | 102   |
| <i>Inputs</i>         |     |       |       |       |     |       |
| <b>u1 (DSP)</b>       | 0   | 32767 | 0     | 32767 | ... | 26214 |
| <b>u2 (DSP)</b>       | 0   | 0     | 32767 | 32767 | ... | 6554  |
| <b>u1</b>             | 0   | 1     | 0     | 1     | ... | 0.8   |
| <b>u2</b>             | 0   | 0     | 1     | 1     | ... | 0.2   |
| <i>Outputs</i>        |     |       |       |       |     |       |
| <b>Out</b>            | 0   | 1     | 1     | 1     | ... | 0.825 |
| <b>Exp. Out</b>       | 0   | 1     | 1     | 1     | ... | 0.825 |
| <b>Out (DSP)</b>      | 0   | 32766 | 32766 | 32766 | ... | 27020 |
| <b>Exp. Out (DSP)</b> | 0   | 32767 | 32767 | 32767 | ... | 27021 |

| Test settings |                                         |
|---------------|-----------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}03$ ( $\pm 50$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 102 |
| Max CPU cycles  | 119 |
| Avg CPU cycles  | 102 |

**Verification: L2Norm FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block L2Norm.

| Test results          |     |       |       |       |     |       |
|-----------------------|-----|-------|-------|-------|-----|-------|
| <b>Time step</b>      | 1   | 2     | 3     | 4     | ... | 94    |
| <b>CPU cycles</b>     | 103 | 98    | 98    | 92    | ... | 98    |
| <i>Inputs</i>         |     |       |       |       |     |       |
| <b>u1 (DSP)</b>       | 0   | 32767 | 0     | 32767 | ... | 26214 |
| <b>u2 (DSP)</b>       | 0   | 0     | 32767 | 32767 | ... | 6554  |
| <b>u1</b>             | 0   | 1     | 0     | 1     | ... | 0.8   |
| <b>u2</b>             | 0   | 0     | 1     | 1     | ... | 0.2   |
| <i>Outputs</i>        |     |       |       |       |     |       |
| <b>Out</b>            | 0   | 1     | 1     | 1     | ... | 0.825 |
| <b>Exp. Out</b>       | 0   | 1     | 1     | 1     | ... | 0.825 |
| <b>Out (DSP)</b>      | 0   | 32766 | 32766 | 32766 | ... | 27020 |
| <b>Exp. Out (DSP)</b> | 0   | 32767 | 32767 | 32767 | ... | 27021 |

| Test settings |                                         |
|---------------|-----------------------------------------|
| Tolerance Out | $\pm 1,5259\text{e-}03$ ( $\pm 50$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 92  |
| Max CPU cycles  | 103 |
| Avg CPU cycles  | 97  |

**Verification: L2Norm FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block L2Norm.

| Test results          |     |            |     |            |
|-----------------------|-----|------------|-----|------------|
| <b>Time step</b>      | 1   | 2          | ... | 94         |
| <b>CPU cycles</b>     | 199 | 199        | ... | 199        |
| <i>Inputs</i>         |     |            |     |            |
| <b>u1 (DSP)</b>       | 0   | 2147483647 | ... | 1717986918 |
| <b>u2 (DSP)</b>       | 0   | 0          | ... | 429496730  |
| <b>u1</b>             | 0   | 1          | ... | 0.8        |
| <b>u2</b>             | 0   | 0          | ... | 0.2        |
| <i>Outputs</i>        |     |            |     |            |
| <b>Out</b>            | 0   | 1          | ... | 0.825      |
| <b>Exp. Out</b>       | 0   | 1          | ... | 0.825      |
| <b>Out (DSP)</b>      | 0   | 2147483645 | ... | 1770859265 |
| <b>Exp. Out (DSP)</b> | 0   | 2147483647 | ... | 1770860382 |

| Test settings |                                       |
|---------------|---------------------------------------|
| Tolerance Out | $\pm 1,8626e-03$ ( $\pm 4000000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 153 |
| Max CPU cycles  | 206 |
| Avg CPU cycles  | 188 |



**Verification: L2Norm FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block L2Norm.

| Test results          |    |            |     |            |
|-----------------------|----|------------|-----|------------|
| <b>Time step</b>      | 1  | 2          | ... | 94         |
| <b>CPU cycles</b>     | 81 | 81         | ... | 81         |
| <i>Inputs</i>         |    |            |     |            |
| <b>u1 (DSP)</b>       | 0  | 2147483647 | ... | 1717986918 |
| <b>u2 (DSP)</b>       | 0  | 0          | ... | 429496730  |
| <b>u1</b>             | 0  | 1          | ... | 0.8        |
| <b>u2</b>             | 0  | 0          | ... | 0.2        |
| <i>Outputs</i>        |    |            |     |            |
| <b>Out</b>            | 0  | 1          | ... | 0.825      |
| <b>Exp. Out</b>       | 0  | 1          | ... | 0.825      |
| <b>Out (DSP)</b>      | 0  | 2147483645 | ... | 1770859265 |
| <b>Exp. Out (DSP)</b> | 0  | 2147483647 | ... | 1770860382 |

| Test settings |                                       |
|---------------|---------------------------------------|
| Tolerance Out | $\pm 1,8626e-03$ ( $\pm 4000000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 75 |
| Max CPU cycles  | 85 |
| Avg CPU cycles  | 79 |

**Verification: L2Norm FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block L2Norm.

| Test results          |     |            |     |            |
|-----------------------|-----|------------|-----|------------|
| <b>Time step</b>      | 1   | 2          | ... | 94         |
| <b>CPU cycles</b>     | 126 | 131        | ... | 131        |
| <i>Inputs</i>         |     |            |     |            |
| <b>u1 (DSP)</b>       | 0   | 2147483647 | ... | 1717986918 |
| <b>u2 (DSP)</b>       | 0   | 0          | ... | 429496730  |
| <b>u1</b>             | 0   | 1          | ... | 0.8        |
| <b>u2</b>             | 0   | 0          | ... | 0.2        |
| <i>Outputs</i>        |     |            |     |            |
| <b>Out</b>            | 0   | 1          | ... | 0.825      |
| <b>Exp. Out</b>       | 0   | 1          | ... | 0.825      |
| <b>Out (DSP)</b>      | 0   | 2147483645 | ... | 1770859265 |
| <b>Exp. Out (DSP)</b> | 0   | 2147483647 | ... | 1770860382 |

| Test settings |                                       |
|---------------|---------------------------------------|
| Tolerance Out | $\pm 1,8626e-03$ ( $\pm 4000000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 126 |
| Max CPU cycles  | 131 |
| Avg CPU cycles  | 129 |

**Verification: L2Norm FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block L2Norm.

| Test results          |     |            |     |            |
|-----------------------|-----|------------|-----|------------|
| <b>Time step</b>      | 1   | 2          | ... | 94         |
| <b>CPU cycles</b>     | 326 | 326        | ... | 326        |
| <i>Inputs</i>         |     |            |     |            |
| <b>u1 (DSP)</b>       | 0   | 2147483647 | ... | 1717986918 |
| <b>u2 (DSP)</b>       | 0   | 0          | ... | 429496730  |
| <b>u1</b>             | 0   | 1          | ... | 0.8        |
| <b>u2</b>             | 0   | 0          | ... | 0.2        |
| <i>Outputs</i>        |     |            |     |            |
| <b>Out</b>            | 0   | 1          | ... | 0.825      |
| <b>Exp. Out</b>       | 0   | 1          | ... | 0.825      |
| <b>Out (DSP)</b>      | 0   | 2147483645 | ... | 1770859265 |
| <b>Exp. Out (DSP)</b> | 0   | 2147483647 | ... | 1770860382 |

| Test settings |                                       |
|---------------|---------------------------------------|
| Tolerance Out | $\pm 1,8626e-03$ ( $\pm 4000000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 326 |
| Max CPU cycles  | 330 |
| Avg CPU cycles  | 327 |

**Verification: L2Norm FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block L2Norm.

| Test results          |    |            |     |            |
|-----------------------|----|------------|-----|------------|
| <b>Time step</b>      | 1  | 2          | ... | 94         |
| <b>CPU cycles</b>     | 71 | 73         | ... | 73         |
| <i>Inputs</i>         |    |            |     |            |
| <b>u1 (DSP)</b>       | 0  | 2147483647 | ... | 1717986918 |
| <b>u2 (DSP)</b>       | 0  | 0          | ... | 429496730  |
| <b>u1</b>             | 0  | 1          | ... | 0.8        |
| <b>u2</b>             | 0  | 0          | ... | 0.2        |
| <i>Outputs</i>        |    |            |     |            |
| <b>Out</b>            | 0  | 1          | ... | 0.825      |
| <b>Exp. Out</b>       | 0  | 1          | ... | 0.825      |
| <b>Out (DSP)</b>      | 0  | 2147483645 | ... | 1770859265 |
| <b>Exp. Out (DSP)</b> | 0  | 2147483647 | ... | 1770860382 |

| Test settings |                                       |
|---------------|---------------------------------------|
| Tolerance Out | $\pm 1,8626e-03$ ( $\pm 4000000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 71 |
| Max CPU cycles  | 77 |
| Avg CPU cycles  | 73 |

**Verification: L2Norm FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block L2Norm.

| Test results          |     |            |     |            |
|-----------------------|-----|------------|-----|------------|
| <b>Time step</b>      | 1   | 2          | ... | 94         |
| <b>CPU cycles</b>     | 450 | 450        | ... | 450        |
| <i>Inputs</i>         |     |            |     |            |
| <b>u1 (DSP)</b>       | 0   | 2147483647 | ... | 1717986918 |
| <b>u2 (DSP)</b>       | 0   | 0          | ... | 429496730  |
| <b>u1</b>             | 0   | 1          | ... | 0.8        |
| <b>u2</b>             | 0   | 0          | ... | 0.2        |
| <i>Outputs</i>        |     |            |     |            |
| <b>Out</b>            | 0   | 1          | ... | 0.825      |
| <b>Exp. Out</b>       | 0   | 1          | ... | 0.825      |
| <b>Out (DSP)</b>      | 0   | 2147483645 | ... | 1770859265 |
| <b>Exp. Out (DSP)</b> | 0   | 2147483647 | ... | 1770860382 |

| Test settings |                                       |
|---------------|---------------------------------------|
| Tolerance Out | $\pm 1,8626e-03$ ( $\pm 4000000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 450 |
| Max CPU cycles  | 474 |
| Avg CPU cycles  | 458 |

**Verification: L2Norm FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block L2Norm.

| Test results          |     |            |     |            |
|-----------------------|-----|------------|-----|------------|
| <b>Time step</b>      | 1   | 2          | ... | 94         |
| <b>CPU cycles</b>     | 129 | 120        | ... | 120        |
| <i>Inputs</i>         |     |            |     |            |
| <b>u1 (DSP)</b>       | 0   | 2147483647 | ... | 1717986918 |
| <b>u2 (DSP)</b>       | 0   | 0          | ... | 429496730  |
| <b>u1</b>             | 0   | 1          | ... | 0.8        |
| <b>u2</b>             | 0   | 0          | ... | 0.2        |
| <i>Outputs</i>        |     |            |     |            |
| <b>Out</b>            | 0   | 1          | ... | 0.825      |
| <b>Exp. Out</b>       | 0   | 1          | ... | 0.825      |
| <b>Out (DSP)</b>      | 0   | 2147483645 | ... | 1770859265 |
| <b>Exp. Out (DSP)</b> | 0   | 2147483647 | ... | 1770860382 |

| Test settings |                                       |
|---------------|---------------------------------------|
| Tolerance Out | $\pm 1,8626e-03$ ( $\pm 4000000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 118 |
| Max CPU cycles  | 129 |
| Avg CPU cycles  | 118 |

**Verification: L2Norm FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block L2Norm.

| Test results          |     |            |     |            |
|-----------------------|-----|------------|-----|------------|
| <b>Time step</b>      | 1   | 2          | ... | 94         |
| <b>CPU cycles</b>     | 182 | 182        | ... | 182        |
| <i>Inputs</i>         |     |            |     |            |
| <b>u1 (DSP)</b>       | 0   | 2147483647 | ... | 1717986918 |
| <b>u2 (DSP)</b>       | 0   | 0          | ... | 429496730  |
| <b>u1</b>             | 0   | 1          | ... | 0.8        |
| <b>u2</b>             | 0   | 0          | ... | 0.2        |
| <i>Outputs</i>        |     |            |     |            |
| <b>Out</b>            | 0   | 1          | ... | 0.825      |
| <b>Exp. Out</b>       | 0   | 1          | ... | 0.825      |
| <b>Out (DSP)</b>      | 0   | 2147483645 | ... | 1770859265 |
| <b>Exp. Out (DSP)</b> | 0   | 2147483647 | ... | 1770860382 |

| Test settings |                                       |
|---------------|---------------------------------------|
| Tolerance Out | $\pm 1,8626e-03$ ( $\pm 4000000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 146 |
| Max CPU cycles  | 193 |
| Avg CPU cycles  | 174 |

**Verification: L2Norm Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block L2Norm.

| Test results          |     |      |     |        |
|-----------------------|-----|------|-----|--------|
| <b>Time step</b>      | 1   | 2    | ... | 94     |
| <b>CPU cycles</b>     | 112 | 180  | ... | 180    |
| <i>Inputs</i>         |     |      |     |        |
| <b>u1 (DSP)</b>       | 0   | 13.2 | ... | 10.56  |
| <b>u2 (DSP)</b>       | 0   | 0    | ... | 2.64   |
| <b>u1</b>             | 0   | 13.2 | ... | 10.56  |
| <b>u2</b>             | 0   | 0    | ... | 2.64   |
| <i>Outputs</i>        |     |      |     |        |
| <b>Out</b>            | 0   | 13.2 | ... | 10.885 |
| <b>Exp. Out</b>       | 0   | 13.2 | ... | 10.885 |
| <b>Out (DSP)</b>      | 0   | 13.2 | ... | 10.885 |
| <b>Exp. Out (DSP)</b> | 0   | 13.2 | ... | 10.885 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 2,3283e-06$ ( $\pm 5000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 112 |
| Max CPU cycles  | 180 |
| Avg CPU cycles  | 177 |



**Verification: L2Norm Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block L2Norm.

| Test results          |    |      |     |        |
|-----------------------|----|------|-----|--------|
| <b>Time step</b>      | 1  | 2    | ... | 94     |
| <b>CPU cycles</b>     | 63 | 63   | ... | 63     |
| <i>Inputs</i>         |    |      |     |        |
| <b>u1 (DSP)</b>       | 0  | 13.2 | ... | 10.56  |
| <b>u2 (DSP)</b>       | 0  | 0    | ... | 2.64   |
| <b>u1</b>             | 0  | 13.2 | ... | 10.56  |
| <b>u2</b>             | 0  | 0    | ... | 2.64   |
| <i>Outputs</i>        |    |      |     |        |
| <b>Out</b>            | 0  | 13.2 | ... | 10.885 |
| <b>Exp. Out</b>       | 0  | 13.2 | ... | 10.885 |
| <b>Out (DSP)</b>      | 0  | 13.2 | ... | 10.885 |
| <b>Exp. Out (DSP)</b> | 0  | 13.2 | ... | 10.885 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 2,3283e-06$ ( $\pm 5000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 63 |
| Max CPU cycles  | 63 |
| Avg CPU cycles  | 63 |

**Verification: L2Norm Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block L2Norm.

| Test results          |    |      |     |        |
|-----------------------|----|------|-----|--------|
| <b>Time step</b>      | 1  | 2    | ... | 94     |
| <b>CPU cycles</b>     | 88 | 88   | ... | 88     |
| <i>Inputs</i>         |    |      |     |        |
| <b>u1 (DSP)</b>       | 0  | 13.2 | ... | 10.56  |
| <b>u2 (DSP)</b>       | 0  | 0    | ... | 2.64   |
| <b>u1</b>             | 0  | 13.2 | ... | 10.56  |
| <b>u2</b>             | 0  | 0    | ... | 2.64   |
| <i>Outputs</i>        |    |      |     |        |
| <b>Out</b>            | 0  | 13.2 | ... | 10.885 |
| <b>Exp. Out</b>       | 0  | 13.2 | ... | 10.885 |
| <b>Out (DSP)</b>      | 0  | 13.2 | ... | 10.885 |
| <b>Exp. Out (DSP)</b> | 0  | 13.2 | ... | 10.885 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 2,3283e-06$ ( $\pm 5000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 88 |
| Max CPU cycles  | 88 |
| Avg CPU cycles  | 88 |

**Verification: L2Norm Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block L2Norm.

| Test results          |     |      |     |        |
|-----------------------|-----|------|-----|--------|
| <b>Time step</b>      | 1   | 2    | ... | 94     |
| <b>CPU cycles</b>     | 556 | 995  | ... | 1091   |
| <i>Inputs</i>         |     |      |     |        |
| <b>u1 (DSP)</b>       | 0   | 13.2 | ... | 10.56  |
| <b>u2 (DSP)</b>       | 0   | 0    | ... | 2.64   |
| <b>u1</b>             | 0   | 13.2 | ... | 10.56  |
| <b>u2</b>             | 0   | 0    | ... | 2.64   |
| <i>Outputs</i>        |     |      |     |        |
| <b>Out</b>            | 0   | 13.2 | ... | 10.885 |
| <b>Exp. Out</b>       | 0   | 13.2 | ... | 10.885 |
| <b>Out (DSP)</b>      | 0   | 13.2 | ... | 10.885 |
| <b>Exp. Out (DSP)</b> | 0   | 13.2 | ... | 10.885 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 2,3283e-06$ ( $\pm 5000$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 556  |
| Max CPU cycles  | 1120 |
| Avg CPU cycles  | 1052 |

**Verification: L2Norm Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block L2Norm.

| Test results          |     |      |     |        |
|-----------------------|-----|------|-----|--------|
| <b>Time step</b>      | 1   | 2    | ... | 94     |
| <b>CPU cycles</b>     | 207 | 438  | ... | 481    |
| <i>Inputs</i>         |     |      |     |        |
| <b>u1 (DSP)</b>       | 0   | 13.2 | ... | 10.56  |
| <b>u2 (DSP)</b>       | 0   | 0    | ... | 2.64   |
| <b>u1</b>             | 0   | 13.2 | ... | 10.56  |
| <b>u2</b>             | 0   | 0    | ... | 2.64   |
| <i>Outputs</i>        |     |      |     |        |
| <b>Out</b>            | 0   | 13.2 | ... | 10.885 |
| <b>Exp. Out</b>       | 0   | 13.2 | ... | 10.885 |
| <b>Out (DSP)</b>      | 0   | 13.2 | ... | 10.885 |
| <b>Exp. Out (DSP)</b> | 0   | 13.2 | ... | 10.885 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 2,3283e-06$ ( $\pm 5000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 207 |
| Max CPU cycles  | 513 |
| Avg CPU cycles  | 468 |

**Verification: L2Norm Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block L2Norm.

| Test results          |     |      |     |        |
|-----------------------|-----|------|-----|--------|
| <b>Time step</b>      | 1   | 2    | ... | 94     |
| <b>CPU cycles</b>     | 496 | 1012 | ... | 1147   |
| <i>Inputs</i>         |     |      |     |        |
| <b>u1 (DSP)</b>       | 0   | 13.2 | ... | 10.56  |
| <b>u2 (DSP)</b>       | 0   | 0    | ... | 2.64   |
| <b>u1</b>             | 0   | 13.2 | ... | 10.56  |
| <b>u2</b>             | 0   | 0    | ... | 2.64   |
| <i>Outputs</i>        |     |      |     |        |
| <b>Out</b>            | 0   | 13.2 | ... | 10.885 |
| <b>Exp. Out</b>       | 0   | 13.2 | ... | 10.885 |
| <b>Out (DSP)</b>      | 0   | 13.2 | ... | 10.885 |
| <b>Exp. Out (DSP)</b> | 0   | 13.2 | ... | 10.885 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 2,3283e-06$ ( $\pm 5000$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 496  |
| Max CPU cycles  | 1247 |
| Avg CPU cycles  | 1089 |

**Verification: L2Norm Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block L2Norm.

| Test results          |    |      |     |        |
|-----------------------|----|------|-----|--------|
| <b>Time step</b>      | 1  | 2    | ... | 94     |
| <b>CPU cycles</b>     | 89 | 78   | ... | 78     |
| <i>Inputs</i>         |    |      |     |        |
| <b>u1 (DSP)</b>       | 0  | 13.2 | ... | 10.56  |
| <b>u2 (DSP)</b>       | 0  | 0    | ... | 2.64   |
| <b>u1</b>             | 0  | 13.2 | ... | 10.56  |
| <b>u2</b>             | 0  | 0    | ... | 2.64   |
| <i>Outputs</i>        |    |      |     |        |
| <b>Out</b>            | 0  | 13.2 | ... | 10.885 |
| <b>Exp. Out</b>       | 0  | 13.2 | ... | 10.885 |
| <b>Out (DSP)</b>      | 0  | 13.2 | ... | 10.885 |
| <b>Exp. Out (DSP)</b> | 0  | 13.2 | ... | 10.885 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 2,3283e-06$ ( $\pm 5000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 78 |
| Max CPU cycles  | 89 |
| Avg CPU cycles  | 78 |

**Verification: L2Norm Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block L2Norm.

| Test results          |     |      |     |        |
|-----------------------|-----|------|-----|--------|
| <b>Time step</b>      | 1   | 2    | ... | 94     |
| <b>CPU cycles</b>     | 102 | 137  | ... | 137    |
| <i>Inputs</i>         |     |      |     |        |
| <b>u1 (DSP)</b>       | 0   | 13.2 | ... | 10.56  |
| <b>u2 (DSP)</b>       | 0   | 0    | ... | 2.64   |
| <b>u1</b>             | 0   | 13.2 | ... | 10.56  |
| <b>u2</b>             | 0   | 0    | ... | 2.64   |
| <i>Outputs</i>        |     |      |     |        |
| <b>Out</b>            | 0   | 13.2 | ... | 10.885 |
| <b>Exp. Out</b>       | 0   | 13.2 | ... | 10.885 |
| <b>Out (DSP)</b>      | 0   | 13.2 | ... | 10.885 |
| <b>Exp. Out (DSP)</b> | 0   | 13.2 | ... | 10.885 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 2,3283e-06$ ( $\pm 5000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 102 |
| Max CPU cycles  | 137 |
| Avg CPU cycles  | 135 |

## Block: Mult

---



Multiplication of input 1 with input 2.

| Inports |                |
|---------|----------------|
| In1     | Multiplicand 1 |
| In2     | Multiplicand 2 |

| Outports |         |
|----------|---------|
| Out      | Product |

### Description:

Calculation:

$$\text{Out} = \text{In}_1 \cdot \text{In}_2$$

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In1               | int8 |
| In2               | int8 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation



| Inports Data Type |       |
|-------------------|-------|
| In1               | int16 |
| In2               | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In1               | int32 |
| In2               | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In1               | float32 |
| In2               | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In1               | float64 |
| In2               | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: Mult FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Mult.

| Test results          |    |       |       |        |     |       |
|-----------------------|----|-------|-------|--------|-----|-------|
| <b>Time step</b>      | 1  | 2     | 3     | 4      | ... | 217   |
| <b>CPU cycles</b>     | 75 | 75    | 75    | 73     | ... | 75    |
| <i>Inputs</i>         |    |       |       |        |     |       |
| <b>In1 (DSP)</b>      | 0  | 16384 | 0     | -32768 | ... | 32767 |
| <b>In2 (DSP)</b>      | 0  | 0     | 16384 | 32767  | ... | 32767 |
| <b>In1</b>            | 0  | 0.5   | 0     | -1     | ... | 1     |
| <b>In2</b>            | 0  | 0     | 0.5   | 1      | ... | 1     |
| <i>Outputs</i>        |    |       |       |        |     |       |
| <b>Out</b>            | 0  | 0     | 0     | -1     | ... | 1     |
| <b>Exp. Out</b>       | 0  | 0     | 0     | -1     | ... | 1     |
| <b>Out (DSP)</b>      | 0  | 0     | 0     | -32767 | ... | 32766 |
| <b>Exp. Out (DSP)</b> | 0  | 0     | 0     | -32768 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 72 |
| Max CPU cycles  | 75 |
| Avg CPU cycles  | 74 |

**Verification: Mult FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Mult.

| Test results          |    |       |       |        |     |       |
|-----------------------|----|-------|-------|--------|-----|-------|
| <b>Time step</b>      | 1  | 2     | 3     | 4      | ... | 217   |
| <b>CPU cycles</b>     | 43 | 43    | 43    | 47     | ... | 43    |
| <i>Inputs</i>         |    |       |       |        |     |       |
| <b>In1 (DSP)</b>      | 0  | 16384 | 0     | -32768 | ... | 32767 |
| <b>In2 (DSP)</b>      | 0  | 0     | 16384 | 32767  | ... | 32767 |
| <b>In1</b>            | 0  | 0.5   | 0     | -1     | ... | 1     |
| <b>In2</b>            | 0  | 0     | 0.5   | 1      | ... | 1     |
| <i>Outputs</i>        |    |       |       |        |     |       |
| <b>Out</b>            | 0  | 0     | 0     | -1     | ... | 1     |
| <b>Exp. Out</b>       | 0  | 0     | 0     | -1     | ... | 1     |
| <b>Out (DSP)</b>      | 0  | 0     | 0     | -32767 | ... | 32766 |
| <b>Exp. Out (DSP)</b> | 0  | 0     | 0     | -32768 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 43 |
| Max CPU cycles  | 53 |
| Avg CPU cycles  | 46 |

**Verification: Mult FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Mult.

| Test results          |    |       |       |        |     |       |
|-----------------------|----|-------|-------|--------|-----|-------|
| <b>Time step</b>      | 1  | 2     | 3     | 4      | ... | 217   |
| <b>CPU cycles</b>     | 91 | 91    | 91    | 91     | ... | 91    |
| <i>Inputs</i>         |    |       |       |        |     |       |
| <b>In1 (DSP)</b>      | 0  | 16384 | 0     | -32768 | ... | 32767 |
| <b>In2 (DSP)</b>      | 0  | 0     | 16384 | 32767  | ... | 32767 |
| <b>In1</b>            | 0  | 0.5   | 0     | -1     | ... | 1     |
| <b>In2</b>            | 0  | 0     | 0.5   | 1      | ... | 1     |
| <i>Outputs</i>        |    |       |       |        |     |       |
| <b>Out</b>            | 0  | 0     | 0     | -1     | ... | 1     |
| <b>Exp. Out</b>       | 0  | 0     | 0     | -1     | ... | 1     |
| <b>Out (DSP)</b>      | 0  | 0     | 0     | -32767 | ... | 32766 |
| <b>Exp. Out (DSP)</b> | 0  | 0     | 0     | -32768 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 91 |
| Max CPU cycles  | 96 |
| Avg CPU cycles  | 92 |

**Verification: Mult FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Mult.

| Test results          |    |       |       |        |     |       |
|-----------------------|----|-------|-------|--------|-----|-------|
| <b>Time step</b>      | 1  | 2     | 3     | 4      | ... | 217   |
| <b>CPU cycles</b>     | 77 | 77    | 77    | 80     | ... | 77    |
| <i>Inputs</i>         |    |       |       |        |     |       |
| <b>In1 (DSP)</b>      | 0  | 16384 | 0     | -32768 | ... | 32767 |
| <b>In2 (DSP)</b>      | 0  | 0     | 16384 | 32767  | ... | 32767 |
| <b>In1</b>            | 0  | 0.5   | 0     | -1     | ... | 1     |
| <b>In2</b>            | 0  | 0     | 0.5   | 1      | ... | 1     |
| <i>Outputs</i>        |    |       |       |        |     |       |
| <b>Out</b>            | 0  | 0     | 0     | -1     | ... | 1     |
| <b>Exp. Out</b>       | 0  | 0     | 0     | -1     | ... | 1     |
| <b>Out (DSP)</b>      | 0  | 0     | 0     | -32767 | ... | 32766 |
| <b>Exp. Out (DSP)</b> | 0  | 0     | 0     | -32768 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 77 |
| Max CPU cycles  | 84 |
| Avg CPU cycles  | 79 |

**Verification: Mult FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Mult.

| Test results          |    |       |       |        |     |       |
|-----------------------|----|-------|-------|--------|-----|-------|
| <b>Time step</b>      | 1  | 2     | 3     | 4      | ... | 217   |
| <b>CPU cycles</b>     | 45 | 45    | 45    | 49     | ... | 45    |
| <i>Inputs</i>         |    |       |       |        |     |       |
| <b>In1 (DSP)</b>      | 0  | 16384 | 0     | -32768 | ... | 32767 |
| <b>In2 (DSP)</b>      | 0  | 0     | 16384 | 32767  | ... | 32767 |
| <b>In1</b>            | 0  | 0.5   | 0     | -1     | ... | 1     |
| <b>In2</b>            | 0  | 0     | 0.5   | 1      | ... | 1     |
| <i>Outputs</i>        |    |       |       |        |     |       |
| <b>Out</b>            | 0  | 0     | 0     | -1     | ... | 1     |
| <b>Exp. Out</b>       | 0  | 0     | 0     | -1     | ... | 1     |
| <b>Out (DSP)</b>      | 0  | 0     | 0     | -32767 | ... | 32766 |
| <b>Exp. Out (DSP)</b> | 0  | 0     | 0     | -32768 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 45 |
| Max CPU cycles  | 50 |
| Avg CPU cycles  | 46 |

**Verification: Mult FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Mult.

| Test results          |    |       |       |        |     |       |
|-----------------------|----|-------|-------|--------|-----|-------|
| <b>Time step</b>      | 1  | 2     | 3     | 4      | ... | 217   |
| <b>CPU cycles</b>     | 49 | 49    | 49    | 57     | ... | 49    |
| <i>Inputs</i>         |    |       |       |        |     |       |
| <b>In1 (DSP)</b>      | 0  | 16384 | 0     | -32768 | ... | 32767 |
| <b>In2 (DSP)</b>      | 0  | 0     | 16384 | 32767  | ... | 32767 |
| <b>In1</b>            | 0  | 0.5   | 0     | -1     | ... | 1     |
| <b>In2</b>            | 0  | 0     | 0.5   | 1      | ... | 1     |
| <i>Outputs</i>        |    |       |       |        |     |       |
| <b>Out</b>            | 0  | 0     | 0     | -1     | ... | 1     |
| <b>Exp. Out</b>       | 0  | 0     | 0     | -1     | ... | 1     |
| <b>Out (DSP)</b>      | 0  | 0     | 0     | -32767 | ... | 32766 |
| <b>Exp. Out (DSP)</b> | 0  | 0     | 0     | -32768 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 49 |
| Max CPU cycles  | 60 |
| Avg CPU cycles  | 52 |

**Verification: Mult FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Mult.

| Test results          |    |       |       |        |     |       |
|-----------------------|----|-------|-------|--------|-----|-------|
| <b>Time step</b>      | 1  | 2     | 3     | 4      | ... | 217   |
| <b>CPU cycles</b>     | 87 | 68    | 68    | 68     | ... | 68    |
| <i>Inputs</i>         |    |       |       |        |     |       |
| <b>In1 (DSP)</b>      | 0  | 16384 | 0     | -32768 | ... | 32767 |
| <b>In2 (DSP)</b>      | 0  | 0     | 16384 | 32767  | ... | 32767 |
| <b>In1</b>            | 0  | 0.5   | 0     | -1     | ... | 1     |
| <b>In2</b>            | 0  | 0     | 0.5   | 1      | ... | 1     |
| <i>Outputs</i>        |    |       |       |        |     |       |
| <b>Out</b>            | 0  | 0     | 0     | -1     | ... | 1     |
| <b>Exp. Out</b>       | 0  | 0     | 0     | -1     | ... | 1     |
| <b>Out (DSP)</b>      | 0  | 0     | 0     | -32767 | ... | 32766 |
| <b>Exp. Out (DSP)</b> | 0  | 0     | 0     | -32768 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 68 |
| Max CPU cycles  | 87 |
| Avg CPU cycles  | 70 |



**Verification: Mult FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Mult.

| Test results          |    |       |       |        |     |       |
|-----------------------|----|-------|-------|--------|-----|-------|
| <b>Time step</b>      | 1  | 2     | 3     | 4      | ... | 217   |
| <b>CPU cycles</b>     | 79 | 79    | 79    | 71     | ... | 79    |
| <i>Inputs</i>         |    |       |       |        |     |       |
| <b>In1 (DSP)</b>      | 0  | 16384 | 0     | -32768 | ... | 32767 |
| <b>In2 (DSP)</b>      | 0  | 0     | 16384 | 32767  | ... | 32767 |
| <b>In1</b>            | 0  | 0.5   | 0     | -1     | ... | 1     |
| <b>In2</b>            | 0  | 0     | 0.5   | 1      | ... | 1     |
| <i>Outputs</i>        |    |       |       |        |     |       |
| <b>Out</b>            | 0  | 0     | 0     | -1     | ... | 1     |
| <b>Exp. Out</b>       | 0  | 0     | 0     | -1     | ... | 1     |
| <b>Out (DSP)</b>      | 0  | 0     | 0     | -32767 | ... | 32766 |
| <b>Exp. Out (DSP)</b> | 0  | 0     | 0     | -32768 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 65 |
| Max CPU cycles  | 79 |
| Avg CPU cycles  | 74 |

**Verification: Mult FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Mult.

| Test results          |    |            |     |            |
|-----------------------|----|------------|-----|------------|
| <b>Time step</b>      | 1  | 2          | ... | 217        |
| <b>CPU cycles</b>     | 80 | 80         | ... | 80         |
| <i>Inputs</i>         |    |            |     |            |
| <b>In1 (DSP)</b>      | 0  | 1073741824 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 0  | 0          | ... | 2147483647 |
| <b>In1</b>            | 0  | 0.5        | ... | 1          |
| <b>In2</b>            | 0  | 0          | ... | 1          |
| <i>Outputs</i>        |    |            |     |            |
| <b>Out</b>            | 0  | 0          | ... | 1          |
| <b>Exp. Out</b>       | 0  | 0          | ... | 1          |
| <b>Out (DSP)</b>      | 0  | 0          | ... | 2147483646 |
| <b>Exp. Out (DSP)</b> | 0  | 0          | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 79 |
| Max CPU cycles  | 80 |
| Avg CPU cycles  | 79 |

**Verification: Mult FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Mult.

| Test results          |    |            |     |            |
|-----------------------|----|------------|-----|------------|
| <b>Time step</b>      | 1  | 2          | ... | 217        |
| <b>CPU cycles</b>     | 43 | 43         | ... | 43         |
| <i>Inputs</i>         |    |            |     |            |
| <b>In1 (DSP)</b>      | 0  | 1073741824 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 0  | 0          | ... | 2147483647 |
| <b>In1</b>            | 0  | 0.5        | ... | 1          |
| <b>In2</b>            | 0  | 0          | ... | 1          |
| <i>Outputs</i>        |    |            |     |            |
| <b>Out</b>            | 0  | 0          | ... | 1          |
| <b>Exp. Out</b>       | 0  | 0          | ... | 1          |
| <b>Out (DSP)</b>      | 0  | 0          | ... | 2147483646 |
| <b>Exp. Out (DSP)</b> | 0  | 0          | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 43 |
| Max CPU cycles  | 51 |
| Avg CPU cycles  | 45 |

**Verification: Mult FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Mult.

| Test results          |    |            |     |            |
|-----------------------|----|------------|-----|------------|
| <b>Time step</b>      | 1  | 2          | ... | 217        |
| <b>CPU cycles</b>     | 96 | 96         | ... | 96         |
| <i>Inputs</i>         |    |            |     |            |
| <b>In1 (DSP)</b>      | 0  | 1073741824 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 0  | 0          | ... | 2147483647 |
| <b>In1</b>            | 0  | 0.5        | ... | 1          |
| <b>In2</b>            | 0  | 0          | ... | 1          |
| <i>Outputs</i>        |    |            |     |            |
| <b>Out</b>            | 0  | 0          | ... | 1          |
| <b>Exp. Out</b>       | 0  | 0          | ... | 1          |
| <b>Out (DSP)</b>      | 0  | 0          | ... | 2147483646 |
| <b>Exp. Out (DSP)</b> | 0  | 0          | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 96  |
| Max CPU cycles  | 101 |
| Avg CPU cycles  | 97  |

**Verification: Mult FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Mult.

| Test results          |     |            |     |            |
|-----------------------|-----|------------|-----|------------|
| <b>Time step</b>      | 1   | 2          | ... | 217        |
| <b>CPU cycles</b>     | 142 | 142        | ... | 142        |
| <i>Inputs</i>         |     |            |     |            |
| <b>In1 (DSP)</b>      | 0   | 1073741824 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 0   | 0          | ... | 2147483647 |
| <b>In1</b>            | 0   | 0.5        | ... | 1          |
| <b>In2</b>            | 0   | 0          | ... | 1          |
| <i>Outputs</i>        |     |            |     |            |
| <b>Out</b>            | 0   | 0          | ... | 1          |
| <b>Exp. Out</b>       | 0   | 0          | ... | 1          |
| <b>Out (DSP)</b>      | 0   | 0          | ... | 2147483646 |
| <b>Exp. Out (DSP)</b> | 0   | 0          | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 142 |
| Max CPU cycles  | 157 |
| Avg CPU cycles  | 147 |

**Verification: Mult FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Mult.

| Test results          |    |            |     |            |
|-----------------------|----|------------|-----|------------|
| <b>Time step</b>      | 1  | 2          | ... | 217        |
| <b>CPU cycles</b>     | 54 | 54         | ... | 56         |
| <i>Inputs</i>         |    |            |     |            |
| <b>In1 (DSP)</b>      | 0  | 1073741824 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 0  | 0          | ... | 2147483647 |
| <b>In1</b>            | 0  | 0.5        | ... | 1          |
| <b>In2</b>            | 0  | 0          | ... | 1          |
| <i>Outputs</i>        |    |            |     |            |
| <b>Out</b>            | 0  | 0          | ... | 1          |
| <b>Exp. Out</b>       | 0  | 0          | ... | 1          |
| <b>Out (DSP)</b>      | 0  | 0          | ... | 2147483646 |
| <b>Exp. Out (DSP)</b> | 0  | 0          | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 54 |
| Max CPU cycles  | 63 |
| Avg CPU cycles  | 58 |

**Verification: Mult FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Mult.

| Test results          |     |            |     |            |
|-----------------------|-----|------------|-----|------------|
| <b>Time step</b>      | 1   | 2          | ... | 217        |
| <b>CPU cycles</b>     | 170 | 170        | ... | 170        |
| <i>Inputs</i>         |     |            |     |            |
| <b>In1 (DSP)</b>      | 0   | 1073741824 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 0   | 0          | ... | 2147483647 |
| <b>In1</b>            | 0   | 0.5        | ... | 1          |
| <b>In2</b>            | 0   | 0          | ... | 1          |
| <i>Outputs</i>        |     |            |     |            |
| <b>Out</b>            | 0   | 0          | ... | 1          |
| <b>Exp. Out</b>       | 0   | 0          | ... | 1          |
| <b>Out (DSP)</b>      | 0   | 0          | ... | 2147483646 |
| <b>Exp. Out (DSP)</b> | 0   | 0          | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 170 |
| Max CPU cycles  | 191 |
| Avg CPU cycles  | 180 |

**Verification: Mult FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Mult.

| Test results          |    |            |     |            |
|-----------------------|----|------------|-----|------------|
| <b>Time step</b>      | 1  | 2          | ... | 217        |
| <b>CPU cycles</b>     | 98 | 87         | ... | 87         |
| <i>Inputs</i>         |    |            |     |            |
| <b>In1 (DSP)</b>      | 0  | 1073741824 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 0  | 0          | ... | 2147483647 |
| <b>In1</b>            | 0  | 0.5        | ... | 1          |
| <b>In2</b>            | 0  | 0          | ... | 1          |
| <i>Outputs</i>        |    |            |     |            |
| <b>Out</b>            | 0  | 0          | ... | 1          |
| <b>Exp. Out</b>       | 0  | 0          | ... | 1          |
| <b>Out (DSP)</b>      | 0  | 0          | ... | 2147483646 |
| <b>Exp. Out (DSP)</b> | 0  | 0          | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 87  |
| Max CPU cycles  | 102 |
| Avg CPU cycles  | 92  |



**Verification: Mult FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Mult.

| Test results          |    |            |     |            |
|-----------------------|----|------------|-----|------------|
| <b>Time step</b>      | 1  | 2          | ... | 217        |
| <b>CPU cycles</b>     | 86 | 86         | ... | 86         |
| <i>Inputs</i>         |    |            |     |            |
| <b>In1 (DSP)</b>      | 0  | 1073741824 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 0  | 0          | ... | 2147483647 |
| <b>In1</b>            | 0  | 0.5        | ... | 1          |
| <b>In2</b>            | 0  | 0          | ... | 1          |
| <i>Outputs</i>        |    |            |     |            |
| <b>Out</b>            | 0  | 0          | ... | 1          |
| <b>Exp. Out</b>       | 0  | 0          | ... | 1          |
| <b>Out (DSP)</b>      | 0  | 0          | ... | 2147483646 |
| <b>Exp. Out (DSP)</b> | 0  | 0          | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 76 |
| Max CPU cycles  | 86 |
| Avg CPU cycles  | 82 |

**Verification: Mult Float32 CPU TMS320F28335****Date of Test** 2026-06-19**Target controller** TMS320F28335**Test case: Inport test****OK**

Inport test for Math block Mult.

| Test results          |    |     |     |     |
|-----------------------|----|-----|-----|-----|
| <b>Time step</b>      | 1  | 2   | ... | 217 |
| <b>CPU cycles</b>     | 53 | 53  | ... | 53  |
| <i>Inputs</i>         |    |     |     |     |
| <b>In1 (DSP)</b>      | 0  | 0.5 | ... | 3   |
| <b>In2 (DSP)</b>      | 0  | 0   | ... | 3   |
| <b>In1</b>            | 0  | 0.5 | ... | 3   |
| <b>In2</b>            | 0  | 0   | ... | 3   |
| <i>Outputs</i>        |    |     |     |     |
| <b>Out</b>            | 0  | 0   | ... | 9   |
| <b>Exp. Out</b>       | 0  | 0   | ... | 9   |
| <b>Out (DSP)</b>      | 0  | 0   | ... | 9   |
| <b>Exp. Out (DSP)</b> | 0  | 0   | ... | 9   |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance Out | $\pm 8,3819\text{e-}07$ ( $\pm 1800$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 53 |
| Max CPU cycles  | 53 |
| Avg CPU cycles  | 53 |

**Verification: Mult Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Mult.

| Test results          |    |     |     |     |
|-----------------------|----|-----|-----|-----|
| <b>Time step</b>      | 1  | 2   | ... | 217 |
| <b>CPU cycles</b>     | 29 | 29  | ... | 29  |
| <i>Inputs</i>         |    |     |     |     |
| <b>In1 (DSP)</b>      | 0  | 0.5 | ... | 3   |
| <b>In2 (DSP)</b>      | 0  | 0   | ... | 3   |
| <b>In1</b>            | 0  | 0.5 | ... | 3   |
| <b>In2</b>            | 0  | 0   | ... | 3   |
| <i>Outputs</i>        |    |     |     |     |
| <b>Out</b>            | 0  | 0   | ... | 9   |
| <b>Exp. Out</b>       | 0  | 0   | ... | 9   |
| <b>Out (DSP)</b>      | 0  | 0   | ... | 9   |
| <b>Exp. Out (DSP)</b> | 0  | 0   | ... | 9   |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance Out | $\pm 8,3819\text{e-}07$ ( $\pm 1800$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 29 |
| Avg CPU cycles  | 29 |

**Verification: Mult Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Mult.

| Test results          |    |     |     |     |
|-----------------------|----|-----|-----|-----|
| <b>Time step</b>      | 1  | 2   | ... | 217 |
| <b>CPU cycles</b>     | 66 | 66  | ... | 66  |
| <i>Inputs</i>         |    |     |     |     |
| <b>In1 (DSP)</b>      | 0  | 0.5 | ... | 3   |
| <b>In2 (DSP)</b>      | 0  | 0   | ... | 3   |
| <b>In1</b>            | 0  | 0.5 | ... | 3   |
| <b>In2</b>            | 0  | 0   | ... | 3   |
| <i>Outputs</i>        |    |     |     |     |
| <b>Out</b>            | 0  | 0   | ... | 9   |
| <b>Exp. Out</b>       | 0  | 0   | ... | 9   |
| <b>Out (DSP)</b>      | 0  | 0   | ... | 9   |
| <b>Exp. Out (DSP)</b> | 0  | 0   | ... | 9   |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance Out | $\pm 8,3819\text{e-}07$ ( $\pm 1800$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 66 |
| Max CPU cycles  | 66 |
| Avg CPU cycles  | 66 |

**Verification: Mult Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Mult.

| Test results          |     |     |     |     |
|-----------------------|-----|-----|-----|-----|
| <b>Time step</b>      | 1   | 2   | ... | 217 |
| <b>CPU cycles</b>     | 176 | 175 | ... | 285 |
| <i>Inputs</i>         |     |     |     |     |
| <b>In1 (DSP)</b>      | 0   | 0.5 | ... | 3   |
| <b>In2 (DSP)</b>      | 0   | 0   | ... | 3   |
| <b>In1</b>            | 0   | 0.5 | ... | 3   |
| <b>In2</b>            | 0   | 0   | ... | 3   |
| <i>Outputs</i>        |     |     |     |     |
| <b>Out</b>            | 0   | 0   | ... | 9   |
| <b>Exp. Out</b>       | 0   | 0   | ... | 9   |
| <b>Out (DSP)</b>      | 0   | 0   | ... | 9   |
| <b>Exp. Out (DSP)</b> | 0   | 0   | ... | 9   |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance Out | $\pm 8,3819\text{e-}07$ ( $\pm 1800$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 171 |
| Max CPU cycles  | 285 |
| Avg CPU cycles  | 227 |

**Verification: Mult Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Mult.

| Test results          |    |     |     |     |
|-----------------------|----|-----|-----|-----|
| <b>Time step</b>      | 1  | 2   | ... | 217 |
| <b>CPU cycles</b>     | 73 | 72  | ... | 89  |
| <i>Inputs</i>         |    |     |     |     |
| <b>In1 (DSP)</b>      | 0  | 0.5 | ... | 3   |
| <b>In2 (DSP)</b>      | 0  | 0   | ... | 3   |
| <b>In1</b>            | 0  | 0.5 | ... | 3   |
| <b>In2</b>            | 0  | 0   | ... | 3   |
| <i>Outputs</i>        |    |     |     |     |
| <b>Out</b>            | 0  | 0   | ... | 9   |
| <b>Exp. Out</b>       | 0  | 0   | ... | 9   |
| <b>Out (DSP)</b>      | 0  | 0   | ... | 9   |
| <b>Exp. Out (DSP)</b> | 0  | 0   | ... | 9   |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance Out | $\pm 8,3819\text{e-}07$ ( $\pm 1800$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 72 |
| Max CPU cycles  | 92 |
| Avg CPU cycles  | 90 |

**Verification: Mult Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Mult.

| Test results          |     |     |     |     |
|-----------------------|-----|-----|-----|-----|
| <b>Time step</b>      | 1   | 2   | ... | 217 |
| <b>CPU cycles</b>     | 149 | 147 | ... | 192 |
| <i>Inputs</i>         |     |     |     |     |
| <b>In1 (DSP)</b>      | 0   | 0.5 | ... | 3   |
| <b>In2 (DSP)</b>      | 0   | 0   | ... | 3   |
| <b>In1</b>            | 0   | 0.5 | ... | 3   |
| <b>In2</b>            | 0   | 0   | ... | 3   |
| <i>Outputs</i>        |     |     |     |     |
| <b>Out</b>            | 0   | 0   | ... | 9   |
| <b>Exp. Out</b>       | 0   | 0   | ... | 9   |
| <b>Out (DSP)</b>      | 0   | 0   | ... | 9   |
| <b>Exp. Out (DSP)</b> | 0   | 0   | ... | 9   |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance Out | $\pm 8,3819\text{e-}07$ ( $\pm 1800$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 147 |
| Max CPU cycles  | 195 |
| Avg CPU cycles  | 191 |

**Verification: Mult Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Mult.

| Test results          |    |     |     |     |
|-----------------------|----|-----|-----|-----|
| <b>Time step</b>      | 1  | 2   | ... | 217 |
| <b>CPU cycles</b>     | 57 | 57  | ... | 57  |
| <i>Inputs</i>         |    |     |     |     |
| <b>In1 (DSP)</b>      | 0  | 0.5 | ... | 3   |
| <b>In2 (DSP)</b>      | 0  | 0   | ... | 3   |
| <b>In1</b>            | 0  | 0.5 | ... | 3   |
| <b>In2</b>            | 0  | 0   | ... | 3   |
| <i>Outputs</i>        |    |     |     |     |
| <b>Out</b>            | 0  | 0   | ... | 9   |
| <b>Exp. Out</b>       | 0  | 0   | ... | 9   |
| <b>Out (DSP)</b>      | 0  | 0   | ... | 9   |
| <b>Exp. Out (DSP)</b> | 0  | 0   | ... | 9   |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance Out | $\pm 8,3819\text{e-}07$ ( $\pm 1800$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 57 |



**Verification: Mult Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Mult.

| Test results          |    |     |     |     |
|-----------------------|----|-----|-----|-----|
| <b>Time step</b>      | 1  | 2   | ... | 217 |
| <b>CPU cycles</b>     | 47 | 47  | ... | 47  |
| <i>Inputs</i>         |    |     |     |     |
| <b>In1 (DSP)</b>      | 0  | 0.5 | ... | 3   |
| <b>In2 (DSP)</b>      | 0  | 0   | ... | 3   |
| <b>In1</b>            | 0  | 0.5 | ... | 3   |
| <b>In2</b>            | 0  | 0   | ... | 3   |
| <i>Outputs</i>        |    |     |     |     |
| <b>Out</b>            | 0  | 0   | ... | 9   |
| <b>Exp. Out</b>       | 0  | 0   | ... | 9   |
| <b>Out (DSP)</b>      | 0  | 0   | ... | 9   |
| <b>Exp. Out (DSP)</b> | 0  | 0   | ... | 9   |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance Out | $\pm 8,3819\text{e-}07$ ( $\pm 1800$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 47 |
| Max CPU cycles  | 47 |
| Avg CPU cycles  | 47 |

## Block: Negation

---



Negation of input signal.

| Inports |       |
|---------|-------|
| In      | Input |

| Outports |                     |
|----------|---------------------|
| Out      | Negated input value |

### Description:

Calculation:

$$\text{Out} = -\text{In}$$

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | int8 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: Negation FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Negation.

| Test results          |        |        |        |        |     |        |
|-----------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 37     |
| <b>CPU cycles</b>     | 59     | 56     | 56     | 56     | ... | 56     |
| <i>Inputs</i>         |        |        |        |        |     |        |
| <b>In (DSP)</b>       | -32768 | -30948 | -29127 | -27307 | ... | 32767  |
| <b>In</b>             | -1     | -0.944 | -0.889 | -0.833 | ... | 1      |
| <i>Outputs</i>        |        |        |        |        |     |        |
| <b>Out</b>            | 1      | 0.944  | 0.889  | 0.833  | ... | -1     |
| <b>Exp. Out</b>       | 1      | 0.944  | 0.889  | 0.833  | ... | -1     |
| <b>Out (DSP)</b>      | 32767  | 30948  | 29127  | 27307  | ... | -32767 |
| <b>Exp. Out (DSP)</b> | 32767  | 30948  | 29127  | 27307  | ... | -32768 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 3,0518\text{e-}05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 59 |
| Avg CPU cycles  | 56 |

**Verification: Negation FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Negation.

| Test results          |        |        |        |        |     |        |
|-----------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 37     |
| <b>CPU cycles</b>     | 29     | 29     | 29     | 29     | ... | 29     |
| <i>Inputs</i>         |        |        |        |        |     |        |
| <b>In (DSP)</b>       | -32768 | -30948 | -29127 | -27307 | ... | 32767  |
| <b>In</b>             | -1     | -0.944 | -0.889 | -0.833 | ... | 1      |
| <i>Outputs</i>        |        |        |        |        |     |        |
| <b>Out</b>            | 1      | 0.944  | 0.889  | 0.833  | ... | -1     |
| <b>Exp. Out</b>       | 1      | 0.944  | 0.889  | 0.833  | ... | -1     |
| <b>Out (DSP)</b>      | 32767  | 30948  | 29127  | 27307  | ... | -32767 |
| <b>Exp. Out (DSP)</b> | 32767  | 30948  | 29127  | 27307  | ... | -32768 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 3,0518\text{e-}05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 29 |
| Avg CPU cycles  | 29 |

## Verification: Negation FiP16 CPU STM32G474RE

Date of Test 2026-06-19  
Target controller STM32G474RE

### Test case: Inport test

OK

Inport test for Math block Negation.

| Test results   |        |        |        |        |     |        |
|----------------|--------|--------|--------|--------|-----|--------|
| Time step      | 1      | 2      | 3      | 4      | ... | 37     |
| CPU cycles     | 66     | 66     | 66     | 66     | ... | 66     |
| Inputs         |        |        |        |        |     |        |
| In (DSP)       | -32768 | -30948 | -29127 | -27307 | ... | 32767  |
| In             | -1     | -0.944 | -0.889 | -0.833 | ... | 1      |
| Outputs        |        |        |        |        |     |        |
| Out            | 1      | 0.944  | 0.889  | 0.833  | ... | -1     |
| Exp. Out       | 1      | 0.944  | 0.889  | 0.833  | ... | -1     |
| Out (DSP)      | 32767  | 30948  | 29127  | 27307  | ... | -32767 |
| Exp. Out (DSP) | 32767  | 30948  | 29127  | 27307  | ... | -32768 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 3,0518\text{e-}05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 66 |
| Max CPU cycles  | 66 |
| Avg CPU cycles  | 66 |

**Verification: Negation FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Negation.

| Test results          |        |        |        |        |     |        |
|-----------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 37     |
| <b>CPU cycles</b>     | 62     | 54     | 54     | 54     | ... | 54     |
| <i>Inputs</i>         |        |        |        |        |     |        |
| <b>In (DSP)</b>       | -32768 | -30948 | -29127 | -27307 | ... | 32767  |
| <b>In</b>             | -1     | -0.944 | -0.889 | -0.833 | ... | 1      |
| <i>Outputs</i>        |        |        |        |        |     |        |
| <b>Out</b>            | 1      | 0.944  | 0.889  | 0.833  | ... | -1     |
| <b>Exp. Out</b>       | 1      | 0.944  | 0.889  | 0.833  | ... | -1     |
| <b>Out (DSP)</b>      | 32767  | 30948  | 29127  | 27307  | ... | -32767 |
| <b>Exp. Out (DSP)</b> | 32767  | 30948  | 29127  | 27307  | ... | -32768 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 3,0518\text{e-}05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 54 |
| Max CPU cycles  | 62 |
| Avg CPU cycles  | 54 |

**Verification: Negation FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Negation.

| Test results          |        |        |        |        |     |        |
|-----------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 37     |
| <b>CPU cycles</b>     | 31     | 31     | 31     | 31     | ... | 31     |
| <i>Inputs</i>         |        |        |        |        |     |        |
| <b>In (DSP)</b>       | -32768 | -30948 | -29127 | -27307 | ... | 32767  |
| <b>In</b>             | -1     | -0.944 | -0.889 | -0.833 | ... | 1      |
| <i>Outputs</i>        |        |        |        |        |     |        |
| <b>Out</b>            | 1      | 0.944  | 0.889  | 0.833  | ... | -1     |
| <b>Exp. Out</b>       | 1      | 0.944  | 0.889  | 0.833  | ... | -1     |
| <b>Out (DSP)</b>      | 32767  | 30948  | 29127  | 27307  | ... | -32767 |
| <b>Exp. Out (DSP)</b> | 32767  | 30948  | 29127  | 27307  | ... | -32768 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 31 |
| Avg CPU cycles  | 31 |



**Verification: Negation FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Negation.

| Test results          |        |        |        |        |     |        |
|-----------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 37     |
| <b>CPU cycles</b>     | 44     | 41     | 41     | 41     | ... | 41     |
| <i>Inputs</i>         |        |        |        |        |     |        |
| <b>In (DSP)</b>       | -32768 | -30948 | -29127 | -27307 | ... | 32767  |
| <b>In</b>             | -1     | -0.944 | -0.889 | -0.833 | ... | 1      |
| <i>Outputs</i>        |        |        |        |        |     |        |
| <b>Out</b>            | 1      | 0.944  | 0.889  | 0.833  | ... | -1     |
| <b>Exp. Out</b>       | 1      | 0.944  | 0.889  | 0.833  | ... | -1     |
| <b>Out (DSP)</b>      | 32767  | 30948  | 29127  | 27307  | ... | -32767 |
| <b>Exp. Out (DSP)</b> | 32767  | 30948  | 29127  | 27307  | ... | -32768 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 3,0518\text{e-}05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 41 |
| Max CPU cycles  | 44 |
| Avg CPU cycles  | 41 |

**Verification: Negation FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Negation.

| Test results          |        |        |        |        |     |        |
|-----------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 37     |
| <b>CPU cycles</b>     | 59     | 59     | 59     | 59     | ... | 59     |
| <i>Inputs</i>         |        |        |        |        |     |        |
| <b>In (DSP)</b>       | -32768 | -30948 | -29127 | -27307 | ... | 32767  |
| <b>In</b>             | -1     | -0.944 | -0.889 | -0.833 | ... | 1      |
| <i>Outputs</i>        |        |        |        |        |     |        |
| <b>Out</b>            | 1      | 0.944  | 0.889  | 0.833  | ... | -1     |
| <b>Exp. Out</b>       | 1      | 0.944  | 0.889  | 0.833  | ... | -1     |
| <b>Out (DSP)</b>      | 32767  | 30948  | 29127  | 27307  | ... | -32767 |
| <b>Exp. Out (DSP)</b> | 32767  | 30948  | 29127  | 27307  | ... | -32768 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 59 |
| Avg CPU cycles  | 59 |

**Verification: Negation FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Negation.

| Test results          |        |        |        |        |     |        |
|-----------------------|--------|--------|--------|--------|-----|--------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 37     |
| <b>CPU cycles</b>     | 54     | 49     | 49     | 49     | ... | 49     |
| <i>Inputs</i>         |        |        |        |        |     |        |
| <b>In (DSP)</b>       | -32768 | -30948 | -29127 | -27307 | ... | 32767  |
| <b>In</b>             | -1     | -0.944 | -0.889 | -0.833 | ... | 1      |
| <i>Outputs</i>        |        |        |        |        |     |        |
| <b>Out</b>            | 1      | 0.944  | 0.889  | 0.833  | ... | -1     |
| <b>Exp. Out</b>       | 1      | 0.944  | 0.889  | 0.833  | ... | -1     |
| <b>Out (DSP)</b>      | 32767  | 30948  | 29127  | 27307  | ... | -32767 |
| <b>Exp. Out (DSP)</b> | 32767  | 30948  | 29127  | 27307  | ... | -32768 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 3,0518\text{e-}05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 49 |
| Max CPU cycles  | 54 |
| Avg CPU cycles  | 49 |

**Verification: Negation FiP32 CPU TMS320F28335**

|                          |              |
|--------------------------|--------------|
| <b>Date of Test</b>      | 2026-06-19   |
| <b>Target controller</b> | TMS320F28335 |

**Test case: Inport test****OK**

Inport test for Math block Negation.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>      | 1           | 2           | ... | 37          |
| <b>CPU cycles</b>     | 59          | 60          | ... | 60          |
| <i>Inputs</i>         |             |             |     |             |
| <b>In (DSP)</b>       | -2147483648 | -2028179001 | ... | 2147483647  |
| <b>In</b>             | -1          | -0.944      | ... | 1           |
| <i>Outputs</i>        |             |             |     |             |
| <b>Out</b>            | 1           | 0.944       | ... | -1          |
| <b>Exp. Out</b>       | 1           | 0.944       | ... | -1          |
| <b>Out (DSP)</b>      | 2147483647  | 2028179001  | ... | -2147483647 |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2028179001  | ... | -2147483648 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 60 |
| Avg CPU cycles  | 59 |

**Verification: Negation FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Negation.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>      | 1           | 2           | ... | 37          |
| <b>CPU cycles</b>     | 31          | 29          | ... | 29          |
| <i>Inputs</i>         |             |             |     |             |
| <b>In (DSP)</b>       | -2147483648 | -2028179001 | ... | 2147483647  |
| <b>In</b>             | -1          | -0.944      | ... | 1           |
| <i>Outputs</i>        |             |             |     |             |
| <b>Out</b>            | 1           | 0.944       | ... | -1          |
| <b>Exp. Out</b>       | 1           | 0.944       | ... | -1          |
| <b>Out (DSP)</b>      | 2147483647  | 2028179001  | ... | -2147483647 |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2028179001  | ... | -2147483648 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 31 |
| Avg CPU cycles  | 29 |

## Verification: Negation FiP32 CPU STM32G474RE

Date of Test 2026-06-19  
Target controller STM32G474RE

### Test case: Inport test

OK

Inport test for Math block Negation.

| Test results   |             |             |     |             |
|----------------|-------------|-------------|-----|-------------|
| Time step      | 1           | 2           | ... | 37          |
| CPU cycles     | 66          | 66          | ... | 66          |
| Inputs         |             |             |     |             |
| In (DSP)       | -2147483648 | -2028179001 | ... | 2147483647  |
| In             | -1          | -0.944      | ... | 1           |
| Outputs        |             |             |     |             |
| Out            | 1           | 0.944       | ... | -1          |
| Exp. Out       | 1           | 0.944       | ... | -1          |
| Out (DSP)      | 2147483647  | 2028179001  | ... | -2147483647 |
| Exp. Out (DSP) | 2147483647  | 2028179001  | ... | -2147483648 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 66 |
| Max CPU cycles  | 66 |
| Avg CPU cycles  | 66 |

**Verification: Negation FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Negation.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>      | 1           | 2           | ... | 37          |
| <b>CPU cycles</b>     | 59          | 51          | ... | 51          |
| <i>Inputs</i>         |             |             |     |             |
| <b>In (DSP)</b>       | -2147483648 | -2028179001 | ... | 2147483647  |
| <b>In</b>             | -1          | -0.944      | ... | 1           |
| <i>Outputs</i>        |             |             |     |             |
| <b>Out</b>            | 1           | 0.944       | ... | -1          |
| <b>Exp. Out</b>       | 1           | 0.944       | ... | -1          |
| <b>Out (DSP)</b>      | 2147483647  | 2028179001  | ... | -2147483647 |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2028179001  | ... | -2147483648 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 51 |
| Max CPU cycles  | 59 |
| Avg CPU cycles  | 51 |

**Verification: Negation FiP32 CPU PIC32MX170F256**

|                          |                |
|--------------------------|----------------|
| <b>Date of Test</b>      | 2026-06-19     |
| <b>Target controller</b> | PIC32MX170F256 |

**Test case: Inport test****OK**

Inport test for Math block Negation.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>      | 1           | 2           | ... | 37          |
| <b>CPU cycles</b>     | 32          | 30          | ... | 30          |
| <i>Inputs</i>         |             |             |     |             |
| <b>In (DSP)</b>       | -2147483648 | -2028179001 | ... | 2147483647  |
| <b>In</b>             | -1          | -0.944      | ... | 1           |
| <i>Outputs</i>        |             |             |     |             |
| <b>Out</b>            | 1           | 0.944       | ... | -1          |
| <b>Exp. Out</b>       | 1           | 0.944       | ... | -1          |
| <b>Out (DSP)</b>      | 2147483647  | 2028179001  | ... | -2147483647 |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2028179001  | ... | -2147483648 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 30 |
| Max CPU cycles  | 32 |
| Avg CPU cycles  | 30 |



**Verification: Negation FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Negation.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>      | 1           | 2           | ... | 37          |
| <b>CPU cycles</b>     | 49          | 46          | ... | 46          |
| <i>Inputs</i>         |             |             |     |             |
| <b>In (DSP)</b>       | -2147483648 | -2028179001 | ... | 2147483647  |
| <b>In</b>             | -1          | -0.944      | ... | 1           |
| <i>Outputs</i>        |             |             |     |             |
| <b>Out</b>            | 1           | 0.944       | ... | -1          |
| <b>Exp. Out</b>       | 1           | 0.944       | ... | -1          |
| <b>Out (DSP)</b>      | 2147483647  | 2028179001  | ... | -2147483647 |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2028179001  | ... | -2147483648 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 46 |
| Max CPU cycles  | 49 |
| Avg CPU cycles  | 46 |

**Verification: Negation FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Negation.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>      | 1           | 2           | ... | 37          |
| <b>CPU cycles</b>     | 67          | 59          | ... | 59          |
| <i>Inputs</i>         |             |             |     |             |
| <b>In (DSP)</b>       | -2147483648 | -2028179001 | ... | 2147483647  |
| <b>In</b>             | -1          | -0.944      | ... | 1           |
| <i>Outputs</i>        |             |             |     |             |
| <b>Out</b>            | 1           | 0.944       | ... | -1          |
| <b>Exp. Out</b>       | 1           | 0.944       | ... | -1          |
| <b>Out (DSP)</b>      | 2147483647  | 2028179001  | ... | -2147483647 |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2028179001  | ... | -2147483648 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 67 |
| Avg CPU cycles  | 59 |

**Verification: Negation FiP32 CPU TMS320F28379D**

|                          |               |
|--------------------------|---------------|
| <b>Date of Test</b>      | 2026-06-22    |
| <b>Target controller</b> | TMS320F28379D |

**Test case: Inport test****OK**

Inport test for Math block Negation.

| Test results          |             |             |     |             |
|-----------------------|-------------|-------------|-----|-------------|
| <b>Time step</b>      | 1           | 2           | ... | 37          |
| <b>CPU cycles</b>     | 57          | 58          | ... | 58          |
| <i>Inputs</i>         |             |             |     |             |
| <b>In (DSP)</b>       | -2147483648 | -2028179001 | ... | 2147483647  |
| <b>In</b>             | -1          | -0.944      | ... | 1           |
| <i>Outputs</i>        |             |             |     |             |
| <b>Out</b>            | 1           | 0.944       | ... | -1          |
| <b>Exp. Out</b>       | 1           | 0.944       | ... | -1          |
| <b>Out (DSP)</b>      | 2147483647  | 2028179001  | ... | -2147483647 |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2028179001  | ... | -2147483648 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 58 |
| Avg CPU cycles  | 57 |

**Verification: Negation Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Negation.

| Test results          |    |        |     |    |
|-----------------------|----|--------|-----|----|
| <b>Time step</b>      | 1  | 2      | ... | 37 |
| <b>CPU cycles</b>     | 51 | 51     | ... | 51 |
| <i>Inputs</i>         |    |        |     |    |
| <b>In (DSP)</b>       | -1 | -0.944 | ... | 1  |
| <b>In</b>             | -1 | -0.944 | ... | 1  |
| <i>Outputs</i>        |    |        |     |    |
| <b>Out</b>            | 1  | 0.944  | ... | -1 |
| <b>Exp. Out</b>       | 1  | 0.944  | ... | -1 |
| <b>Out (DSP)</b>      | 1  | 0.944  | ... | -1 |
| <b>Exp. Out (DSP)</b> | 1  | 0.944  | ... | -1 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,4925e-08$ ( $\pm 75$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 51 |
| Max CPU cycles  | 51 |
| Avg CPU cycles  | 51 |

## Verification: Negation Float32 CPU TM4C123GH6

Date of Test 2026-06-19  
Target controller TM4C123GH6

### Test case: Inport test

OK

Inport test for Math block Negation.

| Test results   |    |        |     |    |
|----------------|----|--------|-----|----|
| Time step      | 1  | 2      | ... | 37 |
| CPU cycles     | 25 | 25     | ... | 25 |
| Inputs         |    |        |     |    |
| In (DSP)       | -1 | -0.944 | ... | 1  |
| In             | -1 | -0.944 | ... | 1  |
| Outputs        |    |        |     |    |
| Out            | 1  | 0.944  | ... | -1 |
| Exp. Out       | 1  | 0.944  | ... | -1 |
| Out (DSP)      | 1  | 0.944  | ... | -1 |
| Exp. Out (DSP) | 1  | 0.944  | ... | -1 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,4925e-08$ ( $\pm 75$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 25 |
| Max CPU cycles  | 25 |
| Avg CPU cycles  | 25 |

**Verification: Negation Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Negation.

| Test results          |    |        |     |    |
|-----------------------|----|--------|-----|----|
| <b>Time step</b>      | 1  | 2      | ... | 37 |
| <b>CPU cycles</b>     | 66 | 66     | ... | 66 |
| <i>Inputs</i>         |    |        |     |    |
| <b>In (DSP)</b>       | -1 | -0.944 | ... | 1  |
| <b>In</b>             | -1 | -0.944 | ... | 1  |
| <i>Outputs</i>        |    |        |     |    |
| <b>Out</b>            | 1  | 0.944  | ... | -1 |
| <b>Exp. Out</b>       | 1  | 0.944  | ... | -1 |
| <b>Out (DSP)</b>      | 1  | 0.944  | ... | -1 |
| <b>Exp. Out (DSP)</b> | 1  | 0.944  | ... | -1 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,4925e-08$ ( $\pm 75$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 66 |
| Max CPU cycles  | 66 |
| Avg CPU cycles  | 66 |

**Verification: Negation Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Negation.

| Test results          |    |        |     |    |
|-----------------------|----|--------|-----|----|
| <b>Time step</b>      | 1  | 2      | ... | 37 |
| <b>CPU cycles</b>     | 50 | 50     | ... | 50 |
| <i>Inputs</i>         |    |        |     |    |
| <b>In (DSP)</b>       | -1 | -0.944 | ... | 1  |
| <b>In</b>             | -1 | -0.944 | ... | 1  |
| <i>Outputs</i>        |    |        |     |    |
| <b>Out</b>            | 1  | 0.944  | ... | -1 |
| <b>Exp. Out</b>       | 1  | 0.944  | ... | -1 |
| <b>Out (DSP)</b>      | 1  | 0.944  | ... | -1 |
| <b>Exp. Out (DSP)</b> | 1  | 0.944  | ... | -1 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,4925e-08$ ( $\pm 75$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 50 |
| Max CPU cycles  | 50 |
| Avg CPU cycles  | 50 |

**Verification: Negation Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Negation.

| Test results          |    |        |     |    |
|-----------------------|----|--------|-----|----|
| <b>Time step</b>      | 1  | 2      | ... | 37 |
| <b>CPU cycles</b>     | 29 | 29     | ... | 29 |
| <i>Inputs</i>         |    |        |     |    |
| <b>In (DSP)</b>       | -1 | -0.944 | ... | 1  |
| <b>In</b>             | -1 | -0.944 | ... | 1  |
| <i>Outputs</i>        |    |        |     |    |
| <b>Out</b>            | 1  | 0.944  | ... | -1 |
| <b>Exp. Out</b>       | 1  | 0.944  | ... | -1 |
| <b>Out (DSP)</b>      | 1  | 0.944  | ... | -1 |
| <b>Exp. Out (DSP)</b> | 1  | 0.944  | ... | -1 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,4925e-08$ ( $\pm 75$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 29 |
| Avg CPU cycles  | 29 |



**Verification: Negation Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Negation.

| Test results          |    |        |     |    |
|-----------------------|----|--------|-----|----|
| <b>Time step</b>      | 1  | 2      | ... | 37 |
| <b>CPU cycles</b>     | 40 | 40     | ... | 40 |
| <i>Inputs</i>         |    |        |     |    |
| <b>In (DSP)</b>       | -1 | -0.944 | ... | 1  |
| <b>In</b>             | -1 | -0.944 | ... | 1  |
| <i>Outputs</i>        |    |        |     |    |
| <b>Out</b>            | 1  | 0.944  | ... | -1 |
| <b>Exp. Out</b>       | 1  | 0.944  | ... | -1 |
| <b>Out (DSP)</b>      | 1  | 0.944  | ... | -1 |
| <b>Exp. Out (DSP)</b> | 1  | 0.944  | ... | -1 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,4925e-08$ ( $\pm 75$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 40 |
| Max CPU cycles  | 40 |
| Avg CPU cycles  | 40 |

**Verification: Negation Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Negation.

| Test results          |    |        |     |    |
|-----------------------|----|--------|-----|----|
| <b>Time step</b>      | 1  | 2      | ... | 37 |
| <b>CPU cycles</b>     | 56 | 56     | ... | 56 |
| <i>Inputs</i>         |    |        |     |    |
| <b>In (DSP)</b>       | -1 | -0.944 | ... | 1  |
| <b>In</b>             | -1 | -0.944 | ... | 1  |
| <i>Outputs</i>        |    |        |     |    |
| <b>Out</b>            | 1  | 0.944  | ... | -1 |
| <b>Exp. Out</b>       | 1  | 0.944  | ... | -1 |
| <b>Out (DSP)</b>      | 1  | 0.944  | ... | -1 |
| <b>Exp. Out (DSP)</b> | 1  | 0.944  | ... | -1 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,4925e-08$ ( $\pm 75$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 56 |
| Avg CPU cycles  | 56 |

**Verification: Negation Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Negation.

| Test results          |    |        |     |    |
|-----------------------|----|--------|-----|----|
| <b>Time step</b>      | 1  | 2      | ... | 37 |
| <b>CPU cycles</b>     | 47 | 47     | ... | 47 |
| <i>Inputs</i>         |    |        |     |    |
| <b>In (DSP)</b>       | -1 | -0.944 | ... | 1  |
| <b>In</b>             | -1 | -0.944 | ... | 1  |
| <i>Outputs</i>        |    |        |     |    |
| <b>Out</b>            | 1  | 0.944  | ... | -1 |
| <b>Exp. Out</b>       | 1  | 0.944  | ... | -1 |
| <b>Out (DSP)</b>      | 1  | 0.944  | ... | -1 |
| <b>Exp. Out (DSP)</b> | 1  | 0.944  | ... | -1 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,4925e-08$ ( $\pm 75$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 47 |
| Max CPU cycles  | 47 |
| Avg CPU cycles  | 47 |

## Block: Sign

---



Signum function.

| Inports |         |
|---------|---------|
| In      | Input u |

| Outports |                                  |
|----------|----------------------------------|
| Out      | Value corresponding to sign of u |

### Description:

Calculation:

$$\text{Out} = \text{sgn}(\text{In}) = \begin{cases} 1 & \text{In} \geq 0 \\ -1 & \text{In} < 0 \end{cases}$$

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | int8 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: Sign FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Sign.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 37    |
| <b>CPU cycles</b>     | 58     | 58     | 58     | 58     | ... | 54    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| <b>In</b>             | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -1     | -1     | -1     | -1     | ... | 1     |
| <b>Exp. Out</b>       | -1     | -1     | -1     | -1     | ... | 1     |
| <b>Out (DSP)</b>      | -32767 | -32767 | -32767 | -32767 | ... | 32767 |
| <b>Exp. Out (DSP)</b> | -32768 | -32768 | -32768 | -32768 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 54 |
| Max CPU cycles  | 58 |
| Avg CPU cycles  | 55 |

**Verification: Sign FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Sign.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 37    |
| <b>CPU cycles</b>     | 33     | 33     | 33     | 33     | ... | 29    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| <b>In</b>             | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -1     | -1     | -1     | -1     | ... | 1     |
| <b>Exp. Out</b>       | -1     | -1     | -1     | -1     | ... | 1     |
| <b>Out (DSP)</b>      | -32767 | -32767 | -32767 | -32767 | ... | 32767 |
| <b>Exp. Out (DSP)</b> | -32768 | -32768 | -32768 | -32768 | ... | 32767 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 3,0518\text{e-}05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 33 |
| Avg CPU cycles  | 30 |

## Verification: Sign FiP16 CPU STM32G474RE

Date of Test 2026-06-19  
Target controller STM32G474RE

### Test case: Inport test

OK

Inport test for Math block Sign.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 37    |
| CPU cycles     | 71     | 71     | 71     | 71     | ... | 71    |
| Inputs         |        |        |        |        |     |       |
| In (DSP)       | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In             | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| Outputs        |        |        |        |        |     |       |
| Out            | -1     | -1     | -1     | -1     | ... | 1     |
| Exp. Out       | -1     | -1     | -1     | -1     | ... | 1     |
| Out (DSP)      | -32767 | -32767 | -32767 | -32767 | ... | 32767 |
| Exp. Out (DSP) | -32768 | -32768 | -32768 | -32768 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 71 |
| Max CPU cycles  | 71 |
| Avg CPU cycles  | 71 |



**Verification: Sign FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Sign.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 37    |
| <b>CPU cycles</b>     | 57     | 57     | 57     | 57     | ... | 57    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| <b>In</b>             | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -1     | -1     | -1     | -1     | ... | 1     |
| <b>Exp. Out</b>       | -1     | -1     | -1     | -1     | ... | 1     |
| <b>Out (DSP)</b>      | -32767 | -32767 | -32767 | -32767 | ... | 32767 |
| <b>Exp. Out (DSP)</b> | -32768 | -32768 | -32768 | -32768 | ... | 32767 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 3,0518\text{e-}05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 57 |

**Verification: Sign FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Sign.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 37    |
| <b>CPU cycles</b>     | 31     | 31     | 31     | 31     | ... | 31    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| <b>In</b>             | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -1     | -1     | -1     | -1     | ... | 1     |
| <b>Exp. Out</b>       | -1     | -1     | -1     | -1     | ... | 1     |
| <b>Out (DSP)</b>      | -32767 | -32767 | -32767 | -32767 | ... | 32767 |
| <b>Exp. Out (DSP)</b> | -32768 | -32768 | -32768 | -32768 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 31 |
| Avg CPU cycles  | 31 |

**Verification: Sign FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Sign.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 37    |
| <b>CPU cycles</b>     | 42     | 42     | 42     | 42     | ... | 39    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| <b>In</b>             | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -1     | -1     | -1     | -1     | ... | 1     |
| <b>Exp. Out</b>       | -1     | -1     | -1     | -1     | ... | 1     |
| <b>Out (DSP)</b>      | -32767 | -32767 | -32767 | -32767 | ... | 32767 |
| <b>Exp. Out (DSP)</b> | -32768 | -32768 | -32768 | -32768 | ... | 32767 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 3,0518\text{e-}05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 39 |
| Max CPU cycles  | 42 |
| Avg CPU cycles  | 40 |

**Verification: Sign FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Sign.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 37    |
| <b>CPU cycles</b>     | 59     | 59     | 59     | 59     | ... | 59    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| <b>In</b>             | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -1     | -1     | -1     | -1     | ... | 1     |
| <b>Exp. Out</b>       | -1     | -1     | -1     | -1     | ... | 1     |
| <b>Out (DSP)</b>      | -32767 | -32767 | -32767 | -32767 | ... | 32767 |
| <b>Exp. Out (DSP)</b> | -32768 | -32768 | -32768 | -32768 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 59 |
| Avg CPU cycles  | 59 |

**Verification: Sign FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Sign.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 37    |
| <b>CPU cycles</b>     | 53     | 53     | 53     | 53     | ... | 47    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| <b>In</b>             | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -1     | -1     | -1     | -1     | ... | 1     |
| <b>Exp. Out</b>       | -1     | -1     | -1     | -1     | ... | 1     |
| <b>Out (DSP)</b>      | -32767 | -32767 | -32767 | -32767 | ... | 32767 |
| <b>Exp. Out (DSP)</b> | -32768 | -32768 | -32768 | -32768 | ... | 32767 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 3,0518\text{e-}05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 47 |
| Max CPU cycles  | 53 |
| Avg CPU cycles  | 49 |

**Verification: Sign FiP32 CPU TMS320F28335**

|                          |              |
|--------------------------|--------------|
| <b>Date of Test</b>      | 2026-06-19   |
| <b>Target controller</b> | TMS320F28335 |

**Test case: Inport test****OK**

Inport test for Math block Sign.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 37         |
| <b>CPU cycles</b>     | 59          | 59          | ... | 60         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2028179001 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.944      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -1          | -1          | ... | 1          |
| <b>Exp. Out</b>       | -1          | -1          | ... | 1          |
| <b>Out (DSP)</b>      | -2147483647 | -2147483647 | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2147483648 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 60 |
| Avg CPU cycles  | 59 |

**Verification: Sign FiP32 CPU TM4C123GH6**

|                          |            |
|--------------------------|------------|
| <b>Date of Test</b>      | 2026-06-19 |
| <b>Target controller</b> | TM4C123GH6 |

**Test case: Inport test****OK**

Inport test for Math block Sign.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 37         |
| <b>CPU cycles</b>     | 29          | 29          | ... | 29         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2028179001 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.944      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -1          | -1          | ... | 1          |
| <b>Exp. Out</b>       | -1          | -1          | ... | 1          |
| <b>Out (DSP)</b>      | -2147483647 | -2147483647 | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2147483648 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 29 |
| Avg CPU cycles  | 29 |

**Verification: Sign FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Sign.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 37         |
| <b>CPU cycles</b>     | 71          | 71          | ... | 71         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2028179001 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.944      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -1          | -1          | ... | 1          |
| <b>Exp. Out</b>       | -1          | -1          | ... | 1          |
| <b>Out (DSP)</b>      | -2147483647 | -2147483647 | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2147483648 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 71 |
| Max CPU cycles  | 71 |
| Avg CPU cycles  | 71 |



**Verification: Sign FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Sign.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 37         |
| <b>CPU cycles</b>     | 54          | 54          | ... | 54         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2028179001 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.944      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -1          | -1          | ... | 1          |
| <b>Exp. Out</b>       | -1          | -1          | ... | 1          |
| <b>Out (DSP)</b>      | -2147483647 | -2147483647 | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2147483648 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 54 |
| Max CPU cycles  | 54 |
| Avg CPU cycles  | 54 |

**Verification: Sign FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Sign.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 37         |
| <b>CPU cycles</b>     | 32          | 32          | ... | 31         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2028179001 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.944      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -1          | -1          | ... | 1          |
| <b>Exp. Out</b>       | -1          | -1          | ... | 1          |
| <b>Out (DSP)</b>      | -2147483647 | -2147483647 | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2147483648 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 32 |
| Avg CPU cycles  | 31 |

**Verification: Sign FiP32 CPU dsPIC33EP256MC502**

|                          |                   |
|--------------------------|-------------------|
| <b>Date of Test</b>      | 2026-06-19        |
| <b>Target controller</b> | dsPIC33EP256MC502 |

**Test case: Inport test****OK**

Inport test for Math block Sign.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 37         |
| <b>CPU cycles</b>     | 47          | 47          | ... | 44         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2028179001 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.944      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -1          | -1          | ... | 1          |
| <b>Exp. Out</b>       | -1          | -1          | ... | 1          |
| <b>Out (DSP)</b>      | -2147483647 | -2147483647 | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2147483648 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 44 |
| Max CPU cycles  | 47 |
| Avg CPU cycles  | 45 |

**Verification: Sign FiP32 CPU XMC4800-F144K2048**

|                          |                   |
|--------------------------|-------------------|
| <b>Date of Test</b>      | 2026-06-19        |
| <b>Target controller</b> | XMC4800-F144K2048 |

**Test case: Inport test****OK**

Inport test for Math block Sign.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 37         |
| <b>CPU cycles</b>     | 65          | 65          | ... | 58         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2028179001 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.944      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -1          | -1          | ... | 1          |
| <b>Exp. Out</b>       | -1          | -1          | ... | 1          |
| <b>Out (DSP)</b>      | -2147483647 | -2147483647 | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2147483648 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 58 |
| Max CPU cycles  | 65 |
| Avg CPU cycles  | 61 |

**Verification: Sign FiP32 CPU TMS320F28379D**

|                          |               |
|--------------------------|---------------|
| <b>Date of Test</b>      | 2026-06-22    |
| <b>Target controller</b> | TMS320F28379D |

**Test case: Inport test****OK**

Inport test for Math block Sign.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 37         |
| <b>CPU cycles</b>     | 57          | 57          | ... | 56         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2028179001 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.944      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -1          | -1          | ... | 1          |
| <b>Exp. Out</b>       | -1          | -1          | ... | 1          |
| <b>Out (DSP)</b>      | -2147483647 | -2147483647 | ... | 2147483647 |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2147483648 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 56 |

**Verification: Sign Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Sign.

| Test results          |    |        |     |    |
|-----------------------|----|--------|-----|----|
| <b>Time step</b>      | 1  | 2      | ... | 37 |
| <b>CPU cycles</b>     | 61 | 61     | ... | 62 |
| <i>Inputs</i>         |    |        |     |    |
| <b>In (DSP)</b>       | -1 | -0.944 | ... | 1  |
| <b>In</b>             | -1 | -0.944 | ... | 1  |
| <i>Outputs</i>        |    |        |     |    |
| <b>Out</b>            | -1 | -1     | ... | 1  |
| <b>Exp. Out</b>       | -1 | -1     | ... | 1  |
| <b>Out (DSP)</b>      | -1 | -1     | ... | 1  |
| <b>Exp. Out (DSP)</b> | -1 | -1     | ... | 1  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 61 |
| Max CPU cycles  | 62 |
| Avg CPU cycles  | 61 |

**Verification: Sign Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Sign.

| Test results          |    |        |     |    |
|-----------------------|----|--------|-----|----|
| <b>Time step</b>      | 1  | 2      | ... | 37 |
| <b>CPU cycles</b>     | 31 | 31     | ... | 31 |
| <i>Inputs</i>         |    |        |     |    |
| <b>In (DSP)</b>       | -1 | -0.944 | ... | 1  |
| <b>In</b>             | -1 | -0.944 | ... | 1  |
| <i>Outputs</i>        |    |        |     |    |
| <b>Out</b>            | -1 | -1     | ... | 1  |
| <b>Exp. Out</b>       | -1 | -1     | ... | 1  |
| <b>Out (DSP)</b>      | -1 | -1     | ... | 1  |
| <b>Exp. Out (DSP)</b> | -1 | -1     | ... | 1  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 31 |
| Avg CPU cycles  | 31 |

## Verification: Sign Float32 CPU STM32G474RE

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

### Test case: Inport test

OK

Inport test for Math block Sign.

| Test results          |    |        |     |    |
|-----------------------|----|--------|-----|----|
| <b>Time step</b>      | 1  | 2      | ... | 37 |
| <b>CPU cycles</b>     | 67 | 67     | ... | 67 |
| <i>Inputs</i>         |    |        |     |    |
| <b>In (DSP)</b>       | -1 | -0.944 | ... | 1  |
| <b>In</b>             | -1 | -0.944 | ... | 1  |
| <i>Outputs</i>        |    |        |     |    |
| <b>Out</b>            | -1 | -1     | ... | 1  |
| <b>Exp. Out</b>       | -1 | -1     | ... | 1  |
| <b>Out (DSP)</b>      | -1 | -1     | ... | 1  |
| <b>Exp. Out (DSP)</b> | -1 | -1     | ... | 1  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 67 |
| Max CPU cycles  | 67 |
| Avg CPU cycles  | 67 |



**Verification: Sign Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Sign.

| Test results          |     |        |     |     |
|-----------------------|-----|--------|-----|-----|
| <b>Time step</b>      | 1   | 2      | ... | 37  |
| <b>CPU cycles</b>     | 146 | 146    | ... | 133 |
| <i>Inputs</i>         |     |        |     |     |
| <b>In (DSP)</b>       | -1  | -0.944 | ... | 1   |
| <b>In</b>             | -1  | -0.944 | ... | 1   |
| <i>Outputs</i>        |     |        |     |     |
| <b>Out</b>            | -1  | -1     | ... | 1   |
| <b>Exp. Out</b>       | -1  | -1     | ... | 1   |
| <b>Out (DSP)</b>      | -1  | -1     | ... | 1   |
| <b>Exp. Out (DSP)</b> | -1  | -1     | ... | 1   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 124 |
| Max CPU cycles  | 146 |
| Avg CPU cycles  | 139 |

**Verification: Sign Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Sign.

| Test results          |    |        |     |    |
|-----------------------|----|--------|-----|----|
| <b>Time step</b>      | 1  | 2      | ... | 37 |
| <b>CPU cycles</b>     | 75 | 75     | ... | 76 |
| <i>Inputs</i>         |    |        |     |    |
| <b>In (DSP)</b>       | -1 | -0.944 | ... | 1  |
| <b>In</b>             | -1 | -0.944 | ... | 1  |
| <i>Outputs</i>        |    |        |     |    |
| <b>Out</b>            | -1 | -1     | ... | 1  |
| <b>Exp. Out</b>       | -1 | -1     | ... | 1  |
| <b>Out (DSP)</b>      | -1 | -1     | ... | 1  |
| <b>Exp. Out (DSP)</b> | -1 | -1     | ... | 1  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 52 |
| Max CPU cycles  | 76 |
| Avg CPU cycles  | 74 |

**Verification: Sign Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Sign.

| Test results          |     |        |     |     |
|-----------------------|-----|--------|-----|-----|
| <b>Time step</b>      | 1   | 2      | ... | 37  |
| <b>CPU cycles</b>     | 144 | 144    | ... | 145 |
| <i>Inputs</i>         |     |        |     |     |
| <b>In (DSP)</b>       | -1  | -0.944 | ... | 1   |
| <b>In</b>             | -1  | -0.944 | ... | 1   |
| <i>Outputs</i>        |     |        |     |     |
| <b>Out</b>            | -1  | -1     | ... | 1   |
| <b>Exp. Out</b>       | -1  | -1     | ... | 1   |
| <b>Out (DSP)</b>      | -1  | -1     | ... | 1   |
| <b>Exp. Out (DSP)</b> | -1  | -1     | ... | 1   |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 144 |
| Max CPU cycles  | 145 |
| Avg CPU cycles  | 144 |

**Verification: Sign Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Sign.

| Test results          |    |        |     |    |
|-----------------------|----|--------|-----|----|
| <b>Time step</b>      | 1  | 2      | ... | 37 |
| <b>CPU cycles</b>     | 73 | 67     | ... | 60 |
| <i>Inputs</i>         |    |        |     |    |
| <b>In (DSP)</b>       | -1 | -0.944 | ... | 1  |
| <b>In</b>             | -1 | -0.944 | ... | 1  |
| <i>Outputs</i>        |    |        |     |    |
| <b>Out</b>            | -1 | -1     | ... | 1  |
| <b>Exp. Out</b>       | -1 | -1     | ... | 1  |
| <b>Out (DSP)</b>      | -1 | -1     | ... | 1  |
| <b>Exp. Out (DSP)</b> | -1 | -1     | ... | 1  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 60 |
| Max CPU cycles  | 73 |
| Avg CPU cycles  | 63 |

**Verification: Sign Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Sign.

| Test results          |    |        |     |    |
|-----------------------|----|--------|-----|----|
| <b>Time step</b>      | 1  | 2      | ... | 37 |
| <b>CPU cycles</b>     | 59 | 59     | ... | 61 |
| <i>Inputs</i>         |    |        |     |    |
| <b>In (DSP)</b>       | -1 | -0.944 | ... | 1  |
| <b>In</b>             | -1 | -0.944 | ... | 1  |
| <i>Outputs</i>        |    |        |     |    |
| <b>Out</b>            | -1 | -1     | ... | 1  |
| <b>Exp. Out</b>       | -1 | -1     | ... | 1  |
| <b>Out (DSP)</b>      | -1 | -1     | ... | 1  |
| <b>Exp. Out (DSP)</b> | -1 | -1     | ... | 1  |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 59 |
| Max CPU cycles  | 61 |
| Avg CPU cycles  | 60 |

## Block: Sin

---



Sine computation of input value.


| Inports  |                  |
|----------|------------------|
| In       | Input u          |
| Outports |                  |
| Out      | Result of sin(u) |

### Description:

Calculation:

$$\text{Out} = \sin(\text{In})$$

Error for 16 Bit Fixed Point Implementation:



### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | int8 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |



**Verification: Sin FiP16 CPU TMS320F28335****Date of Test** 2026-06-19**Target controller** TMS320F28335**Test case: Inport test****OK**

Inport test for Math block Sin.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 76     | 76     | 76     | 76     | ... | 76    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 0      | -0.048 | -0.095 | -0.142 | ... | 0     |
| <b>Exp. Out</b>       | -0     | -0.048 | -0.095 | -0.142 | ... | 0     |
| <b>Out (DSP)</b>      | 0      | -1558  | -3115  | -4662  | ... | 3     |
| <b>Exp. Out (DSP)</b> | 0      | -1559  | -3115  | -4663  | ... | 0     |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,2207\text{e-}04$ ( $\pm 4$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 76 |
| Max CPU cycles  | 76 |
| Avg CPU cycles  | 76 |

**Verification: Sin FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Sin.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 53     | 53     | 53     | 53     | ... | 53    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 0      | -0.048 | -0.095 | -0.142 | ... | 0     |
| <b>Exp. Out</b>       | -0     | -0.048 | -0.095 | -0.142 | ... | 0     |
| <b>Out (DSP)</b>      | 0      | -1558  | -3115  | -4662  | ... | 3     |
| <b>Exp. Out (DSP)</b> | 0      | -1559  | -3115  | -4663  | ... | 0     |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,2207\text{e-}04$ ( $\pm 4$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 53 |
| Max CPU cycles  | 53 |
| Avg CPU cycles  | 53 |

**Verification: Sin FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Sin.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 91     | 96     | 91     | 96     | ... | 91    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 0      | -0.048 | -0.095 | -0.142 | ... | 0     |
| <b>Exp. Out</b>       | -0     | -0.048 | -0.095 | -0.142 | ... | 0     |
| <b>Out (DSP)</b>      | 0      | -1558  | -3115  | -4662  | ... | 3     |
| <b>Exp. Out (DSP)</b> | 0      | -1559  | -3115  | -4663  | ... | 0     |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,2207\text{e-}04$ ( $\pm 4$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 91 |
| Max CPU cycles  | 96 |
| Avg CPU cycles  | 92 |

**Verification: Sin FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Sin.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 71     | 71     | 71     | 71     | ... | 71    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 0      | -0.048 | -0.095 | -0.142 | ... | 0     |
| <b>Exp. Out</b>       | -0     | -0.048 | -0.095 | -0.142 | ... | 0     |
| <b>Out (DSP)</b>      | 0      | -1558  | -3115  | -4662  | ... | 3     |
| <b>Exp. Out (DSP)</b> | 0      | -1559  | -3115  | -4663  | ... | 0     |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,2207\text{e-}04$ ( $\pm 4$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 71 |
| Max CPU cycles  | 71 |
| Avg CPU cycles  | 71 |

**Verification: Sin FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Sin.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 47     | 47     | 47     | 47     | ... | 47    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 0      | -0.048 | -0.095 | -0.142 | ... | 0     |
| <b>Exp. Out</b>       | -0     | -0.048 | -0.095 | -0.142 | ... | 0     |
| <b>Out (DSP)</b>      | 0      | -1558  | -3115  | -4662  | ... | 3     |
| <b>Exp. Out (DSP)</b> | 0      | -1559  | -3115  | -4663  | ... | 0     |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,2207\text{e-}04$ ( $\pm 4$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 47 |
| Max CPU cycles  | 47 |
| Avg CPU cycles  | 47 |

**Verification: Sin FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Sin.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 62     | 62     | 62     | 62     | ... | 62    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 0      | -0.048 | -0.095 | -0.142 | ... | 0     |
| <b>Exp. Out</b>       | -0     | -0.048 | -0.095 | -0.142 | ... | 0     |
| <b>Out (DSP)</b>      | 0      | -1558  | -3115  | -4662  | ... | 3     |
| <b>Exp. Out (DSP)</b> | 0      | -1559  | -3115  | -4663  | ... | 0     |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,2207\text{e-}04$ ( $\pm 4$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 62 |
| Avg CPU cycles  | 62 |

**Verification: Sin FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Sin.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 104    | 87     | 87     | 87     | ... | 87    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 0      | -0.048 | -0.095 | -0.142 | ... | 0     |
| <b>Exp. Out</b>       | -0     | -0.048 | -0.095 | -0.142 | ... | 0     |
| <b>Out (DSP)</b>      | 0      | -1558  | -3115  | -4662  | ... | 3     |
| <b>Exp. Out (DSP)</b> | 0      | -1559  | -3115  | -4663  | ... | 0     |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,2207\text{e-}04$ ( $\pm 4$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 87  |
| Max CPU cycles  | 104 |
| Avg CPU cycles  | 87  |

**Verification: Sin FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Sin.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 64     | 67     | 64     | 64     | ... | 64    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 0      | -0.048 | -0.095 | -0.142 | ... | 0     |
| <b>Exp. Out</b>       | -0     | -0.048 | -0.095 | -0.142 | ... | 0     |
| <b>Out (DSP)</b>      | 0      | -1558  | -3115  | -4662  | ... | 3     |
| <b>Exp. Out (DSP)</b> | 0      | -1559  | -3115  | -4663  | ... | 0     |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 1,2207\text{e-}04$ ( $\pm 4$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 64 |
| Max CPU cycles  | 67 |
| Avg CPU cycles  | 64 |



**Verification: Sin FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Sin.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 85          | 85          | ... | 85         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 0           | -0.048      | ... | 0          |
| <b>Exp. Out</b>       | -0          | -0.048      | ... | 0          |
| <b>Out (DSP)</b>      | 0           | -102179899  | ... | 3          |
| <b>Exp. Out (DSP)</b> | 0           | -102181386  | ... | 0          |

| Test settings |                                             |
|---------------|---------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}05$ ( $\pm 150000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 85 |
| Max CPU cycles  | 85 |
| Avg CPU cycles  | 85 |

**Verification: Sin FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Sin.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 53          | 53          | ... | 53         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 0           | -0.048      | ... | 0          |
| <b>Exp. Out</b>       | -0          | -0.048      | ... | 0          |
| <b>Out (DSP)</b>      | 0           | -102179899  | ... | 3          |
| <b>Exp. Out (DSP)</b> | 0           | -102181386  | ... | 0          |

| Test settings |                                             |
|---------------|---------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}05$ ( $\pm 150000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 53 |
| Max CPU cycles  | 53 |
| Avg CPU cycles  | 53 |

**Verification: Sin FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Sin.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 82          | 87          | ... | 87         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 0           | -0.048      | ... | 0          |
| <b>Exp. Out</b>       | -0          | -0.048      | ... | 0          |
| <b>Out (DSP)</b>      | 0           | -102179899  | ... | 3          |
| <b>Exp. Out (DSP)</b> | 0           | -102181386  | ... | 0          |

| Test settings |                                             |
|---------------|---------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}05$ ( $\pm 150000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 82 |
| Max CPU cycles  | 87 |
| Avg CPU cycles  | 84 |

**Verification: Sin FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Sin.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 147         | 147         | ... | 147        |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 0           | -0.048      | ... | 0          |
| <b>Exp. Out</b>       | -0          | -0.048      | ... | 0          |
| <b>Out (DSP)</b>      | 0           | -102179899  | ... | 3          |
| <b>Exp. Out (DSP)</b> | 0           | -102181386  | ... | 0          |

| Test settings |                                             |
|---------------|---------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}05$ ( $\pm 150000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 147 |
| Max CPU cycles  | 147 |
| Avg CPU cycles  | 147 |

**Verification: Sin FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Sin.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 50          | 51          | ... | 51         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 0           | -0.048      | ... | 0          |
| <b>Exp. Out</b>       | -0          | -0.048      | ... | 0          |
| <b>Out (DSP)</b>      | 0           | -102179899  | ... | 3          |
| <b>Exp. Out (DSP)</b> | 0           | -102181386  | ... | 0          |

| Test settings |                                             |
|---------------|---------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}05$ ( $\pm 150000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 50 |
| Max CPU cycles  | 51 |
| Avg CPU cycles  | 50 |

**Verification: Sin FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Sin.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 208         | 208         | ... | 208        |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 0           | -0.048      | ... | 0          |
| <b>Exp. Out</b>       | -0          | -0.048      | ... | 0          |
| <b>Out (DSP)</b>      | 0           | -102179899  | ... | 3          |
| <b>Exp. Out (DSP)</b> | 0           | -102181386  | ... | 0          |

| Test settings |                                             |
|---------------|---------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}05$ ( $\pm 150000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 201 |
| Max CPU cycles  | 208 |
| Avg CPU cycles  | 204 |

**Verification: Sin FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Sin.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 110         | 96          | ... | 96         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 0           | -0.048      | ... | 0          |
| <b>Exp. Out</b>       | -0          | -0.048      | ... | 0          |
| <b>Out (DSP)</b>      | 0           | -102179899  | ... | 3          |
| <b>Exp. Out (DSP)</b> | 0           | -102181386  | ... | 0          |

| Test settings |                                             |
|---------------|---------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}05$ ( $\pm 150000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 96  |
| Max CPU cycles  | 110 |
| Avg CPU cycles  | 96  |

**Verification: Sin FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Sin.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 73          | 73          | ... | 76         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 0           | -0.048      | ... | 0          |
| <b>Exp. Out</b>       | -0          | -0.048      | ... | 0          |
| <b>Out (DSP)</b>      | 0           | -102179899  | ... | 3          |
| <b>Exp. Out (DSP)</b> | 0           | -102181386  | ... | 0          |

| Test settings |                                             |
|---------------|---------------------------------------------|
| Tolerance Out | $\pm 6,9849\text{e-}05$ ( $\pm 150000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 73 |
| Max CPU cycles  | 76 |
| Avg CPU cycles  | 73 |



**Verification: Sin Float32 CPU TMS320F28335****Date of Test** 2026-06-19**Target controller** TMS320F28335**Test case: Inport test****OK**

Inport test for Math block Sin.

| Test results          |        |        |     |       |
|-----------------------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | ... | 133   |
| <b>CPU cycles</b>     | 211    | 211    | ... | 204   |
| <i>Inputs</i>         |        |        |     |       |
| <b>In (DSP)</b>       | -3.142 | -3.094 | ... | 3.142 |
| <b>In</b>             | -3.142 | -3.094 | ... | 3.142 |
| <i>Outputs</i>        |        |        |     |       |
| <b>Out</b>            | 0      | -0.048 | ... | -0    |
| <b>Exp. Out</b>       | -0     | -0.048 | ... | 0     |
| <b>Out (DSP)</b>      | 0      | -0.048 | ... | -0    |
| <b>Exp. Out (DSP)</b> | -0     | -0.048 | ... | 0     |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 1,3970\text{e-}07$ ( $\pm 300$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 204 |
| Max CPU cycles  | 211 |
| Avg CPU cycles  | 207 |

**Verification: Sin Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Sin.

| Test results          |        |        |     |       |
|-----------------------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | ... | 133   |
| <b>CPU cycles</b>     | 109    | 109    | ... | 109   |
| <i>Inputs</i>         |        |        |     |       |
| <b>In (DSP)</b>       | -3.142 | -3.094 | ... | 3.142 |
| <b>In</b>             | -3.142 | -3.094 | ... | 3.142 |
| <i>Outputs</i>        |        |        |     |       |
| <b>Out</b>            | 0      | -0.048 | ... | -0    |
| <b>Exp. Out</b>       | -0     | -0.048 | ... | 0     |
| <b>Out (DSP)</b>      | 0      | -0.048 | ... | -0    |
| <b>Exp. Out (DSP)</b> | -0     | -0.048 | ... | 0     |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 1,3970\text{e-}07$ ( $\pm 300$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 109 |
| Max CPU cycles  | 109 |
| Avg CPU cycles  | 109 |

**Verification: Sin Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Sin.

| Test results          |        |        |     |       |
|-----------------------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | ... | 133   |
| <b>CPU cycles</b>     | 513    | 468    | ... | 505   |
| <i>Inputs</i>         |        |        |     |       |
| <b>In (DSP)</b>       | -3.142 | -3.094 | ... | 3.142 |
| <b>In</b>             | -3.142 | -3.094 | ... | 3.142 |
| <i>Outputs</i>        |        |        |     |       |
| <b>Out</b>            | 0      | -0.048 | ... | -0    |
| <b>Exp. Out</b>       | -0     | -0.048 | ... | 0     |
| <b>Out (DSP)</b>      | 0      | -0.048 | ... | -0    |
| <b>Exp. Out (DSP)</b> | -0     | -0.048 | ... | 0     |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 1,3970\text{e-}07$ ( $\pm 300$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 134 |
| Max CPU cycles  | 513 |
| Avg CPU cycles  | 359 |

**Verification: Sin Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Sin.

| Test results          |        |        |     |       |
|-----------------------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | ... | 133   |
| <b>CPU cycles</b>     | 5410   | 4645   | ... | 5395  |
| <i>Inputs</i>         |        |        |     |       |
| <b>In (DSP)</b>       | -3.142 | -3.094 | ... | 3.142 |
| <b>In</b>             | -3.142 | -3.094 | ... | 3.142 |
| <i>Outputs</i>        |        |        |     |       |
| <b>Out</b>            | 0      | -0.048 | ... | -0    |
| <b>Exp. Out</b>       | -0     | -0.048 | ... | 0     |
| <b>Out (DSP)</b>      | 0      | -0.048 | ... | -0    |
| <b>Exp. Out (DSP)</b> | -0     | -0.048 | ... | 0     |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 1,3970\text{e-}07$ ( $\pm 300$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 148  |
| Max CPU cycles  | 5410 |
| Avg CPU cycles  | 3692 |

**Verification: Sin Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Sin.

| Test results          |        |        |     |       |
|-----------------------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | ... | 133   |
| <b>CPU cycles</b>     | 435    | 264    | ... | 435   |
| <i>Inputs</i>         |        |        |     |       |
| <b>In (DSP)</b>       | -3.142 | -3.094 | ... | 3.142 |
| <b>In</b>             | -3.142 | -3.094 | ... | 3.142 |
| <i>Outputs</i>        |        |        |     |       |
| <b>Out</b>            | 0      | -0.048 | ... | -0    |
| <b>Exp. Out</b>       | -0     | -0.048 | ... | 0     |
| <b>Out (DSP)</b>      | 0      | -0.048 | ... | -0    |
| <b>Exp. Out (DSP)</b> | -0     | -0.048 | ... | 0     |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,3970e-07$ ( $\pm 300$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 139 |
| Max CPU cycles  | 435 |
| Avg CPU cycles  | 214 |

**Verification: Sin Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Sin.

| Test results          |        |        |     |       |
|-----------------------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | ... | 133   |
| <b>CPU cycles</b>     | 2147   | 4037   | ... | 2147  |
| <i>Inputs</i>         |        |        |     |       |
| <b>In (DSP)</b>       | -3.142 | -3.094 | ... | 3.142 |
| <b>In</b>             | -3.142 | -3.094 | ... | 3.142 |
| <i>Outputs</i>        |        |        |     |       |
| <b>Out</b>            | 0      | -0.048 | ... | -0    |
| <b>Exp. Out</b>       | -0     | -0.048 | ... | 0     |
| <b>Out (DSP)</b>      | 0      | -0.048 | ... | -0    |
| <b>Exp. Out (DSP)</b> | -0     | -0.048 | ... | 0     |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 1,3970\text{e-}07$ ( $\pm 300$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 107  |
| Max CPU cycles  | 4037 |
| Avg CPU cycles  | 3330 |

**Verification: Sin Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Sin.

| Test results          |        |        |     |       |
|-----------------------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | ... | 133   |
| <b>CPU cycles</b>     | 524    | 332    | ... | 374   |
| <i>Inputs</i>         |        |        |     |       |
| <b>In (DSP)</b>       | -3.142 | -3.094 | ... | 3.142 |
| <b>In</b>             | -3.142 | -3.094 | ... | 3.142 |
| <i>Outputs</i>        |        |        |     |       |
| <b>Out</b>            | 0      | -0.048 | ... | -0    |
| <b>Exp. Out</b>       | -0     | -0.048 | ... | 0     |
| <b>Out (DSP)</b>      | 0      | -0.048 | ... | -0    |
| <b>Exp. Out (DSP)</b> | -0     | -0.048 | ... | 0     |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,3970e-07$ ( $\pm 300$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 111 |
| Max CPU cycles  | 524 |
| Avg CPU cycles  | 249 |

**Verification: Sin Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Sin.

| Test results          |        |        |     |       |
|-----------------------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | ... | 133   |
| <b>CPU cycles</b>     | 137    | 137    | ... | 133   |
| <i>Inputs</i>         |        |        |     |       |
| <b>In (DSP)</b>       | -3.142 | -3.094 | ... | 3.142 |
| <b>In</b>             | -3.142 | -3.094 | ... | 3.142 |
| <i>Outputs</i>        |        |        |     |       |
| <b>Out</b>            | 0      | -0.048 | ... | -0    |
| <b>Exp. Out</b>       | -0     | -0.048 | ... | 0     |
| <b>Out (DSP)</b>      | 0      | -0.048 | ... | -0    |
| <b>Exp. Out (DSP)</b> | -0     | -0.048 | ... | 0     |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 1,3970\text{e-}07$ ( $\pm 300$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 133 |
| Max CPU cycles  | 137 |
| Avg CPU cycles  | 135 |



# Block: Sqrt



Square root computation of absolute input value.


| Inports  |                     |
|----------|---------------------|
| In       | Input u             |
| Outports |                     |
| Out      | Result of sqrt( u ) |

## Description:

Calculation:

$$\text{Out} = \sqrt{|\text{In}|}$$

Error for 16 Bit Fixed Point Implementation:



## Implementations:

- FiP8** 8 Bit Fixed Point Implementation
- FiP16** 16 Bit Fixed Point Implementation
- FiP32** 32 Bit Fixed Point Implementation
- Float32** 32 Bit Floating Point Implementation
- Float64** 64 Bit Floating Point Implementation

## Implementation: FiP8

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In                | int8 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In                | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In                | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: Sqrt FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Sqrt.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 76     | 76     | 76     | 76     | ... | 76    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 1      | 0.992  | 0.985  | 0.977  | ... | 1     |
| <b>Exp. Out</b>       | 1      | 0.992  | 0.985  | 0.977  | ... | 1     |
| <b>Out (DSP)</b>      | 32767  | 32519  | 32267  | 32015  | ... | 32766 |
| <b>Exp. Out (DSP)</b> | 32767  | 32519  | 32268  | 32015  | ... | 32767 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,9673e-04$ ( $\pm 13$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 76 |
| Max CPU cycles  | 76 |
| Avg CPU cycles  | 76 |

## Verification: Sqrt FiP16 CPU TM4C123GH6

Date of Test 2026-06-19  
Target controller TM4C123GH6

### Test case: Inport test

OK

Inport test for Math block Sqrt.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 133   |
| CPU cycles     | 53     | 53     | 53     | 53     | ... | 53    |
| Inputs         |        |        |        |        |     |       |
| In (DSP)       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| In             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| Outputs        |        |        |        |        |     |       |
| Out            | 1      | 0.992  | 0.985  | 0.977  | ... | 1     |
| Exp. Out       | 1      | 0.992  | 0.985  | 0.977  | ... | 1     |
| Out (DSP)      | 32767  | 32519  | 32267  | 32015  | ... | 32766 |
| Exp. Out (DSP) | 32767  | 32519  | 32268  | 32015  | ... | 32767 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,9673e-04$ ( $\pm 13$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 53 |
| Max CPU cycles  | 53 |
| Avg CPU cycles  | 53 |

**Verification: Sqrt FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Sqrt.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 91     | 96     | 91     | 96     | ... | 91    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 1      | 0.992  | 0.985  | 0.977  | ... | 1     |
| <b>Exp. Out</b>       | 1      | 0.992  | 0.985  | 0.977  | ... | 1     |
| <b>Out (DSP)</b>      | 32767  | 32519  | 32267  | 32015  | ... | 32766 |
| <b>Exp. Out (DSP)</b> | 32767  | 32519  | 32268  | 32015  | ... | 32767 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,9673e-04$ ( $\pm 13$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 91 |
| Max CPU cycles  | 96 |
| Avg CPU cycles  | 92 |

**Verification: Sqrt FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Sqrt.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 71     | 71     | 71     | 71     | ... | 71    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 1      | 0.992  | 0.985  | 0.977  | ... | 1     |
| <b>Exp. Out</b>       | 1      | 0.992  | 0.985  | 0.977  | ... | 1     |
| <b>Out (DSP)</b>      | 32767  | 32519  | 32267  | 32015  | ... | 32766 |
| <b>Exp. Out (DSP)</b> | 32767  | 32519  | 32268  | 32015  | ... | 32767 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,9673e-04$ ( $\pm 13$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 71 |
| Max CPU cycles  | 71 |
| Avg CPU cycles  | 71 |

**Verification: Sqrt FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Sqrt.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 47     | 47     | 47     | 47     | ... | 47    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 1      | 0.992  | 0.985  | 0.977  | ... | 1     |
| <b>Exp. Out</b>       | 1      | 0.992  | 0.985  | 0.977  | ... | 1     |
| <b>Out (DSP)</b>      | 32767  | 32519  | 32267  | 32015  | ... | 32766 |
| <b>Exp. Out (DSP)</b> | 32767  | 32519  | 32268  | 32015  | ... | 32767 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,9673e-04$ ( $\pm 13$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 47 |
| Max CPU cycles  | 47 |
| Avg CPU cycles  | 47 |



**Verification: Sqrt FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Sqrt.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 62     | 62     | 62     | 62     | ... | 62    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 1      | 0.992  | 0.985  | 0.977  | ... | 1     |
| <b>Exp. Out</b>       | 1      | 0.992  | 0.985  | 0.977  | ... | 1     |
| <b>Out (DSP)</b>      | 32767  | 32519  | 32267  | 32015  | ... | 32766 |
| <b>Exp. Out (DSP)</b> | 32767  | 32519  | 32268  | 32015  | ... | 32767 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,9673e-04$ ( $\pm 13$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 62 |
| Avg CPU cycles  | 62 |

**Verification: Sqrt FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Sqrt.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 92     | 87     | 87     | 87     | ... | 87    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 1      | 0.992  | 0.985  | 0.977  | ... | 1     |
| <b>Exp. Out</b>       | 1      | 0.992  | 0.985  | 0.977  | ... | 1     |
| <b>Out (DSP)</b>      | 32767  | 32519  | 32267  | 32015  | ... | 32766 |
| <b>Exp. Out (DSP)</b> | 32767  | 32519  | 32268  | 32015  | ... | 32767 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,9673e-04$ ( $\pm 13$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 87 |
| Max CPU cycles  | 92 |
| Avg CPU cycles  | 87 |

**Verification: Sqrt FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Sqrt.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 133   |
| <b>CPU cycles</b>     | 67     | 64     | 64     | 64     | ... | 64    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In (DSP)</b>       | -32768 | -32272 | -31775 | -31279 | ... | 32767 |
| <b>In</b>             | -1     | -0.985 | -0.97  | -0.955 | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 1      | 0.992  | 0.985  | 0.977  | ... | 1     |
| <b>Exp. Out</b>       | 1      | 0.992  | 0.985  | 0.977  | ... | 1     |
| <b>Out (DSP)</b>      | 32767  | 32519  | 32267  | 32015  | ... | 32766 |
| <b>Exp. Out (DSP)</b> | 32767  | 32519  | 32268  | 32015  | ... | 32767 |

| Test settings |                                  |
|---------------|----------------------------------|
| Tolerance Out | $\pm 3,9673e-04$ ( $\pm 13$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 64 |
| Max CPU cycles  | 67 |
| Avg CPU cycles  | 64 |

**Verification: Sqrt FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Sqrt.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 85          | 85          | ... | 85         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 0.992       | ... | 1          |
| <b>Exp. Out</b>       | 1           | 0.992       | ... | 1          |
| <b>Out (DSP)</b>      | 2147483647  | 2131151785  | ... | 2147483646 |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2131152737  | ... | 2147483647 |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 3,1665e-04$ ( $\pm 680000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 85 |
| Max CPU cycles  | 85 |
| Avg CPU cycles  | 85 |

## Verification: Sqrt FiP32 CPU TM4C123GH6

Date of Test 2026-06-19  
Target controller TM4C123GH6

### Test case: Inport test

OK

Inport test for Math block Sqrt.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 133        |
| CPU cycles     | 53          | 53          | ... | 53         |
| Inputs         |             |             |     |            |
| In (DSP)       | -2147483648 | -2114946017 | ... | 2147483647 |
| In             | -1          | -0.985      | ... | 1          |
| Outputs        |             |             |     |            |
| Out            | 1           | 0.992       | ... | 1          |
| Exp. Out       | 1           | 0.992       | ... | 1          |
| Out (DSP)      | 2147483647  | 2131151785  | ... | 2147483646 |
| Exp. Out (DSP) | 2147483647  | 2131152737  | ... | 2147483647 |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 3,1665e-04$ ( $\pm 680000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 53 |
| Max CPU cycles  | 53 |
| Avg CPU cycles  | 53 |

**Verification: Sqrt FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Sqrt.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 91          | 96          | ... | 96         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 0.992       | ... | 1          |
| <b>Exp. Out</b>       | 1           | 0.992       | ... | 1          |
| <b>Out (DSP)</b>      | 2147483647  | 2131151785  | ... | 2147483646 |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2131152737  | ... | 2147483647 |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 3,1665e-04$ ( $\pm 680000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 91 |
| Max CPU cycles  | 96 |
| Avg CPU cycles  | 93 |

**Verification: Sqrt FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Sqrt.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 147         | 147         | ... | 147        |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 0.992       | ... | 1          |
| <b>Exp. Out</b>       | 1           | 0.992       | ... | 1          |
| <b>Out (DSP)</b>      | 2147483647  | 2131151785  | ... | 2147483646 |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2131152737  | ... | 2147483647 |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 3,1665e-04$ ( $\pm 680000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 147 |
| Max CPU cycles  | 147 |
| Avg CPU cycles  | 147 |

**Verification: Sqrt FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Sqrt.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 50          | 51          | ... | 51         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 0.992       | ... | 1          |
| <b>Exp. Out</b>       | 1           | 0.992       | ... | 1          |
| <b>Out (DSP)</b>      | 2147483647  | 2131151785  | ... | 2147483646 |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2131152737  | ... | 2147483647 |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 3,1665e-04$ ( $\pm 680000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 50 |
| Max CPU cycles  | 51 |
| Avg CPU cycles  | 50 |



**Verification: Sqrt FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Sqrt.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 208         | 208         | ... | 201        |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 0.992       | ... | 1          |
| <b>Exp. Out</b>       | 1           | 0.992       | ... | 1          |
| <b>Out (DSP)</b>      | 2147483647  | 2131151785  | ... | 2147483646 |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2131152737  | ... | 2147483647 |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 3,1665e-04$ ( $\pm 680000$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 201 |
| Max CPU cycles  | 208 |
| Avg CPU cycles  | 204 |

**Verification: Sqrt FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Sqrt.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 98          | 96          | ... | 98         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 0.992       | ... | 1          |
| <b>Exp. Out</b>       | 1           | 0.992       | ... | 1          |
| <b>Out (DSP)</b>      | 2147483647  | 2131151785  | ... | 2147483646 |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2131152737  | ... | 2147483647 |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 3,1665e-04$ ( $\pm 680000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 96 |
| Max CPU cycles  | 98 |
| Avg CPU cycles  | 96 |

**Verification: Sqrt FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Sqrt.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 133        |
| <b>CPU cycles</b>     | 73          | 73          | ... | 73         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In (DSP)</b>       | -2147483648 | -2114946017 | ... | 2147483647 |
| <b>In</b>             | -1          | -0.985      | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 1           | 0.992       | ... | 1          |
| <b>Exp. Out</b>       | 1           | 0.992       | ... | 1          |
| <b>Out (DSP)</b>      | 2147483647  | 2131151785  | ... | 2147483646 |
| <b>Exp. Out (DSP)</b> | 2147483647  | 2131152737  | ... | 2147483647 |

| Test settings |                                      |
|---------------|--------------------------------------|
| Tolerance Out | $\pm 3,1665e-04$ ( $\pm 680000$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 73 |
| Max CPU cycles  | 76 |
| Avg CPU cycles  | 73 |

## Verification: Sqrt Float32 CPU TMS320F28335

Date of Test 2026-06-19  
Target controller TMS320F28335

### Test case: Inport test

OK

Inport test for Math block Sqrt.

| Test results   |     |        |     |     |
|----------------|-----|--------|-----|-----|
| Time step      | 1   | 2      | ... | 133 |
| CPU cycles     | 180 | 180    | ... | 180 |
| Inputs         |     |        |     |     |
| In (DSP)       | -1  | -0.985 | ... | 1   |
| In             | -1  | -0.985 | ... | 1   |
| Outputs        |     |        |     |     |
| Out            | 1   | 0.992  | ... | 1   |
| Exp. Out       | 1   | 0.992  | ... | 1   |
| Out (DSP)      | 1   | 0.992  | ... | 1   |
| Exp. Out (DSP) | 1   | 0.992  | ... | 1   |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 9,3132\text{e-}08$ ( $\pm 200$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 112 |
| Max CPU cycles  | 180 |
| Avg CPU cycles  | 179 |

## Verification: Sqrt Float32 CPU TM4C123GH6

Date of Test 2026-06-19  
Target controller TM4C123GH6

### Test case: Inport test

OK

Inport test for Math block Sqrt.

| Test results   |    |        |     |     |
|----------------|----|--------|-----|-----|
| Time step      | 1  | 2      | ... | 133 |
| CPU cycles     | 63 | 63     | ... | 63  |
| Inputs         |    |        |     |     |
| In (DSP)       | -1 | -0.985 | ... | 1   |
| In             | -1 | -0.985 | ... | 1   |
| Outputs        |    |        |     |     |
| Out            | 1  | 0.992  | ... | 1   |
| Exp. Out       | 1  | 0.992  | ... | 1   |
| Out (DSP)      | 1  | 0.992  | ... | 1   |
| Exp. Out (DSP) | 1  | 0.992  | ... | 1   |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 9,3132\text{e-}08$ ( $\pm 200$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 63 |
| Max CPU cycles  | 63 |
| Avg CPU cycles  | 63 |

**Verification: Sqrt Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Sqrt.

| Test results          |    |        |     |     |
|-----------------------|----|--------|-----|-----|
| <b>Time step</b>      | 1  | 2      | ... | 133 |
| <b>CPU cycles</b>     | 88 | 88     | ... | 88  |
| <i>Inputs</i>         |    |        |     |     |
| <b>In (DSP)</b>       | -1 | -0.985 | ... | 1   |
| <b>In</b>             | -1 | -0.985 | ... | 1   |
| <i>Outputs</i>        |    |        |     |     |
| <b>Out</b>            | 1  | 0.992  | ... | 1   |
| <b>Exp. Out</b>       | 1  | 0.992  | ... | 1   |
| <b>Out (DSP)</b>      | 1  | 0.992  | ... | 1   |
| <b>Exp. Out (DSP)</b> | 1  | 0.992  | ... | 1   |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 9,3132e-08$ ( $\pm 200$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 88 |
| Max CPU cycles  | 88 |
| Avg CPU cycles  | 88 |

**Verification: Sqrt Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Sqrt.

| Test results          |     |        |     |     |
|-----------------------|-----|--------|-----|-----|
| <b>Time step</b>      | 1   | 2      | ... | 133 |
| <b>CPU cycles</b>     | 700 | 700    | ... | 697 |
| <i>Inputs</i>         |     |        |     |     |
| <b>In (DSP)</b>       | -1  | -0.985 | ... | 1   |
| <b>In</b>             | -1  | -0.985 | ... | 1   |
| <i>Outputs</i>        |     |        |     |     |
| <b>Out</b>            | 1   | 0.992  | ... | 1   |
| <b>Exp. Out</b>       | 1   | 0.992  | ... | 1   |
| <b>Out (DSP)</b>      | 1   | 0.992  | ... | 1   |
| <b>Exp. Out (DSP)</b> | 1   | 0.992  | ... | 1   |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 9,3132e-08$ ( $\pm 200$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 293 |
| Max CPU cycles  | 757 |
| Avg CPU cycles  | 696 |

**Verification: Sqrt Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Sqrt.

| Test results          |     |        |     |     |
|-----------------------|-----|--------|-----|-----|
| <b>Time step</b>      | 1   | 2      | ... | 133 |
| <b>CPU cycles</b>     | 316 | 361    | ... | 317 |
| <i>Inputs</i>         |     |        |     |     |
| <b>In (DSP)</b>       | -1  | -0.985 | ... | 1   |
| <b>In</b>             | -1  | -0.985 | ... | 1   |
| <i>Outputs</i>        |     |        |     |     |
| <b>Out</b>            | 1   | 0.992  | ... | 1   |
| <b>Exp. Out</b>       | 1   | 0.992  | ... | 1   |
| <b>Out (DSP)</b>      | 1   | 0.992  | ... | 1   |
| <b>Exp. Out (DSP)</b> | 1   | 0.992  | ... | 1   |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 9,3132\text{e-}08$ ( $\pm 200$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 115 |
| Max CPU cycles  | 385 |
| Avg CPU cycles  | 348 |



**Verification: Sqrt Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Sqrt.

| Test results          |     |        |     |     |
|-----------------------|-----|--------|-----|-----|
| <b>Time step</b>      | 1   | 2      | ... | 133 |
| <b>CPU cycles</b>     | 718 | 736    | ... | 724 |
| <i>Inputs</i>         |     |        |     |     |
| <b>In (DSP)</b>       | -1  | -0.985 | ... | 1   |
| <b>In</b>             | -1  | -0.985 | ... | 1   |
| <i>Outputs</i>        |     |        |     |     |
| <b>Out</b>            | 1   | 0.992  | ... | 1   |
| <b>Exp. Out</b>       | 1   | 0.992  | ... | 1   |
| <b>Out (DSP)</b>      | 1   | 0.992  | ... | 1   |
| <b>Exp. Out (DSP)</b> | 1   | 0.992  | ... | 1   |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 9,3132e-08$ ( $\pm 200$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 209 |
| Max CPU cycles  | 746 |
| Avg CPU cycles  | 730 |

**Verification: Sqrt Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Sqrt.

| Test results          |    |        |     |     |
|-----------------------|----|--------|-----|-----|
| <b>Time step</b>      | 1  | 2      | ... | 133 |
| <b>CPU cycles</b>     | 87 | 77     | ... | 77  |
| <i>Inputs</i>         |    |        |     |     |
| <b>In (DSP)</b>       | -1 | -0.985 | ... | 1   |
| <b>In</b>             | -1 | -0.985 | ... | 1   |
| <i>Outputs</i>        |    |        |     |     |
| <b>Out</b>            | 1  | 0.992  | ... | 1   |
| <b>Exp. Out</b>       | 1  | 0.992  | ... | 1   |
| <b>Out (DSP)</b>      | 1  | 0.992  | ... | 1   |
| <b>Exp. Out (DSP)</b> | 1  | 0.992  | ... | 1   |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 9,3132e-08$ ( $\pm 200$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 77 |
| Max CPU cycles  | 87 |
| Avg CPU cycles  | 77 |

**Verification: Sqrt Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Sqrt.

| Test results          |     |        |     |     |
|-----------------------|-----|--------|-----|-----|
| <b>Time step</b>      | 1   | 2      | ... | 133 |
| <b>CPU cycles</b>     | 140 | 140    | ... | 140 |
| <i>Inputs</i>         |     |        |     |     |
| <b>In (DSP)</b>       | -1  | -0.985 | ... | 1   |
| <b>In</b>             | -1  | -0.985 | ... | 1   |
| <i>Outputs</i>        |     |        |     |     |
| <b>Out</b>            | 1   | 0.992  | ... | 1   |
| <b>Exp. Out</b>       | 1   | 0.992  | ... | 1   |
| <b>Out (DSP)</b>      | 1   | 0.992  | ... | 1   |
| <b>Exp. Out (DSP)</b> | 1   | 0.992  | ... | 1   |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 9,3132e-08$ ( $\pm 200$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 105 |
| Max CPU cycles  | 140 |
| Avg CPU cycles  | 139 |

## Block: Sub

---



Subtraction of input Minus from input Plus.

| Inports |            |
|---------|------------|
| Plus    | Minuend    |
| Minus   | Subtrahend |

| Outports |            |
|----------|------------|
| Out      | Difference |

### Description:

Calculation:

$$\text{Out} = \text{Plus} - \text{Minus}$$

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| Plus              | int8 |
| Minus             | int8 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| Plus              | int16 |
| Minus             | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| Plus              | int32 |
| Minus             | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| Plus              | float32 |
| Minus             | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| Plus              | float64 |
| Minus             | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: Sub FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Sub.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 68     | 68     | 68     | 68     | ... | 68    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>Plus (DSP)</b>     | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>Minus (DSP)</b>    | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>Plus</b>           | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Minus</b>          | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -1     | -1     | -1     | -1     | ... | 0     |
| <b>Exp. Out</b>       | -1     | -1     | -1     | -1     | ... | 0     |
| <b>Out (DSP)</b>      | -32767 | -32767 | -32767 | -32767 | ... | 0     |
| <b>Exp. Out (DSP)</b> | -32768 | -32768 | -32768 | -32768 | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 64 |
| Max CPU cycles  | 68 |
| Avg CPU cycles  | 67 |

**Verification: Sub FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Sub.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 37     | 37     | 37     | 37     | ... | 37    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>Plus (DSP)</b>     | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>Minus (DSP)</b>    | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>Plus</b>           | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Minus</b>          | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -1     | -1     | -1     | -1     | ... | 0     |
| <b>Exp. Out</b>       | -1     | -1     | -1     | -1     | ... | 0     |
| <b>Out (DSP)</b>      | -32767 | -32767 | -32767 | -32767 | ... | 0     |
| <b>Exp. Out (DSP)</b> | -32768 | -32768 | -32768 | -32768 | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 31 |
| Max CPU cycles  | 37 |
| Avg CPU cycles  | 36 |

**Verification: Sub FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Sub.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 77     | 77     | 77     | 77     | ... | 77    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>Plus (DSP)</b>     | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>Minus (DSP)</b>    | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>Plus</b>           | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Minus</b>          | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -1     | -1     | -1     | -1     | ... | 0     |
| <b>Exp. Out</b>       | -1     | -1     | -1     | -1     | ... | 0     |
| <b>Out (DSP)</b>      | -32767 | -32767 | -32767 | -32767 | ... | 0     |
| <b>Exp. Out (DSP)</b> | -32768 | -32768 | -32768 | -32768 | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 77 |
| Max CPU cycles  | 77 |
| Avg CPU cycles  | 77 |



**Verification: Sub FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Sub.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 65     | 65     | 65     | 65     | ... | 66    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>Plus (DSP)</b>     | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>Minus (DSP)</b>    | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>Plus</b>           | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Minus</b>          | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -1     | -1     | -1     | -1     | ... | 0     |
| <b>Exp. Out</b>       | -1     | -1     | -1     | -1     | ... | 0     |
| <b>Out (DSP)</b>      | -32767 | -32767 | -32767 | -32767 | ... | 0     |
| <b>Exp. Out (DSP)</b> | -32768 | -32768 | -32768 | -32768 | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 65 |
| Max CPU cycles  | 67 |
| Avg CPU cycles  | 66 |

**Verification: Sub FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Sub.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 39     | 39     | 39     | 39     | ... | 39    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>Plus (DSP)</b>     | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>Minus (DSP)</b>    | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>Plus</b>           | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Minus</b>          | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -1     | -1     | -1     | -1     | ... | 0     |
| <b>Exp. Out</b>       | -1     | -1     | -1     | -1     | ... | 0     |
| <b>Out (DSP)</b>      | -32767 | -32767 | -32767 | -32767 | ... | 0     |
| <b>Exp. Out (DSP)</b> | -32768 | -32768 | -32768 | -32768 | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 39 |
| Max CPU cycles  | 39 |
| Avg CPU cycles  | 39 |

**Verification: Sub FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Sub.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 58     | 58     | 58     | 58     | ... | 59    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>Plus (DSP)</b>     | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>Minus (DSP)</b>    | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>Plus</b>           | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Minus</b>          | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -1     | -1     | -1     | -1     | ... | 0     |
| <b>Exp. Out</b>       | -1     | -1     | -1     | -1     | ... | 0     |
| <b>Out (DSP)</b>      | -32767 | -32767 | -32767 | -32767 | ... | 0     |
| <b>Exp. Out (DSP)</b> | -32768 | -32768 | -32768 | -32768 | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 58 |
| Max CPU cycles  | 59 |
| Avg CPU cycles  | 58 |

**Verification: Sub FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Sub.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 85     | 69     | 69     | 69     | ... | 69    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>Plus (DSP)</b>     | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>Minus (DSP)</b>    | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>Plus</b>           | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Minus</b>          | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -1     | -1     | -1     | -1     | ... | 0     |
| <b>Exp. Out</b>       | -1     | -1     | -1     | -1     | ... | 0     |
| <b>Out (DSP)</b>      | -32767 | -32767 | -32767 | -32767 | ... | 0     |
| <b>Exp. Out (DSP)</b> | -32768 | -32768 | -32768 | -32768 | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 69 |
| Max CPU cycles  | 85 |
| Avg CPU cycles  | 69 |

**Verification: Sub FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Sub.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 65     | 65     | 65     | 65     | ... | 65    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>Plus (DSP)</b>     | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>Minus (DSP)</b>    | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>Plus</b>           | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Minus</b>          | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -1     | -1     | -1     | -1     | ... | 0     |
| <b>Exp. Out</b>       | -1     | -1     | -1     | -1     | ... | 0     |
| <b>Out (DSP)</b>      | -32767 | -32767 | -32767 | -32767 | ... | 0     |
| <b>Exp. Out (DSP)</b> | -32768 | -32768 | -32768 | -32768 | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 63 |
| Max CPU cycles  | 65 |
| Avg CPU cycles  | 64 |

**Verification: Sub FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Sub.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 165         | 165         | ... | 159        |
| <i>Inputs</i>         |             |             |     |            |
| <b>Plus (DSP)</b>     | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>Minus (DSP)</b>    | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>Plus</b>           | -1          | -0.981      | ... | 1          |
| <b>Minus</b>          | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -1          | -1          | ... | 0          |
| <b>Exp. Out</b>       | -1          | -1          | ... | 0          |
| <b>Out (DSP)</b>      | -2147483647 | -2147483647 | ... | 0          |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2147483648 | ... | 0          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 112 |
| Max CPU cycles  | 165 |
| Avg CPU cycles  | 153 |

**Verification: Sub FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Sub.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 59          | 59          | ... | 55         |
| <i>Inputs</i>         |             |             |     |            |
| <b>Plus (DSP)</b>     | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>Minus (DSP)</b>    | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>Plus</b>           | -1          | -0.981      | ... | 1          |
| <b>Minus</b>          | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -1          | -1          | ... | 0          |
| <b>Exp. Out</b>       | -1          | -1          | ... | 0          |
| <b>Out (DSP)</b>      | -2147483647 | -2147483647 | ... | 0          |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2147483648 | ... | 0          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 49 |
| Max CPU cycles  | 59 |
| Avg CPU cycles  | 54 |

**Verification: Sub FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Sub.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 82          | 82          | ... | 82         |
| <i>Inputs</i>         |             |             |     |            |
| <b>Plus (DSP)</b>     | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>Minus (DSP)</b>    | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>Plus</b>           | -1          | -0.981      | ... | 1          |
| <b>Minus</b>          | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -1          | -1          | ... | 0          |
| <b>Exp. Out</b>       | -1          | -1          | ... | 0          |
| <b>Out (DSP)</b>      | -2147483647 | -2147483647 | ... | 0          |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2147483648 | ... | 0          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 82 |
| Max CPU cycles  | 82 |
| Avg CPU cycles  | 82 |



**Verification: Sub FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Sub.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 82          | 82          | ... | 81         |
| <i>Inputs</i>         |             |             |     |            |
| <b>Plus (DSP)</b>     | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>Minus (DSP)</b>    | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>Plus</b>           | -1          | -0.981      | ... | 1          |
| <b>Minus</b>          | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -1          | -1          | ... | 0          |
| <b>Exp. Out</b>       | -1          | -1          | ... | 0          |
| <b>Out (DSP)</b>      | -2147483647 | -2147483647 | ... | 0          |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2147483648 | ... | 0          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 81  |
| Max CPU cycles  | 138 |
| Avg CPU cycles  | 83  |

**Verification: Sub FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Sub.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 51          | 51          | ... | 48         |
| <i>Inputs</i>         |             |             |     |            |
| <b>Plus (DSP)</b>     | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>Minus (DSP)</b>    | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>Plus</b>           | -1          | -0.981      | ... | 1          |
| <b>Minus</b>          | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -1          | -1          | ... | 0          |
| <b>Exp. Out</b>       | -1          | -1          | ... | 0          |
| <b>Out (DSP)</b>      | -2147483647 | -2147483647 | ... | 0          |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2147483648 | ... | 0          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 48 |
| Max CPU cycles  | 51 |
| Avg CPU cycles  | 48 |

**Verification: Sub FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Sub.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 82          | 82          | ... | 81         |
| <i>Inputs</i>         |             |             |     |            |
| <b>Plus (DSP)</b>     | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>Minus (DSP)</b>    | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>Plus</b>           | -1          | -0.981      | ... | 1          |
| <b>Minus</b>          | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -1          | -1          | ... | 0          |
| <b>Exp. Out</b>       | -1          | -1          | ... | 0          |
| <b>Out (DSP)</b>      | -2147483647 | -2147483647 | ... | 0          |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2147483648 | ... | 0          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 81 |
| Max CPU cycles  | 82 |
| Avg CPU cycles  | 81 |

**Verification: Sub FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Sub.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 99          | 92          | ... | 92         |
| <i>Inputs</i>         |             |             |     |            |
| <b>Plus (DSP)</b>     | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>Minus (DSP)</b>    | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>Plus</b>           | -1          | -0.981      | ... | 1          |
| <b>Minus</b>          | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -1          | -1          | ... | 0          |
| <b>Exp. Out</b>       | -1          | -1          | ... | 0          |
| <b>Out (DSP)</b>      | -2147483647 | -2147483647 | ... | 0          |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2147483648 | ... | 0          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 92 |
| Max CPU cycles  | 99 |
| Avg CPU cycles  | 92 |

**Verification: Sub FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Sub.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 152         | 152         | ... | 150        |
| <i>Inputs</i>         |             |             |     |            |
| <b>Plus (DSP)</b>     | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>Minus (DSP)</b>    | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>Plus</b>           | -1          | -0.981      | ... | 1          |
| <b>Minus</b>          | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -1          | -1          | ... | 0          |
| <b>Exp. Out</b>       | -1          | -1          | ... | 0          |
| <b>Out (DSP)</b>      | -2147483647 | -2147483647 | ... | 0          |
| <b>Exp. Out (DSP)</b> | -2147483648 | -2147483648 | ... | 0          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 110 |
| Max CPU cycles  | 152 |
| Avg CPU cycles  | 145 |

**Verification: Sub Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Sub.

| Test results          |    |        |     |     |
|-----------------------|----|--------|-----|-----|
| <b>Time step</b>      | 1  | 2      | ... | 214 |
| <b>CPU cycles</b>     | 53 | 53     | ... | 53  |
| <i>Inputs</i>         |    |        |     |     |
| <b>Plus (DSP)</b>     | -2 | -1.962 | ... | 2   |
| <b>Minus (DSP)</b>    | 2  | 1.962  | ... | 2   |
| <b>Plus</b>           | -2 | -1.962 | ... | 2   |
| <b>Minus</b>          | 2  | 1.962  | ... | 2   |
| <i>Outputs</i>        |    |        |     |     |
| <b>Out</b>            | -4 | -3.925 | ... | 0   |
| <b>Exp. Out</b>       | -4 | -3.925 | ... | 0   |
| <b>Out (DSP)</b>      | -4 | -3.925 | ... | 0   |
| <b>Exp. Out (DSP)</b> | -4 | -3.925 | ... | 0   |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,8626e-07$ ( $\pm 400$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 53 |
| Max CPU cycles  | 53 |
| Avg CPU cycles  | 53 |

**Verification: Sub Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Sub.

| Test results          |    |        |     |     |
|-----------------------|----|--------|-----|-----|
| <b>Time step</b>      | 1  | 2      | ... | 214 |
| <b>CPU cycles</b>     | 29 | 29     | ... | 29  |
| <i>Inputs</i>         |    |        |     |     |
| <b>Plus (DSP)</b>     | -2 | -1.962 | ... | 2   |
| <b>Minus (DSP)</b>    | 2  | 1.962  | ... | 2   |
| <b>Plus</b>           | -2 | -1.962 | ... | 2   |
| <b>Minus</b>          | 2  | 1.962  | ... | 2   |
| <i>Outputs</i>        |    |        |     |     |
| <b>Out</b>            | -4 | -3.925 | ... | 0   |
| <b>Exp. Out</b>       | -4 | -3.925 | ... | 0   |
| <b>Out (DSP)</b>      | -4 | -3.925 | ... | 0   |
| <b>Exp. Out (DSP)</b> | -4 | -3.925 | ... | 0   |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,8626e-07$ ( $\pm 400$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 29 |
| Max CPU cycles  | 29 |
| Avg CPU cycles  | 29 |

**Verification: Sub Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Sub.

| Test results          |    |        |     |     |
|-----------------------|----|--------|-----|-----|
| <b>Time step</b>      | 1  | 2      | ... | 214 |
| <b>CPU cycles</b>     | 62 | 62     | ... | 62  |
| <i>Inputs</i>         |    |        |     |     |
| <b>Plus (DSP)</b>     | -2 | -1.962 | ... | 2   |
| <b>Minus (DSP)</b>    | 2  | 1.962  | ... | 2   |
| <b>Plus</b>           | -2 | -1.962 | ... | 2   |
| <b>Minus</b>          | 2  | 1.962  | ... | 2   |
| <i>Outputs</i>        |    |        |     |     |
| <b>Out</b>            | -4 | -3.925 | ... | 0   |
| <b>Exp. Out</b>       | -4 | -3.925 | ... | 0   |
| <b>Out (DSP)</b>      | -4 | -3.925 | ... | 0   |
| <b>Exp. Out (DSP)</b> | -4 | -3.925 | ... | 0   |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,8626e-07$ ( $\pm 400$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 62 |
| Max CPU cycles  | 62 |
| Avg CPU cycles  | 62 |



**Verification: Sub Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block Sub.

| Test results          |     |        |     |     |
|-----------------------|-----|--------|-----|-----|
| <b>Time step</b>      | 1   | 2      | ... | 214 |
| <b>CPU cycles</b>     | 158 | 158    | ... | 152 |
| <i>Inputs</i>         |     |        |     |     |
| <b>Plus (DSP)</b>     | -2  | -1.962 | ... | 2   |
| <b>Minus (DSP)</b>    | 2   | 1.962  | ... | 2   |
| <b>Plus</b>           | -2  | -1.962 | ... | 2   |
| <b>Minus</b>          | 2   | 1.962  | ... | 2   |
| <i>Outputs</i>        |     |        |     |     |
| <b>Out</b>            | -4  | -3.925 | ... | 0   |
| <b>Exp. Out</b>       | -4  | -3.925 | ... | 0   |
| <b>Out (DSP)</b>      | -4  | -3.925 | ... | 0   |
| <b>Exp. Out (DSP)</b> | -4  | -3.925 | ... | 0   |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,8626e-07$ ( $\pm 400$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 152 |
| Max CPU cycles  | 158 |
| Avg CPU cycles  | 155 |

**Verification: Sub Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Sub.

| Test results          |     |        |     |     |
|-----------------------|-----|--------|-----|-----|
| <b>Time step</b>      | 1   | 2      | ... | 214 |
| <b>CPU cycles</b>     | 104 | 104    | ... | 88  |
| <i>Inputs</i>         |     |        |     |     |
| <b>Plus (DSP)</b>     | -2  | -1.962 | ... | 2   |
| <b>Minus (DSP)</b>    | 2   | 1.962  | ... | 2   |
| <b>Plus</b>           | -2  | -1.962 | ... | 2   |
| <b>Minus</b>          | 2   | 1.962  | ... | 2   |
| <i>Outputs</i>        |     |        |     |     |
| <b>Out</b>            | -4  | -3.925 | ... | 0   |
| <b>Exp. Out</b>       | -4  | -3.925 | ... | 0   |
| <b>Out (DSP)</b>      | -4  | -3.925 | ... | 0   |
| <b>Exp. Out (DSP)</b> | -4  | -3.925 | ... | 0   |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,8626e-07$ ( $\pm 400$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 80  |
| Max CPU cycles  | 104 |
| Avg CPU cycles  | 95  |

**Verification: Sub Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block Sub.

| Test results          |     |        |     |     |
|-----------------------|-----|--------|-----|-----|
| <b>Time step</b>      | 1   | 2      | ... | 214 |
| <b>CPU cycles</b>     | 204 | 204    | ... | 241 |
| <i>Inputs</i>         |     |        |     |     |
| <b>Plus (DSP)</b>     | -2  | -1.962 | ... | 2   |
| <b>Minus (DSP)</b>    | 2   | 1.962  | ... | 2   |
| <b>Plus</b>           | -2  | -1.962 | ... | 2   |
| <b>Minus</b>          | 2   | 1.962  | ... | 2   |
| <i>Outputs</i>        |     |        |     |     |
| <b>Out</b>            | -4  | -3.925 | ... | 0   |
| <b>Exp. Out</b>       | -4  | -3.925 | ... | 0   |
| <b>Out (DSP)</b>      | -4  | -3.925 | ... | 0   |
| <b>Exp. Out (DSP)</b> | -4  | -3.925 | ... | 0   |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,8626e-07$ ( $\pm 400$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 204 |
| Max CPU cycles  | 241 |
| Avg CPU cycles  | 222 |

**Verification: Sub Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block Sub.

| Test results          |    |        |     |     |
|-----------------------|----|--------|-----|-----|
| <b>Time step</b>      | 1  | 2      | ... | 214 |
| <b>CPU cycles</b>     | 57 | 57     | ... | 57  |
| <i>Inputs</i>         |    |        |     |     |
| <b>Plus (DSP)</b>     | -2 | -1.962 | ... | 2   |
| <b>Minus (DSP)</b>    | 2  | 1.962  | ... | 2   |
| <b>Plus</b>           | -2 | -1.962 | ... | 2   |
| <b>Minus</b>          | 2  | 1.962  | ... | 2   |
| <i>Outputs</i>        |    |        |     |     |
| <b>Out</b>            | -4 | -3.925 | ... | 0   |
| <b>Exp. Out</b>       | -4 | -3.925 | ... | 0   |
| <b>Out (DSP)</b>      | -4 | -3.925 | ... | 0   |
| <b>Exp. Out (DSP)</b> | -4 | -3.925 | ... | 0   |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,8626e-07$ ( $\pm 400$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 57 |

**Verification: Sub Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block Sub.


| Test results          |    |        |     |     |
|-----------------------|----|--------|-----|-----|
| <b>Time step</b>      | 1  | 2      | ... | 214 |
| <b>CPU cycles</b>     | 50 | 50     | ... | 50  |
| <i>Inputs</i>         |    |        |     |     |
| <b>Plus (DSP)</b>     | -2 | -1.962 | ... | 2   |
| <b>Minus (DSP)</b>    | 2  | 1.962  | ... | 2   |
| <b>Plus</b>           | -2 | -1.962 | ... | 2   |
| <b>Minus</b>          | 2  | 1.962  | ... | 2   |
| <i>Outputs</i>        |    |        |     |     |
| <b>Out</b>            | -4 | -3.925 | ... | 0   |
| <b>Exp. Out</b>       | -4 | -3.925 | ... | 0   |
| <b>Out (DSP)</b>      | -4 | -3.925 | ... | 0   |
| <b>Exp. Out (DSP)</b> | -4 | -3.925 | ... | 0   |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,8626e-07$ ( $\pm 400$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 50 |
| Max CPU cycles  | 50 |
| Avg CPU cycles  | 50 |

## Block: Sum

---



Sum of inputs:

+ ... Input will be added to result.

- ... Input will be subtracted from result.

0 ... Input will be ignored.

| Inports |          |
|---------|----------|
| In1     | Input #1 |
| In2     | Input #2 |
| In3     | Input #3 |
| In4     | Input #4 |
| In5     | Input #5 |
| In6     | Input #6 |
| In7     | Input #7 |
| In8     | Input #8 |

| Outports |        |
|----------|--------|
| Out      | Result |

| Mask Parameters |    |             |
|-----------------|----|-------------|
| Name            | ID | Description |
| In1             | 1  | Input #1    |
| In2             | 2  | Input #2    |
| In3             | 3  | Input #3    |
| In4             | 4  | Input #4    |
| In5             | 5  | Input #5    |
| In6             | 6  | Input #6    |
| In7             | 7  | Input #7    |
| In8             | 8  | Input #8    |

**Implementations:**

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

**Implementation: FiP8**

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In1               | int8 |
| In2               | int8 |
| In3               | int8 |
| In4               | int8 |
| In5               | int8 |
| In6               | int8 |
| In7               | int8 |
| In8               | int8 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

**Implementation: FiP16**

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In1               | int16 |
| In2               | int16 |
| In3               | int16 |
| In4               | int16 |
| In5               | int16 |
| In6               | int16 |
| In7               | int16 |
| In8               | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

---

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In1               | int32 |
| In2               | int32 |
| In3               | int32 |
| In4               | int32 |
| In5               | int32 |
| In6               | int32 |
| In7               | int32 |
| In8               | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

---

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In1               | float32 |
| In2               | float32 |
| In3               | float32 |
| In4               | float32 |
| In5               | float32 |
| In6               | float32 |
| In7               | float32 |
| In8               | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

---

64 Bit Floating Point Implementation



| Inports Data Type |         |
|-------------------|---------|
| In1               | float64 |
| In2               | float64 |
| In3               | float64 |
| In4               | float64 |
| In5               | float64 |
| In6               | float64 |
| In7               | float64 |
| In8               | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: Sum FiP16 CPU TMS320F28335**

---

**Date of Test** 2026-06-19

**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Sum.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 74    |
| CPU cycles     | 222    | 222    | 222    | 222    | ... | 222   |
| Inputs         |        |        |        |        |     |       |
| In1 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In2 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In3 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In4 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In5 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In6 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In7 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In8 (DSP)      | -32768 | -31870 | -30972 | -30075 | ... | 32767 |
| In1            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In2            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In3            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In4            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In5            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In6            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In7            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In8            | -1     | -0.973 | -0.945 | -0.918 | ... | 1     |
| Parameters     |        |        |        |        |     |       |
| In1            | +      |        |        |        |     |       |
| In2            | +      |        |        |        |     |       |
| In3            | +      |        |        |        |     |       |
| In4            | -      |        |        |        |     |       |
| In5            | -      |        |        |        |     |       |
| In6            | -      |        |        |        |     |       |
| In7            | 0      |        |        |        |     |       |
| In8            | +      |        |        |        |     |       |
| Outputs        |        |        |        |        |     |       |
| Out            | -1     | -0.973 | -0.945 | -0.918 | ... | 1     |
| Exp. Out       | -1     | -0.973 | -0.945 | -0.918 | ... | 1     |
| Out (DSP)      | -32767 | -31870 | -30972 | -30075 | ... | 32767 |
| Exp. Out (DSP) | -32768 | -31870 | -30972 | -30075 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 222 |
| Max CPU cycles  | 222 |
| Avg CPU cycles  | 222 |

#### Test case: Conversion test

OK

Conversion test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| In1                          | +     | -     | 0 |
| In2                          | +     | -     | 0 |
| In3                          | +     | -     | 0 |
| In4                          | +     | -     | 0 |
| In5                          | +     | -     | 0 |
| In6                          | +     | -     | 0 |
| In7                          | +     | -     | 0 |
| In8                          | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| sign                         | 21845 | 43690 | 0 |
| Exp. sign                    | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Math block Sum.

| Test results          |       |       |   |
|-----------------------|-------|-------|---|
| Time step             | 1     | 2     | 3 |
| Mask parameters       |       |       |   |
| In1                   | +     | -     | 0 |
| In2                   | +     | -     | 0 |
| In3                   | +     | -     | 0 |
| In4                   | +     | -     | 0 |
| In5                   | +     | -     | 0 |
| In6                   | +     | -     | 0 |
| In7                   | +     | -     | 0 |
| In8                   | +     | -     | 0 |
| Controller parameters |       |       |   |
| sign                  | 21845 | 43690 | 0 |
| Exp. sign             | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 676 |
| Max CPU cycles  | 714 |
| Avg CPU cycles  | 690 |

**Verification: Sum FiP16 CPU TM4C123GH6**

---

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block Sum.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 74    |
| CPU cycles     | 129    | 127    | 127    | 127    | ... | 127   |
| Inputs         |        |        |        |        |     |       |
| In1 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In2 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In3 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In4 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In5 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In6 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In7 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In8 (DSP)      | -32768 | -31870 | -30972 | -30075 | ... | 32767 |
| In1            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In2            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In3            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In4            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In5            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In6            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In7            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In8            | -1     | -0.973 | -0.945 | -0.918 | ... | 1     |
| Parameters     |        |        |        |        |     |       |
| In1            | +      |        |        |        |     |       |
| In2            | +      |        |        |        |     |       |
| In3            | +      |        |        |        |     |       |
| In4            | -      |        |        |        |     |       |
| In5            | -      |        |        |        |     |       |
| In6            | -      |        |        |        |     |       |
| In7            | 0      |        |        |        |     |       |
| In8            | +      |        |        |        |     |       |
| Outputs        |        |        |        |        |     |       |
| Out            | -1     | -0.973 | -0.945 | -0.918 | ... | 1     |
| Exp. Out       | -1     | -0.973 | -0.945 | -0.918 | ... | 1     |
| Out (DSP)      | -32767 | -31870 | -30972 | -30075 | ... | 32767 |
| Exp. Out (DSP) | -32768 | -31870 | -30972 | -30075 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 127 |
| Max CPU cycles  | 129 |
| Avg CPU cycles  | 127 |

#### Test case: Conversion test

OK

Conversion test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| In1                          | +     | -     | 0 |
| In2                          | +     | -     | 0 |
| In3                          | +     | -     | 0 |
| In4                          | +     | -     | 0 |
| In5                          | +     | -     | 0 |
| In6                          | +     | -     | 0 |
| In7                          | +     | -     | 0 |
| In8                          | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| sign                         | 21845 | 43690 | 0 |
| Exp. sign                    | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Math block Sum.



| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| <b>In1</b>                   | +     | -     | 0 |
| <b>In2</b>                   | +     | -     | 0 |
| <b>In3</b>                   | +     | -     | 0 |
| <b>In4</b>                   | +     | -     | 0 |
| <b>In5</b>                   | +     | -     | 0 |
| <b>In6</b>                   | +     | -     | 0 |
| <b>In7</b>                   | +     | -     | 0 |
| <b>In8</b>                   | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| <b>sign</b>                  | 21845 | 43690 | 0 |
| <b>Exp. sign</b>             | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 333 |
| Max CPU cycles  | 357 |
| Avg CPU cycles  | 341 |

**Verification: Sum FiP16 CPU STM32G474RE**

---

**Date of Test** 2026-06-19**Target controller** STM32G474RE**Test case: Inport test****OK**

Inport test for Math block Sum.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 74    |
| CPU cycles     | 245    | 245    | 245    | 245    | ... | 245   |
| Inputs         |        |        |        |        |     |       |
| In1 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In2 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In3 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In4 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In5 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In6 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In7 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In8 (DSP)      | -32768 | -31870 | -30972 | -30075 | ... | 32767 |
| In1            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In2            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In3            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In4            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In5            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In6            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In7            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In8            | -1     | -0.973 | -0.945 | -0.918 | ... | 1     |
| Parameters     |        |        |        |        |     |       |
| In1            | +      |        |        |        |     |       |
| In2            | +      |        |        |        |     |       |
| In3            | +      |        |        |        |     |       |
| In4            | -      |        |        |        |     |       |
| In5            | -      |        |        |        |     |       |
| In6            | -      |        |        |        |     |       |
| In7            | 0      |        |        |        |     |       |
| In8            | +      |        |        |        |     |       |
| Outputs        |        |        |        |        |     |       |
| Out            | -1     | -0.973 | -0.945 | -0.918 | ... | 1     |
| Exp. Out       | -1     | -0.973 | -0.945 | -0.918 | ... | 1     |
| Out (DSP)      | -32767 | -31870 | -30972 | -30075 | ... | 32767 |
| Exp. Out (DSP) | -32768 | -31870 | -30972 | -30075 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 245 |
| Max CPU cycles  | 245 |
| Avg CPU cycles  | 245 |

#### Test case: Conversion test

OK

Conversion test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| In1                          | +     | -     | 0 |
| In2                          | +     | -     | 0 |
| In3                          | +     | -     | 0 |
| In4                          | +     | -     | 0 |
| In5                          | +     | -     | 0 |
| In6                          | +     | -     | 0 |
| In7                          | +     | -     | 0 |
| In8                          | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| sign                         | 21845 | 43690 | 0 |
| Exp. sign                    | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| <b>In1</b>                   | +     | -     | 0 |
| <b>In2</b>                   | +     | -     | 0 |
| <b>In3</b>                   | +     | -     | 0 |
| <b>In4</b>                   | +     | -     | 0 |
| <b>In5</b>                   | +     | -     | 0 |
| <b>In6</b>                   | +     | -     | 0 |
| <b>In7</b>                   | +     | -     | 0 |
| <b>In8</b>                   | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| <b>sign</b>                  | 21845 | 43690 | 0 |
| <b>Exp. sign</b>             | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 507 |
| Max CPU cycles  | 509 |
| Avg CPU cycles  | 507 |

**Verification: Sum FiP16 CPU STM32F072RB**

---

|                          |             |
|--------------------------|-------------|
| <b>Date of Test</b>      | 2026-06-19  |
| <b>Target controller</b> | STM32F072RB |

**Test case: Inport test****OK**

Inport test for Math block Sum.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 74    |
| CPU cycles     | 198    | 199    | 199    | 199    | ... | 199   |
| Inputs         |        |        |        |        |     |       |
| In1 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In2 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In3 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In4 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In5 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In6 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In7 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In8 (DSP)      | -32768 | -31870 | -30972 | -30075 | ... | 32767 |
| In1            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In2            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In3            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In4            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In5            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In6            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In7            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In8            | -1     | -0.973 | -0.945 | -0.918 | ... | 1     |
| Parameters     |        |        |        |        |     |       |
| In1            | +      |        |        |        |     |       |
| In2            | +      |        |        |        |     |       |
| In3            | +      |        |        |        |     |       |
| In4            | -      |        |        |        |     |       |
| In5            | -      |        |        |        |     |       |
| In6            | -      |        |        |        |     |       |
| In7            | 0      |        |        |        |     |       |
| In8            | +      |        |        |        |     |       |
| Outputs        |        |        |        |        |     |       |
| Out            | -1     | -0.973 | -0.945 | -0.918 | ... | 1     |
| Exp. Out       | -1     | -0.973 | -0.945 | -0.918 | ... | 1     |
| Out (DSP)      | -32767 | -31870 | -30972 | -30075 | ... | 32767 |
| Exp. Out (DSP) | -32768 | -31870 | -30972 | -30075 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 198 |
| Max CPU cycles  | 260 |
| Avg CPU cycles  | 199 |

**Test case: Conversion test**

OK

Conversion test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| In1                          | +     | -     | 0 |
| In2                          | +     | -     | 0 |
| In3                          | +     | -     | 0 |
| In4                          | +     | -     | 0 |
| In5                          | +     | -     | 0 |
| In6                          | +     | -     | 0 |
| In7                          | +     | -     | 0 |
| In8                          | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| sign                         | 21845 | 43690 | 0 |
| Exp. sign                    | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Math block Sum.



| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| <b>ln1</b>                   | +     | -     | 0 |
| <b>ln2</b>                   | +     | -     | 0 |
| <b>ln3</b>                   | +     | -     | 0 |
| <b>ln4</b>                   | +     | -     | 0 |
| <b>ln5</b>                   | +     | -     | 0 |
| <b>ln6</b>                   | +     | -     | 0 |
| <b>ln7</b>                   | +     | -     | 0 |
| <b>ln8</b>                   | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| <b>sign</b>                  | 21845 | 43690 | 0 |
| <b>Exp. sign</b>             | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 603 |
| Max CPU cycles  | 614 |
| Avg CPU cycles  | 610 |

**Verification: Sum FiP16 CPU PIC32MX170F256**

---

**Date of Test** 2026-06-19

**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Sum.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 74    |
| CPU cycles     | 110    | 110    | 110    | 110    | ... | 110   |
| Inputs         |        |        |        |        |     |       |
| In1 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In2 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In3 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In4 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In5 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In6 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In7 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In8 (DSP)      | -32768 | -31870 | -30972 | -30075 | ... | 32767 |
| In1            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In2            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In3            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In4            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In5            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In6            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In7            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In8            | -1     | -0.973 | -0.945 | -0.918 | ... | 1     |
| Parameters     |        |        |        |        |     |       |
| In1            | +      |        |        |        |     |       |
| In2            | +      |        |        |        |     |       |
| In3            | +      |        |        |        |     |       |
| In4            | -      |        |        |        |     |       |
| In5            | -      |        |        |        |     |       |
| In6            | -      |        |        |        |     |       |
| In7            | 0      |        |        |        |     |       |
| In8            | +      |        |        |        |     |       |
| Outputs        |        |        |        |        |     |       |
| Out            | -1     | -0.973 | -0.945 | -0.918 | ... | 1     |
| Exp. Out       | -1     | -0.973 | -0.945 | -0.918 | ... | 1     |
| Out (DSP)      | -32767 | -31870 | -30972 | -30075 | ... | 32767 |
| Exp. Out (DSP) | -32768 | -31870 | -30972 | -30075 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 110 |
| Max CPU cycles  | 110 |
| Avg CPU cycles  | 110 |

#### Test case: Conversion test

OK

Conversion test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| In1                          | +     | -     | 0 |
| In2                          | +     | -     | 0 |
| In3                          | +     | -     | 0 |
| In4                          | +     | -     | 0 |
| In5                          | +     | -     | 0 |
| In6                          | +     | -     | 0 |
| In7                          | +     | -     | 0 |
| In8                          | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| sign                         | 21845 | 43690 | 0 |
| Exp. sign                    | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| <b>In1</b>                   | +     | -     | 0 |
| <b>In2</b>                   | +     | -     | 0 |
| <b>In3</b>                   | +     | -     | 0 |
| <b>In4</b>                   | +     | -     | 0 |
| <b>In5</b>                   | +     | -     | 0 |
| <b>In6</b>                   | +     | -     | 0 |
| <b>In7</b>                   | +     | -     | 0 |
| <b>In8</b>                   | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| <b>sign</b>                  | 21845 | 43690 | 0 |
| <b>Exp. sign</b>             | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 280 |
| Max CPU cycles  | 301 |
| Avg CPU cycles  | 293 |

**Verification: Sum FiP16 CPU dsPIC33EP256MC502**

---

|                          |                   |
|--------------------------|-------------------|
| <b>Date of Test</b>      | 2026-06-19        |
| <b>Target controller</b> | dsPIC33EP256MC502 |

**Test case: Inport test****OK**

Inport test for Math block Sum.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 74    |
| CPU cycles     | 173    | 174    | 174    | 174    | ... | 174   |
| Inputs         |        |        |        |        |     |       |
| In1 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In2 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In3 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In4 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In5 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In6 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In7 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In8 (DSP)      | -32768 | -31870 | -30972 | -30075 | ... | 32767 |
| In1            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In2            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In3            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In4            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In5            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In6            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In7            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In8            | -1     | -0.973 | -0.945 | -0.918 | ... | 1     |
| Parameters     |        |        |        |        |     |       |
| In1            | +      |        |        |        |     |       |
| In2            | +      |        |        |        |     |       |
| In3            | +      |        |        |        |     |       |
| In4            | -      |        |        |        |     |       |
| In5            | -      |        |        |        |     |       |
| In6            | -      |        |        |        |     |       |
| In7            | 0      |        |        |        |     |       |
| In8            | +      |        |        |        |     |       |
| Outputs        |        |        |        |        |     |       |
| Out            | -1     | -0.973 | -0.945 | -0.918 | ... | 1     |
| Exp. Out       | -1     | -0.973 | -0.945 | -0.918 | ... | 1     |
| Out (DSP)      | -32767 | -31870 | -30972 | -30075 | ... | 32767 |
| Exp. Out (DSP) | -32768 | -31870 | -30972 | -30075 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 173 |
| Max CPU cycles  | 174 |
| Avg CPU cycles  | 173 |

#### Test case: Conversion test

OK

Conversion test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| In1                          | +     | -     | 0 |
| In2                          | +     | -     | 0 |
| In3                          | +     | -     | 0 |
| In4                          | +     | -     | 0 |
| In5                          | +     | -     | 0 |
| In6                          | +     | -     | 0 |
| In7                          | +     | -     | 0 |
| In8                          | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| sign                         | 21845 | 43690 | 0 |
| Exp. sign                    | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Math block Sum.



| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| <b>In1</b>                   | +     | -     | 0 |
| <b>In2</b>                   | +     | -     | 0 |
| <b>In3</b>                   | +     | -     | 0 |
| <b>In4</b>                   | +     | -     | 0 |
| <b>In5</b>                   | +     | -     | 0 |
| <b>In6</b>                   | +     | -     | 0 |
| <b>In7</b>                   | +     | -     | 0 |
| <b>In8</b>                   | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| <b>sign</b>                  | 21845 | 43690 | 0 |
| <b>Exp. sign</b>             | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 303 |
| Max CPU cycles  | 335 |
| Avg CPU cycles  | 323 |

**Verification: Sum FiP16 CPU XMC4800-F144K2048**

---

|                          |                   |
|--------------------------|-------------------|
| <b>Date of Test</b>      | 2026-06-19        |
| <b>Target controller</b> | XMC4800-F144K2048 |

**Test case: Inport test****OK**

Inport test for Math block Sum.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 74    |
| CPU cycles     | 246    | 164    | 164    | 164    | ... | 164   |
| Inputs         |        |        |        |        |     |       |
| In1 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In2 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In3 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In4 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In5 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In6 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In7 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In8 (DSP)      | -32768 | -31870 | -30972 | -30075 | ... | 32767 |
| In1            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In2            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In3            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In4            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In5            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In6            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In7            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In8            | -1     | -0.973 | -0.945 | -0.918 | ... | 1     |
| Parameters     |        |        |        |        |     |       |
| In1            | +      |        |        |        |     |       |
| In2            | +      |        |        |        |     |       |
| In3            | +      |        |        |        |     |       |
| In4            | -      |        |        |        |     |       |
| In5            | -      |        |        |        |     |       |
| In6            | -      |        |        |        |     |       |
| In7            | 0      |        |        |        |     |       |
| In8            | +      |        |        |        |     |       |
| Outputs        |        |        |        |        |     |       |
| Out            | -1     | -0.973 | -0.945 | -0.918 | ... | 1     |
| Exp. Out       | -1     | -0.973 | -0.945 | -0.918 | ... | 1     |
| Out (DSP)      | -32767 | -31870 | -30972 | -30075 | ... | 32767 |
| Exp. Out (DSP) | -32768 | -31870 | -30972 | -30075 | ... | 32767 |

| Test settings |                                        |
|---------------|----------------------------------------|
| Tolerance Out | $\pm 3,0518\text{e-}05$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 164 |
| Max CPU cycles  | 246 |
| Avg CPU cycles  | 165 |

#### Test case: Conversion test

OK

Conversion test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| In1                          | +     | -     | 0 |
| In2                          | +     | -     | 0 |
| In3                          | +     | -     | 0 |
| In4                          | +     | -     | 0 |
| In5                          | +     | -     | 0 |
| In6                          | +     | -     | 0 |
| In7                          | +     | -     | 0 |
| In8                          | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| sign                         | 21845 | 43690 | 0 |
| Exp. sign                    | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| <b>In1</b>                   | +     | -     | 0 |
| <b>In2</b>                   | +     | -     | 0 |
| <b>In3</b>                   | +     | -     | 0 |
| <b>In4</b>                   | +     | -     | 0 |
| <b>In5</b>                   | +     | -     | 0 |
| <b>In6</b>                   | +     | -     | 0 |
| <b>In7</b>                   | +     | -     | 0 |
| <b>In8</b>                   | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| <b>sign</b>                  | 21845 | 43690 | 0 |
| <b>Exp. sign</b>             | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 336 |
| Max CPU cycles  | 427 |
| Avg CPU cycles  | 375 |

**Verification: Sum FiP16 CPU TMS320F28379D**

---

|                          |               |
|--------------------------|---------------|
| <b>Date of Test</b>      | 2026-06-22    |
| <b>Target controller</b> | TMS320F28379D |

**Test case: Inport test****OK**

Inport test for Math block Sum.

| Test results   |        |        |        |        |     |       |
|----------------|--------|--------|--------|--------|-----|-------|
| Time step      | 1      | 2      | 3      | 4      | ... | 74    |
| CPU cycles     | 250    | 250    | 250    | 250    | ... | 250   |
| Inputs         |        |        |        |        |     |       |
| In1 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In2 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In3 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In4 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In5 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In6 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In7 (DSP)      | -32768 | -30948 | -29127 | -27307 | ... | 32767 |
| In8 (DSP)      | -32768 | -31870 | -30972 | -30075 | ... | 32767 |
| In1            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In2            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In3            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In4            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In5            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In6            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In7            | -1     | -0.944 | -0.889 | -0.833 | ... | 1     |
| In8            | -1     | -0.973 | -0.945 | -0.918 | ... | 1     |
| Parameters     |        |        |        |        |     |       |
| In1            | +      |        |        |        |     |       |
| In2            | +      |        |        |        |     |       |
| In3            | +      |        |        |        |     |       |
| In4            | -      |        |        |        |     |       |
| In5            | -      |        |        |        |     |       |
| In6            | -      |        |        |        |     |       |
| In7            | 0      |        |        |        |     |       |
| In8            | +      |        |        |        |     |       |
| Outputs        |        |        |        |        |     |       |
| Out            | -1     | -0.973 | -0.945 | -0.918 | ... | 1     |
| Exp. Out       | -1     | -0.973 | -0.945 | -0.918 | ... | 1     |
| Out (DSP)      | -32767 | -31870 | -30972 | -30075 | ... | 32767 |
| Exp. Out (DSP) | -32768 | -31870 | -30972 | -30075 | ... | 32767 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 3,0518e-05$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 250 |
| Max CPU cycles  | 250 |
| Avg CPU cycles  | 250 |

**Test case: Conversion test**

OK

Conversion test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| In1                          | +     | -     | 0 |
| In2                          | +     | -     | 0 |
| In3                          | +     | -     | 0 |
| In4                          | +     | -     | 0 |
| In5                          | +     | -     | 0 |
| In6                          | +     | -     | 0 |
| In7                          | +     | -     | 0 |
| In8                          | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| sign                         | 21845 | 43690 | 0 |
| Exp. sign                    | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Math block Sum.



| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| <b>ln1</b>                   | +     | -     | 0 |
| <b>ln2</b>                   | +     | -     | 0 |
| <b>ln3</b>                   | +     | -     | 0 |
| <b>ln4</b>                   | +     | -     | 0 |
| <b>ln5</b>                   | +     | -     | 0 |
| <b>ln6</b>                   | +     | -     | 0 |
| <b>ln7</b>                   | +     | -     | 0 |
| <b>ln8</b>                   | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| <b>sign</b>                  | 21845 | 43690 | 0 |
| <b>Exp. sign</b>             | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 567 |
| Max CPU cycles  | 624 |
| Avg CPU cycles  | 598 |

**Verification: Sum FiP32 CPU TMS320F28335**

---

**Date of Test** 2026-06-19**Target controller** TMS320F28335**Test case: Inport test****OK**

Inport test for Math block Sum.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 74         |
| CPU cycles     | 369         | 364         | ... | 364        |
| Inputs         |             |             |     |            |
| In1 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In2 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In3 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In4 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In5 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In6 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In7 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In8 (DSP)      | -2147483648 | -2088648480 | ... | 2147483647 |
| In1            | -1          | -0.944      | ... | 1          |
| In2            | -1          | -0.944      | ... | 1          |
| In3            | -1          | -0.944      | ... | 1          |
| In4            | -1          | -0.944      | ... | 1          |
| In5            | -1          | -0.944      | ... | 1          |
| In6            | -1          | -0.944      | ... | 1          |
| In7            | -1          | -0.944      | ... | 1          |
| In8            | -1          | -0.973      | ... | 1          |
| Parameters     |             |             |     |            |
| In1            | +           |             |     |            |
| In2            | +           |             |     |            |
| In3            | +           |             |     |            |
| In4            | -           |             |     |            |
| In5            | -           |             |     |            |
| In6            | -           |             |     |            |
| In7            | 0           |             |     |            |
| In8            | +           |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -1          | -0.973      | ... | 1          |
| Exp. Out       | -1          | -0.973      | ... | 1          |
| Out (DSP)      | -2147483647 | -2088648480 | ... | 2147483647 |
| Exp. Out (DSP) | -2147483648 | -2088648480 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 364 |
| Max CPU cycles  | 369 |
| Avg CPU cycles  | 364 |

**Test case: Conversion test**

OK

Conversion test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| In1                          | +     | -     | 0 |
| In2                          | +     | -     | 0 |
| In3                          | +     | -     | 0 |
| In4                          | +     | -     | 0 |
| In5                          | +     | -     | 0 |
| In6                          | +     | -     | 0 |
| In7                          | +     | -     | 0 |
| In8                          | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| sign                         | 21845 | 43690 | 0 |
| Exp. sign                    | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| <b>In1</b>                   | +     | -     | 0 |
| <b>In2</b>                   | +     | -     | 0 |
| <b>In3</b>                   | +     | -     | 0 |
| <b>In4</b>                   | +     | -     | 0 |
| <b>In5</b>                   | +     | -     | 0 |
| <b>In6</b>                   | +     | -     | 0 |
| <b>In7</b>                   | +     | -     | 0 |
| <b>In8</b>                   | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| <b>sign</b>                  | 21845 | 43690 | 0 |
| <b>Exp. sign</b>             | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 671 |
| Max CPU cycles  | 704 |
| Avg CPU cycles  | 684 |

**Verification: Sum FiP32 CPU TM4C123GH6**

---

|                          |            |
|--------------------------|------------|
| <b>Date of Test</b>      | 2026-06-19 |
| <b>Target controller</b> | TM4C123GH6 |

**Test case: Inport test****OK**

Inport test for Math block Sum.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 74         |
| CPU cycles     | 159         | 155         | ... | 155        |
| Inputs         |             |             |     |            |
| In1 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In2 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In3 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In4 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In5 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In6 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In7 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In8 (DSP)      | -2147483648 | -2088648480 | ... | 2147483647 |
| In1            | -1          | -0.944      | ... | 1          |
| In2            | -1          | -0.944      | ... | 1          |
| In3            | -1          | -0.944      | ... | 1          |
| In4            | -1          | -0.944      | ... | 1          |
| In5            | -1          | -0.944      | ... | 1          |
| In6            | -1          | -0.944      | ... | 1          |
| In7            | -1          | -0.944      | ... | 1          |
| In8            | -1          | -0.973      | ... | 1          |
| Parameters     |             |             |     |            |
| In1            | +           |             |     |            |
| In2            | +           |             |     |            |
| In3            | +           |             |     |            |
| In4            | -           |             |     |            |
| In5            | -           |             |     |            |
| In6            | -           |             |     |            |
| In7            | 0           |             |     |            |
| In8            | +           |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -1          | -0.973      | ... | 1          |
| Exp. Out       | -1          | -0.973      | ... | 1          |
| Out (DSP)      | -2147483647 | -2088648480 | ... | 2147483647 |
| Exp. Out (DSP) | -2147483648 | -2088648480 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 155 |
| Max CPU cycles  | 159 |
| Avg CPU cycles  | 155 |

#### Test case: Conversion test

OK

Conversion test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| In1                          | +     | -     | 0 |
| In2                          | +     | -     | 0 |
| In3                          | +     | -     | 0 |
| In4                          | +     | -     | 0 |
| In5                          | +     | -     | 0 |
| In6                          | +     | -     | 0 |
| In7                          | +     | -     | 0 |
| In8                          | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| sign                         | 21845 | 43690 | 0 |
| Exp. sign                    | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Math block Sum.



| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| <b>In1</b>                   | +     | -     | 0 |
| <b>In2</b>                   | +     | -     | 0 |
| <b>In3</b>                   | +     | -     | 0 |
| <b>In4</b>                   | +     | -     | 0 |
| <b>In5</b>                   | +     | -     | 0 |
| <b>In6</b>                   | +     | -     | 0 |
| <b>In7</b>                   | +     | -     | 0 |
| <b>In8</b>                   | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| <b>sign</b>                  | 21845 | 43690 | 0 |
| <b>Exp. sign</b>             | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 333 |
| Max CPU cycles  | 357 |
| Avg CPU cycles  | 341 |

**Verification: Sum FiP32 CPU STM32G474RE**

---

**Date of Test** 2026-06-19

**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block Sum.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 74         |
| CPU cycles     | 248         | 248         | ... | 248        |
| Inputs         |             |             |     |            |
| In1 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In2 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In3 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In4 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In5 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In6 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In7 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In8 (DSP)      | -2147483648 | -2088648480 | ... | 2147483647 |
| In1            | -1          | -0.944      | ... | 1          |
| In2            | -1          | -0.944      | ... | 1          |
| In3            | -1          | -0.944      | ... | 1          |
| In4            | -1          | -0.944      | ... | 1          |
| In5            | -1          | -0.944      | ... | 1          |
| In6            | -1          | -0.944      | ... | 1          |
| In7            | -1          | -0.944      | ... | 1          |
| In8            | -1          | -0.973      | ... | 1          |
| Parameters     |             |             |     |            |
| In1            | +           |             |     |            |
| In2            | +           |             |     |            |
| In3            | +           |             |     |            |
| In4            | -           |             |     |            |
| In5            | -           |             |     |            |
| In6            | -           |             |     |            |
| In7            | 0           |             |     |            |
| In8            | +           |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -1          | -0.973      | ... | 1          |
| Exp. Out       | -1          | -0.973      | ... | 1          |
| Out (DSP)      | -2147483647 | -2088648480 | ... | 2147483647 |
| Exp. Out (DSP) | -2147483648 | -2088648480 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 248 |
| Max CPU cycles  | 248 |
| Avg CPU cycles  | 248 |

#### Test case: Conversion test

OK

Conversion test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| In1                          | +     | -     | 0 |
| In2                          | +     | -     | 0 |
| In3                          | +     | -     | 0 |
| In4                          | +     | -     | 0 |
| In5                          | +     | -     | 0 |
| In6                          | +     | -     | 0 |
| In7                          | +     | -     | 0 |
| In8                          | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| sign                         | 21845 | 43690 | 0 |
| Exp. sign                    | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| <b>In1</b>                   | +     | -     | 0 |
| <b>In2</b>                   | +     | -     | 0 |
| <b>In3</b>                   | +     | -     | 0 |
| <b>In4</b>                   | +     | -     | 0 |
| <b>In5</b>                   | +     | -     | 0 |
| <b>In6</b>                   | +     | -     | 0 |
| <b>In7</b>                   | +     | -     | 0 |
| <b>In8</b>                   | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| <b>sign</b>                  | 21845 | 43690 | 0 |
| <b>Exp. sign</b>             | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 507 |
| Max CPU cycles  | 509 |
| Avg CPU cycles  | 507 |

**Verification: Sum FiP32 CPU STM32F072RB**

---

|                          |             |
|--------------------------|-------------|
| <b>Date of Test</b>      | 2026-06-19  |
| <b>Target controller</b> | STM32F072RB |

**Test case: Inport test****OK**

Inport test for Math block Sum.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 74         |
| CPU cycles     | 287         | 283         | ... | 285        |
| Inputs         |             |             |     |            |
| In1 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In2 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In3 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In4 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In5 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In6 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In7 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In8 (DSP)      | -2147483648 | -2088648480 | ... | 2147483647 |
| In1            | -1          | -0.944      | ... | 1          |
| In2            | -1          | -0.944      | ... | 1          |
| In3            | -1          | -0.944      | ... | 1          |
| In4            | -1          | -0.944      | ... | 1          |
| In5            | -1          | -0.944      | ... | 1          |
| In6            | -1          | -0.944      | ... | 1          |
| In7            | -1          | -0.944      | ... | 1          |
| In8            | -1          | -0.973      | ... | 1          |
| Parameters     |             |             |     |            |
| In1            | +           |             |     |            |
| In2            | +           |             |     |            |
| In3            | +           |             |     |            |
| In4            | -           |             |     |            |
| In5            | -           |             |     |            |
| In6            | -           |             |     |            |
| In7            | 0           |             |     |            |
| In8            | +           |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -1          | -0.973      | ... | 1          |
| Exp. Out       | -1          | -0.973      | ... | 1          |
| Out (DSP)      | -2147483647 | -2088648480 | ... | 2147483647 |
| Exp. Out (DSP) | -2147483648 | -2088648480 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 283 |
| Max CPU cycles  | 287 |
| Avg CPU cycles  | 284 |

**Test case: Conversion test**

OK

Conversion test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| In1                          | +     | -     | 0 |
| In2                          | +     | -     | 0 |
| In3                          | +     | -     | 0 |
| In4                          | +     | -     | 0 |
| In5                          | +     | -     | 0 |
| In6                          | +     | -     | 0 |
| In7                          | +     | -     | 0 |
| In8                          | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| sign                         | 21845 | 43690 | 0 |
| Exp. sign                    | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Math block Sum.



| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| <b>In1</b>                   | +     | -     | 0 |
| <b>In2</b>                   | +     | -     | 0 |
| <b>In3</b>                   | +     | -     | 0 |
| <b>In4</b>                   | +     | -     | 0 |
| <b>In5</b>                   | +     | -     | 0 |
| <b>In6</b>                   | +     | -     | 0 |
| <b>In7</b>                   | +     | -     | 0 |
| <b>In8</b>                   | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| <b>sign</b>                  | 21845 | 43690 | 0 |
| <b>Exp. sign</b>             | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 603 |
| Max CPU cycles  | 614 |
| Avg CPU cycles  | 610 |

**Verification: Sum FiP32 CPU PIC32MX170F256**

---

**Date of Test** 2026-06-19**Target controller** PIC32MX170F256**Test case: Inport test****OK**

Inport test for Math block Sum.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 74         |
| CPU cycles     | 158         | 154         | ... | 153        |
| Inputs         |             |             |     |            |
| In1 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In2 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In3 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In4 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In5 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In6 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In7 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In8 (DSP)      | -2147483648 | -2088648480 | ... | 2147483647 |
| In1            | -1          | -0.944      | ... | 1          |
| In2            | -1          | -0.944      | ... | 1          |
| In3            | -1          | -0.944      | ... | 1          |
| In4            | -1          | -0.944      | ... | 1          |
| In5            | -1          | -0.944      | ... | 1          |
| In6            | -1          | -0.944      | ... | 1          |
| In7            | -1          | -0.944      | ... | 1          |
| In8            | -1          | -0.973      | ... | 1          |
| Parameters     |             |             |     |            |
| In1            | +           |             |     |            |
| In2            | +           |             |     |            |
| In3            | +           |             |     |            |
| In4            | -           |             |     |            |
| In5            | -           |             |     |            |
| In6            | -           |             |     |            |
| In7            | 0           |             |     |            |
| In8            | +           |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -1          | -0.973      | ... | 1          |
| Exp. Out       | -1          | -0.973      | ... | 1          |
| Out (DSP)      | -2147483647 | -2088648480 | ... | 2147483647 |
| Exp. Out (DSP) | -2147483648 | -2088648480 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 153 |
| Max CPU cycles  | 158 |
| Avg CPU cycles  | 153 |

#### Test case: Conversion test

OK

Conversion test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| In1                          | +     | -     | 0 |
| In2                          | +     | -     | 0 |
| In3                          | +     | -     | 0 |
| In4                          | +     | -     | 0 |
| In5                          | +     | -     | 0 |
| In6                          | +     | -     | 0 |
| In7                          | +     | -     | 0 |
| In8                          | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| sign                         | 21845 | 43690 | 0 |
| Exp. sign                    | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| <b>ln1</b>                   | +     | -     | 0 |
| <b>ln2</b>                   | +     | -     | 0 |
| <b>ln3</b>                   | +     | -     | 0 |
| <b>ln4</b>                   | +     | -     | 0 |
| <b>ln5</b>                   | +     | -     | 0 |
| <b>ln6</b>                   | +     | -     | 0 |
| <b>ln7</b>                   | +     | -     | 0 |
| <b>ln8</b>                   | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| <b>sign</b>                  | 21845 | 43690 | 0 |
| <b>Exp. sign</b>             | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 280 |
| Max CPU cycles  | 301 |
| Avg CPU cycles  | 293 |

**Verification: Sum FiP32 CPU dsPIC33EP256MC502**

---

|                          |                   |
|--------------------------|-------------------|
| <b>Date of Test</b>      | 2026-06-19        |
| <b>Target controller</b> | dsPIC33EP256MC502 |

**Test case: Inport test****OK**

Inport test for Math block Sum.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 74         |
| CPU cycles     | 212         | 211         | ... | 211        |
| Inputs         |             |             |     |            |
| In1 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In2 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In3 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In4 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In5 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In6 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In7 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In8 (DSP)      | -2147483648 | -2088648480 | ... | 2147483647 |
| In1            | -1          | -0.944      | ... | 1          |
| In2            | -1          | -0.944      | ... | 1          |
| In3            | -1          | -0.944      | ... | 1          |
| In4            | -1          | -0.944      | ... | 1          |
| In5            | -1          | -0.944      | ... | 1          |
| In6            | -1          | -0.944      | ... | 1          |
| In7            | -1          | -0.944      | ... | 1          |
| In8            | -1          | -0.973      | ... | 1          |
| Parameters     |             |             |     |            |
| In1            | +           |             |     |            |
| In2            | +           |             |     |            |
| In3            | +           |             |     |            |
| In4            | -           |             |     |            |
| In5            | -           |             |     |            |
| In6            | -           |             |     |            |
| In7            | 0           |             |     |            |
| In8            | +           |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -1          | -0.973      | ... | 1          |
| Exp. Out       | -1          | -0.973      | ... | 1          |
| Out (DSP)      | -2147483647 | -2088648480 | ... | 2147483647 |
| Exp. Out (DSP) | -2147483648 | -2088648480 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 211 |
| Max CPU cycles  | 212 |
| Avg CPU cycles  | 211 |

**Test case: Conversion test**

OK

Conversion test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| In1                          | +     | -     | 0 |
| In2                          | +     | -     | 0 |
| In3                          | +     | -     | 0 |
| In4                          | +     | -     | 0 |
| In5                          | +     | -     | 0 |
| In6                          | +     | -     | 0 |
| In7                          | +     | -     | 0 |
| In8                          | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| sign                         | 21845 | 43690 | 0 |
| Exp. sign                    | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Math block Sum.



| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| <b>ln1</b>                   | +     | -     | 0 |
| <b>ln2</b>                   | +     | -     | 0 |
| <b>ln3</b>                   | +     | -     | 0 |
| <b>ln4</b>                   | +     | -     | 0 |
| <b>ln5</b>                   | +     | -     | 0 |
| <b>ln6</b>                   | +     | -     | 0 |
| <b>ln7</b>                   | +     | -     | 0 |
| <b>ln8</b>                   | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| <b>sign</b>                  | 21845 | 43690 | 0 |
| <b>Exp. sign</b>             | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 303 |
| Max CPU cycles  | 335 |
| Avg CPU cycles  | 323 |

**Verification: Sum FiP32 CPU XMC4800-F144K2048**

---

|                          |                   |
|--------------------------|-------------------|
| <b>Date of Test</b>      | 2026-06-19        |
| <b>Target controller</b> | XMC4800-F144K2048 |

**Test case: Inport test****OK**

Inport test for Math block Sum.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 74         |
| CPU cycles     | 267         | 184         | ... | 184        |
| Inputs         |             |             |     |            |
| In1 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In2 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In3 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In4 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In5 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In6 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In7 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In8 (DSP)      | -2147483648 | -2088648480 | ... | 2147483647 |
| In1            | -1          | -0.944      | ... | 1          |
| In2            | -1          | -0.944      | ... | 1          |
| In3            | -1          | -0.944      | ... | 1          |
| In4            | -1          | -0.944      | ... | 1          |
| In5            | -1          | -0.944      | ... | 1          |
| In6            | -1          | -0.944      | ... | 1          |
| In7            | -1          | -0.944      | ... | 1          |
| In8            | -1          | -0.973      | ... | 1          |
| Parameters     |             |             |     |            |
| In1            | +           |             |     |            |
| In2            | +           |             |     |            |
| In3            | +           |             |     |            |
| In4            | -           |             |     |            |
| In5            | -           |             |     |            |
| In6            | -           |             |     |            |
| In7            | 0           |             |     |            |
| In8            | +           |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -1          | -0.973      | ... | 1          |
| Exp. Out       | -1          | -0.973      | ... | 1          |
| Out (DSP)      | -2147483647 | -2088648480 | ... | 2147483647 |
| Exp. Out (DSP) | -2147483648 | -2088648480 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 184 |
| Max CPU cycles  | 267 |
| Avg CPU cycles  | 185 |

**Test case: Conversion test**

OK

Conversion test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| In1                          | +     | -     | 0 |
| In2                          | +     | -     | 0 |
| In3                          | +     | -     | 0 |
| In4                          | +     | -     | 0 |
| In5                          | +     | -     | 0 |
| In6                          | +     | -     | 0 |
| In7                          | +     | -     | 0 |
| In8                          | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| sign                         | 21845 | 43690 | 0 |
| Exp. sign                    | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| <b>In1</b>                   | +     | -     | 0 |
| <b>In2</b>                   | +     | -     | 0 |
| <b>In3</b>                   | +     | -     | 0 |
| <b>In4</b>                   | +     | -     | 0 |
| <b>In5</b>                   | +     | -     | 0 |
| <b>In6</b>                   | +     | -     | 0 |
| <b>In7</b>                   | +     | -     | 0 |
| <b>In8</b>                   | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| <b>sign</b>                  | 21845 | 43690 | 0 |
| <b>Exp. sign</b>             | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 336 |
| Max CPU cycles  | 417 |
| Avg CPU cycles  | 371 |

**Verification: Sum FiP32 CPU TMS320F28379D**

---

|                          |               |
|--------------------------|---------------|
| <b>Date of Test</b>      | 2026-06-22    |
| <b>Target controller</b> | TMS320F28379D |

**Test case: Inport test****OK**

Inport test for Math block Sum.

| Test results   |             |             |     |            |
|----------------|-------------|-------------|-----|------------|
| Time step      | 1           | 2           | ... | 74         |
| CPU cycles     | 394         | 389         | ... | 389        |
| Inputs         |             |             |     |            |
| In1 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In2 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In3 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In4 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In5 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In6 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In7 (DSP)      | -2147483648 | -2028179001 | ... | 2147483647 |
| In8 (DSP)      | -2147483648 | -2088648480 | ... | 2147483647 |
| In1            | -1          | -0.944      | ... | 1          |
| In2            | -1          | -0.944      | ... | 1          |
| In3            | -1          | -0.944      | ... | 1          |
| In4            | -1          | -0.944      | ... | 1          |
| In5            | -1          | -0.944      | ... | 1          |
| In6            | -1          | -0.944      | ... | 1          |
| In7            | -1          | -0.944      | ... | 1          |
| In8            | -1          | -0.973      | ... | 1          |
| Parameters     |             |             |     |            |
| In1            | +           |             |     |            |
| In2            | +           |             |     |            |
| In3            | +           |             |     |            |
| In4            | -           |             |     |            |
| In5            | -           |             |     |            |
| In6            | -           |             |     |            |
| In7            | 0           |             |     |            |
| In8            | +           |             |     |            |
| Outputs        |             |             |     |            |
| Out            | -1          | -0.973      | ... | 1          |
| Exp. Out       | -1          | -0.973      | ... | 1          |
| Out (DSP)      | -2147483647 | -2088648480 | ... | 2147483647 |
| Exp. Out (DSP) | -2147483648 | -2088648480 | ... | 2147483647 |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 4,6566e-10$ ( $\pm 1$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 389 |
| Max CPU cycles  | 394 |
| Avg CPU cycles  | 389 |

#### Test case: Conversion test

OK

Conversion test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| In1                          | +     | -     | 0 |
| In2                          | +     | -     | 0 |
| In3                          | +     | -     | 0 |
| In4                          | +     | -     | 0 |
| In5                          | +     | -     | 0 |
| In6                          | +     | -     | 0 |
| In7                          | +     | -     | 0 |
| In8                          | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| sign                         | 21845 | 43690 | 0 |
| Exp. sign                    | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Math block Sum.



| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| <b>In1</b>                   | +     | -     | 0 |
| <b>In2</b>                   | +     | -     | 0 |
| <b>In3</b>                   | +     | -     | 0 |
| <b>In4</b>                   | +     | -     | 0 |
| <b>In5</b>                   | +     | -     | 0 |
| <b>In6</b>                   | +     | -     | 0 |
| <b>In7</b>                   | +     | -     | 0 |
| <b>In8</b>                   | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| <b>sign</b>                  | 21845 | 43690 | 0 |
| <b>Exp. sign</b>             | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 582 |
| Max CPU cycles  | 623 |
| Avg CPU cycles  | 602 |

**Verification: Sum Float32 CPU TMS320F28335**

---

**Date of Test** 2026-06-19

**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block Sum.

| Test results   |     |        |     |     |
|----------------|-----|--------|-----|-----|
| Time step      | 1   | 2      | ... | 74  |
| CPU cycles     | 203 | 203    | ... | 203 |
| Inputs         |     |        |     |     |
| In1 (DSP)      | -1  | -0.944 | ... | 1   |
| In2 (DSP)      | -1  | -0.944 | ... | 1   |
| In3 (DSP)      | -1  | -0.944 | ... | 1   |
| In4 (DSP)      | -1  | -0.944 | ... | 1   |
| In5 (DSP)      | -1  | -0.944 | ... | 1   |
| In6 (DSP)      | -1  | -0.944 | ... | 1   |
| In7 (DSP)      | -1  | -0.944 | ... | 1   |
| In8 (DSP)      | -1  | -0.973 | ... | 1   |
| In1            | -1  | -0.944 | ... | 1   |
| In2            | -1  | -0.944 | ... | 1   |
| In3            | -1  | -0.944 | ... | 1   |
| In4            | -1  | -0.944 | ... | 1   |
| In5            | -1  | -0.944 | ... | 1   |
| In6            | -1  | -0.944 | ... | 1   |
| In7            | -1  | -0.944 | ... | 1   |
| In8            | -1  | -0.973 | ... | 1   |
| Parameters     |     |        |     |     |
| In1            | +   |        |     |     |
| In2            | +   |        |     |     |
| In3            | +   |        |     |     |
| In4            | -   |        |     |     |
| In5            | -   |        |     |     |
| In6            | -   |        |     |     |
| In7            | 0   |        |     |     |
| In8            | +   |        |     |     |
| Outputs        |     |        |     |     |
| Out            | -1  | -0.973 | ... | 1   |
| Exp. Out       | -1  | -0.973 | ... | 1   |
| Out (DSP)      | -1  | -0.973 | ... | 1   |
| Exp. Out (DSP) | -1  | -0.973 | ... | 1   |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,8626e-07$ ( $\pm 400$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 203 |
| Max CPU cycles  | 203 |
| Avg CPU cycles  | 203 |

**Test case: Conversion test**

OK

Conversion test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| In1                          | +     | -     | 0 |
| In2                          | +     | -     | 0 |
| In3                          | +     | -     | 0 |
| In4                          | +     | -     | 0 |
| In5                          | +     | -     | 0 |
| In6                          | +     | -     | 0 |
| In7                          | +     | -     | 0 |
| In8                          | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| sign                         | 21845 | 43690 | 0 |
| Exp. sign                    | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| <b>In1</b>                   | +     | -     | 0 |
| <b>In2</b>                   | +     | -     | 0 |
| <b>In3</b>                   | +     | -     | 0 |
| <b>In4</b>                   | +     | -     | 0 |
| <b>In5</b>                   | +     | -     | 0 |
| <b>In6</b>                   | +     | -     | 0 |
| <b>In7</b>                   | +     | -     | 0 |
| <b>In8</b>                   | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| <b>sign</b>                  | 21845 | 43690 | 0 |
| <b>Exp. sign</b>             | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 684 |
| Max CPU cycles  | 716 |
| Avg CPU cycles  | 697 |

**Verification: Sum Float32 CPU TM4C123GH6**

---

|                          |            |
|--------------------------|------------|
| <b>Date of Test</b>      | 2026-06-19 |
| <b>Target controller</b> | TM4C123GH6 |

**Test case: Inport test****OK**

Inport test for Math block Sum.

| Test results   |     |        |     |     |
|----------------|-----|--------|-----|-----|
| Time step      | 1   | 2      | ... | 74  |
| CPU cycles     | 117 | 117    | ... | 117 |
| Inputs         |     |        |     |     |
| In1 (DSP)      | -1  | -0.944 | ... | 1   |
| In2 (DSP)      | -1  | -0.944 | ... | 1   |
| In3 (DSP)      | -1  | -0.944 | ... | 1   |
| In4 (DSP)      | -1  | -0.944 | ... | 1   |
| In5 (DSP)      | -1  | -0.944 | ... | 1   |
| In6 (DSP)      | -1  | -0.944 | ... | 1   |
| In7 (DSP)      | -1  | -0.944 | ... | 1   |
| In8 (DSP)      | -1  | -0.973 | ... | 1   |
| In1            | -1  | -0.944 | ... | 1   |
| In2            | -1  | -0.944 | ... | 1   |
| In3            | -1  | -0.944 | ... | 1   |
| In4            | -1  | -0.944 | ... | 1   |
| In5            | -1  | -0.944 | ... | 1   |
| In6            | -1  | -0.944 | ... | 1   |
| In7            | -1  | -0.944 | ... | 1   |
| In8            | -1  | -0.973 | ... | 1   |
| Parameters     |     |        |     |     |
| In1            | +   |        |     |     |
| In2            | +   |        |     |     |
| In3            | +   |        |     |     |
| In4            | -   |        |     |     |
| In5            | -   |        |     |     |
| In6            | -   |        |     |     |
| In7            | 0   |        |     |     |
| In8            | +   |        |     |     |
| Outputs        |     |        |     |     |
| Out            | -1  | -0.973 | ... | 1   |
| Exp. Out       | -1  | -0.973 | ... | 1   |
| Out (DSP)      | -1  | -0.973 | ... | 1   |
| Exp. Out (DSP) | -1  | -0.973 | ... | 1   |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,8626e-07$ ( $\pm 400$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 117 |
| Max CPU cycles  | 117 |
| Avg CPU cycles  | 117 |

**Test case: Conversion test**

OK

Conversion test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| In1                          | +     | -     | 0 |
| In2                          | +     | -     | 0 |
| In3                          | +     | -     | 0 |
| In4                          | +     | -     | 0 |
| In5                          | +     | -     | 0 |
| In6                          | +     | -     | 0 |
| In7                          | +     | -     | 0 |
| In8                          | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| sign                         | 21845 | 43690 | 0 |
| Exp. sign                    | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Math block Sum.



| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| <b>In1</b>                   | +     | -     | 0 |
| <b>In2</b>                   | +     | -     | 0 |
| <b>In3</b>                   | +     | -     | 0 |
| <b>In4</b>                   | +     | -     | 0 |
| <b>In5</b>                   | +     | -     | 0 |
| <b>In6</b>                   | +     | -     | 0 |
| <b>In7</b>                   | +     | -     | 0 |
| <b>In8</b>                   | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| <b>sign</b>                  | 21845 | 43690 | 0 |
| <b>Exp. sign</b>             | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 333 |
| Max CPU cycles  | 357 |
| Avg CPU cycles  | 341 |

**Verification: Sum Float32 CPU STM32G474RE**

---

**Date of Test** 2026-06-19**Target controller** STM32G474RE**Test case: Inport test****OK**

Inport test for Math block Sum.

| Test results   |     |        |     |     |
|----------------|-----|--------|-----|-----|
| Time step      | 1   | 2      | ... | 74  |
| CPU cycles     | 235 | 235    | ... | 235 |
| Inputs         |     |        |     |     |
| In1 (DSP)      | -1  | -0.944 | ... | 1   |
| In2 (DSP)      | -1  | -0.944 | ... | 1   |
| In3 (DSP)      | -1  | -0.944 | ... | 1   |
| In4 (DSP)      | -1  | -0.944 | ... | 1   |
| In5 (DSP)      | -1  | -0.944 | ... | 1   |
| In6 (DSP)      | -1  | -0.944 | ... | 1   |
| In7 (DSP)      | -1  | -0.944 | ... | 1   |
| In8 (DSP)      | -1  | -0.973 | ... | 1   |
| In1            | -1  | -0.944 | ... | 1   |
| In2            | -1  | -0.944 | ... | 1   |
| In3            | -1  | -0.944 | ... | 1   |
| In4            | -1  | -0.944 | ... | 1   |
| In5            | -1  | -0.944 | ... | 1   |
| In6            | -1  | -0.944 | ... | 1   |
| In7            | -1  | -0.944 | ... | 1   |
| In8            | -1  | -0.973 | ... | 1   |
| Parameters     |     |        |     |     |
| In1            | +   |        |     |     |
| In2            | +   |        |     |     |
| In3            | +   |        |     |     |
| In4            | -   |        |     |     |
| In5            | -   |        |     |     |
| In6            | -   |        |     |     |
| In7            | 0   |        |     |     |
| In8            | +   |        |     |     |
| Outputs        |     |        |     |     |
| Out            | -1  | -0.973 | ... | 1   |
| Exp. Out       | -1  | -0.973 | ... | 1   |
| Out (DSP)      | -1  | -0.973 | ... | 1   |
| Exp. Out (DSP) | -1  | -0.973 | ... | 1   |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,8626e-07$ ( $\pm 400$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 235 |
| Max CPU cycles  | 235 |
| Avg CPU cycles  | 235 |

#### Test case: Conversion test

OK

Conversion test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| In1                          | +     | -     | 0 |
| In2                          | +     | -     | 0 |
| In3                          | +     | -     | 0 |
| In4                          | +     | -     | 0 |
| In5                          | +     | -     | 0 |
| In6                          | +     | -     | 0 |
| In7                          | +     | -     | 0 |
| In8                          | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| sign                         | 21845 | 43690 | 0 |
| Exp. sign                    | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| <b>In1</b>                   | +     | -     | 0 |
| <b>In2</b>                   | +     | -     | 0 |
| <b>In3</b>                   | +     | -     | 0 |
| <b>In4</b>                   | +     | -     | 0 |
| <b>In5</b>                   | +     | -     | 0 |
| <b>In6</b>                   | +     | -     | 0 |
| <b>In7</b>                   | +     | -     | 0 |
| <b>In8</b>                   | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| <b>sign</b>                  | 21845 | 43690 | 0 |
| <b>Exp. sign</b>             | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 510 |
| Max CPU cycles  | 512 |
| Avg CPU cycles  | 510 |

**Verification: Sum Float32 CPU STM32F072RB**

---

|                          |             |
|--------------------------|-------------|
| <b>Date of Test</b>      | 2026-06-19  |
| <b>Target controller</b> | STM32F072RB |

**Test case: Inport test****OK**

Inport test for Math block Sum.

| Test results   |     |        |     |     |
|----------------|-----|--------|-----|-----|
| Time step      | 1   | 2      | ... | 74  |
| CPU cycles     | 835 | 908    | ... | 834 |
| Inputs         |     |        |     |     |
| In1 (DSP)      | -1  | -0.944 | ... | 1   |
| In2 (DSP)      | -1  | -0.944 | ... | 1   |
| In3 (DSP)      | -1  | -0.944 | ... | 1   |
| In4 (DSP)      | -1  | -0.944 | ... | 1   |
| In5 (DSP)      | -1  | -0.944 | ... | 1   |
| In6 (DSP)      | -1  | -0.944 | ... | 1   |
| In7 (DSP)      | -1  | -0.944 | ... | 1   |
| In8 (DSP)      | -1  | -0.973 | ... | 1   |
| In1            | -1  | -0.944 | ... | 1   |
| In2            | -1  | -0.944 | ... | 1   |
| In3            | -1  | -0.944 | ... | 1   |
| In4            | -1  | -0.944 | ... | 1   |
| In5            | -1  | -0.944 | ... | 1   |
| In6            | -1  | -0.944 | ... | 1   |
| In7            | -1  | -0.944 | ... | 1   |
| In8            | -1  | -0.973 | ... | 1   |
| Parameters     |     |        |     |     |
| In1            | +   |        |     |     |
| In2            | +   |        |     |     |
| In3            | +   |        |     |     |
| In4            | -   |        |     |     |
| In5            | -   |        |     |     |
| In6            | -   |        |     |     |
| In7            | 0   |        |     |     |
| In8            | +   |        |     |     |
| Outputs        |     |        |     |     |
| Out            | -1  | -0.973 | ... | 1   |
| Exp. Out       | -1  | -0.973 | ... | 1   |
| Out (DSP)      | -1  | -0.973 | ... | 1   |
| Exp. Out (DSP) | -1  | -0.973 | ... | 1   |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,8626e-07$ ( $\pm 400$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 741  |
| Max CPU cycles  | 1025 |
| Avg CPU cycles  | 958  |

#### Test case: Conversion test

OK

Conversion test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| In1                          | +     | -     | 0 |
| In2                          | +     | -     | 0 |
| In3                          | +     | -     | 0 |
| In4                          | +     | -     | 0 |
| In5                          | +     | -     | 0 |
| In6                          | +     | -     | 0 |
| In7                          | +     | -     | 0 |
| In8                          | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| sign                         | 21845 | 43690 | 0 |
| Exp. sign                    | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Math block Sum.



| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| <b>In1</b>                   | +     | -     | 0 |
| <b>In2</b>                   | +     | -     | 0 |
| <b>In3</b>                   | +     | -     | 0 |
| <b>In4</b>                   | +     | -     | 0 |
| <b>In5</b>                   | +     | -     | 0 |
| <b>In6</b>                   | +     | -     | 0 |
| <b>In7</b>                   | +     | -     | 0 |
| <b>In8</b>                   | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| <b>sign</b>                  | 21845 | 43690 | 0 |
| <b>Exp. sign</b>             | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 603 |
| Max CPU cycles  | 614 |
| Avg CPU cycles  | 610 |

**Verification: Sum Float32 CPU PIC32MX170F256**

---

**Date of Test** 2026-06-19

**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block Sum.

| Test results   |     |        |     |     |
|----------------|-----|--------|-----|-----|
| Time step      | 1   | 2      | ... | 74  |
| CPU cycles     | 419 | 427    | ... | 419 |
| Inputs         |     |        |     |     |
| In1 (DSP)      | -1  | -0.944 | ... | 1   |
| In2 (DSP)      | -1  | -0.944 | ... | 1   |
| In3 (DSP)      | -1  | -0.944 | ... | 1   |
| In4 (DSP)      | -1  | -0.944 | ... | 1   |
| In5 (DSP)      | -1  | -0.944 | ... | 1   |
| In6 (DSP)      | -1  | -0.944 | ... | 1   |
| In7 (DSP)      | -1  | -0.944 | ... | 1   |
| In8 (DSP)      | -1  | -0.973 | ... | 1   |
| In1            | -1  | -0.944 | ... | 1   |
| In2            | -1  | -0.944 | ... | 1   |
| In3            | -1  | -0.944 | ... | 1   |
| In4            | -1  | -0.944 | ... | 1   |
| In5            | -1  | -0.944 | ... | 1   |
| In6            | -1  | -0.944 | ... | 1   |
| In7            | -1  | -0.944 | ... | 1   |
| In8            | -1  | -0.973 | ... | 1   |
| Parameters     |     |        |     |     |
| In1            | +   |        |     |     |
| In2            | +   |        |     |     |
| In3            | +   |        |     |     |
| In4            | -   |        |     |     |
| In5            | -   |        |     |     |
| In6            | -   |        |     |     |
| In7            | 0   |        |     |     |
| In8            | +   |        |     |     |
| Outputs        |     |        |     |     |
| Out            | -1  | -0.973 | ... | 1   |
| Exp. Out       | -1  | -0.973 | ... | 1   |
| Out (DSP)      | -1  | -0.973 | ... | 1   |
| Exp. Out (DSP) | -1  | -0.973 | ... | 1   |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,8626e-07$ ( $\pm 400$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 317 |
| Max CPU cycles  | 473 |
| Avg CPU cycles  | 450 |

**Test case: Conversion test**

OK

Conversion test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| In1                          | +     | -     | 0 |
| In2                          | +     | -     | 0 |
| In3                          | +     | -     | 0 |
| In4                          | +     | -     | 0 |
| In5                          | +     | -     | 0 |
| In6                          | +     | -     | 0 |
| In7                          | +     | -     | 0 |
| In8                          | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| sign                         | 21845 | 43690 | 0 |
| Exp. sign                    | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| <b>In1</b>                   | +     | -     | 0 |
| <b>In2</b>                   | +     | -     | 0 |
| <b>In3</b>                   | +     | -     | 0 |
| <b>In4</b>                   | +     | -     | 0 |
| <b>In5</b>                   | +     | -     | 0 |
| <b>In6</b>                   | +     | -     | 0 |
| <b>In7</b>                   | +     | -     | 0 |
| <b>In8</b>                   | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| <b>sign</b>                  | 21845 | 43690 | 0 |
| <b>Exp. sign</b>             | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 280 |
| Max CPU cycles  | 301 |
| Avg CPU cycles  | 293 |

**Verification: Sum Float32 CPU dsPIC33EP256MC502**

---

|                          |                   |
|--------------------------|-------------------|
| <b>Date of Test</b>      | 2026-06-19        |
| <b>Target controller</b> | dsPIC33EP256MC502 |

**Test case: Inport test****OK**

Inport test for Math block Sum.

| Test results   |      |        |     |      |
|----------------|------|--------|-----|------|
| Time step      | 1    | 2      | ... | 74   |
| CPU cycles     | 1160 | 1176   | ... | 1156 |
| Inputs         |      |        |     |      |
| In1 (DSP)      | -1   | -0.944 | ... | 1    |
| In2 (DSP)      | -1   | -0.944 | ... | 1    |
| In3 (DSP)      | -1   | -0.944 | ... | 1    |
| In4 (DSP)      | -1   | -0.944 | ... | 1    |
| In5 (DSP)      | -1   | -0.944 | ... | 1    |
| In6 (DSP)      | -1   | -0.944 | ... | 1    |
| In7 (DSP)      | -1   | -0.944 | ... | 1    |
| In8 (DSP)      | -1   | -0.973 | ... | 1    |
| In1            | -1   | -0.944 | ... | 1    |
| In2            | -1   | -0.944 | ... | 1    |
| In3            | -1   | -0.944 | ... | 1    |
| In4            | -1   | -0.944 | ... | 1    |
| In5            | -1   | -0.944 | ... | 1    |
| In6            | -1   | -0.944 | ... | 1    |
| In7            | -1   | -0.944 | ... | 1    |
| In8            | -1   | -0.973 | ... | 1    |
| Parameters     |      |        |     |      |
| In1            | +    |        |     |      |
| In2            | +    |        |     |      |
| In3            | +    |        |     |      |
| In4            | -    |        |     |      |
| In5            | -    |        |     |      |
| In6            | -    |        |     |      |
| In7            | 0    |        |     |      |
| In8            | +    |        |     |      |
| Outputs        |      |        |     |      |
| Out            | -1   | -0.973 | ... | 1    |
| Exp. Out       | -1   | -0.973 | ... | 1    |
| Out (DSP)      | -1   | -0.973 | ... | 1    |
| Exp. Out (DSP) | -1   | -0.973 | ... | 1    |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,8626e-07$ ( $\pm 400$ LSB) |

| Test statistics |      |
|-----------------|------|
| Min CPU cycles  | 1149 |
| Max CPU cycles  | 1746 |
| Avg CPU cycles  | 1536 |

**Test case: Conversion test**

OK

Conversion test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| In1                          | +     | -     | 0 |
| In2                          | +     | -     | 0 |
| In3                          | +     | -     | 0 |
| In4                          | +     | -     | 0 |
| In5                          | +     | -     | 0 |
| In6                          | +     | -     | 0 |
| In7                          | +     | -     | 0 |
| In8                          | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| sign                         | 21845 | 43690 | 0 |
| Exp. sign                    | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Math block Sum.



| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| <b>In1</b>                   | +     | -     | 0 |
| <b>In2</b>                   | +     | -     | 0 |
| <b>In3</b>                   | +     | -     | 0 |
| <b>In4</b>                   | +     | -     | 0 |
| <b>In5</b>                   | +     | -     | 0 |
| <b>In6</b>                   | +     | -     | 0 |
| <b>In7</b>                   | +     | -     | 0 |
| <b>In8</b>                   | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| <b>sign</b>                  | 21845 | 43690 | 0 |
| <b>Exp. sign</b>             | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 303 |
| Max CPU cycles  | 335 |
| Avg CPU cycles  | 323 |

**Verification: Sum Float32 CPU XMC4800-F144K2048**

---

|                          |                   |
|--------------------------|-------------------|
| <b>Date of Test</b>      | 2026-06-19        |
| <b>Target controller</b> | XMC4800-F144K2048 |

**Test case: Inport test****OK**

Inport test for Math block Sum.

| Test results   |     |        |     |     |
|----------------|-----|--------|-----|-----|
| Time step      | 1   | 2      | ... | 74  |
| CPU cycles     | 234 | 152    | ... | 152 |
| Inputs         |     |        |     |     |
| In1 (DSP)      | -1  | -0.944 | ... | 1   |
| In2 (DSP)      | -1  | -0.944 | ... | 1   |
| In3 (DSP)      | -1  | -0.944 | ... | 1   |
| In4 (DSP)      | -1  | -0.944 | ... | 1   |
| In5 (DSP)      | -1  | -0.944 | ... | 1   |
| In6 (DSP)      | -1  | -0.944 | ... | 1   |
| In7 (DSP)      | -1  | -0.944 | ... | 1   |
| In8 (DSP)      | -1  | -0.973 | ... | 1   |
| In1            | -1  | -0.944 | ... | 1   |
| In2            | -1  | -0.944 | ... | 1   |
| In3            | -1  | -0.944 | ... | 1   |
| In4            | -1  | -0.944 | ... | 1   |
| In5            | -1  | -0.944 | ... | 1   |
| In6            | -1  | -0.944 | ... | 1   |
| In7            | -1  | -0.944 | ... | 1   |
| In8            | -1  | -0.973 | ... | 1   |
| Parameters     |     |        |     |     |
| In1            | +   |        |     |     |
| In2            | +   |        |     |     |
| In3            | +   |        |     |     |
| In4            | -   |        |     |     |
| In5            | -   |        |     |     |
| In6            | -   |        |     |     |
| In7            | 0   |        |     |     |
| In8            | +   |        |     |     |
| Outputs        |     |        |     |     |
| Out            | -1  | -0.973 | ... | 1   |
| Exp. Out       | -1  | -0.973 | ... | 1   |
| Out (DSP)      | -1  | -0.973 | ... | 1   |
| Exp. Out (DSP) | -1  | -0.973 | ... | 1   |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,8626e-07$ ( $\pm 400$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 152 |
| Max CPU cycles  | 234 |
| Avg CPU cycles  | 153 |

**Test case: Conversion test**

OK

Conversion test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| In1                          | +     | -     | 0 |
| In2                          | +     | -     | 0 |
| In3                          | +     | -     | 0 |
| In4                          | +     | -     | 0 |
| In5                          | +     | -     | 0 |
| In6                          | +     | -     | 0 |
| In7                          | +     | -     | 0 |
| In8                          | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| sign                         | 21845 | 43690 | 0 |
| Exp. sign                    | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

**Test case: Conversion-on-Target test**

OK

Conversion-on-Target test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| <b>In1</b>                   | +     | -     | 0 |
| <b>In2</b>                   | +     | -     | 0 |
| <b>In3</b>                   | +     | -     | 0 |
| <b>In4</b>                   | +     | -     | 0 |
| <b>In5</b>                   | +     | -     | 0 |
| <b>In6</b>                   | +     | -     | 0 |
| <b>In7</b>                   | +     | -     | 0 |
| <b>In8</b>                   | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| <b>sign</b>                  | 21845 | 43690 | 0 |
| <b>Exp. sign</b>             | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 336 |
| Max CPU cycles  | 424 |
| Avg CPU cycles  | 374 |

**Verification: Sum Float32 CPU TMS320F28379D**

---

|                          |               |
|--------------------------|---------------|
| <b>Date of Test</b>      | 2026-06-22    |
| <b>Target controller</b> | TMS320F28379D |

**Test case: Inport test****OK**

Inport test for Math block Sum.

| Test results   |     |        |     |     |
|----------------|-----|--------|-----|-----|
| Time step      | 1   | 2      | ... | 74  |
| CPU cycles     | 232 | 232    | ... | 232 |
| Inputs         |     |        |     |     |
| In1 (DSP)      | -1  | -0.944 | ... | 1   |
| In2 (DSP)      | -1  | -0.944 | ... | 1   |
| In3 (DSP)      | -1  | -0.944 | ... | 1   |
| In4 (DSP)      | -1  | -0.944 | ... | 1   |
| In5 (DSP)      | -1  | -0.944 | ... | 1   |
| In6 (DSP)      | -1  | -0.944 | ... | 1   |
| In7 (DSP)      | -1  | -0.944 | ... | 1   |
| In8 (DSP)      | -1  | -0.973 | ... | 1   |
| In1            | -1  | -0.944 | ... | 1   |
| In2            | -1  | -0.944 | ... | 1   |
| In3            | -1  | -0.944 | ... | 1   |
| In4            | -1  | -0.944 | ... | 1   |
| In5            | -1  | -0.944 | ... | 1   |
| In6            | -1  | -0.944 | ... | 1   |
| In7            | -1  | -0.944 | ... | 1   |
| In8            | -1  | -0.973 | ... | 1   |
| Parameters     |     |        |     |     |
| In1            | +   |        |     |     |
| In2            | +   |        |     |     |
| In3            | +   |        |     |     |
| In4            | -   |        |     |     |
| In5            | -   |        |     |     |
| In6            | -   |        |     |     |
| In7            | 0   |        |     |     |
| In8            | +   |        |     |     |
| Outputs        |     |        |     |     |
| Out            | -1  | -0.973 | ... | 1   |
| Exp. Out       | -1  | -0.973 | ... | 1   |
| Out (DSP)      | -1  | -0.973 | ... | 1   |
| Exp. Out (DSP) | -1  | -0.973 | ... | 1   |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 1,8626e-07$ ( $\pm 400$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 232 |
| Max CPU cycles  | 232 |
| Avg CPU cycles  | 232 |

#### Test case: Conversion test

OK

Conversion test for Math block Sum.

| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| In1                          | +     | -     | 0 |
| In2                          | +     | -     | 0 |
| In3                          | +     | -     | 0 |
| In4                          | +     | -     | 0 |
| In5                          | +     | -     | 0 |
| In6                          | +     | -     | 0 |
| In7                          | +     | -     | 0 |
| In8                          | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| sign                         | 21845 | 43690 | 0 |
| Exp. sign                    | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

#### Test case: Conversion-on-Target test

OK

Conversion-on-Target test for Math block Sum.



| Test results                 |       |       |   |
|------------------------------|-------|-------|---|
| Time step                    | 1     | 2     | 3 |
| <i>Mask parameters</i>       |       |       |   |
| <b>In1</b>                   | +     | -     | 0 |
| <b>In2</b>                   | +     | -     | 0 |
| <b>In3</b>                   | +     | -     | 0 |
| <b>In4</b>                   | +     | -     | 0 |
| <b>In5</b>                   | +     | -     | 0 |
| <b>In6</b>                   | +     | -     | 0 |
| <b>In7</b>                   | +     | -     | 0 |
| <b>In8</b>                   | +     | -     | 0 |
| <i>Controller parameters</i> |       |       |   |
| <b>sign</b>                  | 21845 | 43690 | 0 |
| <b>Exp. sign</b>             | 21845 | 43690 | 0 |

| Test settings  |                  |
|----------------|------------------|
| Tolerance sign | $\pm 0,0000e+00$ |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 574 |
| Max CPU cycles  | 622 |
| Avg CPU cycles  | 599 |

## Block: uAdd

---



Addition of input 1 and input 2 with output wrapping.

| Inports |          |
|---------|----------|
| In1     | Addend 1 |
| In2     | Addend 2 |

| Outports |     |
|----------|-----|
| Out      | Sum |

### Description:

Calculation:

$$\text{Out} = \text{In}_1 + \text{In}_2$$

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| In1               | int8 |
| In2               | int8 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In1               | int16 |
| In2               | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| In1               | int32 |
| In2               | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In1               | float32 |
| In2               | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| In1               | float64 |
| In2               | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: uAdd FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block uAdd.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 51     | 51     | 51     | 51     | ... | 51    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In1 (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>In2 (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>In1</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>In2</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -0     | 0      | 0      | 0      | ... | -0    |
| <b>Exp. Out</b>       | 0      | 0      | 0      | 0      | ... | 0     |
| <b>Out (DSP)</b>      | -1     | 0      | 0      | 0      | ... | -2    |
| <b>Exp. Out (DSP)</b> | 0      | 0      | 0      | 0      | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 51 |
| Max CPU cycles  | 51 |
| Avg CPU cycles  | 51 |

**Verification: uAdd FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block uAdd.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 25     | 25     | 25     | 25     | ... | 25    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In1 (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>In2 (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>In1</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>In2</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -0     | 0      | 0      | 0      | ... | -0    |
| <b>Exp. Out</b>       | 0      | 0      | 0      | 0      | ... | 0     |
| <b>Out (DSP)</b>      | -1     | 0      | 0      | 0      | ... | -2    |
| <b>Exp. Out (DSP)</b> | 0      | 0      | 0      | 0      | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 25 |
| Max CPU cycles  | 25 |
| Avg CPU cycles  | 25 |

**Verification: uAdd FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block uAdd.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 57     | 57     | 57     | 57     | ... | 57    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In1 (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>In2 (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>In1</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>In2</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -0     | 0      | 0      | 0      | ... | -0    |
| <b>Exp. Out</b>       | 0      | 0      | 0      | 0      | ... | 0     |
| <b>Out (DSP)</b>      | -1     | 0      | 0      | 0      | ... | -2    |
| <b>Exp. Out (DSP)</b> | 0      | 0      | 0      | 0      | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 57 |

**Verification: uAdd FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block uAdd.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 51     | 51     | 51     | 51     | ... | 51    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In1 (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>In2 (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>In1</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>In2</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -0     | 0      | 0      | 0      | ... | -0    |
| <b>Exp. Out</b>       | 0      | 0      | 0      | 0      | ... | 0     |
| <b>Out (DSP)</b>      | -1     | 0      | 0      | 0      | ... | -2    |
| <b>Exp. Out (DSP)</b> | 0      | 0      | 0      | 0      | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 51  |
| Max CPU cycles  | 112 |
| Avg CPU cycles  | 51  |

**Verification: uAdd FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block uAdd.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 32     | 32     | 32     | 32     | ... | 32    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In1 (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>In2 (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>In1</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>In2</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -0     | 0      | 0      | 0      | ... | -0    |
| <b>Exp. Out</b>       | 0      | 0      | 0      | 0      | ... | 0     |
| <b>Out (DSP)</b>      | -1     | 0      | 0      | 0      | ... | -2    |
| <b>Exp. Out (DSP)</b> | 0      | 0      | 0      | 0      | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 32 |
| Max CPU cycles  | 32 |
| Avg CPU cycles  | 32 |



**Verification: uAdd FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block uAdd.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 38     | 38     | 38     | 38     | ... | 38    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In1 (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>In2 (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>In1</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>In2</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -0     | 0      | 0      | 0      | ... | -0    |
| <b>Exp. Out</b>       | 0      | 0      | 0      | 0      | ... | 0     |
| <b>Out (DSP)</b>      | -1     | 0      | 0      | 0      | ... | -2    |
| <b>Exp. Out (DSP)</b> | 0      | 0      | 0      | 0      | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 38 |
| Max CPU cycles  | 38 |
| Avg CPU cycles  | 38 |

**Verification: uAdd FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block uAdd.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 56     | 56     | 56     | 56     | ... | 56    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In1 (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>In2 (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>In1</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>In2</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -0     | 0      | 0      | 0      | ... | -0    |
| <b>Exp. Out</b>       | 0      | 0      | 0      | 0      | ... | 0     |
| <b>Out (DSP)</b>      | -1     | 0      | 0      | 0      | ... | -2    |
| <b>Exp. Out (DSP)</b> | 0      | 0      | 0      | 0      | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 56 |
| Avg CPU cycles  | 56 |

**Verification: uAdd FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block uAdd.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 46     | 46     | 46     | 46     | ... | 46    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>In1 (DSP)</b>      | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>In2 (DSP)</b>      | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>In1</b>            | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>In2</b>            | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | -0     | 0      | 0      | 0      | ... | -0    |
| <b>Exp. Out</b>       | 0      | 0      | 0      | 0      | ... | 0     |
| <b>Out (DSP)</b>      | -1     | 0      | 0      | 0      | ... | -2    |
| <b>Exp. Out (DSP)</b> | 0      | 0      | 0      | 0      | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 46 |
| Max CPU cycles  | 46 |
| Avg CPU cycles  | 46 |

**Verification: uAdd FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block uAdd.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 51          | 51          | ... | 51         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -0          | 0           | ... | -0         |
| <b>Exp. Out</b>       | 0           | 0           | ... | 0          |
| <b>Out (DSP)</b>      | -1          | 0           | ... | -2         |
| <b>Exp. Out (DSP)</b> | 0           | 0           | ... | 0          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 51 |
| Max CPU cycles  | 51 |
| Avg CPU cycles  | 51 |

**Verification: uAdd FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block uAdd.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 27          | 27          | ... | 27         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -0          | 0           | ... | -0         |
| <b>Exp. Out</b>       | 0           | 0           | ... | 0          |
| <b>Out (DSP)</b>      | -1          | 0           | ... | -2         |
| <b>Exp. Out (DSP)</b> | 0           | 0           | ... | 0          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 27 |
| Max CPU cycles  | 27 |
| Avg CPU cycles  | 27 |

**Verification: uAdd FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block uAdd.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 57          | 57          | ... | 57         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -0          | 0           | ... | -0         |
| <b>Exp. Out</b>       | 0           | 0           | ... | 0          |
| <b>Out (DSP)</b>      | -1          | 0           | ... | -2         |
| <b>Exp. Out (DSP)</b> | 0           | 0           | ... | 0          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 57 |

**Verification: uAdd FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block uAdd.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 51          | 51          | ... | 51         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -0          | 0           | ... | -0         |
| <b>Exp. Out</b>       | 0           | 0           | ... | 0          |
| <b>Out (DSP)</b>      | -1          | 0           | ... | -2         |
| <b>Exp. Out (DSP)</b> | 0           | 0           | ... | 0          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 51  |
| Max CPU cycles  | 110 |
| Avg CPU cycles  | 51  |

**Verification: uAdd FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block uAdd.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 32          | 32          | ... | 32         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -0          | 0           | ... | -0         |
| <b>Exp. Out</b>       | 0           | 0           | ... | 0          |
| <b>Out (DSP)</b>      | -1          | 0           | ... | -2         |
| <b>Exp. Out (DSP)</b> | 0           | 0           | ... | 0          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 32 |
| Max CPU cycles  | 32 |
| Avg CPU cycles  | 32 |



**Verification: uAdd FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block uAdd.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 42          | 42          | ... | 42         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -0          | 0           | ... | -0         |
| <b>Exp. Out</b>       | 0           | 0           | ... | 0          |
| <b>Out (DSP)</b>      | -1          | 0           | ... | -2         |
| <b>Exp. Out (DSP)</b> | 0           | 0           | ... | 0          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 42 |
| Max CPU cycles  | 42 |
| Avg CPU cycles  | 42 |

**Verification: uAdd FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block uAdd.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 56          | 56          | ... | 56         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -0          | 0           | ... | -0         |
| <b>Exp. Out</b>       | 0           | 0           | ... | 0          |
| <b>Out (DSP)</b>      | -1          | 0           | ... | -2         |
| <b>Exp. Out (DSP)</b> | 0           | 0           | ... | 0          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 56 |
| Avg CPU cycles  | 56 |

**Verification: uAdd FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block uAdd.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 44          | 44          | ... | 44         |
| <i>Inputs</i>         |             |             |     |            |
| <b>In1 (DSP)</b>      | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>In2 (DSP)</b>      | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>In1</b>            | -1          | -0.981      | ... | 1          |
| <b>In2</b>            | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | -0          | 0           | ... | -0         |
| <b>Exp. Out</b>       | 0           | 0           | ... | 0          |
| <b>Out (DSP)</b>      | -1          | 0           | ... | -2         |
| <b>Exp. Out (DSP)</b> | 0           | 0           | ... | 0          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 44 |
| Max CPU cycles  | 44 |
| Avg CPU cycles  | 44 |

**Verification: uAdd Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block uAdd.

| Test results          |    |        |     |        |
|-----------------------|----|--------|-----|--------|
| <b>Time step</b>      | 1  | 2      | ... | 214    |
| <b>CPU cycles</b>     | 79 | 79     | ... | 176    |
| <i>Inputs</i>         |    |        |     |        |
| <b>In1 (DSP)</b>      | -2 | -1.962 | ... | 2      |
| <b>In2 (DSP)</b>      | 2  | 1.962  | ... | 2      |
| <b>In1</b>            | -2 | -1.962 | ... | 2      |
| <b>In2</b>            | 2  | 1.962  | ... | 2      |
| <i>Outputs</i>        |    |        |     |        |
| <b>Out</b>            | 0  | 0      | ... | -2.283 |
| <b>Exp. Out</b>       | 0  | 0      | ... | -2.283 |
| <b>Out (DSP)</b>      | 0  | 0      | ... | -2.283 |
| <b>Exp. Out (DSP)</b> | 0  | 0      | ... | -2.283 |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance Out | $\pm 5,5879\text{e-}07$ ( $\pm 1200$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 79  |
| Max CPU cycles  | 182 |
| Avg CPU cycles  | 90  |

**Verification: uAdd Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block uAdd.

| Test results          |    |        |     |        |
|-----------------------|----|--------|-----|--------|
| <b>Time step</b>      | 1  | 2      | ... | 214    |
| <b>CPU cycles</b>     | 67 | 67     | ... | 107    |
| <i>Inputs</i>         |    |        |     |        |
| <b>In1 (DSP)</b>      | -2 | -1.962 | ... | 2      |
| <b>In2 (DSP)</b>      | 2  | 1.962  | ... | 2      |
| <b>In1</b>            | -2 | -1.962 | ... | 2      |
| <b>In2</b>            | 2  | 1.962  | ... | 2      |
| <i>Outputs</i>        |    |        |     |        |
| <b>Out</b>            | 0  | 0      | ... | -2.283 |
| <b>Exp. Out</b>       | 0  | 0      | ... | -2.283 |
| <b>Out (DSP)</b>      | 0  | 0      | ... | -2.283 |
| <b>Exp. Out (DSP)</b> | 0  | 0      | ... | -2.283 |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance Out | $\pm 5,5879\text{e-}07$ ( $\pm 1200$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 67  |
| Max CPU cycles  | 123 |
| Avg CPU cycles  | 72  |

**Verification: uAdd Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block uAdd.

| Test results          |     |        |     |        |
|-----------------------|-----|--------|-----|--------|
| <b>Time step</b>      | 1   | 2      | ... | 214    |
| <b>CPU cycles</b>     | 104 | 104    | ... | 240    |
| <i>Inputs</i>         |     |        |     |        |
| <b>In1 (DSP)</b>      | -2  | -1.962 | ... | 2      |
| <b>In2 (DSP)</b>      | 2   | 1.962  | ... | 2      |
| <b>In1</b>            | -2  | -1.962 | ... | 2      |
| <b>In2</b>            | 2   | 1.962  | ... | 2      |
| <i>Outputs</i>        |     |        |     |        |
| <b>Out</b>            | 0   | 0      | ... | -2.283 |
| <b>Exp. Out</b>       | 0   | 0      | ... | -2.283 |
| <b>Out (DSP)</b>      | 0   | 0      | ... | -2.283 |
| <b>Exp. Out (DSP)</b> | 0   | 0      | ... | -2.283 |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance Out | $\pm 5,5879\text{e-}07$ ( $\pm 1200$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 104 |
| Max CPU cycles  | 240 |
| Avg CPU cycles  | 119 |

**Verification: uAdd Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block uAdd.

| Test results          |     |        |     |        |
|-----------------------|-----|--------|-----|--------|
| <b>Time step</b>      | 1   | 2      | ... | 214    |
| <b>CPU cycles</b>     | 299 | 299    | ... | 673    |
| <i>Inputs</i>         |     |        |     |        |
| <b>In1 (DSP)</b>      | -2  | -1.962 | ... | 2      |
| <b>In2 (DSP)</b>      | 2   | 1.962  | ... | 2      |
| <b>In1</b>            | -2  | -1.962 | ... | 2      |
| <b>In2</b>            | 2   | 1.962  | ... | 2      |
| <i>Outputs</i>        |     |        |     |        |
| <b>Out</b>            | 0   | 0      | ... | -2.283 |
| <b>Exp. Out</b>       | 0   | 0      | ... | -2.283 |
| <b>Out (DSP)</b>      | 0   | 0      | ... | -2.283 |
| <b>Exp. Out (DSP)</b> | 0   | 0      | ... | -2.283 |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance Out | $\pm 5,5879\text{e-}07$ ( $\pm 1200$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 299 |
| Max CPU cycles  | 764 |
| Avg CPU cycles  | 355 |

**Verification: uAdd Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block uAdd.

| Test results          |     |        |     |        |
|-----------------------|-----|--------|-----|--------|
| <b>Time step</b>      | 1   | 2      | ... | 214    |
| <b>CPU cycles</b>     | 176 | 176    | ... | 312    |
| <i>Inputs</i>         |     |        |     |        |
| <b>In1 (DSP)</b>      | -2  | -1.962 | ... | 2      |
| <b>In2 (DSP)</b>      | 2   | 1.962  | ... | 2      |
| <b>In1</b>            | -2  | -1.962 | ... | 2      |
| <b>In2</b>            | 2   | 1.962  | ... | 2      |
| <i>Outputs</i>        |     |        |     |        |
| <b>Out</b>            | 0   | 0      | ... | -2.283 |
| <b>Exp. Out</b>       | 0   | 0      | ... | -2.283 |
| <b>Out (DSP)</b>      | 0   | 0      | ... | -2.283 |
| <b>Exp. Out (DSP)</b> | 0   | 0      | ... | -2.283 |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance Out | $\pm 5,5879\text{e-}07$ ( $\pm 1200$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 162 |
| Max CPU cycles  | 346 |
| Avg CPU cycles  | 197 |



**Verification: uAdd Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block uAdd.

| Test results          |     |        |     |        |
|-----------------------|-----|--------|-----|--------|
| <b>Time step</b>      | 1   | 2      | ... | 214    |
| <b>CPU cycles</b>     | 452 | 452    | ... | 773    |
| <i>Inputs</i>         |     |        |     |        |
| <b>In1 (DSP)</b>      | -2  | -1.962 | ... | 2      |
| <b>In2 (DSP)</b>      | 2   | 1.962  | ... | 2      |
| <b>In1</b>            | -2  | -1.962 | ... | 2      |
| <b>In2</b>            | 2   | 1.962  | ... | 2      |
| <i>Outputs</i>        |     |        |     |        |
| <b>Out</b>            | 0   | 0      | ... | -2.283 |
| <b>Exp. Out</b>       | 0   | 0      | ... | -2.283 |
| <b>Out (DSP)</b>      | 0   | 0      | ... | -2.283 |
| <b>Exp. Out (DSP)</b> | 0   | 0      | ... | -2.283 |

| Test settings |                                           |
|---------------|-------------------------------------------|
| Tolerance Out | $\pm 5,5879\text{e-}07$ ( $\pm 1200$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 411 |
| Max CPU cycles  | 870 |
| Avg CPU cycles  | 472 |

**Verification: uAdd Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block uAdd.

| Test results          |     |        |     |        |
|-----------------------|-----|--------|-----|--------|
| <b>Time step</b>      | 1   | 2      | ... | 214    |
| <b>CPU cycles</b>     | 121 | 91     | ... | 266    |
| <i>Inputs</i>         |     |        |     |        |
| <b>In1 (DSP)</b>      | -2  | -1.962 | ... | 2      |
| <b>In2 (DSP)</b>      | 2   | 1.962  | ... | 2      |
| <b>In1</b>            | -2  | -1.962 | ... | 2      |
| <b>In2</b>            | 2   | 1.962  | ... | 2      |
| <i>Outputs</i>        |     |        |     |        |
| <b>Out</b>            | 0   | 0      | ... | -2.283 |
| <b>Exp. Out</b>       | 0   | 0      | ... | -2.283 |
| <b>Out (DSP)</b>      | 0   | 0      | ... | -2.283 |
| <b>Exp. Out (DSP)</b> | 0   | 0      | ... | -2.283 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 5,5879e-07$ ( $\pm 1200$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 91  |
| Max CPU cycles  | 298 |
| Avg CPU cycles  | 111 |

**Verification: uAdd Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block uAdd.

| Test results          |    |        |     |        |
|-----------------------|----|--------|-----|--------|
| <b>Time step</b>      | 1  | 2      | ... | 214    |
| <b>CPU cycles</b>     | 81 | 81     | ... | 153    |
| <i>Inputs</i>         |    |        |     |        |
| <b>In1 (DSP)</b>      | -2 | -1.962 | ... | 2      |
| <b>In2 (DSP)</b>      | 2  | 1.962  | ... | 2      |
| <b>In1</b>            | -2 | -1.962 | ... | 2      |
| <b>In2</b>            | 2  | 1.962  | ... | 2      |
| <i>Outputs</i>        |    |        |     |        |
| <b>Out</b>            | 0  | 0      | ... | -2.283 |
| <b>Exp. Out</b>       | 0  | 0      | ... | -2.283 |
| <b>Out (DSP)</b>      | 0  | 0      | ... | -2.283 |
| <b>Exp. Out (DSP)</b> | 0  | 0      | ... | -2.283 |

| Test settings |                                    |
|---------------|------------------------------------|
| Tolerance Out | $\pm 5,5879e-07$ ( $\pm 1200$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 81  |
| Max CPU cycles  | 164 |
| Avg CPU cycles  | 89  |

## Block: uSub

---



Subtraction of input Minus from input Plus with output wrapping.

| Inports |            |
|---------|------------|
| Plus    | Minuend    |
| Minus   | Subtrahend |

| Outports |            |
|----------|------------|
| Out      | Difference |

### Description:

Calculation:

$$\text{Out} = \text{Plus} - \text{Minus}$$

### Implementations:

|                |                                      |
|----------------|--------------------------------------|
| <b>FiP8</b>    | 8 Bit Fixed Point Implementation     |
| <b>FiP16</b>   | 16 Bit Fixed Point Implementation    |
| <b>FiP32</b>   | 32 Bit Fixed Point Implementation    |
| <b>Float32</b> | 32 Bit Floating Point Implementation |
| <b>Float64</b> | 64 Bit Floating Point Implementation |

### Implementation: FiP8

---

8 Bit Fixed Point Implementation

| Inports Data Type |      |
|-------------------|------|
| Plus              | int8 |
| Minus             | int8 |

| Outports Data Type |      |
|--------------------|------|
| Out                | int8 |

### Implementation: FiP16

---

16 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| Plus              | int16 |
| Minus             | int16 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int16 |

### Implementation: FiP32

32 Bit Fixed Point Implementation

| Inports Data Type |       |
|-------------------|-------|
| Plus              | int32 |
| Minus             | int32 |

| Outports Data Type |       |
|--------------------|-------|
| Out                | int32 |

### Implementation: Float32

32 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| Plus              | float32 |
| Minus             | float32 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float32 |

### Implementation: Float64

64 Bit Floating Point Implementation

| Inports Data Type |         |
|-------------------|---------|
| Plus              | float64 |
| Minus             | float64 |

| Outports Data Type |         |
|--------------------|---------|
| Out                | float64 |

**Verification: uSub FiP16 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block uSub.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 51     | 51     | 51     | 51     | ... | 51    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>Plus (DSP)</b>     | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>Minus (DSP)</b>    | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>Plus</b>           | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Minus</b>          | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 0      | 0.038  | 0.076  | 0.113  | ... | 0     |
| <b>Exp. Out</b>       | 0      | 0.038  | 0.075  | 0.113  | ... | 0     |
| <b>Out (DSP)</b>      | 1      | 1236   | 2474   | 3710   | ... | 0     |
| <b>Exp. Out (DSP)</b> | 0      | 1237   | 2473   | 3710   | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 51 |
| Max CPU cycles  | 51 |
| Avg CPU cycles  | 51 |

**Verification: uSub FiP16 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block uSub.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 25     | 25     | 25     | 25     | ... | 25    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>Plus (DSP)</b>     | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>Minus (DSP)</b>    | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>Plus</b>           | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Minus</b>          | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 0      | 0.038  | 0.076  | 0.113  | ... | 0     |
| <b>Exp. Out</b>       | 0      | 0.038  | 0.075  | 0.113  | ... | 0     |
| <b>Out (DSP)</b>      | 1      | 1236   | 2474   | 3710   | ... | 0     |
| <b>Exp. Out (DSP)</b> | 0      | 1237   | 2473   | 3710   | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 25 |
| Max CPU cycles  | 25 |
| Avg CPU cycles  | 25 |

**Verification: uSub FiP16 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block uSub.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 57     | 57     | 57     | 57     | ... | 57    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>Plus (DSP)</b>     | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>Minus (DSP)</b>    | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>Plus</b>           | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Minus</b>          | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 0      | 0.038  | 0.076  | 0.113  | ... | 0     |
| <b>Exp. Out</b>       | 0      | 0.038  | 0.075  | 0.113  | ... | 0     |
| <b>Out (DSP)</b>      | 1      | 1236   | 2474   | 3710   | ... | 0     |
| <b>Exp. Out (DSP)</b> | 0      | 1237   | 2473   | 3710   | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 57 |



**Verification: uSub FiP16 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block uSub.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 51     | 51     | 51     | 51     | ... | 51    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>Plus (DSP)</b>     | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>Minus (DSP)</b>    | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>Plus</b>           | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Minus</b>          | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 0      | 0.038  | 0.076  | 0.113  | ... | 0     |
| <b>Exp. Out</b>       | 0      | 0.038  | 0.075  | 0.113  | ... | 0     |
| <b>Out (DSP)</b>      | 1      | 1236   | 2474   | 3710   | ... | 0     |
| <b>Exp. Out (DSP)</b> | 0      | 1237   | 2473   | 3710   | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 51 |
| Max CPU cycles  | 51 |
| Avg CPU cycles  | 51 |

**Verification: uSub FiP16 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block uSub.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 32     | 32     | 32     | 32     | ... | 32    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>Plus (DSP)</b>     | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>Minus (DSP)</b>    | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>Plus</b>           | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Minus</b>          | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 0      | 0.038  | 0.076  | 0.113  | ... | 0     |
| <b>Exp. Out</b>       | 0      | 0.038  | 0.075  | 0.113  | ... | 0     |
| <b>Out (DSP)</b>      | 1      | 1236   | 2474   | 3710   | ... | 0     |
| <b>Exp. Out (DSP)</b> | 0      | 1237   | 2473   | 3710   | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 32 |
| Max CPU cycles  | 32 |
| Avg CPU cycles  | 32 |

**Verification: uSub FiP16 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block uSub.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 38     | 38     | 38     | 38     | ... | 38    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>Plus (DSP)</b>     | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>Minus (DSP)</b>    | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>Plus</b>           | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Minus</b>          | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 0      | 0.038  | 0.076  | 0.113  | ... | 0     |
| <b>Exp. Out</b>       | 0      | 0.038  | 0.075  | 0.113  | ... | 0     |
| <b>Out (DSP)</b>      | 1      | 1236   | 2474   | 3710   | ... | 0     |
| <b>Exp. Out (DSP)</b> | 0      | 1237   | 2473   | 3710   | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 38 |
| Max CPU cycles  | 38 |
| Avg CPU cycles  | 38 |

**Verification: uSub FiP16 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block uSub.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 67     | 56     | 56     | 56     | ... | 56    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>Plus (DSP)</b>     | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>Minus (DSP)</b>    | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>Plus</b>           | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Minus</b>          | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 0      | 0.038  | 0.076  | 0.113  | ... | 0     |
| <b>Exp. Out</b>       | 0      | 0.038  | 0.075  | 0.113  | ... | 0     |
| <b>Out (DSP)</b>      | 1      | 1236   | 2474   | 3710   | ... | 0     |
| <b>Exp. Out (DSP)</b> | 0      | 1237   | 2473   | 3710   | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 67 |
| Avg CPU cycles  | 56 |

**Verification: uSub FiP16 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block uSub.

| Test results          |        |        |        |        |     |       |
|-----------------------|--------|--------|--------|--------|-----|-------|
| <b>Time step</b>      | 1      | 2      | 3      | 4      | ... | 214   |
| <b>CPU cycles</b>     | 46     | 46     | 46     | 46     | ... | 46    |
| <i>Inputs</i>         |        |        |        |        |     |       |
| <b>Plus (DSP)</b>     | -32768 | -32150 | -31531 | -30913 | ... | 32767 |
| <b>Minus (DSP)</b>    | 32767  | 32150  | 31531  | 30913  | ... | 32767 |
| <b>Plus</b>           | -1     | -0.981 | -0.962 | -0.943 | ... | 1     |
| <b>Minus</b>          | 1      | 0.981  | 0.962  | 0.943  | ... | 1     |
| <i>Outputs</i>        |        |        |        |        |     |       |
| <b>Out</b>            | 0      | 0.038  | 0.076  | 0.113  | ... | 0     |
| <b>Exp. Out</b>       | 0      | 0.038  | 0.075  | 0.113  | ... | 0     |
| <b>Out (DSP)</b>      | 1      | 1236   | 2474   | 3710   | ... | 0     |
| <b>Exp. Out (DSP)</b> | 0      | 1237   | 2473   | 3710   | ... | 0     |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 6,1035e-05$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 46 |
| Max CPU cycles  | 46 |
| Avg CPU cycles  | 46 |

**Verification: uSub FiP32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block uSub.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 51          | 51          | ... | 51         |
| <i>Inputs</i>         |             |             |     |            |
| <b>Plus (DSP)</b>     | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>Minus (DSP)</b>    | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>Plus</b>           | -1          | -0.981      | ... | 1          |
| <b>Minus</b>          | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 0           | 0.038       | ... | 0          |
| <b>Exp. Out</b>       | 0           | 0.038       | ... | 0          |
| <b>Out (DSP)</b>      | 1           | 81037118    | ... | 0          |
| <b>Exp. Out (DSP)</b> | 0           | 81037119    | ... | 0          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 51 |
| Max CPU cycles  | 51 |
| Avg CPU cycles  | 51 |

**Verification: uSub FiP32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block uSub.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 27          | 27          | ... | 27         |
| <i>Inputs</i>         |             |             |     |            |
| <b>Plus (DSP)</b>     | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>Minus (DSP)</b>    | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>Plus</b>           | -1          | -0.981      | ... | 1          |
| <b>Minus</b>          | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 0           | 0.038       | ... | 0          |
| <b>Exp. Out</b>       | 0           | 0.038       | ... | 0          |
| <b>Out (DSP)</b>      | 1           | 81037118    | ... | 0          |
| <b>Exp. Out (DSP)</b> | 0           | 81037119    | ... | 0          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 27 |
| Max CPU cycles  | 27 |
| Avg CPU cycles  | 27 |

**Verification: uSub FiP32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block uSub.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 57          | 57          | ... | 57         |
| <i>Inputs</i>         |             |             |     |            |
| <b>Plus (DSP)</b>     | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>Minus (DSP)</b>    | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>Plus</b>           | -1          | -0.981      | ... | 1          |
| <b>Minus</b>          | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 0           | 0.038       | ... | 0          |
| <b>Exp. Out</b>       | 0           | 0.038       | ... | 0          |
| <b>Out (DSP)</b>      | 1           | 81037118    | ... | 0          |
| <b>Exp. Out (DSP)</b> | 0           | 81037119    | ... | 0          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 57 |
| Max CPU cycles  | 57 |
| Avg CPU cycles  | 57 |



**Verification: uSub FiP32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block uSub.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 51          | 51          | ... | 51         |
| <i>Inputs</i>         |             |             |     |            |
| <b>Plus (DSP)</b>     | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>Minus (DSP)</b>    | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>Plus</b>           | -1          | -0.981      | ... | 1          |
| <b>Minus</b>          | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 0           | 0.038       | ... | 0          |
| <b>Exp. Out</b>       | 0           | 0.038       | ... | 0          |
| <b>Out (DSP)</b>      | 1           | 81037118    | ... | 0          |
| <b>Exp. Out (DSP)</b> | 0           | 81037119    | ... | 0          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 51 |
| Max CPU cycles  | 51 |
| Avg CPU cycles  | 51 |

**Verification: uSub FiP32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block uSub.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 32          | 32          | ... | 32         |
| <i>Inputs</i>         |             |             |     |            |
| <b>Plus (DSP)</b>     | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>Minus (DSP)</b>    | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>Plus</b>           | -1          | -0.981      | ... | 1          |
| <b>Minus</b>          | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 0           | 0.038       | ... | 0          |
| <b>Exp. Out</b>       | 0           | 0.038       | ... | 0          |
| <b>Out (DSP)</b>      | 1           | 81037118    | ... | 0          |
| <b>Exp. Out (DSP)</b> | 0           | 81037119    | ... | 0          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 32 |
| Max CPU cycles  | 32 |
| Avg CPU cycles  | 32 |

**Verification: uSub FiP32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block uSub.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 41          | 41          | ... | 41         |
| <i>Inputs</i>         |             |             |     |            |
| <b>Plus (DSP)</b>     | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>Minus (DSP)</b>    | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>Plus</b>           | -1          | -0.981      | ... | 1          |
| <b>Minus</b>          | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 0           | 0.038       | ... | 0          |
| <b>Exp. Out</b>       | 0           | 0.038       | ... | 0          |
| <b>Out (DSP)</b>      | 1           | 81037118    | ... | 0          |
| <b>Exp. Out (DSP)</b> | 0           | 81037119    | ... | 0          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 41 |
| Max CPU cycles  | 41 |
| Avg CPU cycles  | 41 |

**Verification: uSub FiP32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block uSub.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 56          | 56          | ... | 56         |
| <i>Inputs</i>         |             |             |     |            |
| <b>Plus (DSP)</b>     | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>Minus (DSP)</b>    | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>Plus</b>           | -1          | -0.981      | ... | 1          |
| <b>Minus</b>          | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 0           | 0.038       | ... | 0          |
| <b>Exp. Out</b>       | 0           | 0.038       | ... | 0          |
| <b>Out (DSP)</b>      | 1           | 81037118    | ... | 0          |
| <b>Exp. Out (DSP)</b> | 0           | 81037119    | ... | 0          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 56 |
| Max CPU cycles  | 56 |
| Avg CPU cycles  | 56 |

**Verification: uSub FiP32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block uSub.

| Test results          |             |             |     |            |
|-----------------------|-------------|-------------|-----|------------|
| <b>Time step</b>      | 1           | 2           | ... | 214        |
| <b>CPU cycles</b>     | 44          | 44          | ... | 44         |
| <i>Inputs</i>         |             |             |     |            |
| <b>Plus (DSP)</b>     | -2147483648 | -2106965089 | ... | 2147483647 |
| <b>Minus (DSP)</b>    | 2147483647  | 2106965089  | ... | 2147483647 |
| <b>Plus</b>           | -1          | -0.981      | ... | 1          |
| <b>Minus</b>          | 1           | 0.981       | ... | 1          |
| <i>Outputs</i>        |             |             |     |            |
| <b>Out</b>            | 0           | 0.038       | ... | 0          |
| <b>Exp. Out</b>       | 0           | 0.038       | ... | 0          |
| <b>Out (DSP)</b>      | 1           | 81037118    | ... | 0          |
| <b>Exp. Out (DSP)</b> | 0           | 81037119    | ... | 0          |

| Test settings |                                 |
|---------------|---------------------------------|
| Tolerance Out | $\pm 9,3132e-10$ ( $\pm 2$ LSB) |

| Test statistics |    |
|-----------------|----|
| Min CPU cycles  | 44 |
| Max CPU cycles  | 44 |
| Avg CPU cycles  | 44 |

**Verification: uSub Float32 CPU TMS320F28335**

**Date of Test** 2026-06-19  
**Target controller** TMS320F28335

**Test case: Inport test****OK**

Inport test for Math block uSub.

| Test results          |       |        |     |     |
|-----------------------|-------|--------|-----|-----|
| <b>Time step</b>      | 1     | 2      | ... | 214 |
| <b>CPU cycles</b>     | 182   | 182    | ... | 79  |
| <i>Inputs</i>         |       |        |     |     |
| <b>Plus (DSP)</b>     | -2    | -1.962 | ... | 2   |
| <b>Minus (DSP)</b>    | 2     | 1.962  | ... | 2   |
| <b>Plus</b>           | -2    | -1.962 | ... | 2   |
| <b>Minus</b>          | 2     | 1.962  | ... | 2   |
| <i>Outputs</i>        |       |        |     |     |
| <b>Out</b>            | 2.283 | 2.359  | ... | 0   |
| <b>Exp. Out</b>       | 2.283 | 2.359  | ... | 0   |
| <b>Out (DSP)</b>      | 2.283 | 2.359  | ... | 0   |
| <b>Exp. Out (DSP)</b> | 2.283 | 2.359  | ... | 0   |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 2,7940\text{e-}07$ ( $\pm 600$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 79  |
| Max CPU cycles  | 182 |
| Avg CPU cycles  | 90  |

**Verification: uSub Float32 CPU TM4C123GH6**

**Date of Test** 2026-06-19  
**Target controller** TM4C123GH6

**Test case: Inport test****OK**

Inport test for Math block uSub.

| Test results          |       |        |     |     |
|-----------------------|-------|--------|-----|-----|
| <b>Time step</b>      | 1     | 2      | ... | 214 |
| <b>CPU cycles</b>     | 123   | 123    | ... | 67  |
| <i>Inputs</i>         |       |        |     |     |
| <b>Plus (DSP)</b>     | -2    | -1.962 | ... | 2   |
| <b>Minus (DSP)</b>    | 2     | 1.962  | ... | 2   |
| <b>Plus</b>           | -2    | -1.962 | ... | 2   |
| <b>Minus</b>          | 2     | 1.962  | ... | 2   |
| <i>Outputs</i>        |       |        |     |     |
| <b>Out</b>            | 2.283 | 2.359  | ... | 0   |
| <b>Exp. Out</b>       | 2.283 | 2.359  | ... | 0   |
| <b>Out (DSP)</b>      | 2.283 | 2.359  | ... | 0   |
| <b>Exp. Out (DSP)</b> | 2.283 | 2.359  | ... | 0   |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 2,7940e-07$ ( $\pm 600$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 67  |
| Max CPU cycles  | 123 |
| Avg CPU cycles  | 72  |

**Verification: uSub Float32 CPU STM32G474RE**

**Date of Test** 2026-06-19  
**Target controller** STM32G474RE

**Test case: Inport test****OK**

Inport test for Math block uSub.

| Test results          |       |        |     |     |
|-----------------------|-------|--------|-----|-----|
| <b>Time step</b>      | 1     | 2      | ... | 214 |
| <b>CPU cycles</b>     | 237   | 237    | ... | 104 |
| <i>Inputs</i>         |       |        |     |     |
| <b>Plus (DSP)</b>     | -2    | -1.962 | ... | 2   |
| <b>Minus (DSP)</b>    | 2     | 1.962  | ... | 2   |
| <b>Plus</b>           | -2    | -1.962 | ... | 2   |
| <b>Minus</b>          | 2     | 1.962  | ... | 2   |
| <i>Outputs</i>        |       |        |     |     |
| <b>Out</b>            | 2.283 | 2.359  | ... | 0   |
| <b>Exp. Out</b>       | 2.283 | 2.359  | ... | 0   |
| <b>Out (DSP)</b>      | 2.283 | 2.359  | ... | 0   |
| <b>Exp. Out (DSP)</b> | 2.283 | 2.359  | ... | 0   |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 2,7940\text{e-}07$ ( $\pm 600$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 104 |
| Max CPU cycles  | 240 |
| Avg CPU cycles  | 119 |



**Verification: uSub Float32 CPU STM32F072RB**

**Date of Test** 2026-06-19  
**Target controller** STM32F072RB

**Test case: Inport test****OK**

Inport test for Math block uSub.

| Test results          |       |        |     |     |
|-----------------------|-------|--------|-----|-----|
| <b>Time step</b>      | 1     | 2      | ... | 214 |
| <b>CPU cycles</b>     | 751   | 775    | ... | 307 |
| <i>Inputs</i>         |       |        |     |     |
| <b>Plus (DSP)</b>     | -2    | -1.962 | ... | 2   |
| <b>Minus (DSP)</b>    | 2     | 1.962  | ... | 2   |
| <b>Plus</b>           | -2    | -1.962 | ... | 2   |
| <b>Minus</b>          | 2     | 1.962  | ... | 2   |
| <i>Outputs</i>        |       |        |     |     |
| <b>Out</b>            | 2.283 | 2.359  | ... | 0   |
| <b>Exp. Out</b>       | 2.283 | 2.359  | ... | 0   |
| <b>Out (DSP)</b>      | 2.283 | 2.359  | ... | 0   |
| <b>Exp. Out (DSP)</b> | 2.283 | 2.359  | ... | 0   |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 2,7940\text{e-}07$ ( $\pm 600$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 307 |
| Max CPU cycles  | 775 |
| Avg CPU cycles  | 365 |

**Verification: uSub Float32 CPU PIC32MX170F256**

**Date of Test** 2026-06-19  
**Target controller** PIC32MX170F256

**Test case: Inport test****OK**

Inport test for Math block uSub.

| Test results          |       |        |     |     |
|-----------------------|-------|--------|-----|-----|
| <b>Time step</b>      | 1     | 2      | ... | 214 |
| <b>CPU cycles</b>     | 348   | 328    | ... | 178 |
| <i>Inputs</i>         |       |        |     |     |
| <b>Plus (DSP)</b>     | -2    | -1.962 | ... | 2   |
| <b>Minus (DSP)</b>    | 2     | 1.962  | ... | 2   |
| <b>Plus</b>           | -2    | -1.962 | ... | 2   |
| <b>Minus</b>          | 2     | 1.962  | ... | 2   |
| <i>Outputs</i>        |       |        |     |     |
| <b>Out</b>            | 2.283 | 2.359  | ... | 0   |
| <b>Exp. Out</b>       | 2.283 | 2.359  | ... | 0   |
| <b>Out (DSP)</b>      | 2.283 | 2.359  | ... | 0   |
| <b>Exp. Out (DSP)</b> | 2.283 | 2.359  | ... | 0   |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 2,7940e-07$ ( $\pm 600$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 170 |
| Max CPU cycles  | 348 |
| Avg CPU cycles  | 199 |

**Verification: uSub Float32 CPU dsPIC33EP256MC502**

**Date of Test** 2026-06-19  
**Target controller** dsPIC33EP256MC502

**Test case: Inport test****OK**

Inport test for Math block uSub.

| Test results          |       |        |     |     |
|-----------------------|-------|--------|-----|-----|
| <b>Time step</b>      | 1     | 2      | ... | 214 |
| <b>CPU cycles</b>     | 871   | 818    | ... | 453 |
| <i>Inputs</i>         |       |        |     |     |
| <b>Plus (DSP)</b>     | -2    | -1.962 | ... | 2   |
| <b>Minus (DSP)</b>    | 2     | 1.962  | ... | 2   |
| <b>Plus</b>           | -2    | -1.962 | ... | 2   |
| <b>Minus</b>          | 2     | 1.962  | ... | 2   |
| <i>Outputs</i>        |       |        |     |     |
| <b>Out</b>            | 2.283 | 2.359  | ... | 0   |
| <b>Exp. Out</b>       | 2.283 | 2.359  | ... | 0   |
| <b>Out (DSP)</b>      | 2.283 | 2.359  | ... | 0   |
| <b>Exp. Out (DSP)</b> | 2.283 | 2.359  | ... | 0   |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 2,7940e-07$ ( $\pm 600$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 412 |
| Max CPU cycles  | 871 |
| Avg CPU cycles  | 473 |

**Verification: uSub Float32 CPU XMC4800-F144K2048**

**Date of Test** 2026-06-19  
**Target controller** XMC4800-F144K2048

**Test case: Inport test****OK**

Inport test for Math block uSub.

| Test results          |       |        |     |     |
|-----------------------|-------|--------|-----|-----|
| <b>Time step</b>      | 1     | 2      | ... | 214 |
| <b>CPU cycles</b>     | 315   | 268    | ... | 91  |
| <i>Inputs</i>         |       |        |     |     |
| <b>Plus (DSP)</b>     | -2    | -1.962 | ... | 2   |
| <b>Minus (DSP)</b>    | 2     | 1.962  | ... | 2   |
| <b>Plus</b>           | -2    | -1.962 | ... | 2   |
| <b>Minus</b>          | 2     | 1.962  | ... | 2   |
| <i>Outputs</i>        |       |        |     |     |
| <b>Out</b>            | 2.283 | 2.359  | ... | 0   |
| <b>Exp. Out</b>       | 2.283 | 2.359  | ... | 0   |
| <b>Out (DSP)</b>      | 2.283 | 2.359  | ... | 0   |
| <b>Exp. Out (DSP)</b> | 2.283 | 2.359  | ... | 0   |

| Test settings |                                   |
|---------------|-----------------------------------|
| Tolerance Out | $\pm 2,7940e-07$ ( $\pm 600$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 91  |
| Max CPU cycles  | 315 |
| Avg CPU cycles  | 111 |

**Verification: uSub Float32 CPU TMS320F28379D**

**Date of Test** 2026-06-22  
**Target controller** TMS320F28379D

**Test case: Inport test****OK**

Inport test for Math block uSub.

| Test results          |       |        |     |     |
|-----------------------|-------|--------|-----|-----|
| <b>Time step</b>      | 1     | 2      | ... | 214 |
| <b>CPU cycles</b>     | 164   | 164    | ... | 81  |
| <i>Inputs</i>         |       |        |     |     |
| <b>Plus (DSP)</b>     | -2    | -1.962 | ... | 2   |
| <b>Minus (DSP)</b>    | 2     | 1.962  | ... | 2   |
| <b>Plus</b>           | -2    | -1.962 | ... | 2   |
| <b>Minus</b>          | 2     | 1.962  | ... | 2   |
| <i>Outputs</i>        |       |        |     |     |
| <b>Out</b>            | 2.283 | 2.359  | ... | 0   |
| <b>Exp. Out</b>       | 2.283 | 2.359  | ... | 0   |
| <b>Out (DSP)</b>      | 2.283 | 2.359  | ... | 0   |
| <b>Exp. Out (DSP)</b> | 2.283 | 2.359  | ... | 0   |

| Test settings |                                          |
|---------------|------------------------------------------|
| Tolerance Out | $\pm 2,7940\text{e-}07$ ( $\pm 600$ LSB) |

| Test statistics |     |
|-----------------|-----|
| Min CPU cycles  | 81  |
| Max CPU cycles  | 164 |
| Avg CPU cycles  | 89  |