

X2C

*Project Documentation
DemoApplication*

August 30, 2017
© Linz Center of Mechatronics GmbH

Contents

I X2C Model	2
1 Version Information	2
1.1 X2C	2
1.2 Operating System	2
1.3 Scilab	2
2 Model Structure	3
2.1 Xcos Model	3
2.2 Subsystems	4
3 Model Parameter	5
3.1 Sample Time	5
3.2 Scilab Parameter	5
4 Mask Parameter	6
II Frame Program Documentation	8
5 File Index	8
5.1 File List	8
6 File Documentation	8
6.1 inc/Hardware.h File Reference	8
6.1.1 Detailed Description	8
6.1.2 Function Documentation	9
6.2 inc/Main.h File Reference	9
6.2.1 Detailed Description	9
6.2.2 Function Documentation	9
6.3 inc/X2cDataTypes.h File Reference	10
6.3.1 Detailed Description	10
6.3.2 Macro Definition Documentation	10
III Used X2C-Blocks	11
7 Project Specific Blocks	11
8 Internal Library Blocks	11
AutoSwitch	11
Constant	12
Delay	13
I	14
Negation	15
Sin3Gen	16
SinGen	18

Part I

X2C Model

1 Version Information

1.1 X2C

- X2Cfull: Version 1228

1.2 Operating System

- OS: Windows 7 6.1

1.3 Scilab

- Scilab: Version 5.5.2.1427793548
- Java: Version 1.6.0_41

2 Model Structure

2.1 Xcos Model




Figure 1: DemoApplication

2.2 Subsystems




Figure 2: DemoApplication_Oscillator

3 Model Parameter

3.1 Sample Time

Sample Time	
T_S	$100\mu s$

3.2 Scilab Parameter

```
1 // File with model parameters such as sample time, scaling factors, etc...
2 //
3 // Copyright (c) 2016, Linz Center of Mechatronics GmbH (LCM) http://www.lcm.at/
4 // All rights reserved.
5 //
6 // $LastChangedRevision: 1013 $
7 // $LastChangedDate::: 2016-09-01 10:52:56 +0200#$
8 //
9 // This file is part of X2C. http://www.mechatronic-simulation.org/
10
11 // Sampling time
12 X2C_sampleTime = 1/10000;      // 10kHz sampling frequency
13
14 // Scaling factors
15
16 // Controller parameters
```

Listing 1: ModelParameter.sce

4 Mask Parameter

Constant: Amplitude	
Value	0.5
Used Implementation	FiP16

AutoSwitch: AutoSwitch	
Thresh_up	0.6
Thresh_down	0.4
Used Implementation	FiP16

AutoSwitch: AutoSwitch1	
Thresh_up	0.0
Thresh_down	0.0
Used Implementation	FiP16

Constant: Frequency	
Value	0.0080
Used Implementation	FiP16

Constant: LED off	
Value	0.0
Used Implementation	FiP16

Constant: LED on	
Value	1.0
Used Implementation	FiP16

AutoSwitch: Oscillator__AutoSwitch	
Thresh_up	0.5
Thresh_down	-0.5
Used Implementation	FiP16

Constant: Oscillator__C_1	
Value	1.0
Used Implementation	FiP16

Constant: Oscillator__C_enable	
Value	1.0
Used Implementation	Bool

Constant: Oscillator_C_init	
Value	0.0
Used Implementation	FiP16

Delay: Oscillator_Delay	
ts_fact	1.0
Used Implementation	FiP16

I: Oscillator_I	
Ki	50.0
ts_fact	1.0
Used Implementation	FiP16

Negation: Oscillator_Negation	
Used Implementation	FiP16

Sin3Gen: Sin3Gen	
fmax	1000.0
Offset	0.0
ts_fact	1.0
Used Implementation	FiP16

SinGen: SinGen	
fmax	1000.0
Offset	0.0
Phase	0.0
ts_fact	1.0
Used Implementation	FiP16

Part II

Frame Program Documentation

5 File Index

5.1 File List

Here is a list of all documented files with brief descriptions:

inc/ Hardware.h	Hardware initialization	8
inc/ Main.h	Main function	9
inc/ X2cDataTypes.h	Data type definitions for use in X2C	10


6 File Documentation

6.1 inc/Hardware.h File Reference

Hardware initialization.

```
#include "em_device.h"
#include "em_chip.h"
#include "em_cmu.h"
#include "em_emu.h"
#include "em_usart.h"
#include "em_adc.h"
#include "em_prs.h"
```

Include dependency graph for Hardware.h:



Functions

- void [initHardware](#) (void)
Initialization of hardware.
- void [initSerial](#) (tSerial *serial)
Initialization of serial interface.

6.1.1 Detailed Description

Hardware initialization.

6.1.2 Function Documentation

6.1.2.1 void initHardware (void)

Initialization of hardware.

- Configuration of clock and DC-DC regulator
- Configuration of SysTick Timer
 - 100 us system tick as X2C sample time
 - Generation of cyclic interrupt with selected sample time
 - Interrupt calls X2C main task
- Configuration of IO ports
- Configuration of UART
 - Baudrate: 115200 bps
 - Data bits: 8
 - Parity: none
 - Stop bits: 1

6.1.2.2 void initSerial (tSerial * serialP)

Initialization of serial interface.

Parameters

<i>serialP</i>	Serial object
----------------	---------------

6.2 inc/Main.h File Reference

Main function.

Functions

- void **mainTask** (void)

Main control task.

6.2.1 Detailed Description

Main function.

X2C maintenance table, protocol & hardware initialization.

6.2.2 Function Documentation

6.2.2.1 void mainTask (void)

Main control task.

TODO: This task has to be called periodically. Calling rate = 100us


- assign inputs
- update X2C
- update outputs

6.3 inc/X2cDataTypes.h File Reference

Data type definitions for use in X2C.

```
#include <stdio.h>
#include <stdbool.h>
```

Include dependency graph for X2cDataTypes.h:



Macros

- #define **SCOPE_SIZE** 4900

6.3.1 Detailed Description

Data type definitions for use in X2C.

6.3.2 Macro Definition Documentation

6.3.2.1 #define SCOPE_SIZE 4900

Scope data buffer size in bytes


Part III

Used X2C-Blocks

7 Project Specific Blocks

8 Internal Library Blocks

Block: AutoSwitch



Imports	
In1	Input #1
Switch	Input #2: Threshold signal
In3	Input #3

Outports	
Out	Either value of input #1 or input #3 dependent on value of input #2

Mask Parameters	
Thresh_up	Threshold level for rising switch signal
Thresh_down	Threshold level for falling switch signal

Description:

Switch between In1 and In3 dependent on Switch signal:

Switch signal rising: Switch \geq Threshold up \rightarrow Out = In1

Switch signal falling: Switch $<$ Threshold down \rightarrow Out = In3

Implementations:

- FiP8** 8 Bit Fixed Point Implementation
- FiP16** 16 Bit Fixed Point Implementation
- FiP32** 32 Bit Fixed Point Implementation
- Float32** 32 Bit Floating Point Implementation
- Float64** 64 Bit Floating Point Implementation

Block: Constant



Outports	
Out	Constant output

Mask Parameters	
Value	Constant factor

Description:

Constant value.

Implementations:

Bool	Boolean Integration
FiP8	8 Bit Fixed Point Implementation
FiP16	16 Bit Fixed Point Implementation
FiP32	32 Bit Fixed Point Implementation
Float32	32 Bit Floating Point Implementation
Float64	64 Bit Floating Point Implementation

Block: Delay



Imports	
In	Input In(k)

Outports	
Out	Output Out(k)=In(k-1)

Mask Parameters	
ts_fact	Multiplication factor of base sampling time (in integer format)

Description:


Output delay by one sample time interval.

This block can be used to enable feedback loops in the model.

Implementations:

- FiP16** 16 Bit Fixed Point Implementation
- FiP32** 32 Bit Fixed Point Implementation
- Float32** 32 Bit Floating Point Implementation
- Float64** 64 Bit Floating Point Implementation

Block: I



Imports	
In	Control error input
Init	Value which is loaded at initialization function call
Enable	Enable == 0: Deactivation of block; Out set to 0 Enable 0->1: Preload of integral part Enable == 1: Activation of block

Outports	
Out	Control value

Mask Parameters	
Ki	Integral Factor
ts_fact	Multiplication factor of base sampling time (in integer format)

Description:

I controller:

$$G(s) = Ki/s = 1/(Ti^*s)$$

Each fixed point implementation uses the next higher integer datatype for the integrational value storage variable.

A rising flank at the *Enable* import will preload the integrational part with the value present on the *Init* import.

Transfer function (zero-order hold discretization method):

$$G(z) = K_I T_s \frac{1}{z - 1}$$

Implementations:

- FiP8** 8 Bit Fixed Point Implementation
- FiP16** 16 Bit Fixed Point Implementation
- FiP32** 32 Bit Fixed Point Implementation
- Float32** 32 Bit Floating Point Implementation
- Float64** 64 Bit Floating Point Implementation

Block: Negation



Imports	
In	Input

Outports	
Out	Negated input value

Description:

Negation of input signal.


Calculation:

$$Out = -In$$

Implementations:

- FiP8** 8 Bit Fixed Point Implementation
- FiP16** 16 Bit Fixed Point Implementation
- FiP32** 32 Bit Fixed Point Implementation
- Float32** 32 Bit Floating Point Implementation
- Float64** 64 Bit Floating Point Implementation

Block: Sin3Gen



Imports	
A	Amplitude
f	Frequency

Outports	
u	Sine wave output phase u
v	Sine wave output phase v
w	Sine wave output phase w

Mask Parameters	
fmax	Maximum Frequency in Hz
Offset	Offset
ts_fact	Multiplication factor of base sampling time (in integer format)

Description:

Generation of a 3 sine waves with amplitude (A) and frequency (f).

Calculation fixed point implementation:

$$\begin{aligned} u_k &= A_k \cdot \sin(2f_k \cdot f_{max} \cdot kT_S) + A_{Offset} \\ v_k &= A_k \cdot \sin(2f_k \cdot f_{max} \cdot kT_S - \frac{2\pi}{3}) + A_{Offset} \\ w_k &= A_k \cdot \sin(2f_k \cdot f_{max} \cdot kT_S + \frac{2\pi}{3}) + A_{Offset} \end{aligned}$$

For sine calculation a lookup table with 256 entries is used. This results in a short computation time but with the downside of reduced accuracy for the FiP32 implementation.


Calculation floating point implementation (parameter *f_max* is ignored):

$$\begin{aligned} u_k &= A_k \cdot \sin(2\pi f_k \cdot kT_S) + A_{Offset} \\ v_k &= A_k \cdot \sin(2\pi f_k \cdot kT_S - \frac{2\pi}{3}) + A_{Offset} \\ w_k &= A_k \cdot \sin(2\pi f_k \cdot kT_S + \frac{2\pi}{3}) + A_{Offset} \end{aligned}$$

Implementations:

- FiP16** 16 Bit Fixed Point Implementation
- FiP32** 32 Bit Fixed Point Implementation
- Float32** 32 Bit Floating Point Implementation
- Float64** 64 Bit Floating Point Implementation

Block: SinGen



Inputs	
A	Amplitude
f	Frequency

Outports	
u	Sine wave output

Mask Parameters	
fmax	Maximum Frequency in Hz
Offset	Offset
Phase	Phase [-Pi..Pi]
ts_fact	Multiplication factor of base sampling time (in integer format)

Description:

Generation of a sine wave with amplitude (A) and frequency (f).

Calculation fixed point implementation:

$$u_k = A_k \cdot \sin(2f_k \cdot f_{max} \cdot kT_S + \phi_{Phase}) + A_{Offset}$$

For sine calculation a lookup table with 256 entries is used. This results in a short computation time but with the downside of reduced accuracy for the FiP32 implementation.

Calculation floating point implementation (parameter *f_max* is ignored):

$$u_k = A_k \cdot \sin(2\pi f_k \cdot kT_S + \phi_{Phase}) + A_{Offset}$$

Implementations:

- FiP16** 16 Bit Fixed Point Implementation
- FiP32** 32 Bit Fixed Point Implementation
- Float32** 32 Bit Floating Point Implementation
- Float64** 64 Bit Floating Point Implementation